

---

# **Python Frequently Asked Questions**

***Release 3.10.10***

**Guido van Rossum  
and the Python development team**

**April 05, 2023**

**Python Software Foundation  
Email: [docs@python.org](mailto:docs@python.org)**



# CONTENTS

<b>1</b>	<b>General Python FAQ</b>	<b>1</b>
1.1	General Information	1
1.1.1	What is Python?	1
1.1.2	What is the Python Software Foundation?	1
1.1.3	Are there copyright restrictions on the use of Python?	1
1.1.4	Why was Python created in the first place?	2
1.1.5	What is Python good for?	2
1.1.6	How does the Python version numbering scheme work?	2
1.1.7	How do I obtain a copy of the Python source?	3
1.1.8	How do I get documentation on Python?	3
1.1.9	I've never programmed before. Is there a Python tutorial?	3
1.1.10	Is there a newsgroup or mailing list devoted to Python?	3
1.1.11	How do I get a beta test version of Python?	4
1.1.12	How do I submit bug reports and patches for Python?	4
1.1.13	Are there any published articles about Python that I can reference?	4
1.1.14	Are there any books on Python?	4
1.1.15	Where in the world is <a href="http://www.python.org">www.python.org</a> located?	4
1.1.16	Why is it called Python?	4
1.1.17	Do I have to like "Monty Python's Flying Circus"?	5
1.2	Python in the real world	5
1.2.1	How stable is Python?	5
1.2.2	How many people are using Python?	5
1.2.3	Have any significant projects been done in Python?	5
1.2.4	What new developments are expected for Python in the future?	5
1.2.5	Is it reasonable to propose incompatible changes to Python?	6
1.2.6	Is Python a good language for beginning programmers?	6
<b>2</b>	<b>Programming FAQ</b>	<b>9</b>
2.1	General Questions	9
2.1.1	Is there a source code level debugger with breakpoints, single-stepping, etc.?	9
2.1.2	Are there tools to help find bugs or perform static analysis?	9
2.1.3	How can I create a stand-alone binary from a Python script?	10
2.1.4	Are there coding standards or a style guide for Python programs?	10
2.2	Core Language	10
2.2.1	Why am I getting an <code>UnboundLocalError</code> when the variable has a value?	10
2.2.2	What are the rules for local and global variables in Python?	11
2.2.3	Why do lambdas defined in a loop with different values all return the same result?	12
2.2.4	How do I share global variables across modules?	12
2.2.5	What are the "best practices" for using <code>import</code> in a module?	13
2.2.6	Why are default values shared between objects?	13
2.2.7	How can I pass optional or keyword parameters from one function to another?	14
2.2.8	What is the difference between arguments and parameters?	15
2.2.9	Why did changing list 'y' also change list 'x'?	15
2.2.10	How do I write a function with output parameters (call by reference)?	16

2.2.11	How do you make a higher order function in Python? . . . . .	17
2.2.12	How do I copy an object in Python? . . . . .	18
2.2.13	How can I find the methods or attributes of an object? . . . . .	18
2.2.14	How can my code discover the name of an object? . . . . .	18
2.2.15	What's up with the comma operator's precedence? . . . . .	19
2.2.16	Is there an equivalent of C's "?:" ternary operator? . . . . .	19
2.2.17	Is it possible to write obfuscated one-liners in Python? . . . . .	19
2.2.18	What does the slash(/) in the parameter list of a function mean? . . . . .	20
2.3	Numbers and strings . . . . .	20
2.3.1	How do I specify hexadecimal and octal integers? . . . . .	20
2.3.2	Why does -22 // 10 return -3? . . . . .	21
2.3.3	How do I get int literal attribute instead of SyntaxError? . . . . .	21
2.3.4	How do I convert a string to a number? . . . . .	21
2.3.5	How do I convert a number to a string? . . . . .	22
2.3.6	How do I modify a string in place? . . . . .	22
2.3.7	How do I use strings to call functions/methods? . . . . .	22
2.3.8	Is there an equivalent to Perl's chomp() for removing trailing newlines from strings? . . . . .	23
2.3.9	Is there a scanf() or sscanf() equivalent? . . . . .	23
2.3.10	What does 'UnicodeDecodeError' or 'UnicodeEncodeError' error mean? . . . . .	24
2.3.11	Can I end a raw string with an odd number of backslashes? . . . . .	24
2.4	Performance . . . . .	24
2.4.1	My program is too slow. How do I speed it up? . . . . .	24
2.4.2	What is the most efficient way to concatenate many strings together? . . . . .	25
2.5	Sequences (Tuples/Lists) . . . . .	25
2.5.1	How do I convert between tuples and lists? . . . . .	25
2.5.2	What's a negative index? . . . . .	26
2.5.3	How do I iterate over a sequence in reverse order? . . . . .	26
2.5.4	How do you remove duplicates from a list? . . . . .	26
2.5.5	How do you remove multiple items from a list . . . . .	26
2.5.6	How do you make an array in Python? . . . . .	27
2.5.7	How do I create a multidimensional list? . . . . .	27
2.5.8	How do I apply a method to a sequence of objects? . . . . .	28
2.5.9	Why does a_tuple[i] += ['item'] raise an exception when the addition works? . . . . .	28
2.5.10	I want to do a complicated sort: can you do a Schwartzian Transform in Python? . . . . .	29
2.5.11	How can I sort one list by values from another list? . . . . .	29
2.6	Objects . . . . .	29
2.6.1	What is a class? . . . . .	29
2.6.2	What is a method? . . . . .	30
2.6.3	What is self? . . . . .	30
2.6.4	How do I check if an object is an instance of a given class or of a subclass of it? . . . . .	30
2.6.5	What is delegation? . . . . .	31
2.6.6	How do I call a method defined in a base class from a derived class that extends it? . . . . .	32
2.6.7	How can I organize my code to make it easier to change the base class? . . . . .	32
2.6.8	How do I create static class data and static class methods? . . . . .	32
2.6.9	How can I overload constructors (or methods) in Python? . . . . .	33
2.6.10	I try to use __spam and I get an error about _SomeClassName__spam. . . . .	33
2.6.11	My class defines __del__ but it is not called when I delete the object. . . . .	33
2.6.12	How do I get a list of all instances of a given class? . . . . .	34
2.6.13	Why does the result of id() appear to be not unique? . . . . .	34
2.6.14	When can I rely on identity tests with the is operator? . . . . .	34
2.6.15	How can a subclass control what data is stored in an immutable instance? . . . . .	35
2.6.16	How do I cache method calls? . . . . .	36
2.7	Modules . . . . .	37
2.7.1	How do I create a .pyc file? . . . . .	37
2.7.2	How do I find the current module name? . . . . .	38
2.7.3	How can I have modules that mutually import each other? . . . . .	38
2.7.4	__import__('x.y.z') returns <module 'x'>; how do I get z? . . . . .	39

2.7.5	When I edit an imported module and reimport it, the changes don't show up. Why does this happen? . . . . .	39
<b>3</b>	<b>Design and History FAQ . . . . .</b>	<b>41</b>
3.1	Why does Python use indentation for grouping of statements? . . . . .	41
3.2	Why am I getting strange results with simple arithmetic operations? . . . . .	41
3.3	Why are floating-point calculations so inaccurate? . . . . .	41
3.4	Why are Python strings immutable? . . . . .	42
3.5	Why must 'self' be used explicitly in method definitions and calls? . . . . .	42
3.6	Why can't I use an assignment in an expression? . . . . .	43
3.7	Why does Python use methods for some functionality (e.g. list.index()) but functions for other (e.g. len(list))? . . . . .	43
3.8	Why is join() a string method instead of a list or tuple method? . . . . .	43
3.9	How fast are exceptions? . . . . .	44
3.10	Why isn't there a switch or case statement in Python? . . . . .	44
3.11	Can't you emulate threads in the interpreter instead of relying on an OS-specific thread implementation? . . . . .	45
3.12	Why can't lambda expressions contain statements? . . . . .	45
3.13	Can Python be compiled to machine code, C or some other language? . . . . .	45
3.14	How does Python manage memory? . . . . .	45
3.15	Why doesn't CPython use a more traditional garbage collection scheme? . . . . .	46
3.16	Why isn't all memory freed when CPython exits? . . . . .	46
3.17	Why are there separate tuple and list data types? . . . . .	46
3.18	How are lists implemented in CPython? . . . . .	47
3.19	How are dictionaries implemented in CPython? . . . . .	47
3.20	Why must dictionary keys be immutable? . . . . .	47
3.21	Why doesn't list.sort() return the sorted list? . . . . .	48
3.22	How do you specify and enforce an interface spec in Python? . . . . .	48
3.23	Why is there no goto? . . . . .	49
3.24	Why can't raw strings (r-strings) end with a backslash? . . . . .	49
3.25	Why doesn't Python have a "with" statement for attribute assignments? . . . . .	50
3.26	Why don't generators support the with statement? . . . . .	51
3.27	Why are colons required for the if/while/def/class statements? . . . . .	51
3.28	Why does Python allow commas at the end of lists and tuples? . . . . .	51
<b>4</b>	<b>Library and Extension FAQ . . . . .</b>	<b>53</b>
4.1	General Library Questions . . . . .	53
4.1.1	How do I find a module or application to perform task X? . . . . .	53
4.1.2	Where is the math.py (socket.py, regex.py, etc.) source file? . . . . .	53
4.1.3	How do I make a Python script executable on Unix? . . . . .	53
4.1.4	Is there a curses/termcap package for Python? . . . . .	54
4.1.5	Is there an equivalent to C's onexit() in Python? . . . . .	54
4.1.6	Why don't my signal handlers work? . . . . .	54
4.2	Common tasks . . . . .	54
4.2.1	How do I test a Python program or component? . . . . .	54
4.2.2	How do I create documentation from doc strings? . . . . .	55
4.2.3	How do I get a single keypress at a time? . . . . .	55
4.3	Threads . . . . .	55
4.3.1	How do I program using threads? . . . . .	55
4.3.2	None of my threads seem to run: why? . . . . .	55
4.3.3	How do I parcel out work among a bunch of worker threads? . . . . .	56
4.3.4	What kinds of global value mutation are thread-safe? . . . . .	57
4.3.5	Can't we get rid of the Global Interpreter Lock? . . . . .	58
4.4	Input and Output . . . . .	58
4.4.1	How do I delete a file? (And other file questions...) . . . . .	58
4.4.2	How do I copy a file? . . . . .	59
4.4.3	How do I read (or write) binary data? . . . . .	59
4.4.4	I can't seem to use os.read() on a pipe created with os.popen(); why? . . . . .	59
4.4.5	How do I access the serial (RS232) port? . . . . .	59

4.4.6	Why doesn't closing <code>sys.stdout</code> ( <code>stdin</code> , <code>stderr</code> ) really close it?	59
4.5	Network/Internet Programming	60
4.5.1	What WWW tools are there for Python?	60
4.5.2	How can I mimic CGI form submission ( <code>METHOD=POST</code> )?	60
4.5.3	What module should I use to help with generating HTML?	61
4.5.4	How do I send mail from a Python script?	61
4.5.5	How do I avoid blocking in the <code>connect()</code> method of a socket?	61
4.6	Databases	62
4.6.1	Are there any interfaces to database packages in Python?	62
4.6.2	How do you implement persistent objects in Python?	62
4.7	Mathematics and Numerics	62
4.7.1	How do I generate random numbers in Python?	62
<b>5</b>	<b>Extending/Embedding FAQ</b>	<b>63</b>
5.1	Can I create my own functions in C?	63
5.2	Can I create my own functions in C++?	63
5.3	Writing C is hard; are there any alternatives?	63
5.4	How can I execute arbitrary Python statements from C?	63
5.5	How can I evaluate an arbitrary Python expression from C?	64
5.6	How do I extract C values from a Python object?	64
5.7	How do I use <code>Py_BuildValue()</code> to create a tuple of arbitrary length?	64
5.8	How do I call an object's method from C?	64
5.9	How do I catch the output from <code>PyErr_Print()</code> (or anything that prints to <code>stdout/stderr</code> )?	65
5.10	How do I access a module written in Python from C?	65
5.11	How do I interface to C++ objects from Python?	66
5.12	I added a module using the Setup file and the make fails; why?	66
5.13	How do I debug an extension?	66
5.14	I want to compile a Python module on my Linux system, but some files are missing. Why?	66
5.15	How do I tell "incomplete input" from "invalid input"?	66
5.16	How do I find undefined g++ symbols <code>__builtin_new</code> or <code>__pure_virtual</code> ?	67
5.17	Can I create an object class with some methods implemented in C and others in Python (e.g. through inheritance)?	67
<b>6</b>	<b>Python on Windows FAQ</b>	<b>69</b>
6.1	How do I run a Python program under Windows?	69
6.2	How do I make Python scripts executable?	70
6.3	Why does Python sometimes take so long to start?	70
6.4	How do I make an executable from a Python script?	70
6.5	Is a <code>*.pyd</code> file the same as a DLL?	70
6.6	How can I embed Python into a Windows application?	71
6.7	How do I keep editors from inserting tabs into my Python source?	72
6.8	How do I check for a keypress without blocking?	72
6.9	How do I solve the missing <code>api-ms-win-crt-runtime-l1-1-0.dll</code> error?	72
<b>7</b>	<b>Graphic User Interface FAQ</b>	<b>73</b>
7.1	General GUI Questions	73
7.2	What GUI toolkits exist for Python?	73
7.3	Tkinter questions	73
7.3.1	How do I freeze Tkinter applications?	73
7.3.2	Can I have Tk events handled while waiting for I/O?	73
7.3.3	I can't get key bindings to work in Tkinter: why?	74
<b>8</b>	<b>"Why is Python Installed on my Computer?" FAQ</b>	<b>75</b>
8.1	What is Python?	75
8.2	Why is Python installed on my machine?	75
8.3	Can I delete Python?	75
<b>A</b>	<b>Glossary</b>	<b>77</b>

<b>B</b>	<b>About these documents</b>	<b>91</b>
B.1	Contributors to the Python Documentation . . . . .	91
<b>C</b>	<b>History and License</b>	<b>93</b>
C.1	History of the software . . . . .	93
C.2	Terms and conditions for accessing or otherwise using Python . . . . .	94
C.2.1	PSF LICENSE AGREEMENT FOR PYTHON 3.10.10 . . . . .	94
C.2.2	BEOPEN.COM LICENSE AGREEMENT FOR PYTHON 2.0 . . . . .	95
C.2.3	CNRI LICENSE AGREEMENT FOR PYTHON 1.6.1 . . . . .	96
C.2.4	CWI LICENSE AGREEMENT FOR PYTHON 0.9.0 THROUGH 1.2 . . . . .	97
C.2.5	ZERO-CLAUSE BSD LICENSE FOR CODE IN THE PYTHON 3.10.10 DOCUMENTATION . . . . .	97
C.3	Licenses and Acknowledgements for Incorporated Software . . . . .	98
C.3.1	Mersenne Twister . . . . .	98
C.3.2	Sockets . . . . .	99
C.3.3	Asynchronous socket services . . . . .	99
C.3.4	Cookie management . . . . .	100
C.3.5	Execution tracing . . . . .	100
C.3.6	UUencode and UUdecode functions . . . . .	101
C.3.7	XML Remote Procedure Calls . . . . .	101
C.3.8	test_epoll . . . . .	102
C.3.9	Select kqueue . . . . .	102
C.3.10	SipHash24 . . . . .	103
C.3.11	strtod and dtoa . . . . .	103
C.3.12	OpenSSL . . . . .	104
C.3.13	expat . . . . .	106
C.3.14	libffi . . . . .	106
C.3.15	zlib . . . . .	107
C.3.16	cfuhash . . . . .	107
C.3.17	libmpdec . . . . .	108
C.3.18	W3C C14N test suite . . . . .	108
C.3.19	Audioop . . . . .	109
<b>D</b>	<b>Copyright</b>	<b>111</b>
	<b>Index</b>	<b>113</b>





## GENERAL PYTHON FAQ

### 1.1 General Information

#### 1.1.1 What is Python?

Python is an interpreted, interactive, object-oriented programming language. It incorporates modules, exceptions, dynamic typing, very high level dynamic data types, and classes. It supports multiple programming paradigms beyond object-oriented programming, such as procedural and functional programming. Python combines remarkable power with very clear syntax. It has interfaces to many system calls and libraries, as well as to various window systems, and is extensible in C or C++. It is also usable as an extension language for applications that need a programmable interface. Finally, Python is portable: it runs on many Unix variants including Linux and macOS, and on Windows.

To find out more, start with [tutorial-index](#). The [Beginner's Guide to Python](#) links to other introductory tutorials and resources for learning Python.

#### 1.1.2 What is the Python Software Foundation?

The Python Software Foundation is an independent non-profit organization that holds the copyright on Python versions 2.1 and newer. The PSF's mission is to advance open source technology related to the Python programming language and to publicize the use of Python. The PSF's home page is at <https://www.python.org/psf/>.

Donations to the PSF are tax-exempt in the US. If you use Python and find it helpful, please contribute via [the PSF donation page](#).

#### 1.1.3 Are there copyright restrictions on the use of Python?

You can do anything you want with the source, as long as you leave the copyrights in and display those copyrights in any documentation about Python that you produce. If you honor the copyright rules, it's OK to use Python for commercial use, to sell copies of Python in source or binary form (modified or unmodified), or to sell products that incorporate Python in some form. We would still like to know about all commercial use of Python, of course.

See [the PSF license page](#) to find further explanations and a link to the full text of the license.

The Python logo is trademarked, and in certain cases permission is required to use it. Consult [the Trademark Usage Policy](#) for more information.

### 1.1.4 Why was Python created in the first place?

Here's a *very* brief summary of what started it all, written by Guido van Rossum:

I had extensive experience with implementing an interpreted language in the ABC group at CWI, and from working with this group I had learned a lot about language design. This is the origin of many Python features, including the use of indentation for statement grouping and the inclusion of very-high-level data types (although the details are all different in Python).

I had a number of gripes about the ABC language, but also liked many of its features. It was impossible to extend the ABC language (or its implementation) to remedy my complaints – in fact its lack of extensibility was one of its biggest problems. I had some experience with using Modula-2+ and talked with the designers of Modula-3 and read the Modula-3 report. Modula-3 is the origin of the syntax and semantics used for exceptions, and some other Python features.

I was working in the Amoeba distributed operating system group at CWI. We needed a better way to do system administration than by writing either C programs or Bourne shell scripts, since Amoeba had its own system call interface which wasn't easily accessible from the Bourne shell. My experience with error handling in Amoeba made me acutely aware of the importance of exceptions as a programming language feature.

It occurred to me that a scripting language with a syntax like ABC but with access to the Amoeba system calls would fill the need. I realized that it would be foolish to write an Amoeba-specific language, so I decided that I needed a language that was generally extensible.

During the 1989 Christmas holidays, I had a lot of time on my hand, so I decided to give it a try. During the next year, while still mostly working on it in my own time, Python was used in the Amoeba project with increasing success, and the feedback from colleagues made me add many early improvements.

In February 1991, after just over a year of development, I decided to post to USENET. The rest is in the `Misc/HISTORY` file.

### 1.1.5 What is Python good for?

Python is a high-level general-purpose programming language that can be applied to many different classes of problems.

The language comes with a large standard library that covers areas such as string processing (regular expressions, Unicode, calculating differences between files), internet protocols (HTTP, FTP, SMTP, XML-RPC, POP, IMAP, CGI programming), software engineering (unit testing, logging, profiling, parsing Python code), and operating system interfaces (system calls, filesystems, TCP/IP sockets). Look at the table of contents for [library-index](#) to get an idea of what's available. A wide variety of third-party extensions are also available. Consult [the Python Package Index](#) to find packages of interest to you.

### 1.1.6 How does the Python version numbering scheme work?

Python versions are numbered “A.B.C” or “A.B”:

- *A* is the major version number – it is only incremented for really major changes in the language.
- *B* is the minor version number – it is incremented for less earth-shattering changes.
- *C* is the micro version number – it is incremented for each bugfix release.

See [PEP 6](#) for more information about bugfix releases.

Not all releases are bugfix releases. In the run-up to a new major release, a series of development releases are made, denoted as alpha, beta, or release candidate. Alphas are early releases in which interfaces aren't yet finalized; it's not unexpected to see an interface change between two alpha releases. Betas are more stable, preserving existing interfaces but possibly adding new modules, and release candidates are frozen, making no changes except as needed to fix critical bugs.

Alpha, beta and release candidate versions have an additional suffix:

- The suffix for an alpha version is “a $N$ ” for some small number  $N$ .
- The suffix for a beta version is “b $N$ ” for some small number  $N$ .
- The suffix for a release candidate version is “rc $N$ ” for some small number  $N$ .

In other words, all versions labeled 2.0a $N$  precede the versions labeled 2.0b $N$ , which precede versions labeled 2.0rc $N$ , and *those* precede 2.0.

You may also find version numbers with a “+” suffix, e.g. “2.2+”. These are unreleased versions, built directly from the CPython development repository. In practice, after a final minor release is made, the version is incremented to the next minor version, which becomes the “a0” version, e.g. “2.4a0”.

See also the documentation for `sys.version`, `sys.hexversion`, and `sys.version_info`.

### 1.1.7 How do I obtain a copy of the Python source?

The latest Python source distribution is always available from [python.org](https://www.python.org/downloads/), at <https://www.python.org/downloads/>. The latest development sources can be obtained at <https://github.com/python/cpython/>.

The source distribution is a gzipped tar file containing the complete C source, Sphinx-formatted documentation, Python library modules, example programs, and several useful pieces of freely distributable software. The source will compile and run out of the box on most UNIX platforms.

Consult the [Getting Started section of the Python Developer’s Guide](#) for more information on getting the source code and compiling it.

### 1.1.8 How do I get documentation on Python?

The standard documentation for the current stable version of Python is available at <https://docs.python.org/3/>. PDF, plain text, and downloadable HTML versions are also available at <https://docs.python.org/3/download.html>.

The documentation is written in reStructuredText and processed by the [Sphinx documentation tool](#). The reStructuredText source for the documentation is part of the Python source distribution.

### 1.1.9 I’ve never programmed before. Is there a Python tutorial?

There are numerous tutorials and books available. The standard documentation includes [tutorial-index](#).

Consult the [Beginner’s Guide](#) to find information for beginning Python programmers, including lists of tutorials.

### 1.1.10 Is there a newsgroup or mailing list devoted to Python?

There is a newsgroup, `comp.lang.python`, and a mailing list, [python-list](#). The newsgroup and mailing list are gatewayed into each other – if you can read news it’s unnecessary to subscribe to the mailing list. `comp.lang.python` is high-traffic, receiving hundreds of postings every day, and Usenet readers are often more able to cope with this volume.

Announcements of new software releases and events can be found in `comp.lang.python.announce`, a low-traffic moderated list that receives about five postings per day. It’s available as the [python-announce mailing list](#).

More info about other mailing lists and newsgroups can be found at <https://www.python.org/community/lists/>.

### 1.1.11 How do I get a beta test version of Python?

Alpha and beta releases are available from <https://www.python.org/downloads/>. All releases are announced on the comp.lang.python and comp.lang.python.announce newsgroups and on the Python home page at <https://www.python.org/>; an RSS feed of news is available.

You can also access the development version of Python through Git. See [The Python Developer's Guide](#) for details.

### 1.1.12 How do I submit bug reports and patches for Python?

To report a bug or submit a patch, please use the Roundup installation at <https://bugs.python.org/>.

You must have a Roundup account to report bugs; this makes it possible for us to contact you if we have follow-up questions. It will also enable Roundup to send you updates as we act on your bug. If you had previously used SourceForge to report bugs to Python, you can obtain your Roundup password through Roundup's [password reset procedure](#).

For more information on how Python is developed, consult [the Python Developer's Guide](#).

### 1.1.13 Are there any published articles about Python that I can reference?

It's probably best to cite your favorite book about Python.

The [very first article](#) about Python was written in 1991 and is now quite outdated.

Guido van Rossum and Jelke de Boer, "Interactively Testing Remote Servers Using the Python Programming Language", CWI Quarterly, Volume 4, Issue 4 (December 1991), Amsterdam, pp 283–303.

### 1.1.14 Are there any books on Python?

Yes, there are many, and more are being published. See the python.org wiki at <https://wiki.python.org/moin/PythonBooks> for a list.

You can also search online bookstores for "Python" and filter out the Monty Python references; or perhaps search for "Python" and "language".

### 1.1.15 Where in the world is www.python.org located?

The Python project's infrastructure is located all over the world and is managed by the Python Infrastructure Team. Details [here](#).

### 1.1.16 Why is it called Python?

When he began implementing Python, Guido van Rossum was also reading the published scripts from "[Monty Python's Flying Circus](#)", a BBC comedy series from the 1970s. Van Rossum thought he needed a name that was short, unique, and slightly mysterious, so he decided to call the language Python.

### 1.1.17 Do I have to like “Monty Python’s Flying Circus”?

No, but it helps. :)

## 1.2 Python in the real world

### 1.2.1 How stable is Python?

Very stable. New, stable releases have been coming out roughly every 6 to 18 months since 1991, and this seems likely to continue. As of version 3.9, Python will have a major new release every 12 months ([PEP 602](#)).

The developers issue “bugfix” releases of older versions, so the stability of existing releases gradually improves. Bugfix releases, indicated by a third component of the version number (e.g. 3.5.3, 3.6.2), are managed for stability; only fixes for known problems are included in a bugfix release, and it’s guaranteed that interfaces will remain the same throughout a series of bugfix releases.

The latest stable releases can always be found on the [Python download page](#). There are two production-ready versions of Python: 2.x and 3.x. The recommended version is 3.x, which is supported by most widely used libraries. Although 2.x is still widely used, [it is not maintained anymore](#).

### 1.2.2 How many people are using Python?

There are probably millions of users, though it’s difficult to obtain an exact count.

Python is available for free download, so there are no sales figures, and it’s available from many different sites and packaged with many Linux distributions, so download statistics don’t tell the whole story either.

The `comp.lang.python` newsgroup is very active, but not all Python users post to the group or even read it.

### 1.2.3 Have any significant projects been done in Python?

See <https://www.python.org/about/success> for a list of projects that use Python. Consulting the proceedings for [past Python conferences](#) will reveal contributions from many different companies and organizations.

High-profile Python projects include [the Mailman mailing list manager](#) and [the Zope application server](#). Several Linux distributions, most notably [Red Hat](#), have written part or all of their installer and system administration software in Python. Companies that use Python internally include Google, Yahoo, and Lucasfilm Ltd.

### 1.2.4 What new developments are expected for Python in the future?

See <https://www.python.org/dev/peps/> for the Python Enhancement Proposals (PEPs). PEPs are design documents describing a suggested new feature for Python, providing a concise technical specification and a rationale. Look for a PEP titled “Python X.Y Release Schedule”, where X.Y is a version that hasn’t been publicly released yet.

New development is discussed on [the python-dev mailing list](#).

## 1.2.5 Is it reasonable to propose incompatible changes to Python?

In general, no. There are already millions of lines of Python code around the world, so any change in the language that invalidates more than a very small fraction of existing programs has to be frowned upon. Even if you can provide a conversion program, there's still the problem of updating all documentation; many books have been written about Python, and we don't want to invalidate them all at a single stroke.

Providing a gradual upgrade path is necessary if a feature has to be changed. [PEP 5](#) describes the procedure followed for introducing backward-incompatible changes while minimizing disruption for users.

## 1.2.6 Is Python a good language for beginning programmers?

Yes.

It is still common to start students with a procedural and statically typed language such as Pascal, C, or a subset of C++ or Java. Students may be better served by learning Python as their first language. Python has a very simple and consistent syntax and a large standard library and, most importantly, using Python in a beginning programming course lets students concentrate on important programming skills such as problem decomposition and data type design. With Python, students can be quickly introduced to basic concepts such as loops and procedures. They can probably even work with user-defined objects in their very first course.

For a student who has never programmed before, using a statically typed language seems unnatural. It presents additional complexity that the student must master and slows the pace of the course. The students are trying to learn to think like a computer, decompose problems, design consistent interfaces, and encapsulate data. While learning to use a statically typed language is important in the long term, it is not necessarily the best topic to address in the students' first programming course.

Many other aspects of Python make it a good first language. Like Java, Python has a large standard library so that students can be assigned programming projects very early in the course that *do* something. Assignments aren't restricted to the standard four-function calculator and check balancing programs. By using the standard library, students can gain the satisfaction of working on realistic applications as they learn the fundamentals of programming. Using the standard library also teaches students about code reuse. Third-party modules such as PyGame are also helpful in extending the students' reach.

Python's interactive interpreter enables students to test language features while they're programming. They can keep a window with the interpreter running while they enter their program's source in another window. If they can't remember the methods for a list, they can do something like this:

```
>>> L = []
>>> dir(L)
['__add__', '__class__', '__contains__', '__delattr__', '__delitem__',
 '__dir__', '__doc__', '__eq__', '__format__', '__ge__',
 '__getattr__', '__getitem__', '__gt__', '__hash__', '__iadd__',
 '__imul__', '__init__', '__iter__', '__le__', '__len__', '__lt__',
 '__mul__', '__ne__', '__new__', '__reduce__', '__reduce_ex__',
 '__repr__', '__reversed__', '__rmul__', '__setattr__', '__setitem__',
 '__sizeof__', '__str__', '__subclasshook__', 'append', 'clear',
 'copy', 'count', 'extend', 'index', 'insert', 'pop', 'remove',
 'reverse', 'sort']
>>> [d for d in dir(L) if '__' not in d]
['append', 'clear', 'copy', 'count', 'extend', 'index', 'insert', 'pop', 'remove',
 ↪ 'reverse', 'sort']

>>> help(L.append)
Help on built-in function append:

append(...)
    L.append(object) -> None -- append object to end

>>> L.append(1)
```

(continues on next page)

(continued from previous page)

```
>>> L  
[1]
```

With the interpreter, documentation is never far from the student as they are programming.

There are also good IDEs for Python. IDLE is a cross-platform IDE for Python that is written in Python using Tkinter. Emacs users will be happy to know that there is a very good Python mode for Emacs. All of these programming environments provide syntax highlighting, auto-indenting, and access to the interactive interpreter while coding. Consult [the Python wiki](#) for a full list of Python editing environments.

If you want to discuss Python's use in education, you may be interested in joining [the edu-sig mailing list](#).





## PROGRAMMING FAQ

### 2.1 General Questions

#### 2.1.1 Is there a source code level debugger with breakpoints, single-stepping, etc.?

Yes.

Several debuggers for Python are described below, and the built-in function `breakpoint()` allows you to drop into any of them.

The `pdb` module is a simple but adequate console-mode debugger for Python. It is part of the standard Python library, and is documented in the [Library Reference Manual](#). You can also write your own debugger by using the code for `pdb` as an example.

The IDLE interactive development environment, which is part of the standard Python distribution (normally available as [Tools/scripts/idle3](#)), includes a graphical debugger.

PythonWin is a Python IDE that includes a GUI debugger based on `pdb`. The PythonWin debugger colors breakpoints and has quite a few cool features such as debugging non-PythonWin programs. PythonWin is available as part of [pywin32](#) project and as a part of the [ActivePython](#) distribution.

Eric is an IDE built on PyQt and the Scintilla editing component.

[trepan3k](#) is a gdb-like debugger.

[Visual Studio Code](#) is an IDE with debugging tools that integrates with version-control software.

There are a number of commercial Python IDEs that include graphical debuggers. They include:

- [Wing IDE](#)
- [Komodo IDE](#)
- [PyCharm](#)

#### 2.1.2 Are there tools to help find bugs or perform static analysis?

Yes.

[Pylint](#) and [Pyflakes](#) do basic checking that will help you catch bugs sooner.

Static type checkers such as [Mypy](#), [Pyre](#), and [Pytype](#) can check type hints in Python source code.

### 2.1.3 How can I create a stand-alone binary from a Python script?

You don't need the ability to compile Python to C code if all you want is a stand-alone program that users can download and run without having to install the Python distribution first. There are a number of tools that determine the set of modules required by a program and bind these modules together with a Python binary to produce a single executable.

One is to use the freeze tool, which is included in the Python source tree as [Tools/freeze](#). It converts Python byte code to C arrays; with a C compiler you can embed all your modules into a new program, which is then linked with the standard Python modules.

It works by scanning your source recursively for import statements (in both forms) and looking for the modules in the standard Python path as well as in the source directory (for built-in modules). It then turns the bytecode for modules written in Python into C code (array initializers that can be turned into code objects using the marshal module) and creates a custom-made config file that only contains those built-in modules which are actually used in the program. It then compiles the generated C code and links it with the rest of the Python interpreter to form a self-contained binary which acts exactly like your script.

The following packages can help with the creation of console and GUI executables:

- [Nuitka](#) (Cross-platform)
- [PyInstaller](#) (Cross-platform)
- [PyOxidizer](#) (Cross-platform)
- [cx\\_Freeze](#) (Cross-platform)
- [py2app](#) (macOS only)
- [py2exe](#) (Windows only)

### 2.1.4 Are there coding standards or a style guide for Python programs?

Yes. The coding style required for standard library modules is documented as [PEP 8](#).

## 2.2 Core Language

### 2.2.1 Why am I getting an `UnboundLocalError` when the variable has a value?

It can be a surprise to get the `UnboundLocalError` in previously working code when it is modified by adding an assignment statement somewhere in the body of a function.

This code:

```
>>> x = 10
>>> def bar():
...     print(x)
...
>>> bar()
10
```

works, but this code:

```
>>> x = 10
>>> def foo():
...     print(x)
...     x += 1
```

results in an `UnboundLocalError`:

```
>>> foo()
Traceback (most recent call last):
...
UnboundLocalError: local variable 'x' referenced before assignment
```

This is because when you make an assignment to a variable in a scope, that variable becomes local to that scope and shadows any similarly named variable in the outer scope. Since the last statement in `foo` assigns a new value to `x`, the compiler recognizes it as a local variable. Consequently when the earlier `print(x)` attempts to print the uninitialized local variable and an error results.

In the example above you can access the outer scope variable by declaring it `global`:

```
>>> x = 10
>>> def foobar():
...     global x
...     print(x)
...     x += 1
...
>>> foobar()
10
```

This explicit declaration is required in order to remind you that (unlike the superficially analogous situation with class and instance variables) you are actually modifying the value of the variable in the outer scope:

```
>>> print(x)
11
```

You can do a similar thing in a nested scope using the `nonlocal` keyword:

```
>>> def foo():
...     x = 10
...     def bar():
...         nonlocal x
...         print(x)
...         x += 1
...     bar()
...     print(x)
...
>>> foo()
10
11
```

## 2.2.2 What are the rules for local and global variables in Python?

In Python, variables that are only referenced inside a function are implicitly global. If a variable is assigned a value anywhere within the function's body, it's assumed to be a local unless explicitly declared as `global`.

Though a bit surprising at first, a moment's consideration explains this. On one hand, requiring `global` for assigned variables provides a bar against unintended side-effects. On the other hand, if `global` was required for all global references, you'd be using `global` all the time. You'd have to declare as `global` every reference to a built-in function or to a component of an imported module. This clutter would defeat the usefulness of the `global` declaration for identifying side-effects.

## 2.2.3 Why do lambdas defined in a loop with different values all return the same result?

Assume you use a for loop to define a few different lambdas (or even plain functions), e.g.:

```
>>> squares = []
>>> for x in range(5):
...     squares.append(lambda: x**2)
```

This gives you a list that contains 5 lambdas that calculate  $x**2$ . You might expect that, when called, they would return, respectively, 0, 1, 4, 9, and 16. However, when you actually try you will see that they all return 16:

```
>>> squares[2]()
16
>>> squares[4]()
16
```

This happens because  $x$  is not local to the lambdas, but is defined in the outer scope, and it is accessed when the lambda is called — not when it is defined. At the end of the loop, the value of  $x$  is 4, so all the functions now return  $4**2$ , i.e. 16. You can also verify this by changing the value of  $x$  and see how the results of the lambdas change:

```
>>> x = 8
>>> squares[2]()
64
```

In order to avoid this, you need to save the values in variables local to the lambdas, so that they don't rely on the value of the global  $x$ :

```
>>> squares = []
>>> for x in range(5):
...     squares.append(lambda n=x: n**2)
```

Here,  $n=x$  creates a new variable  $n$  local to the lambda and computed when the lambda is defined so that it has the same value that  $x$  had at that point in the loop. This means that the value of  $n$  will be 0 in the first lambda, 1 in the second, 2 in the third, and so on. Therefore each lambda will now return the correct result:

```
>>> squares[2]()
4
>>> squares[4]()
16
```

Note that this behaviour is not peculiar to lambdas, but applies to regular functions too.

## 2.2.4 How do I share global variables across modules?

The canonical way to share information across modules within a single program is to create a special module (often called config or cfg). Just import the config module in all modules of your application; the module then becomes available as a global name. Because there is only one instance of each module, any changes made to the module object get reflected everywhere. For example:

config.py:

```
x = 0    # Default value of the 'x' configuration setting
```

mod.py:

```
import config
config.x = 1
```

main.py:

```
import config
import mod
print(config.x)
```

Note that using a module is also the basis for implementing the singleton design pattern, for the same reason.

## 2.2.5 What are the “best practices” for using import in a module?

In general, don’t use `from modulename import *`. Doing so clutters the importer’s namespace, and makes it much harder for linters to detect undefined names.

Import modules at the top of a file. Doing so makes it clear what other modules your code requires and avoids questions of whether the module name is in scope. Using one import per line makes it easy to add and delete module imports, but using multiple imports per line uses less screen space.

It’s good practice if you import modules in the following order:

1. standard library modules – e.g. `sys`, `os`, `argparse`, `re`
2. third-party library modules (anything installed in Python’s site-packages directory) – e.g. `dateutil`, `requests`, `PIL.Image`
3. locally developed modules

It is sometimes necessary to move imports to a function or class to avoid problems with circular imports. Gordon McMillan says:

Circular imports are fine where both modules use the “import <module>” form of import. They fail when the 2nd module wants to grab a name out of the first (“from module import name”) and the import is at the top level. That’s because names in the 1st are not yet available, because the first module is busy importing the 2nd.

In this case, if the second module is only used in one function, then the import can easily be moved into that function. By the time the import is called, the first module will have finished initializing, and the second module can do its import.

It may also be necessary to move imports out of the top level of code if some of the modules are platform-specific. In that case, it may not even be possible to import all of the modules at the top of the file. In this case, importing the correct modules in the corresponding platform-specific code is a good option.

Only move imports into a local scope, such as inside a function definition, if it’s necessary to solve a problem such as avoiding a circular import or are trying to reduce the initialization time of a module. This technique is especially helpful if many of the imports are unnecessary depending on how the program executes. You may also want to move imports into a function if the modules are only ever used in that function. Note that loading a module the first time may be expensive because of the one time initialization of the module, but loading a module multiple times is virtually free, costing only a couple of dictionary lookups. Even if the module name has gone out of scope, the module is probably available in `sys.modules`.

## 2.2.6 Why are default values shared between objects?

This type of bug commonly bites neophyte programmers. Consider this function:

```
def foo(mydict={}): # Danger: shared reference to one dict for all calls
    ... compute something ...
    mydict[key] = value
    return mydict
```

The first time you call this function, `mydict` contains a single item. The second time, `mydict` contains two items because when `foo()` begins executing, `mydict` starts out with an item already in it.

It is often expected that a function call creates new objects for default values. This is not what happens. Default values are created exactly once, when the function is defined. If that object is changed, like the dictionary in this example, subsequent calls to the function will refer to this changed object.

By definition, immutable objects such as numbers, strings, tuples, and `None`, are safe from change. Changes to mutable objects such as dictionaries, lists, and class instances can lead to confusion.

Because of this feature, it is good programming practice to not use mutable objects as default values. Instead, use `None` as the default value and inside the function, check if the parameter is `None` and create a new list/dictionary/whatever if it is. For example, don't write:

```
def foo(mydict={}):  
    ...
```

but:

```
def foo(mydict=None):  
    if mydict is None:  
        mydict = {} # create a new dict for local namespace
```

This feature can be useful. When you have a function that's time-consuming to compute, a common technique is to cache the parameters and the resulting value of each call to the function, and return the cached value if the same value is requested again. This is called “memoizing”, and can be implemented like this:

```
# Callers can only provide two parameters and optionally pass _cache by keyword  
def expensive(arg1, arg2, *, _cache={}):  
    if (arg1, arg2) in _cache:  
        return _cache[(arg1, arg2)]  
  
    # Calculate the value  
    result = ... expensive computation ...  
    _cache[(arg1, arg2)] = result # Store result in the cache  
    return result
```

You could use a global variable containing a dictionary instead of the default value; it's a matter of taste.

### 2.2.7 How can I pass optional or keyword parameters from one function to another?

Collect the arguments using the `*` and `**` specifiers in the function's parameter list; this gives you the positional arguments as a tuple and the keyword arguments as a dictionary. You can then pass these arguments when calling another function by using `*` and `**`:

```
def f(x, *args, **kwargs):  
    ...  
    kwargs['width'] = '14.3c'  
    ...  
    g(x, *args, **kwargs)
```

## 2.2.8 What is the difference between arguments and parameters?

*Parameters* are defined by the names that appear in a function definition, whereas *arguments* are the values actually passed to a function when calling it. Parameters define what *kind of arguments* a function can accept. For example, given the function definition:

```
def func(foo, bar=None, **kwargs):
    pass
```

`foo`, `bar` and `kwargs` are parameters of `func`. However, when calling `func`, for example:

```
func(42, bar=314, extra=somevar)
```

the values 42, 314, and `somevar` are arguments.

## 2.2.9 Why did changing list ‘y’ also change list ‘x’?

If you wrote code like:

```
>>> x = []
>>> y = x
>>> y.append(10)
>>> y
[10]
>>> x
[10]
```

you might be wondering why appending an element to `y` changed `x` too.

There are two factors that produce this result:

- 1) Variables are simply names that refer to objects. Doing `y = x` doesn't create a copy of the list – it creates a new variable `y` that refers to the same object `x` refers to. This means that there is only one object (the list), and both `x` and `y` refer to it.
- 2) Lists are *mutable*, which means that you can change their content.

After the call to `append()`, the content of the mutable object has changed from `[]` to `[10]`. Since both the variables refer to the same object, using either name accesses the modified value `[10]`.

If we instead assign an immutable object to `x`:

```
>>> x = 5 # ints are immutable
>>> y = x
>>> x = x + 1 # 5 can't be mutated, we are creating a new object here
>>> x
6
>>> y
5
```

we can see that in this case `x` and `y` are not equal anymore. This is because integers are *immutable*, and when we do `x = x + 1` we are not mutating the int 5 by incrementing its value; instead, we are creating a new object (the int 6) and assigning it to `x` (that is, changing which object `x` refers to). After this assignment we have two objects (the ints 6 and 5) and two variables that refer to them (`x` now refers to 6 but `y` still refers to 5).

Some operations (for example `y.append(10)` and `y.sort()`) mutate the object, whereas superficially similar operations (for example `y = y + [10]` and `sorted(y)`) create a new object. In general in Python (and in all cases in the standard library) a method that mutates an object will return `None` to help avoid getting the two types of operations confused. So if you mistakenly write `y.sort()` thinking it will give you a sorted copy of `y`, you'll instead end up with `None`, which will likely cause your program to generate an easily diagnosed error.

However, there is one class of operations where the same operation sometimes has different behaviors with different types: the augmented assignment operators. For example, `+=` mutates lists but not tuples or ints (`a_list +=`

[1, 2, 3] is equivalent to `a_list.extend([1, 2, 3])` and mutates `a_list`, whereas `some_tuple += (1, 2, 3)` and `some_int += 1` create new objects).

In other words:

- If we have a mutable object (`list`, `dict`, `set`, etc.), we can use some specific operations to mutate it and all the variables that refer to it will see the change.
- If we have an immutable object (`str`, `int`, `tuple`, etc.), all the variables that refer to it will always see the same value, but operations that transform that value into a new value always return a new object.

If you want to know if two variables refer to the same object or not, you can use the `is` operator, or the built-in function `id()`.

## 2.2.10 How do I write a function with output parameters (call by reference)?

Remember that arguments are passed by assignment in Python. Since assignment just creates references to objects, there's no alias between an argument name in the caller and callee, and so no call-by-reference per se. You can achieve the desired effect in a number of ways.

- 1) By returning a tuple of the results:

```
>>> def func1(a, b):
...     a = 'new-value'           # a and b are local names
...     b = b + 1                 # assigned to new objects
...     return a, b              # return new values
...
>>> x, y = 'old-value', 99
>>> func1(x, y)
('new-value', 100)
```

This is almost always the clearest solution.

- 2) By using global variables. This isn't thread-safe, and is not recommended.
- 3) By passing a mutable (changeable in-place) object:

```
>>> def func2(a):
...     a[0] = 'new-value'        # 'a' references a mutable list
...     a[1] = a[1] + 1           # changes a shared object
...
>>> args = ['old-value', 99]
>>> func2(args)
>>> args
['new-value', 100]
```

- 4) By passing in a dictionary that gets mutated:

```
>>> def func3(args):
...     args['a'] = 'new-value'    # args is a mutable dictionary
...     args['b'] = args['b'] + 1  # change it in-place
...
>>> args = {'a': 'old-value', 'b': 99}
>>> func3(args)
>>> args
{'a': 'new-value', 'b': 100}
```

- 5) Or bundle up values in a class instance:

```
>>> class Namespace:
...     def __init__(self, /, **args):
...         for key, value in args.items():
...             setattr(self, key, value)
```

(continues on next page)



(continued from previous page)

```

...
>>> def func4(args):
...     args.a = 'new-value'           # args is a mutable Namespace
...     args.b = args.b + 1           # change object in-place
...
>>> args = Namespace(a='old-value', b=99)
>>> func4(args)
>>> vars(args)
{'a': 'new-value', 'b': 100}

```

There's almost never a good reason to get this complicated.

Your best choice is to return a tuple containing the multiple results.

## 2.2.11 How do you make a higher order function in Python?

You have two choices: you can use nested scopes or you can use callable objects. For example, suppose you wanted to define `linear(a,b)` which returns a function `f(x)` that computes the value  $a \cdot x + b$ . Using nested scopes:

```

def linear(a, b):
    def result(x):
        return a * x + b
    return result

```

Or using a callable object:

```

class linear:

    def __init__(self, a, b):
        self.a, self.b = a, b

    def __call__(self, x):
        return self.a * x + self.b

```

In both cases,

```
taxes = linear(0.3, 2)
```

gives a callable object where `taxes(10e6) == 0.3 * 10e6 + 2`.

The callable object approach has the disadvantage that it is a bit slower and results in slightly longer code. However, note that a collection of callables can share their signature via inheritance:

```

class exponential(linear):
    # __init__ inherited
    def __call__(self, x):
        return self.a * (x ** self.b)

```

Object can encapsulate state for several methods:

```

class counter:

    value = 0

    def set(self, x):
        self.value = x

    def up(self):
        self.value = self.value + 1

```

(continues on next page)

(continued from previous page)

```
def down(self):
    self.value = self.value - 1

count = counter()
inc, dec, reset = count.up, count.down, count.set
```

Here `inc()`, `dec()` and `reset()` act like functions which share the same counting variable.

## 2.2.12 How do I copy an object in Python?

In general, try `copy.copy()` or `copy.deepcopy()` for the general case. Not all objects can be copied, but most can.

Some objects can be copied more easily. Dictionaries have a `copy()` method:

```
newdict = olddict.copy()
```

Sequences can be copied by slicing:

```
new_l = l[:]
```

## 2.2.13 How can I find the methods or attributes of an object?

For an instance `x` of a user-defined class, `dir(x)` returns an alphabetized list of the names containing the instance attributes and methods and attributes defined by its class.

## 2.2.14 How can my code discover the name of an object?

Generally speaking, it can't, because objects don't really have names. Essentially, assignment always binds a name to a value; the same is true of `def` and `class` statements, but in that case the value is a callable. Consider the following code:

```
>>> class A:
...     pass
...
>>> B = A
>>> a = B()
>>> b = a
>>> print(b)
<__main__.A object at 0x16D07CC>
>>> print(a)
<__main__.A object at 0x16D07CC>
```

Arguably the class has a name: even though it is bound to two names and invoked through the name `B` the created instance is still reported as an instance of class `A`. However, it is impossible to say whether the instance's name is `a` or `b`, since both names are bound to the same value.

Generally speaking it should not be necessary for your code to “know the names” of particular values. Unless you are deliberately writing introspective programs, this is usually an indication that a change of approach might be beneficial.

In `comp.lang.python`, Fredrik Lundh once gave an excellent analogy in answer to this question:

The same way as you get the name of that cat you found on your porch: the cat (object) itself cannot tell you its name, and it doesn't really care – so the only way to find out what it's called is to ask all your neighbours (namespaces) if it's their cat (object)...

...and don't be surprised if you'll find that it's known by many names, or no name at all!

## 2.2.15 What's up with the comma operator's precedence?

Comma is not an operator in Python. Consider this session:

```
>>> "a" in "b", "a"
(False, 'a')
```

Since the comma is not an operator, but a separator between expressions the above is evaluated as if you had entered:

```
("a" in "b"), "a"
```

not:

```
"a" in ("b", "a")
```

The same is true of the various assignment operators (`=`, `+=` etc). They are not truly operators but syntactic delimiters in assignment statements.

## 2.2.16 Is there an equivalent of C's "?:" ternary operator?

Yes, there is. The syntax is as follows:

```
[on_true] if [expression] else [on_false]

x, y = 50, 25
small = x if x < y else y
```

Before this syntax was introduced in Python 2.5, a common idiom was to use logical operators:

```
[expression] and [on_true] or [on_false]
```

However, this idiom is unsafe, as it can give wrong results when `on_true` has a false boolean value. Therefore, it is always better to use the `... if ... else ...` form.

## 2.2.17 Is it possible to write obfuscated one-liners in Python?

Yes. Usually this is done by nesting `lambda` within `lambda`. See the following three examples, slightly adapted from Ulf Bartelt:

```
from functools import reduce

# Primes < 1000
print(list(filter(None, map(lambda y: y*reduce(lambda x, y: x*y!=0,
map(lambda x, y: y%x, range(2, int(pow(y, 0.5)+1))), 1), range(2, 1000)))))

# First 10 Fibonacci numbers
print(list(map(lambda x, f: lambda x, f: (f(x-1, f)+f(x-2, f)) if x>1 else 1:
f(x, f), range(10))))

# Mandelbrot set
print((lambda Ru, Ro, Iu, Io, IM, Sx, Sy: reduce(lambda x, y: x+'\n'+y, map(lambda y,
Iu=Iu, Io=Io, Ru=Ru, Ro=Ro, Sy=Sy, L=lambda yc, Iu=Iu, Io=Io, Ru=Ru, Ro=Ro, i=IM,
Sx=Sx, Sy=Sy: reduce(lambda x, y: x+y, map(lambda x, yc=Ru, yc=yc, Ru=Ru, Ro=Ro,
i=i, Sx=Sx, F=lambda xc, yc, x, y, k, f: lambda xc, yc, x, y, k, f: (k<=0) or (x*x+y*y
>=4.0) or 1+f(xc, yc, x*x-y*y+xc, 2.0*x*y+yc, k-1, f): f(xc, yc, x, y, k, f): chr(
64+F(Ru+x*(Ro-Ru)/Sx, yc, 0, 0, i)), range(Sx))), L(Iu+y*(Io-Iu)/Sy), range(Sy
)))) (-2.1, 0.7, -1.2, 1.2, 30, 80, 24))
#      \_____/ \_____/ | | | lines on screen
#          V          V | | | columns on screen
```

(continues on next page)

(continued from previous page)

```
#           /           /           / _____ maximum of "iterations"
#           /           / _____ range on y axis
#           / _____ range on x axis
```

Don't try this at home, kids!

## 2.2.18 What does the slash(/) in the parameter list of a function mean?

A slash in the argument list of a function denotes that the parameters prior to it are positional-only. Positional-only parameters are the ones without an externally usable name. Upon calling a function that accepts positional-only parameters, arguments are mapped to parameters based solely on their position. For example, `divmod()` is a function that accepts positional-only parameters. Its documentation looks like this:

```
>>> help(divmod)
Help on built-in function divmod in module builtins:

divmod(x, y, /)
    Return the tuple (x//y, x%y).  Invariant: div*y + mod == x.
```

The slash at the end of the parameter list means that both parameters are positional-only. Thus, calling `divmod()` with keyword arguments would lead to an error:

```
>>> divmod(x=3, y=4)
Traceback (most recent call last):
  File "<stdin>", line 1, in <module>
TypeError: divmod() takes no keyword arguments
```

## 2.3 Numbers and strings

### 2.3.1 How do I specify hexadecimal and octal integers?

To specify an octal digit, precede the octal value with a zero, and then a lower or uppercase “o”. For example, to set the variable “a” to the octal value “10” (8 in decimal), type:

```
>>> a = 0o10
>>> a
8
```

Hexadecimal is just as easy. Simply precede the hexadecimal number with a zero, and then a lower or uppercase “x”. Hexadecimal digits can be specified in lower or uppercase. For example, in the Python interpreter:

```
>>> a = 0xa5
>>> a
165
>>> b = 0xB2
>>> b
178
```

### 2.3.2 Why does `-22 // 10` return `-3`?

It's primarily driven by the desire that `i % j` have the same sign as `j`. If you want that, and also want:

```
i == (i // j) * j + (i % j)
```

then integer division has to return the floor. C also requires that identity to hold, and then compilers that truncate `i // j` need to make `i % j` have the same sign as `i`.

There are few real use cases for `i % j` when `j` is negative. When `j` is positive, there are many, and in virtually all of them it's more useful for `i % j` to be  $\geq 0$ . If the clock says 10 now, what did it say 200 hours ago? `-190 % 12 == 2` is useful; `-190 % 12 == -10` is a bug waiting to bite.

### 2.3.3 How do I get `int` literal attribute instead of `SyntaxError`?

Trying to lookup an `int` literal attribute in the normal manner gives a `SyntaxError` because the period is seen as a decimal point:

```
>>> 1.__class__
File "<stdin>", line 1
  1.__class__
    ^
SyntaxError: invalid decimal literal
```

The solution is to separate the literal from the period with either a space or parentheses.

```
>>> 1 .__class__
<class 'int'>
>>> (1).__class__
<class 'int'>
```

### 2.3.4 How do I convert a string to a number?

For integers, use the built-in `int()` type constructor, e.g. `int('144') == 144`. Similarly, `float()` converts to floating-point, e.g. `float('144') == 144.0`.

By default, these interpret the number as decimal, so that `int('0144') == 144` holds true, and `int('0x144')` raises `ValueError`. `int(string, base)` takes the base to convert from as a second optional argument, so `int('0x144', 16) == 324`. If the base is specified as 0, the number is interpreted using Python's rules: a leading '0o' indicates octal, and '0x' indicates a hex number.

Do not use the built-in function `eval()` if all you need is to convert strings to numbers. `eval()` will be significantly slower and it presents a security risk: someone could pass you a Python expression that might have unwanted side effects. For example, someone could pass `__import__('os').system("rm -rf $HOME")` which would erase your home directory.

`eval()` also has the effect of interpreting numbers as Python expressions, so that e.g. `eval('09')` gives a syntax error because Python does not allow leading '0' in a decimal number (except '0').

### 2.3.5 How do I convert a number to a string?

To convert, e.g., the number 144 to the string '144', use the built-in type constructor `str()`. If you want a hexadecimal or octal representation, use the built-in functions `hex()` or `oct()`. For fancy formatting, see the f-strings and formatstrings sections, e.g. `"{:04d}".format(144)` yields '0144' and `"{: .3f}".format(1.0/3.0)` yields '0.333'.

### 2.3.6 How do I modify a string in place?

You can't, because strings are immutable. In most situations, you should simply construct a new string from the various parts you want to assemble it from. However, if you need an object with the ability to modify in-place unicode data, try using an `io.StringIO` object or the `array` module:

```
>>> import io
>>> s = "Hello, world"
>>> sio = io.StringIO(s)
>>> sio.getvalue()
'Hello, world'
>>> sio.seek(7)
7
>>> sio.write("there!")
6
>>> sio.getvalue()
'Hello, there!'

>>> import array
>>> a = array.array('u', s)
>>> print(a)
array('u', 'Hello, world')
>>> a[0] = 'y'
>>> print(a)
array('u', 'yello, world')
>>> a.tounicode()
'yello, world'
```

### 2.3.7 How do I use strings to call functions/methods?

There are various techniques.

- The best is to use a dictionary that maps strings to functions. The primary advantage of this technique is that the strings do not need to match the names of the functions. This is also the primary technique used to emulate a case construct:

```
def a():
    pass

def b():
    pass

dispatch = {'go': a, 'stop': b}  # Note lack of parens for funcs

dispatch[get_input()]()  # Note trailing parens to call function
```

- Use the built-in function `getattr()`:

```
import foo
getattr(foo, 'bar')()
```

Note that `getattr()` works on any object, including classes, class instances, modules, and so on.

This is used in several places in the standard library, like this:

```
class Foo:
    def do_foo(self):
        ...

    def do_bar(self):
        ...

f = getattr(foo_instance, 'do_' + opname)
f()
```

- Use `locals()` to resolve the function name:

```
def myFunc():
    print("hello")

fname = "myFunc"

f = locals()[fname]
f()
```

### 2.3.8 Is there an equivalent to Perl’s `chomp()` for removing trailing newlines from strings?

You can use `S.rstrip("\r\n")` to remove all occurrences of any line terminator from the end of the string `S` without removing other trailing whitespace. If the string `S` represents more than one line, with several empty lines at the end, the line terminators for all the blank lines will be removed:

```
>>> lines = ("line 1 \r\n"
...          "\r\n"
...          "\r\n")
>>> lines.rstrip("\n\r")
'line 1 '
```

Since this is typically only desired when reading text one line at a time, using `S.rstrip()` this way works well.

### 2.3.9 Is there a `scanf()` or `sscanf()` equivalent?

Not as such.

For simple input parsing, the easiest approach is usually to split the line into whitespace-delimited words using the `split()` method of string objects and then convert decimal strings to numeric values using `int()` or `float()`. `split()` supports an optional “sep” parameter which is useful if the line uses something other than whitespace as a separator.

For more complicated input parsing, regular expressions are more powerful than C’s `sscanf` and better suited for the task.

## 2.3.10 What does ‘UnicodeDecodeError’ or ‘UnicodeEncodeError’ error mean?

See the [unicode-howto](#).

## 2.3.11 Can I end a raw string with an odd number of backslashes?

A raw string ending with an odd number of backslashes will escape the string’s quote:

```
>>> r'C:\this\will\not\work\'
File "<stdin>", line 1
    r'C:\this\will\not\work\'
      ^
SyntaxError: unterminated string literal (detected at line 1)
```

There are several workarounds for this. One is to use regular strings and double the backslashes:

```
>>> 'C:\\this\\will\\work\\'
'C:\\this\\will\\work\\'
```

Another is to concatenate a regular string containing an escaped backslash to the raw string:

```
>>> r'C:\this\will\work' '\\'
'C:\\this\\will\\work\\'
```

It is also possible to use `os.path.join()` to append a backslash on Windows:

```
>>> os.path.join(r'C:\this\will\work', '')
'C:\\this\\will\\work\\'
```

Note that while a backslash will “escape” a quote for the purposes of determining where the raw string ends, no escaping occurs when interpreting the value of the raw string. That is, the backslash remains present in the value of the raw string:

```
>>> r'backslash\'preserved'
"backslash\\'preserved"
```

Also see the specification in the [language reference](#).

## 2.4 Performance

### 2.4.1 My program is too slow. How do I speed it up?

That’s a tough one, in general. First, here are a list of things to remember before diving further:

- Performance characteristics vary across Python implementations. This FAQ focuses on *CPython*.
- Behaviour can vary across operating systems, especially when talking about I/O or multi-threading.
- You should always find the hot spots in your program *before* attempting to optimize any code (see the `profile` module).
- Writing benchmark scripts will allow you to iterate quickly when searching for improvements (see the `timeit` module).
- It is highly recommended to have good code coverage (through unit testing or any other technique) before potentially introducing regressions hidden in sophisticated optimizations.

That being said, there are many tricks to speed up Python code. Here are some general principles which go a long way towards reaching acceptable performance levels:



- Making your algorithms faster (or changing to faster ones) can yield much larger benefits than trying to sprinkle micro-optimization tricks all over your code.
- Use the right data structures. Study documentation for the builtin-types and the `collections` module.
- When the standard library provides a primitive for doing something, it is likely (although not guaranteed) to be faster than any alternative you may come up with. This is doubly true for primitives written in C, such as builtins and some extension types. For example, be sure to use either the `list.sort()` built-in method or the related `sorted()` function to do sorting (and see the `sortinghowto` for examples of moderately advanced usage).
- Abstractions tend to create indirections and force the interpreter to work more. If the levels of indirection outweigh the amount of useful work done, your program will be slower. You should avoid excessive abstraction, especially under the form of tiny functions or methods (which are also often detrimental to readability).

If you have reached the limit of what pure Python can allow, there are tools to take you further away. For example, [Cython](#) can compile a slightly modified version of Python code into a C extension, and can be used on many different platforms. Cython can take advantage of compilation (and optional type annotations) to make your code significantly faster than when interpreted. If you are confident in your C programming skills, you can also write a C extension module yourself.

**See also:**

The wiki page devoted to [performance tips](#).

## 2.4.2 What is the most efficient way to concatenate many strings together?

`str` and `bytes` objects are immutable, therefore concatenating many strings together is inefficient as each concatenation creates a new object. In the general case, the total runtime cost is quadratic in the total string length.

To accumulate many `str` objects, the recommended idiom is to place them into a list and call `str.join()` at the end:

```
chunks = []
for s in my_strings:
    chunks.append(s)
result = ''.join(chunks)
```

(another reasonably efficient idiom is to use `io.StringIO`)

To accumulate many `bytes` objects, the recommended idiom is to extend a `bytearray` object using in-place concatenation (the `+=` operator):

```
result = bytearray()
for b in my_bytes_objects:
    result += b
```

## 2.5 Sequences (Tuples/Lists)

### 2.5.1 How do I convert between tuples and lists?

The type constructor `tuple(seq)` converts any sequence (actually, any iterable) into a tuple with the same items in the same order.

For example, `tuple([1, 2, 3])` yields `(1, 2, 3)` and `tuple('abc')` yields `('a', 'b', 'c')`. If the argument is a tuple, it does not make a copy but returns the same object, so it is cheap to call `tuple()` when you aren't sure that an object is already a tuple.

The type constructor `list(seq)` converts any sequence or iterable into a list with the same items in the same order. For example, `list((1, 2, 3))` yields `[1, 2, 3]` and `list('abc')` yields `['a', 'b', 'c']`. If the argument is a list, it makes a copy just like `seq[:]` would.

## 2.5.2 What's a negative index?

Python sequences are indexed with positive numbers and negative numbers. For positive numbers 0 is the first index 1 is the second index and so forth. For negative indices -1 is the last index and -2 is the penultimate (next to last) index and so forth. Think of `seq[-n]` as the same as `seq[len(seq)-n]`.

Using negative indices can be very convenient. For example `S[:-1]` is all of the string except for its last character, which is useful for removing the trailing newline from a string.

## 2.5.3 How do I iterate over a sequence in reverse order?

Use the `reversed()` built-in function:

```
for x in reversed(sequence):  
    ... # do something with x ...
```

This won't touch your original sequence, but build a new copy with reversed order to iterate over.

## 2.5.4 How do you remove duplicates from a list?

See the Python Cookbook for a long discussion of many ways to do this:

<https://code.activestate.com/recipes/52560/>

If you don't mind reordering the list, sort it and then scan from the end of the list, deleting duplicates as you go:

```
if mylist:  
    mylist.sort()  
    last = mylist[-1]  
    for i in range(len(mylist)-2, -1, -1):  
        if last == mylist[i]:  
            del mylist[i]  
        else:  
            last = mylist[i]
```

If all elements of the list may be used as set keys (i.e. they are all *hashable*) this is often faster

```
mylist = list(set(mylist))
```

This converts the list into a set, thereby removing duplicates, and then back into a list.

## 2.5.5 How do you remove multiple items from a list

As with removing duplicates, explicitly iterating in reverse with a delete condition is one possibility. However, it is easier and faster to use slice replacement with an implicit or explicit forward iteration. Here are three variations.:

```
mylist[:] = filter(keep_function, mylist)  
mylist[:] = (x for x in mylist if keep_condition)  
mylist[:] = [x for x in mylist if keep_condition]
```

The list comprehension may be fastest.

## 2.5.6 How do you make an array in Python?

Use a list:

```
["this", 1, "is", "an", "array"]
```

Lists are equivalent to C or Pascal arrays in their time complexity; the primary difference is that a Python list can contain objects of many different types.

The `array` module also provides methods for creating arrays of fixed types with compact representations, but they are slower to index than lists. Also note that `NumPy` and other third party packages define array-like structures with various characteristics as well.

To get Lisp-style linked lists, you can emulate *cons cells* using tuples:

```
lisp_list = ("like", ("this", ("example", None) ) )
```

If mutability is desired, you could use lists instead of tuples. Here the analogue of a Lisp *car* is `lisp_list[0]` and the analogue of *cdr* is `lisp_list[1]`. Only do this if you're sure you really need to, because it's usually a lot slower than using Python lists.

## 2.5.7 How do I create a multidimensional list?

You probably tried to make a multidimensional array like this:

```
>>> A = [[None] * 2] * 3
```

This looks correct if you print it:

```
>>> A
[[None, None], [None, None], [None, None]]
```

But when you assign a value, it shows up in multiple places:

```
>>> A[0][0] = 5
>>> A
[[5, None], [5, None], [5, None]]
```

The reason is that replicating a list with `*` doesn't create copies, it only creates references to the existing objects. The `*3` creates a list containing 3 references to the same list of length two. Changes to one row will show in all rows, which is almost certainly not what you want.

The suggested approach is to create a list of the desired length first and then fill in each element with a newly created list:

```
A = [None] * 3
for i in range(3):
    A[i] = [None] * 2
```

This generates a list containing 3 different lists of length two. You can also use a list comprehension:

```
w, h = 2, 3
A = [[None] * w for i in range(h)]
```

Or, you can use an extension that provides a matrix datatype; `NumPy` is the best known.

### 2.5.8 How do I apply a method to a sequence of objects?

Use a list comprehension:

```
result = [obj.method() for obj in mylist]
```

### 2.5.9 Why does `a_tuple[i] += ['item']` raise an exception when the addition works?

This is because of a combination of the fact that augmented assignment operators are *assignment* operators, and the difference between mutable and immutable objects in Python.

This discussion applies in general when augmented assignment operators are applied to elements of a tuple that point to mutable objects, but we'll use a `list` and `+=` as our exemplar.

If you wrote:

```
>>> a_tuple = (1, 2)
>>> a_tuple[0] += 1
Traceback (most recent call last):
...
TypeError: 'tuple' object does not support item assignment
```

The reason for the exception should be immediately clear: 1 is added to the object `a_tuple[0]` points to (1), producing the result object, 2, but when we attempt to assign the result of the computation, 2, to element 0 of the tuple, we get an error because we can't change what an element of a tuple points to.

Under the covers, what this augmented assignment statement is doing is approximately this:

```
>>> result = a_tuple[0] + 1
>>> a_tuple[0] = result
Traceback (most recent call last):
...
TypeError: 'tuple' object does not support item assignment
```

It is the assignment part of the operation that produces the error, since a tuple is immutable.

When you write something like:

```
>>> a_tuple = (['foo'], 'bar')
>>> a_tuple[0] += ['item']
Traceback (most recent call last):
...
TypeError: 'tuple' object does not support item assignment
```

The exception is a bit more surprising, and even more surprising is the fact that even though there was an error, the append worked:

```
>>> a_tuple[0]
['foo', 'item']
```

To see why this happens, you need to know that (a) if an object implements an `__iadd__()` magic method, it gets called when the `+=` augmented assignment is executed, and its return value is what gets used in the assignment statement; and (b) for lists, `__iadd__()` is equivalent to calling `extend()` on the list and returning the list. That's why we say that for lists, `+=` is a “shorthand” for `list.extend()`:

```
>>> a_list = []
>>> a_list += [1]
>>> a_list
[1]
```

This is equivalent to:

```
>>> result = a_list.__iadd__([1])
>>> a_list = result
```

The object pointed to by `a_list` has been mutated, and the pointer to the mutated object is assigned back to `a_list`. The end result of the assignment is a no-op, since it is a pointer to the same object that `a_list` was previously pointing to, but the assignment still happens.

Thus, in our tuple example what is happening is equivalent to:

```
>>> result = a_tuple[0].__iadd__(['item'])
>>> a_tuple[0] = result
Traceback (most recent call last):
...
TypeError: 'tuple' object does not support item assignment
```

The `__iadd__()` succeeds, and thus the list is extended, but even though `result` points to the same object that `a_tuple[0]` already points to, that final assignment still results in an error, because tuples are immutable.

## 2.5.10 I want to do a complicated sort: can you do a Schwartzian Transform in Python?

The technique, attributed to Randal Schwartz of the Perl community, sorts the elements of a list by a metric which maps each element to its “sort value”. In Python, use the `key` argument for the `list.sort()` method:

```
Isorted = L[:]
Isorted.sort(key=lambda s: int(s[10:15]))
```

## 2.5.11 How can I sort one list by values from another list?

Merge them into an iterator of tuples, sort the resulting list, and then pick out the element you want.

```
>>> list1 = ["what", "I'm", "sorting", "by"]
>>> list2 = ["something", "else", "to", "sort"]
>>> pairs = zip(list1, list2)
>>> pairs = sorted(pairs)
>>> pairs
[('I'm', 'else'), ('by', 'sort'), ('sorting', 'to'), ('what', 'something')]
>>> result = [x[1] for x in pairs]
>>> result
['else', 'sort', 'to', 'something']
```

## 2.6 Objects

### 2.6.1 What is a class?

A class is the particular object type created by executing a class statement. Class objects are used as templates to create instance objects, which embody both the data (attributes) and code (methods) specific to a datatype.

A class can be based on one or more other classes, called its base class(es). It then inherits the attributes and methods of its base classes. This allows an object model to be successively refined by inheritance. You might have a generic `Mailbox` class that provides basic accessor methods for a mailbox, and subclasses such as `MboxMailbox`, `MaildirMailbox`, `OutlookMailbox` that handle various specific mailbox formats.

## 2.6.2 What is a method?

A method is a function on some object `x` that you normally call as `x.name(arguments...)`. Methods are defined as functions inside the class definition:

```
class C:
    def meth(self, arg):
        return arg * 2 + self.attribute
```

## 2.6.3 What is self?

Self is merely a conventional name for the first argument of a method. A method defined as `meth(self, a, b, c)` should be called as `x.meth(a, b, c)` for some instance `x` of the class in which the definition occurs; the called method will think it is called as `meth(x, a, b, c)`.

See also *Why must 'self' be used explicitly in method definitions and calls?*.

## 2.6.4 How do I check if an object is an instance of a given class or of a subclass of it?

Use the built-in function `isinstance(obj, cls)`. You can check if an object is an instance of any of a number of classes by providing a tuple instead of a single class, e.g. `isinstance(obj, (class1, class2, ...))`, and can also check whether an object is one of Python's built-in types, e.g. `isinstance(obj, str)` or `isinstance(obj, (int, float, complex))`.

Note that `isinstance()` also checks for virtual inheritance from an *abstract base class*. So, the test will return `True` for a registered class even if hasn't directly or indirectly inherited from it. To test for "true inheritance", scan the *MRO* of the class:

```
from collections.abc import Mapping

class P:
    pass

class C(P):
    pass

Mapping.register(P)
```

```
>>> c = C()
>>> isinstance(c, C)           # direct
True
>>> isinstance(c, P)           # indirect
True
>>> isinstance(c, Mapping)     # virtual
True

# Actual inheritance chain
>>> type(c).__mro__
(<class 'C'>, <class 'P'>, <class 'object'>)

# Test for "true inheritance"
>>> Mapping in type(c).__mro__
False
```

Note that most programs do not use `isinstance()` on user-defined classes very often. If you are developing the classes yourself, a more proper object-oriented style is to define methods on the classes that encapsulate a particular behaviour, instead of checking the object's class and doing a different thing based on what class it is. For example, if you have a function that does something:

```
def search(obj):
    if isinstance(obj, Mailbox):
        ... # code to search a mailbox
    elif isinstance(obj, Document):
        ... # code to search a document
    elif ...
```

A better approach is to define a `search()` method on all the classes and just call it:

```
class Mailbox:
    def search(self):
        ... # code to search a mailbox

class Document:
    def search(self):
        ... # code to search a document

obj.search()
```

## 2.6.5 What is delegation?

Delegation is an object oriented technique (also called a design pattern). Let's say you have an object `x` and want to change the behaviour of just one of its methods. You can create a new class that provides a new implementation of the method you're interested in changing and delegates all other methods to the corresponding method of `x`.

Python programmers can easily implement delegation. For example, the following class implements a class that behaves like a file but converts all written data to uppercase:

```
class UpperOut:

    def __init__(self, outfile):
        self._outfile = outfile

    def write(self, s):
        self._outfile.write(s.upper())

    def __getattr__(self, name):
        return getattr(self._outfile, name)
```

Here the `UpperOut` class redefines the `write()` method to convert the argument string to uppercase before calling the underlying `self._outfile.write()` method. All other methods are delegated to the underlying `self._outfile` object. The delegation is accomplished via the `__getattr__()` method; consult the language reference for more information about controlling attribute access.

Note that for more general cases delegation can get trickier. When attributes must be set as well as retrieved, the class must define a `__setattr__()` method too, and it must do so carefully. The basic implementation of `__setattr__()` is roughly equivalent to the following:

```
class X:
    ...
    def __setattr__(self, name, value):
        self.__dict__[name] = value
    ...
```

Most `__setattr__()` implementations must modify `self.__dict__` to store local state for `self` without causing an infinite recursion.

## 2.6.6 How do I call a method defined in a base class from a derived class that extends it?

Use the built-in `super()` function:

```
class Derived(Base):
    def meth(self):
        super().meth()    # calls Base.meth
```

In the example, `super()` will automatically determine the instance from which it was called (the `self` value), look up the *method resolution order* (MRO) with `type(self).__mro__`, and return the next in line after `Derived` in the MRO: `Base`.

## 2.6.7 How can I organize my code to make it easier to change the base class?

You could assign the base class to an alias and derive from the alias. Then all you have to change is the value assigned to the alias. Incidentally, this trick is also handy if you want to decide dynamically (e.g. depending on availability of resources) which base class to use. Example:

```
class Base:
    ...

BaseAlias = Base

class Derived(BaseAlias):
    ...
```

## 2.6.8 How do I create static class data and static class methods?

Both static data and static methods (in the sense of C++ or Java) are supported in Python.

For static data, simply define a class attribute. To assign a new value to the attribute, you have to explicitly use the class name in the assignment:

```
class C:
    count = 0    # number of times C.__init__ called

    def __init__(self):
        C.count = C.count + 1

    def getcount(self):
        return C.count    # or return self.count
```

`c.count` also refers to `C.count` for any `c` such that `isinstance(c, C)` holds, unless overridden by `c` itself or by some class on the base-class search path from `c.__class__` back to `C`.

Caution: within a method of `C`, an assignment like `self.count = 42` creates a new and unrelated instance named “count” in `self`’s own dict. Rebinding of a class-static data name must always specify the class whether inside a method or not:

```
C.count = 314
```

Static methods are possible:

```
class C:
    @staticmethod
    def static(arg1, arg2, arg3):
        # No 'self' parameter!
        ...
```



However, a far more straightforward way to get the effect of a static method is via a simple module-level function:

```
def getcount():
    return C.count
```

If your code is structured so as to define one class (or tightly related class hierarchy) per module, this supplies the desired encapsulation.

## 2.6.9 How can I overload constructors (or methods) in Python?

This answer actually applies to all methods, but the question usually comes up first in the context of constructors.

In C++ you'd write

```
class C {
    C() { cout << "No arguments\n"; }
    C(int i) { cout << "Argument is " << i << "\n"; }
}
```

In Python you have to write a single constructor that catches all cases using default arguments. For example:

```
class C:
    def __init__(self, i=None):
        if i is None:
            print("No arguments")
        else:
            print("Argument is", i)
```

This is not entirely equivalent, but close enough in practice.

You could also try a variable-length argument list, e.g.

```
def __init__(self, *args):
    ...
```

The same approach works for all method definitions.

## 2.6.10 I try to use `__spam` and I get an error about `_SomeClassName__spam`.

Variable names with double leading underscores are “mangled” to provide a simple but effective way to define class private variables. Any identifier of the form `__spam` (at least two leading underscores, at most one trailing underscore) is textually replaced with `_classname__spam`, where `classname` is the current class name with any leading underscores stripped.

This doesn't guarantee privacy: an outside user can still deliberately access the “`_classname__spam`” attribute, and private values are visible in the object's `__dict__`. Many Python programmers never bother to use private variable names at all.

## 2.6.11 My class defines `__del__` but it is not called when I delete the object.

There are several possible reasons for this.

The `del` statement does not necessarily call `__del__()` – it simply decrements the object's reference count, and if this reaches zero `__del__()` is called.

If your data structures contain circular links (e.g. a tree where each child has a parent reference and each parent has a list of children) the reference counts will never go back to zero. Once in a while Python runs an algorithm to detect such cycles, but the garbage collector might run some time after the last reference to your data structure vanishes, so your `__del__()` method may be called at an inconvenient and random time. This is inconvenient if you're trying

to reproduce a problem. Worse, the order in which object's `__del__()` methods are executed is arbitrary. You can run `gc.collect()` to force a collection, but there *are* pathological cases where objects will never be collected.

Despite the cycle collector, it's still a good idea to define an explicit `close()` method on objects to be called whenever you're done with them. The `close()` method can then remove attributes that refer to subobjects. Don't call `__del__()` directly – `__del__()` should call `close()` and `close()` should make sure that it can be called more than once for the same object.

Another way to avoid cyclical references is to use the `weakref` module, which allows you to point to objects without incrementing their reference count. Tree data structures, for instance, should use weak references for their parent and sibling references (if they need them!).

Finally, if your `__del__()` method raises an exception, a warning message is printed to `sys.stderr`.

## 2.6.12 How do I get a list of all instances of a given class?

Python does not keep track of all instances of a class (or of a built-in type). You can program the class's constructor to keep track of all instances by keeping a list of weak references to each instance.

## 2.6.13 Why does the result of `id()` appear to be not unique?

The `id()` builtin returns an integer that is guaranteed to be unique during the lifetime of the object. Since in CPython, this is the object's memory address, it happens frequently that after an object is deleted from memory, the next freshly created object is allocated at the same position in memory. This is illustrated by this example:

```
>>> id(1000)
13901272
>>> id(2000)
13901272
```

The two ids belong to different integer objects that are created before, and deleted immediately after execution of the `id()` call. To be sure that objects whose id you want to examine are still alive, create another reference to the object:

```
>>> a = 1000; b = 2000
>>> id(a)
13901272
>>> id(b)
13891296
```

## 2.6.14 When can I rely on identity tests with the `is` operator?

The `is` operator tests for object identity. The test `a is b` is equivalent to `id(a) == id(b)`.

The most important property of an identity test is that an object is always identical to itself, `a is a` always returns `True`. Identity tests are usually faster than equality tests. And unlike equality tests, identity tests are guaranteed to return a boolean `True` or `False`.

However, identity tests can *only* be substituted for equality tests when object identity is assured. Generally, there are three circumstances where identity is guaranteed:

- 1) Assignments create new names but do not change object identity. After the assignment `new = old`, it is guaranteed that `new is old`.
- 2) Putting an object in a container that stores object references does not change object identity. After the list assignment `s[0] = x`, it is guaranteed that `s[0] is x`.
- 3) If an object is a singleton, it means that only one instance of that object can exist. After the assignments `a = None` and `b = None`, it is guaranteed that `a is b` because `None` is a singleton.

In most other circumstances, identity tests are inadvisable and equality tests are preferred. In particular, identity tests should not be used to check constants such as `int` and `str` which aren't guaranteed to be singletons:

```
>>> a = 1000
>>> b = 500
>>> c = b + 500
>>> a is c
False

>>> a = 'Python'
>>> b = 'Py'
>>> c = b + 'thon'
>>> a is c
False
```

Likewise, new instances of mutable containers are never identical:

```
>>> a = []
>>> b = []
>>> a is b
False
```

In the standard library code, you will see several common patterns for correctly using identity tests:

- 1) As recommended by **PEP 8**, an identity test is the preferred way to check for `None`. This reads like plain English in code and avoids confusion with other objects that may have boolean values that evaluate to false.
- 2) Detecting optional arguments can be tricky when `None` is a valid input value. In those situations, you can create a singleton sentinel object guaranteed to be distinct from other objects. For example, here is how to implement a method that behaves like `dict.pop()`:

```
_sentinel = object()

def pop(self, key, default=_sentinel):
    if key in self:
        value = self[key]
        del self[key]
        return value
    if default is _sentinel:
        raise KeyError(key)
    return default
```

- 3) Container implementations sometimes need to augment equality tests with identity tests. This prevents the code from being confused by objects such as `float('NaN')` that are not equal to themselves.

For example, here is the implementation of `collections.abc.Sequence.__contains__()`:

```
def __contains__(self, value):
    for v in self:
        if v is value or v == value:
            return True
    return False
```

## 2.6.15 How can a subclass control what data is stored in an immutable instance?

When subclassing an immutable type, override the `__new__()` method instead of the `__init__()` method. The latter only runs *after* an instance is created, which is too late to alter data in an immutable instance.

All of these immutable classes have a different signature than their parent class:

```
from datetime import date

class FirstOfMonthDate(date):
```

(continues on next page)

(continued from previous page)

```
"Always choose the first day of the month"
def __new__(cls, year, month, day):
    return super().__new__(cls, year, month, 1)

class NamedInt(int):
    "Allow text names for some numbers"
    xlat = {'zero': 0, 'one': 1, 'ten': 10}
    def __new__(cls, value):
        value = cls.xlat.get(value, value)
        return super().__new__(cls, value)

class TitleStr(str):
    "Convert str to name suitable for a URL path"
    def __new__(cls, s):
        s = s.lower().replace(' ', '-')
        s = ''.join([c for c in s if c.isalnum() or c == '-'])
        return super().__new__(cls, s)
```

The classes can be used like this:

```
>>> FirstOfMonthDate(2012, 2, 14)
FirstOfMonthDate(2012, 2, 1)
>>> NamedInt('ten')
10
>>> NamedInt(20)
20
>>> TitleStr('Blog: Why Python Rocks')
'blog-why-python-rocks'
```

## 2.6.16 How do I cache method calls?

The two principal tools for caching methods are `functools.cached_property()` and `functools.lru_cache()`. The former stores results at the instance level and the latter at the class level.

The *cached\_property* approach only works with methods that do not take any arguments. It does not create a reference to the instance. The cached method result will be kept only as long as the instance is alive.

The advantage is that when an instance is no longer used, the cached method result will be released right away. The disadvantage is that if instances accumulate, so too will the accumulated method results. They can grow without bound.

The *lru\_cache* approach works with methods that have *hashable* arguments. It creates a reference to the instance unless special efforts are made to pass in weak references.

The advantage of the least recently used algorithm is that the cache is bounded by the specified *maxsize*. The disadvantage is that instances are kept alive until they age out of the cache or until the cache is cleared.

This example shows the various techniques:

```
class Weather:
    "Lookup weather information on a government website"

    def __init__(self, station_id):
        self._station_id = station_id
        # The _station_id is private and immutable

    def current_temperature(self):
        "Latest hourly observation"
        # Do not cache this because old results
        # can be out of date.
```

(continues on next page)

(continued from previous page)

```

@cached_property
def location(self):
    "Return the longitude/latitude coordinates of the station"
    # Result only depends on the station_id

@lru_cache(maxsize=20)
def historic_rainfall(self, date, units='mm'):
    "Rainfall on a given date"
    # Depends on the station_id, date, and units.

```

The above example assumes that the *station\_id* never changes. If the relevant instance attributes are mutable, the *cached\_property* approach can't be made to work because it cannot detect changes to the attributes.

The *lru\_cache* approach can be made to work, but the class needs to define the *\_\_eq\_\_* and *\_\_hash\_\_* methods so the cache can detect relevant attribute updates:

```

class Weather:
    "Example with a mutable station identifier"

    def __init__(self, station_id):
        self.station_id = station_id

    def change_station(self, station_id):
        self.station_id = station_id

    def __eq__(self, other):
        return self.station_id == other.station_id

    def __hash__(self):
        return hash(self.station_id)

@lru_cache(maxsize=20)
def historic_rainfall(self, date, units='cm'):
    'Rainfall on a given date'
    # Depends on the station_id, date, and units.

```

## 2.7 Modules

### 2.7.1 How do I create a .pyc file?

When a module is imported for the first time (or when the source file has changed since the current compiled file was created) a *.pyc* file containing the compiled code should be created in a *\_\_pycache\_\_* subdirectory of the directory containing the *.py* file. The *.pyc* file will have a filename that starts with the same name as the *.py* file, and ends with *.pyc*, with a middle component that depends on the particular *python* binary that created it. (See [PEP 3147](#) for details.)

One reason that a *.pyc* file may not be created is a permissions problem with the directory containing the source file, meaning that the *\_\_pycache\_\_* subdirectory cannot be created. This can happen, for example, if you develop as one user but run as another, such as if you are testing with a web server.

Unless the *PYTHONDONTWRITEBYTECODE* environment variable is set, creation of a *.pyc* file is automatic if you're importing a module and Python has the ability (permissions, free space, etc...) to create a *\_\_pycache\_\_* subdirectory and write the compiled module to that subdirectory.

Running Python on a top level script is not considered an import and no *.pyc* will be created. For example, if you have a top-level module *foo.py* that imports another module *xyz.py*, when you run *foo* (by typing *python foo.py* as a shell command), a *.pyc* will be created for *xyz* because *xyz* is imported, but no *.pyc* file will be created for *foo* since *foo.py* isn't being imported.

If you need to create a `.pyc` file for `foo` – that is, to create a `.pyc` file for a module that is not imported – you can, using the `py_compile` and `compileall` modules.

The `py_compile` module can manually compile any module. One way is to use the `compile()` function in that module interactively:

```
>>> import py_compile
>>> py_compile.compile('foo.py')
```

This will write the `.pyc` to a `__pycache__` subdirectory in the same location as `foo.py` (or you can override that with the optional parameter `cfile`).

You can also automatically compile all files in a directory or directories using the `compileall` module. You can do it from the shell prompt by running `compileall.py` and providing the path of a directory containing Python files to compile:

```
python -m compileall .
```

### 2.7.2 How do I find the current module name?

A module can find out its own module name by looking at the predefined global variable `__name__`. If this has the value `'__main__'`, the program is running as a script. Many modules that are usually used by importing them also provide a command-line interface or a self-test, and only execute this code after checking `__name__`:

```
def main():
    print('Running test...')
    ...

if __name__ == '__main__':
    main()
```

### 2.7.3 How can I have modules that mutually import each other?

Suppose you have the following modules:

`foo.py`:

```
from bar import bar_var
foo_var = 1
```

`bar.py`:

```
from foo import foo_var
bar_var = 2
```

The problem is that the interpreter will perform the following steps:

- main imports `foo`
- Empty globals for `foo` are created
- `foo` is compiled and starts executing
- `foo` imports `bar`
- Empty globals for `bar` are created
- `bar` is compiled and starts executing
- `bar` imports `foo` (which is a no-op since there already is a module named `foo`)
- The import mechanism tries to read `foo_var` from `foo` globals, to set `bar.foo_var = foo.foo_var`

The last step fails, because Python isn't done with interpreting `foo` yet and the global symbol dictionary for `foo` is still empty.

The same thing happens when you use `import foo`, and then try to access `foo.foo_var` in global code.

There are (at least) three possible workarounds for this problem.

Guido van Rossum recommends avoiding all uses of `from <module> import ...`, and placing all code inside functions. Initializations of global variables and class variables should use constants or built-in functions only. This means everything from an imported module is referenced as `<module>.<name>`.

Jim Roskind suggests performing steps in the following order in each module:

- exports (globals, functions, and classes that don't need imported base classes)
- `import` statements
- active code (including globals that are initialized from imported values).

Van Rossum doesn't like this approach much because the imports appear in a strange place, but it does work.

Matthias Urlichs recommends restructuring your code so that the recursive import is not necessary in the first place.

These solutions are not mutually exclusive.

## 2.7.4 `__import__`('x.y.z') returns <module 'x'>; how do I get z?

Consider using the convenience function `import_module()` from `importlib` instead:

```
z = importlib.import_module('x.y.z')
```

## 2.7.5 When I edit an imported module and reimport it, the changes don't show up. Why does this happen?

For reasons of efficiency as well as consistency, Python only reads the module file on the first time a module is imported. If it didn't, in a program consisting of many modules where each one imports the same basic module, the basic module would be parsed and re-parsed many times. To force re-reading of a changed module, do this:

```
import importlib
import modname
importlib.reload(modname)
```

Warning: this technique is not 100% fool-proof. In particular, modules containing statements like

```
from modname import some_objects
```

will continue to work with the old version of the imported objects. If the module contains class definitions, existing class instances will *not* be updated to use the new class definition. This can result in the following paradoxical behaviour:

```
>>> import importlib
>>> import cls
>>> c = cls.C()                                # Create an instance of C
>>> importlib.reload(cls)
<module 'cls' from 'cls.py'>
>>> isinstance(c, cls.C)                       # isinstance is false?!?
False
```

The nature of the problem is made clear if you print out the “identity” of the class objects:

```
>>> hex(id(c.__class__))  
'0x7352a0'  
>>> hex(id(cls.C))  
'0x4198d0'
```



## DESIGN AND HISTORY FAQ

### 3.1 Why does Python use indentation for grouping of statements?

Guido van Rossum believes that using indentation for grouping is extremely elegant and contributes a lot to the clarity of the average Python program. Most people learn to love this feature after a while.

Since there are no begin/end brackets there cannot be a disagreement between grouping perceived by the parser and the human reader. Occasionally C programmers will encounter a fragment of code like this:

```
if (x <= y)
    x++;
    y--;
z++;
```

Only the `x++` statement is executed if the condition is true, but the indentation leads many to believe otherwise. Even experienced C programmers will sometimes stare at it a long time wondering as to why `y` is being decremented even for `x > y`.

Because there are no begin/end brackets, Python is much less prone to coding-style conflicts. In C there are many different ways to place the braces. After becoming used to reading and writing code using a particular style, it is normal to feel somewhat uneasy when reading (or being required to write) in a different one.

Many coding styles place begin/end brackets on a line by themselves. This makes programs considerably longer and wastes valuable screen space, making it harder to get a good overview of a program. Ideally, a function should fit on one screen (say, 20–30 lines). 20 lines of Python can do a lot more work than 20 lines of C. This is not solely due to the lack of begin/end brackets – the lack of declarations and the high-level data types are also responsible – but the indentation-based syntax certainly helps.

### 3.2 Why am I getting strange results with simple arithmetic operations?

See the next question.

### 3.3 Why are floating-point calculations so inaccurate?

Users are often surprised by results like this:

```
>>> 1.2 - 1.0
0.19999999999999996
```

and think it is a bug in Python. It's not. This has little to do with Python, and much more to do with how the underlying platform handles floating-point numbers.

The `float` type in CPython uses a C `double` for storage. A `float` object's value is stored in binary floating-point with a fixed precision (typically 53 bits) and Python uses C operations, which in turn rely on the hardware implementation in the processor, to perform floating-point operations. This means that as far as floating-point operations are concerned, Python behaves like many popular languages including C and Java.

Many numbers that can be written easily in decimal notation cannot be expressed exactly in binary floating-point. For example, after:

```
>>> x = 1.2
```

the value stored for `x` is a (very good) approximation to the decimal value `1.2`, but is not exactly equal to it. On a typical machine, the actual stored value is:

```
1.0011001100110011001100110011001100110011001100110011001100110011 (binary)
```

which is exactly:

```
1.1999999999999999555910790149937383830547332763671875 (decimal)
```

The typical precision of 53 bits provides Python floats with 15–16 decimal digits of accuracy.

For a fuller explanation, please see the floating point arithmetic chapter in the Python tutorial.

## 3.4 Why are Python strings immutable?

There are several advantages.

One is performance: knowing that a string is immutable means we can allocate space for it at creation time, and the storage requirements are fixed and unchanging. This is also one of the reasons for the distinction between tuples and lists.

Another advantage is that strings in Python are considered as “elemental” as numbers. No amount of activity will change the value `8` to anything else, and in Python, no amount of activity will change the string “eight” to anything else.

## 3.5 Why must ‘self’ be used explicitly in method definitions and calls?

The idea was borrowed from Modula-3. It turns out to be very useful, for a variety of reasons.

First, it's more obvious that you are using a method or instance attribute instead of a local variable. Reading `self.x` or `self.meth()` makes it absolutely clear that an instance variable or method is used even if you don't know the class definition by heart. In C++, you can sort of tell by the lack of a local variable declaration (assuming globals are rare or easily recognizable) – but in Python, there are no local variable declarations, so you'd have to look up the class definition to be sure. Some C++ and Java coding standards call for instance attributes to have an `m_` prefix, so this explicitness is still useful in those languages, too.

Second, it means that no special syntax is necessary if you want to explicitly reference or call the method from a particular class. In C++, if you want to use a method from a base class which is overridden in a derived class, you have to use the `::` operator – in Python you can write `baseclass.methodname(self, <argument list>)`. This is particularly useful for `__init__()` methods, and in general in cases where a derived class method wants to extend the base class method of the same name and thus has to call the base class method somehow.

Finally, for instance variables it solves a syntactic problem with assignment: since local variables in Python are (by definition!) those variables to which a value is assigned in a function body (and that aren't explicitly declared global), there has to be some way to tell the interpreter that an assignment was meant to assign to an instance variable instead of to a local variable, and it should preferably be syntactic (for efficiency reasons). C++ does this through declarations, but Python doesn't have declarations and it would be a pity having to introduce them just for this purpose. Using the

explicit `self.var` solves this nicely. Similarly, for using instance variables, having to write `self.var` means that references to unqualified names inside a method don't have to search the instance's directories. To put it another way, local variables and instance variables live in two different namespaces, and you need to tell Python which namespace to use.

### 3.6 Why can't I use an assignment in an expression?

Starting in Python 3.8, you can!

Assignment expressions using the walrus operator `:=` assign a variable in an expression:

```
while chunk := fp.read(200):
    print(chunk)
```

See [PEP 572](#) for more information.

### 3.7 Why does Python use methods for some functionality (e.g. `list.index()`) but functions for other (e.g. `len(list)`)?

As Guido said:

(a) For some operations, prefix notation just reads better than postfix – prefix (and infix!) operations have a long tradition in mathematics which likes notations where the visuals help the mathematician thinking about a problem. Compare the ease with which we rewrite a formula like  $x \cdot (a+b)$  into  $x \cdot a + x \cdot b$  to the clumsiness of doing the same thing using a raw OO notation.

(b) When I read code that says `len(x)` I *know* that it is asking for the length of something. This tells me two things: the result is an integer, and the argument is some kind of container. To the contrary, when I read `x.len()`, I have to already know that `x` is some kind of container implementing an interface or inheriting from a class that has a standard `len()`. Witness the confusion we occasionally have when a class that is not implementing a mapping has a `get()` or `keys()` method, or something that isn't a file has a `write()` method.

—<https://mail.python.org/pipermail/python-3000/2006-November/004643.html>

### 3.8 Why is `join()` a string method instead of a list or tuple method?

Strings became much more like other standard types starting in Python 1.6, when methods were added which give the same functionality that has always been available using the functions of the string module. Most of these new methods have been widely accepted, but the one which appears to make some programmers feel uncomfortable is:

```
", ".join(['1', '2', '4', '8', '16'])
```

which gives the result:

```
"1, 2, 4, 8, 16"
```

There are two common arguments against this usage.

The first runs along the lines of: “It looks really ugly using a method of a string literal (string constant)”, to which the answer is that it might, but a string literal is just a fixed value. If the methods are to be allowed on names bound to strings there is no logical reason to make them unavailable on literals.

The second objection is typically cast as: “I am really telling a sequence to join its members together with a string constant”. Sadly, you aren't. For some reason there seems to be much less difficulty with having `split()` as a string method, since in that case it is easy to see that

```
"1, 2, 4, 8, 16".split(", ")
```

is an instruction to a string literal to return the substrings delimited by the given separator (or, by default, arbitrary runs of white space).

`join()` is a string method because in using it you are telling the separator string to iterate over a sequence of strings and insert itself between adjacent elements. This method can be used with any argument which obeys the rules for sequence objects, including any new classes you might define yourself. Similar methods exist for bytes and bytearray objects.

## 3.9 How fast are exceptions?

A try/except block is extremely efficient if no exceptions are raised. Actually catching an exception is expensive. In versions of Python prior to 2.0 it was common to use this idiom:

```
try:
    value = mydict[key]
except KeyError:
    mydict[key] = getvalue(key)
    value = mydict[key]
```

This only made sense when you expected the dict to have the key almost all the time. If that wasn't the case, you coded it like this:

```
if key in mydict:
    value = mydict[key]
else:
    value = mydict[key] = getvalue(key)
```

For this specific case, you could also use `value = dict.setdefault(key, getvalue(key))`, but only if the `getvalue()` call is cheap enough because it is evaluated in all cases.

## 3.10 Why isn't there a switch or case statement in Python?

You can do this easily enough with a sequence of `if... elif... elif... else`. For literal values, or constants within a namespace, you can also use a `match ... case` statement.

For cases where you need to choose from a very large number of possibilities, you can create a dictionary mapping case values to functions to call. For example:

```
functions = {'a': function_1,
            'b': function_2,
            'c': self.method_1}

func = functions[value]
func()
```

For calling methods on objects, you can simplify yet further by using the `getattr()` built-in to retrieve methods with a particular name:

```
class MyVisitor:
    def visit_a(self):
        ...

    def dispatch(self, value):
        method_name = 'visit_' + str(value)
        method = getattr(self, method_name)
        method()
```

It's suggested that you use a prefix for the method names, such as `visit_` in this example. Without such a prefix, if values are coming from an untrusted source, an attacker would be able to call any method on your object.

### 3.11 Can't you emulate threads in the interpreter instead of relying on an OS-specific thread implementation?

Answer 1: Unfortunately, the interpreter pushes at least one C stack frame for each Python stack frame. Also, extensions can call back into Python at almost random moments. Therefore, a complete threads implementation requires thread support for C.

Answer 2: Fortunately, there is [Stackless Python](#), which has a completely redesigned interpreter loop that avoids the C stack.

### 3.12 Why can't lambda expressions contain statements?

Python lambda expressions cannot contain statements because Python's syntactic framework can't handle statements nested inside expressions. However, in Python, this is not a serious problem. Unlike lambda forms in other languages, where they add functionality, Python lambdas are only a shorthand notation if you're too lazy to define a function.

Functions are already first class objects in Python, and can be declared in a local scope. Therefore the only advantage of using a lambda instead of a locally defined function is that you don't need to invent a name for the function – but that's just a local variable to which the function object (which is exactly the same type of object that a lambda expression yields) is assigned!

### 3.13 Can Python be compiled to machine code, C or some other language?

[Cython](#) compiles a modified version of Python with optional annotations into C extensions. [Nuitka](#) is an up-and-coming compiler of Python into C++ code, aiming to support the full Python language.

### 3.14 How does Python manage memory?

The details of Python memory management depend on the implementation. The standard implementation of Python, [CPython](#), uses reference counting to detect inaccessible objects, and another mechanism to collect reference cycles, periodically executing a cycle detection algorithm which looks for inaccessible cycles and deletes the objects involved. The `gc` module provides functions to perform a garbage collection, obtain debugging statistics, and tune the collector's parameters.

Other implementations (such as [Jython](#) or [PyPy](#)), however, can rely on a different mechanism such as a full-blown garbage collector. This difference can cause some subtle porting problems if your Python code depends on the behavior of the reference counting implementation.

In some Python implementations, the following code (which is fine in CPython) will probably run out of file descriptors:

```
for file in very_long_list_of_files:
    f = open(file)
    c = f.read(1)
```

Indeed, using CPython's reference counting and destructor scheme, each new assignment to `f` closes the previous file. With a traditional GC, however, those file objects will only get collected (and closed) at varying and possibly long intervals.

If you want to write code that will work with any Python implementation, you should explicitly close the file or use the `with` statement; this will work regardless of memory management scheme:

```
for file in very_long_list_of_files:
    with open(file) as f:
        c = f.read(1)
```

### 3.15 Why doesn't CPython use a more traditional garbage collection scheme?

For one thing, this is not a C standard feature and hence it's not portable. (Yes, we know about the Boehm GC library. It has bits of assembler code for *most* common platforms, not for all of them, and although it is mostly transparent, it isn't completely transparent; patches are required to get Python to work with it.)

Traditional GC also becomes a problem when Python is embedded into other applications. While in a standalone Python it's fine to replace the standard `malloc()` and `free()` with versions provided by the GC library, an application embedding Python may want to have its *own* substitute for `malloc()` and `free()`, and may not want Python's. Right now, CPython works with anything that implements `malloc()` and `free()` properly.

### 3.16 Why isn't all memory freed when CPython exits?

Objects referenced from the global namespaces of Python modules are not always deallocated when Python exits. This may happen if there are circular references. There are also certain bits of memory that are allocated by the C library that are impossible to free (e.g. a tool like Purify will complain about these). Python is, however, aggressive about cleaning up memory on exit and does try to destroy every single object.

If you want to force Python to delete certain things on deallocation use the `atexit` module to run a function that will force those deletions.

### 3.17 Why are there separate tuple and list data types?

Lists and tuples, while similar in many respects, are generally used in fundamentally different ways. Tuples can be thought of as being similar to Pascal records or C structs; they're small collections of related data which may be of different types which are operated on as a group. For example, a Cartesian coordinate is appropriately represented as a tuple of two or three numbers.

Lists, on the other hand, are more like arrays in other languages. They tend to hold a varying number of objects all of which have the same type and which are operated on one-by-one. For example, `os.listdir('.')` returns a list of strings representing the files in the current directory. Functions which operate on this output would generally not break if you added another file or two to the directory.

Tuples are immutable, meaning that once a tuple has been created, you can't replace any of its elements with a new value. Lists are mutable, meaning that you can always change a list's elements. Only immutable elements can be used as dictionary keys, and hence only tuples and not lists can be used as keys.

### 3.18 How are lists implemented in CPython?

CPython's lists are really variable-length arrays, not Lisp-style linked lists. The implementation uses a contiguous array of references to other objects, and keeps a pointer to this array and the array's length in a list head structure.

This makes indexing a list `a[i]` an operation whose cost is independent of the size of the list or the value of the index.

When items are appended or inserted, the array of references is resized. Some cleverness is applied to improve the performance of appending items repeatedly; when the array must be grown, some extra space is allocated so the next few times don't require an actual resize.

### 3.19 How are dictionaries implemented in CPython?

CPython's dictionaries are implemented as resizable hash tables. Compared to B-trees, this gives better performance for lookup (the most common operation by far) under most circumstances, and the implementation is simpler.

Dictionaries work by computing a hash code for each key stored in the dictionary using the `hash()` built-in function. The hash code varies widely depending on the key and a per-process seed; for example, "Python" could hash to -539294296 while "python", a string that differs by a single bit, could hash to 1142331976. The hash code is then used to calculate a location in an internal array where the value will be stored. Assuming that you're storing keys that all have different hash values, this means that dictionaries take constant time –  $O(1)$ , in Big-O notation – to retrieve a key.

### 3.20 Why must dictionary keys be immutable?

The hash table implementation of dictionaries uses a hash value calculated from the key value to find the key. If the key were a mutable object, its value could change, and thus its hash could also change. But since whoever changes the key object can't tell that it was being used as a dictionary key, it can't move the entry around in the dictionary. Then, when you try to look up the same object in the dictionary it won't be found because its hash value is different. If you tried to look up the old value it wouldn't be found either, because the value of the object found in that hash bin would be different.

If you want a dictionary indexed with a list, simply convert the list to a tuple first; the function `tuple(L)` creates a tuple with the same entries as the list `L`. Tuples are immutable and can therefore be used as dictionary keys.

Some unacceptable solutions that have been proposed:

- Hash lists by their address (object ID). This doesn't work because if you construct a new list with the same value it won't be found; e.g.:

```
mydict = {[1, 2]: '12'}
print(mydict[[1, 2]])
```

would raise a `KeyError` exception because the id of the `[1, 2]` used in the second line differs from that in the first line. In other words, dictionary keys should be compared using `==`, not using `is`.

- Make a copy when using a list as a key. This doesn't work because the list, being a mutable object, could contain a reference to itself, and then the copying code would run into an infinite loop.
- Allow lists as keys but tell the user not to modify them. This would allow a class of hard-to-track bugs in programs when you forgot or modified a list by accident. It also invalidates an important invariant of dictionaries: every value in `d.keys()` is usable as a key of the dictionary.
- Mark lists as read-only once they are used as a dictionary key. The problem is that it's not just the top-level object that could change its value; you could use a tuple containing a list as a key. Entering anything as a key into a dictionary would require marking all objects reachable from there as read-only – and again, self-referential objects could cause an infinite loop.

There is a trick to get around this if you need to, but use it at your own risk: You can wrap a mutable structure inside a class instance which has both a `__eq__()` and a `__hash__()` method. You must then make sure that the hash value for all such wrapper objects that reside in a dictionary (or other hash based structure), remain fixed while the object is in the dictionary (or other structure).

```
class ListWrapper:
    def __init__(self, the_list):
        self.the_list = the_list

    def __eq__(self, other):
        return self.the_list == other.the_list

    def __hash__(self):
        l = self.the_list
        result = 98767 - len(l)*555
        for i, el in enumerate(l):
            try:
                result = result + (hash(el) % 9999999) * 1001 + i
            except Exception:
                result = (result % 7777777) + i * 333
        return result
```

Note that the hash computation is complicated by the possibility that some members of the list may be unhashable and also by the possibility of arithmetic overflow.

Furthermore it must always be the case that if `o1 == o2` (ie `o1.__eq__(o2)` is True) then `hash(o1) == hash(o2)` (ie, `o1.__hash__() == o2.__hash__()`), regardless of whether the object is in a dictionary or not. If you fail to meet these restrictions dictionaries and other hash based structures will misbehave.

In the case of `ListWrapper`, whenever the wrapper object is in a dictionary the wrapped list must not change to avoid anomalies. Don't do this unless you are prepared to think hard about the requirements and the consequences of not meeting them correctly. Consider yourself warned.

## 3.21 Why doesn't `list.sort()` return the sorted list?

In situations where performance matters, making a copy of the list just to sort it would be wasteful. Therefore, `list.sort()` sorts the list in place. In order to remind you of that fact, it does not return the sorted list. This way, you won't be fooled into accidentally overwriting a list when you need a sorted copy but also need to keep the unsorted version around.

If you want to return a new list, use the built-in `sorted()` function instead. This function creates a new list from a provided iterable, sorts it and returns it. For example, here's how to iterate over the keys of a dictionary in sorted order:

```
for key in sorted(mydict):
    ... # do whatever with mydict[key]...
```

## 3.22 How do you specify and enforce an interface spec in Python?

An interface specification for a module as provided by languages such as C++ and Java describes the prototypes for the methods and functions of the module. Many feel that compile-time enforcement of interface specifications helps in the construction of large programs.

Python 2.6 adds an `abc` module that lets you define Abstract Base Classes (ABCs). You can then use `isinstance()` and `issubclass()` to check whether an instance or a class implements a particular ABC. The `collections.abc` module defines a set of useful ABCs such as `Iterable`, `Container`, and `MutableMapping`.



For Python, many of the advantages of interface specifications can be obtained by an appropriate test discipline for components.

A good test suite for a module can both provide a regression test and serve as a module interface specification and a set of examples. Many Python modules can be run as a script to provide a simple “self test.” Even modules which use complex external interfaces can often be tested in isolation using trivial “stub” emulations of the external interface. The `doctest` and `unittest` modules or third-party test frameworks can be used to construct exhaustive test suites that exercise every line of code in a module.

An appropriate testing discipline can help build large complex applications in Python as well as having interface specifications would. In fact, it can be better because an interface specification cannot test certain properties of a program. For example, the `append()` method is expected to add new elements to the end of some internal list; an interface specification cannot test that your `append()` implementation will actually do this correctly, but it’s trivial to check this property in a test suite.

Writing test suites is very helpful, and you might want to design your code to make it easily tested. One increasingly popular technique, test-driven development, calls for writing parts of the test suite first, before you write any of the actual code. Of course Python allows you to be sloppy and not write test cases at all.

### 3.23 Why is there no goto?

In the 1970s people realized that unrestricted `goto` could lead to messy “spaghetti” code that was hard to understand and revise. In a high-level language, it is also unneeded as long as there are ways to branch (in Python, with `if` statements and `or`, `and`, and `if-else` expressions) and loop (with `while` and `for` statements, possibly containing `continue` and `break`).

One can also use exceptions to provide a “structured goto” that works even across function calls. Many feel that exceptions can conveniently emulate all reasonable uses of the “go” or “goto” constructs of C, Fortran, and other languages. For example:

```
class label(Exception): pass # declare a label

try:
    ...
    if condition: raise label() # goto label
    ...
except label: # where to goto
    pass
...
```

This doesn’t allow you to jump into the middle of a loop, but that’s usually considered an abuse of `goto` anyway. Use sparingly.

### 3.24 Why can’t raw strings (r-strings) end with a backslash?

More precisely, they can’t end with an odd number of backslashes: the unpaired backslash at the end escapes the closing quote character, leaving an unterminated string.

Raw strings were designed to ease creating input for processors (chiefly regular expression engines) that want to do their own backslash escape processing. Such processors consider an unmatched trailing backslash to be an error anyway, so raw strings disallow that. In return, they allow you to pass on the string quote character by escaping it with a backslash. These rules work well when r-strings are used for their intended purpose.

If you’re trying to build Windows pathnames, note that all Windows system calls accept forward slashes too:

```
f = open("/mydir/file.txt") # works fine!
```

If you’re trying to build a pathname for a DOS command, try e.g. one of

```
dir = r"\this\is\my\dos\dir" "\\ "  
dir = r"\this\is\my\dos\dir\ "[:-1]  
dir = "\\this\\is\\my\\dos\\dir\\"
```

## 3.25 Why doesn't Python have a “with” statement for attribute assignments?

Python has a ‘with’ statement that wraps the execution of a block, calling code on the entrance and exit from the block. Some languages have a construct that looks like this:

```
with obj:  
    a = 1                # equivalent to obj.a = 1  
    total = total + 1    # obj.total = obj.total + 1
```

In Python, such a construct would be ambiguous.

Other languages, such as Object Pascal, Delphi, and C++, use static types, so it's possible to know, in an unambiguous way, what member is being assigned to. This is the main point of static typing – the compiler *always* knows the scope of every variable at compile time.

Python uses dynamic types. It is impossible to know in advance which attribute will be referenced at runtime. Member attributes may be added or removed from objects on the fly. This makes it impossible to know, from a simple reading, what attribute is being referenced: a local one, a global one, or a member attribute?

For instance, take the following incomplete snippet:

```
def foo(a):  
    with a:  
        print(x)
```

The snippet assumes that “a” must have a member attribute called “x”. However, there is nothing in Python that tells the interpreter this. What should happen if “a” is, let us say, an integer? If there is a global variable named “x”, will it be used inside the with block? As you see, the dynamic nature of Python makes such choices much harder.

The primary benefit of “with” and similar language features (reduction of code volume) can, however, easily be achieved in Python by assignment. Instead of:

```
function(args).mydict[index][index].a = 21  
function(args).mydict[index][index].b = 42  
function(args).mydict[index][index].c = 63
```

write this:

```
ref = function(args).mydict[index][index]  
ref.a = 21  
ref.b = 42  
ref.c = 63
```

This also has the side-effect of increasing execution speed because name bindings are resolved at run-time in Python, and the second version only needs to perform the resolution once.

### 3.26 Why don't generators support the with statement?

For technical reasons, a generator used directly as a context manager would not work correctly. When, as is most common, a generator is used as an iterator run to completion, no closing is needed. When it is, wrap it as “`contextlib.closing(generator)`” in the ‘with’ statement.

### 3.27 Why are colons required for the if/while/def/class statements?

The colon is required primarily to enhance readability (one of the results of the experimental ABC language). Consider this:

```
if a == b
    print(a)
```

versus

```
if a == b:
    print(a)
```

Notice how the second one is slightly easier to read. Notice further how a colon sets off the example in this FAQ answer; it's a standard usage in English.

Another minor reason is that the colon makes it easier for editors with syntax highlighting; they can look for colons to decide when indentation needs to be increased instead of having to do a more elaborate parsing of the program text.

### 3.28 Why does Python allow commas at the end of lists and tuples?

Python lets you add a trailing comma at the end of lists, tuples, and dictionaries:

```
[1, 2, 3,]
('a', 'b', 'c',)
d = {
    "A": [1, 5],
    "B": [6, 7], # last trailing comma is optional but good style
}
```

There are several reasons to allow this.

When you have a literal value for a list, tuple, or dictionary spread across multiple lines, it's easier to add more elements because you don't have to remember to add a comma to the previous line. The lines can also be reordered without creating a syntax error.

Accidentally omitting the comma can lead to errors that are hard to diagnose. For example:

```
x = [
    "fee",
    "fie",
    "foo",
    "fum"
]
```

This list looks like it has four elements, but it actually contains three: “fee”, “fiefoo” and “fum”. Always adding the comma avoids this source of error.

Allowing the trailing comma may also make programmatic code generation easier.



## LIBRARY AND EXTENSION FAQ

### 4.1 General Library Questions

#### 4.1.1 How do I find a module or application to perform task X?

Check the Library Reference to see if there's a relevant standard library module. (Eventually you'll learn what's in the standard library and will be able to skip this step.)

For third-party packages, search the [Python Package Index](#) or try [Google](#) or another web search engine. Searching for "Python" plus a keyword or two for your topic of interest will usually find something helpful.

#### 4.1.2 Where is the `math.py` (`socket.py`, `regex.py`, etc.) source file?

If you can't find a source file for a module it may be a built-in or dynamically loaded module implemented in C, C++ or other compiled language. In this case you may not have the source file or it may be something like `mathmodule.c`, somewhere in a C source directory (not on the Python Path).

There are (at least) three kinds of modules in Python:

- 1) modules written in Python (`.py`);
- 2) modules written in C and dynamically loaded (`.dll`, `.pyd`, `.so`, `.sl`, etc);
- 3) modules written in C and linked with the interpreter; to get a list of these, type:

```
import sys
print(sys.builtin_module_names)
```

#### 4.1.3 How do I make a Python script executable on Unix?

You need to do two things: the script file's mode must be executable and the first line must begin with `#!` followed by the path of the Python interpreter.

The first is done by executing `chmod +x scriptfile` or perhaps `chmod 755 scriptfile`.

The second can be done in a number of ways. The most straightforward way is to write

```
#!/usr/local/bin/python
```

as the very first line of your file, using the pathname for where the Python interpreter is installed on your platform.

If you would like the script to be independent of where the Python interpreter lives, you can use the `env` program. Almost all Unix variants support the following, assuming the Python interpreter is in a directory on the user's `PATH`:

```
#!/usr/bin/env python
```

*Don't* do this for CGI scripts. The `PATH` variable for CGI scripts is often very minimal, so you need to use the actual absolute pathname of the interpreter.

Occasionally, a user's environment is so full that the `/usr/bin/env` program fails; or there's no `env` program at all. In that case, you can try the following hack (due to Alex Rezinsky):

```
#!/bin/sh
""" : """
exec python $0 ${1+"$@"}
"""
```

The minor disadvantage is that this defines the script's `__doc__` string. However, you can fix that by adding

```
__doc__ = """...Whatever..."""
```

### 4.1.4 Is there a `curses/termcap` package for Python?

For Unix variants: The standard Python source distribution comes with a `curses` module in the [Modules](#) subdirectory, though it's not compiled by default. (Note that this is not available in the Windows distribution – there is no `curses` module for Windows.)

The `curses` module supports basic `curses` features as well as many additional functions from `ncurses` and `SVSV` `curses` such as colour, alternative character set support, pads, and mouse support. This means the module isn't compatible with operating systems that only have BSD `curses`, but there don't seem to be any currently maintained OSes that fall into this category.

### 4.1.5 Is there an equivalent to C's `onexit()` in Python?

The `atexit` module provides a register function that is similar to C's `onexit()`.

### 4.1.6 Why don't my signal handlers work?

The most common problem is that the signal handler is declared with the wrong argument list. It is called as

```
handler(signum, frame)
```

so it should be declared with two parameters:

```
def handler(signum, frame):
    ...
```

## 4.2 Common tasks

### 4.2.1 How do I test a Python program or component?

Python comes with two testing frameworks. The `doctest` module finds examples in the docstrings for a module and runs them, comparing the output with the expected output given in the docstring.

The `unittest` module is a fancier testing framework modelled on Java and Smalltalk testing frameworks.

To make testing easier, you should use good modular design in your program. Your program should have almost all functionality encapsulated in either functions or class methods – and this sometimes has the surprising and delightful effect of making the program run faster (because local variable accesses are faster than global accesses). Furthermore the program should avoid depending on mutating global variables, since this makes testing much more difficult to do.

The “global main logic” of your program may be as simple as

```
if __name__ == "__main__":
    main_logic()
```

at the bottom of the main module of your program.

Once your program is organized as a tractable collection of function and class behaviours, you should write test functions that exercise the behaviours. A test suite that automates a sequence of tests can be associated with each module. This sounds like a lot of work, but since Python is so terse and flexible it's surprisingly easy. You can make coding much more pleasant and fun by writing your test functions in parallel with the "production code", since this makes it easy to find bugs and even design flaws earlier.

"Support modules" that are not intended to be the main module of a program may include a self-test of the module.

```
if __name__ == "__main__":
    self_test()
```

Even programs that interact with complex external interfaces may be tested when the external interfaces are unavailable by using "fake" interfaces implemented in Python.

## 4.2.2 How do I create documentation from doc strings?

The `pydoc` module can create HTML from the doc strings in your Python source code. An alternative for creating API documentation purely from docstrings is `epydoc`. `Sphinx` can also include docstring content.

## 4.2.3 How do I get a single keypress at a time?

For Unix variants there are several solutions. It's straightforward to do this using `curses`, but `curses` is a fairly large module to learn.

# 4.3 Threads

## 4.3.1 How do I program using threads?

Be sure to use the `threading` module and not the `_thread` module. The `threading` module builds convenient abstractions on top of the low-level primitives provided by the `_thread` module.

## 4.3.2 None of my threads seem to run: why?

As soon as the main thread exits, all threads are killed. Your main thread is running too quickly, giving the threads no time to do any work.

A simple fix is to add a sleep to the end of the program that's long enough for all the threads to finish:

```
import threading, time

def thread_task(name, n):
    for i in range(n):
        print(name, i)

for i in range(10):
    T = threading.Thread(target=thread_task, args=(str(i), i))
    T.start()

time.sleep(10) # <-----!)
```

But now (on many platforms) the threads don't run in parallel, but appear to run sequentially, one at a time! The reason is that the OS thread scheduler doesn't start a new thread until the previous thread is blocked.

A simple fix is to add a tiny sleep to the start of the run function:

```
def thread_task(name, n):
    time.sleep(0.001) # <-----!
    for i in range(n):
        print(name, i)

for i in range(10):
    T = threading.Thread(target=thread_task, args=(str(i), i))
    T.start()

time.sleep(10)
```

Instead of trying to guess a good delay value for `time.sleep()`, it's better to use some kind of semaphore mechanism. One idea is to use the `queue` module to create a queue object, let each thread append a token to the queue when it finishes, and let the main thread read as many tokens from the queue as there are threads.

### 4.3.3 How do I parcel out work among a bunch of worker threads?

The easiest way is to use the `concurrent.futures` module, especially the `ThreadPoolExecutor` class.

Or, if you want fine control over the dispatching algorithm, you can write your own logic manually. Use the `queue` module to create a queue containing a list of jobs. The `Queue` class maintains a list of objects and has a `.put(obj)` method that adds items to the queue and a `.get()` method to return them. The class will take care of the locking necessary to ensure that each job is handed out exactly once.

Here's a trivial example:

```
import threading, queue, time

# The worker thread gets jobs off the queue. When the queue is empty, it
# assumes there will be no more work and exits.
# (Realistically workers will run until terminated.)
def worker():
    print('Running worker')
    time.sleep(0.1)
    while True:
        try:
            arg = q.get(block=False)
        except queue.Empty:
            print('Worker', threading.current_thread(), end=' ')
            print('queue empty')
            break
        else:
            print('Worker', threading.current_thread(), end=' ')
            print('running with argument', arg)
            time.sleep(0.5)

# Create queue
q = queue.Queue()

# Start a pool of 5 workers
for i in range(5):
    t = threading.Thread(target=worker, name='worker %i' % (i+1))
    t.start()

# Begin adding work to the queue
for i in range(50):
    q.put(i)
```

(continues on next page)



(continued from previous page)

```
# Give threads time to run
print('Main thread sleeping')
time.sleep(5)
```

When run, this will produce the following output:

```
Running worker
Running worker
Running worker
Running worker
Running worker
Main thread sleeping
Worker <Thread(worker 1, started 130283832797456)> running with argument 0
Worker <Thread(worker 2, started 130283824404752)> running with argument 1
Worker <Thread(worker 3, started 130283816012048)> running with argument 2
Worker <Thread(worker 4, started 130283807619344)> running with argument 3
Worker <Thread(worker 5, started 130283799226640)> running with argument 4
Worker <Thread(worker 1, started 130283832797456)> running with argument 5
...
```

Consult the module's documentation for more details; the `Queue` class provides a featureful interface.

#### 4.3.4 What kinds of global value mutation are thread-safe?

A *global interpreter lock* (GIL) is used internally to ensure that only one thread runs in the Python VM at a time. In general, Python offers to switch among threads only between bytecode instructions; how frequently it switches can be set via `sys.setswitchinterval()`. Each bytecode instruction and therefore all the C implementation code reached from each instruction is therefore atomic from the point of view of a Python program.

In theory, this means an exact accounting requires an exact understanding of the PVM bytecode implementation. In practice, it means that operations on shared variables of built-in data types (ints, lists, dicts, etc) that “look atomic” really are.

For example, the following operations are all atomic (L, L1, L2 are lists, D, D1, D2 are dicts, x, y are objects, i, j are ints):

```
L.append(x)
L1.extend(L2)
x = L[i]
x = L.pop()
L1[i:j] = L2
L.sort()
x = y
x.field = y
D[x] = y
D1.update(D2)
D.keys()
```

These aren't:

```
i = i+1
L.append(L[-1])
L[i] = L[j]
D[x] = D[x] + 1
```

Operations that replace other objects may invoke those other objects' `__del__()` method when their reference count reaches zero, and that can affect things. This is especially true for the mass updates to dictionaries and lists. When in doubt, use a mutex!

### 4.3.5 Can't we get rid of the Global Interpreter Lock?

The *global interpreter lock* (GIL) is often seen as a hindrance to Python's deployment on high-end multiprocessor server machines, because a multi-threaded Python program effectively only uses one CPU, due to the insistence that (almost) all Python code can only run while the GIL is held.

Back in the days of Python 1.5, Greg Stein actually implemented a comprehensive patch set (the "free threading" patches) that removed the GIL and replaced it with fine-grained locking. Adam Olsen recently did a similar experiment in his `python-safethread` project. Unfortunately, both experiments exhibited a sharp drop in single-thread performance (at least 30% slower), due to the amount of fine-grained locking necessary to compensate for the removal of the GIL.

This doesn't mean that you can't make good use of Python on multi-CPU machines! You just have to be creative with dividing the work up between multiple *processes* rather than multiple *threads*. The `ProcessPoolExecutor` class in the new `concurrent.futures` module provides an easy way of doing so; the `multiprocessing` module provides a lower-level API in case you want more control over dispatching of tasks.

Judicious use of C extensions will also help; if you use a C extension to perform a time-consuming task, the extension can release the GIL while the thread of execution is in the C code and allow other threads to get some work done. Some standard library modules such as `zlib` and `hashlib` already do this.

It has been suggested that the GIL should be a per-interpreter-state lock rather than truly global; interpreters then wouldn't be able to share objects. Unfortunately, this isn't likely to happen either. It would be a tremendous amount of work, because many object implementations currently have global state. For example, small integers and short strings are cached; these caches would have to be moved to the interpreter state. Other object types have their own free list; these free lists would have to be moved to the interpreter state. And so on.

And I doubt that it can even be done in finite time, because the same problem exists for 3rd party extensions. It is likely that 3rd party extensions are being written at a faster rate than you can convert them to store all their global state in the interpreter state.

And finally, once you have multiple interpreters not sharing any state, what have you gained over running each interpreter in a separate process?

## 4.4 Input and Output

### 4.4.1 How do I delete a file? (And other file questions...)

Use `os.remove(filename)` or `os.unlink(filename)`; for documentation, see the `os` module. The two functions are identical; `unlink()` is simply the name of the Unix system call for this function.

To remove a directory, use `os.rmdir()`; use `os.mkdir()` to create one. `os.makedirs(path)` will create any intermediate directories in `path` that don't exist. `os.removedirs(path)` will remove intermediate directories as long as they're empty; if you want to delete an entire directory tree and its contents, use `shutil.rmtree()`.

To rename a file, use `os.rename(old_path, new_path)`.

To truncate a file, open it using `f = open(filename, "rb+")`, and use `f.truncate(offset)`; `offset` defaults to the current seek position. There's also `os.ftruncate(fd, offset)` for files opened with `os.open()`, where `fd` is the file descriptor (a small integer).

The `shutil` module also contains a number of functions to work on files including `copyfile()`, `copytree()`, and `rmtree()`.

### 4.4.2 How do I copy a file?

The `shutil` module contains a `copyfile()` function. Note that on Windows NTFS volumes, it does not copy *alternate data streams* nor *resource forks* on macOS HFS+ volumes, though both are now rarely used. It also doesn't copy file permissions and metadata, though using `shutil.copy2()` instead will preserve most (though not all) of it.

### 4.4.3 How do I read (or write) binary data?

To read or write complex binary data formats, it's best to use the `struct` module. It allows you to take a string containing binary data (usually numbers) and convert it to Python objects; and vice versa.

For example, the following code reads two 2-byte integers and one 4-byte integer in big-endian format from a file:

```
import struct

with open(filename, "rb") as f:
    s = f.read(8)
    x, y, z = struct.unpack(">hhl", s)
```

The `'>'` in the format string forces big-endian data; the letter `'h'` reads one “short integer” (2 bytes), and `'l'` reads one “long integer” (4 bytes) from the string.

For data that is more regular (e.g. a homogeneous list of ints or floats), you can also use the `array` module.

---

**Note:** To read and write binary data, it is mandatory to open the file in binary mode (here, passing `"rb"` to `open()`). If you use `"r"` instead (the default), the file will be open in text mode and `f.read()` will return `str` objects rather than `bytes` objects.

---

### 4.4.4 I can't seem to use `os.read()` on a pipe created with `os.popen()`; why?

`os.read()` is a low-level function which takes a file descriptor, a small integer representing the opened file. `os.popen()` creates a high-level file object, the same type returned by the built-in `open()` function. Thus, to read *n* bytes from a pipe *p* created with `os.popen()`, you need to use `p.read(n)`.

### 4.4.5 How do I access the serial (RS232) port?

For Win32, OSX, Linux, BSD, Jython, IronPython:

<https://pypi.org/project/pyserial/>

For Unix, see a Usenet post by Mitch Chapman:

<https://groups.google.com/groups?selm=34A04430.CF9@ohioee.com>

### 4.4.6 Why doesn't closing `sys.stdout` (`stdin`, `stderr`) really close it?

Python *file objects* are a high-level layer of abstraction on low-level C file descriptors.

For most file objects you create in Python via the built-in `open()` function, `f.close()` marks the Python file object as being closed from Python's point of view, and also arranges to close the underlying C file descriptor. This also happens automatically in `f`'s destructor, when `f` becomes garbage.

But `stdin`, `stdout` and `stderr` are treated specially by Python, because of the special status also given to them by C. Running `sys.stdout.close()` marks the Python-level file object as being closed, but does *not* close the associated C file descriptor.

To close the underlying C file descriptor for one of these three, you should first be sure that's what you really want to do (e.g., you may confuse extension modules trying to do I/O). If it is, use `os.close()`:

```
os.close(stdin.fileno())
os.close(stdout.fileno())
os.close(stderr.fileno())
```

Or you can use the numeric constants 0, 1 and 2, respectively.

## 4.5 Network/Internet Programming

### 4.5.1 What WWW tools are there for Python?

See the chapters titled `internet` and `netdata` in the Library Reference Manual. Python has many modules that will help you build server-side and client-side web systems.

A summary of available frameworks is maintained by Paul Boddie at <https://wiki.python.org/moin/WebProgramming>.

Cameron Laird maintains a useful set of pages about Python web technologies at [https://web.archive.org/web/20210224183619/http://phaseit.net/claird/comp.lang.python/web\\_python](https://web.archive.org/web/20210224183619/http://phaseit.net/claird/comp.lang.python/web_python).

### 4.5.2 How can I mimic CGI form submission (METHOD=POST)?

I would like to retrieve web pages that are the result of POSTing a form. Is there existing code that would let me do this easily?

Yes. Here's a simple example that uses `urllib.request`:

```
#!/usr/local/bin/python

import urllib.request

# build the query string
qs = "First=Josephine&MI=Q&Last=Public"

# connect and send the server a path
req = urllib.request.urlopen('http://www.some-server.out-there'
                             '/cgi-bin/some-cgi-script', data=qs)

with req:
    msg, hdrs = req.read(), req.info()
```

Note that in general for percent-encoded POST operations, query strings must be quoted using `urllib.parse.urlencode()`. For example, to send `name=Guy Steele, Jr.`:

```
>>> import urllib.parse
>>> urllib.parse.urlencode({'name': 'Guy Steele, Jr.'})
'name=Guy+Steele%2C+Jr.'
```

**See also:**

`urllib-howto` for extensive examples.

### 4.5.3 What module should I use to help with generating HTML?

You can find a collection of useful links on the [Web Programming wiki page](#).

### 4.5.4 How do I send mail from a Python script?

Use the standard library module `smtplib`.

Here's a very simple interactive mail sender that uses it. This method will work on any host that supports an SMTP listener.

```
import sys, smtplib

fromaddr = input("From: ")
toaddrs = input("To: ").split(',')
print("Enter message, end with ^D:")
msg = ''
while True:
    line = sys.stdin.readline()
    if not line:
        break
    msg += line

# The actual mail send
server = smtplib.SMTP('localhost')
server.sendmail(fromaddr, toaddrs, msg)
server.quit()
```

A Unix-only alternative uses `sendmail`. The location of the `sendmail` program varies between systems; sometimes it is `/usr/lib/sendmail`, sometimes `/usr/sbin/sendmail`. The `sendmail` manual page will help you out. Here's some sample code:

```
import os

SENDMAIL = "/usr/sbin/sendmail" # sendmail location
p = os.popen("%s -t -i" % SENDMAIL, "w")
p.write("To: receiver@example.com\n")
p.write("Subject: test\n")
p.write("\n") # blank line separating headers from body
p.write("Some text\n")
p.write("some more text\n")
sts = p.close()
if sts != 0:
    print("Sendmail exit status", sts)
```

### 4.5.5 How do I avoid blocking in the `connect()` method of a socket?

The `select` module is commonly used to help with asynchronous I/O on sockets.

To prevent the TCP connect from blocking, you can set the socket to non-blocking mode. Then when you do the `socket.connect()`, you will either connect immediately (unlikely) or get an exception that contains the error number as `.errno`. `errno.EINPROGRESS` indicates that the connection is in progress, but hasn't finished yet. Different OSes will return different values, so you're going to have to check what's returned on your system.

You can use the `socket.connect_ex()` method to avoid creating an exception. It will just return the `errno` value. To poll, you can call `socket.connect_ex()` again later – 0 or `errno.EISCONN` indicate that you're connected – or you can pass this socket to `select.select()` to check if it's writable.

---

**Note:** The `asyncio` module provides a general purpose single-threaded and concurrent asynchronous library,

which can be used for writing non-blocking network code. The third-party [Twisted](#) library is a popular and feature-rich alternative.

---

## 4.6 Databases

### 4.6.1 Are there any interfaces to database packages in Python?

Yes.

Interfaces to disk-based hashes such as DBM and GDBM are also included with standard Python. There is also the `sqlite3` module, which provides a lightweight disk-based relational database.

Support for most relational databases is available. See the [DatabaseProgramming wiki page](#) for details.

### 4.6.2 How do you implement persistent objects in Python?

The `pickle` library module solves this in a very general way (though you still can't store things like open files, sockets or windows), and the `shelve` library module uses pickle and (g)dbm to create persistent mappings containing arbitrary Python objects.

## 4.7 Mathematics and Numerics

### 4.7.1 How do I generate random numbers in Python?

The standard module `random` implements a random number generator. Usage is simple:

```
import random
random.random()
```

This returns a random floating point number in the range [0, 1).

There are also many other specialized generators in this module, such as:

- `randrange(a, b)` chooses an integer in the range [a, b).
- `uniform(a, b)` chooses a floating point number in the range [a, b).
- `normalvariate(mean, sdev)` samples the normal (Gaussian) distribution.

Some higher-level functions operate on sequences directly, such as:

- `choice(S)` chooses a random element from a given sequence.
- `shuffle(L)` shuffles a list in-place, i.e. permutes it randomly.

There's also a `Random` class you can instantiate to create independent multiple random number generators.

## EXTENDING/EMBEDDING FAQ

### 5.1 Can I create my own functions in C?

Yes, you can create built-in modules containing functions, variables, exceptions and even new types in C. This is explained in the document [extending-index](#).

Most intermediate or advanced Python books will also cover this topic.

### 5.2 Can I create my own functions in C++?

Yes, using the C compatibility features found in C++. Place `extern "C" { ... }` around the Python include files and put `extern "C"` before each function that is going to be called by the Python interpreter. Global or static C++ objects with constructors are probably not a good idea.

### 5.3 Writing C is hard; are there any alternatives?

There are a number of alternatives to writing your own C extensions, depending on what you're trying to do.

[Cython](#) and its relative [Pyrex](#) are compilers that accept a slightly modified form of Python and generate the corresponding C code. Cython and Pyrex make it possible to write an extension without having to learn Python's C API.

If you need to interface to some C or C++ library for which no Python extension currently exists, you can try wrapping the library's data types and functions with a tool such as [SWIG](#). [SIP](#), [CXX Boost](#), or [Weave](#) are also alternatives for wrapping C++ libraries.

### 5.4 How can I execute arbitrary Python statements from C?

The highest-level function to do this is `PyRun_SimpleString()` which takes a single string argument to be executed in the context of the module `__main__` and returns 0 for success and -1 when an exception occurred (including `SyntaxError`). If you want more control, use `PyRun_String()`; see the source for `PyRun_SimpleString()` in `Python/pythonrun.c`.

## 5.5 How can I evaluate an arbitrary Python expression from C?

Call the function `PyRun_String()` from the previous question with the start symbol `Py_eval_input`; it parses an expression, evaluates it and returns its value.

## 5.6 How do I extract C values from a Python object?

That depends on the object's type. If it's a tuple, `PyTuple_Size()` returns its length and `PyTuple_GetItem()` returns the item at a specified index. Lists have similar functions, `PyList_Size()` and `PyList_GetItem()`.

For bytes, `PyBytes_Size()` returns its length and `PyBytes_AsStringAndSize()` provides a pointer to its value and its length. Note that Python bytes objects may contain null bytes so C's `strlen()` should not be used.

To test the type of an object, first make sure it isn't `NULL`, and then use `PyBytes_Check()`, `PyTuple_Check()`, `PyList_Check()`, etc.

There is also a high-level API to Python objects which is provided by the so-called 'abstract' interface – read `Include/abstract.h` for further details. It allows interfacing with any kind of Python sequence using calls like `PySequence_Length()`, `PySequence_GetItem()`, etc. as well as many other useful protocols such as numbers (`PyNumber_Index()` et al.) and mappings in the `PyMapping` APIs.

## 5.7 How do I use `Py_BuildValue()` to create a tuple of arbitrary length?

You can't. Use `PyTuple_Pack()` instead.

## 5.8 How do I call an object's method from C?

The `PyObject_CallMethod()` function can be used to call an arbitrary method of an object. The parameters are the object, the name of the method to call, a format string like that used with `Py_BuildValue()`, and the argument values:

```
PyObject *
PyObject_CallMethod(PyObject *object, const char *method_name,
                    const char *arg_format, ...);
```

This works for any object that has methods – whether built-in or user-defined. You are responsible for eventually `Py_DECREF()` 'ing the return value.

To call, e.g., a file object's "seek" method with arguments 10, 0 (assuming the file object pointer is "f"):

```
res = PyObject_CallMethod(f, "seek", "(ii)", 10, 0);
if (res == NULL) {
    ... an exception occurred ...
}
else {
    Py_DECREF(res);
}
```

Note that since `PyObject_CallObject()` *always* wants a tuple for the argument list, to call a function without arguments, pass "()" for the format, and to call a function with one argument, surround the argument in parentheses, e.g. "(i)".



## 5.9 How do I catch the output from `PyErr_Print()` (or anything that prints to `stdout/stderr`)?

In Python code, define an object that supports the `write()` method. Assign this object to `sys.stdout` and `sys.stderr`. Call `print_error`, or just allow the standard traceback mechanism to work. Then, the output will go wherever your `write()` method sends it.

The easiest way to do this is to use the `io.StringIO` class:

```
>>> import io, sys
>>> sys.stdout = io.StringIO()
>>> print('foo')
>>> print('hello world!')
>>> sys.stderr.write(sys.stdout.getvalue())
foo
hello world!
```

A custom object to do the same would look like this:

```
>>> import io, sys
>>> class StdoutCatcher(io.TextIOBase):
...     def __init__(self):
...         self.data = []
...     def write(self, stuff):
...         self.data.append(stuff)
...
>>> import sys
>>> sys.stdout = StdoutCatcher()
>>> print('foo')
>>> print('hello world!')
>>> sys.stderr.write(''.join(sys.stdout.data))
foo
hello world!
```

## 5.10 How do I access a module written in Python from C?

You can get a pointer to the module object as follows:

```
module = PyImport_ImportModule("<modulename>");
```

If the module hasn't been imported yet (i.e. it is not yet present in `sys.modules`), this initializes the module; otherwise it simply returns the value of `sys.modules["<modulename>"]`. Note that it doesn't enter the module into any namespace – it only ensures it has been initialized and is stored in `sys.modules`.

You can then access the module's attributes (i.e. any name defined in the module) as follows:

```
attr = PyObject_GetAttrString(module, "<attrname>");
```

Calling `PyObject_SetAttrString()` to assign to variables in the module also works.

## 5.11 How do I interface to C++ objects from Python?

Depending on your requirements, there are many approaches. To do this manually, begin by reading the “Extending and Embedding” document. Realize that for the Python run-time system, there isn’t a whole lot of difference between C and C++ – so the strategy of building a new Python type around a C structure (pointer) type will also work for C++ objects.

For C++ libraries, see *Writing C is hard; are there any alternatives?*.

## 5.12 I added a module using the Setup file and the make fails; why?

Setup must end in a newline, if there is no newline there, the build process fails. (Fixing this requires some ugly shell script hackery, and this bug is so minor that it doesn’t seem worth the effort.)

## 5.13 How do I debug an extension?

When using GDB with dynamically loaded extensions, you can’t set a breakpoint in your extension until your extension is loaded.

In your `.gdbinit` file (or interactively), add the command:

```
br _PyImport_LoadDynamicModule
```

Then, when you run GDB:

```
$ gdb /local/bin/python
gdb) run myscript.py
gdb) continue # repeat until your extension is loaded
gdb) finish   # so that your extension is loaded
gdb) br myfunction.c:50
gdb) continue
```

## 5.14 I want to compile a Python module on my Linux system, but some files are missing. Why?

Most packaged versions of Python don’t include the `/usr/lib/python2.x/config/` directory, which contains various files required for compiling Python extensions.

For Red Hat, install the `python-devel` RPM to get the necessary files.

For Debian, run `apt-get install python-dev`.

## 5.15 How do I tell “incomplete input” from “invalid input”?

Sometimes you want to emulate the Python interactive interpreter’s behavior, where it gives you a continuation prompt when the input is incomplete (e.g. you typed the start of an “if” statement or you didn’t close your parentheses or triple string quotes), but it gives you a syntax error message immediately when the input is invalid.

In Python you can use the `codeop` module, which approximates the parser’s behavior sufficiently. IDLE uses this, for example.

The easiest way to do it in C is to call `PyRun_InteractiveLoop()` (perhaps in a separate thread) and let the Python interpreter handle the input for you. You can also set the `PyOS_ReadlineFunctionPointer()`

to point at your custom input function. See `Modules/readline.c` and `Parser/myreadline.c` for more hints.

## 5.16 How do I find undefined g++ symbols `__builtin_new` or `__pure_virtual`?

To dynamically load g++ extension modules, you must recompile Python, relink it using g++ (change `LINKCC` in the `Python Modules Makefile`), and link your extension module using g++ (e.g., `g++ -shared -o mymodule.so mymodule.o`).

## 5.17 Can I create an object class with some methods implemented in C and others in Python (e.g. through inheritance)?

Yes, you can inherit from built-in classes such as `int`, `list`, `dict`, etc.

The Boost Python Library (BPL, <https://www.boost.org/libs/python/doc/index.html>) provides a way of doing this from C++ (i.e. you can inherit from an extension class written in C++ using the BPL).



## PYTHON ON WINDOWS FAQ

### 6.1 How do I run a Python program under Windows?

This is not necessarily a straightforward question. If you are already familiar with running programs from the Windows command line then everything will seem obvious; otherwise, you might need a little more guidance.

Unless you use some sort of integrated development environment, you will end up *typing* Windows commands into what is referred to as a “Command prompt window”. Usually you can create such a window from your search bar by searching for `cmd`. You should be able to recognize when you have started such a window because you will see a Windows “command prompt”, which usually looks like this:

```
C:\>
```

The letter may be different, and there might be other things after it, so you might just as easily see something like:

```
D:\YourName\Projects\Python>
```

depending on how your computer has been set up and what else you have recently done with it. Once you have started such a window, you are well on the way to running Python programs.

You need to realize that your Python scripts have to be processed by another program called the Python *interpreter*. The interpreter reads your script, compiles it into bytecodes, and then executes the bytecodes to run your program. So, how do you arrange for the interpreter to handle your Python?

First, you need to make sure that your command window recognises the word “py” as an instruction to start the interpreter. If you have opened a command window, you should try entering the command `py` and hitting return:

```
C:\Users\YourName> py
```

You should then see something like:

```
Python 3.6.4 (v3.6.4:d48eceb, Dec 19 2017, 06:04:45) [MSC v.1900 32 bit (Intel)]  on win32
Type "help", "copyright", "credits" or "license" for more information.
>>>
```

You have started the interpreter in “interactive mode”. That means you can enter Python statements or expressions interactively and have them executed or evaluated while you wait. This is one of Python’s strongest features. Check it by entering a few expressions of your choice and seeing the results:

```
>>> print("Hello")
Hello
>>> "Hello" * 3
'HelloHelloHello'
```

Many people use the interactive mode as a convenient yet highly programmable calculator. When you want to end your interactive Python session, call the `exit()` function or hold the `Ctrl` key down while you enter a `Z`, then hit the “Enter” key to get back to your Windows command prompt.

You may also find that you have a Start-menu entry such as *Start ▶ Programs ▶ Python 3.x ▶ Python (command line)* that results in you seeing the `>>>` prompt in a new window. If so, the window will disappear after you call the `exit()` function or enter the `Ctrl-Z` character; Windows is running a single “python” command in the window, and closes it when you terminate the interpreter.

Now that we know the `py` command is recognized, you can give your Python script to it. You’ll have to give either an absolute or a relative path to the Python script. Let’s say your Python script is located in your desktop and is named `hello.py`, and your command prompt is nicely opened in your home directory so you’re seeing something similar to:

```
C:\Users\YourName>
```

So now you’ll ask the `py` command to give your script to Python by typing `py` followed by your script path:

```
C:\Users\YourName> py Desktop\hello.py
hello
```

## 6.2 How do I make Python scripts executable?

On Windows, the standard Python installer already associates the `.py` extension with a file type (Python.File) and gives that file type an open command that runs the interpreter (`D:\Program Files\Python\python.exe "%1" %*`). This is enough to make scripts executable from the command prompt as ‘foo.py’. If you’d rather be able to execute the script by simple typing ‘foo’ with no extension you need to add `.py` to the `PATHEXT` environment variable.

## 6.3 Why does Python sometimes take so long to start?

Usually Python starts very quickly on Windows, but occasionally there are bug reports that Python suddenly begins to take a long time to start up. This is made even more puzzling because Python will work fine on other Windows systems which appear to be configured identically.

The problem may be caused by a misconfiguration of virus checking software on the problem machine. Some virus scanners have been known to introduce startup overhead of two orders of magnitude when the scanner is configured to monitor all reads from the filesystem. Try checking the configuration of virus scanning software on your systems to ensure that they are indeed configured identically. McAfee, when configured to scan all file system read activity, is a particular offender.

## 6.4 How do I make an executable from a Python script?

See *How can I create a stand-alone binary from a Python script?* for a list of tools that can be used to make executables.

## 6.5 Is a `*.pyd` file the same as a DLL?

Yes, `.pyd` files are `dll`’s, but there are a few differences. If you have a `DLL` named `foo.pyd`, then it must have a function `PyInit_foo()`. You can then write Python “import foo”, and Python will search for `foo.pyd` (as well as `foo.py`, `foo.pyc`) and if it finds it, will attempt to call `PyInit_foo()` to initialize it. You do not link your `.exe` with `foo.lib`, as that would cause Windows to require the `DLL` to be present.

Note that the search path for `foo.pyd` is `PYTHONPATH`, not the same as the path that Windows uses to search for `foo.dll`. Also, `foo.pyd` need not be present to run your program, whereas if you linked your program with a `dll`, the `dll` is required. Of course, `foo.pyd` is required if you want to say `import foo`. In a `DLL`, linkage is declared in the source code with `__declspec(dllexport)`. In a `.pyd`, linkage is defined in a list of available functions.

## 6.6 How can I embed Python into a Windows application?

Embedding the Python interpreter in a Windows app can be summarized as follows:

1. Do **not** build Python into your .exe file directly. On Windows, Python must be a DLL to handle importing modules that are themselves DLL's. (This is the first key undocumented fact.) Instead, link to `pythonNN.dll`; it is typically installed in `C:\Windows\System`. *NN* is the Python version, a number such as "33" for Python 3.3.

You can link to Python in two different ways. Load-time linking means linking against `pythonNN.lib`, while run-time linking means linking against `pythonNN.dll`. (General note: `pythonNN.lib` is the so-called "import lib" corresponding to `pythonNN.dll`. It merely defines symbols for the linker.)

Run-time linking greatly simplifies link options; everything happens at run time. Your code must load `pythonNN.dll` using the Windows `LoadLibraryEx()` routine. The code must also use access routines and data in `pythonNN.dll` (that is, Python's C API's) using pointers obtained by the Windows `GetProcAddress()` routine. Macros can make using these pointers transparent to any C code that calls routines in Python's C API.

2. If you use SWIG, it is easy to create a Python "extension module" that will make the app's data and methods available to Python. SWIG will handle just about all the grungy details for you. The result is C code that you link *into* your .exe file (!) You do **not** have to create a DLL file, and this also simplifies linking.
3. SWIG will create an init function (a C function) whose name depends on the name of the extension module. For example, if the name of the module is `leo`, the init function will be called `initleo()`. If you use SWIG shadow classes, as you should, the init function will be called `initleoc()`. This initializes a mostly hidden helper class used by the shadow class.

The reason you can link the C code in step 2 into your .exe file is that calling the initialization function is equivalent to importing the module into Python! (This is the second key undocumented fact.)

4. In short, you can use the following code to initialize the Python interpreter with your extension module.

```
#include "python.h"
...
Py_Initialize(); // Initialize Python.
initmyAppc(); // Initialize (import) the helper class.
PyRun_SimpleString("import myApp"); // Import the shadow class.
```

5. There are two problems with Python's C API which will become apparent if you use a compiler other than MSVC, the compiler used to build `pythonNN.dll`.

Problem 1: The so-called "Very High Level" functions that take `FILE *` arguments will not work in a multi-compiler environment because each compiler's notion of a `struct FILE` will be different. From an implementation standpoint these are very low level functions.

Problem 2: SWIG generates the following code when generating wrappers to void functions:

```
Py_INCREF(Py_None);
_resultobj = Py_None;
return _resultobj;
```

Alas, `Py_None` is a macro that expands to a reference to a complex data structure called `_Py_NoneStruct` inside `pythonNN.dll`. Again, this code will fail in a multi-compiler environment. Replace such code by:

```
return Py_BuildValue("");
```

It may be possible to use SWIG's `%typemap` command to make the change automatically, though I have not been able to get this to work (I'm a complete SWIG newbie).

6. Using a Python shell script to put up a Python interpreter window from inside your Windows app is not a good idea; the resulting window will be independent of your app's windowing system. Rather, you (or the `wxPythonWindow` class) should create a "native" interpreter window. It is easy to connect that window to the

Python interpreter. You can redirect Python's i/o to `_any_` object that supports read and write, so all you need is a Python object (defined in your extension module) that contains `read()` and `write()` methods.

## 6.7 How do I keep editors from inserting tabs into my Python source?

The FAQ does not recommend using tabs, and the Python style guide, [PEP 8](#), recommends 4 spaces for distributed Python code; this is also the Emacs python-mode default.

Under any editor, mixing tabs and spaces is a bad idea. MSVC is no different in this respect, and is easily configured to use spaces: Take *Tools* ▶ *Options* ▶ *Tabs*, and for file type “Default” set “Tab size” and “Indent size” to 4, and select the “Insert spaces” radio button.

Python raises `IndentationError` or `TabError` if mixed tabs and spaces are causing problems in leading whitespace. You may also run the `tabnanny` module to check a directory tree in batch mode.

## 6.8 How do I check for a keypress without blocking?

Use the `msvcrt` module. This is a standard Windows-specific extension module. It defines a function `kbhit()` which checks whether a keyboard hit is present, and `getch()` which gets one character without echoing it.

## 6.9 How do I solve the missing `api-ms-win-crt-runtime-l1-1-0.dll` error?

This can occur on Python 3.5 and later when using Windows 8.1 or earlier without all updates having been installed. First ensure your operating system is supported and is up to date, and if that does not resolve the issue, visit the [Microsoft support page](#) for guidance on manually installing the C Runtime update.



## GRAPHIC USER INTERFACE FAQ

### 7.1 General GUI Questions

### 7.2 What GUI toolkits exist for Python?

Standard builds of Python include an object-oriented interface to the Tcl/Tk widget set, called tkinter. This is probably the easiest to install (since it comes included with most [binary distributions](#) of Python) and use. For more info about Tk, including pointers to the source, see the [Tcl/Tk home page](#). Tcl/Tk is fully portable to the macOS, Windows, and Unix platforms.

Depending on what platform(s) you are aiming at, there are also several alternatives. A [list of cross-platform and platform-specific](#) GUI frameworks can be found on the python wiki.

### 7.3 Tkinter questions

#### 7.3.1 How do I freeze Tkinter applications?

Freeze is a tool to create stand-alone applications. When freezing Tkinter applications, the applications will not be truly stand-alone, as the application will still need the Tcl and Tk libraries.

One solution is to ship the application with the Tcl and Tk libraries, and point to them at run-time using the `TCL_LIBRARY` and `TK_LIBRARY` environment variables.

To get truly stand-alone applications, the Tcl scripts that form the library have to be integrated into the application as well. One tool supporting that is SAM (stand-alone modules), which is part of the Tix distribution (<https://tix.sourceforge.net/>).

Build Tix with SAM enabled, perform the appropriate call to `Tclsam_init()`, etc. inside Python's `Modules/tkappinit.c`, and link with `libtclsam` and `libtkjam` (you might include the Tix libraries as well).

#### 7.3.2 Can I have Tk events handled while waiting for I/O?

On platforms other than Windows, yes, and you don't even need threads! But you'll have to restructure your I/O code a bit. Tk has the equivalent of Xt's `XtAddInput()` call, which allows you to register a callback function which will be called from the Tk mainloop when I/O is possible on a file descriptor. See [tkinter-file-handlers](#).

### 7.3.3 I can't get key bindings to work in Tkinter: why?

An often-heard complaint is that event handlers bound to events with the `bind()` method don't get handled even when the appropriate key is pressed.

The most common cause is that the widget to which the binding applies doesn't have "keyboard focus". Check out the Tk documentation for the `focus` command. Usually a widget is given the keyboard focus by clicking in it (but not for labels; see the `takefocus` option).

## “WHY IS PYTHON INSTALLED ON MY COMPUTER?” FAQ

### 8.1 What is Python?

Python is a programming language. It's used for many different applications. It's used in some high schools and colleges as an introductory programming language because Python is easy to learn, but it's also used by professional software developers at places such as Google, NASA, and Lucasfilm Ltd.

If you wish to learn more about Python, start with the [Beginner's Guide to Python](#).

### 8.2 Why is Python installed on my machine?

If you find Python installed on your system but don't remember installing it, there are several possible ways it could have gotten there.

- Perhaps another user on the computer wanted to learn programming and installed it; you'll have to figure out who's been using the machine and might have installed it.
- A third-party application installed on the machine might have been written in Python and included a Python installation. There are many such applications, from GUI programs to network servers and administrative scripts.
- Some Windows machines also have Python installed. At this writing we're aware of computers from Hewlett-Packard and Compaq that include Python. Apparently some of HP/Compaq's administrative tools are written in Python.
- Many Unix-compatible operating systems, such as macOS and some Linux distributions, have Python installed by default; it's included in the base installation.

### 8.3 Can I delete Python?

That depends on where Python came from.

If someone installed it deliberately, you can remove it without hurting anything. On Windows, use the Add/Remove Programs icon in the Control Panel.

If Python was installed by a third-party application, you can also remove it, but that application will no longer work. You should use that application's uninstaller rather than removing Python directly.

If Python came with your operating system, removing it is not recommended. If you remove it, whatever tools were written in Python will no longer run, and some of them might be important to you. Reinstalling the whole system would then be required to fix things again.



## GLOSSARY

**>>>** The default Python prompt of the interactive shell. Often seen for code examples which can be executed interactively in the interpreter.

**...** Can refer to:

- The default Python prompt of the interactive shell when entering the code for an indented code block, when within a pair of matching left and right delimiters (parentheses, square brackets, curly braces or triple quotes), or after specifying a decorator.
- The `Ellipsis` built-in constant.

**2to3** A tool that tries to convert Python 2.x code to Python 3.x code by handling most of the incompatibilities which can be detected by parsing the source and traversing the parse tree.

2to3 is available in the standard library as `lib2to3`; a standalone entry point is provided as `Tools/scripts/2to3`. See 2to3-reference.

**abstract base class** Abstract base classes complement *duck-typing* by providing a way to define interfaces when other techniques like `hasattr()` would be clumsy or subtly wrong (for example with magic methods). ABCs introduce virtual subclasses, which are classes that don't inherit from a class but are still recognized by `isinstance()` and `issubclass()`; see the `abc` module documentation. Python comes with many built-in ABCs for data structures (in the `collections.abc` module), numbers (in the `numbers` module), streams (in the `io` module), import finders and loaders (in the `importlib.abc` module). You can create your own ABCs with the `abc` module.

**annotation** A label associated with a variable, a class attribute or a function parameter or return value, used by convention as a *type hint*.

Annotations of local variables cannot be accessed at runtime, but annotations of global variables, class attributes, and functions are stored in the `__annotations__` special attribute of modules, classes, and functions, respectively.

See *variable annotation*, *function annotation*, **PEP 484** and **PEP 526**, which describe this functionality. Also see *annotations-howto* for best practices on working with annotations.

**argument** A value passed to a *function* (or *method*) when calling the function. There are two kinds of argument:

- *keyword argument*: an argument preceded by an identifier (e.g. `name=`) in a function call or passed as a value in a dictionary preceded by `**`. For example, 3 and 5 are both keyword arguments in the following calls to `complex()`:

```
complex(real=3, imag=5)
complex(**{'real': 3, 'imag': 5})
```

- *positional argument*: an argument that is not a keyword argument. Positional arguments can appear at the beginning of an argument list and/or be passed as elements of an *iterable* preceded by `*`. For example, 3 and 5 are both positional arguments in the following calls:

```
complex(3, 5)
complex(*(3, 5))
```

Arguments are assigned to the named local variables in a function body. See the calls section for the rules governing this assignment. Syntactically, any expression can be used to represent an argument; the evaluated value is assigned to the local variable.

See also the [parameter](#) glossary entry, the FAQ question on [the difference between arguments and parameters](#), and [PEP 362](#).

**asynchronous context manager** An object which controls the environment seen in an `async with` statement by defining `__aenter__()` and `__aexit__()` methods. Introduced by [PEP 492](#).

**asynchronous generator** A function which returns an [asynchronous generator iterator](#). It looks like a coroutine function defined with `async def` except that it contains `yield` expressions for producing a series of values usable in an `async for` loop.

Usually refers to an asynchronous generator function, but may refer to an [asynchronous generator iterator](#) in some contexts. In cases where the intended meaning isn't clear, using the full terms avoids ambiguity.

An asynchronous generator function may contain `await` expressions as well as `async for`, and `async with` statements.

**asynchronous generator iterator** An object created by a [asynchronous generator](#) function.

This is an [asynchronous iterator](#) which when called using the `__anext__()` method returns an awaitable object which will execute the body of the asynchronous generator function until the next `yield` expression.

Each `yield` temporarily suspends processing, remembering the location execution state (including local variables and pending try-statements). When the [asynchronous generator iterator](#) effectively resumes with another awaitable returned by `__anext__()`, it picks up where it left off. See [PEP 492](#) and [PEP 525](#).

**asynchronous iterable** An object, that can be used in an `async for` statement. Must return an [asynchronous iterator](#) from its `__aiter__()` method. Introduced by [PEP 492](#).

**asynchronous iterator** An object that implements the `__aiter__()` and `__anext__()` methods. `__anext__` must return an [awaitable](#) object. `async for` resolves the awaitables returned by an asynchronous iterator's `__anext__()` method until it raises a `StopAsyncIteration` exception. Introduced by [PEP 492](#).

**attribute** A value associated with an object which is usually referenced by name using dotted expressions. For example, if an object *o* has an attribute *a* it would be referenced as *o.a*.

It is possible to give an object an attribute whose name is not an identifier as defined by identifiers, for example using `setattr()`, if the object allows it. Such an attribute will not be accessible using a dotted expression, and would instead need to be retrieved with `getattr()`.

**awaitable** An object that can be used in an `await` expression. Can be a [coroutine](#) or an object with an `__await__()` method. See also [PEP 492](#).

**BDFL** Benevolent Dictator For Life, a.k.a. [Guido van Rossum](#), Python's creator.

**binary file** A [file object](#) able to read and write [bytes-like objects](#). Examples of binary files are files opened in binary mode ('rb', 'wb' or 'rb+'), `sys.stdin.buffer`, `sys.stdout.buffer`, and instances of `io.BytesIO` and `gzip.GzipFile`.

See also [text file](#) for a file object able to read and write `str` objects.

**borrowed reference** In Python's C API, a borrowed reference is a reference to an object. It does not modify the object reference count. It becomes a dangling pointer if the object is destroyed. For example, a garbage collection can remove the last [strong reference](#) to the object and so destroy it.

Calling `Py_INCREF()` on the [borrowed reference](#) is recommended to convert it to a [strong reference](#) in-place, except when the object cannot be destroyed before the last usage of the borrowed reference. The `Py_NewRef()` function can be used to create a new [strong reference](#).

**bytes-like object** An object that supports the bufferobjects and can export a C-[contiguous](#) buffer. This includes all `bytes`, `bytearray`, and `array.array` objects, as well as many common `memoryview` objects. Bytes-like objects can be used for various operations that work with binary data; these include compression, saving to a binary file, and sending over a socket.

Some operations need the binary data to be mutable. The documentation often refers to these as “read-write bytes-like objects”. Example mutable buffer objects include `bytearray` and a `memoryview` of a `bytearray`. Other operations require the binary data to be stored in immutable objects (“read-only bytes-like objects”); examples of these include `bytes` and a `memoryview` of a `bytes` object.

**bytecode** Python source code is compiled into bytecode, the internal representation of a Python program in the CPython interpreter. The bytecode is also cached in `.pyc` files so that executing the same file is faster the second time (recompilation from source to bytecode can be avoided). This “intermediate language” is said to run on a *virtual machine* that executes the machine code corresponding to each bytecode. Do note that bytecodes are not expected to work between different Python virtual machines, nor to be stable between Python releases.

A list of bytecode instructions can be found in the documentation for the `dis` module.

**callable** A callable is an object that can be called, possibly with a set of arguments (see *argument*), with the following syntax:

```
callable(argument1, argument2, ...)
```

A *function*, and by extension a *method*, is a callable. An instance of a class that implements the `__call__()` method is also a callable.

**callback** A subroutine function which is passed as an argument to be executed at some point in the future.

**class** A template for creating user-defined objects. Class definitions normally contain method definitions which operate on instances of the class.

**class variable** A variable defined in a class and intended to be modified only at class level (i.e., not in an instance of the class).

**coercion** The implicit conversion of an instance of one type to another during an operation which involves two arguments of the same type. For example, `int(3.15)` converts the floating point number to the integer 3, but in `3+4.5`, each argument is of a different type (one `int`, one `float`), and both must be converted to the same type before they can be added or it will raise a `TypeError`. Without coercion, all arguments of even compatible types would have to be normalized to the same value by the programmer, e.g., `float(3)+4.5` rather than just `3+4.5`.

**complex number** An extension of the familiar real number system in which all numbers are expressed as a sum of a real part and an imaginary part. Imaginary numbers are real multiples of the imaginary unit (the square root of  $-1$ ), often written `i` in mathematics or `j` in engineering. Python has built-in support for complex numbers, which are written with this latter notation; the imaginary part is written with a `j` suffix, e.g., `3+1j`. To get access to complex equivalents of the `math` module, use `cmath`. Use of complex numbers is a fairly advanced mathematical feature. If you’re not aware of a need for them, it’s almost certain you can safely ignore them.

**context manager** An object which controls the environment seen in a `with` statement by defining `__enter__()` and `__exit__()` methods. See [PEP 343](#).

**context variable** A variable which can have different values depending on its context. This is similar to Thread-Local Storage in which each execution thread may have a different value for a variable. However, with context variables, there may be several contexts in one execution thread and the main usage for context variables is to keep track of variables in concurrent asynchronous tasks. See `contextvars`.

**contiguous** A buffer is considered contiguous exactly if it is either *C-contiguous* or *Fortran contiguous*. Zero-dimensional buffers are C and Fortran contiguous. In one-dimensional arrays, the items must be laid out in memory next to each other, in order of increasing indexes starting from zero. In multidimensional C-contiguous arrays, the last index varies the fastest when visiting items in order of memory address. However, in Fortran contiguous arrays, the first index varies the fastest.

**coroutine** Coroutines are a more generalized form of subroutines. Subroutines are entered at one point and exited at another point. Coroutines can be entered, exited, and resumed at many different points. They can be implemented with the `async def` statement. See also [PEP 492](#).

**coroutine function** A function which returns a *coroutine* object. A coroutine function may be defined with the `async def` statement, and may contain `await`, `async for`, and `async with` keywords. These were introduced by [PEP 492](#).

**CPython** The canonical implementation of the Python programming language, as distributed on [python.org](https://python.org). The term “CPython” is used when necessary to distinguish this implementation from others such as Jython or IronPython.

**decorator** A function returning another function, usually applied as a function transformation using the `@wrapper` syntax. Common examples for decorators are `classmethod()` and `staticmethod()`.

The decorator syntax is merely syntactic sugar, the following two function definitions are semantically equivalent:

```
def f(arg):
    ...
f = staticmethod(f)

@staticmethod
def f(arg):
    ...
```

The same concept exists for classes, but is less commonly used there. See the documentation for function definitions and class definitions for more about decorators.

**descriptor** Any object which defines the methods `__get__()`, `__set__()`, or `__delete__()`. When a class attribute is a descriptor, its special binding behavior is triggered upon attribute lookup. Normally, using `a.b` to get, set or delete an attribute looks up the object named `b` in the class dictionary for `a`, but if `b` is a descriptor, the respective descriptor method gets called. Understanding descriptors is a key to a deep understanding of Python because they are the basis for many features including functions, methods, properties, class methods, static methods, and reference to super classes.

For more information about descriptors’ methods, see [descriptors](#) or the [Descriptor How To Guide](#).

**dictionary** An associative array, where arbitrary keys are mapped to values. The keys can be any object with `__hash__()` and `__eq__()` methods. Called a hash in Perl.

**dictionary comprehension** A compact way to process all or part of the elements in an iterable and return a dictionary with the results. `results = {n: n ** 2 for n in range(10)}` generates a dictionary containing key `n` mapped to value `n ** 2`. See [comprehensions](#).

**dictionary view** The objects returned from `dict.keys()`, `dict.values()`, and `dict.items()` are called dictionary views. They provide a dynamic view on the dictionary’s entries, which means that when the dictionary changes, the view reflects these changes. To force the dictionary view to become a full list use `list(dictview)`. See [dict-views](#).

**docstring** A string literal which appears as the first expression in a class, function or module. While ignored when the suite is executed, it is recognized by the compiler and put into the `__doc__` attribute of the enclosing class, function or module. Since it is available via introspection, it is the canonical place for documentation of the object.

**duck-typing** A programming style which does not look at an object’s type to determine if it has the right interface; instead, the method or attribute is simply called or used (“If it looks like a duck and quacks like a duck, it must be a duck.”) By emphasizing interfaces rather than specific types, well-designed code improves its flexibility by allowing polymorphic substitution. Duck-typing avoids tests using `type()` or `isinstance()`. (Note, however, that duck-typing can be complemented with [abstract base classes](#).) Instead, it typically employs `hasattr()` tests or [EAFP](#) programming.

**EAFP** Easier to ask for forgiveness than permission. This common Python coding style assumes the existence of valid keys or attributes and catches exceptions if the assumption proves false. This clean and fast style is characterized by the presence of many `try` and `except` statements. The technique contrasts with the [LBYL](#) style common to many other languages such as C.

**expression** A piece of syntax which can be evaluated to some value. In other words, an expression is an accumulation of expression elements like literals, names, attribute access, operators or function calls which all return a value. In contrast to many other languages, not all language constructs are expressions. There are also [statements](#) which cannot be used as expressions, such as `while`. Assignments are also statements, not expressions.

**extension module** A module written in C or C++, using Python’s C API to interact with the core and with user code.



**f-string** String literals prefixed with 'f' or 'F' are commonly called “f-strings” which is short for formatted string literals. See also [PEP 498](#).

**file object** An object exposing a file-oriented API (with methods such as `read()` or `write()`) to an underlying resource. Depending on the way it was created, a file object can mediate access to a real on-disk file or to another type of storage or communication device (for example standard input/output, in-memory buffers, sockets, pipes, etc.). File objects are also called *file-like objects* or *streams*.

There are actually three categories of file objects: raw *binary files*, buffered *binary files* and *text files*. Their interfaces are defined in the `io` module. The canonical way to create a file object is by using the `open()` function.

**file-like object** A synonym for *file object*.

**filesystem encoding and error handler** Encoding and error handler used by Python to decode bytes from the operating system and encode Unicode to the operating system.

The filesystem encoding must guarantee to successfully decode all bytes below 128. If the file system encoding fails to provide this guarantee, API functions can raise `UnicodeError`.

The `sys.getfilesystemencoding()` and `sys.getfilesystemencodeerrors()` functions can be used to get the filesystem encoding and error handler.

The *filesystem encoding and error handler* are configured at Python startup by the `PyConfig_Read()` function: see `filesystem_encoding` and `filesystem_errors` members of `PyConfig`.

See also the *locale encoding*.

**finder** An object that tries to find the *loader* for a module that is being imported.

Since Python 3.3, there are two types of finder: *meta path finders* for use with `sys.meta_path`, and *path entry finders* for use with `sys.path_hooks`.

See [PEP 302](#), [PEP 420](#) and [PEP 451](#) for much more detail.

**floor division** Mathematical division that rounds down to nearest integer. The floor division operator is `//`. For example, the expression `11 // 4` evaluates to 2 in contrast to the `2.75` returned by float true division. Note that `(-11) // 4` is `-3` because that is `-2.75` rounded *downward*. See [PEP 238](#).

**function** A series of statements which returns some value to a caller. It can also be passed zero or more *arguments* which may be used in the execution of the body. See also *parameter*, *method*, and the function section.

**function annotation** An *annotation* of a function parameter or return value.

Function annotations are usually used for *type hints*: for example, this function is expected to take two `int` arguments and is also expected to have an `int` return value:

```
def sum_two_numbers(a: int, b: int) -> int:
    return a + b
```

Function annotation syntax is explained in section [function](#).

See *variable annotation* and [PEP 484](#), which describe this functionality. Also see [annotations-howto](#) for best practices on working with annotations.

**\_\_future\_\_** A future statement, from `__future__ import <feature>`, directs the compiler to compile the current module using syntax or semantics that will become standard in a future release of Python. The `__future__` module documents the possible values of *feature*. By importing this module and evaluating its variables, you can see when a new feature was first added to the language and when it will (or did) become the default:

```
>>> import __future__
>>> __future__.division
_Feature((2, 2, 0, 'alpha', 2), (3, 0, 0, 'alpha', 0), 8192)
```

**garbage collection** The process of freeing memory when it is not used anymore. Python performs garbage collection via reference counting and a cyclic garbage collector that is able to detect and break reference cycles. The garbage collector can be controlled using the `gc` module.

**generator** A function which returns a *generator iterator*. It looks like a normal function except that it contains `yield` expressions for producing a series of values usable in a for-loop or that can be retrieved one at a time with the `next()` function.

Usually refers to a generator function, but may refer to a *generator iterator* in some contexts. In cases where the intended meaning isn't clear, using the full terms avoids ambiguity.

**generator iterator** An object created by a *generator* function.

Each `yield` temporarily suspends processing, remembering the location execution state (including local variables and pending try-statements). When the *generator iterator* resumes, it picks up where it left off (in contrast to functions which start fresh on every invocation).

**generator expression** An expression that returns an iterator. It looks like a normal expression followed by a `for` clause defining a loop variable, range, and an optional `if` clause. The combined expression generates values for an enclosing function:

```
>>> sum(i*i for i in range(10))           # sum of squares 0, 1, 4, ... 81
285
```

**generic function** A function composed of multiple functions implementing the same operation for different types. Which implementation should be used during a call is determined by the dispatch algorithm.

See also the *single dispatch* glossary entry, the `functools.singledispatch()` decorator, and [PEP 443](#).

**generic type** A *type* that can be parameterized; typically a container class such as `list` or `dict`. Used for *type hints* and *annotations*.

For more details, see generic alias types, [PEP 483](#), [PEP 484](#), [PEP 585](#), and the `typing` module.

**GIL** See *global interpreter lock*.

**global interpreter lock** The mechanism used by the *CPython* interpreter to assure that only one thread executes Python *bytecode* at a time. This simplifies the CPython implementation by making the object model (including critical built-in types such as `dict`) implicitly safe against concurrent access. Locking the entire interpreter makes it easier for the interpreter to be multi-threaded, at the expense of much of the parallelism afforded by multi-processor machines.

However, some extension modules, either standard or third-party, are designed so as to release the GIL when doing computationally intensive tasks such as compression or hashing. Also, the GIL is always released when doing I/O.

Past efforts to create a “free-threaded” interpreter (one which locks shared data at a much finer granularity) have not been successful because performance suffered in the common single-processor case. It is believed that overcoming this performance issue would make the implementation much more complicated and therefore costlier to maintain.

**hash-based pyc** A bytecode cache file that uses the hash rather than the last-modified time of the corresponding source file to determine its validity. See `pyc`-invalidation.

**hashable** An object is *hashable* if it has a hash value which never changes during its lifetime (it needs a `__hash__()` method), and can be compared to other objects (it needs an `__eq__()` method). Hashable objects which compare equal must have the same hash value.

Hashability makes an object usable as a dictionary key and a set member, because these data structures use the hash value internally.

Most of Python's immutable built-in objects are hashable; mutable containers (such as lists or dictionaries) are not; immutable containers (such as tuples and frozensets) are only hashable if their elements are hashable. Objects which are instances of user-defined classes are hashable by default. They all compare unequal (except with themselves), and their hash value is derived from their `id()`.

**IDLE** An Integrated Development and Learning Environment for Python. `idle` is a basic editor and interpreter environment which ships with the standard distribution of Python.

**immutable** An object with a fixed value. Immutable objects include numbers, strings and tuples. Such an object cannot be altered. A new object has to be created if a different value has to be stored. They play an important role in places where a constant hash value is needed, for example as a key in a dictionary.

**import path** A list of locations (or *path entries*) that are searched by the *path based finder* for modules to import. During import, this list of locations usually comes from `sys.path`, but for subpackages it may also come from the parent package's `__path__` attribute.

**importing** The process by which Python code in one module is made available to Python code in another module.

**importer** An object that both finds and loads a module; both a *finder* and *loader* object.

**interactive** Python has an interactive interpreter which means you can enter statements and expressions at the interpreter prompt, immediately execute them and see their results. Just launch `python` with no arguments (possibly by selecting it from your computer's main menu). It is a very powerful way to test out new ideas or inspect modules and packages (remember `help(x)`).

**interpreted** Python is an interpreted language, as opposed to a compiled one, though the distinction can be blurry because of the presence of the bytecode compiler. This means that source files can be run directly without explicitly creating an executable which is then run. Interpreted languages typically have a shorter development/debug cycle than compiled ones, though their programs generally also run more slowly. See also *interactive*.

**interpreter shutdown** When asked to shut down, the Python interpreter enters a special phase where it gradually releases all allocated resources, such as modules and various critical internal structures. It also makes several calls to the *garbage collector*. This can trigger the execution of code in user-defined destructors or weakref callbacks. Code executed during the shutdown phase can encounter various exceptions as the resources it relies on may not function anymore (common examples are library modules or the warnings machinery).

The main reason for interpreter shutdown is that the `__main__` module or the script being run has finished executing.

**iterable** An object capable of returning its members one at a time. Examples of iterables include all sequence types (such as `list`, `str`, and `tuple`) and some non-sequence types like `dict`, *file objects*, and objects of any classes you define with an `__iter__()` method or with a `__getitem__()` method that implements *Sequence* semantics.

Iterables can be used in a `for` loop and in many other places where a sequence is needed (`zip()`, `map()`, ...). When an iterable object is passed as an argument to the built-in function `iter()`, it returns an iterator for the object. This iterator is good for one pass over the set of values. When using iterables, it is usually not necessary to call `iter()` or deal with iterator objects yourself. The `for` statement does that automatically for you, creating a temporary unnamed variable to hold the iterator for the duration of the loop. See also *iterator*, *sequence*, and *generator*.

**iterator** An object representing a stream of data. Repeated calls to the iterator's `__next__()` method (or passing it to the built-in function `next()`) return successive items in the stream. When no more data are available a `StopIteration` exception is raised instead. At this point, the iterator object is exhausted and any further calls to its `__next__()` method just raise `StopIteration` again. Iterators are required to have an `__iter__()` method that returns the iterator object itself so every iterator is also iterable and may be used in most places where other iterables are accepted. One notable exception is code which attempts multiple iteration passes. A container object (such as a `list`) produces a fresh new iterator each time you pass it to the `iter()` function or use it in a `for` loop. Attempting this with an iterator will just return the same exhausted iterator object used in the previous iteration pass, making it appear like an empty container.

More information can be found in *typeiter*.

**CPython implementation detail:** CPython does not consistently apply the requirement that an iterator define `__iter__()`.

**key function** A key function or collation function is a callable that returns a value used for sorting or ordering. For example, `locale.strxfrm()` is used to produce a sort key that is aware of locale specific sort conventions.

A number of tools in Python accept key functions to control how elements are ordered or grouped. They include `min()`, `max()`, `sorted()`, `list.sort()`, `heapq.merge()`, `heapq.nsmallest()`, `heapq.nlargest()`, and `itertools.groupby()`.

There are several ways to create a key function. For example, the `str.lower()` method can serve as a key function for case insensitive sorts. Alternatively, a key function can be built from a `lambda` expression such as `lambda r: (r[0], r[2])`. Also, the `operator` module provides three key function constructors: `attrgetter()`, `itemgetter()`, and `methodcaller()`. See the [Sorting HOW TO](#) for examples of how to create and use key functions.

**keyword argument** See [argument](#).

**lambda** An anonymous inline function consisting of a single [expression](#) which is evaluated when the function is called. The syntax to create a lambda function is `lambda [parameters]: expression`

**LBYL** Look before you leap. This coding style explicitly tests for pre-conditions before making calls or lookups. This style contrasts with the [EAFP](#) approach and is characterized by the presence of many `if` statements.

In a multi-threaded environment, the LBYL approach can risk introducing a race condition between “the looking” and “the leaping”. For example, the code, `if key in mapping: return mapping[key]` can fail if another thread removes *key* from *mapping* after the test, but before the lookup. This issue can be solved with locks or by using the EAFP approach.

**locale encoding** On Unix, it is the encoding of the `LC_CTYPE` locale. It can be set with `locale.setlocale(locale.LC_CTYPE, new_locale)`.

On Windows, it is the ANSI code page (ex: `cp1252`).

`locale.getpreferredencoding(False)` can be used to get the locale encoding.

Python uses the [filesystem encoding and error handler](#) to convert between Unicode filenames and bytes filenames.

**list** A built-in Python [sequence](#). Despite its name it is more akin to an array in other languages than to a linked list since access to elements is  $O(1)$ .

**list comprehension** A compact way to process all or part of the elements in a sequence and return a list with the results. `result = ['{:04x}'.format(x) for x in range(256) if x % 2 == 0]` generates a list of strings containing even hex numbers (0x..) in the range from 0 to 255. The `if` clause is optional. If omitted, all elements in `range(256)` are processed.

**loader** An object that loads a module. It must define a method named `load_module()`. A loader is typically returned by a [finder](#). See [PEP 302](#) for details and `importlib.abc.Loader` for an [abstract base class](#).

**magic method** An informal synonym for [special method](#).

**mapping** A container object that supports arbitrary key lookups and implements the methods specified in the `Mapping` or `MutableMapping` abstract base classes. Examples include `dict`, `collections.defaultdict`, `collections.OrderedDict` and `collections.Counter`.

**meta path finder** A [finder](#) returned by a search of `sys.meta_path`. Meta path finders are related to, but different from [path entry finders](#).

See `importlib.abc.MetaPathFinder` for the methods that meta path finders implement.

**metaclass** The class of a class. Class definitions create a class name, a class dictionary, and a list of base classes. The metaclass is responsible for taking those three arguments and creating the class. Most object oriented programming languages provide a default implementation. What makes Python special is that it is possible to create custom metaclasses. Most users never need this tool, but when the need arises, metaclasses can provide powerful, elegant solutions. They have been used for logging attribute access, adding thread-safety, tracking object creation, implementing singletons, and many other tasks.

More information can be found in metaclasses.

**method** A function which is defined inside a class body. If called as an attribute of an instance of that class, the method will get the instance object as its first [argument](#) (which is usually called `self`). See [function](#) and [nested scope](#).

**method resolution order** Method Resolution Order is the order in which base classes are searched for a member during lookup. See [The Python 2.3 Method Resolution Order](#) for details of the algorithm used by the Python interpreter since the 2.3 release.

**module** An object that serves as an organizational unit of Python code. Modules have a namespace containing arbitrary Python objects. Modules are loaded into Python by the process of [importing](#).

See also [package](#).

**module spec** A namespace containing the import-related information used to load a module. An instance of `importlib.machinery.ModuleSpec`.

**MRO** See [method resolution order](#).

**mutable** Mutable objects can change their value but keep their `id()`. See also [immutable](#).

**named tuple** The term “named tuple” applies to any type or class that inherits from tuple and whose indexable elements are also accessible using named attributes. The type or class may have other features as well.

Several built-in types are named tuples, including the values returned by `time.localtime()` and `os.stat()`. Another example is `sys.float_info`:

```
>>> sys.float_info[1]                # indexed access
1024
>>> sys.float_info.max_exp           # named field access
1024
>>> isinstance(sys.float_info, tuple) # kind of tuple
True
```

Some named tuples are built-in types (such as the above examples). Alternatively, a named tuple can be created from a regular class definition that inherits from `tuple` and that defines named fields. Such a class can be written by hand or it can be created with the factory function `collections.namedtuple()`. The latter technique also adds some extra methods that may not be found in hand-written or built-in named tuples.

**namespace** The place where a variable is stored. Namespaces are implemented as dictionaries. There are the local, global and built-in namespaces as well as nested namespaces in objects (in methods). Namespaces support modularity by preventing naming conflicts. For instance, the functions `builtins.open` and `os.open()` are distinguished by their namespaces. Namespaces also aid readability and maintainability by making it clear which module implements a function. For instance, writing `random.seed()` or `itertools.islice()` makes it clear that those functions are implemented by the `random` and `itertools` modules, respectively.

**namespace package** A [PEP 420 package](#) which serves only as a container for subpackages. Namespace packages may have no physical representation, and specifically are not like a [regular package](#) because they have no `__init__.py` file.

See also [module](#).

**nested scope** The ability to refer to a variable in an enclosing definition. For instance, a function defined inside another function can refer to variables in the outer function. Note that nested scopes by default work only for reference and not for assignment. Local variables both read and write in the innermost scope. Likewise, global variables read and write to the global namespace. The `nonlocal` allows writing to outer scopes.

**new-style class** Old name for the flavor of classes now used for all class objects. In earlier Python versions, only new-style classes could use Python’s newer, versatile features like `__slots__`, descriptors, properties, `__getattr__()`, class methods, and static methods.

**object** Any data with state (attributes or value) and defined behavior (methods). Also the ultimate base class of any [new-style class](#).

**package** A Python [module](#) which can contain submodules or recursively, subpackages. Technically, a package is a Python module with a `__path__` attribute.

See also [regular package](#) and [namespace package](#).

**parameter** A named entity in a [function](#) (or method) definition that specifies an [argument](#) (or in some cases, arguments) that the function can accept. There are five kinds of parameter:

- *positional-or-keyword*: specifies an argument that can be passed either *positionally* or as a *keyword argument*. This is the default kind of parameter, for example *foo* and *bar* in the following:

```
def func(foo, bar=None): ...
```

- *positional-only*: specifies an argument that can be supplied only by position. Positional-only parameters can be defined by including a `/` character in the parameter list of the function definition after them, for example *posonly1* and *posonly2* in the following:

```
def func(posonly1, posonly2, /, positional_or_keyword): ...
```

- *keyword-only*: specifies an argument that can be supplied only by keyword. Keyword-only parameters can be defined by including a single var-positional parameter or bare `*` in the parameter list of the function definition before them, for example *kw\_only1* and *kw\_only2* in the following:

```
def func(arg, *, kw_only1, kw_only2): ...
```

- *var-positional*: specifies that an arbitrary sequence of positional arguments can be provided (in addition to any positional arguments already accepted by other parameters). Such a parameter can be defined by prepending the parameter name with `*`, for example *args* in the following:

```
def func(*args, **kwargs): ...
```

- *var-keyword*: specifies that arbitrarily many keyword arguments can be provided (in addition to any keyword arguments already accepted by other parameters). Such a parameter can be defined by prepending the parameter name with `**`, for example *kwargs* in the example above.

Parameters can specify both optional and required arguments, as well as default values for some optional arguments.

See also the *argument* glossary entry, the FAQ question on *the difference between arguments and parameters*, the `inspect.Parameter` class, the function section, and [PEP 362](#).

**path entry** A single location on the *import path* which the *path based finder* consults to find modules for importing.

**path entry finder** A *finder* returned by a callable on `sys.path_hooks` (i.e. a *path entry hook*) which knows how to locate modules given a *path entry*.

See `importlib.abc.PathEntryFinder` for the methods that path entry finders implement.

**path entry hook** A callable on the `sys.path_hook` list which returns a *path entry finder* if it knows how to find modules on a specific *path entry*.

**path based finder** One of the default *meta path finders* which searches an *import path* for modules.

**path-like object** An object representing a file system path. A path-like object is either a `str` or `bytes` object representing a path, or an object implementing the `os.PathLike` protocol. An object that supports the `os.PathLike` protocol can be converted to a `str` or `bytes` file system path by calling the `os.fspath()` function; `os.fsdecode()` and `os.fsencode()` can be used to guarantee a `str` or `bytes` result instead, respectively. Introduced by [PEP 519](#).

**PEP** Python Enhancement Proposal. A PEP is a design document providing information to the Python community, or describing a new feature for Python or its processes or environment. PEPs should provide a concise technical specification and a rationale for proposed features.

PEPs are intended to be the primary mechanisms for proposing major new features, for collecting community input on an issue, and for documenting the design decisions that have gone into Python. The PEP author is responsible for building consensus within the community and documenting dissenting opinions.

See [PEP 1](#).

**portion** A set of files in a single directory (possibly stored in a zip file) that contribute to a namespace package, as defined in [PEP 420](#).

**positional argument** See *argument*.



**provisional API** A provisional API is one which has been deliberately excluded from the standard library’s backwards compatibility guarantees. While major changes to such interfaces are not expected, as long as they are marked provisional, backwards incompatible changes (up to and including removal of the interface) may occur if deemed necessary by core developers. Such changes will not be made gratuitously – they will occur only if serious fundamental flaws are uncovered that were missed prior to the inclusion of the API.

Even for provisional APIs, backwards incompatible changes are seen as a “solution of last resort” - every attempt will still be made to find a backwards compatible resolution to any identified problems.

This process allows the standard library to continue to evolve over time, without locking in problematic design errors for extended periods of time. See [PEP 411](#) for more details.

**provisional package** See *provisional API*.

**Python 3000** Nickname for the Python 3.x release line (coined long ago when the release of version 3 was something in the distant future.) This is also abbreviated “Py3k”.

**Pythonic** An idea or piece of code which closely follows the most common idioms of the Python language, rather than implementing code using concepts common to other languages. For example, a common idiom in Python is to loop over all elements of an iterable using a `for` statement. Many other languages don’t have this type of construct, so people unfamiliar with Python sometimes use a numerical counter instead:

```
for i in range(len(food)) :
    print (food[i])
```

As opposed to the cleaner, Pythonic method:

```
for piece in food:
    print (piece)
```

**qualified name** A dotted name showing the “path” from a module’s global scope to a class, function or method defined in that module, as defined in [PEP 3155](#). For top-level functions and classes, the qualified name is the same as the object’s name:

```
>>> class C:
...     class D:
...         def meth(self):
...             pass
...
>>> C.__qualname__
'C'
>>> C.D.__qualname__
'C.D'
>>> C.D.meth.__qualname__
'C.D.meth'
```

When used to refer to modules, the *fully qualified name* means the entire dotted path to the module, including any parent packages, e.g. `email.mime.text`:

```
>>> import email.mime.text
>>> email.mime.text.__name__
'email.mime.text'
```

**reference count** The number of references to an object. When the reference count of an object drops to zero, it is deallocated. Reference counting is generally not visible to Python code, but it is a key element of the *CPython* implementation. The `sys` module defines a `getrefcount()` function that programmers can call to return the reference count for a particular object.

**regular package** A traditional *package*, such as a directory containing an `__init__.py` file.

See also *namespace package*.

**`__slots__`** A declaration inside a class that saves memory by pre-declaring space for instance attributes and eliminating instance dictionaries. Though popular, the technique is somewhat tricky to get right and is best reserved for rare cases where there are large numbers of instances in a memory-critical application.

**sequence** An *iterable* which supports efficient element access using integer indices via the `__getitem__()` special method and defines a `__len__()` method that returns the length of the sequence. Some built-in sequence types are `list`, `str`, `tuple`, and `bytes`. Note that `dict` also supports `__getitem__()` and `__len__()`, but is considered a mapping rather than a sequence because the lookups use arbitrary *immutable* keys rather than integers.

The `collections.abc.Sequence` abstract base class defines a much richer interface that goes beyond just `__getitem__()` and `__len__()`, adding `count()`, `index()`, `__contains__()`, and `__reversed__()`. Types that implement this expanded interface can be registered explicitly using `register()`.

**set comprehension** A compact way to process all or part of the elements in an iterable and return a set with the results. `results = {c for c in 'abracadabra' if c not in 'abc'}` generates the set of strings `{'r', 'd'}`. See *comprehensions*.

**single dispatch** A form of *generic function* dispatch where the implementation is chosen based on the type of a single argument.

**slice** An object usually containing a portion of a *sequence*. A slice is created using the subscript notation, `[]` with colons between numbers when several are given, such as in `variable_name[1:3:5]`. The bracket (subscript) notation uses `slice` objects internally.

**special method** A method that is called implicitly by Python to execute a certain operation on a type, such as addition. Such methods have names starting and ending with double underscores. Special methods are documented in *specialnames*.

**statement** A statement is part of a suite (a “block” of code). A statement is either an *expression* or one of several constructs with a keyword, such as `if`, `while` or `for`.

**strong reference** In Python’s C API, a strong reference is a reference to an object which increments the object’s reference count when it is created and decrements the object’s reference count when it is deleted.

The `Py_NewRef()` function can be used to create a strong reference to an object. Usually, the `Py_DECREF()` function must be called on the strong reference before exiting the scope of the strong reference, to avoid leaking one reference.

See also *borrowed reference*.

**text encoding** A string in Python is a sequence of Unicode code points (in range U+0000–U+10FFFF). To store or transfer a string, it needs to be serialized as a sequence of bytes.

Serializing a string into a sequence of bytes is known as “encoding”, and recreating the string from the sequence of bytes is known as “decoding”.

There are a variety of different text serialization codecs, which are collectively referred to as “text encodings”.

**text file** A *file object* able to read and write `str` objects. Often, a text file actually accesses a byte-oriented datastream and handles the *text encoding* automatically. Examples of text files are files opened in text mode (`'r'` or `'w'`), `sys.stdin`, `sys.stdout`, and instances of `io.StringIO`.

See also *binary file* for a file object able to read and write *bytes-like objects*.

**triple-quoted string** A string which is bound by three instances of either a quotation mark (`"""`) or an apostrophe (`'''`). While they don’t provide any functionality not available with single-quoted strings, they are useful for a number of reasons. They allow you to include unescaped single and double quotes within a string and they can span multiple lines without the use of the continuation character, making them especially useful when writing docstrings.

**type** The type of a Python object determines what kind of object it is; every object has a type. An object’s type is accessible as its `__class__` attribute or can be retrieved with `type(obj)`.

**type alias** A synonym for a type, created by assigning the type to an identifier.

Type aliases are useful for simplifying *type hints*. For example:



```
def remove_gray_shades(
    colors: list[tuple[int, int, int]]) -> list[tuple[int, int, int]]:
    pass
```

could be made more readable like this:

```
Color = tuple[int, int, int]

def remove_gray_shades(colors: list[Color]) -> list[Color]:
    pass
```

See [typing](#) and [PEP 484](#), which describe this functionality.

**type hint** An *annotation* that specifies the expected type for a variable, a class attribute, or a function parameter or return value.

Type hints are optional and are not enforced by Python but they are useful to static type analysis tools, and aid IDEs with code completion and refactoring.

Type hints of global variables, class attributes, and functions, but not local variables, can be accessed using `typing.get_type_hints()`.

See [typing](#) and [PEP 484](#), which describe this functionality.

**universal newlines** A manner of interpreting text streams in which all of the following are recognized as ending a line: the Unix end-of-line convention `'\n'`, the Windows convention `'\r\n'`, and the old Macintosh convention `'\r'`. See [PEP 278](#) and [PEP 3116](#), as well as `bytes.splitlines()` for an additional use.

**variable annotation** An *annotation* of a variable or a class attribute.

When annotating a variable or a class attribute, assignment is optional:

```
class C:
    field: 'annotation'
```

Variable annotations are usually used for *type hints*: for example this variable is expected to take `int` values:

```
count: int = 0
```

Variable annotation syntax is explained in section [annassign](#).

See [function annotation](#), [PEP 484](#) and [PEP 526](#), which describe this functionality. Also see [annotations-howto](#) for best practices on working with annotations.

**virtual environment** A cooperatively isolated runtime environment that allows Python users and applications to install and upgrade Python distribution packages without interfering with the behaviour of other Python applications running on the same system.

See also `venv`.

**virtual machine** A computer defined entirely in software. Python’s virtual machine executes the *bytecode* emitted by the bytecode compiler.

**Zen of Python** Listing of Python design principles and philosophies that are helpful in understanding and using the language. The listing can be found by typing `“import this”` at the interactive prompt.



## ABOUT THESE DOCUMENTS

These documents are generated from `reStructuredText` sources by `Sphinx`, a document processor specifically written for the Python documentation.

Development of the documentation and its toolchain is an entirely volunteer effort, just like Python itself. If you want to contribute, please take a look at the [reporting-bugs](#) page for information on how to do so. New volunteers are always welcome!

Many thanks go to:

- Fred L. Drake, Jr., the creator of the original Python documentation toolset and writer of much of the content;
- the `Docutils` project for creating `reStructuredText` and the `Docutils` suite;
- Fredrik Lundh for his Alternative Python Reference project from which `Sphinx` got many good ideas.

### B.1 Contributors to the Python Documentation

Many people have contributed to the Python language, the Python standard library, and the Python documentation. See [Misc/ACKS](#) in the Python source distribution for a partial list of contributors.

It is only with the input and contributions of the Python community that Python has such wonderful documentation – Thank You!



## HISTORY AND LICENSE

### C.1 History of the software

Python was created in the early 1990s by Guido van Rossum at Stichting Mathematisch Centrum (CWI, see <https://www.cwi.nl/>) in the Netherlands as a successor of a language called ABC. Guido remains Python's principal author, although it includes many contributions from others.

In 1995, Guido continued his work on Python at the Corporation for National Research Initiatives (CNRI, see <https://www.cnri.reston.va.us/>) in Reston, Virginia where he released several versions of the software.

In May 2000, Guido and the Python core development team moved to BeOpen.com to form the BeOpen Python-Labs team. In October of the same year, the PythonLabs team moved to Digital Creations (now Zope Corporation; see <https://www.zope.org/>). In 2001, the Python Software Foundation (PSF, see <https://www.python.org/psf/>) was formed, a non-profit organization created specifically to own Python-related Intellectual Property. Zope Corporation is a sponsoring member of the PSF.

All Python releases are Open Source (see <https://opensource.org/> for the Open Source Definition). Historically, most, but not all, Python releases have also been GPL-compatible; the table below summarizes the various releases.

Release	Derived from	Year	Owner	GPL compatible?
0.9.0 thru 1.2	n/a	1991-1995	CWI	yes
1.3 thru 1.5.2	1.2	1995-1999	CNRI	yes
1.6	1.5.2	2000	CNRI	no
2.0	1.6	2000	BeOpen.com	no
1.6.1	1.6	2001	CNRI	no
2.1	2.0+1.6.1	2001	PSF	no
2.0.1	2.0+1.6.1	2001	PSF	yes
2.1.1	2.1+2.0.1	2001	PSF	yes
2.1.2	2.1.1	2002	PSF	yes
2.1.3	2.1.2	2002	PSF	yes
2.2 and above	2.1.1	2001-now	PSF	yes

**Note:** GPL-compatible doesn't mean that we're distributing Python under the GPL. All Python licenses, unlike the GPL, let you distribute a modified version without making your changes open source. The GPL-compatible licenses make it possible to combine Python with other software that is released under the GPL; the others don't.

Thanks to the many outside volunteers who have worked under Guido's direction to make these releases possible.

## C.2 Terms and conditions for accessing or otherwise using Python

Python software and documentation are licensed under the *PSF License Agreement*.

Starting with Python 3.8.6, examples, recipes, and other code in the documentation are dual licensed under the PSF License Agreement and the *Zero-Clause BSD license*.

Some software incorporated into Python is under different licenses. The licenses are listed with code falling under that license. See *Licenses and Acknowledgements for Incorporated Software* for an incomplete list of these licenses.

### C.2.1 PSF LICENSE AGREEMENT FOR PYTHON 3.10.10

1. This LICENSE AGREEMENT is between the Python Software Foundation,  
→ ("PSF"), and  
the Individual or Organization ("Licensee") accessing and otherwise  
→ using Python  
3.10.10 software in source or binary form and its associated  
→ documentation.
2. Subject to the terms and conditions of this License Agreement, PSF  
→ hereby  
grants Licensee a nonexclusive, royalty-free, world-wide license to  
→ reproduce,  
analyze, test, perform and/or display publicly, prepare derivative  
→ works,  
distribute, and otherwise use Python 3.10.10 alone or in any derivative  
version, provided, however, that PSF's License Agreement and PSF's  
→ notice of  
copyright, i.e., "Copyright © 2001-2023 Python Software Foundation; All  
→ Rights  
Reserved" are retained in Python 3.10.10 alone or in any derivative  
→ version  
prepared by Licensee.
3. In the event Licensee prepares a derivative work that is based on or  
incorporates Python 3.10.10 or any part thereof, and wants to make the  
derivative work available to others as provided herein, then Licensee  
→ hereby  
agrees to include in any such work a brief summary of the changes made  
→ to Python  
3.10.10.
4. PSF is making Python 3.10.10 available to Licensee on an "AS IS" basis.  
PSF MAKES NO REPRESENTATIONS OR WARRANTIES, EXPRESS OR IMPLIED. BY WAY  
→ OF  
EXAMPLE, BUT NOT LIMITATION, PSF MAKES NO AND DISCLAIMS ANY  
→ REPRESENTATION OR  
WARRANTY OF MERCHANTABILITY OR FITNESS FOR ANY PARTICULAR PURPOSE OR  
→ THAT THE  
USE OF PYTHON 3.10.10 WILL NOT INFRINGE ANY THIRD PARTY RIGHTS.
5. PSF SHALL NOT BE LIABLE TO LICENSEE OR ANY OTHER USERS OF PYTHON 3.10.10  
FOR ANY INCIDENTAL, SPECIAL, OR CONSEQUENTIAL DAMAGES OR LOSS AS A  
→ RESULT OF  
MODIFYING, DISTRIBUTING, OR OTHERWISE USING PYTHON 3.10.10, OR ANY  
→ DERIVATIVE

THEREOF, EVEN IF ADVISED OF THE POSSIBILITY THEREOF.

6. This License Agreement will automatically terminate upon a material breach of its terms and conditions.
7. Nothing in this License Agreement shall be deemed to create any relationship of agency, partnership, or joint venture between PSF and Licensee. This License Agreement does not grant permission to use PSF trademarks or trade name in a trademark sense to endorse or promote products or services of Licensee, or any third party.
8. By copying, installing or otherwise using Python 3.10.10, Licensee agrees to be bound by the terms and conditions of this License Agreement.

## C.2.2 BEOPEN.COM LICENSE AGREEMENT FOR PYTHON 2.0

### BEOPEN PYTHON OPEN SOURCE LICENSE AGREEMENT VERSION 1

1. This LICENSE AGREEMENT is between BeOpen.com ("BeOpen"), having an office at 160 Saratoga Avenue, Santa Clara, CA 95051, and the Individual or Organization ("Licensee") accessing and otherwise using this software in source or binary form and its associated documentation ("the Software").
2. Subject to the terms and conditions of this BeOpen Python License Agreement, BeOpen hereby grants Licensee a non-exclusive, royalty-free, world-wide license to reproduce, analyze, test, perform and/or display publicly, prepare derivative works, distribute, and otherwise use the Software alone or in any derivative version, provided, however, that the BeOpen Python License is retained in the Software, alone or in any derivative version prepared by Licensee.
3. BeOpen is making the Software available to Licensee on an "AS IS" basis. BEOPEN MAKES NO REPRESENTATIONS OR WARRANTIES, EXPRESS OR IMPLIED. BY WAY OF EXAMPLE, BUT NOT LIMITATION, BEOPEN MAKES NO AND DISCLAIMS ANY REPRESENTATION OR WARRANTY OF MERCHANTABILITY OR FITNESS FOR ANY PARTICULAR PURPOSE OR THAT THE USE OF THE SOFTWARE WILL NOT INFRINGE ANY THIRD PARTY RIGHTS.
4. BEOPEN SHALL NOT BE LIABLE TO LICENSEE OR ANY OTHER USERS OF THE SOFTWARE FOR ANY INCIDENTAL, SPECIAL, OR CONSEQUENTIAL DAMAGES OR LOSS AS A RESULT OF USING, MODIFYING OR DISTRIBUTING THE SOFTWARE, OR ANY DERIVATIVE THEREOF, EVEN IF ADVISED OF THE POSSIBILITY THEREOF.
5. This License Agreement will automatically terminate upon a material breach of its terms and conditions.
6. This License Agreement shall be governed by and interpreted in all respects by the law of the State of California, excluding conflict of law provisions. Nothing in this License Agreement shall be deemed to create any relationship of agency, partnership, or joint venture between BeOpen and Licensee. This License Agreement does not grant permission to use BeOpen trademarks or trade names in a trademark sense to endorse or promote products or services of Licensee, or any third party. As an exception, the "BeOpen Python" logos available at <http://www.pythonlabs.com/logos.html> may be used according to the permissions granted on that web page.

(continues on next page)

(continued from previous page)

7. By copying, installing or otherwise using the software, Licensee agrees to be bound by the terms and conditions of this License Agreement.

### C.2.3 CNRI LICENSE AGREEMENT FOR PYTHON 1.6.1

1. This LICENSE AGREEMENT is between the Corporation for National Research Initiatives, having an office at 1895 Preston White Drive, Reston, VA 20191 ("CNRI"), and the Individual or Organization ("Licensee") accessing and otherwise using Python 1.6.1 software in source or binary form and its associated documentation.
2. Subject to the terms and conditions of this License Agreement, CNRI hereby grants Licensee a nonexclusive, royalty-free, world-wide license to reproduce, analyze, test, perform and/or display publicly, prepare derivative works, distribute, and otherwise use Python 1.6.1 alone or in any derivative version, provided, however, that CNRI's License Agreement and CNRI's notice of copyright, i.e., "Copyright © 1995-2001 Corporation for National Research Initiatives; All Rights Reserved" are retained in Python 1.6.1 alone or in any derivative version prepared by Licensee. Alternately, in lieu of CNRI's License Agreement, Licensee may substitute the following text (omitting the quotes): "Python 1.6.1 is made available subject to the terms and conditions in CNRI's License Agreement. This Agreement together with Python 1.6.1 may be located on the internet using the following unique, persistent identifier (known as a handle): 1895.22/1013. This Agreement may also be obtained from a proxy server on the internet using the following URL: <http://hdl.handle.net/1895.22/1013>."
3. In the event Licensee prepares a derivative work that is based on or incorporates Python 1.6.1 or any part thereof, and wants to make the derivative work available to others as provided herein, then Licensee hereby agrees to include in any such work a brief summary of the changes made to Python 1.6.1.
4. CNRI is making Python 1.6.1 available to Licensee on an "AS IS" basis. CNRI MAKES NO REPRESENTATIONS OR WARRANTIES, EXPRESS OR IMPLIED. BY WAY OF EXAMPLE, BUT NOT LIMITATION, CNRI MAKES NO AND DISCLAIMS ANY REPRESENTATION OR WARRANTY OF MERCHANTABILITY OR FITNESS FOR ANY PARTICULAR PURPOSE OR THAT THE USE OF PYTHON 1.6.1 WILL NOT INFRINGE ANY THIRD PARTY RIGHTS.
5. CNRI SHALL NOT BE LIABLE TO LICENSEE OR ANY OTHER USERS OF PYTHON 1.6.1 FOR ANY INCIDENTAL, SPECIAL, OR CONSEQUENTIAL DAMAGES OR LOSS AS A RESULT OF MODIFYING, DISTRIBUTING, OR OTHERWISE USING PYTHON 1.6.1, OR ANY DERIVATIVE THEREOF, EVEN IF ADVISED OF THE POSSIBILITY THEREOF.
6. This License Agreement will automatically terminate upon a material breach of its terms and conditions.
7. This License Agreement shall be governed by the federal intellectual property law of the United States, including without limitation the federal copyright law, and, to the extent such U.S. federal law does not apply, by the law of the Commonwealth of Virginia, excluding Virginia's conflict of law provisions. Notwithstanding the foregoing, with regard to derivative works based on Python 1.6.1 that incorporate non-separable material that was previously distributed under the GNU General Public License (GPL), the law of the Commonwealth of Virginia shall govern this License Agreement only as to issues arising under or with respect to Paragraphs 4, 5, and 7 of this License Agreement. Nothing in this License Agreement shall be deemed to create any relationship of agency, partnership, or joint venture between CNRI and Licensee. This License Agreement does not grant permission to use CNRI trademarks or trade name in a trademark sense to endorse or promote products or services of Licensee, or any third party.

(continues on next page)



(continued from previous page)

8. By clicking on the "ACCEPT" button where indicated, or by copying, installing or otherwise using Python 1.6.1, Licensee agrees to be bound by the terms and conditions of this License Agreement.

## C.2.4 CWI LICENSE AGREEMENT FOR PYTHON 0.9.0 THROUGH 1.2

Copyright © 1991 - 1995, Stichting Mathematisch Centrum Amsterdam, The Netherlands. All rights reserved.

Permission to use, copy, modify, and distribute this software and its documentation for any purpose and without fee is hereby granted, provided that the above copyright notice appear in all copies and that both that copyright notice and this permission notice appear in supporting documentation, and that the name of Stichting Mathematisch Centrum or CWI not be used in advertising or publicity pertaining to distribution of the software without specific, written prior permission.

STICHTING MATHEMATISCH CENTRUM DISCLAIMS ALL WARRANTIES WITH REGARD TO THIS SOFTWARE, INCLUDING ALL IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS, IN NO EVENT SHALL STICHTING MATHEMATISCH CENTRUM BE LIABLE FOR ANY SPECIAL, INDIRECT OR CONSEQUENTIAL DAMAGES OR ANY DAMAGES WHATSOEVER RESULTING FROM LOSS OF USE, DATA OR PROFITS, WHETHER IN AN ACTION OF CONTRACT, NEGLIGENCE OR OTHER TORTIOUS ACTION, ARISING OUT OF OR IN CONNECTION WITH THE USE OR PERFORMANCE OF THIS SOFTWARE.

## C.2.5 ZERO-CLAUSE BSD LICENSE FOR CODE IN THE PYTHON 3.10.10 DOCUMENTATION

Permission to use, copy, modify, and/or distribute this software for any purpose with or without fee is hereby granted.

THE SOFTWARE IS PROVIDED "AS IS" AND THE AUTHOR DISCLAIMS ALL WARRANTIES WITH REGARD TO THIS SOFTWARE INCLUDING ALL IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS. IN NO EVENT SHALL THE AUTHOR BE LIABLE FOR ANY SPECIAL, DIRECT, INDIRECT, OR CONSEQUENTIAL DAMAGES OR ANY DAMAGES WHATSOEVER RESULTING FROM LOSS OF USE, DATA OR PROFITS, WHETHER IN AN ACTION OF CONTRACT, NEGLIGENCE OR OTHER TORTIOUS ACTION, ARISING OUT OF OR IN CONNECTION WITH THE USE OR PERFORMANCE OF THIS SOFTWARE.

## C.3 Licenses and Acknowledgements for Incorporated Software

This section is an incomplete, but growing list of licenses and acknowledgements for third-party software incorporated in the Python distribution.

### C.3.1 Mersenne Twister

The `_random` module includes code based on a download from <http://www.math.sci.hiroshima-u.ac.jp/~m-mat/MT/MT2002/emt19937ar.html>. The following are the verbatim comments from the original code:

```
A C-program for MT19937, with initialization improved 2002/1/26.
Coded by Takuji Nishimura and Makoto Matsumoto.

Before using, initialize the state by using init_genrand(seed)
or init_by_array(init_key, key_length).

Copyright (C) 1997 - 2002, Makoto Matsumoto and Takuji Nishimura,
All rights reserved.

Redistribution and use in source and binary forms, with or without
modification, are permitted provided that the following conditions
are met:

1. Redistributions of source code must retain the above copyright
   notice, this list of conditions and the following disclaimer.

2. Redistributions in binary form must reproduce the above copyright
   notice, this list of conditions and the following disclaimer in the
   documentation and/or other materials provided with the distribution.

3. The names of its contributors may not be used to endorse or promote
   products derived from this software without specific prior written
   permission.

THIS SOFTWARE IS PROVIDED BY THE COPYRIGHT HOLDERS AND CONTRIBUTORS
"AS IS" AND ANY EXPRESS OR IMPLIED WARRANTIES, INCLUDING, BUT NOT
LIMITED TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR
A PARTICULAR PURPOSE ARE DISCLAIMED. IN NO EVENT SHALL THE COPYRIGHT OWNER OR
CONTRIBUTORS BE LIABLE FOR ANY DIRECT, INDIRECT, INCIDENTAL, SPECIAL,
EXEMPLARY, OR CONSEQUENTIAL DAMAGES (INCLUDING, BUT NOT LIMITED TO,
PROCUREMENT OF SUBSTITUTE GOODS OR SERVICES; LOSS OF USE, DATA, OR
PROFITS; OR BUSINESS INTERRUPTION) HOWEVER CAUSED AND ON ANY THEORY OF
LIABILITY, WHETHER IN CONTRACT, STRICT LIABILITY, OR TORT (INCLUDING
NEGLIGENCE OR OTHERWISE) ARISING IN ANY WAY OUT OF THE USE OF THIS
SOFTWARE, EVEN IF ADVISED OF THE POSSIBILITY OF SUCH DAMAGE.

Any feedback is very welcome.
http://www.math.sci.hiroshima-u.ac.jp/~m-mat/MT/emt.html
email: m-mat @ math.sci.hiroshima-u.ac.jp (remove space)
```

### C.3.2 Sockets

The `socket` module uses the functions, `getaddrinfo()`, and `getnameinfo()`, which are coded in separate source files from the WIDE Project, <https://www.wide.ad.jp/>.

Copyright (C) 1995, 1996, 1997, and 1998 WIDE Project.  
All rights reserved.

Redistribution and use in source and binary forms, with or without modification, are permitted provided that the following conditions are met:

1. Redistributions of source code must retain the above copyright notice, this list of conditions and the following disclaimer.
2. Redistributions in binary form must reproduce the above copyright notice, this list of conditions and the following disclaimer in the documentation and/or other materials provided with the distribution.
3. Neither the name of the project nor the names of its contributors may be used to endorse or promote products derived from this software without specific prior written permission.

THIS SOFTWARE IS PROVIDED BY THE PROJECT AND CONTRIBUTORS ``AS IS'' AND ANY EXPRESS OR IMPLIED WARRANTIES, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE ARE DISCLAIMED. IN NO EVENT SHALL THE PROJECT OR CONTRIBUTORS BE LIABLE FOR ANY DIRECT, INDIRECT, INCIDENTAL, SPECIAL, EXEMPLARY, OR CONSEQUENTIAL DAMAGES (INCLUDING, BUT NOT LIMITED TO, PROCUREMENT OF SUBSTITUTE GOODS OR SERVICES; LOSS OF USE, DATA, OR PROFITS; OR BUSINESS INTERRUPTION) HOWEVER CAUSED AND ON ANY THEORY OF LIABILITY, WHETHER IN CONTRACT, STRICT LIABILITY, OR TORT (INCLUDING NEGLIGENCE OR OTHERWISE) ARISING IN ANY WAY OUT OF THE USE OF THIS SOFTWARE, EVEN IF ADVISED OF THE POSSIBILITY OF SUCH DAMAGE.

### C.3.3 Asynchronous socket services

The `asynchat` and `asyncore` modules contain the following notice:

Copyright 1996 by Sam Rushing

All Rights Reserved

Permission to use, copy, modify, and distribute this software and its documentation for any purpose and without fee is hereby granted, provided that the above copyright notice appear in all copies and that both that copyright notice and this permission notice appear in supporting documentation, and that the name of Sam Rushing not be used in advertising or publicity pertaining to distribution of the software without specific, written prior permission.

SAM RUSHING DISCLAIMS ALL WARRANTIES WITH REGARD TO THIS SOFTWARE, INCLUDING ALL IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS, IN NO EVENT SHALL SAM RUSHING BE LIABLE FOR ANY SPECIAL, INDIRECT OR CONSEQUENTIAL DAMAGES OR ANY DAMAGES WHATSOEVER RESULTING FROM LOSS OF USE, DATA OR PROFITS, WHETHER IN AN ACTION OF CONTRACT, NEGLIGENCE OR OTHER TORTIOUS ACTION, ARISING OUT OF OR IN CONNECTION WITH THE USE OR PERFORMANCE OF THIS SOFTWARE.

### C.3.4 Cookie management

The `http.cookies` module contains the following notice:

```
Copyright 2000 by Timothy O'Malley <timo@alum.mit.edu>

    All Rights Reserved

Permission to use, copy, modify, and distribute this software
and its documentation for any purpose and without fee is hereby
granted, provided that the above copyright notice appear in all
copies and that both that copyright notice and this permission
notice appear in supporting documentation, and that the name of
Timothy O'Malley not be used in advertising or publicity
pertaining to distribution of the software without specific, written
prior permission.

Timothy O'Malley DISCLAIMS ALL WARRANTIES WITH REGARD TO THIS
SOFTWARE, INCLUDING ALL IMPLIED WARRANTIES OF MERCHANTABILITY
AND FITNESS, IN NO EVENT SHALL Timothy O'Malley BE LIABLE FOR
ANY SPECIAL, INDIRECT OR CONSEQUENTIAL DAMAGES OR ANY DAMAGES
WHATSOEVER RESULTING FROM LOSS OF USE, DATA OR PROFITS,
WHETHER IN AN ACTION OF CONTRACT, NEGLIGENCE OR OTHER TORTIOUS
ACTION, ARISING OUT OF OR IN CONNECTION WITH THE USE OR
PERFORMANCE OF THIS SOFTWARE.
```

### C.3.5 Execution tracing

The `trace` module contains the following notice:

```
portions copyright 2001, Autonomous Zones Industries, Inc., all rights...
err... reserved and offered to the public under the terms of the
Python 2.2 license.
Author: Zooko O'Whielacronx
http://zooko.com/
mailto:zooko@zooko.com

Copyright 2000, Mojam Media, Inc., all rights reserved.
Author: Skip Montanaro

Copyright 1999, Bioreason, Inc., all rights reserved.
Author: Andrew Dalke

Copyright 1995-1997, Automatrix, Inc., all rights reserved.
Author: Skip Montanaro

Copyright 1991-1995, Stichting Mathematisch Centrum, all rights reserved.

Permission to use, copy, modify, and distribute this Python software and
its associated documentation for any purpose without fee is hereby
granted, provided that the above copyright notice appears in all copies,
and that both that copyright notice and this permission notice appear in
supporting documentation, and that the name of neither Automatrix,
Bioreason or Mojam Media be used in advertising or publicity pertaining to
distribution of the software without specific, written prior permission.
```

### C.3.6 UUencode and UUdecode functions

The `uu` module contains the following notice:

```
Copyright 1994 by Lance Ellinghouse
Cathedral City, California Republic, United States of America.
    All Rights Reserved
Permission to use, copy, modify, and distribute this software and its
documentation for any purpose and without fee is hereby granted,
provided that the above copyright notice appear in all copies and that
both that copyright notice and this permission notice appear in
supporting documentation, and that the name of Lance Ellinghouse
not be used in advertising or publicity pertaining to distribution
of the software without specific, written prior permission.
LANCE ELLINGHOUSE DISCLAIMS ALL WARRANTIES WITH REGARD TO
THIS SOFTWARE, INCLUDING ALL IMPLIED WARRANTIES OF MERCHANTABILITY AND
FITNESS, IN NO EVENT SHALL LANCE ELLINGHOUSE CENTRUM BE LIABLE
FOR ANY SPECIAL, INDIRECT OR CONSEQUENTIAL DAMAGES OR ANY DAMAGES
WHATSOEVER RESULTING FROM LOSS OF USE, DATA OR PROFITS, WHETHER IN AN
ACTION OF CONTRACT, NEGLIGENCE OR OTHER TORTIOUS ACTION, ARISING OUT
OF OR IN CONNECTION WITH THE USE OR PERFORMANCE OF THIS SOFTWARE.

Modified by Jack Jansen, CWI, July 1995:
- Use binascii module to do the actual line-by-line conversion
  between ascii and binary. This results in a 1000-fold speedup. The C
  version is still 5 times faster, though.
- Arguments more compliant with Python standard
```

### C.3.7 XML Remote Procedure Calls

The `xmlrpc.client` module contains the following notice:

```
The XML-RPC client interface is

Copyright (c) 1999-2002 by Secret Labs AB
Copyright (c) 1999-2002 by Fredrik Lundh

By obtaining, using, and/or copying this software and/or its
associated documentation, you agree that you have read, understood,
and will comply with the following terms and conditions:

Permission to use, copy, modify, and distribute this software and
its associated documentation for any purpose and without fee is
hereby granted, provided that the above copyright notice appears in
all copies, and that both that copyright notice and this permission
notice appear in supporting documentation, and that the name of
Secret Labs AB or the author not be used in advertising or publicity
pertaining to distribution of the software without specific, written
prior permission.

SECRET LABS AB AND THE AUTHOR DISCLAIMS ALL WARRANTIES WITH REGARD
TO THIS SOFTWARE, INCLUDING ALL IMPLIED WARRANTIES OF MERCHANT-
ABILITY AND FITNESS. IN NO EVENT SHALL SECRET LABS AB OR THE AUTHOR
BE LIABLE FOR ANY SPECIAL, INDIRECT OR CONSEQUENTIAL DAMAGES OR ANY
DAMAGES WHATSOEVER RESULTING FROM LOSS OF USE, DATA OR PROFITS,
WHETHER IN AN ACTION OF CONTRACT, NEGLIGENCE OR OTHER TORTIOUS
ACTION, ARISING OUT OF OR IN CONNECTION WITH THE USE OR PERFORMANCE
OF THIS SOFTWARE.
```

### C.3.8 test\_epoll

The `test_epoll` module contains the following notice:

```
Copyright (c) 2001-2006 Twisted Matrix Laboratories.
```

```
Permission is hereby granted, free of charge, to any person obtaining
a copy of this software and associated documentation files (the
"Software"), to deal in the Software without restriction, including
without limitation the rights to use, copy, modify, merge, publish,
distribute, sublicense, and/or sell copies of the Software, and to
permit persons to whom the Software is furnished to do so, subject to
the following conditions:
```

```
The above copyright notice and this permission notice shall be
included in all copies or substantial portions of the Software.
```

```
THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND,
EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF
MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE AND
NONINFRINGEMENT. IN NO EVENT SHALL THE AUTHORS OR COPYRIGHT HOLDERS BE
LIABLE FOR ANY CLAIM, DAMAGES OR OTHER LIABILITY, WHETHER IN AN ACTION
OF CONTRACT, TORT OR OTHERWISE, ARISING FROM, OUT OF OR IN CONNECTION
WITH THE SOFTWARE OR THE USE OR OTHER DEALINGS IN THE SOFTWARE.
```

### C.3.9 Select kqueue

The `select` module contains the following notice for the `kqueue` interface:

```
Copyright (c) 2000 Doug White, 2006 James Knight, 2007 Christian Heimes
All rights reserved.
```

```
Redistribution and use in source and binary forms, with or without
modification, are permitted provided that the following conditions
are met:
```

1. Redistributions of source code must retain the above copyright notice, this list of conditions and the following disclaimer.
2. Redistributions in binary form must reproduce the above copyright notice, this list of conditions and the following disclaimer in the documentation and/or other materials provided with the distribution.

```
THIS SOFTWARE IS PROVIDED BY THE AUTHOR AND CONTRIBUTORS ``AS IS'' AND
ANY EXPRESS OR IMPLIED WARRANTIES, INCLUDING, BUT NOT LIMITED TO, THE
IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE
ARE DISCLAIMED. IN NO EVENT SHALL THE AUTHOR OR CONTRIBUTORS BE LIABLE
FOR ANY DIRECT, INDIRECT, INCIDENTAL, SPECIAL, EXEMPLARY, OR CONSEQUENTIAL
DAMAGES (INCLUDING, BUT NOT LIMITED TO, PROCUREMENT OF SUBSTITUTE GOODS
OR SERVICES; LOSS OF USE, DATA, OR PROFITS; OR BUSINESS INTERRUPTION)
HOWEVER CAUSED AND ON ANY THEORY OF LIABILITY, WHETHER IN CONTRACT, STRICT
LIABILITY, OR TORT (INCLUDING NEGLIGENCE OR OTHERWISE) ARISING IN ANY WAY
OUT OF THE USE OF THIS SOFTWARE, EVEN IF ADVISED OF THE POSSIBILITY OF
SUCH DAMAGE.
```

### C.3.10 SipHash24

The file `Python/pyhash.c` contains Marek Majkowski's implementation of Dan Bernstein's SipHash24 algorithm. It contains the following note:

```
<MIT License>
Copyright (c) 2013  Marek Majkowski <marek@popcount.org>

Permission is hereby granted, free of charge, to any person obtaining a copy
of this software and associated documentation files (the "Software"), to deal
in the Software without restriction, including without limitation the rights
to use, copy, modify, merge, publish, distribute, sublicense, and/or sell
copies of the Software, and to permit persons to whom the Software is
furnished to do so, subject to the following conditions:

The above copyright notice and this permission notice shall be included in
all copies or substantial portions of the Software.
</MIT License>

Original location:
  https://github.com/majek/csiphash/

Solution inspired by code from:
  Samuel Neves (supercop/crypto_auth/siphhash24/little)
  djb (supercop/crypto_auth/siphhash24/little2)
  Jean-Philippe Aumasson (https://131002.net/siphhash/siphhash24.c)
```

### C.3.11 strtod and dtoa

The file `Python/dtoa.c`, which supplies C functions `dtoa` and `strtod` for conversion of C doubles to and from strings, is derived from the file of the same name by David M. Gay, currently available from <https://web.archive.org/web/20220517033456/http://www.netlib.org/fp/dtoa.c>. The original file, as retrieved on March 16, 2009, contains the following copyright and licensing notice:

```
/*****
 *
 * The author of this software is David M. Gay.
 *
 * Copyright (c) 1991, 2000, 2001 by Lucent Technologies.
 *
 * Permission to use, copy, modify, and distribute this software for any
 * purpose without fee is hereby granted, provided that this entire notice
 * is included in all copies of any software which is or includes a copy
 * or modification of this software and in all copies of the supporting
 * documentation for such software.
 *
 * THIS SOFTWARE IS BEING PROVIDED "AS IS", WITHOUT ANY EXPRESS OR IMPLIED
 * WARRANTY. IN PARTICULAR, NEITHER THE AUTHOR NOR LUCENT MAKES ANY
 * REPRESENTATION OR WARRANTY OF ANY KIND CONCERNING THE MERCHANTABILITY
 * OF THIS SOFTWARE OR ITS FITNESS FOR ANY PARTICULAR PURPOSE.
 *****/
```

## C.3.12 OpenSSL

The modules `hashlib`, `posix`, `ssl`, `crypt` use the OpenSSL library for added performance if made available by the operating system. Additionally, the Windows and macOS installers for Python may include a copy of the OpenSSL libraries, so we include a copy of the OpenSSL license here:

### LICENSE ISSUES

=====

The OpenSSL toolkit stays under a dual license, i.e. both the conditions of the OpenSSL License and the original SSLeay license apply to the toolkit. See below for the actual license texts. Actually both licenses are BSD-style Open Source licenses. In case of any license issues related to OpenSSL please contact [openssl-core@openssl.org](mailto:openssl-core@openssl.org).

### OpenSSL License

-----

```
/* =====
 * Copyright (c) 1998-2008 The OpenSSL Project. All rights reserved.
 *
 * Redistribution and use in source and binary forms, with or without
 * modification, are permitted provided that the following conditions
 * are met:
 *
 * 1. Redistributions of source code must retain the above copyright
 * notice, this list of conditions and the following disclaimer.
 *
 * 2. Redistributions in binary form must reproduce the above copyright
 * notice, this list of conditions and the following disclaimer in
 * the documentation and/or other materials provided with the
 * distribution.
 *
 * 3. All advertising materials mentioning features or use of this
 * software must display the following acknowledgment:
 * "This product includes software developed by the OpenSSL Project
 * for use in the OpenSSL Toolkit. (http://www.openssl.org/)"
 *
 * 4. The names "OpenSSL Toolkit" and "OpenSSL Project" must not be used to
 * endorse or promote products derived from this software without
 * prior written permission. For written permission, please contact
 * openssl-core@openssl.org.
 *
 * 5. Products derived from this software may not be called "OpenSSL"
 * nor may "OpenSSL" appear in their names without prior written
 * permission of the OpenSSL Project.
 *
 * 6. Redistributions of any form whatsoever must retain the following
 * acknowledgment:
 * "This product includes software developed by the OpenSSL Project
 * for use in the OpenSSL Toolkit (http://www.openssl.org/)"
 *
 * THIS SOFTWARE IS PROVIDED BY THE OpenSSL PROJECT ``AS IS'' AND ANY
 * EXPRESSED OR IMPLIED WARRANTIES, INCLUDING, BUT NOT LIMITED TO, THE
 * IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR
 * PURPOSE ARE DISCLAIMED. IN NO EVENT SHALL THE OpenSSL PROJECT OR
 * ITS CONTRIBUTORS BE LIABLE FOR ANY DIRECT, INDIRECT, INCIDENTAL,
 * SPECIAL, EXEMPLARY, OR CONSEQUENTIAL DAMAGES (INCLUDING, BUT
 * NOT LIMITED TO, PROCUREMENT OF SUBSTITUTE GOODS OR SERVICES;
 * LOSS OF USE, DATA, OR PROFITS; OR BUSINESS INTERRUPTION)
 * HOWEVER CAUSED AND ON ANY THEORY OF LIABILITY, WHETHER IN CONTRACT,
 * STRICT LIABILITY, OR TORT (INCLUDING NEGLIGENCE OR OTHERWISE)
```

(continues on next page)



(continued from previous page)

```

* ARISING IN ANY WAY OUT OF THE USE OF THIS SOFTWARE, EVEN IF ADVISED
* OF THE POSSIBILITY OF SUCH DAMAGE.
* =====
*
* This product includes cryptographic software written by Eric Young
* (eay@cryptsoft.com). This product includes software written by Tim
* Hudson (tjh@cryptsoft.com).
*
*/

```

Original SSLeay License

-----

```

/* Copyright (C) 1995-1998 Eric Young (eay@cryptsoft.com)
* All rights reserved.
*
* This package is an SSL implementation written
* by Eric Young (eay@cryptsoft.com).
* The implementation was written so as to conform with Netscapes SSL.
*
* This library is free for commercial and non-commercial use as long as
* the following conditions are aheared to. The following conditions
* apply to all code found in this distribution, be it the RC4, RSA,
* lhash, DES, etc., code; not just the SSL code. The SSL documentation
* included with this distribution is covered by the same copyright terms
* except that the holder is Tim Hudson (tjh@cryptsoft.com).
*
* Copyright remains Eric Young's, and as such any Copyright notices in
* the code are not to be removed.
* If this package is used in a product, Eric Young should be given attribution
* as the author of the parts of the library used.
* This can be in the form of a textual message at program startup or
* in documentation (online or textual) provided with the package.
*
* Redistribution and use in source and binary forms, with or without
* modification, are permitted provided that the following conditions
* are met:
* 1. Redistributions of source code must retain the copyright
* notice, this list of conditions and the following disclaimer.
* 2. Redistributions in binary form must reproduce the above copyright
* notice, this list of conditions and the following disclaimer in the
* documentation and/or other materials provided with the distribution.
* 3. All advertising materials mentioning features or use of this software
* must display the following acknowledgement:
* "This product includes cryptographic software written by
* Eric Young (eay@cryptsoft.com)"
* The word 'cryptographic' can be left out if the rouines from the library
* being used are not cryptographic related :-).
* 4. If you include any Windows specific code (or a derivative thereof) from
* the apps directory (application code) you must include an acknowledgement:
* "This product includes software written by Tim Hudson (tjh@cryptsoft.com)"
*
* THIS SOFTWARE IS PROVIDED BY ERIC YOUNG ``AS IS'' AND
* ANY EXPRESS OR IMPLIED WARRANTIES, INCLUDING, BUT NOT LIMITED TO, THE
* IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE
* ARE DISCLAIMED. IN NO EVENT SHALL THE AUTHOR OR CONTRIBUTORS BE LIABLE
* FOR ANY DIRECT, INDIRECT, INCIDENTAL, SPECIAL, EXEMPLARY, OR CONSEQUENTIAL
* DAMAGES (INCLUDING, BUT NOT LIMITED TO, PROCUREMENT OF SUBSTITUTE GOODS
* OR SERVICES; LOSS OF USE, DATA, OR PROFITS; OR BUSINESS INTERRUPTION)
* HOWEVER CAUSED AND ON ANY THEORY OF LIABILITY, WHETHER IN CONTRACT, STRICT
* LIABILITY, OR TORT (INCLUDING NEGLIGENCE OR OTHERWISE) ARISING IN ANY WAY

```

(continues on next page)

(continued from previous page)

```
* OUT OF THE USE OF THIS SOFTWARE, EVEN IF ADVISED OF THE POSSIBILITY OF
* SUCH DAMAGE.
*
* The licence and distribution terms for any publically available version or
* derivative of this code cannot be changed. i.e. this code cannot simply be
* copied and put under another distribution licence
* [including the GNU Public Licence.]
*/
```

### C.3.13 expat

The `pyexpat` extension is built using an included copy of the expat sources unless the build is configured `--with-system-expat`:

```
Copyright (c) 1998, 1999, 2000 Thai Open Source Software Center Ltd
and Clark Cooper

Permission is hereby granted, free of charge, to any person obtaining
a copy of this software and associated documentation files (the
"Software"), to deal in the Software without restriction, including
without limitation the rights to use, copy, modify, merge, publish,
distribute, sublicense, and/or sell copies of the Software, and to
permit persons to whom the Software is furnished to do so, subject to
the following conditions:

The above copyright notice and this permission notice shall be included
in all copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND,
EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF
MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE AND NONINFRINGEMENT.
IN NO EVENT SHALL THE AUTHORS OR COPYRIGHT HOLDERS BE LIABLE FOR ANY
CLAIM, DAMAGES OR OTHER LIABILITY, WHETHER IN AN ACTION OF CONTRACT,
TORT OR OTHERWISE, ARISING FROM, OUT OF OR IN CONNECTION WITH THE
SOFTWARE OR THE USE OR OTHER DEALINGS IN THE SOFTWARE.
```

### C.3.14 libffi

The `_ctypes` extension is built using an included copy of the libffi sources unless the build is configured `--with-system-libffi`:

```
Copyright (c) 1996-2008 Red Hat, Inc and others.

Permission is hereby granted, free of charge, to any person obtaining
a copy of this software and associated documentation files (the
``Software''), to deal in the Software without restriction, including
without limitation the rights to use, copy, modify, merge, publish,
distribute, sublicense, and/or sell copies of the Software, and to
permit persons to whom the Software is furnished to do so, subject to
the following conditions:

The above copyright notice and this permission notice shall be included
in all copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED ``AS IS'', WITHOUT WARRANTY OF ANY KIND,
EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF
MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE AND
```

(continues on next page)

(continued from previous page)

```
NONINFRINGEMENT.  IN NO EVENT SHALL THE AUTHORS OR COPYRIGHT
HOLDERS BE LIABLE FOR ANY CLAIM, DAMAGES OR OTHER LIABILITY,
WHETHER IN AN ACTION OF CONTRACT, TORT OR OTHERWISE, ARISING FROM,
OUT OF OR IN CONNECTION WITH THE SOFTWARE OR THE USE OR OTHER
DEALINGS IN THE SOFTWARE.
```

### C.3.15 zlib

The `zlib` extension is built using an included copy of the `zlib` sources if the `zlib` version found on the system is too old to be used for the build:

```
Copyright (C) 1995-2011 Jean-loup Gailly and Mark Adler
```

```
This software is provided 'as-is', without any express or implied
warranty.  In no event will the authors be held liable for any damages
arising from the use of this software.
```

```
Permission is granted to anyone to use this software for any purpose,
including commercial applications, and to alter it and redistribute it
freely, subject to the following restrictions:
```

1. The origin of this software must not be misrepresented; you must not claim that you wrote the original software. If you use this software in a product, an acknowledgment in the product documentation would be appreciated but is not required.
2. Altered source versions must be plainly marked as such, and must not be misrepresented as being the original software.
3. This notice may not be removed or altered from any source distribution.

```
Jean-loup Gailly      jloup@gzip.org
```

```
Mark Adler      madler@alumni.caltech.edu
```

### C.3.16 cfuhash

The implementation of the hash table used by the `tracemalloc` is based on the `cfuhash` project:

```
Copyright (c) 2005 Don Owens
All rights reserved.
```

```
This code is released under the BSD license:
```

```
Redistribution and use in source and binary forms, with or without
modification, are permitted provided that the following conditions
are met:
```

- \* Redistributions of source code must retain the above copyright notice, this list of conditions and the following disclaimer.
- \* Redistributions in binary form must reproduce the above copyright notice, this list of conditions and the following disclaimer in the documentation and/or other materials provided with the distribution.
- \* Neither the name of the author nor the names of its contributors may be used to endorse or promote products derived

(continues on next page)

(continued from previous page)

```
from this software without specific prior written permission.
```

```
THIS SOFTWARE IS PROVIDED BY THE COPYRIGHT HOLDERS AND CONTRIBUTORS
"AS IS" AND ANY EXPRESS OR IMPLIED WARRANTIES, INCLUDING, BUT NOT
LIMITED TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS
FOR A PARTICULAR PURPOSE ARE DISCLAIMED. IN NO EVENT SHALL THE
COPYRIGHT OWNER OR CONTRIBUTORS BE LIABLE FOR ANY DIRECT, INDIRECT,
INCIDENTAL, SPECIAL, EXEMPLARY, OR CONSEQUENTIAL DAMAGES
(INCLUDING, BUT NOT LIMITED TO, PROCUREMENT OF SUBSTITUTE GOODS OR
SERVICES; LOSS OF USE, DATA, OR PROFITS; OR BUSINESS INTERRUPTION)
HOWEVER CAUSED AND ON ANY THEORY OF LIABILITY, WHETHER IN CONTRACT,
STRICT LIABILITY, OR TORT (INCLUDING NEGLIGENCE OR OTHERWISE)
ARISING IN ANY WAY OUT OF THE USE OF THIS SOFTWARE, EVEN IF ADVISED
OF THE POSSIBILITY OF SUCH DAMAGE.
```

### C.3.17 libmpdec

The `_decimal` module is built using an included copy of the libmpdec library unless the build is configured `--with-system-libmpdec`:

```
Copyright (c) 2008-2020 Stefan Krah. All rights reserved.
```

```
Redistribution and use in source and binary forms, with or without
modification, are permitted provided that the following conditions
are met:
```

1. Redistributions of source code must retain the above copyright notice, this list of conditions and the following disclaimer.
2. Redistributions in binary form must reproduce the above copyright notice, this list of conditions and the following disclaimer in the documentation and/or other materials provided with the distribution.

```
THIS SOFTWARE IS PROVIDED BY THE AUTHOR AND CONTRIBUTORS "AS IS" AND
ANY EXPRESS OR IMPLIED WARRANTIES, INCLUDING, BUT NOT LIMITED TO, THE
IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE
ARE DISCLAIMED. IN NO EVENT SHALL THE AUTHOR OR CONTRIBUTORS BE LIABLE
FOR ANY DIRECT, INDIRECT, INCIDENTAL, SPECIAL, EXEMPLARY, OR CONSEQUENTIAL
DAMAGES (INCLUDING, BUT NOT LIMITED TO, PROCUREMENT OF SUBSTITUTE GOODS
OR SERVICES; LOSS OF USE, DATA, OR PROFITS; OR BUSINESS INTERRUPTION)
HOWEVER CAUSED AND ON ANY THEORY OF LIABILITY, WHETHER IN CONTRACT, STRICT
LIABILITY, OR TORT (INCLUDING NEGLIGENCE OR OTHERWISE) ARISING IN ANY WAY
OUT OF THE USE OF THIS SOFTWARE, EVEN IF ADVISED OF THE POSSIBILITY OF
SUCH DAMAGE.
```

### C.3.18 W3C C14N test suite

The C14N 2.0 test suite in the test package (Lib/test/xmltestdata/c14n-20/) was retrieved from the W3C website at <https://www.w3.org/TR/xml-c14n2-testcases/> and is distributed under the 3-clause BSD license:

```
Copyright (c) 2013 W3C(R) (MIT, ERCIM, Keio, Beihang),
All Rights Reserved.
```

```
Redistribution and use in source and binary forms, with or without
modification, are permitted provided that the following conditions
are met:
```

(continues on next page)

(continued from previous page)

- \* Redistributions of works must retain the original copyright notice, this list of conditions and the following disclaimer.
- \* Redistributions in binary form must reproduce the original copyright notice, this list of conditions and the following disclaimer in the documentation and/or other materials provided with the distribution.
- \* Neither the name of the W3C nor the names of its contributors may be used to endorse or promote products derived from this work without specific prior written permission.

THIS SOFTWARE IS PROVIDED BY THE COPYRIGHT HOLDERS AND CONTRIBUTORS "AS IS" AND ANY EXPRESS OR IMPLIED WARRANTIES, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE ARE DISCLAIMED. IN NO EVENT SHALL THE COPYRIGHT OWNER OR CONTRIBUTORS BE LIABLE FOR ANY DIRECT, INDIRECT, INCIDENTAL, SPECIAL, EXEMPLARY, OR CONSEQUENTIAL DAMAGES (INCLUDING, BUT NOT LIMITED TO, PROCUREMENT OF SUBSTITUTE GOODS OR SERVICES; LOSS OF USE, DATA, OR PROFITS; OR BUSINESS INTERRUPTION) HOWEVER CAUSED AND ON ANY THEORY OF LIABILITY, WHETHER IN CONTRACT, STRICT LIABILITY, OR TORT (INCLUDING NEGLIGENCE OR OTHERWISE) ARISING IN ANY WAY OUT OF THE USE OF THIS SOFTWARE, EVEN IF ADVISED OF THE POSSIBILITY OF SUCH DAMAGE.

### C.3.19 Audioop

The audioop module uses the code base in g771.c file of the SoX project:

```
Programming the AdLib/Sound Blaster
FM Music Chips
Version 2.0 (24 Feb 1992)
Copyright (c) 1991, 1992 by Jeffrey S. Lee
jlee@smylex.uucp
Warranty and Copyright Policy
This document is provided on an "as-is" basis, and its author makes
no warranty or representation, express or implied, with respect to
its quality performance or fitness for a particular purpose. In no
event will the author of this document be liable for direct, indirect,
special, incidental, or consequential damages arising out of the use
or inability to use the information contained within. Use of this
document is at your own risk.
This file may be used and copied freely so long as the applicable
copyright notices are retained, and no modifications are made to the
text of the document. No money shall be charged for its distribution
beyond reasonable shipping, handling and duplication costs, nor shall
proprietary changes be made to this document so that it cannot be
distributed freely. This document may not be included in published
material or commercial packages without the written consent of its
author.
```



## COPYRIGHT

Python and this documentation is:

Copyright © 2001-2023 Python Software Foundation. All rights reserved.

Copyright © 2000 BeOpen.com. All rights reserved.

Copyright © 1995-2000 Corporation for National Research Initiatives. All rights reserved.

Copyright © 1991-1995 Stichting Mathematisch Centrum. All rights reserved.

---

See *[History and License](#)* for complete license and permissions information.





## Non-alphabetical

..., [77](#)  
 2to3, [77](#)  
 >>>, [77](#)  
 \_\_future\_\_, [81](#)  
 \_\_slots\_\_, [87](#)

## A

abstract base class, [77](#)  
 annotation, [77](#)  
 argument, [77](#)  
     difference from parameter, [14](#)  
 asynchronous context manager, [78](#)  
 asynchronous generator, [78](#)  
 asynchronous generator iterator, [78](#)  
 asynchronous iterable, [78](#)  
 asynchronous iterator, [78](#)  
 attribute, [78](#)  
 awaitable, [78](#)

## B

BDFL, [78](#)  
 binary file, [78](#)  
 borrowed reference, [78](#)  
 bytecode, [79](#)  
 bytes-like object, [78](#)

## C

callable, [79](#)  
 callback, [79](#)  
 C-contiguous, [79](#)  
 class, [79](#)  
 class variable, [79](#)  
 coercion, [79](#)  
 complex number, [79](#)  
 context manager, [79](#)  
 context variable, [79](#)  
 contiguous, [79](#)  
 coroutine, [79](#)  
 coroutine function, [79](#)  
 CPython, [80](#)

## D

decorator, [80](#)  
 descriptor, [80](#)  
 dictionary, [80](#)

dictionary comprehension, [80](#)  
 dictionary view, [80](#)  
 docstring, [80](#)  
 duck-typing, [80](#)

## E

EAFP, [80](#)  
 environment variable  
     PATH, [53](#), [54](#)  
     PYTHONDONTWRITEBYTECODE, [37](#)  
     TCL\_LIBRARY, [73](#)  
     TK\_LIBRARY, [73](#)  
 expression, [80](#)  
 extension module, [80](#)

## F

f-string, [81](#)  
 file object, [81](#)  
 file-like object, [81](#)  
 filesystem encoding and error  
     handler, [81](#)  
 finder, [81](#)  
 floor division, [81](#)  
 Fortran contiguous, [79](#)  
 function, [81](#)  
 function annotation, [81](#)

## G

garbage collection, [82](#)  
 generator, [82](#)  
 generator expression, [82](#)  
 generator iterator, [82](#)  
 generic function, [82](#)  
 generic type, [82](#)  
 GIL, [82](#)  
 global interpreter lock, [82](#)

## H

hash-based pyc, [82](#)  
 hashable, [82](#)

## I

IDLE, [83](#)  
 immutable, [83](#)  
 import path, [83](#)  
 importer, [83](#)

- importing, [83](#)
- interactive, [83](#)
- interpreted, [83](#)
- interpreter shutdown, [83](#)
- iterable, [83](#)
- iterator, [83](#)

## K

- key function, [83](#)
- keyword argument, [84](#)

## L

- lambda, [84](#)
- LBYL, [84](#)
- list, [84](#)
- list comprehension, [84](#)
- loader, [84](#)
- locale encoding, [84](#)

## M

- magic
  - method, [84](#)
- magic method, [84](#)
- mapping, [84](#)
- meta path finder, [84](#)
- metaclass, [84](#)
- method, [84](#)
  - magic, [84](#)
  - special, [88](#)
- method resolution order, [85](#)
- module, [85](#)
- module spec, [85](#)
- MRO, [85](#)
- mutable, [85](#)

## N

- named tuple, [85](#)
- namespace, [85](#)
- namespace package, [85](#)
- nested scope, [85](#)
- new-style class, [85](#)

## O

- object, [85](#)

## P

- package, [85](#)
- parameter, [85](#)
  - difference from argument, [14](#)
- PATH, [53](#), [54](#)
- path based finder, [86](#)
- path entry, [86](#)
- path entry finder, [86](#)
- path entry hook, [86](#)
- path-like object, [86](#)
- PEP, [86](#)
- portion, [86](#)
- positional argument, [86](#)

- provisional API, [87](#)
- provisional package, [87](#)
- Python 3000, [87](#)
- Python Enhancement Proposals

- PEP 1, [86](#)
- PEP 5, [6](#)
- PEP 6, [2](#)
- PEP 8, [10](#), [35](#), [72](#)
- PEP 238, [81](#)
- PEP 278, [89](#)
- PEP 302, [81](#), [84](#)
- PEP 343, [79](#)
- PEP 362, [78](#), [86](#)
- PEP 411, [87](#)
- PEP 420, [81](#), [85](#), [86](#)
- PEP 443, [82](#)
- PEP 451, [81](#)
- PEP 483, [82](#)
- PEP 484, [77](#), [81](#), [82](#), [89](#)
- PEP 492, [78](#), [79](#)
- PEP 498, [81](#)
- PEP 519, [86](#)
- PEP 525, [78](#)
- PEP 526, [77](#), [89](#)
- PEP 572, [43](#)
- PEP 585, [82](#)
- PEP 602, [5](#)
- PEP 3116, [89](#)
- PEP 3147, [37](#)
- PEP 3155, [87](#)

- PYTHONDONTWRITEBYTECODE, [37](#)

- Pythonic, [87](#)

## Q

- qualified name, [87](#)

## R

- reference count, [87](#)
- regular package, [87](#)

## S

- sequence, [88](#)
- set comprehension, [88](#)
- single dispatch, [88](#)
- slice, [88](#)
- special
  - method, [88](#)
- special method, [88](#)
- statement, [88](#)
- strong reference, [88](#)

## T

- TCL\_LIBRARY, [73](#)
- text encoding, [88](#)
- text file, [88](#)
- TK\_LIBRARY, [73](#)
- triple-quoted string, [88](#)
- type, [88](#)

type alias, [88](#)  
type hint, [89](#)

## U

universal newlines, [89](#)

## V

variable annotation, [89](#)  
virtual environment, [89](#)  
virtual machine, [89](#)

## Z

Zen of Python, [89](#)