
What's New in Python

Release 3.11.0a5

A. M. Kuchling

March 07, 2022

Python Software Foundation

Email: docs@python.org

Contents

1	Summary – Release highlights	2
2	New Features	2
2.1	Enhanced error locations in tracebacks	2
3	Other Language Changes	4
4	Other CPython Implementation Changes	4
5	New Modules	4
6	Improved Modules	5
6.1	fractions	5
6.2	IDLE and idlelib	5
6.3	inspect	5
6.4	math	5
6.5	operator	5
6.6	os	5
6.7	socket	6
6.8	sqlite3	6
6.9	sys	6
6.10	threading	6
6.11	time	7
6.12	unicodedata	7
6.13	fcntl	7
7	Optimizations	7
8	CPython bytecode changes	7
9	Deprecated	8
10	Removed	9

11 Porting to Python 3.11	10
11.1 Changes in the Python API	10
12 Build Changes	10
13 C API Changes	11
13.1 New Features	11
13.2 Porting to Python 3.11	12
13.3 Deprecated	15
13.4 Removed	16
Index	17

Release 3.11.0a5

Date March 07, 2022

This article explains the new features in Python 3.11, compared to 3.10.

For full details, see the changelog.

Note: Prerelease users should be aware that this document is currently in draft form. It will be updated substantially as Python 3.11 moves towards release, so it's worth checking back even after reading earlier versions.

1 Summary – Release highlights

PEP-654: Exception Groups and `except*`. (Contributed by Irit Katriel in [bpo-45292](#).) PEP-673: `Self` Type. (Contributed by James Hilton-Balfe and Pradeep Kumar in [bpo-30924](#).)

2 New Features

2.1 Enhanced error locations in tracebacks

When printing tracebacks, the interpreter will now point to the exact expression that caused the error instead of just the line. For example:

```
Traceback (most recent call last):
  File "distance.py", line 11, in <module>
    print(manhattan_distance(p1, p2))
    ^^^^^^^^^^^^^^^^^^^^^^^^^^^^^^^^^
  File "distance.py", line 6, in manhattan_distance
    return abs(point_1.x - point_2.x) + abs(point_1.y - point_2.y)
           ^^^^^^^^^
AttributeError: 'NoneType' object has no attribute 'x'
```

Previous versions of the interpreter would point to just the line making it ambiguous which object was `None`. These enhanced errors can also be helpful when dealing with deeply nested dictionary objects and multiple function calls,

as well as complex arithmetic expressions:

See **PEP 657** for more details. (Contributed by Pablo Galindo, Batuhan Taskaya and Ammar Askar in [bpo-43950](#).)

Column information for code objects

- The `codeobject.co_positions()` method in Python.
- The `PyCode_Addr2Location()` function in the C-API.

See **PEP 657** for more details. (Contributed by Pablo Galindo, Batuhan Taskaya and Ammar Askar in [bpo-43950](#).)

The `__note__` field was added to `BaseException`. It is `None` by default but can be set to a string which is added to the exception's traceback. (Contributed by Irit Katriel in [bpo-45607](#).)

3 Other Language Changes

- Starred expressions can be used in for statements. (See [bpo-46725](#) for more details.)
- Asynchronous comprehensions are now allowed inside comprehensions in asynchronous functions. Outer comprehensions implicitly become asynchronous. (Contributed by Serhiy Storchaka in [bpo-33346](#).)
- A `TypeError` is now raised instead of an `AttributeError` in `contextlib.ExitStack.enter_context()` and `contextlib.AsyncExitStack.enter_async_context()` for objects which do not support the context manager or asynchronous context manager protocols correspondingly. (Contributed by Serhiy Storchaka in [bpo-44471](#).)
- A `TypeError` is now raised instead of an `AttributeError` in `with` and `async with` statements for objects which do not support the context manager or asynchronous context manager protocols correspondingly. (Contributed by Serhiy Storchaka in [bpo-12022](#).)

4 Other CPython Implementation Changes

- Special methods `complex.__complex__()` and `bytes.__bytes__()` are implemented to support `typing.SupportsComplex` and `typing.SupportsBytes` protocols. (Contributed by Mark Dickinson and Dong-hee Na in [bpo-24234](#).)
- `siphash13` is added as a new internal hashing algorithms. It's has similar security properties as `siphash24` but it is slightly faster for long inputs. `str`, `bytes`, and some other types now use it as default algorithm for `hash()`. **PEP 552** hash-based pyc files now use `siphash13`, too. (Contributed by Inada Naoki in [bpo-29410](#).)
- When an active exception is re-raised by a `raise` statement with no parameters, the traceback attached to this exception is now always `sys.exc_info()[1].__traceback__`. This means that changes made to the traceback in the current `except` clause are reflected in the re-raised exception. (Contributed by Irit Katriel in [bpo-45711](#).)
- The interpreter state's representation of handled exceptions (a.k.a `exc_info`, or `_PyErr_StackItem`) now has only the `exc_value` field, `exc_type` and `exc_traceback` have been removed as their values can be derived from `exc_value`. (Contributed by Irit Katriel in [bpo-45711](#).)
- A new command line option for the Windows installer `AppendPath` has been added. It behaves similar to `PrependPath` but appends the install and scripts directories instead of prepending it. (Contributed by Bastian Neuburger in [bpo-44934](#).)

5 New Modules

- None yet.

6 Improved Modules

6.1 fractions

- Support **PEP 515**-style initialization of `Fraction` from string. (Contributed by Sergey B Kirpichev in [bpo-44258](#).)
- `Fraction` now implements an `__int__` method, so that an `isinstance(some_fraction, typing.SupportsInt)` check passes. (Contributed by Mark Dickinson in [bpo-44547](#).)

6.2 IDLE and idlelib

- Apply syntax highlighting to `.pyi` files. (Contributed by Alex Waygood and Terry Jan Reedy in [bpo-45447](#).)

6.3 inspect

- Add `inspect.getmembers_static()`: return all members without triggering dynamic lookup via the descriptor protocol. (Contributed by Weipeng Hong in [bpo-30533](#).)
- Add `inspect.ismethodwrapper()` for checking if the type of an object is a `MethodWrapperType`. (Contributed by Hakan Çelik in [bpo-29418](#).)

6.4 math

- Add `math.exp2()`: return 2 raised to the power of x. (Contributed by Gideon Mitchell in [bpo-45917](#).)
- Add `math.cbrt()`: return the cube root of x. (Contributed by Ajith Ramachandran in [bpo-44357](#).)
- The behaviour of two `math.pow()` corner cases was changed, for consistency with the IEEE 754 specification. The operations `math.pow(0.0, -math.inf)` and `math.pow(-0.0, -math.inf)` now return `inf`. Previously they raised `ValueError`. (Contributed by Mark Dickinson in [bpo-44339](#).)

6.5 operator

- A new function `operator.call` has been added, such that `operator.call(obj, *args, **kwargs) == obj(*args, **kwargs)`. (Contributed by Antony Lee in [bpo-44019](#).)

6.6 os

- On Windows, `os.urandom()` now uses `BCryptGenRandom()`, instead of `CryptGenRandom()` which is deprecated. (Contributed by Dong-hee Na in [bpo-44611](#).)

6.7 socket

- Add CAN Socket support for NetBSD. (Contributed by Thomas Klausner in [bpo-30512](#).)

6.8 sqlite3

- You can now disable the authorizer by passing `None` to `set_authorizer()`. (Contributed by Erlend E. Aasland in [bpo-44491](#).)
- Collation name `create_collation()` can now contain any Unicode character. Collation names with invalid characters now raise `UnicodeEncodeError` instead of `sqlite3.ProgrammingError`. (Contributed by Erlend E. Aasland in [bpo-44688](#).)
- `sqlite3` exceptions now include the SQLite extended error code as `sqlite_errorcode` and the SQLite error name as `sqlite_errormsg`. (Contributed by Aviv Palivoda, Daniel Shahaf, and Erlend E. Aasland in [bpo-16379](#) and [bpo-24139](#).)
- Add `setlimit()` and `getlimit()` to `sqlite3.Connection` for setting and getting SQLite limits by connection basis. (Contributed by Erlend E. Aasland in [bpo-45243](#).)
- `sqlite3` now sets `sqlite3.threadafety` based on the default threading mode the underlying SQLite library has been compiled with. (Contributed by Erlend E. Aasland in [bpo-45613](#).)
- `sqlite3` C callbacks now use unraisable exceptions if callback tracebacks are enabled. Users can now register an unraisable hook handler to improve their debug experience. (Contributed by Erlend E. Aasland in [bpo-45828](#).)
- Fetch across rollback no longer raises `InterfaceError`. Instead we leave it to the SQLite library to handle these cases. (Contributed by Erlend E. Aasland in [bpo-44092](#).)

6.9 sys

- `sys.exc_info()` now derives the `type` and `traceback` fields from the `value` (the exception instance), so when an exception is modified while it is being handled, the changes are reflected in the results of subsequent calls to `exc_info()`. (Contributed by Irit Katriel in [bpo-45711](#).)
- Add `sys.exception()` which returns the active exception instance (equivalent to `sys.exc_info()[1]`). (Contributed by Irit Katriel in [bpo-46328](#).)

6.10 threading

- On Unix, if the `sem_clockwait()` function is available in the C library (glibc 2.30 and newer), the `threading.Lock.acquire()` method now uses the monotonic clock (`time.CLOCK_MONOTONIC`) for the timeout, rather than using the system clock (`time.CLOCK_REALTIME`), to not be affected by system clock changes. (Contributed by Victor Stinner in [bpo-41710](#).)

6.11 time

- On Unix, `time.sleep()` now uses the `clock_nanosleep()` or `nanosleep()` function, if available, which has a resolution of 1 nanosecond (10^{-9} seconds), rather than using `select()` which has a resolution of 1 microsecond (10^{-6} seconds). (Contributed by Benjamin Szöke and Victor Stinner in [bpo-21302](#).)
- On Windows 8.1 and newer, `time.sleep()` now uses a waitable timer based on [high-resolution timers](#) which has a resolution of 100 nanoseconds (10^{-7} seconds). Previously, it had a resolution of 1 millisecond (10^{-3} seconds). (Contributed by Benjamin Szöke, Dong-hee Na, Eryk Sun and Victor Stinner in [bpo-21302](#) and [bpo-45429](#).)

6.12 unicodedata

- The Unicode database has been updated to version 14.0.0. ([bpo-45190](#)).

6.13 fcntl

- On FreeBSD, the `F_DUP2FD` and `F_DUP2FD_CLOEXEC` flags respectively are supported, the former equals to `dup2` usage while the latter set the `FD_CLOEXEC` flag in addition.

7 Optimizations

- Compiler now optimizes simple C-style formatting with literal format containing only format codes `%s`, `%r` and `%a` and makes it as fast as corresponding f-string expression. (Contributed by Serhiy Storchaka in [bpo-28307](#).)
- “Zero-cost” exceptions are implemented. The cost of `try` statements is almost eliminated when no exception is raised. (Contributed by Mark Shannon in [bpo-40222](#).)
- Method calls with keywords are now faster due to bytecode changes which avoid creating bound method instances. Previously, this optimization was applied only to method calls with purely positional arguments. (Contributed by Ken Jin and Mark Shannon in [bpo-26110](#), based on ideas implemented in PyPy.)
- Pure ASCII strings are now normalized in constant time by `unicodedata.normalize()`. (Contributed by Dong-hee Na in [bpo-44987](#).)
- `math` functions `comb()` and `perm()` are now up to 10 times or more faster for large arguments (the speed up is larger for larger k). (Contributed by Serhiy Storchaka in [bpo-37295](#).)
- Dict don't store hash value when all inserted keys are Unicode objects. This reduces dict size. For example, `sys.getsizeof(dict.fromkeys("abcdefg"))` becomes 272 bytes from 352 bytes on 64bit platform. (Contributed by Inada Naoki in [bpo-46845](#).)

8 CPython bytecode changes

- Replaced all numeric `BINARY_*` and `INPLACE_*` instructions with a single `BINARY_OP` implementation.
- Replaced the three call instructions: `CALL_FUNCTION`, `CALL_FUNCTION_KW` and `CALL_METHOD` with `PUSH_NULL`, `PRECALL`, `CALL`, and `KW_NAMES`. This decouples the argument shifting for methods from the handling of keyword arguments and allows better specialization of calls.
- Removed `COPY_DICT_WITHOUT_KEYS` and `GEN_START`.

- `MATCH_CLASS` and `MATCH_KEYS` no longer push an additional boolean value indicating whether the match succeeded or failed. Instead, they indicate failure with `None` (where a tuple of extracted values would otherwise be).
- Replace several stack manipulation instructions (`DUP_TOP`, `DUP_TOP_TWO`, `ROT_TWO`, `ROT_THREE`, `ROT_FOUR`, and `ROT_N`) with new `COPY` and `SWAP` instructions.
- Add `POP_JUMP_IF_NOT_NONE` and `POP_JUMP_IF_NONE` opcodes to speed up conditional jumps.
- `JUMP_IF_NOT_EXC_MATCH` no longer pops the active exception.

9 Deprecated

- The `lib2to3` package and `2to3` tool are now deprecated and may not be able to parse Python 3.10 or newer. See the [PEP 617](#) (New PEG parser for CPython). (Contributed by Victor Stinner in [bpo-40360](#).)
- `webbrowser.MacOSX` is deprecated and will be removed in Python 3.13. It is untested and undocumented and also not used by `webbrowser` itself. (Contributed by Dong-hee Na in [bpo-42255](#).)
- The behavior of returning a value from a `TestCase` and `IsolatedAsyncioTestCase` test methods (other than the default `None` value), is now deprecated.
- Deprecated the following `unittest` functions, scheduled for removal in Python 3.13:

- `unittest.findTestCases()`
- `unittest.makeSuite()`
- `unittest.getTestCaseNames()`

Use `TestLoader` method instead:

- `unittest.TestLoader.loadTestsFromModule()`
- `unittest.TestLoader.loadTestsFromTestCase()`
- `unittest.TestLoader.getTestCaseNames()`

(Contributed by Erlend E. Aasland in [bpo-5846](#).)

- The `turtle.RawTurtle.settiltangle()` is deprecated since Python 3.1, it now emits a deprecation warning and will be removed in Python 3.13. Use `turtle.RawTurtle.tiltangle()` instead (it was earlier incorrectly marked as deprecated, its docstring is now corrected). (Contributed by Hugo van Kemenade in [bpo-45837](#).)
- The delegation of `int()` to `__trunc__()` is now deprecated. Calling `int(a)` when `type(a)` implements `__trunc__()` but not `__int__()` or `__index__()` now raises a `DeprecationWarning`. (Contributed by Zackery Spytz in [bpo-44977](#).)
- The following have been deprecated in `configparser` since Python 3.2. Their deprecation warnings have now been updated to note they will be removed in Python 3.12:
 - the `configparser.SafeConfigParser` class
 - the `configparser.ParsingError.filename` property
 - the `configparser.ParsingError.readfp()` method

(Contributed by Hugo van Kemenade in [bpo-45173](#).)

- The `locale.getdefaultlocale()` function is deprecated and will be removed in Python 3.13. Use `locale.setlocale()`, `locale.getpreferredencoding(False)` and `locale.getlocale()` functions instead. (Contributed by Victor Stinner in [bpo-46659](#).)

10 Removed

- `smtpd.MailmanProxy` is now removed as it is unusable without an external module, `mailman`. (Contributed by Dong-hee Na in [bpo-35800](#).)
- The `binhex` module, deprecated in Python 3.9, is now removed. The following `binascii` functions, deprecated in Python 3.9, are now also removed:
 - `a2b_hqx()`, `b2a_hqx()`;
 - `rlecode_hqx()`, `rledecode_hqx()`.

The `binascii.crc_hqx()` function remains available.

(Contributed by Victor Stinner in [bpo-45085](#).)

- The `distutils.bdist_msi` command, deprecated in Python 3.9, is now removed. Use `bdist_wheel` (wheel packages) instead. (Contributed by Hugo van Kemenade in [bpo-45124](#).)
- Due to significant security concerns, the `reuse_address` parameter of `asyncio.loop.create_datagram_endpoint()`, disabled in Python 3.9, is now entirely removed. This is because of the behavior of the socket option `SO_REUSEADDR` in UDP. (Contributed by Hugo van Kemenade in [bpo-45129](#).)
- Removed `__getitem__()` methods of `xml.dom.pulldom.DOMEvntStream`, `wsgiref.util.FileWrapper` and `fileinput.FileInput`, deprecated since Python 3.9. (Contributed by Hugo van Kemenade in [bpo-45132](#).)
- The following deprecated functions and methods are removed in the `gettext` module: `lgettext()`, `ldgettext()`, `lngettext()` and `ldngettext()`.
Function `bind_textdomain_codeset()`, methods `output_charset()` and `set_output_charset()`, and the `codeset` parameter of functions `translation()` and `install()` are also removed, since they are only used for the `l*gettext()` functions. (Contributed by Dong-hee Na and Serhiy Storchaka in [bpo-44235](#).)
- The `@asyncio.coroutine` decorator enabling legacy generator-based coroutines to be compatible with `async/await` code. The function has been deprecated since Python 3.8 and the removal was initially scheduled for Python 3.10. Use `async def` instead. (Contributed by Illia Volochii in [bpo-43216](#).)
- `asyncio.coroutines.CoroWrapper` used for wrapping legacy generator-based coroutine objects in the debug mode. (Contributed by Illia Volochii in [bpo-43216](#).)
- Removed the deprecated `split()` method of `_tkinter.TkappType`. (Contributed by Erlend E. Aasland in [bpo-38371](#).)

- Removed from the `inspect` module:
 - the `getargspec` function, deprecated since Python 3.0; use `inspect.signature()` or `inspect.getfullargspec()` instead.
 - the `formatargspec` function, deprecated since Python 3.5; use the `inspect.signature()` function and `Signature` object directly.
 - the undocumented `Signature.from_builtin` and `Signature.from_function` functions, deprecated since Python 3.5; use the `Signature.from_callable()` method instead.

(Contributed by Hugo van Kemenade in [bpo-45320](#).)

- Remove namespace package support from `unittest` discovery. It was introduced in Python 3.4 but has been broken since Python 3.7. (Contributed by Inada Naoki in [bpo-23882](#).)

- Remove `__class_getitem__` method from `pathlib.PurePath`, because it was not used and added by mistake in previous versions. (Contributed by Nikita Sobolev in [bpo-46483](#).)
- Remove the undocumented private `float.__set_format__()` method, previously known as `float.__setformat__()` in Python 3.7. Its docstring said: “You probably don’t want to use this function. It exists mainly to be used in Python’s test suite.” (Contributed by Victor Stinner in [bpo-46852](#).)

11 Porting to Python 3.11

This section lists previously described changes and other bugfixes that may require changes to your code.

11.1 Changes in the Python API

- Prohibited passing `non-concurrent.futures.ThreadPoolExecutor` executors to `loop.set_default_executor()` following a deprecation in Python 3.8. (Contributed by Illia Volochii in [bpo-43234](#).)
- `open()`, `io.open()`, `codecs.open()` and `fileinput.FileInput` no longer accept `'U'` (“universal newline”) in the file mode. This flag was deprecated since Python 3.3. In Python 3, the “universal newline” is used by default when a file is open in text mode. The `newline` parameter of `open()` controls how universal newlines works. (Contributed by Victor Stinner in [bpo-37330](#).)
- The `pdb` module now reads the `.pdbrc` configuration file with the `'utf-8'` encoding. (Contributed by Srinivas Reddy Thatiparthi ([@sreemurthy](#)) in [bpo-41137](#).)
- When sorting using tuples as keys, the order of the result may differ from earlier releases if the tuple elements don’t define a total ordering (see [expressions-value-comparisons](#) for information on total ordering). It’s generally true that the result of sorting simply isn’t well-defined in the absence of a total ordering on list elements.
- `calendar`: The `calendar.LocaleTextCalendar` and `calendar.LocaleHTMLCalendar` classes now use `locale.getlocale()`, instead of using `locale.getdefaultlocale()`, if no locale is specified. (Contributed by Victor Stinner in [bpo-46659](#).)

12 Build Changes

- Building Python now requires a C11 compiler without optional C11 features. (Contributed by Victor Stinner in [bpo-46656](#).)
- CPython can now be built with the ThinLTO option via `--with-lto=thin`. (Contributed by Dong-hee Na and Brett Holman in [bpo-44340](#).)
- `libpython` is no longer linked against `libcrypt`. (Contributed by Mike Gilbert in [bpo-45433](#).)
- Building Python now requires a C99 `<math.h>` header file providing the following functions: `copysign()`, `hypot()`, `isfinite()`, `isinf()`, `isnan()`, `round()`. (Contributed by Victor Stinner in [bpo-45440](#).)
- Building Python now requires a C99 `<math.h>` header file providing a NAN constant, or the `__builtin_nan()` built-in function. (Contributed by Victor Stinner in [bpo-46640](#).)
- Building Python now requires support for floating point Not-a-Number (NaN): remove the `Py_NO_NAN` macro. (Contributed by Victor Stinner in [bpo-46656](#).)
- Freelists for object structs can now be disabled. A new **configure** option `--without-freelists` can be used to disable all freelists except empty tuple singleton. (Contributed by Christian Heimes in [bpo-45522](#).)

- `Modules/Setup` and `Modules/makesetup` have been improved and tied up. Extension modules can now be built through `makesetup`. All except some test modules can be linked statically into main binary or library. (Contributed by Brett Cannon and Christian Heimes in [bpo-45548](#), [bpo-45570](#), [bpo-45571](#), and [bpo-43974](#).)
- Build dependencies, compiler flags, and linker flags for most `stdlib` extension modules are now detected by **configure**. `libffi`, `libnsl`, `libsqlite3`, `zlib`, `bzip2`, `liblzma`, `libcrypt`, and `uuid` flags are detected by `pkg-config` (when available). (Contributed by Christian Heimes and Erlend Egeberg Aasland in [bpo-bpo-45847](#), [bpo-45747](#), and [bpo-45763](#).)
- CPython now has experimental support for cross compiling to WebAssembly platform `wasm32-emscripten`. The effort is inspired by previous work like Pyodide. (Contributed by Christian Heimes and Ethan Smith in [bpo-40280](#).)
- CPython will now use 30-bit digits by default for the Python `int` implementation. Previously, the default was to use 30-bit digits on platforms with `SIZEOF_VOID_P >= 8`, and 15-bit digits otherwise. It's still possible to explicitly request use of 15-bit digits via either the `--enable-big-digits` option to the configure script or (for Windows) the `PYLONG_BITS_IN_DIGIT` variable in `PC/pyconfig.h`, but this option may be removed at some point in the future. (Contributed by Mark Dickinson in [bpo-45569](#).)

13 C API Changes

- `PyErr_SetExcInfo()` no longer uses the `type` and `traceback` arguments, the interpreter now derives those values from the exception instance (the `value` argument). The function still steals references of all three arguments. (Contributed by Irit Katriel in [bpo-45711](#).)
- `PyErr_GetExcInfo()` now derives the `type` and `traceback` fields of the result from the exception instance (the `value` field). (Contributed by Irit Katriel in [bpo-45711](#).)
- `_frozen` has a new `is_package` field to indicate whether or not the frozen module is a package. Previously, a negative value in the `size` field was the indicator. Now only non-negative values be used for `size`. (Contributed by Kumar Aditya in [bpo-46608](#).)

13.1 New Features

- Add a new `PyType_GetName()` function to get type's short name. (Contributed by Hai Shi in [bpo-42035](#).)
- Add a new `PyType_GetQualName()` function to get type's qualified name. (Contributed by Hai Shi in [bpo-42035](#).)
- Add new `PyThreadState_EnterTracing()` and `PyThreadState_LeaveTracing()` functions to the limited C API to suspend and resume tracing and profiling. (Contributed by Victor Stinner in [bpo-43760](#).)
- Added the `Py_Version` constant which bears the same value as `PY_VERSION_HEX`. (Contributed by Gabriele N. Tornaletta in [bpo-43931](#).)
- `Py_buffer` and APIs are now part of the limited API and the stable ABI:
 - `PyObject_CheckBuffer()`
 - `PyObject_GetBuffer()`
 - `PyBuffer_GetPointer()`
 - `PyBuffer_SizeFromFormat()`
 - `PyBuffer_ToContiguous()`
 - `PyBuffer_FromContiguous()`

- PyBuffer_CopyData()
- PyBuffer_IsContiguous()
- PyBuffer_FillContiguousStrides()
- PyBuffer_FillInfo()
- PyBuffer_Release()
- PyMemoryView_FromBuffer()
- bf_getbuffer and bf_releasebuffer type slots

(Contributed by Christian Heimes in [bpo-45459](#).)

- Added the `PyType_GetModuleByDef` function, used to get the module in which a method was defined, in cases where this information is not available directly (via `PyCMethod`). (Contributed by Petr Viktorin in [bpo-46613](#).)

13.2 Porting to Python 3.11

- The old trashcan macros (`Py_TRASHCAN_SAFE_BEGIN`/`Py_TRASHCAN_SAFE_END`) are now deprecated. They should be replaced by the new macros `Py_TRASHCAN_BEGIN` and `Py_TRASHCAN_END`.

A `tp_dealloc` function that has the old macros, such as:

```
static void
mytype_dealloc(mytype *p)
{
    PyObject_GC_UnTrack(p);
    Py_TRASHCAN_SAFE_BEGIN(p);
    ...
    Py_TRASHCAN_SAFE_END
}
```

should migrate to the new macros as follows:

```
static void
mytype_dealloc(mytype *p)
{
    PyObject_GC_UnTrack(p);
    Py_TRASHCAN_BEGIN(p, mytype_dealloc)
    ...
    Py_TRASHCAN_END
}
```

Note that `Py_TRASHCAN_BEGIN` has a second argument which should be the deallocation function it is in.

To support older Python versions in the same codebase, you can define the following macros and use them throughout the code (credit: these were copied from the `mypy` codebase):

```
#if PY_MAJOR_VERSION >= 3 && PY_MINOR_VERSION >= 8
# define CPy_TRASHCAN_BEGIN(op, dealloc) Py_TRASHCAN_BEGIN(op, dealloc)
# define CPy_TRASHCAN_END(op) Py_TRASHCAN_END
#else
# define CPy_TRASHCAN_BEGIN(op, dealloc) Py_TRASHCAN_SAFE_BEGIN(op)
# define CPy_TRASHCAN_END(op) Py_TRASHCAN_SAFE_END(op)
#endif
```

- The `PyType_Ready()` function now raises an error if a type is defined with the `Py_TPFLAGS_HAVE_GC` flag set but has no traverse function (`PyTypeObject.tp_traverse`). (Contributed by Victor Stinner in [bpo-44263](#).)
- Heap types with the `Py_TPFLAGS_IMMUTABLETYPE` flag can now inherit the **PEP 590** vectorcall protocol. Previously, this was only possible for static types. (Contributed by Erlend E. Aasland in [bpo-43908](#))
- Since `Py_TYPE()` is changed to a inline static function, `Py_TYPE(obj) = new_type` must be replaced with `Py_SET_TYPE(obj, new_type)`: see the `Py_SET_TYPE()` function (available since Python 3.9). For backward compatibility, this macro can be used:

```
#if PY_VERSION_HEX < 0x030900A4 && !defined(Py_SET_TYPE)
static inline void _Py_SET_TYPE(PyObject *ob, PyTypeObject *type)
{ ob->ob_type = type; }
#define Py_SET_TYPE(ob, type) _Py_SET_TYPE((PyObject*)(ob), type)
#endif
```

(Contributed by Victor Stinner in [bpo-39573](#).)

- Since `Py_SIZE()` is changed to a inline static function, `Py_SIZE(obj) = new_size` must be replaced with `Py_SET_SIZE(obj, new_size)`: see the `Py_SET_SIZE()` function (available since Python 3.9). For backward compatibility, this macro can be used:

```
#if PY_VERSION_HEX < 0x030900A4 && !defined(Py_SET_SIZE)
static inline void _Py_SET_SIZE(PyVarObject *ob, Py_ssize_t size)
{ ob->ob_size = size; }
#define Py_SET_SIZE(ob, size) _Py_SET_SIZE((PyVarObject*)(ob), size)
#endif
```

(Contributed by Victor Stinner in [bpo-39573](#).)

- `<Python.h>` no longer includes the header files `<stdlib.h>`, `<stdio.h>`, `<errno.h>` and `<string.h>` when the `Py_LIMITED_API` macro is set to `0x030b0000` (Python 3.11) or higher. C extensions should explicitly include the header files after `#include <Python.h>`. (Contributed by Victor Stinner in [bpo-45434](#).)
- The non-limited API files `cellobject.h`, `classobject.h`, `context.h`, `funcobject.h`, `genobject.h` and `longintrepr.h` have been moved to the `Include/cpython` directory. Moreover, the `eval.h` header file was removed. These files must not be included directly, as they are already included in `Python.h`: Include Files. If they have been included directly, consider including `Python.h` instead. (Contributed by Victor Stinner in [bpo-35134](#).)
- The `PyUnicode_CHECK_INTERNED()` macro has been excluded from the limited C API. It was never usable there, because it used internal structures which are not available in the limited C API. (Contributed by Victor Stinner in [bpo-46007](#).)
- The `PyFrameObject` structure member has been moved to the internal C API headers.

While the documentation notes that the `PyFrameObject` fields are subject to change at any time, they have been stable for a long time and were used in several popular extensions.

In Python 3.11, the frame struct was reorganized to allow performance optimizations. Some fields were removed entirely, as they were details of the old implementation.

`PyFrameObject` fields:

- `f_back`: use `PyFrame_GetBack()`.
- `f_blockstack`: removed.
- `f_builtins`: use `PyObject_GetAttrString((PyObject*)frame, "f_builtins")`.
- `f_code`: use `PyFrame_GetCode()`.

- f_gen: removed.
- f_globals: use `PyObject_GetAttrString((PyObject*)frame, "f_globals")`.
- f_iblock: removed.
- f_lasti: use `PyObject_GetAttrString((PyObject*)frame, "f_lasti")`. Code using `f_lasti` with `PyCode_Addr2Line()` must use `PyFrame_GetLineNumber()` instead.
- f_lineno: use `PyFrame_GetLineNumber()`
- f_locals: use `PyObject_GetAttrString((PyObject*)frame, "f_locals")`.
- f_stackdepth: removed.
- f_state: no public API (renamed to `f_frame.f_state`).
- f_trace: no public API.
- f_trace_lines: use `PyObject_GetAttrString((PyObject*)frame, "f_trace_lines")` (it also be modified).
- f_trace_opcodes: use `PyObject_GetAttrString((PyObject*)frame, "f_trace_opcodes")` (it also be modified).
- f_localsplus: no public API (renamed to `f_frame.localsplus`).
- f_valstack: removed.

The Python frame object is now created lazily. A side effect is that the `f_back` member must not be accessed directly, since its value is now also computed lazily. The `PyFrame_GetBack()` function must be called instead.

Code defining `PyFrame_GetCode()` on Python 3.8 and older:

```
#if PY_VERSION_HEX < 0x030900B1
static inline PyCodeObject* PyFrame_GetCode(PyFrameObject *frame)
{
    Py_INCREF(frame->f_code);
    return frame->f_code;
}
#endif
```

Code defining `PyFrame_GetBack()` on Python 3.8 and older:

```
#if PY_VERSION_HEX < 0x030900B1
static inline PyFrameObject* PyFrame_GetBack(PyFrameObject *frame)
{
    Py_XINCRREF(frame->f_back);
    return frame->f_back;
}
#endif
```

Or use the [pythoncapi_compat](#) project to get these two functions on older Python versions.

- Changes of the `PyThreadState` structure members:
 - frame: removed, use `PyThreadState_GetFrame()` (function added to Python 3.9 by [bpo-40429](#)).
Warning: the function returns a strong reference, need to call `Py_XDECREF()`.
 - tracing: changed, use `PyThreadState_EnterTracing()` and `PyThreadState_LeaveTracing()` (functions added to Python 3.11 by [bpo-43760](#)).
 - recursion_depth: removed, use `(tstate->recursion_limit - tstate->recursion_remaining)` instead.

- stackcheck_counter: removed.

Code defining PyThreadState_GetFrame () on Python 3.8 and older:

```
#if PY_VERSION_HEX < 0x030900B1
static inline PyFrameObject* PyThreadState_GetFrame(PyThreadState *tstate)
{
    Py_XINCREF(tstate->frame);
    return tstate->frame;
}
#endif
```

Code defining PyThreadState_EnterTracing() and PyThreadState_LeaveTracing() on Python 3.10 and older:

```
#if PY_VERSION_HEX < 0x030B00A2
static inline void PyThreadState_EnterTracing(PyThreadState *tstate)
{
    tstate->tracing++;
    #if PY_VERSION_HEX >= 0x030A00A1
        tstate->cframe->use_tracing = 0;
    #else
        tstate->use_tracing = 0;
    #endif
}

static inline void PyThreadState_LeaveTracing(PyThreadState *tstate)
{
    int use_tracing = (tstate->c_tracefunc != NULL || tstate->c_profilefunc !=
↳ NULL);
    tstate->tracing--;
    #if PY_VERSION_HEX >= 0x030A00A1
        tstate->cframe->use_tracing = use_tracing;
    #else
        tstate->use_tracing = use_tracing;
    #endif
}
#endif
```

Or use the [pythoncapi_compat](#) project to get these functions on old Python functions.

13.3 Deprecated

- Deprecate the following functions to configure the Python initialization:

- PySys_AddWarnOptionUnicode()
- PySys_AddWarnOption()
- PySys_AddXOption()
- PySys_HasWarnOptions()
- Py_SetPath()
- Py_SetProgramName()
- Py_SetPythonHome()
- Py_SetStandardStreamEncoding()

- `_Py_SetProgramFullPath()`

Use the new `PyConfig` API of the Python Initialization Configuration instead ([PEP 587](#)). (Contributed by Victor Stinner in [bpo-44113](#).)

- Deprecate the `ob_shash` member of the `PyBytesObject`. Use `PyObject_Hash()` instead. (Contributed by Inada Naoki in [bpo-46864](#).)

13.4 Removed

- `PyFrame_BlockSetup()` and `PyFrame_BlockPop()` have been removed. (Contributed by Mark Shannon in [bpo-40222](#).)

- Remove the following math macros using the `errno` variable:

- `Py_ADJUST_ERANGE1()`
- `Py_ADJUST_ERANGE2()`
- `Py_OVERFLOWED()`
- `Py_SET_ERANGE_IF_OVERFLOW()`
- `Py_SET_ERRNO_ON_MATH_ERROR()`

(Contributed by Victor Stinner in [bpo-45412](#).)

- Remove `Py_UNICODE_COPY()` and `Py_UNICODE_FILL()` macros, deprecated since Python 3.3. Use `PyUnicode_CopyCharacters()` or `memcpy()` (`wchar_t* string`), and `PyUnicode_Fill()` functions instead. (Contributed by Victor Stinner in [bpo-41123](#).)
- Remove the `pysrhex.h` header file. It only contains private functions. C extensions should only include the main `<Python.h>` header file. (Contributed by Victor Stinner in [bpo-45434](#).)
- Remove the `Py_FORCE_DOUBLE()` macro. It was used by the `Py_IS_INFINITY()` macro. (Contributed by Victor Stinner in [bpo-45440](#).)
- The following items are no longer available when `Py_LIMITED_API` is defined:

- `PyMarshal_WriteLongToFile()`
- `PyMarshal_WriteObjectToFile()`
- `PyMarshal_ReadObjectFromString()`
- `PyMarshal_WriteObjectToString()`
- the `Py_MARSHAL_VERSION` macro

These are not part of the limited API.

(Contributed by Victor Stinner in [bpo-45474](#).)

- Exclude `PyWeakref_GET_OBJECT()` from the limited C API. It never worked since the `PyWeakReference` structure is opaque in the limited C API. (Contributed by Victor Stinner in [bpo-35134](#).)
- Remove the `PyHeapType_GET_MEMBERS()` macro. It was exposed in the public C API by mistake, it must only be used by Python internally. Use the `PyTypeObject.tp_members` member instead. (Contributed by Victor Stinner in [bpo-40170](#).)
- Remove the `HAVE_PY_SET_53BIT_PRECISION` macro (moved to the internal C API). (Contributed by Victor Stinner in [bpo-45412](#).)

Index

E

environment variable
 PYTHONNODEBUGRANGES, 3

P

Python Enhancement Proposals
 PEP 515, 5
 PEP 552, 4
 PEP 587, 16
 PEP 590, 13
 PEP 617, 8
 PEP 657, 3
PYTHONNODEBUGRANGES, 3