

---

# Python support for the Linux perf profiler

Release 3.13.0a1

Guido van Rossum and the Python development team

November 23, 2023

Python Software Foundation  
Email: docs@python.org

## Contents

1	How to enable <code>perf</code> profiling support	4
2	How to obtain the best results	4
	Index	5

---

### author

Pablo Galindo

The Linux `perf` profiler is a very powerful tool that allows you to profile and obtain information about the performance of your application. `perf` also has a very vibrant ecosystem of tools that aid with the analysis of the data that it produces.

The main problem with using the `perf` profiler with Python applications is that `perf` only gets information about native symbols, that is, the names of functions and procedures written in C. This means that the names and file names of Python functions in your code will not appear in the output of `perf`.

Since Python 3.12, the interpreter can run in a special mode that allows Python functions to appear in the output of the `perf` profiler. When this mode is enabled, the interpreter will interpose a small piece of code compiled on the fly before the execution of every Python function and it will teach `perf` the relationship between this piece of code and the associated Python function using `perf` map files.

---

**Note:** Support for the `perf` profiler is currently only available for Linux on select architectures. Check the output of the `configure` build step or check the output of `python -m sysconfig | grep HAVE_PERF_TRAMPOLINE` to see if your system is supported.

---

For example, consider the following script:

```
def foo(n):
    result = 0
    for _ in range(n):
        result += 1
    return result
```

(continues on next page)







## Index

### E

environment variable  
    PYTHONPERFSUPPORT, 4

### P

PYTHONPERFSUPPORT, 4