
Installing Python Modules

Release 2.7.18

**Guido van Rossum
and the Python development team**

maio 07, 2020

**Python Software Foundation
Email: docs@python.org**

| | | |
|----------|---|-----------|
| 1 | Termos chave | 3 |
| 2 | Basic usage | 5 |
| 3 | How do I ...? | 7 |
| 3.1 | ... install <code>pip</code> in versions of Python prior to Python 2.7.9? | 7 |
| 3.2 | ... install packages just for the current user? | 7 |
| 3.3 | ... install scientific Python packages? | 7 |
| 3.4 | ... work with multiple versions of Python installed in parallel? | 8 |
| 4 | Common installation issues | 9 |
| 4.1 | Installing into the system Python on Linux | 9 |
| 4.2 | Pip not installed | 9 |
| 4.3 | Installing binary extensions | 9 |
| A | Glossário | 11 |
| B | Sobre esses documentos | 21 |
| B.1 | Contribuidores da Documentação do Python | 21 |
| C | História e Licença | 23 |
| C.1 | História do software | 23 |
| C.2 | Termos e condições para acessar ou usar Python | 24 |
| C.3 | Licenças e Reconhecimentos para Software Incorporado | 27 |
| D | Copyright | 39 |
| | Índice | 41 |

Email distutils-sig@python.org

Como um projeto popular de desenvolvimento open source, Python tem uma comunidade de apoio ativa de colaboradores e usuários, que também fazem o seu software disponível para outros desenvolvedores de Python para usar sob os termos da licença de código aberto.

Isso permite aos usuários Python compartilhar e colaborar efetivamente, se beneficiando das soluções que outros já tenham criado para os problemas mais comuns(em alguns casos até mesmo os raros), bem como potencialmente contribuindo com suas próprias soluções para o conjunto de soluções comuns.

Este guia cobre a parte do processo de instalação. Para um guia sobre criar e compartilhar seus próprios projetos Python, refira-se à guia de distribuição.

Nota: Para corporações e outros usuários institucionais, esteja ciente que muitas organizações têm suas próprias políticas em relação ao uso e contribuição para o software de código aberto. Por favor, leve em conta essas políticas ao usar as ferramentas de distribuição e instalação fornecidas com o Python.

CAPÍTULO 1

Termos chave

- `pip` is the preferred installer program. Starting with Python 2.7.9, it is included by default with the Python binary installers.
- a virtual environment is a semi-isolated Python environment that allows packages to be installed for use by a particular application, rather than being installed system wide
- `virtualenv` is a third party tools for creating virtual environments, it is defaults to installing `pip` into all created virtual environments.
- the [Python Packaging Index](#) is a public repository of open source licensed packages made available for use by other Python users
- the [Python Packaging Authority](#) are the group of developers and documentation authors responsible for the maintenance and evolution of the standard packaging tools and the associated metadata and file format standards. They maintain a variety of tools, documentation and issue trackers on both [GitHub](#) and [BitBucket](#).
- `distutils` is the original build and distribution system first added to the Python standard library in 1998. While direct use of `distutils` is being phased out, it still laid the foundation for the current packaging and distribution infrastructure, and it not only remains part of the standard library, but its name lives on in other ways (such as the name of the mailing list used to coordinate Python packaging standards development).

CAPÍTULO 2

Basic usage

The standard packaging tools are all designed to be used from the command line.

The following command will install the latest version of a module and its dependencies from the Python Packaging Index:

```
python -m pip install SomePackage
```

Nota: For POSIX users (including Mac OS X and Linux users), the examples in this guide assume the use of a *virtual environment*. You may install `virtualenv` to provide such environments using either `pip` (`pip install virtualenv`) or through your system package manager (commonly called `virtualenv` or `python-virtualenv`).

For Windows users, the examples in this guide assume that the option to adjust the system `PATH` environment variable was selected when installing Python.

It's also possible to specify an exact or minimum version directly on the command line. When using comparator operators such as `>`, `<` or some other special character which get interpreted by shell, the package name and the version should be enclosed within double quotes:

```
python -m pip install SomePackage==1.0.4    # specific version
python -m pip install "SomePackage>=1.0.4"  # minimum version
```

Normally, if a suitable module is already installed, attempting to install it again will have no effect. Upgrading existing modules must be requested explicitly:

```
python -m pip install --upgrade SomePackage
```

More information and resources regarding `pip` and its capabilities can be found in the [Python Packaging User Guide](#).

Ver también:

[Python Packaging User Guide: Installing Python Distribution Packages](#)

Estas são respostas rápidas ou links para algumas tarefas comuns.

3.1 ... install `pip` in versions of Python prior to Python 2.7.9?

Python only started bundling `pip` with Python 2.7.9. For earlier versions, `pip` needs to be “bootstrapped” as described in the Python Packaging User Guide.

Ver também:

[Python Packaging User Guide: Requirements for Installing Packages](#)

3.2 ... install packages just for the current user?

Passing the `--user` option to `python -m pip install` will install a package just for the current user, rather than for all users of the system.

3.3 ... install scientific Python packages?

A number of scientific Python packages have complex binary dependencies, and aren’t currently easy to install using `pip` directly. At this point in time, it will often be easier for users to install these packages by [other means](#) rather than attempting to install them with `pip`.

Ver também:

[Python Packaging User Guide: Installing Scientific Packages](#)

3.4 ... work with multiple versions of Python installed in parallel?

On Linux, Mac OS X and other POSIX systems, use the versioned Python commands in combination with the `-m` switch to run the appropriate copy of `pip`:

```
python2    -m pip install SomePackage # default Python 2
python2.7  -m pip install SomePackage # specifically Python 2.7
python3    -m pip install SomePackage # default Python 3
python3.4  -m pip install SomePackage # specifically Python 3.4
```

(appropriately versioned `pip` commands may also be available)

On Windows, use the `py` Python launcher in combination with the `-m` switch:

```
py -2      -m pip install SomePackage # default Python 2
py -2.7    -m pip install SomePackage # specifically Python 2.7
py -3      -m pip install SomePackage # default Python 3
py -3.4    -m pip install SomePackage # specifically Python 3.4
```

Common installation issues

4.1 Installing into the system Python on Linux

On Linux systems, a Python installation will typically be included as part of the distribution. Installing into this Python installation requires root access to the system, and may interfere with the operation of the system package manager and other components of the system if a component is unexpectedly upgraded using `pip`.

On such systems, it is often better to use a virtual environment or a per-user installation when installing packages with `pip`.

4.2 Pip not installed

It is possible that `pip` does not get installed by default. One potential fix is:

```
python -m ensurepip --default-pip
```

There are also additional resources for [installing pip](#).

4.3 Installing binary extensions

Python has typically relied heavily on source based distribution, with end users being expected to compile extension modules from source as part of the installation process.

With the introduction of support for the binary `wheel` format, and the ability to publish wheels for at least Windows and Mac OS X through the Python Packaging Index, this problem is expected to diminish over time, as users are more regularly able to install pre-built extensions rather than needing to build them themselves.

Some of the solutions for installing [scientific software](#) that is not yet available as pre-built `wheel` files may also help with obtaining other binary extensions without needing to build them locally.

Ver también:

Python Packaging User Guide: Binary Extensions

>>> O prompt padrão do shell interativo do Python. Normalmente visto em exemplos de código que podem ser executados interativamente no interpretador.

... The default Python prompt of the interactive shell when entering code for an indented code block, when within a pair of matching left and right delimiters (parentheses, square brackets, curly braces or triple quotes), or after specifying a decorator.

2to3 Uma ferramenta que tenta converter código Python 2.x em código Python 3.x tratando a maioria das incompatibilidades que podem se detectadas com análise do código-fonte e navegação na árvore sintática.

O 2to3 está disponível na biblioteca padrão como `lib2to3`; um ponto de entrada é disponibilizado como `Tools/scripts/2to3`. Veja `2to3-reference`.

classe base abstrata Abstract base classes complement *duck-typing* by providing a way to define interfaces when other techniques like `hasattr()` would be clumsy or subtly wrong (for example with magic methods). ABCs introduce virtual subclasses, which are classes that don't inherit from a class but are still recognized by `isinstance()` and `issubclass()`; see the `abc` module documentation. Python comes with many built-in ABCs for data structures (in the `collections` module), numbers (in the `numbers` module), and streams (in the `io` module). You can create your own ABCs with the `abc` module.

argumento A value passed to a *function* (or *method*) when calling the function. There are two types of arguments:

- *argumento nomeado*: um argumento precedido por um identificador (por exemplo, `nome=`) na chamada de uma função ou passada como um valor em um dicionário precedido por `**`. Por exemplo, 3 e 5 são ambos argumentos nomeados na chamada da função `complex()` a seguir:

```
complex(real=3, imag=5)
complex(**{'real': 3, 'imag': 5})
```

- *argumento posicional*: um argumento que não é um argumento nomeado. Argumentos posicionais podem aparecer no início da lista de argumentos e/ou podem ser passados com elementos de um *iterável* precedido por `*`. Por exemplo, 3 e 5 são ambos argumentos posicionais nas chamadas a seguir:

```
complex(3, 5)
complex(*(3, 5))
```

Argumentos são atribuídos às variáveis locais nomeadas no corpo da função. Veja a seção [calls](#) para as regras de atribuição. Sintaticamente, qualquer expressão pode ser usada para representar um argumento; avaliada a expressão, o valor é atribuído à variável local.

See also the [parameter](#) glossary entry and the FAQ question on the difference between arguments and parameters.

atributo Um valor associado a um objeto que é referenciado pelo nome separado por um ponto. Por exemplo, se um objeto *o* tem um atributo *a* esse seria referenciado como *o.a*.

BDFL Benevolent Dictator For Life, a.k.a. [Guido van Rossum](#), Python's creator.

objeto byte ou similar An object that supports the buffer protocol, like `str`, `bytearray` or `memoryview`. Bytes-like objects can be used for various operations that expect binary data, such as compression, saving to a binary file or sending over a socket. Some operations need the binary data to be mutable, in which case not all bytes-like objects can apply.

bytecode Python source code is compiled into bytecode, the internal representation of a Python program in the CPython interpreter. The bytecode is also cached in `.pyc` and `.pyo` files so that executing the same file is faster the second time (recompilation from source to bytecode can be avoided). This “intermediate language” is said to run on a [virtual machine](#) that executes the machine code corresponding to each bytecode. Do note that bytecodes are not expected to work between different Python virtual machines, nor to be stable between Python releases.

Uma lista de instruções bytecode pode ser encontrada na documentação para o módulo `dis`.

Classe Um modelo para criação de objetos definidos pelo usuário. Definições de classe normalmente contém definições de métodos que operam sobre instâncias da classe.

classic class Any class which does not inherit from `object`. See [new-style class](#). Classic classes have been removed in Python 3.

coerção The implicit conversion of an instance of one type to another during an operation which involves two arguments of the same type. For example, `int(3.15)` converts the floating point number to the integer 3, but in `3+4.5`, each argument is of a different type (one int, one float), and both must be converted to the same type before they can be added or it will raise a `TypeError`. Coercion between two operands can be performed with the `coerce` built-in function; thus, `3+4.5` is equivalent to calling `operator.add(*coerce(3, 4.5))` and results in `operator.add(3.0, 4.5)`. Without coercion, all arguments of even compatible types would have to be normalized to the same value by the programmer, e.g., `float(3)+4.5` rather than just `3+4.5`.

número complexo Uma extensão ao familiar sistema de números reais em que todos os números são expressos como uma soma de uma parte real e uma parte imaginária. Números imaginários são múltiplos reais da unidade imaginária (a raiz quadrada de -1), normalmente escrita como *i* em matemática ou *j* em engenharia. O Python tem suporte nativo para números complexos, que são escritos com esta última notação; a parte imaginária escrita com um sufixo *j*, p.ex., `3+1j`. Para ter acesso aos equivalentes para números complexos do módulo `math`, utilize `cmath`. O uso de números complexos é uma funcionalidade matemática bastante avançada. Se você não sabe se irá precisar deles, é quase certo que você pode ignorá-los sem problemas.

gerenciador de contexto Um objeto que controla o ambiente visto numa instrução `with` por meio da definição dos métodos `__enter__()` e `__exit__()`. Veja [PEP 343](#).

CPython A implementação canônica da linguagem de programação Python, como disponibilizada pelo [python.org](#). O termo “CPython” é quando for necessário distinguir esta implementação de outras como Jython ou IronPython.

decorador Uma função que retorna outra função, geralmente aplicada como uma transformação de função usando a sintaxe `@wrapper`. Exemplos comuns para decoradores são `classmethod()` e `staticmethod()`.

A sintaxe do decorador é meramente um açúcar-sintático, as duas definições de funções a seguir são semanticamente equivalentes:

```
def f(...):  
    ...  
f = staticmethod(f)
```

(continua na próxima página)

(continuação da página anterior)

```
@staticmethod
def f(...):
    ...
```

O mesmo conceito existe para as classes, mas não é comumente utilizado. Veja a documentação de function definitions e class definitions para obter mais informações sobre decoradores.

descriptor Any *new-style* object which defines the methods `__get__()`, `__set__()`, or `__delete__()`. When a class attribute is a descriptor, its special binding behavior is triggered upon attribute lookup. Normally, using *a.b* to get, set or delete an attribute looks up the object named *b* in the class dictionary for *a*, but if *b* is a descriptor, the respective descriptor method gets called. Understanding descriptors is a key to a deep understanding of Python because they are the basis for many features including functions, methods, properties, class methods, static methods, and reference to super classes.

Para obter mais informações sobre os métodos dos descritores, veja: descriptors.

dicionário An associative array, where arbitrary keys are mapped to values. The keys can be any object with `__hash__()` and `__eq__()` methods. Called a hash in Perl.

visualização de dicionário The objects returned from `dict.viewkeys()`, `dict.viewvalues()`, and `dict.viewitems()` are called dictionary views. They provide a dynamic view on the dictionary's entries, which means that when the dictionary changes, the view reflects these changes. To force the dictionary view to become a full list use `list(dictview)`. See dict-views.

docstring Uma string literal que aparece como primeira expressão numa classe, função ou módulo. Ainda que sejam ignoradas quando a suíte é executada, é reconhecida pelo compilador que a coloca no atributo `__doc__` da classe, função ou módulo que a encapsula. Como ficam disponíveis por meio de introspecção, docstrings são o lugar canônico para documentação do objeto.

duck-typing (tipagem pato) Um estilo de programação que não verifica o tipo do objeto para determinar se ele possui a interface correta; em vez disso, o método ou atributo é simplesmente chamado ou utilizado (“Se se parece com um pato e grasna como um pato, então deve ser um pato.”) Enfatizando interfaces ao invés de tipos específicos, o código bem desenvolvido aprimora sua flexibilidade por permitir substituição polimórfica. Tipagem pato evita necessidade de testes que usem `type()` ou `isinstance()`. (Note, porém, que a tipagem pato pode ser complementada com o uso de *classes base abstratas*.) Ao invés disso, são normalmente empregados testes `hasattr()` ou programação *EAFP*.

EAFP Iniciais da expressão em inglês “easier to ask for forgiveness than permission” que significa “é mais fácil pedir perdão que permissão”. Este estilo de codificação comum em Python assume a existência de chaves ou atributos válidos e captura exceções caso essa premissa se prove falsa. Este estilo limpo e rápido se caracteriza pela presença de várias instruções `try` e `except`. A técnica diverge do estilo *LYBL*, comum em outras linguagens como C, por exemplo.

expressão A piece of syntax which can be evaluated to some value. In other words, an expression is an accumulation of expression elements like literals, names, attribute access, operators or function calls which all return a value. In contrast to many other languages, not all language constructs are expressions. There are also *statements* which cannot be used as expressions, such as `print` or `if`. Assignments are also statements, not expressions.

extension module (módulo de extensão) Um módulo escrito em C ou C++, usando a API C de Python para interagir tanto com código de usuário quanto do núcleo.

objeto arquivo Um objeto que expõe uma API orientada a arquivos (com métodos tais como `read()` ou `write()`) para um recurso subjacente. Dependendo da maneira como foi criado, um objeto arquivo pode mediar o acesso a um arquivo real no disco ou outro tipo de dispositivo de armazenamento ou de comunicação (por exemplo a entrada/saída padrão, buffers em memória, soquetes, pipes, etc.). Objetos arquivo também são chamados de *file-like objects* ou *streams*.

There are actually three categories of file objects: raw binary files, buffered binary files and text files. Their interfaces are defined in the `io` module. The canonical way to create a file object is by using the `open()` function.

objeto como-arquivo Um sinônimo do termo *file object*.

localizador An object that tries to find the *loader* for a module. It must implement a method named `find_module()`. See [PEP 302](#) for details.

divisão pelo piso Divisão matemática que arredonda para baixo para o inteiro mais próximo. O operador de divisão pelo piso é `//`. Por exemplo, a expressão `11 // 4` retorna o valor 2 ao invés de `2.75`, que seria retornado pela divisão de ponto flutuante. Note que `(-11) // 4` é `-3` porque é `-2.75` arredondado *para baixo*. Consulte a [PEP 238](#).

função Uma série de instruções que retorna algum valor para um chamador. Também pode ser passado zero ou mais *argumentos* que podem ser usados na execução do corpo. Veja também *parâmetro*, *métodos* e a seção *function*.

__future__ A pseudo-module which programmers can use to enable new language features which are not compatible with the current interpreter. For example, the expression `11/4` currently evaluates to `2`. If the module in which it is executed had enabled *true division* by executing:

```
from __future__ import division
```

the expression `11/4` would evaluate to `2.75`. By importing the `__future__` module and evaluating its variables, you can see when a new feature was first added to the language and when it will become the default:

```
>>> import __future__
>>> __future__.division
_Feature((2, 2, 0, 'alpha', 2), (3, 0, 0, 'alpha', 0), 8192)
```

garbage collection (coletor de lixo) The process of freeing memory when it is not used anymore. Python performs garbage collection via reference counting and a cyclic garbage collector that is able to detect and break reference cycles.

gerador A function which returns an iterator. It looks like a normal function except that it contains `yield` statements for producing a series of values usable in a `for`-loop or that can be retrieved one at a time with the `next()` function. Each `yield` temporarily suspends processing, remembering the location execution state (including local variables and pending try-statements). When the generator resumes, it picks up where it left off (in contrast to functions which start fresh on every invocation).

generator expression An expression that returns an iterator. It looks like a normal expression followed by a `for` expression defining a loop variable, range, and an optional `if` expression. The combined expression generates values for an enclosing function:

```
>>> sum(i*i for i in range(10))           # sum of squares 0, 1, 4, ... 81
285
```

GIL Veja *global interpreter lock*.

global interpreter lock (bloqueio global do interpretador) O mecanismo utilizado pelo interpretador *CPython* para garantir que apenas uma thread execute o *bytecode* Python por vez. Isto simplifica a implementação do *CPython* ao fazer com que o modelo de objetos (incluindo tipos internos críticos como o `dict`) ganhem segurança implícita contra acesso concorrente. Travar todo o interpretador facilita que o interpretador em si seja multitarefa, às custas de muito do paralelismo já provido por máquinas multiprocessador.

No entanto, alguns módulos de extensão, tanto da biblioteca padrão quanto de terceiros, são desenvolvidos de forma a liberar o GIL ao realizar tarefas computacionalmente muito intensas, como compactação ou cálculos de hash. Além disso, o GIL é sempre liberado nas operações de E/S.

No passado, esforços para criar um interpretador que lidasse plenamente com threads (travando dados compartilhados numa granularidade bem mais fina) não foram bem sucedidos devido a queda no desempenho ao serem

executados em processadores de apenas um núcleo. Acredita-se que superar essa questão de desempenho acabaria tornando a implementação muito mais complicada e bem mais difícil de manter.

hasheável An object is *hashable* if it has a hash value which never changes during its lifetime (it needs a `__hash__()` method), and can be compared to other objects (it needs an `__eq__()` or `__cmp__()` method). Hashable objects which compare equal must have the same hash value.

A hashabilidade faz com que um objeto possa ser usado como chave de um dicionário e como membro de um conjunto, pois estas estruturas de dados utilizam os valores de hash internamente.

All of Python's immutable built-in objects are hashable, while no mutable containers (such as lists or dictionaries) are. Objects which are instances of user-defined classes are hashable by default; they all compare unequal (except with themselves), and their hash value is derived from their `id()`.

IDLE Um ambiente de desenvolvimento integrado para Python. IDLE é um editor básico e um ambiente interpretador que vem junto com a distribuição padrão do Python.

imutável Um objeto que possui um valor fixo. Objetos imutáveis incluem números, strings e tuplas. Estes objetos não podem ser alterados. Um novo objeto deve ser criado se um valor diferente tiver de ser armazenado. Objetos imutáveis têm um papel importante em lugares onde um valor constante de hash seja necessário, como por exemplo uma chave em um dicionário.

integer division Mathematical division discarding any remainder. For example, the expression `11/4` currently evaluates to 2 in contrast to the `2.75` returned by float division. Also called *floor division*. When dividing two integers the outcome will always be another integer (having the floor function applied to it). However, if one of the operands is another numeric type (such as a `float`), the result will be coerced (see *coercion*) to a common type. For example, an integer divided by a float will result in a float value, possibly with a decimal fraction. Integer division can be forced by using the `//` operator instead of the `/` operator. See also *__future__*.

importing (importando) O processo pelo qual o código Python em um módulo é disponibilizado para o código Python em outro módulo.

importer Um objeto que localiza e carrega um módulo; Tanto um *finder* e o objeto *loader*.

interactive Python tem um interpretador interativo, o que significa que você pode digitar comandos e expressões no prompt do interpretador, executá-los imediatamente e ver seus resultados. Apenas execute `python` sem argumentos (possivelmente selecionando-o a partir do menu de aplicações de seu sistema operacional). O interpretador interativo é uma maneira poderosa de testar novas ideias ou aprender mais sobre módulos e pacotes (lembre-se do comando `help(x)`).

interpreted Python é uma linguagem interpretada, em oposição àquelas que são compiladas, embora esta distinção possa ser nebulosa devido à presença do compilador de bytecode. Isto significa que os arquivos-fontes podem ser executados diretamente sem necessidade explícita de se criar um arquivo executável. Linguagens interpretadas normalmente têm um ciclo de desenvolvimento/depuração mais curto que as linguagens compiladas, apesar de seus programas geralmente serem executados mais lentamente. Veja também *interativo*.

iterável An object capable of returning its members one at a time. Examples of iterables include all sequence types (such as `list`, `str`, and `tuple`) and some non-sequence types like `dict` and `file` and objects of any classes you define with an `__iter__()` or `__getitem__()` method. Iterables can be used in a `for` loop and in many other places where a sequence is needed (`zip()`, `map()`, ...). When an iterable object is passed as an argument to the built-in function `iter()`, it returns an iterator for the object. This iterator is good for one pass over the set of values. When using iterables, it is usually not necessary to call `iter()` or deal with iterator objects yourself. The `for` statement does that automatically for you, creating a temporary unnamed variable to hold the iterator for the duration of the loop. See also *iterator*, *sequence*, and *generator*.

iterador An object representing a stream of data. Repeated calls to the iterator's `next()` method return successive items in the stream. When no more data are available a `StopIteration` exception is raised instead. At this point, the iterator object is exhausted and any further calls to its `next()` method just raise `StopIteration` again. Iterators are required to have an `__iter__()` method that returns the iterator object itself so every iterator is also iterable and may be used in most places where other iterables are accepted. One notable exception is code

which attempts multiple iteration passes. A container object (such as a `list`) produces a fresh new iterator each time you pass it to the `iter()` function or use it in a `for` loop. Attempting this with an iterator will just return the same exhausted iterator object used in the previous iteration pass, making it appear like an empty container.

Mais informações podem ser encontradas em `typeiter`.

key function (função chave) Uma função chave ou função colação é algo que retorna um valor utilizado para ordenação ou classificação. Por exemplo, `locale.strxfrm()` é usada para produzir uma chave de ordenação que leva o `locale` em consideração para fins de ordenação.

A number of tools in Python accept key functions to control how elements are ordered or grouped. They include `min()`, `max()`, `sorted()`, `list.sort()`, `heapq.nsmallest()`, `heapq.nlargest()`, and `itertools.groupby()`.

There are several ways to create a key function. For example, the `str.lower()` method can serve as a key function for case insensitive sorts. Alternatively, an ad-hoc key function can be built from a `lambda` expression such as `lambda r: (r[0], r[2])`. Also, the `operator` module provides three key function constructors: `attrgetter()`, `itemgetter()`, and `methodcaller()`. See the Sorting HOW TO for examples of how to create and use key functions.

argumento nomeado Veja o *argument*.

lambda Uma função de linha anônima consistindo de uma única *expression*, que é avaliada quando a função é chamada. A sintaxe para criar uma função `lambda` é `lambda [parameters]: expression`

LBYL Iniciais da expressão em inglês “look before you leap”, que significa algo como “olhe antes de pisar”. Este estilo de codificação testa as pré-condições explicitamente antes de fazer chamadas ou buscas. Este estilo contrasta com a abordagem *EAFP* e é caracterizada pela presença de muitos comandos `if`.

Em um ambiente multithread, a abordagem LBYL pode arriscar a introdução de uma condição de corrida entre “o olhar” e “o pisar”. Por exemplo, o código `if key in mapping: return mapping[key]` pode falhar se outra thread remover `key` do `mapping` após o teste, mas antes da olhada. Esse problema pode ser resolvido com bloqueios ou usando a abordagem *EAFP*.

lista Uma *sequence* embutida no Python. Apesar do seu nome, é mais próximo de um vetor em outras linguagens do que uma lista encadeada, como o acesso aos elementos é da ordem $O(1)$.

list comprehension A compact way to process all or part of the elements in a sequence and return a list with the results. `result = ["0x%02x" % x for x in range(256) if x % 2 == 0]` generates a list of strings containing even hex numbers (0x..) in the range from 0 to 255. The `if` clause is optional. If omitted, all elements in `range(256)` are processed.

loader An object that loads a module. It must define a method named `load_module()`. A loader is typically returned by a *finder*. See **PEP 302** for details.

método mágico Um sinônimo informal para um *special method*.

mapeamento A container object that supports arbitrary key lookups and implements the methods specified in the Mapping or MutableMapping abstract base classes. Examples include `dict`, `collections.defaultdict`, `collections.OrderedDict` and `collections.Counter`.

metaclass A classe de uma classe. Definições de classe criam um nome de classe, um dicionário de classe e uma lista de classes base. A metaclasses é responsável por receber estes três argumentos e criar a classe. A maioria das linguagens de programação orientadas a objetos provê uma implementação default. O que torna o Python especial é o fato de ser possível criar metaclasses personalizadas. A maioria dos usuários nunca vai precisar deste recurso, mas quando houver necessidade, metaclasses possibilitam soluções poderosas e elegantes. Metaclasses têm sido utilizadas para gerar registros de acesso a atributos, para incluir proteção contra acesso concorrente, rastrear a criação de objetos, implementar singletons, dentre muitas outras tarefas.

More information can be found in metaclasses.

method (método) Uma função que é definida dentro do corpo de uma classe. Se chamada como um atributo de uma instância daquela classe, o método receberá a instância do objeto como seu primeiro *argumento* (que comumente é chamado de `self`). Veja *função* e *nested scope*.

method resolution order (ordem de resolução de método) Ordem de resolução de métodos é a ordem em que os membros de uma classe base são buscados durante a pesquisa. Veja *A ordem de resolução de métodos do Python 2.3*.

módulo Um objeto que serve como uma unidade organizacional de código Python. Os módulos têm um namespace contendo objetos Python arbitrários. Os módulos são carregados pelo Python através do processo de *importação*.

Veja também *pacote*.

MRO Veja *method resolution order*.

mutável Objeto mutável é aquele que pode modificar seus valor mas manter seu `id()`. Veja também *immutable*.

tupla nomeada Any tuple-like class whose indexable elements are also accessible using named attributes (for example, `time.localtime()` returns a tuple-like object where the *year* is accessible either with an index such as `t[0]` or with a named attribute like `t.tm_year`).

A named tuple can be a built-in type such as `time.struct_time`, or it can be created with a regular class definition. A full featured named tuple can also be created with the factory function `collections.namedtuple()`. The latter approach automatically provides extra features such as a self-documenting representation like `Employee(name='jones', title='programmer')`.

namespace The place where a variable is stored. Namespaces are implemented as dictionaries. There are the local, global and built-in namespaces as well as nested namespaces in objects (in methods). Namespaces support modularity by preventing naming conflicts. For instance, the functions `__builtin__.open()` and `os.open()` are distinguished by their namespaces. Namespaces also aid readability and maintainability by making it clear which module implements a function. For instance, writing `random.seed()` or `itertools.izip()` makes it clear that those functions are implemented by the `random` and `itertools` modules, respectively.

nested scope (escopo aninhado) The ability to refer to a variable in an enclosing definition. For instance, a function defined inside another function can refer to variables in the outer function. Note that nested scopes work only for reference and not for assignment which will always write to the innermost scope. In contrast, local variables both read and write in the innermost scope. Likewise, global variables read and write to the global namespace.

new-style class (novo estilo de classes) Any class which inherits from `object`. This includes all built-in types like `list` and `dict`. Only new-style classes can use Python's newer, versatile features like `__slots__`, descriptors, properties, and `__getattr__()`.

More information can be found in *newstyle*.

object (objeto) Qualquer dado que tenha estado (atributos ou valores) e comportamento definidos (métodos). Também a última classe base de qualquer *new-style class*.

pacote Um *module* Python é capaz de conter submódulos ou recursivamente, sub-pacotes. Tecnicamente, um pacote é um módulo Python com um atributo `__path__`.

parâmetro A named entity in a *function* (or method) definition that specifies an *argument* (or in some cases, arguments) that the function can accept. There are four types of parameters:

- *posicional-ou-nomeado*: especifica um argumento que pode ser tanto *posicional* quanto *nomeado*. Esse é o tipo padrão de parâmetro, por exemplo *foo* e *bar* a seguir:

```
def func(foo, bar=None): ...
```

- *positional-only*: specifies an argument that can be supplied only by position. Python has no syntax for defining positional-only parameters. However, some built-in functions have positional-only parameters (e.g. `abs()`).

- *var-posicional*: especifica quem uma sequência arbitrária de argumentos posicionais pode ser fornecida (em adição a qualquer argumento posicional já aceito por outros parâmetros). Tal parâmetro pode ser definido colocando um `*` antes do nome, por exemplo *args* a seguir:

```
def func(*args, **kwargs): ...
```

- *var-nomeado*: especifica que, arbitrariamente, muitos argumentos nomeados podem ser fornecidos (em adição a qualquer argumento nomeado já aceito por outros parâmetros). Tal parâmetro pode ser definido colocando-se `**` antes do nome, por exemplo *kwargs* no exemplo acima.

Parâmetros podem especificar tanto argumentos opcionais quanto obrigatórios, assim como valores padrões para alguns argumentos opcionais.

See also the [argument](#) glossary entry, the FAQ question on the difference between arguments and parameters, and the function section.

PEP Proposta de melhoria do Python. Uma PEP é um documento de design que fornece informação para a comunidade Python, ou descreve uma nova funcionalidade para o Python ou seus predecessores ou ambientes. PEPs devem prover uma especificação técnica concisa e um racional para funcionalidades propostas.

PEPs tem a intenção de ser os mecanismos primários para propor novas funcionalidades significativas, para coletar opiniões da comunidade sobre um problema, e para documentar as decisões de design que foram adicionadas ao Python. O autor da PEP é responsável por construir um consenso dentro da comunidade e documentar opiniões dissidentes.

Veja [PEP 1](#).

positional argument (argumento posicional) Veja o [argument](#).

Python 3000 Apelido para a versão do Python 3.x linha de lançamento (cunhado há muito tempo, quando o lançamento da versão 3 era algo em um futuro muito distante.) Esse termo possui a seguinte abreviação: “Py3k”.

Pythonic Uma ideia ou um pedaço de código que segue de perto os idiomas mais comuns da linguagem Python, ao invés de implementar códigos usando conceitos comuns a outros idiomas. Por exemplo, um idioma comum em Python é fazer um loop sobre todos os elementos de uma iterável usando a instrução `for`. Muitas outras linguagens não têm esse tipo de construção, então as pessoas que não estão familiarizadas com o Python usam um contador numérico:

```
for i in range(len(food)):
    print food[i]
```

Ao contrário do método limpo, ou então, Pythonico:

```
for piece in food:
    print piece
```

reference count O número de referências para um objeto. Quando a contagem de referências de um objeto atinge zero, ele é desalocado. Contagem de referências geralmente não é visível no código Python, mas é um elemento chave da implementação *CPython*. O módulo `sys` define a função `getrefcount()` que programadores podem chamar para retornar a contagem de referências para um objeto em particular.

__slots__ A declaration inside a *new-style class* that saves memory by pre-declaring space for instance attributes and eliminating instance dictionaries. Though popular, the technique is somewhat tricky to get right and is best reserved for rare cases where there are large numbers of instances in a memory-critical application.

sequência An *iterable* which supports efficient element access using integer indices via the `__getitem__()` special method and defines a `len()` method that returns the length of the sequence. Some built-in sequence types are `list`, `str`, `tuple`, and `unicode`. Note that `dict` also supports `__getitem__()` and `__len__()`, but is considered a mapping rather than a sequence because the lookups use arbitrary *immutable* keys rather than integers.

fatia An object usually containing a portion of a *sequence*. A slice is created using the subscript notation, `[]` with colons between numbers when several are given, such as in `variable_name[1:3:5]`. The bracket (subscript) notation uses `slice` objects internally (or in older versions, `__getslice__()` and `__setslice__()`).

método especial Um método que é chamado implicitamente pelo Python para executar uma certa operação em um tipo, como uma adição por exemplo. Tais métodos tem nomes iniciando e terminando com dois underscores. Métodos especiais estão documentados em `specialnames`.

instrução Uma instrução é parte de uma suíte (um “bloco” de código). Uma instrução é ou uma *expression* ou uma de várias construções com uma palavra-chave, tal como `if`, `while` ou `for`.

struct sequence A tuple with named elements. Struct sequences expose an interface similar to *named tuple* in that elements can be accessed either by index or as an attribute. However, they do not have any of the named tuple methods like `_make()` or `_asdict()`. Examples of struct sequences include `sys.float_info` and the return value of `os.stat()`.

aspas triplas Uma string que está definida com três ocorrências de aspas duplas (“) ou apóstrofes ('). Enquanto elas não fornecem nenhuma funcionalidade não disponível com strings de aspas simples, elas são úteis para inúmeras razões. Elas permitem que você inclua aspas simples e duplas não encerradas dentro de uma string, e elas podem utilizar múltiplas linhas sem o uso de caractere de continuação, fazendo-as especialmente úteis quando escrevemos documentação em docstrings.

type O tipo de um objeto Python determina qual tipo de objeto ele é; cada objeto tem um tipo. Um tipo de objeto é acessível pelo atributo `__class__` ou pode ser recuperado com `type(obj)`.

Novas linhas universais A manner of interpreting text streams in which all of the following are recognized as ending a line: the Unix end-of-line convention `'\n'`, the Windows convention `'\r\n'`, and the old Macintosh convention `'\r'`. See [PEP 278](#) and [PEP 3116](#), as well as `str.splitlines()` for an additional use.

ambiente virtual Um ambiente de execução isolado que permite usuários Python e aplicações instalarem e atualizarem pacotes Python sem interferir no comportamento de outras aplicações Python em execução no mesmo sistema.

máquina virtual Um computador definido inteiramente em software. A máquina virtual de Python executa o *bytecode* emitido pelo compilador de bytecode.

Zen of Python Lista de princípios de projeto e filosofias do Python que são úteis para a compreensão e uso da linguagem. A lista é exibida quando se digita `“import this”` no console interativo.

Sobre esses documentos

Esses documentos são gerados a partir de [reStructuredText](#) pelo [Sphinx](#), um processador de documentos especificamente escrito para documentação do Python.

O desenvolvimento da documentação e de suas ferramentas é um esforço totalmente voluntário, como o Python em si. Se você quer contribuir, por favor dê uma olhada na página [reporting-bugs](#) para informações sobre como fazer. Novos voluntários são sempre bem vindos!

Agradecimentos especiais para:

- Fred L. Drake, Jr., o criador do primeiro conjunto de ferramentas para documentar o Python e escritor de boa parte do conteúdo;
- O projeto [Docutils](#) para criar [reStructuredText](#) e o pacote [Docutils](#);
- Fredrik Lundh por seu projeto [Referência Alternativa para Python](#) do qual Sphinx teve muitas ideias boas.

B.1 Contribuidores da Documentação do Python

Muitas pessoas tem contribuído para a linguagem Python, sua biblioteca padrão e sua documentação. Veja [Misc/ACKS](#) na distribuição do código do Python para ver uma lista parcial de contribuidores.

Tudo isso só foi possível com o esforço e a contribuição da comunidade Python, por isso temos essa maravilhosa documentação – Obrigado a todos!

História e Licença

C.1 História do software

O Python foi criado no início dos anos 1990 por Guido van Rossum na Stichting Mathematisch Centrum (CWI, veja <https://www.cwi.nl/>) na Holanda como um sucessor de uma linguagem chamada ABC. Guido continua a ser o principal autor de Python, embora inclua muitas contribuições de outros.

Em 1995, Guido continuou seu trabalho em Python na Corporação para Iniciativas Nacionais de Pesquisa (CNRI, veja <https://www.cnri.reston.va.us/>) em Reston, Virgínia, onde lançou várias versões do software.

Em maio de 2000, Guido e a equipe principal de desenvolvimento do Python mudaram-se para o BeOpen.com para formar a equipe BeOpen PythonLabs. Em outubro do mesmo ano, a equipe da PythonLabs mudou para a Digital Creations (agora Zope Corporation; veja <https://www.zope.org/>). Em 2001, formou-se a Python Software Foundation (PSF, ver <https://www.python.org/psf/>), uma organização sem fins lucrativos criada especificamente para possuir propriedade intelectual relacionada a Python. A Zope Corporation é um membro patrocinador do PSF.

Todas as versões do Python são de código aberto (consulte <https://opensource.org/> para a definição de código aberto). Historicamente, a maioria, mas não todas, versões do Python também são compatíveis com GPL; a tabela abaixo resume os vários lançamentos.

| Release | Derivado de | Ano | Proprietário | GPL compatível? |
|-------------|-------------|------------|--------------|-----------------|
| 0.9.0 a 1.2 | n/a | 1991-1995 | CWI | sim |
| 1.3 a 1.5.2 | 1.2 | 1995-1999 | CNRI | sim |
| 1.6 | 1.5.2 | 2000 | CNRI | não |
| 2.0 | 1.6 | 2000 | BeOpen.com | não |
| 1.6.1 | 1.6 | 2001 | CNRI | não |
| 2.1 | 2.0+1.6.1 | 2001 | PSF | não |
| 2.0.1 | 2.0+1.6.1 | 2001 | PSF | sim |
| 2.1.1 | 2.1+2.0.1 | 2001 | PSF | sim |
| 2.1.2 | 2.1.1 | 2002 | PSF | sim |
| 2.1.3 | 2.1.2 | 2002 | PSF | sim |
| 2.2 e acima | 2.1.1 | 2001-agora | PSF | sim |

Nota: Compatível com GPL não significa que estamos distribuindo Python sob a GPL. Todas as licenças do Python, ao contrário da GPL, permitem distribuir uma versão modificada sem fazer alterações em código aberto. As licenças compatíveis com GPL possibilitam combinar o Python com outro software lançado sob a GPL; os outros não.

Graças aos muitos voluntários externos que trabalharam sob a direção de Guido para tornar esses lançamentos possíveis.

C.2 Termos e condições para acessar ou usar Python

C.2.1 PSF LICENSE AGREEMENT FOR PYTHON 2.7.18

1. This LICENSE AGREEMENT is between the Python Software Foundation ("PSF"),
and
the Individual or Organization ("Licensee") accessing and otherwise using
Python
2.7.18 software in source or binary form and its associated documentation.
2. Subject to the terms and conditions of this License Agreement, PSF hereby
grants Licensee a nonexclusive, royalty-free, world-wide license to
reproduce,
analyze, test, perform and/or display publicly, prepare derivative works,
distribute, and otherwise use Python 2.7.18 alone or in any derivative
version, provided, however, that PSF's License Agreement and PSF's notice
of
copyright, i.e., "Copyright © 2001-2020 Python Software Foundation; All
Rights
Reserved" are retained in Python 2.7.18 alone or in any derivative version
prepared by Licensee.
3. In the event Licensee prepares a derivative work that is based on or
incorporates Python 2.7.18 or any part thereof, and wants to make the
derivative work available to others as provided herein, then Licensee
hereby
agrees to include in any such work a brief summary of the changes made to
Python
2.7.18.
4. PSF is making Python 2.7.18 available to Licensee on an "AS IS" basis.
PSF MAKES NO REPRESENTATIONS OR WARRANTIES, EXPRESS OR IMPLIED. BY WAY OF
EXAMPLE, BUT NOT LIMITATION, PSF MAKES NO AND DISCLAIMS ANY REPRESENTATION
OR
WARRANTY OF MERCHANTABILITY OR FITNESS FOR ANY PARTICULAR PURPOSE OR THAT
THE
USE OF PYTHON 2.7.18 WILL NOT INFRINGE ANY THIRD PARTY RIGHTS.
5. PSF SHALL NOT BE LIABLE TO LICENSEE OR ANY OTHER USERS OF PYTHON 2.7.18
FOR ANY INCIDENTAL, SPECIAL, OR CONSEQUENTIAL DAMAGES OR LOSS AS A RESULT
OF
MODIFYING, DISTRIBUTING, OR OTHERWISE USING PYTHON 2.7.18, OR ANY
DERIVATIVE
THEREOF, EVEN IF ADVISED OF THE POSSIBILITY THEREOF.

6. This License Agreement will automatically terminate upon a material breach of its terms and conditions.
7. Nothing in this License Agreement shall be deemed to create any relationship of agency, partnership, or joint venture between PSF and Licensee. This License Agreement does not grant permission to use PSF trademarks or trade name in a trademark sense to endorse or promote products or services of Licensee, or any third party.
8. By copying, installing or otherwise using Python 2.7.18, Licensee agrees to be bound by the terms and conditions of this License Agreement.

C.2.2 ACORDO DE LICENÇA DA BEOPEN.COM PARA PYTHON 2.0

CONTRATO DE LICENÇA DE FONTE ABERTA DO BEOPEN PYTHON VERSÃO 1

1. This LICENSE AGREEMENT is between BeOpen.com ("BeOpen"), having an office at 160 Saratoga Avenue, Santa Clara, CA 95051, and the Individual or Organization ("Licensee") accessing and otherwise using this software in source or binary form and its associated documentation ("the Software").
2. Subject to the terms and conditions of this BeOpen Python License Agreement, BeOpen hereby grants Licensee a non-exclusive, royalty-free, world-wide license to reproduce, analyze, test, perform and/or display publicly, prepare derivative works, distribute, and otherwise use the Software alone or in any derivative version, provided, however, that the BeOpen Python License is retained in the Software, alone or in any derivative version prepared by Licensee.
3. BeOpen is making the Software available to Licensee on an "AS IS" basis. BEOPEN MAKES NO REPRESENTATIONS OR WARRANTIES, EXPRESS OR IMPLIED. BY WAY OF EXAMPLE, BUT NOT LIMITATION, BEOPEN MAKES NO AND DISCLAIMS ANY REPRESENTATION OR WARRANTY OF MERCHANTABILITY OR FITNESS FOR ANY PARTICULAR PURPOSE OR THAT THE USE OF THE SOFTWARE WILL NOT INFRINGE ANY THIRD PARTY RIGHTS.
4. BEOPEN SHALL NOT BE LIABLE TO LICENSEE OR ANY OTHER USERS OF THE SOFTWARE FOR ANY INCIDENTAL, SPECIAL, OR CONSEQUENTIAL DAMAGES OR LOSS AS A RESULT OF USING, MODIFYING OR DISTRIBUTING THE SOFTWARE, OR ANY DERIVATIVE THEREOF, EVEN IF ADVISED OF THE POSSIBILITY THEREOF.
5. This License Agreement will automatically terminate upon a material breach of its terms and conditions.
6. This License Agreement shall be governed by and interpreted in all respects by the law of the State of California, excluding conflict of law provisions. Nothing in this License Agreement shall be deemed to create any relationship of agency, partnership, or joint venture between BeOpen and Licensee. This License Agreement does not grant permission to use BeOpen trademarks or trade names in a trademark sense to endorse or promote products or services of Licensee, or any third party. As an exception, the "BeOpen Python" logos available at

(continua na próxima página)

(continuação da página anterior)

<http://www.pythonlabs.com/logos.html> may be used according to the permissions granted on that web page.

7. By copying, installing or otherwise using the software, Licensee agrees to be bound by the terms and conditions of this License Agreement.

C.2.3 CONTRATO DE LICENÇA DA CNRI PARA O PYTHON 1.6.1

1. This LICENSE AGREEMENT is between the Corporation for National Research Initiatives, having an office at 1895 Preston White Drive, Reston, VA 20191 ("CNRI"), and the Individual or Organization ("Licensee") accessing and otherwise using Python 1.6.1 software in source or binary form and its associated documentation.
2. Subject to the terms and conditions of this License Agreement, CNRI hereby grants Licensee a nonexclusive, royalty-free, world-wide license to reproduce, analyze, test, perform and/or display publicly, prepare derivative works, distribute, and otherwise use Python 1.6.1 alone or in any derivative version, provided, however, that CNRI's License Agreement and CNRI's notice of copyright, i.e., "Copyright © 1995-2001 Corporation for National Research Initiatives; All Rights Reserved" are retained in Python 1.6.1 alone or in any derivative version prepared by Licensee. Alternately, in lieu of CNRI's License Agreement, Licensee may substitute the following text (omitting the quotes): "Python 1.6.1 is made available subject to the terms and conditions in CNRI's License Agreement. This Agreement together with Python 1.6.1 may be located on the Internet using the following unique, persistent identifier (known as a handle): 1895.22/1013. This Agreement may also be obtained from a proxy server on the Internet using the following URL: <http://hdl.handle.net/1895.22/1013>."
3. In the event Licensee prepares a derivative work that is based on or incorporates Python 1.6.1 or any part thereof, and wants to make the derivative work available to others as provided herein, then Licensee hereby agrees to include in any such work a brief summary of the changes made to Python 1.6.1.
4. CNRI is making Python 1.6.1 available to Licensee on an "AS IS" basis. CNRI MAKES NO REPRESENTATIONS OR WARRANTIES, EXPRESS OR IMPLIED. BY WAY OF EXAMPLE, BUT NOT LIMITATION, CNRI MAKES NO AND DISCLAIMS ANY REPRESENTATION OR WARRANTY OF MERCHANTABILITY OR FITNESS FOR ANY PARTICULAR PURPOSE OR THAT THE USE OF PYTHON 1.6.1 WILL NOT INFRINGE ANY THIRD PARTY RIGHTS.
5. CNRI SHALL NOT BE LIABLE TO LICENSEE OR ANY OTHER USERS OF PYTHON 1.6.1 FOR ANY INCIDENTAL, SPECIAL, OR CONSEQUENTIAL DAMAGES OR LOSS AS A RESULT OF MODIFYING, DISTRIBUTING, OR OTHERWISE USING PYTHON 1.6.1, OR ANY DERIVATIVE THEREOF, EVEN IF ADVISED OF THE POSSIBILITY THEREOF.
6. This License Agreement will automatically terminate upon a material breach of its terms and conditions.
7. This License Agreement shall be governed by the federal intellectual property law of the United States, including without limitation the federal copyright law, and, to the extent such U.S. federal law does not apply, by the law of the Commonwealth of Virginia, excluding Virginia's conflict of law provisions. Notwithstanding the foregoing, with regard to derivative works based on Python 1.6.1 that incorporate non-separable material that was previously distributed

(continua na próxima página)

(continuação da página anterior)

under the GNU General Public License (GPL), the law of the Commonwealth of Virginia shall govern this License Agreement only as to issues arising under or with respect to Paragraphs 4, 5, and 7 of this License Agreement. Nothing in this License Agreement shall be deemed to create any relationship of agency, partnership, or joint venture between CNRI and Licensee. This License Agreement does not grant permission to use CNRI trademarks or trade name in a trademark sense to endorse or promote products or services of Licensee, or any third party.

8. By clicking on the "ACCEPT" button where indicated, or by copying, installing or otherwise using Python 1.6.1, Licensee agrees to be bound by the terms and conditions of this License Agreement.

C.2.4 ACORDO DE LICENÇA DA CWI PARA PYTHON 0.9.0 A 1.2

Copyright © 1991 - 1995, Stichting Mathematisch Centrum Amsterdam, The Netherlands. All rights reserved.

Permission to use, copy, modify, and distribute this software and its documentation for any purpose and without fee is hereby granted, provided that the above copyright notice appear in all copies and that both that copyright notice and this permission notice appear in supporting documentation, and that the name of Stichting Mathematisch Centrum or CWI not be used in advertising or publicity pertaining to distribution of the software without specific, written prior permission.

STICHTING MATHEMATISCH CENTRUM DISCLAIMS ALL WARRANTIES WITH REGARD TO THIS SOFTWARE, INCLUDING ALL IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS, IN NO EVENT SHALL STICHTING MATHEMATISCH CENTRUM BE LIABLE FOR ANY SPECIAL, INDIRECT OR CONSEQUENTIAL DAMAGES OR ANY DAMAGES WHATSOEVER RESULTING FROM LOSS OF USE, DATA OR PROFITS, WHETHER IN AN ACTION OF CONTRACT, NEGLIGENCE OR OTHER TORTIOUS ACTION, ARISING OUT OF OR IN CONNECTION WITH THE USE OR PERFORMANCE OF THIS SOFTWARE.

C.3 Licenças e Reconhecimentos para Software Incorporado

Esta seção é uma lista incompleta, mas crescente, de licenças e confirmações para softwares de terceiros incorporados na distribuição do Python.

C.3.1 Mersenne Twister

O módulo `_random` inclui código baseado em um download de <http://www.math.sci.hiroshima-u.ac.jp/~m-mat/MT/MT2002/emt19937ar.html>. A seguir estão os comentários literais do código original:

A C-program for MT19937, with initialization improved 2002/1/26.
Coded by Takuji Nishimura and Makoto Matsumoto.

Before using, initialize the state by using `init_genrand(seed)`
or `init_by_array(init_key, key_length)`.

(continua na próxima página)

(continuação da página anterior)

Copyright (C) 1997 - 2002, Makoto Matsumoto and Takuji Nishimura,
All rights reserved.

Redistribution and use in source and binary forms, with or without
modification, are permitted provided that the following conditions
are met:

1. Redistributions of source code must retain the above copyright
notice, this list of conditions and the following disclaimer.
2. Redistributions in binary form must reproduce the above copyright
notice, this list of conditions and the following disclaimer in the
documentation and/or other materials provided with the distribution.
3. The names of its contributors may not be used to endorse or promote
products derived from this software without specific prior written
permission.

THIS SOFTWARE IS PROVIDED BY THE COPYRIGHT HOLDERS AND CONTRIBUTORS
"AS IS" AND ANY EXPRESS OR IMPLIED WARRANTIES, INCLUDING, BUT NOT
LIMITED TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR
A PARTICULAR PURPOSE ARE DISCLAIMED. IN NO EVENT SHALL THE COPYRIGHT OWNER OR
CONTRIBUTORS BE LIABLE FOR ANY DIRECT, INDIRECT, INCIDENTAL, SPECIAL,
EXEMPLARY, OR CONSEQUENTIAL DAMAGES (INCLUDING, BUT NOT LIMITED TO,
PROCUREMENT OF SUBSTITUTE GOODS OR SERVICES; LOSS OF USE, DATA, OR
PROFITS; OR BUSINESS INTERRUPTION) HOWEVER CAUSED AND ON ANY THEORY OF
LIABILITY, WHETHER IN CONTRACT, STRICT LIABILITY, OR TORT (INCLUDING
NEGLIGENCE OR OTHERWISE) ARISING IN ANY WAY OUT OF THE USE OF THIS
SOFTWARE, EVEN IF ADVISED OF THE POSSIBILITY OF SUCH DAMAGE.

Any feedback is very welcome.

<http://www.math.sci.hiroshima-u.ac.jp/~m-mat/MT/emt.html>

email: m-mat @ math.sci.hiroshima-u.ac.jp (remove space)

C.3.2 Sockets

O módulo `socket` usa as funções `getaddrinfo()` e `getnameinfo()`, que são codificadas em arquivos de origem separados do Projeto WIDE, <http://www.wide.ad.jp/>.

Copyright (C) 1995, 1996, 1997, and 1998 WIDE Project.
All rights reserved.

Redistribution and use in source and binary forms, with or without
modification, are permitted provided that the following conditions
are met:

1. Redistributions of source code must retain the above copyright
notice, this list of conditions and the following disclaimer.
2. Redistributions in binary form must reproduce the above copyright
notice, this list of conditions and the following disclaimer in the
documentation and/or other materials provided with the distribution.
3. Neither the name of the project nor the names of its contributors
may be used to endorse or promote products derived from this software
without specific prior written permission.

(continua na próxima página)

(continuação da página anterior)

```
THIS SOFTWARE IS PROVIDED BY THE PROJECT AND CONTRIBUTORS ``AS IS'' AND
ANY EXPRESS OR IMPLIED WARRANTIES, INCLUDING, BUT NOT LIMITED TO, THE
IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE
ARE DISCLAIMED.  IN NO EVENT SHALL THE PROJECT OR CONTRIBUTORS BE LIABLE
FOR ANY DIRECT, INDIRECT, INCIDENTAL, SPECIAL, EXEMPLARY, OR CONSEQUENTIAL
DAMAGES (INCLUDING, BUT NOT LIMITED TO, PROCUREMENT OF SUBSTITUTE GOODS
OR SERVICES; LOSS OF USE, DATA, OR PROFITS; OR BUSINESS INTERRUPTION)
HOWEVER CAUSED AND ON ANY THEORY OF LIABILITY, WHETHER IN CONTRACT, STRICT
LIABILITY, OR TORT (INCLUDING NEGLIGENCE OR OTHERWISE) ARISING IN ANY WAY
OUT OF THE USE OF THIS SOFTWARE, EVEN IF ADVISED OF THE POSSIBILITY OF
SUCH DAMAGE.
```

C.3.3 Floating point exception control

The source for the `fpectl` module includes the following notice:

```
-----
/                               Copyright (c) 1996.                               \
|                               The Regents of the University of California.          |
|                               All rights reserved.                                |
|                                                                                 |
|  Permission to use, copy, modify, and distribute this software for               |
|  any purpose without fee is hereby granted, provided that this en-               |
|  tire notice is included in all copies of any software which is or               |
|  includes a copy or modification of this software and in all                     |
|  copies of the supporting documentation for such software.                       |
|                                                                                 |
|  This work was produced at the University of California, Lawrence                  |
|  Livermore National Laboratory under contract no. W-7405-ENG-48                  |
|  between the U.S. Department of Energy and The Regents of the                   |
|  University of California for the operation of UC LLNL.                          |
|                                                                                 |
|                               DISCLAIMER                                           |
|                                                                                 |
|  This software was prepared as an account of work sponsored by an                |
|  agency of the United States Government. Neither the United States               |
|  Government nor the University of California nor any of their em-                |
|  ployees, makes any warranty, express or implied, or assumes any                 |
|  liability or responsibility for the accuracy, completeness, or                  |
|  usefulness of any information, apparatus, product, or process                   |
|  disclosed, or represents that its use would not infringe                       |
|  privately-owned rights. Reference herein to any specific commer-                |
|  cial products, process, or service by trade name, trademark,                    |
|  manufacturer, or otherwise, does not necessarily constitute or                  |
|  imply its endorsement, recommendation, or favoring by the United               |
|  States Government or the University of California. The views and                |
|  opinions of authors expressed herein do not necessarily state or                |
|  reflect those of the United States Government or the University                 |
|  of California, and shall not be used for advertising or product                 |
|  \ endorsement purposes.                                                         /
-----
```

C.3.4 MD5 message digest algorithm

The source code for the md5 module contains the following notice:

```
Copyright (C) 1999, 2002 Aladdin Enterprises. All rights reserved.

This software is provided 'as-is', without any express or implied
warranty. In no event will the authors be held liable for any damages
arising from the use of this software.

Permission is granted to anyone to use this software for any purpose,
including commercial applications, and to alter it and redistribute it
freely, subject to the following restrictions:

1. The origin of this software must not be misrepresented; you must not
   claim that you wrote the original software. If you use this software
   in a product, an acknowledgment in the product documentation would be
   appreciated but is not required.
2. Altered source versions must be plainly marked as such, and must not be
   misrepresented as being the original software.
3. This notice may not be removed or altered from any source distribution.

L. Peter Deutsch
ghost@aladdin.com

Independent implementation of MD5 (RFC 1321).

This code implements the MD5 Algorithm defined in RFC 1321, whose
text is available at
    http://www.ietf.org/rfc/rfc1321.txt
The code is derived from the text of the RFC, including the test suite
(section A.5) but excluding the rest of Appendix A. It does not include
any code or documentation that is identified in the RFC as being
copyrighted.

The original and principal author of md5.h is L. Peter Deutsch
<ghost@aladdin.com>. Other authors are noted in the change history
that follows (in reverse chronological order):

2002-04-13 lpd Removed support for non-ANSI compilers; removed
    references to Ghostscript; clarified derivation from RFC 1321;
    now handles byte order either statically or dynamically.
1999-11-04 lpd Edited comments slightly for automatic TOC extraction.
1999-10-18 lpd Fixed typo in header comment (ansi2knr rather than md5);
    added conditionalization for C++ compilation from Martin
    Purschke <purschke@bnl.gov>.
1999-05-03 lpd Original version.
```

C.3.5 Serviços de soquete assíncrono

Os módulos `asyncio` e `asyncore` contêm o seguinte aviso:

```
Copyright 1996 by Sam Rushing
```

```
    All Rights Reserved
```

```
Permission to use, copy, modify, and distribute this software and
its documentation for any purpose and without fee is hereby
granted, provided that the above copyright notice appear in all
copies and that both that copyright notice and this permission
notice appear in supporting documentation, and that the name of Sam
Rushing not be used in advertising or publicity pertaining to
distribution of the software without specific, written prior
permission.
```

```
SAM RUSHING DISCLAIMS ALL WARRANTIES WITH REGARD TO THIS SOFTWARE,
INCLUDING ALL IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS, IN
NO EVENT SHALL SAM RUSHING BE LIABLE FOR ANY SPECIAL, INDIRECT OR
CONSEQUENTIAL DAMAGES OR ANY DAMAGES WHATSOEVER RESULTING FROM LOSS
OF USE, DATA OR PROFITS, WHETHER IN AN ACTION OF CONTRACT,
NEGLIGENCE OR OTHER TORTIOUS ACTION, ARISING OUT OF OR IN
CONNECTION WITH THE USE OR PERFORMANCE OF THIS SOFTWARE.
```

C.3.6 Gerenciamento de cookies

The `Cookie` module contains the following notice:

```
Copyright 2000 by Timothy O'Malley <timo@alum.mit.edu>
```

```
    All Rights Reserved
```

```
Permission to use, copy, modify, and distribute this software
and its documentation for any purpose and without fee is hereby
granted, provided that the above copyright notice appear in all
copies and that both that copyright notice and this permission
notice appear in supporting documentation, and that the name of
Timothy O'Malley not be used in advertising or publicity
pertaining to distribution of the software without specific, written
prior permission.
```

```
Timothy O'Malley DISCLAIMS ALL WARRANTIES WITH REGARD TO THIS
SOFTWARE, INCLUDING ALL IMPLIED WARRANTIES OF MERCHANTABILITY
AND FITNESS, IN NO EVENT SHALL Timothy O'Malley BE LIABLE FOR
ANY SPECIAL, INDIRECT OR CONSEQUENTIAL DAMAGES OR ANY DAMAGES
WHATSOEVER RESULTING FROM LOSS OF USE, DATA OR PROFITS,
WHETHER IN AN ACTION OF CONTRACT, NEGLIGENCE OR OTHER TORTIOUS
ACTION, ARISING OUT OF OR IN CONNECTION WITH THE USE OR
PERFORMANCE OF THIS SOFTWARE.
```

C.3.7 Rastreamento de execução

O módulo `trace` contém o seguinte aviso:

```
portions copyright 2001, Autonomous Zones Industries, Inc., all rights...
err... reserved and offered to the public under the terms of the
Python 2.2 license.
Author: Zooko O'Whielacronx
http://zooko.com/
mailto:zooko@zooko.com

Copyright 2000, Mojam Media, Inc., all rights reserved.
Author: Skip Montanaro

Copyright 1999, Bioreason, Inc., all rights reserved.
Author: Andrew Dalke

Copyright 1995-1997, Automatrix, Inc., all rights reserved.
Author: Skip Montanaro

Copyright 1991-1995, Stichting Mathematisch Centrum, all rights reserved.

Permission to use, copy, modify, and distribute this Python software and
its associated documentation for any purpose without fee is hereby
granted, provided that the above copyright notice appears in all copies,
and that both that copyright notice and this permission notice appear in
supporting documentation, and that the name of neither Automatrix,
Bioreason or Mojam Media be used in advertising or publicity pertaining to
distribution of the software without specific, written prior permission.
```

C.3.8 Funções `UUencode` e `UUdecode`

O módulo `uu` contém o seguinte aviso:

```
Copyright 1994 by Lance Ellinghouse
Cathedral City, California Republic, United States of America.
    All Rights Reserved
Permission to use, copy, modify, and distribute this software and its
documentation for any purpose and without fee is hereby granted,
provided that the above copyright notice appear in all copies and that
both that copyright notice and this permission notice appear in
supporting documentation, and that the name of Lance Ellinghouse
not be used in advertising or publicity pertaining to distribution
of the software without specific, written prior permission.
LANCE ELLINGHOUSE DISCLAIMS ALL WARRANTIES WITH REGARD TO
THIS SOFTWARE, INCLUDING ALL IMPLIED WARRANTIES OF MERCHANTABILITY AND
FITNESS, IN NO EVENT SHALL LANCE ELLINGHOUSE CENTRUM BE LIABLE
FOR ANY SPECIAL, INDIRECT OR CONSEQUENTIAL DAMAGES OR ANY DAMAGES
WHATSOEVER RESULTING FROM LOSS OF USE, DATA OR PROFITS, WHETHER IN AN
ACTION OF CONTRACT, NEGLIGENCE OR OTHER TORTIOUS ACTION, ARISING OUT
OF OR IN CONNECTION WITH THE USE OR PERFORMANCE OF THIS SOFTWARE.

Modified by Jack Jansen, CWI, July 1995:
- Use binascii module to do the actual line-by-line conversion
  between ascii and binary. This results in a 1000-fold speedup. The C
```

(continua na próxima página)

(continuação da página anterior)

```
version is still 5 times faster, though.  
- Arguments more compliant with Python standard
```

C.3.9 Chamadas de Procedimento Remoto XML

The `xmlrpclib` module contains the following notice:

```
The XML-RPC client interface is  
  
Copyright (c) 1999-2002 by Secret Labs AB  
Copyright (c) 1999-2002 by Fredrik Lundh  
  
By obtaining, using, and/or copying this software and/or its  
associated documentation, you agree that you have read, understood,  
and will comply with the following terms and conditions:  
  
Permission to use, copy, modify, and distribute this software and  
its associated documentation for any purpose and without fee is  
hereby granted, provided that the above copyright notice appears in  
all copies, and that both that copyright notice and this permission  
notice appear in supporting documentation, and that the name of  
Secret Labs AB or the author not be used in advertising or publicity  
pertaining to distribution of the software without specific, written  
prior permission.  
  
SECRET LABS AB AND THE AUTHOR DISCLAIMS ALL WARRANTIES WITH REGARD  
TO THIS SOFTWARE, INCLUDING ALL IMPLIED WARRANTIES OF MERCHANT-  
ABILITY AND FITNESS. IN NO EVENT SHALL SECRET LABS AB OR THE AUTHOR  
BE LIABLE FOR ANY SPECIAL, INDIRECT OR CONSEQUENTIAL DAMAGES OR ANY  
DAMAGES WHATSOEVER RESULTING FROM LOSS OF USE, DATA OR PROFITS,  
WHETHER IN AN ACTION OF CONTRACT, NEGLIGENCE OR OTHER TORTIOUS  
ACTION, ARISING OUT OF OR IN CONNECTION WITH THE USE OR PERFORMANCE  
OF THIS SOFTWARE.
```

C.3.10 test_epoll

The `test_epoll` contains the following notice:

```
Copyright (c) 2001-2006 Twisted Matrix Laboratories.  
  
Permission is hereby granted, free of charge, to any person obtaining  
a copy of this software and associated documentation files (the  
"Software"), to deal in the Software without restriction, including  
without limitation the rights to use, copy, modify, merge, publish,  
distribute, sublicense, and/or sell copies of the Software, and to  
permit persons to whom the Software is furnished to do so, subject to  
the following conditions:  
  
The above copyright notice and this permission notice shall be  
included in all copies or substantial portions of the Software.  
  
THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND,  
EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF
```

(continua na próxima página)

(continuação da página anterior)

```
MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE AND
NONINFRINGEMENT. IN NO EVENT SHALL THE AUTHORS OR COPYRIGHT HOLDERS BE
LIABLE FOR ANY CLAIM, DAMAGES OR OTHER LIABILITY, WHETHER IN AN ACTION
OF CONTRACT, TORT OR OTHERWISE, ARISING FROM, OUT OF OR IN CONNECTION
WITH THE SOFTWARE OR THE USE OR OTHER DEALINGS IN THE SOFTWARE.
```

C.3.11 Selezione o kqueue

The select and contains the following notice for the kqueue interface:

```
Copyright (c) 2000 Doug White, 2006 James Knight, 2007 Christian Heimes
All rights reserved.
```

```
Redistribution and use in source and binary forms, with or without
modification, are permitted provided that the following conditions
are met:
```

1. Redistributions of source code must retain the above copyright notice, this list of conditions and the following disclaimer.
2. Redistributions in binary form must reproduce the above copyright notice, this list of conditions and the following disclaimer in the documentation and/or other materials provided with the distribution.

```
THIS SOFTWARE IS PROVIDED BY THE AUTHOR AND CONTRIBUTORS ``AS IS'' AND
ANY EXPRESS OR IMPLIED WARRANTIES, INCLUDING, BUT NOT LIMITED TO, THE
IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE
ARE DISCLAIMED. IN NO EVENT SHALL THE AUTHOR OR CONTRIBUTORS BE LIABLE
FOR ANY DIRECT, INDIRECT, INCIDENTAL, SPECIAL, EXEMPLARY, OR CONSEQUENTIAL
DAMAGES (INCLUDING, BUT NOT LIMITED TO, PROCUREMENT OF SUBSTITUTE GOODS
OR SERVICES; LOSS OF USE, DATA, OR PROFITS; OR BUSINESS INTERRUPTION)
HOWEVER CAUSED AND ON ANY THEORY OF LIABILITY, WHETHER IN CONTRACT, STRICT
LIABILITY, OR TORT (INCLUDING NEGLIGENCE OR OTHERWISE) ARISING IN ANY WAY
OUT OF THE USE OF THIS SOFTWARE, EVEN IF ADVISED OF THE POSSIBILITY OF
SUCH DAMAGE.
```

C.3.12 strtod e dtoa

O arquivo `Python/dtoa.c`, que fornece as funções C `dtoa` e `strtod` para conversão de duplas de C para e de strings, é derivado do arquivo com o mesmo nome de David M. Gay, atualmente disponível em <http://www.netlib.org/fp/>. O arquivo original, conforme recuperado em 16 de março de 2009, contém os seguintes avisos de direitos autorais e de licenciamento:

```
/*****
 *
 * The author of this software is David M. Gay.
 *
 * Copyright (c) 1991, 2000, 2001 by Lucent Technologies.
 *
 * Permission to use, copy, modify, and distribute this software for any
 * purpose without fee is hereby granted, provided that this entire notice
 * is included in all copies of any software which is or includes a copy
 * or modification of this software and in all copies of the supporting
 * documentation for such software.
 */
```

(continua na próxima página)

(continuação da página anterior)

```
* THIS SOFTWARE IS BEING PROVIDED "AS IS", WITHOUT ANY EXPRESS OR IMPLIED
* WARRANTY. IN PARTICULAR, NEITHER THE AUTHOR NOR LUCENT MAKES ANY
* REPRESENTATION OR WARRANTY OF ANY KIND CONCERNING THE MERCHANTABILITY
* OF THIS SOFTWARE OR ITS FITNESS FOR ANY PARTICULAR PURPOSE.
*
*****/
```

C.3.13 OpenSSL

Os módulos `hashlib`, `posix`, `ssl`, `crypt` usam a biblioteca OpenSSL para desempenho adicional se forem disponibilizados pelo sistema operacional. Além disso, os instaladores do Windows e do Mac OS X para Python podem incluir uma cópia das bibliotecas do OpenSSL, portanto incluímos uma cópia da licença do OpenSSL aqui:

LICENSE ISSUES

```
=====
```

The OpenSSL toolkit stays under a dual license, i.e. both the conditions of the OpenSSL License and the original SSLeay license apply to the toolkit. See below for the actual license texts. Actually both licenses are BSD-style Open Source licenses. In case of any license issues related to OpenSSL please contact openssl-core@openssl.org.

OpenSSL License

```
-----
```

```
/* =====
 * Copyright (c) 1998-2008 The OpenSSL Project. All rights reserved.
 *
 * Redistribution and use in source and binary forms, with or without
 * modification, are permitted provided that the following conditions
 * are met:
 *
 * 1. Redistributions of source code must retain the above copyright
 * notice, this list of conditions and the following disclaimer.
 *
 * 2. Redistributions in binary form must reproduce the above copyright
 * notice, this list of conditions and the following disclaimer in
 * the documentation and/or other materials provided with the
 * distribution.
 *
 * 3. All advertising materials mentioning features or use of this
 * software must display the following acknowledgment:
 * "This product includes software developed by the OpenSSL Project
 * for use in the OpenSSL Toolkit. (http://www.openssl.org/)"
 *
 * 4. The names "OpenSSL Toolkit" and "OpenSSL Project" must not be used to
 * endorse or promote products derived from this software without
 * prior written permission. For written permission, please contact
 * openssl-core@openssl.org.
 *
 * 5. Products derived from this software may not be called "OpenSSL"
 * nor may "OpenSSL" appear in their names without prior written
 * permission of the OpenSSL Project.
 *
 * 6. Redistributions of any form whatsoever must retain the following
```

(continua na próxima página)

(continuação da página anterior)

```

*   acknowledgment:
*   "This product includes software developed by the OpenSSL Project
*   for use in the OpenSSL Toolkit (http://www.openssl.org/)"
*
* THIS SOFTWARE IS PROVIDED BY THE OpenSSL PROJECT ``AS IS'' AND ANY
* EXPRESSED OR IMPLIED WARRANTIES, INCLUDING, BUT NOT LIMITED TO, THE
* IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR
* PURPOSE ARE DISCLAIMED.  IN NO EVENT SHALL THE OpenSSL PROJECT OR
* ITS CONTRIBUTORS BE LIABLE FOR ANY DIRECT, INDIRECT, INCIDENTAL,
* SPECIAL, EXEMPLARY, OR CONSEQUENTIAL DAMAGES (INCLUDING, BUT
* NOT LIMITED TO, PROCUREMENT OF SUBSTITUTE GOODS OR SERVICES;
* LOSS OF USE, DATA, OR PROFITS; OR BUSINESS INTERRUPTION)
* HOWEVER CAUSED AND ON ANY THEORY OF LIABILITY, WHETHER IN CONTRACT,
* STRICT LIABILITY, OR TORT (INCLUDING NEGLIGENCE OR OTHERWISE)
* ARISING IN ANY WAY OUT OF THE USE OF THIS SOFTWARE, EVEN IF ADVISED
* OF THE POSSIBILITY OF SUCH DAMAGE.
* =====
*
* This product includes cryptographic software written by Eric Young
* (eay@cryptsoft.com).  This product includes software written by Tim
* Hudson (tjh@cryptsoft.com).
*
*/

```

Original SSLeay License

```

/* Copyright (C) 1995-1998 Eric Young (eay@cryptsoft.com)
* All rights reserved.
*
* This package is an SSL implementation written
* by Eric Young (eay@cryptsoft.com).
* The implementation was written so as to conform with Netscapes SSL.
*
* This library is free for commercial and non-commercial use as long as
* the following conditions are aheared to.  The following conditions
* apply to all code found in this distribution, be it the RC4, RSA,
* lhash, DES, etc., code; not just the SSL code.  The SSL documentation
* included with this distribution is covered by the same copyright terms
* except that the holder is Tim Hudson (tjh@cryptsoft.com).
*
* Copyright remains Eric Young's, and as such any Copyright notices in
* the code are not to be removed.
* If this package is used in a product, Eric Young should be given attribution
* as the author of the parts of the library used.
* This can be in the form of a textual message at program startup or
* in documentation (online or textual) provided with the package.
*
* Redistribution and use in source and binary forms, with or without
* modification, are permitted provided that the following conditions
* are met:
* 1. Redistributions of source code must retain the copyright
*    notice, this list of conditions and the following disclaimer.
* 2. Redistributions in binary form must reproduce the above copyright
*    notice, this list of conditions and the following disclaimer in the
*    documentation and/or other materials provided with the distribution.
* 3. All advertising materials mentioning features or use of this software

```

(continua na próxima página)

(continuação da página anterior)

```

* must display the following acknowledgement:
* "This product includes cryptographic software written by
* Eric Young (eay@cryptsoft.com)"
* The word 'cryptographic' can be left out if the routines from the library
* being used are not cryptographic related :-).
* 4. If you include any Windows specific code (or a derivative thereof) from
* the apps directory (application code) you must include an acknowledgement:
* "This product includes software written by Tim Hudson (tjh@cryptsoft.com)"
*
* THIS SOFTWARE IS PROVIDED BY ERIC YOUNG ``AS IS'' AND
* ANY EXPRESS OR IMPLIED WARRANTIES, INCLUDING, BUT NOT LIMITED TO, THE
* IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE
* ARE DISCLAIMED. IN NO EVENT SHALL THE AUTHOR OR CONTRIBUTORS BE LIABLE
* FOR ANY DIRECT, INDIRECT, INCIDENTAL, SPECIAL, EXEMPLARY, OR CONSEQUENTIAL
* DAMAGES (INCLUDING, BUT NOT LIMITED TO, PROCUREMENT OF SUBSTITUTE GOODS
* OR SERVICES; LOSS OF USE, DATA, OR PROFITS; OR BUSINESS INTERRUPTION)
* HOWEVER CAUSED AND ON ANY THEORY OF LIABILITY, WHETHER IN CONTRACT, STRICT
* LIABILITY, OR TORT (INCLUDING NEGLIGENCE OR OTHERWISE) ARISING IN ANY WAY
* OUT OF THE USE OF THIS SOFTWARE, EVEN IF ADVISED OF THE POSSIBILITY OF
* SUCH DAMAGE.
*
* The licence and distribution terms for any publically available version or
* derivative of this code cannot be changed. i.e. this code cannot simply be
* copied and put under another distribution licence
* [including the GNU Public Licence.]
*/

```

C.3.14 expat

A extensão pyexpat é construída usando uma cópia incluída das fontes de expatriadas, a menos que a compilação esteja configurada `--with-system-expat`:

```

Copyright (c) 1998, 1999, 2000 Thai Open Source Software Center Ltd
and Clark Cooper

Permission is hereby granted, free of charge, to any person obtaining
a copy of this software and associated documentation files (the
"Software"), to deal in the Software without restriction, including
without limitation the rights to use, copy, modify, merge, publish,
distribute, sublicense, and/or sell copies of the Software, and to
permit persons to whom the Software is furnished to do so, subject to
the following conditions:

The above copyright notice and this permission notice shall be included
in all copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND,
EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF
MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE AND NONINFRINGEMENT.
IN NO EVENT SHALL THE AUTHORS OR COPYRIGHT HOLDERS BE LIABLE FOR ANY
CLAIM, DAMAGES OR OTHER LIABILITY, WHETHER IN AN ACTION OF CONTRACT,
TORT OR OTHERWISE, ARISING FROM, OUT OF OR IN CONNECTION WITH THE
SOFTWARE OR THE USE OR OTHER DEALINGS IN THE SOFTWARE.

```

C.3.15 libffi

A extensão `_ctypes` é construída usando uma cópia incluída das fontes `libffi`, a menos que a compilação esteja configurada `--with-system-libffi`:

```
Copyright (c) 1996-2008 Red Hat, Inc and others.

Permission is hereby granted, free of charge, to any person obtaining
a copy of this software and associated documentation files (the
``Software''), to deal in the Software without restriction, including
without limitation the rights to use, copy, modify, merge, publish,
distribute, sublicense, and/or sell copies of the Software, and to
permit persons to whom the Software is furnished to do so, subject to
the following conditions:

The above copyright notice and this permission notice shall be included
in all copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED ``AS IS'', WITHOUT WARRANTY OF ANY KIND,
EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF
MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE AND
NONINFRINGEMENT. IN NO EVENT SHALL THE AUTHORS OR COPYRIGHT
HOLDERS BE LIABLE FOR ANY CLAIM, DAMAGES OR OTHER LIABILITY,
WHETHER IN AN ACTION OF CONTRACT, TORT OR OTHERWISE, ARISING FROM,
OUT OF OR IN CONNECTION WITH THE SOFTWARE OR THE USE OR OTHER
DEALINGS IN THE SOFTWARE.
```

C.3.16 zlib

A extensão `zlib` é construída usando uma cópia incluída das fontes `zlib` se a versão do `zlib` encontrada no sistema for muito antiga para ser usada na construção:

```
Copyright (C) 1995-2010 Jean-loup Gailly and Mark Adler

This software is provided 'as-is', without any express or implied
warranty. In no event will the authors be held liable for any damages
arising from the use of this software.

Permission is granted to anyone to use this software for any purpose,
including commercial applications, and to alter it and redistribute it
freely, subject to the following restrictions:

1. The origin of this software must not be misrepresented; you must not
   claim that you wrote the original software. If you use this software
   in a product, an acknowledgment in the product documentation would be
   appreciated but is not required.

2. Altered source versions must be plainly marked as such, and must not be
   misrepresented as being the original software.

3. This notice may not be removed or altered from any source distribution.

Jean-loup Gailly          Mark Adler
jloup@gzip.org            madler@alumni.caltech.edu
```

APÊNDICE D

Copyright

Python e essa documentação é:

Copyright © 2001-2020 Python Software Foundation. Todos os direitos reservados.

Copyright © 2000 BeOpen.com. Todos os direitos reservados.

Copyright © 1995-2000 Corporation for National Research Initiatives. Todos os direitos reservados.

Copyright © 1991-1995 Stichting Mathematisch Centrum. Todos os direitos reservados.

Veja: *História e Licença* para informações completas de licença e permissões.

Não alfabético

..., [11](#)
2to3, [11](#)
>>>, [11](#)
__future__, [14](#)
__slots__, [18](#)

A

ambiente virtual, [19](#)
argumento, [11](#)
argumento nomeado, [16](#)
aspas triplas, [19](#)
atributo, [12](#)

B

BDFL, [12](#)
bytecode, [12](#)

C

Classe, [12](#)
classe base abstrata, [11](#)
classic class, [12](#)
coerção, [12](#)
CPython, [12](#)

D

decorador, [12](#)
descritor, [13](#)
dicionário, [13](#)
divisão pelo piso, [14](#)
docstring, [13](#)
duck-typing (*tipagem pato*), [13](#)

E

EAFP, [13](#)
expressão, [13](#)
extension module (*módulo de extensão*), [13](#)

F

fatia, [19](#)
função, [14](#)

G

garbage collection (*coletor de lixo*), [14](#)
generator, [14](#)
generator expression, [14](#)
gerador, [14](#)
gerenciador de contexto, [12](#)
GIL, [14](#)
global interpreter lock (*bloqueio global do interpretador*), [14](#)

H

hasheável, [15](#)

I

IDLE, [15](#)
importer, [15](#)
importing (*importando*), [15](#)
imutável, [15](#)
instrução, [19](#)
integer division, [15](#)
interactive, [15](#)
interpreted, [15](#)
iterador, [15](#)
iterável, [15](#)

K

key function (*função chave*), [16](#)

L

lambda, [16](#)
LBYL, [16](#)
list comprehension, [16](#)
lista, [16](#)
loader, [16](#)
localizador, [14](#)

M

- magic
 - method, [16](#)
- mapeamento, [16](#)
- máquina virtual, [19](#)
- metaclass, [16](#)
- method
 - magic, [16](#)
 - special, [19](#)
- method (*método*), [17](#)
- method resolution order (*ordem de resolução de método*), [17](#)
- método especial, [19](#)
- método mágico, [16](#)
- módulo, [17](#)
- MRO, [17](#)
- mutável, [17](#)

N

- namespace, [17](#)
- nested scope (*escopo aninhado*), [17](#)
- new-style class (*novo estilo de classes*), [17](#)
- Novas linhas universais, [19](#)
- número complexo, [12](#)

O

- object (*objeto*), [17](#)
- objeto arquivo, [13](#)
- objeto byte ou similar, [12](#)
- objeto como-arquivo, [14](#)

P

- pacote, [17](#)
- parâmetro, [17](#)
- PEP, [18](#)
- positional argument (*argumento posicional*), [18](#)
- Propostas Estendidas Python
 - PEP 1, [18](#)
 - PEP 238, [14](#)
 - PEP 278, [19](#)
 - PEP 302, [14](#), [16](#)
 - PEP 343, [12](#)
 - PEP 3116, [19](#)
- Python 3000, [18](#)
- Pythonic, [18](#)

R

- reference count, [18](#)

S

- sequência, [18](#)
- special
 - method, [19](#)

- struct sequence, [19](#)

T

- tupla nomeada, [17](#)
- type, [19](#)

V

- visualização de dicionário, [13](#)

Z

- Zen of Python, [19](#)