

---

# What's New in Python

*Yayın 3.13.0rc2*

**A. M. Kuchling**

Eylül 11, 2024

Python Software Foundation  
Email: [docs@python.org](mailto:docs@python.org)

## İçindekiler

<b>1</b>	<b>Summary – Release Highlights</b>	<b>3</b>
<b>2</b>	<b>New Features</b>	<b>5</b>
2.1	A better interactive interpreter . . . . .	5
2.2	Improved error messages . . . . .	6
2.3	Free-threaded CPython . . . . .	7
2.4	An experimental just-in-time (JIT) compiler . . . . .	7
2.5	Defined mutation semantics for <code>locals()</code> . . . . .	8
2.6	Support for mobile platforms . . . . .	9
2.7	Incremental garbage collection . . . . .	9
<b>3</b>	<b>Other Language Changes</b>	<b>9</b>
<b>4</b>	<b>New Modules</b>	<b>11</b>
<b>5</b>	<b>Improved Modules</b>	<b>11</b>
5.1	<code>argparse</code> . . . . .	11
5.2	<code>array</code> . . . . .	11
5.3	<code>ast</code> . . . . .	11
5.4	<code>asyncio</code> . . . . .	12
5.5	<code>base64</code> . . . . .	12
5.6	<code>compileall</code> . . . . .	13
5.7	<code>configparser</code> . . . . .	13
5.8	<code>concurrent.futures</code> . . . . .	13
5.9	<code>configparser</code> . . . . .	13
5.10	<code>copy</code> . . . . .	13
5.11	<code>dbm</code> . . . . .	13
5.12	<code>dis</code> . . . . .	14
5.13	<code>doctest</code> . . . . .	14
5.14	<code>email</code> . . . . .	14
5.15	<code>fractions</code> . . . . .	14
5.16	<code>gc</code> . . . . .	14
5.17	<code>glob</code> . . . . .	15
5.18	<code>importlib</code> . . . . .	15

5.19	io	15
5.20	ipaddress	15
5.21	itertools	16
5.22	marshal	16
5.23	math	16
5.24	mimetypes	16
5.25	mmap	16
5.26	multiprocessing	16
5.27	os	16
5.28	os.path	17
5.29	pathlib	17
5.30	pdb	18
5.31	queue	18
5.32	random	18
5.33	re	18
5.34	shutil	18
5.35	site	18
5.36	sqlite3	18
5.37	ssl	19
5.38	statistics	19
5.39	subprocess	19
5.40	sys	19
5.41	tempfile	20
5.42	time	20
5.43	tkinter	20
5.44	traceback	21
5.45	types	21
5.46	typing	21
5.47	unicodedata	21
5.48	venv	21
5.49	warnings	22
5.50	xml	22
5.51	zipimport	22
<b>6</b>	<b>Optimizations</b>	<b>22</b>
<b>7</b>	<b>Removed Modules And APIs</b>	<b>23</b>
7.1	PEP 594: Remove “dead batteries” from the standard library	23
7.2	2to3	24
7.3	builtins	24
7.4	configparser	24
7.5	importlib.metadata	24
7.6	locale	24
7.7	opcode	24
7.8	pathlib	25
7.9	re	25
7.10	tkinter.tix	25
7.11	turtle	25
7.12	typing	25
7.13	unittest	25
7.14	urllib	26
7.15	webbrowser	26
<b>8</b>	<b>New Deprecations</b>	<b>26</b>

8.1	Pending Removal in Python 3.14	28
8.2	Pending Removal in Python 3.15	29
8.3	Pending Removal in Python 3.16	30
8.4	Pending Removal in Future Versions	30
<b>9</b>	<b>CPython Bytecode Changes</b>	<b>33</b>
<b>10</b>	<b>C API Changes</b>	<b>33</b>
10.1	New Features	33
<b>11</b>	<b>Build Changes</b>	<b>36</b>
<b>12</b>	<b>Porting to Python 3.13</b>	<b>36</b>
12.1	Changes in the Python API	36
12.2	Changes in the C API	37
12.3	Removed C APIs	38
12.4	Deprecated C APIs	40
<b>13</b>	<b>Regression Test Changes</b>	<b>43</b>
	<b>Dizin</b>	<b>44</b>

---

## Editor

Thomas Wouters

This article explains the new features in Python 3.13, compared to 3.12. Python 3.13 will be released on October 1, 2024. For full details, see the changelog.

## Ayrıca bakınız

[PEP 719](#) – Python 3.13 Release Schedule

## Not

Prerelease users should be aware that this document is currently in draft form. It will be updated substantially as Python 3.13 moves towards release, so it's worth checking back even after reading earlier versions.

# 1 Summary – Release Highlights

Python 3.13 will be the latest stable release of the Python programming language, with a mix of changes to the language, the implementation and the standard library. The biggest changes include a new *interactive interpreter*, experimental support for running in a *free-threaded mode* ([PEP 703](#)), and a *Just-In-Time compiler* ([PEP 744](#)).

Error messages continue to improve, with tracebacks now highlighted in color by default. The `locals()` builtin now has *defined semantics* for changing the returned mapping, and type parameters now support default values.

The library changes contain removal of deprecated APIs and modules, as well as the usual improvements in user-friendliness and correctness. Several legacy standard library modules have now *been removed* following their deprecation in Python 3.11 ([PEP 594](#)).

This article doesn't attempt to provide a complete specification of all new features, but instead gives a convenient overview. For full details refer to the documentation, such as the Library Reference and Language Reference. To understand the complete implementation and design rationale for a change, refer to the PEP for a particular new feature; but note that PEPs usually are not kept up-to-date once a feature has been fully implemented. See [Porting to Python 3.13](#) for guidance on upgrading from earlier versions of Python.

---

#### Interpreter improvements:

- A greatly improved *interactive interpreter* and *improved error messages*.
- **PEP 667**: The `locals()` builtin now has *defined semantics* when mutating the returned mapping. Python debuggers and similar tools may now more reliably update local variables in optimized scopes even during concurrent code execution.
- **PEP 703**: CPython 3.13 has experimental support for running with the global interpreter lock disabled. See *Free-threaded CPython* for more details.
- **PEP 744**: A basic *JIT compiler* was added. It is currently disabled by default (though we may turn it on later). Performance improvements are modest – we expect to improve this over the next few releases.
- Color support in the new *interactive interpreter*, as well as in *tracebacks* and *doctest* output. This can be disabled through the `PYTHON_COLORS` and `NO_COLOR` environment variables.

#### Python data model improvements:

- `__static_attributes__` stores the names of attributes accessed through `self.X` in any function in a class body.
- `__firstlineno__` records the first line number of a class definition.

#### Significant improvements in the standard library:

- Add a new `PythonFinalizationError` exception, raised when an operation is blocked during finalization.
- The `argparse` module now supports deprecating command-line options, positional arguments, and subcommands.
- The new functions `base64.z85encode()` and `base64.z85decode()` support encoding and decoding [Z85 data](#).
- The `copy` module now has a `copy.replace()` function, with support for many builtin types and any class defining the `__replace__()` method.
- The `dbm.sqlite3` module is now the default `dbm` backend.
- The `os` module has a suite of new functions for working with Linux's timer notification file descriptors.
- The `random` module now has a command-line interface.

#### Security improvements:

- `ssl.create_default_context()` sets `ssl.VERIFY_X509_PARTIAL_CHAIN` and `ssl.VERIFY_X509_STRICT` as default flags.

#### C API improvements:

- The `Py_mod_gil` slot is now used to indicate that an extension module supports running with the GIL disabled.
- The `PyTime` C API has been added, providing access to system clocks.
- `PyMutex` is a new lightweight mutex that occupies a single byte.

#### New typing features:

- **PEP 696:** Type parameters (`typing.TypeVar`, `typing.ParamSpec`, and `typing.TypeVarTuple`) now support defaults.
- **PEP 702:** The new `warnings.deprecated()` decorator adds support for marking deprecations in the type system.
- **PEP 705:** `typing.ReadOnly` can be used to mark an item of a `typing.TypedDict` as read-only for type checkers.
- **PEP 742:** `typing.TypeIs` provides more intuitive type narrowing behavior, as an alternative to `typing.TypeGuard`.

Platform support:

- **PEP 730:** Apple’s iOS is now an *officially supported platform*, at **tier 3**. Official Android support (**PEP 738**) is in the works as well.
- `wasm32-wasi` is now supported as a **tier 2** platform.
- `wasm32-emscripten` is no longer an officially supported platform.

Important removals:

- **PEP 594:** The remaining 19 “dead batteries” have been removed from the standard library: `aifc`, `audioop`, `cgi`, `cgitb`, `chunk`, `crypt`, `imghdr`, `mailcap`, `msilib`, `nis`, `nntplib`, `ossaudiodev`, `pipes`, `sndhdr`, `spwd`, `sunau`, `telnetlib`, `uu` and `xdrlib`.
- Remove the `2to3` tool and `lib2to3` module (deprecated in Python 3.11).
- Remove the `tkinter.tix` module (deprecated in Python 3.6).
- Remove `locale.resetlocale()`.
- Remove `typing.io` and `typing.re`.
- Remove chained `classmethod` descriptors.

Release schedule changes:

**PEP 602** (“Annual Release Cycle for Python”) has been updated to extend the full support (‘bugfix’) period for new releases to two years. This updated policy means that:

- Python 3.9–3.12 have one and a half years of full support, followed by three and a half years of security fixes.
- Python 3.13 and later have two years of full support, followed by three years of security fixes.

## 2 New Features

### 2.1 A better interactive interpreter

Python now uses a new interactive shell by default, based on code from the [PyPy project](#). When the user starts the REPL from an interactive terminal, the following new features are now supported:

- Multiline editing with history preservation.
- Direct support for REPL-specific commands like `help`, `exit`, and `quit`, without the need to call them as functions.
- Prompts and tracebacks with color enabled by default.
- Interactive help browsing using `F1` with a separate command history.
- History browsing using `F2` that skips output as well as the `>>>` and `...` prompts.



## 2.3 Free-threaded CPython

CPython now has experimental support for running in a free-threaded mode, with the global interpreter lock (GIL) disabled. This is an experimental feature and therefore is not enabled by default. The free-threaded mode requires a different executable, usually called `python3.13t` or `python3.13t.exe`. Pre-built binaries marked as *free-threaded* can be installed as part of the official Windows and macOS installers, or CPython can be built from source with the `--disable-gil` option.

Free-threaded execution allows for full utilization of the available processing power by running threads in parallel on available CPU cores. While not all software will benefit from this automatically, programs designed with threading in mind will run faster on multi-core hardware. **The free-threaded mode is experimental** and work is ongoing to improve it: expect some bugs and a substantial single-threaded performance hit. Free-threaded builds of CPython support optionally running with the GIL enabled at runtime using the environment variable `PYTHON_GIL` or the command-line option `-X gil`.

To check if the current interpreter supports free-threading, `python -VV` and `sys.version` contain “experimental free-threading build”. The new `sys._is_gil_enabled()` function can be used to check whether the GIL is actually disabled in the running process.

C-API extension modules need to be built specifically for the free-threaded build. Extensions that support running with the GIL disabled should use the `Py_mod_gil` slot. Extensions using single-phase init should use `PyUnstable_Module_SetGIL()` to indicate whether they support running with the GIL disabled. Importing C extensions that don’t use these mechanisms will cause the GIL to be enabled, unless the GIL was explicitly disabled with the `PYTHON_GIL` environment variable or the `-X gil=0` option. pip 24.1 or newer is required to install packages with C extensions in the free-threaded build.

### Ayrıca bakınız

**PEP 703** “Making the Global Interpreter Lock Optional in CPython” contains rationale and information surrounding this work.

[Porting Extension Modules to Support Free-Threading](#): A community-maintained porting guide for extension authors.

## 2.4 An experimental just-in-time (JIT) compiler

When CPython is configured and built using the `--enable-experimental-jit` option, a just-in-time (JIT) compiler is added which may speed up some Python programs. On Windows, use `PCbuild/build.bat --experimental-jit` to enable the JIT or `--experimental-jit-interpreter` to enable the Tier 2 interpreter. Build requirements and further supporting information are contained at `Tools/jit/README.md`.

The `--enable-experimental-jit` option takes these (optional) values, defaulting to `yes` if `--enable-experimental-jit` is present without the optional value.

- `no`: Disable the entire Tier 2 and JIT pipeline.
- `yes`: Enable the JIT. To disable the JIT at runtime, pass the environment variable `PYTHON_JIT=0`.
- `yes-off`: Build the JIT but disable it by default. To enable the JIT at runtime, pass the environment variable `PYTHON_JIT=1`.
- `interpreter`: Enable the Tier 2 interpreter but disable the JIT. The interpreter can be disabled by running with `PYTHON_JIT=0`.

The internal architecture is roughly as follows:

- We start with specialized *Tier 1 bytecode*. See What’s new in 3.11 for details.

- When the Tier 1 bytecode gets hot enough, it gets translated to a new purely internal intermediate representation (IR), called the *Tier 2 IR*, and sometimes referred to as micro-ops (“uops”).
- The Tier 2 IR uses the same stack-based virtual machine as Tier 1, but the instruction format is better suited to translation to machine code.
- We have several optimization passes for Tier 2 IR, which are applied before it is interpreted or translated to machine code.
- There is a Tier 2 interpreter, but it is mostly intended for debugging the earlier stages of the optimization pipeline. The Tier 2 interpreter can be enabled by configuring Python with `--enable-experimental-jit=interpreter`.
- When the JIT is enabled, the optimized Tier 2 IR is translated to machine code, which is then executed.
- The machine code translation process uses a technique called *copy-and-patch*. It has no runtime dependencies, but there is a new build-time dependency on LLVM.

#### Ayrıca bakınız

**PEP 744**

(JIT by Brandt Bucher, inspired by a paper by Haoran Xu and Fredrik Kjolstad. Tier 2 IR by Mark Shannon and Guido van Rossum. Tier 2 optimizer by Ken Jin.)

## 2.5 Defined mutation semantics for `locals()`

Historically, the expected result of mutating the return value of `locals()` has been left to individual Python implementations to define. Starting from Python 3.13, **PEP 667** standardises the historical behaviour of CPython for most code execution scopes, but changes optimized scopes (functions, generators, coroutines, comprehensions, and generator expressions) to explicitly return independent snapshots of the currently assigned local variables, including locally referenced nonlocal variables captured in closures.

This change to the semantics of `locals()` in optimized scopes also affects the default behaviour of code execution functions that implicitly target `locals()` if no explicit namespace is provided (such as `exec()` and `eval()`). In previous versions, whether or not changes could be accessed by calling `locals()` after calling the code execution function was implementation-dependent. In CPython specifically, such code would typically appear to work as desired, but could sometimes fail in optimized scopes based on other code (including debuggers and code execution tracing tools) potentially resetting the shared snapshot in that scope. Now, the code will always run against an independent snapshot of the local variables in optimized scopes, and hence the changes will never be visible in subsequent calls to `locals()`. To access the changes made in these cases, an explicit namespace reference must now be passed to the relevant function. Alternatively, it may make sense to update affected code to use a higher level code execution API that returns the resulting code execution namespace (e.g. `runpy.run_path()` when executing Python files from disk).

To ensure debuggers and similar tools can reliably update local variables in scopes affected by this change, `FrameType.f_locals` now returns a write-through proxy to the frame’s local and locally referenced nonlocal variables in these scopes, rather than returning an inconsistently updated shared `dict` instance with undefined runtime semantics.

See **PEP 667** for more details, including related C API changes and deprecations. Porting notes are also provided below for the affected *Python APIs* and *C APIs*.

(PEP and implementation contributed by Mark Shannon and Tian Gao in [gh-74929](https://github.com/python/cpython/pull/74929). Documentation updates provided by Guido van Rossum and Alyssa Coghlan.)



## 2.6 Support for mobile platforms

**PEP 730:** iOS is now a **PEP 11** supported platform, with the `arm64-apple-ios` and `arm64-apple-ios-simulator` targets at tier 3 (iPhone and iPad devices released after 2013 and the Xcode iOS simulator running on Apple silicon hardware, respectively). `x86_64-apple-ios-simulator` (the Xcode iOS simulator running on older `x86_64` hardware) is not a tier 3 supported platform, but will have best-effort support. (PEP written and implementation contributed by Russell Keith-Magee in [gh-114099](#).)

**PEP 738:** Android support is being actively worked on, but the platform is not yet officially supported. (PEP written and implementation contributed by Malcolm Smith in [gh-116622](#).)

Ayrıca bakınız

PEP 730, PEP 738

## 2.7 Incremental garbage collection

The cycle garbage collector is now incremental. This means that maximum pause times are reduced by an order of magnitude or more for larger heaps.

There are now only two generations: young and old. When `gc.collect()` is not called directly, the GC is invoked a little less frequently. When invoked, it collects the young generation and an increment of the old generation, instead of collecting one or more generations.

The behavior of `gc.collect()` changes slightly:

- `gc.collect(1)`: Performs an increment of GC, rather than collecting generation 1.
- Other calls to `gc.collect()` are unchanged.

(Contributed by Mark Shannon in [gh-108362](#).)

## 3 Other Language Changes

- The compiler now strips common leading whitespace from every line in a docstring. This reduces the size of the bytecode cache (such as `.pyc` files), with reductions in file size of around 5%, for example in `sqlalchemy.orm.session` from SQLAlchemy 2.0. This change affects tools that use docstrings, such as `doctest`.

```
>>> def spam():
...     """
...         This is a docstring with
...         leading whitespace.
...
...         It even has multiple paragraphs!
...     """
...
>>> spam.__doc__
'\nThis is a docstring with\n  leading whitespace.\n\nIt even has multiple
↳ paragraphs!\n'
```

(Contributed by Inada Naoki in [gh-81283](#).)

- Annotation scopes within class scopes can now contain lambdas and comprehensions. Comprehensions that are located within class scopes are not inlined into their parent scope.

```
class C[T]:
    type Alias = lambda: T
```

(Contributed by Jelle Zijlstra in [gh-109118](#) and [gh-118160](#).)

- Future statements are no longer triggered by relative imports of the `__future__` module, meaning that statements of the form `from __future__ import ...` are now simply standard relative imports, with no special features activated. (Contributed by Jeremiah Gabriel Pascual in [gh-118216](#).)
- `global` declarations are now permitted in `except` blocks when that `global` is used in the `else` block. Previously this raised an erroneous `SyntaxError`. (Contributed by Irit Katriel in [gh-111123](#).)
- Add `PYTHON_FROZEN_MODULES`, a new environment variable that determines whether frozen modules are ignored by the import machinery, equivalent to the `-X frozen_modules` command-line option. (Contributed by Yilei Yang in [gh-111374](#).)
- Add support for the `perf` profiler working without `frame pointers` through the new environment variable `PYTHON_PERF_JIT_SUPPORT` and command-line option `-X perf_jit`. (Contributed by Pablo Galindo in [gh-118518](#).)
- The location of a `.python_history` file can be changed via the new `PYTHON_HISTORY` environment variable. (Contributed by Levi Sabah, Zackery Spytz and Hugo van Kemenade in [gh-73965](#).)
- Classes have a new `__static_attributes__` attribute. This is populated by the compiler with a tuple of the class's attribute names which are assigned through `self.<name>` from any function in its body. (Contributed by Irit Katriel in [gh-115775](#).)
- The compiler now creates a `__firstlineno__` attribute on classes with the line number of the first line of the class definition. (Contributed by Serhiy Storchaka in [gh-118465](#).)
- The `exec()` and `eval()` builtins now accept the `globals` and `locals` arguments as keywords. (Contributed by Raphael Gaschignard in [gh-105879](#).)
- The `compile()` builtin now accepts a new flag, `ast.PyCF_OPTIMIZED_AST`, which is similar to `ast.PyCF_ONLY_AST` except that the returned AST is optimized according to the value of the `optimize` argument. (Contributed by Irit Katriel in [gh-108113](#).)
- Add `PythonFinalizationError`, a new exception derived from `RuntimeError` and used to signal when operations are blocked during finalization. The following callables now raise `PythonFinalizationError`, instead of `RuntimeError`:

```
- _thread.start_new_thread()
- os.fork()
- os.forkpty()
- subprocess.Popen
```

(Contributed by Victor Stinner in [gh-114570](#).)

- Allow the `count` argument of `str.replace()` to be a keyword. (Contributed by Hugo van Kemenade in [gh-106487](#).)
- Many functions now emit a warning if a boolean value is passed as a file descriptor argument. This can help catch some errors earlier. (Contributed by Serhiy Storchaka in [gh-82626](#).)
- Added `name` and `mode` attributes for compressed and archived file-like objects in the `bz2`, `lzma`, `tarfile`, and `zipfile` modules. (Contributed by Serhiy Storchaka in [gh-115961](#).)
- Add a `__name__` attribute on property objects. (Contributed by Eugene Toder in [gh-101860](#).)

## 4 New Modules

- `dbm.sqlite3`: An SQLite backend for `dbm`. (Contributed by Raymond Hettinger and Erlend E. Aasland in [gh-100414](#).)

## 5 Improved Modules

### 5.1 `argparse`

- Add the *deprecated* parameter to the `add_argument()` and `add_parser()` methods, to enable deprecating command-line options, positional arguments, and subcommands. (Contributed by Serhiy Storchaka in [gh-83648](#).)

### 5.2 `array`

- Add the 'w' type code (`Py_UCS4`) for Unicode characters. It should be used instead of the deprecated 'u' type code. (Contributed by Inada Naoki in [gh-80480](#).)
- Register `array.array` as a `MutableSequence` by implementing the `clear()` method. (Contributed by Mike Zimin in [gh-114894](#).)

### 5.3 `ast`

- The constructors of node types in the `ast` module are now stricter in the arguments they accept, with more intuitive behaviour when arguments are omitted.

If an optional field on an AST node is not included as an argument when constructing an instance, the field will now be set to `None`. Similarly, if a list field is omitted, that field will now be set to an empty list, and if an `expr_context` field is omitted, it defaults to `Load()`. (Previously, in all cases, the attribute would be missing on the newly constructed AST node instance.)

In all other cases, where a required argument is omitted, the node constructor will emit a `DeprecationWarning`. This will raise an exception in Python 3.15. Similarly, passing a keyword argument to the constructor that does not map to a field on the AST node is now deprecated, and will raise an exception in Python 3.15.

These changes do not apply to user-defined subclasses of `ast.AST` unless the class opts in to the new behavior by defining the `AST._field_types` mapping.

(Contributed by Jelle Zijlstra in [gh-105858](#), [gh-117486](#), and [gh-118851](#).)

- `ast.parse()` now accepts an optional argument *optimize* which is passed on to `compile()`. This makes it possible to obtain an optimized AST. (Contributed by Irit Katriel in [gh-108113](#).)

## 5.4 asyncio

- `asyncio.as_completed()` now returns an object that is both an asynchronous iterator and a plain iterator of awaitables. The awaitables yielded by asynchronous iteration include original task or future objects that were passed in, making it easier to associate results with the tasks being completed. (Contributed by Justin Arthur in [gh-77714](#).)
- `asyncio.loop.create_unix_server()` will now automatically remove the Unix socket when the server is closed. (Contributed by Pierre Ossman in [gh-111246](#).)
- `DatagramTransport.sendto()` will now send zero-length datagrams if called with an empty bytes object. The transport flow control also now accounts for the datagram header when calculating the buffer size. (Contributed by Jamie Phan in [gh-115199](#).)
- Add `Queue.shutdown` and `QueueShutDown` to manage queue termination. (Contributed by Laurie Opperman and Yves Duprat in [gh-104228](#).)
- Add the `Server.close_clients()` and `Server.abort_clients()` methods, which more forcefully close an asyncio server. (Contributed by Pierre Ossman in [gh-113538](#).)
- Accept a tuple of separators in `StreamReader.readuntil()`, stopping when any one of them is encountered. (Contributed by Bruce Merry in [gh-81322](#).)
- Improve the behavior of `TaskGroup` when an external cancellation collides with an internal cancellation. For example, when two task groups are nested and both experience an exception in a child task simultaneously, it was possible that the outer task group would hang, because its internal cancellation was swallowed by the inner task group.

In the case where a task group is cancelled externally and also must raise an `ExceptionGroup`, it will now call the parent task's `cancel()` method. This ensures that a `CancelledError` will be raised at the next `await`, so the cancellation is not lost.

An added benefit of these changes is that task groups now preserve the cancellation count (`cancelling()`).

In order to handle some corner cases, `uncancel()` may now reset the undocumented `_must_cancel` flag when the cancellation count reaches zero.

(Inspired by an issue reported by Arthur Tacca in [gh-116720](#).)

- When `TaskGroup.create_task()` is called on an inactive `TaskGroup`, the given coroutine will be closed (which prevents a `RuntimeWarning` about the given coroutine being never awaited). (Contributed by Arthur Tacca and Jason Zhang in [gh-115957](#).)

## 5.5 base64

- Add `z85encode()` and `z85decode()` functions for encoding bytes as Z85 data and decoding Z85-encoded data to bytes. (Contributed by Matan Perelman in [gh-75299](#).)

## 5.6 compileall

- The default number of worker threads and processes is now selected using `os.process_cpu_count()` instead of `os.cpu_count()`. (Contributed by Victor Stinner in [gh-109649](#).)

## 5.7 configparser

- The `configparser.ConfigParser` now accepts unnamed sections before named ones if configured to do so. (Contributed by Pedro Sousa Lacerda in [gh-66449](#).)

## 5.8 concurrent.futures

- The default number of worker threads and processes is now selected using `os.process_cpu_count()` instead of `os.cpu_count()`. (Contributed by Victor Stinner in [gh-109649](#).)

## 5.9 configparser

- `ConfigParser` now has support for unnamed sections, which allows for top-level key-value pairs. This can be enabled with the new `allow_unnamed_section` parameter. (Contributed by Pedro Sousa Lacerda in [gh-66449](#).)

## 5.10 copy

- The new `replace()` function and the `replace` protocol make creating modified copies of objects much simpler. This is especially useful when working with immutable objects. The following types support the `replace()` function and implement the `replace` protocol:

- `collections.namedtuple()`
- `dataclasses.dataclass`
- `datetime.datetime`, `datetime.date`, `datetime.time`
- `inspect.Signature`, `inspect.Parameter`
- `types.SimpleNamespace`
- code objects

Any user-defined class can also support `copy.replace()` by defining the `__replace__()` method. (Contributed by Serhiy Storchaka in [gh-108751](#).)

## 5.11 dbm

- Add `dbm.sqlite3`, a new module which implements an SQLite backend, and make it the default `dbm` backend. (Contributed by Raymond Hettinger and Erlend E. Aasland in [gh-100414](#).)
- Allow removing all items from the database through the new `gdbm.clear()` and `ndbm.clear()` methods. (Contributed by Donghee Na in [gh-107122](#).)

## 5.12 dis

- Change the output of `dis` module functions to show logical labels for jump targets and exception handlers, rather than offsets. The offsets can be added with the new `-O` command-line option or the `show_offsets` argument. (Contributed by Irit Katriel in [gh-112137](#).)
- `get_instructions()` no longer represents cache entries as separate instructions. Instead, it returns them as part of the `Instruction`, in the new `cache_info` field. The `show_caches` argument to `get_instructions()` is deprecated and no longer has any effect. (Contributed by Irit Katriel in [gh-112962](#).)

## 5.13 doctest

- `doctest` output is now colored by default. This can be controlled via the new `PYTHON_COLORS` environment variable as well as the canonical `NO_COLOR` and `FORCE_COLOR` environment variables. See also `using-on-controlling-color`. (Contributed by Hugo van Kemenade in [gh-117225](#).)
- The `DocTestRunner.run()` method now counts the number of skipped tests. Add the `DocTestRunner.skips` and `TestResults.skipped` attributes. (Contributed by Victor Stinner in [gh-108794](#).)

## 5.14 email

- Headers with embedded newlines are now quoted on output. The `generator` will now refuse to serialize (write) headers that are improperly folded or delimited, such that they would be parsed as multiple headers or joined with adjacent data. If you need to turn this safety feature off, set `verify_generated_headers`. (Contributed by Bas Bloemsaat and Petr Viktorin in [gh-121650](#).)
- `getaddresses()` and `parseaddr()` now return `(' ', '')` pairs in more situations where invalid email addresses are encountered instead of potentially inaccurate values. The two functions have a new optional `strict` parameter (default `True`). To get the old behaviour (accepting malformed input), use `strict=False`. `getattr(email.utils, 'supports_strict_parsing', False)` can be used to check if the `strict` parameter is available. (Contributed by Thomas Dwyer and Victor Stinner for [gh-102988](#) to improve the [CVE-2023-27043](#) fix.)

## 5.15 fractions

- `Fraction` objects now support the standard format specification mini-language rules for fill, alignment, sign handling, minimum width, and grouping. (Contributed by Mark Dickinson in [gh-111320](#).)

## 5.16 gc

The cyclic garbage collector is now incremental, which changes the meaning of the results of `get_threshold()` and `set_threshold()` as well as `get_count()` and `get_stats()`.

- For backwards compatibility, `get_threshold()` continues to return a three-item tuple. The first value is the threshold for young collections, as before; the second value determines the rate at which the old collection is scanned (the default is 10, and higher values mean that the old collection is scanned more slowly). The third value is meaningless and is always zero.
- `set_threshold()` ignores any items after the second.
- `get_count()` and `get_stats()` continue to return the same format of results. The only difference is that instead of the results referring to the young, aging and old generations, the results refer to the young generation and the aging and collecting spaces of the old generation.

In summary, code that attempted to manipulate the behavior of the cycle GC may not work exactly as intended, but it is very unlikely to be harmful. All other code will work just fine.

## 5.17 glob

- Add `translate()`, a function to convert a path specification with shell-style wildcards to a regular expression. (Contributed by Barney Gale in [gh-72904](#).)

## 5.18 importlib

- The following functions in `importlib.resources` now allow accessing a directory (or tree) of resources, using multiple positional arguments (the *encoding* and *errors* arguments in the text-reading functions are now keyword-only):

- `is_resource()`
- `open_binary()`
- `open_text()`
- `path()`
- `read_binary()`
- `read_text()`

These functions are no longer deprecated and are not scheduled for removal. (Contributed by Petr Viktorin in [gh-106532](#).)

- `contents()` remains deprecated in favor of the fully-featured Traversable API. However, there is now no plan to remove it. (Contributed by Petr Viktorin in [gh-106532](#).)

## 5.19 io

- The `IOBase` finalizer now logs any errors raised by the `close()` method with `sys.unraisablehook`. Previously, errors were ignored silently by default, and only logged in Python Development Mode or when using a Python debug build. (Contributed by Victor Stinner in [gh-62948](#).)

## 5.20 ipaddress

- Add the `IPv4Address.ipv6_mapped` property, which returns the IPv4-mapped IPv6 address. (Contributed by Charles Machalow in [gh-109466](#).)
- Fix `is_global` and `is_private` behavior in `IPv4Address`, `IPv6Address`, `IPv4Network`, and `IPv6Network`. (Contributed by Jakub Stasiak in [gh-113171](#).)

## 5.21 itertools

- `batched()` has a new *strict* parameter, which raises a `ValueError` if the final batch is shorter than the specified batch size. (Contributed by Raymond Hettinger in [gh-113202](#).)

## 5.22 marshal

- Add the *allow\_code* parameter in module functions. Passing `allow_code=False` prevents serialization and de-serialization of code objects which are incompatible between Python versions. (Contributed by Serhiy Storchaka in [gh-113626](#).)

## 5.23 math

- The new function `fma()` performs fused multiply-add operations. This computes  $x * y + z$  with only a single round, and so avoids any intermediate loss of precision. It wraps the `fma()` function provided by C99, and follows the specification of the IEEE 754 “fusedMultiplyAdd” operation for special cases. (Contributed by Mark Dickinson and Victor Stinner in [gh-73468](#).)

## 5.24 mimetypes

- Add the `guess_file_type()` function to guess a MIME type from a filesystem path. Using paths with `guess_type()` is now soft deprecated. (Contributed by Serhiy Storchaka in [gh-66543](#).)

## 5.25 mmap

- `mmap` is now protected from crashing on Windows when the mapped memory is inaccessible due to file system errors or access violations. (Contributed by Jannis Weigend in [gh-118209](#).)
- `mmap` has a new `seekable()` method that can be used when a seekable file-like object is required. The `seek()` method now returns the new absolute position. (Contributed by Donghee Na and Sylvie Liberman in [gh-111835](#).)
- The new UNIX-only *trackfd* parameter for `mmap` controls file descriptor duplication; if `false`, the file descriptor specified by *fileno* will not be duplicated. (Contributed by Zackery Spytz and Petr Viktorin in [gh-78502](#).)

## 5.26 multiprocessing

- The default number of worker threads and processes is now selected using `os.process_cpu_count()` instead of `os.cpu_count()`. (Contributed by Victor Stinner in [gh-109649](#).)

## 5.27 os

- Add `process_cpu_count()` function to get the number of logical CPU cores usable by the calling thread of the current process. (Contributed by Victor Stinner in [gh-109649](#).)
- `cpu_count()` and `process_cpu_count()` can be overridden through the new environment variable `PYTHON_CPU_COUNT` or the new command-line option `-X cpu_count`. This option is useful for users who need to limit CPU resources of a container system without having to modify application code or the container itself. (Contributed by Donghee Na in [gh-109595](#).)



- Add a low level interface to Linux’s *timer file descriptors* via `timerfd_create()`, `timerfd_settime()`, `timerfd_settime_ns()`, `timerfd_gettime()`, `timerfd_gettime_ns()`, `TFD_NONBLOCK`, `TFD_CLOEXEC`, `TFD_TIMER_ABSTIME`, and `TFD_TIMER_CANCEL_ON_SET` (Contributed by Masaru Tsuchiyama in [gh-108277](#).)
- `lchmod()` and the `follow_symlinks` argument of `chmod()` are both now available on Windows. Note that the default value of `follow_symlinks` in `lchmod()` is `False` on Windows. (Contributed by Serhiy Storchaka in [gh-59616](#).)
- `fchmod()` and support for file descriptors in `chmod()` are both now available on Windows. (Contributed by Serhiy Storchaka in [gh-113191](#).)
- On Windows, `mkdir()` and `makedirs()` now support passing a *mode* value of `0o700` to apply access control to the new directory. This implicitly affects `tempfile.mkdtemp()` and is a mitigation for [CVE-2024-4030](#). Other values for *mode* continue to be ignored. (Contributed by Steve Dower in [gh-118486](#).)
- `posix_spawn()` now accepts `None` for the *env* argument, which makes the newly spawned process use the current process environment. (Contributed by Jakub Kulik in [gh-113119](#).)
- `posix_spawn()` can now use the `POSIX_SPAWN_CLOSEFROM` attribute in the *file\_actions* parameter on platforms that support `posix_spawn_file_actions_addclosefrom_np()`. (Contributed by Jakub Kulik in [gh-113117](#).)

## 5.28 os.path

- Add `isreserved()` to check if a path is reserved on the current system. This function is only available on Windows. (Contributed by Barney Gale in [gh-88569](#).)
- On Windows, `isabs()` no longer considers paths starting with exactly one slash (`\` or `/`) to be absolute. (Contributed by Barney Gale and Jon Foster in [gh-44626](#).)
- `realpath()` now resolves MS-DOS style file names even if the file is not accessible. (Contributed by Moonsik Park in [gh-82367](#).)

## 5.29 pathlib

- Add `UnsupportedOperation`, which is raised instead of `NotImplementedError` when a path operation isn’t supported. (Contributed by Barney Gale in [gh-89812](#).)
- Add a new constructor for creating `Path` objects from ‘file’ URIs (`file:///`), `Path.from_uri()`. (Contributed by Barney Gale in [gh-107465](#).)
- Add `PurePath.full_match()` for matching paths with shell-style wildcards, including the recursive wildcard `***`. (Contributed by Barney Gale in [gh-73435](#).)
- Add the `PurePath.parser` class attribute to store the implementation of `os.path` used for low-level path parsing and joining. This will be either `posixpath` or `ntpath`.
- Add `recurse_symlinks` keyword-only argument to `Path.glob()` and `rglob()`. (Contributed by Barney Gale in [gh-77609](#).)
- `Path.glob()` and `rglob()` now return files and directories when given a pattern that ends with `***`. Previously, only directories were returned. (Contributed by Barney Gale in [gh-70303](#).)
- Add the `follow_symlinks` keyword-only argument to `Path.is_file`, `Path.is_dir`, `Path.owner()`, and `Path.group()`. (Contributed by Barney Gale in [gh-105793](#) and Kamil Turek in [gh-107962](#).)

### 5.30 pdb

- `breakpoint()` and `set_trace()` now enter the debugger immediately rather than on the next line of code to be executed. This change prevents the debugger from breaking outside of the context when `breakpoint()` is positioned at the end of the context. (Contributed by Tian Gao in [gh-118579](#).)
- `sys.path[0]` is no longer replaced by the directory of the script being debugged when `sys.flags.safe_path` is set. (Contributed by Tian Gao and Christian Walther in [gh-111762](#).)
- `zipapp` is now supported as a debugging target. (Contributed by Tian Gao in [gh-118501](#).)
- Add ability to move between chained exceptions during post-mortem debugging in `pm()` using the new `exceptions [exc_number]` command for `Pdb`. (Contributed by Matthias Bussonnier in [gh-106676](#).)
- Expressions and statements whose prefix is a `pdb` command are now correctly identified and executed. (Contributed by Tian Gao in [gh-108464](#).)

### 5.31 queue

- Add `Queue.shutdown` and `ShutDown` to manage queue termination. (Contributed by Laurie Opperman and Yves Duprat in [gh-104750](#).)

### 5.32 random

- Add a command-line interface. (Contributed by Hugo van Kemenade in [gh-118131](#).)

### 5.33 re

- Rename `re.error` to `PatternError` for improved clarity. `re.error` is kept for backward compatibility.

### 5.34 shutil

- Support the `dir_fd` and `follow_symlinks` keyword arguments in `chown()`. (Contributed by Berker Peksag and Tahia K in [gh-62308](#))

### 5.35 site

- `.pth` files are now decoded using UTF-8 first, and then with the locale encoding if UTF-8 decoding fails. (Contributed by Inada Naoki in [gh-117802](#).)

### 5.36 sqlite3

- A `ResourceWarning` is now emitted if a `Connection` object is not closed explicitly. (Contributed by Erlend E. Aasland in [gh-105539](#).)
- Add the `filter` keyword-only parameter to `Connection.iterdump()` for filtering database objects to dump. (Contributed by Mariusz Felisiak in [gh-91602](#).)

## 5.37 ssl

- The `create_default_context()` API now includes `VERIFY_X509_PARTIAL_CHAIN` and `VERIFY_X509_STRICT` in its default flags.

### Not

`VERIFY_X509_STRICT` may reject pre-**RFC 5280** or malformed certificates that the underlying OpenSSL implementation might otherwise accept. Whilst disabling this is not recommended, you can do so using:

```
import ssl

ctx = ssl.create_default_context()
ctx.verify_flags |= ~ssl.VERIFY_X509_STRICT
```

(Contributed by William Woodruff in [gh-112389](#).)

## 5.38 statistics

- Add `kde()` for kernel density estimation. This makes it possible to estimate a continuous probability density function from a fixed number of discrete samples. (Contributed by Raymond Hettinger in [gh-115863](#).)
- Add `kde_random()` for sampling from an estimated probability density function created by `kde()`. (Contributed by Raymond Hettinger in [gh-115863](#).)

## 5.39 subprocess

- The `subprocess` module now uses the `posix_spawn()` function in more situations.

Notably, when `close_fds` is `True` (the default), `posix_spawn()` will be used when the C library provides `posix_spawn_file_actions_addclosefrom_np()`, which includes recent versions of Linux, FreeBSD, and Solaris. On Linux, this should perform similarly to the existing Linux `vfork()` based code.

A private control knob `subprocess._USE_POSIX_SPAWN` can be set to `False` if you need to force `subprocess` to never use `posix_spawn()`. Please report your reason and platform details in the issue tracker if you set this so that we can improve our API selection logic for everyone. (Contributed by Jakub Kulik in [gh-113117](#).)

## 5.40 sys

- Add the `_is_interned()` function to test if a string was interned. This function is not guaranteed to exist in all implementations of Python. (Contributed by Serhiy Storchaka in [gh-78573](#).)

## 5.41 tempfile

- On Windows, the default mode `0o700` used by `tempfile.mkdtemp()` now limits access to the new directory due to changes to `os.mkdir()`. This is a mitigation for [CVE-2024-4030](#). (Contributed by Steve Dower in [gh-118486](#).)

## 5.42 time

- On Windows, `monotonic()` now uses the `QueryPerformanceCounter()` clock for a resolution of 1 microsecond, instead of the `GetTickCount64()` clock which has a resolution of 15.6 milliseconds. (Contributed by Victor Stinner in [gh-88494](#).)
- On Windows, `time()` now uses the `GetSystemTimePreciseAsFileTime()` clock for a resolution of 1 microsecond, instead of the `GetSystemTimeAsFileTime()` clock which has a resolution of 15.6 milliseconds. (Contributed by Victor Stinner in [gh-63207](#).)

## 5.43 tkinter

- Add `tkinter` widget methods: `tk_busy_hold()`, `tk_busy_configure()`, `tk_busy_cget()`, `tk_busy_forget()`, `tk_busy_current()`, and `tk_busy_status()`. (Contributed by Miguel, klapp-nase and Serhiy Storchaka in [gh-72684](#).)
- The `tkinter` widget method `wm_attributes()` now accepts the attribute name without the minus prefix to get window attributes, for example `w.wm_attributes('alpha')` and allows specifying attributes and values to set as keyword arguments, for example `w.wm_attributes(alpha=0.5)`. (Contributed by Serhiy Storchaka in [gh-43457](#).)
- `wm_attributes()` can now return attributes as a dict, by using the new optional keyword-only parameter `return_python_dict`. (Contributed by Serhiy Storchaka in [gh-43457](#).)
- `Text.count()` can now return a simple `int` when the new optional keyword-only parameter `return_ints` is used. Otherwise, the single count is returned as a 1-tuple or `None`. (Contributed by Serhiy Storchaka in [gh-97928](#).)
- Support the “vsapi” element type in the `element_create()` method of `tkinter.ttk.Style`. (Contributed by Serhiy Storchaka in [gh-68166](#).)
- Add the `after_info()` method for `Tkinter` widgets. (Contributed by Cheryl Sabella in [gh-77020](#).)
- Add a new `copy_replace()` method to `PhotoImage` to copy a region from one image to another, possibly with pixel zooming, subsampling, or both. (Contributed by Serhiy Storchaka in [gh-118225](#).)
- Add `from_coords` parameter to the `PhotoImage` methods `copy()`, `zoom()` and `subsample()`. Add `zoom` and `subsample` parameters to the `PhotoImage` method `copy()`. (Contributed by Serhiy Storchaka in [gh-118225](#).)
- Add the `PhotoImage` methods `read()` to read an image from a file and `data()` to get the image data. Add `background` and `grayscale` parameters to the `write()` method. (Contributed by Serhiy Storchaka in [gh-118271](#).)

## 5.44 traceback

- Add the `exc_type_str` attribute to `TracebackException`, which holds a string display of the `exc_type`. Deprecate the `exc_type` attribute, which holds the type object itself. Add parameter `save_exc_type` (default `True`) to indicate whether `exc_type` should be saved. (Contributed by Irit Katriel in [gh-112332](#).)
- Add a new `show_group` keyword-only parameter to `TracebackException.format_exception_only()` to (recursively) format the nested exceptions of a `BaseExceptionGroup` instance. (Contributed by Irit Katriel in [gh-105292](#).)

## 5.45 types

- `SimpleNamespace` can now take a single positional argument to initialise the namespace's arguments. This argument must either be a mapping or an iterable of key-value pairs. (Contributed by Serhiy Storchaka in [gh-108191](#).)

## 5.46 typing

- **PEP 705**: Add `ReadOnly`, a special typing construct to mark a `TypedDict` item as read-only for type checkers.
- **PEP 742**: Add `TypeIs`, a typing construct that can be used to instruct a type checker how to narrow a type.
- Add `NoDefault`, a sentinel object used to represent the defaults of some parameters in the `typing` module. (Contributed by Jelle Zijlstra in [gh-116126](#).)
- Add `get_protocol_members()` to return the set of members defining a `typing.Protocol`. (Contributed by Jelle Zijlstra in [gh-104873](#).)
- Add `is_protocol()` to check whether a class is a `Protocol`. (Contributed by Jelle Zijlstra in [gh-104873](#).)
- `ClassVar` can now be nested in `Final`, and vice versa. (Contributed by Mehdi Drissi in [gh-89547](#).)

## 5.47 unicodedata

- Update the Unicode database to [version 15.1.0](#). (Contributed by James Gerity in [gh-109559](#).)

## 5.48 venv

- Add support for creating source control management (SCM) ignore files in a virtual environment's directory. By default, Git is supported. This is implemented as opt-in via the API, which can be extended to support other SCMs (`EnvBuilder` and `create()`), and opt-out via the CLI, using `--without-scm-ignore-files`. (Contributed by Brett Cannon in [gh-108125](#).)

## 5.49 warnings

- **PEP 702**: The new `warnings.deprecated()` decorator provides a way to communicate deprecations to a static type checker and to warn on usage of deprecated classes and functions. A `DeprecationWarning` may also be emitted when a decorated function or class is used at runtime. (Contributed by Jelle Zijlstra in [gh-104003](#).)

## 5.50 xml

- Allow controlling Expat  $\geq 2.6.0$  reparsing deferral ([CVE-2023-52425](#)) by adding five new methods:

- `xml.etree.ElementTree.XMLParser.flush()`
- `xml.etree.ElementTree.XMLPullParser.flush()`
- `xml.parsers.expat.xmlparser.GetReparseDeferralEnabled()`
- `xml.parsers.expat.xmlparser.SetReparseDeferralEnabled()`
- `xml.sax.expatreader.ExpatParser.flush()`

(Contributed by Sebastian Pipping in [gh-115623](#).)

- Add the `close()` method for the iterator returned by `iterparse()` for explicit cleanup. (Contributed by Serhiy Storchaka in [gh-69893](#).)

## 5.51 zipimport

- Add support for [ZIP64](#) format files. Everybody loves huge data, right? (Contributed by Tim Hatch in [gh-94146](#).)

# 6 Optimizations

- The new *incremental garbage collector* means that maximum pause times are reduced by an order of magnitude or more for larger heaps. (Contributed by Mark Shannon in [gh-108362](#).)
- Several standard library modules have had their import times significantly improved. For example, the import time of the `typing` module has been reduced by around a third by removing dependencies on `re` and `contextlib`. Other modules to enjoy import-time speedups include `email.utils`, `enum`, `functools`, `importlib.metadata`, and `threading`. (Contributed by Alex Waygood, Shantanu Jain, Adam Turner, Daniel Hollas, and others in [gh-109653](#).)
- `textwrap.indent()` is now around 30% faster than before for large input. (Contributed by Inada Naoki in [gh-107369](#).)
- The `subprocess` module now uses the `posix_spawn()` function in more situations, including when `close_fds` is `True` (the default) on many modern platforms. This should provide a notable performance increase when launching processes on FreeBSD and Solaris. See the *subprocess* section above for details. (Contributed by Jakub Kulik in [gh-113117](#).)

## 7 Removed Modules And APIs

### 7.1 PEP 594: Remove “dead batteries” from the standard library

**PEP 594** proposed removing 19 modules from the standard library, colloquially referred to as ‘dead batteries’ due to their historic, obsolete, or insecure status. All of the following modules were deprecated in Python 3.11, and are now removed:

- `aifc`
- `audioop`
- `chunk`
- `cgi` and `cgitb`
  - `cgi.FieldStorage` can typically be replaced with `urllib.parse.parse_qs()` for GET and HEAD requests, and the `email.message` module or the [multipart](#) library for POST and PUT requests.
  - `cgi.parse()` can be replaced by calling `urllib.parse.parse_qs()` directly on the desired query string, unless the input is multipart/form-data, which should be replaced as described below for `cgi.parse_multipart()`.
  - `cgi.parse_header()` can be replaced with the functionality in the `email` package, which implements the same MIME RFCs. For example, with `email.message.EmailMessage`:

```
from email.message import EmailMessage

msg = EmailMessage()
msg['content-type'] = 'application/json; charset="utf8"'
main, params = msg.get_content_type(), msg['content-type'].params
```

- `cgi.parse_multipart()` can be replaced with the functionality in the `email` package, which implements the same MIME RFCs, or with the [multipart](#) library. For example, the `email.message.EmailMessage` and `email.message.Message` classes.
- `crypt` and the private `_crypt` extension. The `hashlib` module may be an appropriate replacement when simply hashing a value is required. Otherwise, various third-party libraries on PyPI are available:
  - [bcrypt](#): Modern password hashing for your software and your servers.
  - [passlib](#): Comprehensive password hashing framework supporting over 30 schemes.
  - [argon2-cffi](#): The secure Argon2 password hashing algorithm.
  - [legacycrypt](#): ctypes wrapper to the POSIX crypt library call and associated functionality.
  - [crypt\\_r](#): Fork of the `crypt` module, wrapper to the [crypt\\_r\(3\)](#) library call and associated functionality.
- `imghdr`: The [filetype](#), [puremagic](#), or [python-magic](#) libraries should be used as replacements. For example, the `puremagic.what()` function can be used to replace the `imghdr.what()` function for all file formats that were supported by `imghdr`.
- `mailcap`: Use the `mimetypes` module instead.
- `msilib`
- `nis`
- `nntplib`: Use the [nntplib](#) library from PyPI instead.
- `ossaudiodev`: For audio playback, use the [pygame](#) library from PyPI instead.
- `pipes`: Use the `subprocess` module instead.

- `sndhdr`: The `filetype`, `puremagic`, or `python-magic` libraries should be used as replacements.
- `spwd`: Use the `python-pam` library from PyPI instead.
- `sunau`
- `telnetlib`, Use the `telnetlib3` or `Exscript` libraries from PyPI instead.
- `uu`: Use the `base64` module instead, as a modern alternative.
- `xdrlib`

(Contributed by Victor Stinner and Zachary Ware in [gh-104773](#) and [gh-104780](#).)

## 7.2 2to3

- Remove the `2to3` program and the `lib2to3` module, previously deprecated in Python 3.11. (Contributed by Victor Stinner in [gh-104780](#).)

## 7.3 builtins

- Remove support for chained `classmethod` descriptors (introduced in [gh-63272](#)). These can no longer be used to wrap other descriptors, such as `property`. The core design of this feature was flawed and led to several problems. To “pass-through” a `classmethod`, consider using the `__wrapped__` attribute that was added in Python 3.10. (Contributed by Raymond Hettinger in [gh-89519](#).)

## 7.4 configparser

- Remove the undocumented `LegacyInterpolation` class, deprecated in the docstring since Python 3.2, and at runtime since Python 3.11. (Contributed by Hugo van Kemenade in [gh-104886](#).)

## 7.5 importlib.metadata

- Remove deprecated subscript (`__getitem__()`) access for `EntryPoint` objects. (Contributed by Jason R. Coombs in [gh-113175](#).)

## 7.6 locale

- Remove the `locale.resetlocale()` function, deprecated in Python 3.11. Use `locale.setlocale(locale.LC_ALL, "")` instead. (Contributed by Victor Stinner in [gh-104783](#).)

## 7.7 opcode

- Move `opcode.ENABLE_SPECIALIZATION` to `_opcode.ENABLE_SPECIALIZATION`. This field was added in 3.12, it was never documented, and is not intended for external use. (Contributed by Irit Katriel in [gh-105481](#).)
- Remove `opcode.is_pseudo()`, `opcode.MIN_PSEUDO_OPCODE`, and `opcode.MAX_PSEUDO_OPCODE`, which were added in Python 3.12, but were neither documented nor exposed through `dis`, and were not intended to be used externally. (Contributed by Irit Katriel in [gh-105481](#).)



## 7.8 pathlib

- Remove the ability to use `Path` objects as context managers. This functionality was deprecated and has had no effect since Python 3.9. (Contributed by Barney Gale in [gh-83863](#).)

## 7.9 re

- Remove the undocumented, deprecated, and broken `re.template()` function and `re.TEMPLATE / re.T` flag. (Contributed by Serhiy Storchaka and Nikita Sobolev in [gh-105687](#).)

## 7.10 tkinter.tix

- Remove the `tkinter.tix` module, deprecated in Python 3.6. The third-party Tix library which the module wrapped is unmaintained. (Contributed by Zachary Ware in [gh-75552](#).)

## 7.11 turtle

- Remove the `RawTurtle.settiltangle()` method, deprecated in the documentation since Python 3.1 and at runtime since Python 3.11. (Contributed by Hugo van Kemenade in [gh-104876](#).)

## 7.12 typing

- Remove the `typing.io` and `typing.re` namespaces, deprecated since Python 3.8. The items in those namespaces can be imported directly from the `typing` module. (Contributed by Sebastian Rittau in [gh-92871](#).)
- Remove the keyword-argument method of creating `TypedDict` types, deprecated in Python 3.11. (Contributed by Tomas Roun in [gh-104786](#).)

## 7.13 unittest

- Remove the following `unittest` functions, deprecated in Python 3.11:

- `unittest.findTestCases()`
  - `unittest.makeSuite()`
  - `unittest.getTestCaseNames()`

Use `TestLoader` methods instead:

- `loadTestsFromModule()`
  - `loadTestsFromTestCase()`
  - `getTestCaseNames()`

(Contributed by Hugo van Kemenade in [gh-104835](#).)

- Remove the untested and undocumented `TestProgram.usageExit()` method, deprecated in Python 3.11. (Contributed by Hugo van Kemenade in [gh-104992](#).)

## 7.14 urllib

- Remove the *cafile*, *capath*, and *cadefault* parameters of the `urllib.request.urlopen()` function, deprecated in Python 3.6. Use the *context* parameter instead with an `SSLContext` instance. The `ssl.SSLContext.load_cert_chain()` function can be used to load specific certificates, or let `ssl.create_default_context()` select the operating system's trusted certificate authority (CA) certificates. (Contributed by Victor Stinner in [gh-105382](#).)

## 7.15 webbrowser

- Remove the untested and undocumented `MacOSX` class, deprecated in Python 3.11. Use the `MacOSXOSAScript` class (introduced in Python 3.2) instead. (Contributed by Hugo van Kemenade in [gh-104804](#).)
- Remove the deprecated `MacOSXOSAScript._name` attribute. Use the `MacOSXOSAScript.name` attribute instead. (Contributed by Nikita Sobolev in [gh-105546](#).)

# 8 New Deprecations

- `array`: `array`'s 'u' format code, deprecated in docs since Python 3.3, emits `DeprecationWarning` since 3.13 and will be removed in Python 3.16. Use the 'w' format code instead. (Contributed by Hugo van Kemenade in [gh-80480](#).)
- `ctypes`: Deprecate undocumented `ctypes.SetPointerType()` function. Soft-deprecate the `ctypes.ARRAY()` function in favor of multiplication. (Contributed by Victor Stinner in [gh-105733](#).)
- `decimal`: Deprecate non-standard format specifier “N” for `decimal.Decimal`. It was not documented and only supported in the C implementation. (Contributed by Serhiy Storchaka in [gh-89902](#).)
- `dis`: The `dis.HAVE_ARGUMENT` separator is deprecated. Check membership in `hasarg` instead. (Contributed by Irit Katriel in [gh-109319](#).)
- `frame-objects`: Calling `frame.clear()` on a suspended frame raises `RuntimeError` (as has always been the case for an executing frame). (Contributed by Irit Katriel in [gh-79932](#).)
- `getopt` and `optparse` modules: They are now soft deprecated: the `argparse` module should be used for new projects. Previously, the `optparse` module was already deprecated, its removal was not scheduled, and no warnings was emitted: so there is no change in practice. (Contributed by Victor Stinner in [gh-106535](#).)
- `gettext`: Emit deprecation warning for non-integer numbers in `gettext` functions and methods that consider plural forms even if the translation was not found. (Contributed by Serhiy Storchaka in [gh-88434](#).)
- `glob`: The undocumented `glob.glob0()` and `glob.glob1()` functions are deprecated. Use `glob.glob()` and pass a directory to its *root\_dir* argument instead. (Contributed by Barney Gale in [gh-117337](#).)
- `http.server`: `http.server.CGIHTTPRequestHandler` now emits a `DeprecationWarning` as it will be removed in 3.15. Process-based CGI HTTP servers have been out of favor for a very long time. This code was outdated, unmaintained, and rarely used. It has a high potential for both security and functionality bugs. This includes removal of the `--cgi` flag to the `python -m http.server` command line in 3.15.
- `mimetypes`: Passing file path instead of URL in `guess_type()` is soft deprecated. Use `guess_file_type()` instead. (Contributed by Serhiy Storchaka in [gh-66543](#).)
- `re`: Passing optional arguments *maxsplit*, *count* and *flags* in module-level functions `re.split()`, `re.sub()` and `re.subn()` as positional arguments is now deprecated. In future Python versions these parameters will be keyword-only. (Contributed by Serhiy Storchaka in [gh-56166](#).)

- `pathlib`: `pathlib.PurePath.is_reserved()` is deprecated and scheduled for removal in Python 3.15. Use `os.path.isreserved()` to detect reserved paths on Windows.
- `platform`: `java_ver()` is deprecated and will be removed in 3.15. It was largely untested, had a confusing API, and was only useful for Jython support. (Contributed by Nikita Sobolev in [gh-116349](#).)
- `pydoc`: Deprecate undocumented `pydoc.ispackage()` function. (Contributed by Zackery Spytz in [gh-64020](#).)
- `sqlite3`: Passing more than one positional argument to `sqlite3.connect()` and the `sqlite3.Connection` constructor is deprecated. The remaining parameters will become keyword-only in Python 3.15.

Deprecate passing name, number of arguments, and the callable as keyword arguments for the following `sqlite3.Connection` APIs:

- `create_function()`
- `create_aggregate()`

Deprecate passing the callback callable by keyword for the following `sqlite3.Connection` APIs:

- `set_authorizer()`
- `set_progress_handler()`
- `set_trace_callback()`

The affected parameters will become positional-only in Python 3.15.

(Contributed by Erlend E. Aasland in [gh-107948](#) and [gh-108278](#).)

- `sys`: The `sys._enablelegacywindowsfsencoding()` function is deprecated. Replace it with the `PYTHONLEGACYWINDOWSFSENCODING` environment variable. (Contributed by Inada Naoki in [gh-73427](#).)
- `tarfile`: The undocumented and unused `tarfile` attribute of `tarfile.TarFile` is deprecated and scheduled for removal in Python 3.16.
- `traceback`: The field `exc_type` of `traceback.TracebackException` is deprecated. Use `exc_type_str` instead.
- `typing`:
  - Creating a `typing.NamedTuple` class using keyword arguments to denote the fields (`NT = NamedTuple("NT", x=int, y=int)`) is deprecated, and will be disallowed in Python 3.15. Use the class-based syntax or the functional syntax instead. (Contributed by Alex Waygood in [gh-105566](#).)
  - When using the functional syntax to create a `typing.NamedTuple` class or a `typing.TypedDict` class, failing to pass a value to the 'fields' parameter (`NT = NamedTuple("NT")` or `TD = TypedDict("TD")`) is deprecated. Passing `None` to the 'fields' parameter (`NT = NamedTuple("NT", None)` or `TD = TypedDict("TD", None)`) is also deprecated. Both will be disallowed in Python 3.15. To create a `NamedTuple` class with zero fields, use `class NT(NamedTuple): pass` or `NT = NamedTuple("NT", [])`. To create a `TypedDict` class with zero fields, use `class TD(TypedDict): pass` or `TD = TypedDict("TD", {})`. (Contributed by Alex Waygood in [gh-105566](#) and [gh-105570](#).)
  - `typing.no_type_check_decorator()` is deprecated, and scheduled for removal in Python 3.15. After eight years in the `typing` module, it has yet to be supported by any major type checkers. (Contributed by Alex Waygood in [gh-106309](#).)
  - `typing.AnyStr` is deprecated. In Python 3.16, it will be removed from `typing.__all__`, and a `DeprecationWarning` will be emitted when it is imported or accessed. It will be removed entirely in Python 3.18. Use the new type parameter syntax instead. (Contributed by Michael The in [gh-107116](#).)

- **user-defined-funcs:** Assignment to a function's `__code__` attribute where the new code object's type does not match the function's type is deprecated. The different types are: plain function, generator, async generator and coroutine. (Contributed by Irit Katriel in [gh-81137](#).)
- **wave:** Deprecate the `getmark()`, `setmark()` and `getmarkers()` methods of the `wave.Wave_read` and `wave.Wave_write` classes. They will be removed in Python 3.15. (Contributed by Victor Stinner in [gh-105096](#).)

## 8.1 Pending Removal in Python 3.14

- **argparse:** The *type*, *choices*, and *metavar* parameters of `argparse.BooleanOptionalAction` are deprecated and will be removed in 3.14. (Contributed by Nikita Sobolev in [gh-92248](#).)
- **ast:** The following features have been deprecated in documentation since Python 3.8, now cause a `DeprecationWarning` to be emitted at runtime when they are accessed or used, and will be removed in Python 3.14:

- `ast.Num`
- `ast.Str`
- `ast.Bytes`
- `ast.NameConstant`
- `ast.Ellipsis`

Use `ast.Constant` instead. (Contributed by Serhiy Storchaka in [gh-90953](#).)

- **asyncio:**
  - The child watcher classes `MultiLoopChildWatcher`, `FastChildWatcher`, `AbstractChildWatcher` and `SafeChildWatcher` are deprecated and will be removed in Python 3.14. (Contributed by Kumar Aditya in [gh-94597](#).)
  - `asyncio.set_child_watcher()`, `asyncio.get_child_watcher()`, `asyncio.AbstractEventLoopPolicy.set_child_watcher()` and `asyncio.AbstractEventLoopPolicy.get_child_watcher()` are deprecated and will be removed in Python 3.14. (Contributed by Kumar Aditya in [gh-94597](#).)
  - The `get_event_loop()` method of the default event loop policy now emits a `DeprecationWarning` if there is no current event loop set and it decides to create one. (Contributed by Serhiy Storchaka and Guido van Rossum in [gh-100160](#).)
- **collections.abc:** Deprecated `ByteString`. Prefer `Sequence` or `Buffer`. For use in typing, prefer a union, like `bytes | bytearray`, or `collections.abc.Buffer`. (Contributed by Shantanu Jain in [gh-91896](#).)
- **email:** Deprecate the *isdst* parameter in `email.utils.localtime()`. (Contributed by Alan Williams in [gh-72346](#).)
- **importlib:** `__package__` and `__cached__` will cease to be set or taken into consideration by the import system ([gh-97879](#)).
- **importlib.abc deprecated classes:**
  - `importlib.abc.ResourceReader`
  - `importlib.abc.Traversable`
  - `importlib.abc.TraversableResources`

Use `importlib.resources.abc` classes instead:

- `importlib.resources.abc.Traversable`
- `importlib.resources.abc.TraversableResources`

(Contributed by Jason R. Coombs and Hugo van Kemenade in [gh-93963](#).)

- `itertools` had undocumented, inefficient, historically buggy, and inconsistent support for `copy`, `deepcopy`, and `pickle` operations. This will be removed in 3.14 for a significant reduction in code volume and maintenance burden. (Contributed by Raymond Hettinger in [gh-101588](#).)
- `multiprocessing`: The default start method will change to a safer one on Linux, BSDs, and other non-macOS POSIX platforms where `'fork'` is currently the default ([gh-84559](#)). Adding a runtime warning about this was deemed too disruptive as the majority of code is not expected to care. Use the `get_context()` or `set_start_method()` APIs to explicitly specify when your code *requires* `'fork'`. See `multiprocessing-start-methods`.
- `pathlib`: `is_relative_to()` and `relative_to()`: passing additional arguments is deprecated.
- `pkgutil`: `find_loader()` and `get_loader()` now raise `DeprecationWarning`; use `importlib.util.find_spec()` instead. (Contributed by Nikita Sobolev in [gh-97850](#).)
- `pty`:
  - `master_open()`: use `pty.openpty()`.
  - `slave_open()`: use `pty.openpty()`.
- `sqlite3`:
  - `version` and `version_info`.
  - `execute()` and `executemany()` if named placeholders are used and *parameters* is a sequence instead of a dict.
  - date and datetime adapter, date and timestamp converter: see the `sqlite3` documentation for suggested replacement recipes.
- `types.CodeType`: Accessing `co_notab` was deprecated in [PEP 626](#) since 3.10 and was planned to be removed in 3.12, but it only got a proper `DeprecationWarning` in 3.12. May be removed in 3.14. (Contributed by Nikita Sobolev in [gh-101866](#).)
- `typing`: `ByteString`, deprecated since Python 3.9, now causes a `DeprecationWarning` to be emitted when it is used.
- `urllib`: `urllib.parse.Quoter` is deprecated: it was not intended to be a public API. (Contributed by Gregory P. Smith in [gh-88168](#).)

## 8.2 Pending Removal in Python 3.15

- `http.server.CGIHTTPRequestHandler` will be removed along with its related `--cgi` flag to `python -m http.server`. It was obsolete and rarely used. No direct replacement exists. *Anything* is better than CGI to interface a web server with a request handler.
- `locale`: `locale.getdefaultlocale()` was deprecated in Python 3.11 and originally planned for removal in Python 3.13 ([gh-90817](#)), but removal has been postponed to Python 3.15. Use `locale.setlocale()`, `locale.getencoding()` and `locale.getlocale()` instead. (Contributed by Hugo van Kemenade in [gh-111187](#).)
- `pathlib`: `pathlib.PurePath.is_reserved()` is deprecated and scheduled for removal in Python 3.15. Use `os.path.isreserved()` to detect reserved paths on Windows.

- `platform.java_ver()` is deprecated and will be removed in 3.15. It was largely untested, had a confusing API, and was only useful for Jython support. (Contributed by Nikita Sobolev in [gh-116349](#).)
- `threading`: Passing any arguments to `threading.RLock()` is now deprecated. C version allows any numbers of args and kwargs, but they are just ignored. Python version does not allow any arguments. All arguments will be removed from `threading.RLock()` in Python 3.15. (Contributed by Nikita Sobolev in [gh-102029](#).)
- `typing.NamedTuple`:
  - The undocumented keyword argument syntax for creating `NamedTuple` classes (`NT = NamedTuple("NT", x=int)`) is deprecated, and will be disallowed in 3.15. Use the class-based syntax or the functional syntax instead.
  - When using the functional syntax to create a `NamedTuple` class, failing to pass a value to the *fields* parameter (`NT = NamedTuple("NT")`) is deprecated. Passing `None` to the *fields* parameter (`NT = NamedTuple("NT", None)`) is also deprecated. Both will be disallowed in Python 3.15. To create a `NamedTuple` class with 0 fields, use `class NT(NamedTuple): pass` or `NT = NamedTuple("NT", [])`.
- `typing.TypedDict`: When using the functional syntax to create a `TypedDict` class, failing to pass a value to the *fields* parameter (`TD = TypedDict("TD")`) is deprecated. Passing `None` to the *fields* parameter (`TD = TypedDict("TD", None)`) is also deprecated. Both will be disallowed in Python 3.15. To create a `TypedDict` class with 0 fields, use `class TD(TypedDict): pass` or `TD = TypedDict("TD", {})`.
- `wave`: Deprecate the `getmark()`, `setmark()` and `getmarkers()` methods of the `wave.Wave_read` and `wave.Wave_write` classes. They will be removed in Python 3.15. (Contributed by Victor Stinner in [gh-105096](#).)

### 8.3 Pending Removal in Python 3.16

- `array.array`: `array 'u' type (wchar_t)`: use the `'w'` type instead (`Py_UCS4`).
- `builtins`: `~bool`, bitwise inversion on `bool`.
- `symtable`: Deprecate `symtable.Class.get_methods()` due to the lack of interest. (Contributed by Bénédict Tran in [gh-119698](#).)

### 8.4 Pending Removal in Future Versions

The following APIs will be removed in the future, although there is currently no date scheduled for their removal.

- `argparse`: Nesting argument groups and nesting mutually exclusive groups are deprecated.
- `array`'s `'u'` format code ([gh-57281](#))
- `builtins`:
  - `bool(NotImplemented)`.
  - `Generators`: `throw(type, exc, tb)` and `athrow(type, exc, tb)` signature is deprecated: use `throw(exc)` and `athrow(exc)` instead, the single argument signature.
  - Currently Python accepts numeric literals immediately followed by keywords, for example `0 in x, 1 or x, 0 if 1 else 2`. It allows confusing and ambiguous expressions like `[0x1 for x in y]` (which can be interpreted as `[0x1 for x in y]` or `[0x1 if or x in y]`). A syntax warning is raised if the numeric literal is immediately followed by one of keywords and, else, for, if, in, is and or. In a future release it will be changed to a syntax error. ([gh-87999](#))

- Support for `__index__()` and `__int__()` method returning non-int type: these methods will be required to return an instance of a strict subclass of `int`.
- Support for `__float__()` method returning a strict subclass of `float`: these methods will be required to return an instance of `float`.
- Support for `__complex__()` method returning a strict subclass of `complex`: these methods will be required to return an instance of `complex`.
- Delegation of `int()` to `__trunc__()` method.
- Passing a complex number as the *real* or *imag* argument in the `complex()` constructor is now deprecated; it should only be passed as a single positional argument. (Contributed by Serhiy Storchaka in [gh-109218](#).)
- `calendar`: `calendar.January` and `calendar.February` constants are deprecated and replaced by `calendar.JANUARY` and `calendar.FEBRUARY`. (Contributed by Prince Roshan in [gh-103636](#).)
- `codeobject.co_lnotab`: use the `codeobject.co_lines()` method instead.
- `datetime`:
  - `utcnow()`: use `datetime.datetime.now(tz =datetime.UTC)`.
  - `utcfromtimestamp()`: use `datetime.datetime.fromtimestamp(timestamp, tz =datetime.UTC)`.
- `gettext`: Plural value must be an integer.
- `importlib`:
  - `load_module()` method: use `exec_module()` instead.
  - `cache_from_source()` *debug\_override* parameter is deprecated: use the *optimization* parameter instead.
- `importlib.metadata`:
  - `EntryPoints` tuple interface.
  - Implicit `None` on return values.
- `logging`: the `warn()` method has been deprecated since Python 3.3, use `warning()` instead.
- `mailbox`: Use of `StringIO` input and text mode is deprecated, use `BytesIO` and binary mode instead.
- `os`: Calling `os.register_at_fork()` in multi-threaded process.
- `pydoc.ErrorDuringImport`: A tuple value for *exc\_info* parameter is deprecated, use an exception instance.
- `re`: More strict rules are now applied for numerical group references and group names in regular expressions. Only sequence of ASCII digits is now accepted as a numerical reference. The group name in bytes patterns and replacement strings can now only contain ASCII letters and digits and underscore. (Contributed by Serhiy Storchaka in [gh-91760](#).)
- `sre_compile`, `sre_constants` and `sre_parse` modules.
- `shutil`: `rmtree()`'s *onerror* parameter is deprecated in Python 3.12; use the *onexc* parameter instead.
- `ssl` options and protocols:
  - `ssl.SSLContext` without protocol argument is deprecated.
  - `ssl.SSLContext`: `set_npn_protocols()` and `selected_npn_protocol()` are deprecated: use ALPN instead.
  - `ssl.OP_NO_SSL*` options
  - `ssl.OP_NO_TLS*` options

- `ssl.PROTOCOL_SSLv3`
- `ssl.PROTOCOL_TLS`
- `ssl.PROTOCOL_TLSv1`
- `ssl.PROTOCOL_TLSv1_1`
- `ssl.PROTOCOL_TLSv1_2`
- `ssl.TLSVersion.SSLv3`
- `ssl.TLSVersion.TLSv1`
- `ssl.TLSVersion.TLSv1_1`
- `sysconfig.is_python_build()` *check\_home* parameter is deprecated and ignored.
- **threading methods:**
  - `threading.Condition.notifyAll()`: use `notify_all()`.
  - `threading.Event.isSet()`: use `is_set()`.
  - `threading.Thread.isDaemon()`, `threading.Thread.setDaemon()`: use `threading.Thread.daemon` **attribute**.
  - `threading.Thread.getName()`, `threading.Thread.setName()`: use `threading.Thread.name` **attribute**.
  - `threading.currentThread()`: use `threading.current_thread()`.
  - `threading.activeCount()`: use `threading.active_count()`.
- `typing.Text` ([gh-92332](#)).
- `unittest.IsolatedAsyncioTestCase`: it is deprecated to return a value that is not `None` from a test case.
- `urllib.parse` **deprecated functions**: `urlparse()` instead
  - `splitattr()`
  - `splithost()`
  - `splitnport()`
  - `splitpasswd()`
  - `splitport()`
  - `splitquery()`
  - `splittag()`
  - `splitttype()`
  - `splituser()`
  - `splitvalue()`
  - `to_bytes()`
- `urllib.request`: `URLOpener` and `FancyURLOpener` style of invoking requests is deprecated. Use newer `urlopen()` **functions and methods**.
- `wsgiref.SimpleHandler.stdout.write()` should not do partial writes.
- `xml.etree.ElementTree`: Testing the truth value of an `Element` is deprecated. In a future release it will always return `True`. Prefer explicit `len(elem)` or `elem is not None` tests instead.



- `zipimport.zipimporter.load_module()` is deprecated: use `exec_module()` instead.

## 9 CPython Bytecode Changes

- The oparg of `YIELD_VALUE` is now 1 if the yield is part of a yield-from or await, and 0 otherwise. The oparg of `RESUME` was changed to add a bit indicating whether the except-depth is 1, which is needed to optimize closing of generators. (Contributed by Irit Katriel in [gh-111354](#).)

## 10 C API Changes

### 10.1 New Features

- You no longer have to define the `PY_SSIZE_T_CLEAN` macro before including `Python.h` when using `#` formats in format codes. APIs accepting the format codes always use `Py_ssize_t` for `#` formats. (Contributed by Inada Naoki in [gh-104922](#).)
- The `keywords` parameter of `PyArg_ParseTupleAndKeywords()` and `PyArg_VaParseTupleAndKeywords()` now has type `char*const*` in C and `const char*const*` in C++, instead of `char**`. It makes these functions compatible with arguments of type `const char*const*`, `const char**` or `char*const*` in C++ and `char*const*` in C without an explicit type cast. This can be overridden with the `PY_CXX_CONST` macro. (Contributed by Serhiy Storchaka in [gh-65210](#).)
- Add `PyImport_AddModuleRef()`: similar to `PyImport_AddModule()`, but return a strong reference instead of a borrowed reference. (Contributed by Victor Stinner in [gh-105922](#).)
- Add `PyWeakref_GetRef()` function: similar to `PyWeakref_GetObject()` but returns a strong reference, or `NULL` if the referent is no longer live. (Contributed by Victor Stinner in [gh-105927](#).)
- Add `PyObject_GetOptionalAttr()` and `PyObject_GetOptionalAttrString()`, variants of `PyObject_GetAttr()` and `PyObject_GetAttrString()` which don't raise `AttributeError` if the attribute is not found. These variants are more convenient and faster if the missing attribute should not be treated as a failure. (Contributed by Serhiy Storchaka in [gh-106521](#).)
- Add `PyMapping_GetOptionalItem()` and `PyMapping_GetOptionalItemString()`: variants of `PyObject_GetItem()` and `PyMapping_GetItemString()` which don't raise `KeyError` if the key is not found. These variants are more convenient and faster if the missing key should not be treated as a failure. (Contributed by Serhiy Storchaka in [gh-106307](#).)
- Add fixed variants of functions which silently ignore errors:
  - `PyObject_HasAttrWithError()` replaces `PyObject_HasAttr()`.
  - `PyObject_HasAttrStringWithError()` replaces `PyObject_HasAttrString()`.
  - `PyMapping_HasKeyWithError()` replaces `PyMapping_HasKey()`.
  - `PyMapping_HasKeyStringWithError()` replaces `PyMapping_HasKeyString()`.

New functions return not only 1 for true and 0 for false, but also -1 for error.

(Contributed by Serhiy Storchaka in [gh-108511](#).)

- If Python is built in debug mode or with assertions, `PyTuple_SET_ITEM()` and `PyList_SET_ITEM()` now check the index argument with an assertion. (Contributed by Victor Stinner in [gh-106168](#).)

- Add `PyModule_Add()` function: similar to `PyModule_AddObjectRef()` and `PyModule_AddObject()` but always steals a reference to the value. (Contributed by Serhiy Storchaka in [gh-86493](#).)
- Add `PyDict_GetItemRef()` and `PyDict_GetItemStringRef()` functions: similar to `PyDict_GetItemWithError()` but returning a strong reference instead of a borrowed reference. Moreover, these functions return -1 on error and so checking `PyErr_Occurred()` is not needed. (Contributed by Victor Stinner in [gh-106004](#).)
- Added `PyDict_SetDefaultRef()`, which is similar to `PyDict_SetDefault()` but returns a strong reference instead of a borrowed reference. This function returns -1 on error, 0 on insertion, and 1 if the key was already present in the dictionary. (Contributed by Sam Gross in [gh-112066](#).)
- Add `PyDict_ContainsString()` function: same as `PyDict_Contains()`, but `key` is specified as a `const char*` UTF-8 encoded bytes string, rather than a `PyObject*`. (Contributed by Victor Stinner in [gh-108314](#).)
- Added `PyList_GetItemRef()` function: similar to `PyList_GetItem()` but returns a strong reference instead of a borrowed reference.
- Add `Py_IsFinalizing()` function: check if the main Python interpreter is shutting down. (Contributed by Victor Stinner in [gh-108014](#).)
- Add `PyLong_AsInt()` function: similar to `PyLong_AsLong()`, but store the result in a C `int` instead of a C `long`. Previously, it was known as the private function `_PyLong_AsInt()` (with an underscore prefix). (Contributed by Victor Stinner in [gh-108014](#).)
- Python built with `configure --with-trace-refs` (tracing references) now supports the Limited API. (Contributed by Victor Stinner in [gh-108634](#).)
- Add `PyObject_VisitManagedDict()` and `PyObject_ClearManagedDict()` functions which must be called by the traverse and clear functions of a type using `Py_TPFLAGS_MANAGED_DICT` flag. The [pythoncapi-compat](#) project can be used to get these functions on Python 3.11 and 3.12. (Contributed by Victor Stinner in [gh-107073](#).)
- Add `PyUnicode_EqualToUTF8AndSize()` and `PyUnicode_EqualToUTF8()` functions: compare Unicode object with a `const char*` UTF-8 encoded string and return true (1) if they are equal, or false (0) otherwise. These functions do not raise exceptions. (Contributed by Serhiy Storchaka in [gh-110289](#).)
- Add `PyThreadState_GetUnchecked()` function: similar to `PyThreadState_Get()`, but don't kill the process with a fatal error if it is NULL. The caller is responsible to check if the result is NULL. Previously, the function was private and known as `_PyThreadState_UncheckedGet()`. (Contributed by Victor Stinner in [gh-108867](#).)
- Add `PySys_AuditTuple()` function: similar to `PySys_Audit()`, but pass event arguments as a Python tuple object. (Contributed by Victor Stinner in [gh-85283](#).)
- `PyArg_ParseTupleAndKeywords()` now supports non-ASCII keyword parameter names. (Contributed by Serhiy Storchaka in [gh-110815](#).)
- Add `PyMem_RawMalloc()`, `PyMem_RawCalloc()`, `PyMem_RawRealloc()` and `PyMem_RawFree()` to the limited C API (version 3.13). (Contributed by Victor Stinner in [gh-85283](#).)
- Add `PySys_Audit()` and `PySys_AuditTuple()` functions to the limited C API. (Contributed by Victor Stinner in [gh-85283](#).)
- Add `PyErr_FormatUnraisable()` function: similar to `PyErr_WriteUnraisable()`, but allow customizing the warning message. (Contributed by Serhiy Storchaka in [gh-108082](#).)
- Add `PyList_Extend()` and `PyList_Clear()` functions: similar to `Python list.extend()` and `list.clear()` methods. (Contributed by Victor Stinner in [gh-111138](#).)

- Add `PyDict_Pop()` and `PyDict_PopString()` functions: remove a key from a dictionary and optionally return the removed value. This is similar to `dict.pop()`, but without the default value and not raising `KeyError` if the key is missing. (Contributed by Stefan Behnel and Victor Stinner in [gh-111262](#).)
- Add `Py_HashPointer()` function to hash a pointer. (Contributed by Victor Stinner in [gh-111545](#).)
- Add `PyObject_GenericHash()` function that implements the default hashing function of a Python object. (Contributed by Serhiy Storchaka in [gh-113024](#).)
- Add PyTime C API:
  - `PyTime_t` type.
  - `PyTime_MIN` and `PyTime_MAX` constants.
  - Add functions:
    - \* `PyTime_AsSecondsDouble()`.
    - \* `PyTime_Monotonic()`.
    - \* `PyTime_MonotonicRaw()`.
    - \* `PyTime_PerfCounter()`.
    - \* `PyTime_PerfCounterRaw()`.
    - \* `PyTime_Time()`.
    - \* `PyTime_TimeRaw()`.

(Contributed by Victor Stinner and Petr Viktorin in [gh-110850](#).)

- Add `PyLong_AsNativeBytes()`, `PyLong_FromNativeBytes()` and `PyLong_FromUnsignedNativeBytes()` functions to simplify converting between native integer types and Python `int` objects. (Contributed by Steve Dower in [gh-111140](#).)
- Add `PyType_GetFullyQualifiedName()` function to get the type's fully qualified name. Equivalent to `f"{type.__module__}.{type.__qualname__}"`, or `type.__qualname__` if `type.__module__` is not a string or is equal to `"builtins"`. (Contributed by Victor Stinner in [gh-111696](#).)
- Add `PyType_GetModuleName()` function to get the type's module name. Equivalent to getting the `type.__module__` attribute. (Contributed by Eric Snow and Victor Stinner in [gh-111696](#).)
- Add support for `%T`, `##T`, `%N` and `##N` formats to `PyUnicode_FromFormat()`: format the fully qualified name of an object type and of a type: call `PyType_GetModuleName()`. See [PEP 737](#) for more information. (Contributed by Victor Stinner in [gh-111696](#).)
- Add `Py_GetConstant()` and `Py_GetConstantBorrowed()` functions to get constants. For example, `Py_GetConstant(Py_CONSTANT_ZERO)` returns a strong reference to the constant zero. (Contributed by Victor Stinner in [gh-115754](#).)
- Add `PyType_GetModuleByDef()` to the limited C API (Contributed by Victor Stinner in [gh-116936](#).)
- Add two new functions to the C-API, `PyRefTracer_SetTracer()` and `PyRefTracer_GetTracer()`, that allow to track object creation and destruction the same way the `tracemalloc` module does. (Contributed by Pablo Galindo in [gh-93502](#).)
- Add `PyEval_GetFrameBuiltins()`, `PyEval_GetFrameGlobals()`, and `PyEval_GetFrameLocals()` to the C API. These replacements for `PyEval_GetBuiltins()`, `PyEval_GetGlobals()`, and `PyEval_GetLocals()` return strong references rather than borrowed references. (Added as part of [PEP 667](#).)
- Add `PyMutex` API, a lightweight mutex that occupies a single byte. The `PyMutex_Lock()` function will release the GIL (if currently held) if the operation needs to block. (Contributed by Sam Gross in [gh-108724](#).)

## 11 Build Changes

- The configure option `--with-system-libmpdec` now defaults to `yes`. The bundled copy of `libmpdecimal` will be removed in Python 3.15.
- Autoconf 2.71 and aclocal 1.16.4 are now required to regenerate the `configure` script. (Contributed by Christian Heimes in [gh-89886](#).)
- SQLite 3.15.2 or newer is required to build the `sqlite3` extension module. (Contributed by Erlend Aasland in [gh-105875](#).)
- Python built with `configure --with-trace-refs` (tracing references) is now ABI compatible with the Python release build and debug build. (Contributed by Victor Stinner in [gh-108634](#).)
- Building CPython now requires a compiler with support for the C11 atomic library, GCC built-in atomic functions, or MSVC interlocked intrinsics.
- The `errno`, `fcntl`, `grp`, `md5`, `pwd`, `resource`, `termios`, `winsound`, `_ctypes_test`, `_multiprocessing.posixshm`, `_scproxy`, `_stat`, `_statistics`, `_testconsole`, `_testimportmultiple` and `_uuid` C extensions are now built with the limited C API. (Contributed by Victor Stinner in [gh-85283](#).)
- `wasm32-wasi` is now a **PEP 11** tier 2 platform. (Contributed by Brett Cannon in [gh-115192](#).)
- `wasm32-emscripten` is no longer a **PEP 11** supported platform. (Contributed by Brett Cannon in [gh-115192](#).)
- Python now bundles the `mimalloc` library. It is licensed under the MIT license; see `mimalloc` license. The bundled `mimalloc` has custom changes, see [gh-113141](#) for details. (Contributed by Dino Viehland in [gh-109914](#).)
- On POSIX systems, the `pkg-config (.pc)` filenames now include the ABI flags. For example, the free-threaded build generates `python-3.13t.pc` and the debug build generates `python-3.13d.pc`.

## 12 Porting to Python 3.13

This section lists previously described changes and other bugfixes that may require changes to your code.

### 12.1 Changes in the Python API

- An `OSError` is now raised by `getpass.getuser()` for any failure to retrieve a username, instead of `ImportError` on non-Unix platforms or `KeyError` on Unix platforms where the password database is empty.
- The `threading` module now expects the `_thread` module to have an `_is_main_interpreter` attribute. It is a function with no arguments that returns `True` if the current interpreter is the main interpreter.  
Any library or application that provides a custom `_thread` module must provide `_is_main_interpreter()`, just like the module's other “private” attributes. (See [gh-112826](#).)
- `mailbox.Maildir` now ignores files with a leading dot. (Contributed by Zackery Spytz in [gh-65559](#).)
- `pathlib.Path.glob()` and `rglob()` now return both files and directories if a pattern that ends with “`***`” is given, rather than directories only. Users may add a trailing slash to match only directories.
- The value of the `mode` attribute of `gzip.GzipFile` was changed from integer (1 or 2) to string (`'rb'` or `'wb'`). The value of the `mode` attribute of the readable file-like object returned by `zipfile.ZipFile.open()` was changed from `'r'` to `'rb'`. (Contributed by Serhiy Storchaka in [gh-115961](#).)

- `functools.partial` now emits a `FutureWarning` when it is used as a method. Its behavior will be changed in future Python versions. Wrap it in `staticmethod()` if you want to preserve the old behavior. (Contributed by Serhiy Storchaka in [gh-121027](#).)
- Calling `locals()` in an optimized scope now produces an independent snapshot on each call, and hence no longer implicitly updates previously returned references. Obtaining the legacy CPython behaviour now requires explicit calls to update the initially returned dictionary with the results of subsequent calls to `locals()`. Code execution functions that implicitly target `locals()` (such as `exec` and `eval`) must be passed an explicit namespace to access their results in an optimized scope. (Changed as part of [PEP 667](#).)
- Calling `locals()` from a comprehension at module or class scope (including via `exec` or `eval`) once more behaves as if the comprehension were running as an independent nested function (i.e. the local variables from the containing scope are not included). In Python 3.12, this had changed to include the local variables from the containing scope when implementing [PEP 709](#). (Changed as part of [PEP 667](#).)
- Accessing `FrameType.f_locals` in an optimized scope now returns a write-through proxy rather than a snapshot that gets updated at ill-specified times. If a snapshot is desired, it must be created explicitly with `dict` or the proxy's `.copy()` method. (Changed as part of [PEP 667](#).)

## 12.2 Changes in the C API

- `Python.h` no longer includes the `<ieeefp.h>` standard header. It was included for the `finite()` function which is now provided by the `<math.h>` header. It should now be included explicitly if needed. Remove also the `HAVE_IEEEFP_H` macro. (Contributed by Victor Stinner in [gh-108765](#).)
- `Python.h` no longer includes these standard header files: `<time.h>`, `<sys/select.h>` and `<sys/time.h>`. If needed, they should now be included explicitly. For example, `<time.h>` provides the `clock()` and `gmtime()` functions, `<sys/select.h>` provides the `select()` function, and `<sys/time.h>` provides the `futimes()`, `gettimeofday()` and `setitimer()` functions. (Contributed by Victor Stinner in [gh-108765](#).)
- On Windows, `Python.h` no longer includes the `<stddef.h>` standard header file. If needed, it should now be included explicitly. For example, it provides `offsetof()` function, and `size_t` and `ptrdiff_t` types. Including `<stddef.h>` explicitly was already needed by all other platforms, the `HAVE_STDDEF_H` macro is only defined on Windows. (Contributed by Victor Stinner in [gh-108765](#).)
- If the `Py_LIMITED_API` macro is defined, `Py_BUILD_CORE`, `Py_BUILD_CORE_BUILTIN` and `Py_BUILD_CORE_MODULE` macros are now undefined by `<Python.h>`. (Contributed by Victor Stinner in [gh-85283](#).)
- The old trashcan macros `Py_TRASHCAN_SAFE_BEGIN` and `Py_TRASHCAN_SAFE_END` were removed. They should be replaced by the new macros `Py_TRASHCAN_BEGIN` and `Py_TRASHCAN_END`.

A `tp_dealloc` function that has the old macros, such as:

```
static void
mytype_dealloc(mytype *p)
{
    PyObject_GC_UnTrack(p);
    Py_TRASHCAN_SAFE_BEGIN(p);
    ...
    Py_TRASHCAN_SAFE_END
}
```

should migrate to the new macros as follows:

```
static void
mytype_dealloc(mytype *p)
{
    PyObject_GC_UnTrack(p);
    Py_TRASHCAN_BEGIN(p, mytype_dealloc)
    ...
    Py_TRASHCAN_END
}
```

Note that `Py_TRASHCAN_BEGIN` has a second argument which should be the deallocation function it is in. The new macros were added in Python 3.8 and the old macros were deprecated in Python 3.11. (Contributed by Irit Katriel in [gh-105111](#).)

- **Functions** `PyDict_GetItem()`, `PyDict_GetItemString()`, `PyMapping_HasKey()`, `PyMapping_HasKeyString()`, `PyObject_HasAttr()`, `PyObject_HasAttrString()`, and `PySys_GetObject()`, which clear all errors which occurred when calling them, now report them using `sys.unraisablehook()`. You may replace them with other functions as recommended in the documentation. (Contributed by Serhiy Storchaka in [gh-106672](#).)
- `PyCode_GetFirstFree()` is an unstable API now and has been renamed to `PyUnstable_Code_GetFirstFree()`. (Contributed by Bogdan Romanyuk in [gh-115781](#).)
- The effects of mutating the dictionary returned from `PyEval_GetLocals()` in an optimized scope have changed. New dict entries added this way will now *only* be visible to subsequent `PyEval_GetLocals()` calls in that frame, as `PyFrame_GetLocals()`, `locals()`, and `FrameType.f_locals` no longer access the same underlying cached dictionary. Changes made to entries for actual variable names and names added via the write-through proxy interfaces will be overwritten on subsequent calls to `PyEval_GetLocals()` in that frame. The recommended code update depends on how the function was being used, so refer to the deprecation notice on the function for details. (Changed as part of [PEP 667](#).)
- Calling `PyFrame_GetLocals()` in an optimized scope now returns a write-through proxy rather than a snapshot that gets updated at ill-specified times. If a snapshot is desired, it must be created explicitly (e.g. with `PyDict_Copy()`) or by calling the new `PyEval_GetFrameLocals()` API. (Changed as part of [PEP 667](#).)
- `PyFrame_FastToLocals()` and `PyFrame_FastToLocalsWithError()` no longer have any effect. Calling these functions has been redundant since Python 3.11, when `PyFrame_GetLocals()` was first introduced. (Changed as part of [PEP 667](#).)
- `PyFrame_LocalsToFast()` no longer has any effect. Calling this function is redundant now that `PyFrame_GetLocals()` returns a write-through proxy for optimized scopes. (Changed as part of [PEP 667](#).)

## 12.3 Removed C APIs

- Remove many APIs (functions, macros, variables) with names prefixed by `_Py` or `_PY` (considered as private API). If your project is affected by one of these removals and you consider that the removed API should remain available, please open a new issue to request a public C API and add `cc @vstinner` to the issue to notify Victor Stinner. (Contributed by Victor Stinner in [gh-106320](#).)
- Remove functions deprecated in Python 3.9:
  - `PyEval_CallObject()`, `PyEval_CallObjectWithKeywords()`: use `PyObject_CallNoArgs()` or `PyObject_Call()` instead. Warning: `PyObject_Call()` positional arguments must be a tuple and must not be NULL, keyword arguments must be a dict or NULL, whereas removed functions checked arguments type and accepted NULL positional and keyword arguments. To replace `PyEval_CallObjectWithKeywords(func, NULL, kwargs)` with `PyObject_Call()`, pass an empty tuple as positional arguments using `PyTuple_New(0)`.
  - `PyEval_CallFunction()`: use `PyObject_CallFunction()` instead.

- `PyEval_CallMethod()`: use `PyObject_CallMethod()` instead.
- `PyCFunction_Call()`: use `PyObject_Call()` instead.

(Contributed by Victor Stinner in [gh-105107](#).)

- Remove old buffer protocols deprecated in Python 3.0. Use `bufferobjects` instead.

- `PyObject_CheckReadBuffer()`: Use `PyObject_CheckBuffer()` to test if the object supports the buffer protocol. Note that `PyObject_CheckBuffer()` doesn't guarantee that `PyObject_GetBuffer()` will succeed. To test if the object is actually readable, see the next example of `PyObject_GetBuffer()`.
- `PyObject_AsCharBuffer()`, `PyObject_AsReadBuffer()`: `PyObject_GetBuffer()` and `PyBuffer_Release()` instead:

```
Py_buffer view;
if (PyObject_GetBuffer(obj, &view, PyBUF_SIMPLE) < 0) {
    return NULL;
}
// Use `view.buf` and `view.len` to read from the buffer.
// You may need to cast buf as `(const char*)view.buf`.
PyBuffer_Release(&view);
```

- `PyObject_AsWriteBuffer()`: Use `PyObject_GetBuffer()` and `PyBuffer_Release()` instead:

```
Py_buffer view;
if (PyObject_GetBuffer(obj, &view, PyBUF_WRITABLE) < 0) {
    return NULL;
}
// Use `view.buf` and `view.len` to write to the buffer.
PyBuffer_Release(&view);
```

(Contributed by Inada Naoki in [gh-85275](#).)

- Remove the following old functions to configure the Python initialization, deprecated in Python 3.11:
  - `PySys_AddWarnOptionUnicode()`: use `PyConfig.warnoptions` instead.
  - `PySys_AddWarnOption()`: use `PyConfig.warnoptions` instead.
  - `PySys_AddXOption()`: use `PyConfig.xoptions` instead.
  - `PySys_HasWarnOptions()`: use `PyConfig.xoptions` instead.
  - `PySys_SetPath()`: set `PyConfig.module_search_paths` instead.
  - `Py_SetPath()`: set `PyConfig.module_search_paths` instead.
  - `Py_SetStandardStreamEncoding()`: set `PyConfig.stdio_encoding` instead, and set also maybe `PyConfig.legacy_windows_stdio` (on Windows).
  - `_Py_SetProgramFullPath()`: set `PyConfig.executable` instead.

Use the new `PyConfig` API of the Python Initialization Configuration instead ([PEP 587](#)), added to Python 3.8. (Contributed by Victor Stinner in [gh-105145](#).)

- Remove `PyEval_ThreadsInitialized()` function, deprecated in Python 3.9. Since Python 3.7, `Py_Initialize()` always creates the GIL: calling `PyEval_InitThreads()` does nothing and `PyEval_ThreadsInitialized()` always returned non-zero. (Contributed by Victor Stinner in [gh-105182](#).)
- Remove `PyEval_AcquireLock()` and `PyEval_ReleaseLock()` functions, deprecated in Python 3.2. They didn't update the current thread state. They can be replaced with:



- `PyEval_SaveThread()` and `PyEval_RestoreThread()`;
- low-level `PyEval_AcquireThread()` and `PyEval_RestoreThread()`;
- or `PyGILState_Ensure()` and `PyGILState_Release()`.

(Contributed by Victor Stinner in [gh-105182](#).)

- Remove private `_PyObject_FastCall()` function: use `PyObject_Vectorcall()` which is available since Python 3.8 (**PEP 590**). (Contributed by Victor Stinner in [gh-106023](#).)
- Remove `cpython/pytime.h` header file: it only contained private functions. (Contributed by Victor Stinner in [gh-106316](#).)
- Remove `_PyInterpreterState_Get()` alias to `PyInterpreterState_Get()` which was kept for backward compatibility with Python 3.8. The [pythoncapi-compat](#) project can be used to get `PyInterpreterState_Get()` on Python 3.8 and older. (Contributed by Victor Stinner in [gh-106320](#).)
- The `PyModule_AddObject()` function is now soft deprecated: `PyModule_Add()` or `PyModule_AddObjectRef()` functions should be used instead. (Contributed by Serhiy Storchaka in [gh-86493](#).)
- Remove undocumented `PY_TIMEOUT_MAX` constant from the limited C API. (Contributed by Victor Stinner in [gh-110014](#).)

## 12.4 Deprecated C APIs

- Deprecate the old `Py_UNICODE` and `PY_UNICODE_TYPE` types: use directly the `wchar_t` type instead. Since Python 3.3, `Py_UNICODE` and `PY_UNICODE_TYPE` are just aliases to `wchar_t`. (Contributed by Victor Stinner in [gh-105156](#).)
- Deprecate old Python initialization functions:
  - `PySys_ResetWarnOptions()`: clear `sys.warnoptions` and `warnings.filters` instead.
  - `Py_GetExecPrefix()`: get `sys.exec_prefix` instead.
  - `Py_GetPath()`: get `sys.path` instead.
  - `Py_GetPrefix()`: get `sys.prefix` instead.
  - `Py_GetProgramFullPath()`: get `sys.executable` instead.
  - `Py_GetProgramName()`: get `sys.executable` instead.
  - `Py_GetPythonHome()`: get `PyConfig.home` or `PYTHONHOME` environment variable instead.

Functions scheduled for removal in Python 3.15. (Contributed by Victor Stinner in [gh-105145](#).)

- Deprecate the `PyImport_ImportModuleNoBlock()` function which is just an alias to `PyImport_ImportModule()` since Python 3.3. Scheduled for removal in Python 3.15. (Contributed by Victor Stinner in [gh-105396](#).)
- Deprecate the `PyWeakref_GetObject()` and `PyWeakref_GET_OBJECT()` functions, which return a borrowed reference: use the new `PyWeakref_GetRef()` function instead, it returns a strong reference. The [pythoncapi-compat](#) project can be used to get `PyWeakref_GetRef()` on Python 3.12 and older. (Contributed by Victor Stinner in [gh-105927](#).)
- Deprecate the `PyEval_GetBuiltins()`, `PyEval_GetGlobals()`, and `PyEval_GetLocals()` functions, which return a borrowed reference. Refer to the deprecation notices on each function for their recommended replacements. (Soft deprecated as part of **PEP 667**.)



## Pending Removal in Python 3.14

- The `ma_version_tag` field in `PyDictObject` for extension modules ([PEP 699](#); [gh-101193](#)).
- Creating immutable types with mutable bases ([gh-95388](#)).
- Functions to configure Python's initialization, deprecated in Python 3.11:
  - `PySys_SetArgvEx()`: set `PyConfig.argv` instead.
  - `PySys_SetArgv()`: set `PyConfig.argv` instead.
  - `Py_SetProgramName()`: set `PyConfig.program_name` instead.
  - `Py_SetPythonHome()`: set `PyConfig.home` instead.

The `Py_InitializeFromConfig()` API should be used with `PyConfig` instead.

- Global configuration variables:
  - `Py_DebugFlag`: use `PyConfig.parser_debug` instead.
  - `Py_VerboseFlag`: use `PyConfig.verbose` instead.
  - `Py_QuietFlag`: use `PyConfig.quiet` instead.
  - `Py_InteractiveFlag`: use `PyConfig.interactive` instead.
  - `Py_InspectFlag`: use `PyConfig.inspect` instead.
  - `Py_OptimizeFlag`: use `PyConfig.optimization_level` instead.
  - `Py_NoSiteFlag`: use `PyConfig.site_import` instead.
  - `Py_BytesWarningFlag`: use `PyConfig.bytes_warning` instead.
  - `Py_FrozenFlag`: use `PyConfig.pathconfig_warnings` instead.
  - `Py_IgnoreEnvironmentFlag`: use `PyConfig.use_environment` instead.
  - `Py_DontWriteBytecodeFlag`: use `PyConfig.write_bytecode` instead.
  - `Py_NoUserSiteDirectory`: use `PyConfig.user_site_directory` instead.
  - `Py_UnbufferedStdioFlag`: use `PyConfig.buffered_stdio` instead.
  - `Py_HashRandomizationFlag`: use `PyConfig.use_hash_seed` and `PyConfig.hash_seed` instead.
  - `Py_IsolatedFlag`: use `PyConfig.isolated` instead.
  - `Py_LegacyWindowsFSEncodingFlag`: use `PyPreConfig.legacy_windows_fs_encoding` instead.
  - `Py_LegacyWindowsStdioFlag`: use `PyConfig.legacy_windows_stdio` instead.
  - `Py_FileSystemDefaultEncoding`: use `PyConfig.filesystem_encoding` instead.
  - `Py_HasFileSystemDefaultEncoding`: use `PyConfig.filesystem_encoding` instead.
  - `Py_FileSystemDefaultEncodeErrors`: use `PyConfig.filesystem_errors` instead.
  - `Py_UTF8Mode`: use `PyPreConfig.utf8_mode` instead. (see `Py_PreInitialize()`)

The `Py_InitializeFromConfig()` API should be used with `PyConfig` instead.

## Pending Removal in Python 3.15

- The bundled copy of `libmpdecimal`.
- `PyImport_ImportModuleNoBlock()`: use `PyImport_ImportModule()` instead.
- `PyWeakref_GET_OBJECT()`: use `PyWeakref_GetRef()` instead.
- `PyWeakref_GetObject()`: use `PyWeakref_GetRef()` instead.
- `Py_UNICODE_WIDE` type: use `wchar_t` instead.
- `Py_UNICODE` type: use `wchar_t` instead.
- Python initialization functions:
  - `PySys_ResetWarnOptions()`: clear `sys.warnoptions` and `warnings.filters` instead.
  - `Py_GetExecPrefix()`: get `sys.exec_prefix` instead.
  - `Py_GetPath()`: get `sys.path` instead.
  - `Py_GetPrefix()`: get `sys.prefix` instead.
  - `Py_GetProgramFullPath()`: get `sys.executable` instead.
  - `Py_GetProgramName()`: get `sys.executable` instead.
  - `Py_GetPythonHome()`: get `PyConfig.home` or the `PYTHONHOME` environment variable instead.

## Pending Removal in Future Versions

The following APIs are deprecated and will be removed, although there is currently no date scheduled for their removal.

- `Py_TPFLAGS_HAVE_FINALIZE`: unneeded since Python 3.8.
- `PyErr_Fetch()`: use `PyErr_GetRaisedException()` instead.
- `PyErr_NormalizeException()`: use `PyErr_GetRaisedException()` instead.
- `PyErr_Restore()`: use `PyErr_SetRaisedException()` instead.
- `PyModule_GetFilename()`: use `PyModule_GetFilenameObject()` instead.
- `PyOS_AfterFork()`: use `PyOS_AfterFork_Child()` instead.
- `PySlice_GetIndicesEx()`: use `PySlice_Unpack()` and `PySlice_AdjustIndices()` instead.
- `PyUnicode_AsDecodedObject()`: use `PyCodec_Decode()` instead.
- `PyUnicode_AsDecodedUnicode()`: use `PyCodec_Decode()` instead.
- `PyUnicode_AsEncodedObject()`: use `PyCodec_Encode()` instead.
- `PyUnicode_AsEncodedUnicode()`: use `PyCodec_Encode()` instead.
- `PyUnicode_READY()`: unneeded since Python 3.12
- `PyErr_Display()`: use `PyErr_DisplayException()` instead.
- `_PyErr_ChainExceptions()`: use `_PyErr_ChainExceptions1` instead.
- `PyBytesObject.ob_shash` member: call `PyObject_Hash()` instead.
- `PyDictObject.ma_version_tag` member.
- Thread Local Storage (TLS) API:
  - `PyThread_create_key()`: use `PyThread_tss_alloc()` instead.

- `PyThread_delete_key()`: use `PyThread_tss_free()` instead.
- `PyThread_set_key_value()`: use `PyThread_tss_set()` instead.
- `PyThread_get_key_value()`: use `PyThread_tss_get()` instead.
- `PyThread_delete_key_value()`: use `PyThread_tss_delete()` instead.
- `PyThread_ReInitTLS()`: unneeded since Python 3.7.

## 13 Regression Test Changes

- Python built with `configure --with-pydebug` now supports a `-X presite =package.module` command-line option. If used, it specifies a module that should be imported early in the lifecycle of the interpreter, before `site.py` is executed. (Contributed by Łukasz Langa in [gh-110769](#).)

## Dizin

### O

ortam değişkeni

- PYTHON\_BASIC\_REPL, 6
- PYTHON\_COLORS, 4, 6, 14
- PYTHON\_CPU\_COUNT, 16
- PYTHON\_FROZEN\_MODULES, 10
- PYTHON\_GIL, 7
- PYTHON\_HISTORY, 10
- PYTHON\_PERF\_JIT\_SUPPORT, 10
- PYTHONHOME, 40, 42
- PYTHONLEGACYWINDOWSFSENCODING, 27

### P

Python Geliştirme Önerileri

- PEP 11, 9, 36
- PEP 11#tier-2, 5
- PEP 11#tier-3, 5
- PEP 587, 39
- PEP 590, 40
- PEP 594, 3, 23
- PEP 602, 5
- PEP 626, 29
- PEP 667, 4, 8, 35, 37, 38, 40
- PEP 696, 5
- PEP 699, 41
- PEP 702, 5, 22
- PEP 703, 3, 4, 7
- PEP 705, 5, 21
- PEP 709, 37
- PEP 719, 3
- PEP 730, 5, 9
- PEP 737, 35
- PEP 738, 5, 9
- PEP 742, 5, 21
- PEP 744, 3, 4, 8

- PYTHON\_BASIC\_REPL, 6
- PYTHON\_COLORS, 4, 6, 14
- PYTHON\_CPU\_COUNT, 16
- PYTHON\_FROZEN\_MODULES, 10
- PYTHON\_GIL, 7
- PYTHON\_HISTORY, 10
- PYTHON\_PERF\_JIT\_SUPPORT, 10
- PYTHONHOME, 40, 42
- PYTHONLEGACYWINDOWSFSENCODING, 27

### R

RFC

- RFC 5280, 19