
Extending and Embedding Python

Yayım 3.13.0

Guido van Rossum and the Python development team

Kasım 15, 2024

1 Önerilen üçüncü taraf araçları	3
2 Üçüncü taraf araçları olmadan uzantılar oluşturma	5
2.1 Extending Python with C or C++	5
2.1.1 A Simple Example	5
2.1.2 Intermezzo: Errors and Exceptions	7
2.1.3 Back to the Example	8
2.1.4 The Module's Method Table and Initialization Function	9
2.1.5 Compilation and Linkage	11
2.1.6 Calling Python Functions from C	11
2.1.7 Extracting Parameters in Extension Functions	13
2.1.8 Keyword Parameters for Extension Functions	15
2.1.9 Building Arbitrary Values	16
2.1.10 Reference Counts	17
2.1.11 Writing Extensions in C++	20
2.1.12 Providing a C API for an Extension Module	20
2.2 Defining Extension Types: Tutorial	23
2.2.1 The Basics	23
2.2.2 Adding data and methods to the Basic example	27
2.2.3 Providing finer control over data attributes	34
2.2.4 Supporting cyclic garbage collection	39
2.2.5 Subclassing other types	44
2.3 Defining Extension Types: Assorted Topics	47
2.3.1 Finalization and De-allocation	49
2.3.2 Object Presentation	50
2.3.3 Attribute Management	51
2.3.4 Object Comparison	53
2.3.5 Abstract Protocol Support	53
2.3.6 Weak Reference Support	55
2.3.7 More Suggestions	55
2.4 Building C and C++ Extensions	56
2.4.1 Building C and C++ Extensions with setuptools	56
2.5 Windows'ta C ve C++ Uzantıları Oluşturmak	56
2.5.1 Bir Yemek Kitabı Yaklaşımı	57
2.5.2 Unix ve Windows Arasındaki Farklar	57
2.5.3 DLL'leri Uygulamada Kullanma	58
3 CPython çalışma zamanını daha büyük bir uygulamaya gömme	59
3.1 Python'ı Başka Bir Uygulamaya Gömme	59
3.1.1 Çok Üst Düzey Gömmme	60
3.1.2 Çok Yüksek Düzeyde Gömmenin Ötesinde: Genel Bir Bakış	61

3.1.3	Saf Gömme	61
3.1.4	Gömülü Python'u Genişletme	63
3.1.5	Python'u C++'a Gömmek	64
3.1.6	Unix benzeri sistemler altında Derleme ve Bağlama	64
A	Sözlük	67
B	Bu dokümanlar hakkında	85
B.1	Python Dokümantasyonuna Katkıda Bulunanlar	85
C	Tarihçe ve Lisans	87
C.1	Yazılımin tarihçesi	87
C.2	Python'a erişmek veya başka bir şekilde kullanmak için şartlar ve koşullar	88
C.2.1	PYTHON İÇİN PSF LİSANS ANLAŞMASI 3.13.0	88
C.2.2	PYTHON 2.0 İÇİN BEOPEN.COM LİSANS SÖZLEŞMESİ	89
C.2.3	PYTHON 1.6.1 İÇİN CNRI LİSANS ANLAŞMASI	89
C.2.4	0.9.0 ARASI 1.2 PYTHON İÇİN CWI LİSANS SÖZLEŞMESİ	90
C.2.5	PYTHON 3.13.0 BELGELERİNDEKİ KOD İÇİN SIFIR MADDE BSD LİSANSI	91
C.3	Tüzel Yazılımlar için Lisanslar ve Onaylar	91
C.3.1	Mersenne Twister'ı	91
C.3.2	Soketler	92
C.3.3	Asenkron soket hizmetleri	93
C.3.4	Çerez yönetimi	93
C.3.5	Çalıştırma izleme	94
C.3.6	UUencode ve UUdecode fonksiyonları	94
C.3.7	XML Uzaktan Yordam Çağrıları	95
C.3.8	test_epoll	95
C.3.9	kqueue seçin	96
C.3.10	SipHash24	96
C.3.11	strtod ve dtoa	97
C.3.12	OpenSSL	97
C.3.13	expat	100
C.3.14	libffi	101
C.3.15	zlib	101
C.3.16	cfuhash	102
C.3.17	libmpdec	102
C.3.18	W3C C14N test paketi	103
C.3.19	mimalloc	104
C.3.20	asyncio	104
C.3.21	Global Unbounded Sequences (GUS)	104
D	Telif Hakkı	107
Dizin		109

Bu belge, Python yorumlayıcısını yeni modüllerle genişletmek için C veya C++’da modüllerin nasıl yazılacağını açıklar. Bu modüller sadece yeni fonksiyonları değil, aynı zamanda yeni nesne tiplerini ve metodlarını da tanımlayabilir. Belge ayrıca Python yorumlayıcısının bir uzantı dili olarak kullanılmak üzere başka bir uygulamaya nasıl yerleştirileceğini de açıklar. Son olarak, temeldeki işletim sistemi bu özelliği destekliyorsa, uzantı modüllerinin yorumlayıcıya dinamik olarak (çalışma zamanında) yüklenmesi için nasıl derleneceğini ve bağlanacağını gösterir.

Bu belge, Python hakkında temel bilgiye sahip olduğunuzu varsayar. Dile gayri resmi bir giriş için bkz. library-index. library-index, dilin daha resmi bir tanımını verir. library-index, dile geniş uygulama yelpazesi sağlayan mevcut nesne türlerini, işlevleri ve modülleri (hem yerleşik hem de Python’da yazılmış) belgeler.

Tüm Python/C API’sinin ayrıntılı açıklaması için ayrı c-api-index’a bakın.

BÖLÜM 1

Önerilen üçüncü taraf araçları

Bu kılavuz, yalnızca CPython'un bu sürümünün bir parçası olarak sağlanan uzantıları oluşturmak için temel araçları kapsar. [Cython](#), [cffi](#), [SWIG](#) ve [Numba](#) gibi üçüncü taraf araçlar, Python için C ve C++ uzantıları oluşturmaya yönelik hem daha basit hem de daha karmaşık yaklaşım sunar.

Ayrıca bakınız

Python Paketleme Kullanıcı Kılavuzu: İkili Uzantılar

Python Paketleme Kullanıcı Kılavuzu, yalnızca ikili uzantıların oluşturulmasını basitleştiren çeşitli mevcut araçları kapsamakla kalmaz, aynı zamanda bir uzantı modülü oluşturmanın en başta neden istenebileceğinin çeşitli nedenlerini de tartışır.

BÖLÜM 2

Üçüncü taraf araçları olmadan uzantılar oluşturma

Kılavuzun bu bölümü, üçüncü taraf araçlardan yardım almadan C ve C++ uzantıları oluşturmayı kapsar. Kendi C uzantılarınızı oluşturmanız için önerilen bir yol olmaktan ziyade, öncelikle bu araçların yaratıcılarına yönelikir.

2.1 Extending Python with C or C++

It is quite easy to add new built-in modules to Python, if you know how to program in C. Such *extension modules* can do two things that can't be done directly in Python: they can implement new built-in object types, and they can call C library functions and system calls.

To support extensions, the Python API (Application Programmers Interface) defines a set of functions, macros and variables that provide access to most aspects of the Python run-time system. The Python API is incorporated in a C source file by including the header "Python.h".

The compilation of an extension module depends on its intended use as well as on your system setup; details are given in later chapters.

Not

The C extension interface is specific to CPython, and extension modules do not work on other Python implementations. In many cases, it is possible to avoid writing C extensions and preserve portability to other implementations. For example, if your use case is calling C library functions or system calls, you should consider using the `ctypes` module or the `cffi` library rather than writing custom C code. These modules let you write Python code to interface with C code and are more portable between implementations of Python than writing and compiling a C extension module.

2.1.1 A Simple Example

Let's create an extension module called `spam` (the favorite food of Monty Python fans...) and let's say we want to create a Python interface to the C library function `system()`¹. This function takes a null-terminated character string as argument and returns an integer. We want this function to be callable from Python as follows:

```
>>> import spam  
>>> status = spam.system("ls -l")
```

¹ An interface for this function already exists in the standard module `os` — it was chosen as a simple and straightforward example.

Begin by creating a file `spammodule.c`. (Historically, if a module is called `spam`, the C file containing its implementation is called `spammodule.c`; if the module name is very long, like `spammify`, the module name can be just `spammify.c`.)

The first two lines of our file can be:

```
#define PY_SSIZE_T_CLEAN
#include <Python.h>
```

which pulls in the Python API (you can add a comment describing the purpose of the module and a copyright notice if you like).

Not

Since Python may define some pre-processor definitions which affect the standard headers on some systems, you *must* include `Python.h` before any standard headers are included.

`#define PY_SSIZE_T_CLEAN` was used to indicate that `Py_ssize_t` should be used in some APIs instead of `int`. It is not necessary since Python 3.13, but we keep it here for backward compatibility. See `arg-parsing-string-and-buffers` for a description of this macro.

All user-visible symbols defined by `Python.h` have a prefix of `Py` or `PY`, except those defined in standard header files. For convenience, and since they are used extensively by the Python interpreter, "`Python.h`" includes a few standard header files: `<stdio.h>`, `<string.h>`, `<errno.h>`, and `<stdlib.h>`. If the latter header file does not exist on your system, it declares the functions `malloc()`, `free()` and `realloc()` directly.

The next thing we add to our module file is the C function that will be called when the Python expression `spam.system(string)` is evaluated (we'll see shortly how it ends up being called):

```
static PyObject *
spam_system(PyObject *self, PyObject *args)
{
    const char *command;
    int sts;

    if (!PyArg_ParseTuple(args, "s", &command))
        return NULL;
    sts = system(command);
    return PyLong_FromLong(sts);
}
```

There is a straightforward translation from the argument list in Python (for example, the single expression `"ls -l"`) to the arguments passed to the C function. The C function always has two arguments, conventionally named `self` and `args`.

The `self` argument points to the module object for module-level functions; for a method it would point to the object instance.

The `args` argument will be a pointer to a Python tuple object containing the arguments. Each item of the tuple corresponds to an argument in the call's argument list. The arguments are Python objects — in order to do anything with them in our C function we have to convert them to C values. The function `PyArg_ParseTuple()` in the Python API checks the argument types and converts them to C values. It uses a template string to determine the required types of the arguments as well as the types of the C variables into which to store the converted values. More about this later.

`PyArg_ParseTuple()` returns true (nonzero) if all arguments have the right type and its components have been stored in the variables whose addresses are passed. It returns false (zero) if an invalid argument list was passed. In the latter case it also raises an appropriate exception so the calling function can return `NULL` immediately (as we saw in the example).

2.1.2 Intermezzo: Errors and Exceptions

An important convention throughout the Python interpreter is the following: when a function fails, it should set an exception condition and return an error value (usually `-1` or a `NULL` pointer). Exception information is stored in three members of the interpreter's thread state. These are `NULL` if there is no exception. Otherwise they are the C equivalents of the members of the Python tuple returned by `sys.exc_info()`. These are the exception type, exception instance, and a traceback object. It is important to know about them to understand how errors are passed around.

The Python API defines a number of functions to set various types of exceptions.

The most common one is `PyErr_SetString()`. Its arguments are an exception object and a C string. The exception object is usually a predefined object like `PyExc_ZeroDivisionError`. The C string indicates the cause of the error and is converted to a Python string object and stored as the “associated value” of the exception.

Another useful function is `PyErr_SetFromErrno()`, which only takes an exception argument and constructs the associated value by inspection of the global variable `errno`. The most general function is `PyErr_SetObject()`, which takes two object arguments, the exception and its associated value. You don't need to `Py_INCREF()` the objects passed to any of these functions.

You can test non-destructively whether an exception has been set with `PyErr_Occurred()`. This returns the current exception object, or `NULL` if no exception has occurred. You normally don't need to call `PyErr_Occurred()` to see whether an error occurred in a function call, since you should be able to tell from the return value.

When a function *f* that calls another function *g* detects that the latter fails, *f* should itself return an error value (usually `NULL` or `-1`). It should *not* call one of the `PyErr_*` functions — one has already been called by *g*. *f*'s caller is then supposed to also return an error indication to *its* caller, again *without* calling `PyErr_*`, and so on — the most detailed cause of the error was already reported by the function that first detected it. Once the error reaches the Python interpreter's main loop, this aborts the currently executing Python code and tries to find an exception handler specified by the Python programmer.

(There are situations where a module can actually give a more detailed error message by calling another `PyErr_*` function, and in such cases it is fine to do so. As a general rule, however, this is not necessary, and can cause information about the cause of the error to be lost: most operations can fail for a variety of reasons.)

To ignore an exception set by a function call that failed, the exception condition must be cleared explicitly by calling `PyErr_Clear()`. The only time C code should call `PyErr_Clear()` is if it doesn't want to pass the error on to the interpreter but wants to handle it completely by itself (possibly by trying something else, or pretending nothing went wrong).

Every failing `malloc()` call must be turned into an exception — the direct caller of `malloc()` (or `realloc()`) must call `PyErr_NoMemory()` and return a failure indicator itself. All the object-creating functions (for example, `PyLong_FromLong()`) already do this, so this note is only relevant to those who call `malloc()` directly.

Also note that, with the important exception of `PyArg_ParseTuple()` and friends, functions that return an integer status usually return a positive value or zero for success and `-1` for failure, like Unix system calls.

Finally, be careful to clean up garbage (by making `Py_XDECREF()` or `Py_DECREF()` calls for objects you have already created) when you return an error indicator!

The choice of which exception to raise is entirely yours. There are predeclared C objects corresponding to all built-in Python exceptions, such as `PyExc_ZeroDivisionError`, which you can use directly. Of course, you should choose exceptions wisely — don't use `PyExc_TypeError` to mean that a file couldn't be opened (that should probably be `PyExc_OSError`). If something's wrong with the argument list, the `PyArg_ParseTuple()` function usually raises `PyExc_TypeError`. If you have an argument whose value must be in a particular range or must satisfy other conditions, `PyExc_ValueError` is appropriate.

You can also define a new exception that is unique to your module. For this, you usually declare a static object variable at the beginning of your file:

```
static PyObject *SpamError;
```

and initialize it in your module's initialization function (`PyInit_spam()`) with an exception object:

```
PyMODINIT_FUNC
PyInit_spam(void)
{
    PyObject *m;

    m = PyModule_Create(&spammodule);
    if (m == NULL)
        return NULL;

    SpamError = PyErr_NewException("spam.error", NULL, NULL);
    if (PyModule_AddObjectRef(m, "error", SpamError) < 0) {
        Py_CLEAR(SpamError);
        Py_DECREF(m);
        return NULL;
    }

    return m;
}
```

Note that the Python name for the exception object is `spam.error`. The `PyErr_NewException()` function may create a class with the base class being `Exception` (unless another class is passed in instead of `NULL`), described in `bltin-exceptions`.

Note also that the `SpamError` variable retains a reference to the newly created exception class; this is intentional! Since the exception could be removed from the module by external code, an owned reference to the class is needed to ensure that it will not be discarded, causing `SpamError` to become a dangling pointer. Should it become a dangling pointer, C code which raises the exception could cause a core dump or other unintended side effects.

We discuss the use of `PyMODINIT_FUNC` as a function return type later in this sample.

The `spam.error` exception can be raised in your extension module using a call to `PyErr_SetString()` as shown below:

```
static PyObject *
spam_system(PyObject *self, PyObject *args)
{
    const char *command;
    int sts;

    if (!PyArg_ParseTuple(args, "s", &command))
        return NULL;
    sts = system(command);
    if (sts < 0) {
        PyErr_SetString(SpamError, "System command failed");
        return NULL;
    }
    return PyLong_FromLong(sts);
}
```

2.1.3 Back to the Example

Going back to our example function, you should now be able to understand this statement:

```
if (!PyArg_ParseTuple(args, "s", &command))
    return NULL;
```

It returns `NULL` (the error indicator for functions returning object pointers) if an error is detected in the argument list, relying on the exception set by `PyArg_ParseTuple()`. Otherwise the string value of the argument has been

copied to the local variable `command`. This is a pointer assignment and you are not supposed to modify the string to which it points (so in Standard C, the variable `command` should properly be declared as `const char *command`).

The next statement is a call to the Unix function `system()`, passing it the string we just got from `PyArg_ParseTuple()`:

```
sts = system(command);
```

Our `spam.system()` function must return the value of `sts` as a Python object. This is done using the function `PyLong_FromLong()`.

```
return PyLong_FromLong(sts);
```

In this case, it will return an integer object. (Yes, even integers are objects on the heap in Python!)

If you have a C function that returns no useful argument (a function returning `void`), the corresponding Python function must return `None`. You need this idiom to do so (which is implemented by the `Py_RETURN_NONE` macro):

```
Py_INCREF(Py_None);
return Py_None;
```

`Py_None` is the C name for the special Python object `None`. It is a genuine Python object rather than a `NULL` pointer, which means “error” in most contexts, as we have seen.

2.1.4 The Module’s Method Table and Initialization Function

I promised to show how `spam_system()` is called from Python programs. First, we need to list its name and address in a “method table”:

```
static PyMethodDef SpamMethods[] = {
    ...
    {"system",    spam_system, METH_VARARGS,
     "Execute a shell command."},
    ...
    {NULL, NULL, 0, NULL}           /* Sentinel */
};
```

Note the third entry (`METH_VARARGS`). This is a flag telling the interpreter the calling convention to be used for the C function. It should normally always be `METH_VARARGS` or `METH_VARARGS | METH_KEYWORDS`; a value of 0 means that an obsolete variant of `PyArg_ParseTuple()` is used.

When using only `METH_VARARGS`, the function should expect the Python-level parameters to be passed in as a tuple acceptable for parsing via `PyArg_ParseTuple()`; more information on this function is provided below.

The `METH_KEYWORDS` bit may be set in the third field if keyword arguments should be passed to the function. In this case, the C function should accept a third `PyObject *` parameter which will be a dictionary of keywords. Use `PyArg_ParseTupleAndKeywords()` to parse the arguments to such a function.

The method table must be referenced in the module definition structure:

```
static struct PyModuleDef spammodule = {
    PyModuleDef_HEAD_INIT,
    "spam",      /* name of module */
    spam_doc,   /* module documentation, may be NULL */
    -1,          /* size of per-interpreter state of the module,
                  or -1 if the module keeps state in global variables. */
    SpamMethods
};
```

This structure, in turn, must be passed to the interpreter in the module’s initialization function. The initialization function must be named `PyInit_name()`, where `name` is the name of the module, and should be the only non-`static` item defined in the module file:

```
PyMODINIT_FUNC
PyInit_spam(void)
{
    return PyModule_Create(&spammodule);
}
```

Note that `PyMODINIT_FUNC` declares the function as `PyObject *` return type, declares any special linkage declarations required by the platform, and for C++ declares the function as `extern "C"`.

When the Python program imports module `spam` for the first time, `PyInit_spam()` is called. (See below for comments about embedding Python.) It calls `PyModule_Create()`, which returns a module object, and inserts built-in function objects into the newly created module based upon the table (an array of `PyMethodDef` structures) found in the module definition. `PyModule_Create()` returns a pointer to the module object that it creates. It may abort with a fatal error for certain errors, or return `NULL` if the module could not be initialized satisfactorily. The init function must return the module object to its caller, so that it then gets inserted into `sys.modules`.

When embedding Python, the `PyInit_spam()` function is not called automatically unless there's an entry in the `PyImport_Inittab` table. To add the module to the initialization table, use `PyImport_AppendInittab()`, optionally followed by an import of the module:

```
#define PY_SSIZE_T_CLEAN
#include <Python.h>

int
main(int argc, char *argv[])
{
    PyStatus status;
    PyConfig config;
    PyConfig_InitPythonConfig(&config);

    /* Add a built-in module, before Py_Initialize */
    if (PyImport_AppendInittab("spam", PyInit_spam) == -1) {
        fprintf(stderr, "Error: could not extend in-built modules table\n");
        exit(1);
    }

    /* Pass argv[0] to the Python interpreter */
    status = PyConfig_SetBytesString(&config, &config.program_name, argv[0]);
    if (PyStatus_Exception(status)) {
        goto exception;
    }

    /* Initialize the Python interpreter. Required.
       If this step fails, it will be a fatal error. */
    status = Py_InitializeFromConfig(&config);
    if (PyStatus_Exception(status)) {
        goto exception;
    }
    PyConfig_Clear(&config);

    /* Optionally import the module; alternatively,
       import can be deferred until the embedded script
       imports it. */
    PyObject *pmodule = PyImport_ImportModule("spam");
    if (!pmodule) {
        PyErr_Print();
        fprintf(stderr, "Error: could not import module 'spam'\n");
    }
}
```

(sonraki sayfaya devam)

(önceki sayfadan devam)

```
// ... use Python C API here ...

return 0;

exception:
    PyConfig_Clear(&config);
    Py_ExitStatusException(status);
}
```

i Not

Removing entries from `sys.modules` or importing compiled modules into multiple interpreters within a process (or following a `fork()` without an intervening `exec()`) can create problems for some extension modules. Extension module authors should exercise caution when initializing internal data structures.

A more substantial example module is included in the Python source distribution as `Modules/xxmodule.c`. This file may be used as a template or simply read as an example.

i Not

Unlike our `spam` example, `xxmodule` uses *multi-phase initialization* (new in Python 3.5), where a `PyModuleDef` structure is returned from `PyInit_spam`, and creation of the module is left to the import machinery. For details on multi-phase initialization, see [PEP 489](#).

2.1.5 Compilation and Linkage

There are two more things to do before you can use your new extension: compiling and linking it with the Python system. If you use dynamic loading, the details may depend on the style of dynamic loading your system uses; see the chapters about building extension modules (chapter [Building C and C++ Extensions](#)) and additional information that pertains only to building on Windows (chapter [Windows'ta C ve C++ Uzantıları Oluşturma](#)) for more information about this.

If you can't use dynamic loading, or if you want to make your module a permanent part of the Python interpreter, you will have to change the configuration setup and rebuild the interpreter. Luckily, this is very simple on Unix: just place your file (`spammodule.c` for example) in the `Modules/` directory of an unpacked source distribution, add a line to the file `Modules/Setup.local` describing your file:

```
spam spammodule.o
```

and rebuild the interpreter by running `make` in the toplevel directory. You can also run `make` in the `Modules/` subdirectory, but then you must first rebuild `Makefile` there by running '`make Makefile`'. (This is necessary each time you change the `Setup` file.)

If your module requires additional libraries to link with, these can be listed on the line in the configuration file as well, for instance:

```
spam spammodule.o -lX11
```

2.1.6 Calling Python Functions from C

So far we have concentrated on making C functions callable from Python. The reverse is also useful: calling Python functions from C. This is especially the case for libraries that support so-called “callback” functions. If a C interface makes use of callbacks, the equivalent Python often needs to provide a callback mechanism to the Python programmer; the implementation will require calling the Python callback functions from a C callback. Other uses are also imaginable.

Fortunately, the Python interpreter is easily called recursively, and there is a standard interface to call a Python function. (I won't dwell on how to call the Python parser with a particular string as input — if you're interested, have a look at the implementation of the `-c` command line option in `Modules/main.c` from the Python source code.)

Calling a Python function is easy. First, the Python program must somehow pass you the Python function object. You should provide a function (or some other interface) to do this. When this function is called, save a pointer to the Python function object (be careful to `Py_INCREF()` it!) in a global variable — or wherever you see fit. For example, the following function might be part of a module definition:

```
static PyObject *my_callback = NULL;

static PyObject *
my_set_callback(PyObject *dummy, PyObject *args)
{
    PyObject *result = NULL;
    PyObject *temp;

    if (PyArg_ParseTuple(args, "O:set_callback", &temp)) {
        if (!PyCallable_Check(temp)) {
            PyErr_SetString(PyExc_TypeError, "parameter must be callable");
            return NULL;
        }
        Py_XINCREF(temp);           /* Add a reference to new callback */
        Py_XDECREF(my_callback);   /* Dispose of previous callback */
        my_callback = temp;        /* Remember new callback */
        /* Boilerplate to return "None" */
        Py_INCREF(Py_None);
        result = Py_None;
    }
    return result;
}
```

This function must be registered with the interpreter using the `METH_VARARGS` flag; this is described in section [The Module's Method Table and Initialization Function](#). The `PyArg_ParseTuple()` function and its arguments are documented in section [Extracting Parameters in Extension Functions](#).

The macros `Py_XINCREF()` and `Py_XDECREF()` increment/decrement the reference count of an object and are safe in the presence of `NULL` pointers (but note that `temp` will not be `NULL` in this context). More info on them in section [Reference Counts](#).

Later, when it is time to call the function, you call the C function `PyObject_CallObject()`. This function has two arguments, both pointers to arbitrary Python objects: the Python function, and the argument list. The argument list must always be a tuple object, whose length is the number of arguments. To call the Python function with no arguments, pass in `NULL`, or an empty tuple; to call it with one argument, pass a singleton tuple. `Py_BuildValue()` returns a tuple when its format string consists of zero or more format codes between parentheses. For example:

```
int arg;
PyObject *arglist;
PyObject *result;
...
arg = 123;
...
/* Time to call the callback */
arglist = Py_BuildValue("(i)", arg);
result = PyObject_CallObject(my_callback, arglist);
Py_DECREF(arglist);
```

`PyObject_CallObject()` returns a Python object pointer: this is the return value of the Python function. `PyObject_CallObject()` is “reference-count-neutral” with respect to its arguments. In the example a new tuple was created to serve as the argument list, which is `Py_DECREF()`-ed immediately after the

```
PyObject_CallObject() call.
```

The return value of `PyObject_CallObject()` is “new”: either it is a brand new object, or it is an existing object whose reference count has been incremented. So, unless you want to save it in a global variable, you should somehow `Py_DECREF()` the result, even (especially!) if you are not interested in its value.

Before you do this, however, it is important to check that the return value isn’t `NULL`. If it is, the Python function terminated by raising an exception. If the C code that called `PyObject_CallObject()` is called from Python, it should now return an error indication to its Python caller, so the interpreter can print a stack trace, or the calling Python code can handle the exception. If this is not possible or desirable, the exception should be cleared by calling `PyErr_Clear()`. For example:

```
if (result == NULL)
    return NULL; /* Pass error back */
...use result...
Py_DECREF(result);
```

Depending on the desired interface to the Python callback function, you may also have to provide an argument list to `PyObject_CallObject()`. In some cases the argument list is also provided by the Python program, through the same interface that specified the callback function. It can then be saved and used in the same manner as the function object. In other cases, you may have to construct a new tuple to pass as the argument list. The simplest way to do this is to call `Py_BuildValue()`. For example, if you want to pass an integral event code, you might use the following code:

```
PyObject *arglist;
...
arglist = Py_BuildValue("(l)", eventcode);
result = PyObject_CallObject(my_callback, arglist);
Py_DECREF(arglist);
if (result == NULL)
    return NULL; /* Pass error back */
/* Here maybe use the result */
Py_DECREF(result);
```

Note the placement of `Py_DECREF(arglist)` immediately after the call, before the error check! Also note that strictly speaking this code is not complete: `Py_BuildValue()` may run out of memory, and this should be checked.

You may also call a function with keyword arguments by using `PyObject_Call()`, which supports arguments and keyword arguments. As in the above example, we use `Py_BuildValue()` to construct the dictionary.

```
PyObject *dict;
...
dict = Py_BuildValue("{s:i}", "name", val);
result = PyObject_Call(my_callback, NULL, dict);
Py_DECREF(dict);
if (result == NULL)
    return NULL; /* Pass error back */
/* Here maybe use the result */
Py_DECREF(result);
```

2.1.7 Extracting Parameters in Extension Functions

The `PyArg_ParseTuple()` function is declared as follows:

```
int PyArg_ParseTuple(PyObject *arg, const char *format, ...);
```

The `arg` argument must be a tuple object containing an argument list passed from Python to a C function. The `format` argument must be a format string, whose syntax is explained in arg-parsing in the Python/C API Reference Manual. The remaining arguments must be addresses of variables whose type is determined by the format string.

Note that while `PyArg_ParseTuple()` checks that the Python arguments have the required types, it cannot check the validity of the addresses of C variables passed to the call: if you make mistakes there, your code will probably crash or at least overwrite random bits in memory. So be careful!

Note that any Python object references which are provided to the caller are *borrowed* references; do not decrement their reference count!

Some example calls:

```
#define PY_SSIZE_T_CLEAN
#include <Python.h>
```

```
int ok;
int i, j;
long k, l;
const char *s;
Py_ssize_t size;

ok = PyArg_ParseTuple(args, ""); /* No arguments */
/* Python call: f() */
```

```
ok = PyArg_ParseTuple(args, "s", &s); /* A string */
/* Possible Python call: f('whoops!') */
```

```
ok = PyArg_ParseTuple(args, "lls", &k, &l, &s); /* Two longs and a string */
/* Possible Python call: f(1, 2, 'three') */
```

```
ok = PyArg_ParseTuple(args, "(ii)s#", &i, &j, &s, &size);
/* A pair of ints and a string, whose size is also returned */
/* Possible Python call: f((1, 2), 'three') */
```

```
{
    const char *file;
    const char *mode = "r";
    int bufsize = 0;
    ok = PyArg_ParseTuple(args, "s|si", &file, &mode, &bufsize);
    /* A string, and optionally another string and an integer */
    /* Possible Python calls:
        f('spam')
        f('spam', 'w')
        f('spam', 'wb', 100000) */
}
```

```
{
    int left, top, right, bottom, h, v;
    ok = PyArg_ParseTuple(args, "((ii)(ii))(ii)",
        &left, &top, &right, &bottom, &h, &v);
    /* A rectangle and a point */
    /* Possible Python call:
        f(((0, 0), (400, 300)), (10, 10)) */
}
```

```
{
    Py_complex c;
    ok = PyArg_ParseTuple(args, "D:myfunction", &c);
    /* a complex, also providing a function name for errors */
```

(sonraki sayfaya devam)

(önceki sayfadan devam)

```
/* Possible Python call: myfunction(1+2j) */
}
```

2.1.8 Keyword Parameters for Extension Functions

The `PyArg_ParseTupleAndKeywords()` function is declared as follows:

```
int PyArg_ParseTupleAndKeywords(PyObject *arg, PyObject *kwdict,
                               const char *format, char * const *kwlist, ...);
```

The `arg` and `format` parameters are identical to those of the `PyArg_ParseTuple()` function. The `kwdict` parameter is the dictionary of keywords received as the third parameter from the Python runtime. The `kwlist` parameter is a NULL-terminated list of strings which identify the parameters; the names are matched with the type information from `format` from left to right. On success, `PyArg_ParseTupleAndKeywords()` returns true, otherwise it returns false and raises an appropriate exception.

Not

Nested tuples cannot be parsed when using keyword arguments! Keyword parameters passed in which are not present in the `kwlist` will cause `TypeError` to be raised.

Here is an example module which uses keywords, based on an example by Geoff Philbrick (philbrick@hks.com):

```
#define PY_SSIZE_T_CLEAN
#include <Python.h>

static PyObject *
keywdarg_parrot(PyObject *self, PyObject *args, PyObject *keywds)
{
    int voltage;
    const char *state = "a stiff";
    const char *action = "voom";
    const char *type = "Norwegian Blue";

    static char *kwlist[] = {"voltage", "state", "action", "type", NULL};

    if (!PyArg_ParseTupleAndKeywords(args, keywds, "i|sss", kwlist,
                                    &voltage, &state, &action, &type))
        return NULL;

    printf("-- This parrot wouldn't %s if you put %i Volts through it.\n",
           action, voltage);
    printf("-- Lovely plumage, the %s -- It's %s!\n", type, state);

    Py_RETURN_NONE;
}

static PyMethodDef keywdarg_methods[] = {
    /* The cast of the function is necessary since PyCFunction values
     * only take two PyObject* parameters, and keywdarg_parrot() takes
     * three.
     */
    {"parrot", (PyCFunction)(void(*)(void))keywdarg_parrot, METH_VARARGS | METH_
     KEYWORDS,
     "Print a lovely skit to standard output."},
```

(sonraki sayfaya devam)

(önceki sayfadan devam)

```

{NULL, NULL, 0, NULL} /* sentinel */
};

static struct PyModuleDef keywdargmodule = {
    PyModuleDef_HEAD_INIT,
    "keywdarg",
    NULL,
    -1,
    keywdarg_methods
};

PyMODINIT_FUNC
PyInit_keywdarg(void)
{
    return PyModule_Create(&keywdargmodule);
}

```

2.1.9 Building Arbitrary Values

This function is the counterpart to `PyArg_ParseTuple()`. It is declared as follows:

```
PyObject *Py_BuildValue(const char *format, ...);
```

It recognizes a set of format units similar to the ones recognized by `PyArg_ParseTuple()`, but the arguments (which are input to the function, not output) must not be pointers, just values. It returns a new Python object, suitable for returning from a C function called from Python.

One difference with `PyArg_ParseTuple()`: while the latter requires its first argument to be a tuple (since Python argument lists are always represented as tuples internally), `Py_BuildValue()` does not always build a tuple. It builds a tuple only if its format string contains two or more format units. If the format string is empty, it returns `None`; if it contains exactly one format unit, it returns whatever object is described by that format unit. To force it to return a tuple of size 0 or one, parenthesize the format string.

Examples (to the left the call, to the right the resulting Python value):

Py_BuildValue("")	None
Py_BuildValue("i", 123)	123
Py_BuildValue("iii", 123, 456, 789)	(123, 456, 789)
Py_BuildValue("s", "hello")	'hello'
Py_BuildValue("y", "hello")	b'hello'
Py_BuildValue("ss", "hello", "world")	('hello', 'world')
Py_BuildValue("s#", "hello", 4)	'hell'
Py_BuildValue("y#", "hello", 4)	b'hell'
Py_BuildValue("(())")	()
Py_BuildValue("(i)", 123)	(123,)
Py_BuildValue("(ii)", 123, 456)	(123, 456)
Py_BuildValue("(i,i)", 123, 456)	(123, 456)
Py_BuildValue("[i,i]", 123, 456)	[123, 456]
Py_BuildValue("{s:i,s:i}", "abc", 123, "def", 456)	{'abc': 123, 'def': 456}
Py_BuildValue("((ii)(ii)) (ii)", 1, 2, 3, 4, 5, 6)	((1, 2), (3, 4)), (5, 6))

2.1.10 Reference Counts

In languages like C or C++, the programmer is responsible for dynamic allocation and deallocation of memory on the heap. In C, this is done using the functions `malloc()` and `free()`. In C++, the operators `new` and `delete` are used with essentially the same meaning and we'll restrict the following discussion to the C case.

Every block of memory allocated with `malloc()` should eventually be returned to the pool of available memory by exactly one call to `free()`. It is important to call `free()` at the right time. If a block's address is forgotten but `free()` is not called for it, the memory it occupies cannot be reused until the program terminates. This is called a *memory leak*. On the other hand, if a program calls `free()` for a block and then continues to use the block, it creates a conflict with reuse of the block through another `malloc()` call. This is called *using freed memory*. It has the same bad consequences as referencing uninitialized data — core dumps, wrong results, mysterious crashes.

Common causes of memory leaks are unusual paths through the code. For instance, a function may allocate a block of memory, do some calculation, and then free the block again. Now a change in the requirements for the function may add a test to the calculation that detects an error condition and can return prematurely from the function. It's easy to forget to free the allocated memory block when taking this premature exit, especially when it is added later to the code. Such leaks, once introduced, often go undetected for a long time: the error exit is taken only in a small fraction of all calls, and most modern machines have plenty of virtual memory, so the leak only becomes apparent in a long-running process that uses the leaking function frequently. Therefore, it's important to prevent leaks from happening by having a coding convention or strategy that minimizes this kind of errors.

Since Python makes heavy use of `malloc()` and `free()`, it needs a strategy to avoid memory leaks as well as the use of freed memory. The chosen method is called *reference counting*. The principle is simple: every object contains a counter, which is incremented when a reference to the object is stored somewhere, and which is decremented when a reference to it is deleted. When the counter reaches zero, the last reference to the object has been deleted and the object is freed.

An alternative strategy is called *automatic garbage collection*. (Sometimes, reference counting is also referred to as a garbage collection strategy, hence my use of “automatic” to distinguish the two.) The big advantage of automatic garbage collection is that the user doesn't need to call `free()` explicitly. (Another claimed advantage is an improvement in speed or memory usage — this is no hard fact however.) The disadvantage is that for C, there is no truly portable automatic garbage collector, while reference counting can be implemented portably (as long as the functions `malloc()` and `free()` are available — which the C Standard guarantees). Maybe some day a sufficiently portable automatic garbage collector will be available for C. Until then, we'll have to live with reference counts.

While Python uses the traditional reference counting implementation, it also offers a cycle detector that works to detect reference cycles. This allows applications to not worry about creating direct or indirect circular references; these are the weakness of garbage collection implemented using only reference counting. Reference cycles consist of objects which contain (possibly indirect) references to themselves, so that each object in the cycle has a reference count which is non-zero. Typical reference counting implementations are not able to reclaim the memory belonging to any objects in a reference cycle, or referenced from the objects in the cycle, even though there are no further references to the cycle itself.

The cycle detector is able to detect garbage cycles and can reclaim them. The `gc` module exposes a way to run the detector (the `collect()` function), as well as configuration interfaces and the ability to disable the detector at runtime.

Reference Counting in Python

There are two macros, `Py_INCREF(x)` and `Py_DECREF(x)`, which handle the incrementing and decrementing of the reference count. `Py_DECREF()` also frees the object when the count reaches zero. For flexibility, it doesn't call `free()` directly — rather, it makes a call through a function pointer in the object's *type object*. For this purpose (and others), every object also contains a pointer to its type object.

The big question now remains: when to use `Py_INCREF(x)` and `Py_DECREF(x)`? Let's first introduce some terms. Nobody “owns” an object; however, you can *own a reference* to an object. An object's reference count is now defined as the number of owned references to it. The owner of a reference is responsible for calling `Py_DECREF()` when the reference is no longer needed. Ownership of a reference can be transferred. There are three ways to dispose of an owned reference: pass it on, store it, or call `Py_DECREF()`. Forgetting to dispose of an owned reference creates a memory leak.

It is also possible to *borrow*² a reference to an object. The borrower of a reference should not call `Py_DECREF()`. The borrower must not hold on to the object longer than the owner from which it was borrowed. Using a borrowed reference after the owner has disposed of it risks using freed memory and should be avoided completely³.

The advantage of borrowing over owning a reference is that you don't need to take care of disposing of the reference on all possible paths through the code — in other words, with a borrowed reference you don't run the risk of leaking when a premature exit is taken. The disadvantage of borrowing over owning is that there are some subtle situations where in seemingly correct code a borrowed reference can be used after the owner from which it was borrowed has in fact disposed of it.

A borrowed reference can be changed into an owned reference by calling `Py_INCREF()`. This does not affect the status of the owner from which the reference was borrowed — it creates a new owned reference, and gives full owner responsibilities (the new owner must dispose of the reference properly, as well as the previous owner).

Ownership Rules

Whenever an object reference is passed into or out of a function, it is part of the function's interface specification whether ownership is transferred with the reference or not.

Most functions that return a reference to an object pass on ownership with the reference. In particular, all functions whose function it is to create a new object, such as `PyLong_FromLong()` and `Py_BuildValue()`, pass ownership to the receiver. Even if the object is not actually new, you still receive ownership of a new reference to that object. For instance, `PyLong_FromLong()` maintains a cache of popular values and can return a reference to a cached item.

Many functions that extract objects from other objects also transfer ownership with the reference, for instance `PyObject_GetAttrString()`. The picture is less clear, here, however, since a few common routines are exceptions: `PyTuple_GetItem()`, `PyList_GetItem()`, `PyDict_GetItem()`, and `PyDict_GetItemString()` all return references that you borrow from the tuple, list or dictionary.

The function `PyImport_AddModule()` also returns a borrowed reference, even though it may actually create the object it returns: this is possible because an owned reference to the object is stored in `sys.modules`.

When you pass an object reference into another function, in general, the function borrows the reference from you — if it needs to store it, it will use `Py_INCREF()` to become an independent owner. There are exactly two important exceptions to this rule: `PyTuple_SetItem()` and `PyList_SetItem()`. These functions take over ownership of the item passed to them — even if they fail! (Note that `PyDict_SetItem()` and friends don't take over ownership — they are “normal.”)

When a C function is called from Python, it borrows references to its arguments from the caller. The caller owns a reference to the object, so the borrowed reference's lifetime is guaranteed until the function returns. Only when such a borrowed reference must be stored or passed on, it must be turned into an owned reference by calling `Py_INCREF()`.

The object reference returned from a C function that is called from Python must be an owned reference — ownership is transferred from the function to its caller.

Thin Ice

There are a few situations where seemingly harmless use of a borrowed reference can lead to problems. These all have to do with implicit invocations of the interpreter, which can cause the owner of a reference to dispose of it.

The first and most important case to know about is using `Py_DECREF()` on an unrelated object while borrowing a reference to a list item. For instance:

```
void
bug(PyObject *list)
{
    PyObject *item = PyList_GetItem(list, 0);

    PyList_SetItem(list, 1, PyLong_FromLong(0L));
```

(sonraki sayfaya devam)

² The metaphor of “borrowing” a reference is not completely correct: the owner still has a copy of the reference.

³ Checking that the reference count is at least 1 **does not work** — the reference count itself could be in freed memory and may thus be reused for another object!

(önceki sayfadan devam)

```
PyObject_Print(item, stdout, 0); /* BUG! */
}
```

This function first borrows a reference to `list[0]`, then replaces `list[1]` with the value 0, and finally prints the borrowed reference. Looks harmless, right? But it's not!

Let's follow the control flow into `PyList_SetItem()`. The list owns references to all its items, so when item 1 is replaced, it has to dispose of the original item 1. Now let's suppose the original item 1 was an instance of a user-defined class, and let's further suppose that the class defined a `__del__()` method. If this class instance has a reference count of 1, disposing of it will call its `__del__()` method.

Since it is written in Python, the `__del__()` method can execute arbitrary Python code. Could it perhaps do something to invalidate the reference to `item` in `bug()`? You bet! Assuming that the list passed into `bug()` is accessible to the `__del__()` method, it could execute a statement to the effect of `del list[0]`, and assuming this was the last reference to that object, it would free the memory associated with it, thereby invalidating `item`.

The solution, once you know the source of the problem, is easy: temporarily increment the reference count. The correct version of the function reads:

```
void
no_bug(PyObject *list)
{
    PyObject *item = PyList_GetItem(list, 0);

    Py_INCREF(item);
    PyList_SetItem(list, 1, PyLong_FromLong(0L));
    PyObject_Print(item, stdout, 0);
    Py_DECREF(item);
}
```

This is a true story. An older version of Python contained variants of this bug and someone spent a considerable amount of time in a C debugger to figure out why his `__del__()` methods would fail...

The second case of problems with a borrowed reference is a variant involving threads. Normally, multiple threads in the Python interpreter can't get in each other's way, because there is a global lock protecting Python's entire object space. However, it is possible to temporarily release this lock using the macro `Py_BEGIN_ALLOW_THREADS`, and to re-acquire it using `Py_END_ALLOW_THREADS`. This is common around blocking I/O calls, to let other threads use the processor while waiting for the I/O to complete. Obviously, the following function has the same problem as the previous one:

```
void
bug(PyObject *list)
{
    PyObject *item = PyList_GetItem(list, 0);
    Py_BEGIN_ALLOW_THREADS
    ...some blocking I/O call...
    Py_END_ALLOW_THREADS
    PyObject_Print(item, stdout, 0); /* BUG! */
}
```

NULL Pointers

In general, functions that take object references as arguments do not expect you to pass them `NULL` pointers, and will dump core (or cause later core dumps) if you do so. Functions that return object references generally return `NULL` only to indicate that an exception occurred. The reason for not testing for `NULL` arguments is that functions often pass the objects they receive on to other function — if each function were to test for `NULL`, there would be a lot of redundant tests and the code would run more slowly.

It is better to test for `NULL` only at the “source:” when a pointer that may be `NULL` is received, for example, from `malloc()` or from a function that may raise an exception.

The macros `Py_INCREF()` and `Py_DECREF()` do not check for `NULL` pointers — however, their variants `Py_XINCREF()` and `Py_XDECREF()` do.

The macros for checking for a particular object type (`Pytype_Check()`) don't check for `NULL` pointers — again, there is much code that calls several of these in a row to test an object against various different expected types, and this would generate redundant tests. There are no variants with `NULL` checking.

The C function calling mechanism guarantees that the argument list passed to C functions (`args` in the examples) is never `NULL` — in fact it guarantees that it is always a tuple⁴.

It is a severe error to ever let a `NULL` pointer “escape” to the Python user.

2.1.11 Writing Extensions in C++

It is possible to write extension modules in C++. Some restrictions apply. If the main program (the Python interpreter) is compiled and linked by the C compiler, global or static objects with constructors cannot be used. This is not a problem if the main program is linked by the C++ compiler. Functions that will be called by the Python interpreter (in particular, module initialization functions) have to be declared using `extern "C"`. It is unnecessary to enclose the Python header files in `extern "C" { . . . }` — they use this form already if the symbol `__cplusplus` is defined (all recent C++ compilers define this symbol).

2.1.12 Providing a C API for an Extension Module

Many extension modules just provide new functions and types to be used from Python, but sometimes the code in an extension module can be useful for other extension modules. For example, an extension module could implement a type “collection” which works like lists without order. Just like the standard Python list type has a C API which permits extension modules to create and manipulate lists, this new collection type should have a set of C functions for direct manipulation from other extension modules.

At first sight this seems easy: just write the functions (without declaring them `static`, of course), provide an appropriate header file, and document the C API. And in fact this would work if all extension modules were always linked statically with the Python interpreter. When modules are used as shared libraries, however, the symbols defined in one module may not be visible to another module. The details of visibility depend on the operating system; some systems use one global namespace for the Python interpreter and all extension modules (Windows, for example), whereas others require an explicit list of imported symbols at module link time (AIX is one example), or offer a choice of different strategies (most Unices). And even if symbols are globally visible, the module whose functions one wishes to call might not have been loaded yet!

Portability therefore requires not to make any assumptions about symbol visibility. This means that all symbols in extension modules should be declared `static`, except for the module's initialization function, in order to avoid name clashes with other extension modules (as discussed in section [The Module's Method Table and Initialization Function](#)). And it means that symbols that *should* be accessible from other extension modules must be exported in a different way.

Python provides a special mechanism to pass C-level information (pointers) from one extension module to another one: Capsules. A Capsule is a Python data type which stores a pointer (`void*`). Capsules can only be created and accessed via their C API, but they can be passed around like any other Python object. In particular, they can be assigned to a name in an extension module's namespace. Other extension modules can then import this module, retrieve the value of this name, and then retrieve the pointer from the Capsule.

There are many ways in which Capsules can be used to export the C API of an extension module. Each function could get its own Capsule, or all C API pointers could be stored in an array whose address is published in a Capsule. And the various tasks of storing and retrieving the pointers can be distributed in different ways between the module providing the code and the client modules.

Whichever method you choose, it's important to name your Capsules properly. The function `PyCapsule_New()` takes a name parameter (`const char*`); you're permitted to pass in a `NULL` name, but we strongly encourage you to specify a name. Properly named Capsules provide a degree of runtime type-safety; there is no feasible way to tell one unnamed Capsule from another.

In particular, Capsules used to expose C APIs should be given a name following this convention:

⁴ These guarantees don't hold when you use the “old” style calling convention — this is still found in much existing code.

```
modulename.attributename
```

The convenience function `PyCapsule_Import()` makes it easy to load a C API provided via a Capsule, but only if the Capsule's name matches this convention. This behavior gives C API users a high degree of certainty that the Capsule they load contains the correct C API.

The following example demonstrates an approach that puts most of the burden on the writer of the exporting module, which is appropriate for commonly used library modules. It stores all C API pointers (just one in the example!) in an array of `void` pointers which becomes the value of a Capsule. The header file corresponding to the module provides a macro that takes care of importing the module and retrieving its C API pointers; client modules only have to call this macro before accessing the C API.

The exporting module is a modification of the `spam` module from section [A Simple Example](#). The function `spam.system()` does not call the C library function `system()` directly, but a function `PySpam_System()`, which would of course do something more complicated in reality (such as adding "spam" to every command). This function `PySpam_System()` is also exported to other extension modules.

The function `PySpam_System()` is a plain C function, declared `static` like everything else:

```
static int
PySpam_System(const char *command)
{
    return system(command);
}
```

The function `spam_system()` is modified in a trivial way:

```
static PyObject *
spam_system(PyObject *self, PyObject *args)
{
    const char *command;
    int sts;

    if (!PyArg_ParseTuple(args, "s", &command))
        return NULL;
    sts = PySpam_System(command);
    return PyLong_FromLong(sts);
}
```

In the beginning of the module, right after the line

```
#include <Python.h>
```

two more lines must be added:

```
#define SPAM_MODULE
#include "spammodule.h"
```

The `#define` is used to tell the header file that it is being included in the exporting module, not a client module. Finally, the module's initialization function must take care of initializing the C API pointer array:

```
PyMODINIT_FUNC
PyInit_spam(void)
{
    PyObject *m;
    static void *PySpam_API[PySpam_API_pointers];
    PyObject *c_api_object;

    m = PyModule_Create(&spammodule);
```

(sonraki sayfaya devam)

(önceki sayfadan devam)

```

if (m == NULL)
    return NULL;

/* Initialize the C API pointer array */
PySpam_API[PySpam_System_NUM] = (void *)PySpam_System;

/* Create a Capsule containing the API pointer array's address */
c_api_object = PyCapsule_New((void *)PySpam_API, "spam._C_API", NULL);

if (PyModule_Add(m, "_C_API", c_api_object) < 0) {
    Py_DECREF(m);
    return NULL;
}

return m;
}

```

Note that `PySpam_API` is declared `static`; otherwise the pointer array would disappear when `PyInit_spam()` terminates!

The bulk of the work is in the header file `spammodule.h`, which looks like this:

```

#ifndef Py_SPAMMODULE_H
#define Py_SPAMMODULE_H
#ifndef __cplusplus
extern "C" {
#endif

/* Header file for spammodule */

/* C API functions */
#define PySpam_System_NUM 0
#define PySpam_System_RETURN int
#define PySpam_System_PROTO (const char *command)

/* Total number of C API pointers */
#define PySpam_API_pointers 1

#ifndef SPAM_MODULE
/* This section is used when compiling spammodule.c */

static PySpam_System_RETURN PySpam_System PySpam_System_PROTO;

#else
/* This section is used in modules that use spammodule's API */

static void **PySpam_API;

#define PySpam_System \
    (*(PySpam_System_RETURN (*)PySpam_System_PROTO) PySpam_API[PySpam_System_NUM])

/* Return -1 on error, 0 on success.
 * PyCapsule_Import will set an exception if there's an error.
 */
static int
import_spam(void)

```

(sonraki sayfaya devam)

(önceki sayfadan devam)

```
{
    PySpam_API = (void **)PyCapsule_Import("spam._C_API", 0);
    return (PySpam_API != NULL) ? 0 : -1;
}

#endif

#ifdef __cplusplus
}
#endif

#endif /* !defined(Py_SPAMMODULE_H) */
```

All that a client module must do in order to have access to the function `PySpam_System()` is to call the function (or rather macro) `import_spam()` in its initialization function:

```
PyMODINIT_FUNC
PyInit_client(void)
{
    PyObject *m;

    m = PyModule_Create(&clientmodule);
    if (m == NULL)
        return NULL;
    if (import_spam() < 0)
        return NULL;
    /* additional initialization can happen here */
    return m;
}
```

The main disadvantage of this approach is that the file `spammodule.h` is rather complicated. However, the basic structure is the same for each function that is exported, so it has to be learned only once.

Finally it should be mentioned that Capsules offer additional functionality, which is especially useful for memory allocation and deallocation of the pointer stored in a Capsule. The details are described in the Python/C API Reference Manual in the section capsules and in the implementation of Capsules (files `Include/pycapsule.h` and `Objects/pycapsule.c` in the Python source code distribution).

2.2 Defining Extension Types: Tutorial

Python allows the writer of a C extension module to define new types that can be manipulated from Python code, much like the built-in `str` and `list` types. The code for all extension types follows a pattern, but there are some details that you need to understand before you can get started. This document is a gentle introduction to the topic.

2.2.1 The Basics

The *C*Python runtime sees all Python objects as variables of type `PyObject*`, which serves as a “base type” for all Python objects. The `PyObject` structure itself only contains the object’s *reference count* and a pointer to the object’s “type object”. This is where the action is; the type object determines which (C) functions get called by the interpreter when, for instance, an attribute gets looked up on an object, a method called, or it is multiplied by another object. These C functions are called “type methods”.

So, if you want to define a new extension type, you need to create a new type object.

This sort of thing can only be explained by example, so here’s a minimal, but complete, module that defines a new type named `Custom` inside a C extension module `custom`:

Not

What we're showing here is the traditional way of defining *static* extension types. It should be adequate for most uses. The C API also allows defining heap-allocated extension types using the `PyType_FromSpec()` function, which isn't covered in this tutorial.

```
#define PY_SSIZE_T_CLEAN
#include <Python.h>

typedef struct {
    PyObject_HEAD
    /* Type-specific fields go here. */
} CustomObject;

static PyTypeObject CustomType = {
    .ob_base = PyVarObject_HEAD_INIT(NULL, 0)
    .tp_name = "custom.Custom",
    .tp_doc = PyDoc_STR("Custom objects"),
    .tp_basicsize = sizeof(CustomObject),
    .tp_itemsize = 0,
    .tp_flags = Py_TPFLAGS_DEFAULT,
    .tp_new = PyType_GenericNew,
};

static PyModuleDef custommodule = {
    .m_base = PyModuleDef_HEAD_INIT,
    .m_name = "custom",
    .m_doc = "Example module that creates an extension type.",
    .m_size = -1,
};

PyMODINIT_FUNC
PyInit_custom(void)
{
    PyObject *m;
    if (PyType_Ready(&CustomType) < 0)
        return NULL;

    m = PyModule_Create(&custommodule);
    if (m == NULL)
        return NULL;

    if (PyModule_AddObjectRef(m, "Custom", (PyObject *) &CustomType) < 0) {
        Py_DECREF(m);
        return NULL;
    }

    return m;
}
```

Now that's quite a bit to take in at once, but hopefully bits will seem familiar from the previous chapter. This file defines three things:

1. What a `Custom object` contains: this is the `CustomObject` struct, which is allocated once for each `Custom` instance.
2. How the `Custom type` behaves: this is the `CustomType` struct, which defines a set of flags and function pointers that the interpreter inspects when specific operations are requested.

3. How to initialize the `custom` module: this is the `PyInit_custom` function and the associated `CustomModule` struct.

The first bit is:

```
typedef struct {
    PyObject_HEAD
} CustomObject;
```

This is what a Custom object will contain. `PyObject_HEAD` is mandatory at the start of each object struct and defines a field called `ob_base` of type `PyObject`, containing a pointer to a type object and a reference count (these can be accessed using the macros `Py_TYPE` and `Py_REF_CNT` respectively). The reason for the macro is to abstract away the layout and to enable additional fields in debug builds.

i Not

There is no semicolon above after the `PyObject_HEAD` macro. Be wary of adding one by accident: some compilers will complain.

Of course, objects generally store additional data besides the standard `PyObject_HEAD` boilerplate; for example, here is the definition for standard Python floats:

```
typedef struct {
    PyObject_HEAD
    double ob_fval;
} PyFloatObject;
```

The second bit is the definition of the type object.

```
static PyTypeObject CustomType = {
    .ob_base = PyVarObject_HEAD_INIT(NULL, 0)
    .tp_name = "custom.Custom",
    .tp_doc = PyDoc_STR("Custom objects"),
    .tp_basicsize = sizeof(CustomObject),
    .tp_itemsize = 0,
    .tp_flags = Py_TPFLAGS_DEFAULT,
    .tp_new = PyType_GenericNew,
};
```

i Not

We recommend using C99-style designated initializers as above, to avoid listing all the `PyTypeObject` fields that you don't care about and also to avoid caring about the fields' declaration order.

The actual definition of `PyTypeObject` in `object.h` has many more fields than the definition above. The remaining fields will be filled with zeros by the C compiler, and it's common practice to not specify them explicitly unless you need them.

We're going to pick it apart, one field at a time:

```
.ob_base = PyVarObject_HEAD_INIT(NULL, 0)
```

This line is mandatory boilerplate to initialize the `ob_base` field mentioned above.

```
.tp_name = "custom.Custom",
```

The name of our type. This will appear in the default textual representation of our objects and in some error messages, for example:

```
>>> "" + custom.Custom()
Traceback (most recent call last):
  File "<stdin>", line 1, in <module>
TypeError: can only concatenate str (not "custom.Custom") to str
```

Note that the name is a dotted name that includes both the module name and the name of the type within the module. The module in this case is `custom` and the type is `Custom`, so we set the type name to `custom.Custom`. Using the real dotted import path is important to make your type compatible with the `pydoc` and `pickle` modules.

```
.tp_basicsize = sizeof(CustomObject),
.tp_itemsize = 0,
```

This is so that Python knows how much memory to allocate when creating new `Custom` instances. `tp_itemsize` is only used for variable-sized objects and should otherwise be zero.

i Not

If you want your type to be subclassable from Python, and your type has the same `tp_basicsize` as its base type, you may have problems with multiple inheritance. A Python subclass of your type will have to list your type first in its `__bases__`, or else it will not be able to call your type's `__new__()` method without getting an error. You can avoid this problem by ensuring that your type has a larger value for `tp_basicsize` than its base type does. Most of the time, this will be true anyway, because either your base type will be `object`, or else you will be adding data members to your base type, and therefore increasing its size.

We set the class flags to `Py_TPFLAGS_DEFAULT`.

```
.tp_flags = Py_TPFLAGS_DEFAULT,
```

All types should include this constant in their flags. It enables all of the members defined until at least Python 3.3. If you need further members, you will need to OR the corresponding flags.

We provide a doc string for the type in `tp_doc`.

```
.tp_doc = PyDoc_STR("Custom objects"),
```

To enable object creation, we have to provide a `tp_new` handler. This is the equivalent of the Python method `__new__()`, but has to be specified explicitly. In this case, we can just use the default implementation provided by the API function `PyType_GenericNew()`.

```
.tp_new = PyType_GenericNew,
```

Everything else in the file should be familiar, except for some code in `PyInit_custom()`:

```
if (PyType_Ready(&CustomType) < 0)
    return;
```

This initializes the `Custom` type, filling in a number of members to the appropriate default values, including `ob_type` that we initially set to `NULL`.

```
if (PyModule_AddObjectRef(m, "Custom", (PyObject *) &CustomType) < 0) {
    Py_DECREF(m);
    return NULL;
}
```

This adds the type to the module dictionary. This allows us to create `Custom` instances by calling the `Custom` class:

```
>>> import custom
>>> mycustom = custom.Custom()
```

That's it! All that remains is to build it; put the above code in a file called `custom.c`,

```
[build-system]
requires = ["setuptools"]
build-backend = "setuptools.build_meta"

[project]
name = "custom"
version = "1"
```

in a file called `pyproject.toml`, and

```
from setuptools import Extension, setup
setup(ext_modules=[Extension("custom", ["custom.c"])])
```

in a file called `setup.py`; then typing

```
$ python -m pip install .
```

in a shell should produce a file `custom.so` in a subdirectory and install it; now fire up Python — you should be able to import `custom` and play around with `Custom` objects.

That wasn't so hard, was it?

Of course, the current `Custom` type is pretty uninteresting. It has no data and doesn't do anything. It can't even be subclassed.

2.2.2 Adding data and methods to the Basic example

Let's extend the basic example to add some data and methods. Let's also make the type usable as a base class. We'll create a new module, `custom2` that adds these capabilities:

```
#define PY_SSIZE_T_CLEAN
#include <Python.h>
#include <stddef.h> /* for offsetof() */

typedef struct {
    PyObject_HEAD
    PyObject *first; /* first name */
    PyObject *last; /* last name */
    int number;
} CustomObject;

static void
Custom_dealloc(CustomObject *self)
{
    Py_XDECREF(self->first);
    Py_XDECREF(self->last);
    Py_TYPE(self)->tp_free((PyObject *) self);
}

static PyObject *
Custom_new(PyTypeObject *type, PyObject *args, PyObject *kwds)
{
    CustomObject *self;
    self = (CustomObject *) type->tp_alloc(type, 0);
    if (self != NULL) {
        self->first = PyUnicode_FromString("");
        if (self->first == NULL) {
```

(sonraki sayfaya devam)

(önceki sayfadan devam)

```

        Py_DECREF(self);
        return NULL;
    }
    self->last = PyUnicode_FromString("");
    if (self->last == NULL) {
        Py_DECREF(self);
        return NULL;
    }
    self->number = 0;
}
return (PyObject *) self;
}

static int
Custom_init(CustomObject *self, PyObject *args, PyObject *kwds)
{
    static char *kwlist[] = {"first", "last", "number", NULL};
    PyObject *first = NULL, *last = NULL;

    if (!PyArg_ParseTupleAndKeywords(args, kwds, "|OOi", kwlist,
                                    &first, &last,
                                    &self->number))
        return -1;

    if (first) {
        Py_XSETREF(self->first, Py_NewRef(first));
    }
    if (last) {
        Py_XSETREF(self->last, Py_NewRef(last));
    }
    return 0;
};

static PyMemberDef Custom_members[] = {
    {"first", Py_T_OBJECT_EX, offsetof(CustomObject, first), 0,
     "first name"},
    {"last", Py_T_OBJECT_EX, offsetof(CustomObject, last), 0,
     "last name"},
    {"number", Py_T_INT, offsetof(CustomObject, number), 0,
     "custom number"},
    {NULL} /* Sentinel */
};

static PyObject *
Custom_name(CustomObject *self, PyObject *Py_UNUSED(ignored))
{
    if (self->first == NULL) {
        PyErr_SetString(PyExc_AttributeError, "first");
        return NULL;
    }
    if (self->last == NULL) {
        PyErr_SetString(PyExc_AttributeError, "last");
        return NULL;
    }
    return PyUnicode_FromFormat("%S %S", self->first, self->last);
}

```

(sonraki sayfaya devam)

(önceki sayfadan devam)

```

static PyMethodDef Custom_methods[] = {
    {"name", (PyCFunction) Custom_name, METH_NOARGS,
     "Return the name, combining the first and last name"
    },
    {NULL} /* Sentinel */
};

static PyTypeObject CustomType = {
    .ob_base = PyVarObject_HEAD_INIT(NULL, 0)
    .tp_name = "custom2.Custom",
    .tp_doc = PyDoc_STR("Custom objects"),
    .tp_basicsize = sizeof(CustomObject),
    .tp_itemsize = 0,
    .tp_flags = Py_TPFLAGS_DEFAULT | Py_TPFLAGS_BASETYPE,
    .tp_new = Custom_new,
    .tp_init = (initproc) Custom_init,
    .tp_dealloc = (destructor) Custom_dealloc,
    .tp_members = Custom_members,
    .tp_methods = Custom_methods,
};

static PyModuleDef custommodule = {
    .m_base = PyModuleDef_HEAD_INIT,
    .m_name = "custom2",
    .m_doc = "Example module that creates an extension type.",
    .m_size = -1,
};

PyMODINIT_FUNC
PyInit_custom2(void)
{
    PyObject *m;
    if (PyType_Ready(&CustomType) < 0)
        return NULL;

    m = PyModule_Create(&custommodule);
    if (m == NULL)
        return NULL;

    if (PyModule_AddObjectRef(m, "Custom", (PyObject *) &CustomType) < 0) {
        Py_DECREF(m);
        return NULL;
    }

    return m;
}

```

This version of the module has a number of changes.

The `Custom` type now has three data attributes in its C struct, `first`, `last`, and `number`. The `first` and `last` variables are Python strings containing first and last names. The `number` attribute is a C integer.

The object structure is updated accordingly:

```

typedef struct {
    PyObject_HEAD

```

(sonraki sayfaya devam)

(önceki sayfadan devam)

```
PyObject *first; /* first name */
PyObject *last; /* last name */
int number;
} CustomObject;
```

Because we now have data to manage, we have to be more careful about object allocation and deallocation. At a minimum, we need a deallocation method:

```
static void
Custom_dealloc(CustomObject *self)
{
    Py_XDECREF(self->first);
    Py_XDECREF(self->last);
    Py_TYPE(self)->tp_free((PyObject *) self);
}
```

which is assigned to the `tp_dealloc` member:

```
.tp_dealloc = (destructor) Custom_dealloc,
```

This method first clears the reference counts of the two Python attributes. `Py_XDECREF()` correctly handles the case where its argument is `NULL` (which might happen here if `tp_new` failed midway). It then calls the `tp_free` member of the object's type (computed by `Py_TYPE(self)`) to free the object's memory. Note that the object's type might not be `CustomType`, because the object may be an instance of a subclass.

Not

The explicit cast to `destructor` above is needed because we defined `Custom_dealloc` to take a `CustomObject *` argument, but the `tp_dealloc` function pointer expects to receive a `PyObject *` argument. Otherwise, the compiler will emit a warning. This is object-oriented polymorphism, in C!

We want to make sure that the first and last names are initialized to empty strings, so we provide a `tp_new` implementation:

```
static PyObject *
Custom_new(PyTypeObject *type, PyObject *args, PyObject *kwds)
{
    CustomObject *self;
    self = (CustomObject *) type->tp_alloc(type, 0);
    if (self != NULL) {
        self->first = PyUnicode_FromString("");
        if (self->first == NULL) {
            Py_DECREF(self);
            return NULL;
        }
        self->last = PyUnicode_FromString("");
        if (self->last == NULL) {
            Py_DECREF(self);
            return NULL;
        }
        self->number = 0;
    }
    return (PyObject *) self;
}
```

and install it in the `tp_new` member:

```
.tp_new = Custom_new,
```

The `tp_new` handler is responsible for creating (as opposed to initializing) objects of the type. It is exposed in Python as the `__new__()` method. It is not required to define a `tp_new` member, and indeed many extension types will simply reuse `PyType_GenericNew()` as done in the first version of the `Custom` type above. In this case, we use the `tp_new` handler to initialize the `first` and `last` attributes to non-NULL default values.

`tp_new` is passed the type being instantiated (not necessarily `CustomType`, if a subclass is instantiated) and any arguments passed when the type was called, and is expected to return the instance created. `tp_new` handlers always accept positional and keyword arguments, but they often ignore the arguments, leaving the argument handling to initializer (a.k.a. `tp_init` in C or `__init__` in Python) methods.

i Not

`tp_new` shouldn't call `tp_init` explicitly, as the interpreter will do it itself.

The `tp_new` implementation calls the `tp_alloc` slot to allocate memory:

```
self = (CustomObject *) type->tp_alloc(type, 0);
```

Since memory allocation may fail, we must check the `tp_alloc` result against `NULL` before proceeding.

i Not

We didn't fill the `tp_alloc` slot ourselves. Rather `PyType_Ready()` fills it for us by inheriting it from our base class, which is `object` by default. Most types use the default allocation strategy.

i Not

If you are creating a co-operative `tp_new` (one that calls a base type's `tp_new` or `__new__()`), you must *not* try to determine what method to call using method resolution order at runtime. Always statically determine what type you are going to call, and call its `tp_new` directly, or via `type->tp_base->tp_new`. If you do not do this, Python subclasses of your type that also inherit from other Python-defined classes may not work correctly. (Specifically, you may not be able to create instances of such subclasses without getting a `TypeError`.)

We also define an initialization function which accepts arguments to provide initial values for our instance:

```
static int
Custom_init(CustomObject *self, PyObject *args, PyObject *kwds)
{
    static char *kwlist[] = {"first", "last", "number", NULL};
    PyObject *first = NULL, *last = NULL, *tmp;

    if (!PyArg_ParseTupleAndKeywords(args, kwds, "|OOi", kwlist,
                                    &first, &last,
                                    &self->number))
        return -1;

    if (first) {
        tmp = self->first;
        Py_INCREF(first);
        self->first = first;
        Py_XDECREF(tmp);
    }
}
```

(sonraki sayfaya devam)

(önceki sayfadan devam)

```

if (last) {
    tmp = self->last;
    Py_INCREF(last);
    self->last = last;
    Py_XDECREF(tmp);
}
return 0;
}

```

by filling the `tp_init` slot.

```
.tp_init = (initproc) Custom_init,
```

The `tp_init` slot is exposed in Python as the `__init__()` method. It is used to initialize an object after it's created. Initializers always accept positional and keyword arguments, and they should return either `0` on success or `-1` on error.

Unlike the `tp_new` handler, there is no guarantee that `tp_init` is called at all (for example, the `pickle` module by default doesn't call `__init__()` on unpickled instances). It can also be called multiple times. Anyone can call the `__init__()` method on our objects. For this reason, we have to be extra careful when assigning the new attribute values. We might be tempted, for example to assign the `first` member like this:

```

if (first) {
    Py_XDECREF(self->first);
    Py_INCREF(first);
    self->first = first;
}

```

But this would be risky. Our type doesn't restrict the type of the `first` member, so it could be any kind of object. It could have a destructor that causes code to be executed that tries to access the `first` member; or that destructor could release the *Global Interpreter Lock* and let arbitrary code run in other threads that accesses and modifies our object.

To be paranoid and protect ourselves against this possibility, we almost always reassign members before decrementing their reference counts. When don't we have to do this?

- when we absolutely know that the reference count is greater than 1;
- when we know that deallocation of the object¹ will neither release the *GIL* nor cause any calls back into our type's code;
- when decrementing a reference count in a `tp_dealloc` handler on a type which doesn't support cyclic garbage collection².

We want to expose our instance variables as attributes. There are a number of ways to do that. The simplest way is to define member definitions:

```

static PyMemberDef Custom_members[] = {
    {"first", Py_T_OBJECT_EX, offsetof(CustomObject, first), 0,
     "first name"},
    {"last", Py_T_OBJECT_EX, offsetof(CustomObject, last), 0,
     "last name"},
    {"number", Py_T_INT, offsetof(CustomObject, number), 0,
     "custom number"},
    {NULL} /* Sentinel */
};

```

and put the definitions in the `tp_members` slot:

¹ This is true when we know that the object is a basic type, like a string or a float.

² We relied on this in the `tp_dealloc` handler in this example, because our type doesn't support garbage collection.

```
.tp_members = Custom_members,
```

Each member definition has a member name, type, offset, access flags and documentation string. See the [Generic Attribute Management](#) section below for details.

A disadvantage of this approach is that it doesn't provide a way to restrict the types of objects that can be assigned to the Python attributes. We expect the first and last names to be strings, but any Python objects can be assigned. Further, the attributes can be deleted, setting the C pointers to `NULL`. Even though we can make sure the members are initialized to non-`NULL` values, the members can be set to `NULL` if the attributes are deleted.

We define a single method, `Custom.name()`, that outputs the objects name as the concatenation of the first and last names.

```
static PyObject *
Custom_name(CustomObject *self, PyObject *Py_UNUSED(ignored))
{
    if (self->first == NULL) {
        PyErr_SetString(PyExc_AttributeError, "first");
        return NULL;
    }
    if (self->last == NULL) {
        PyErr_SetString(PyExc_AttributeError, "last");
        return NULL;
    }
    return PyUnicode_FromFormat("%s %s", self->first, self->last);
}
```

The method is implemented as a C function that takes a `Custom` (or `Custom` subclass) instance as the first argument. Methods always take an instance as the first argument. Methods often take positional and keyword arguments as well, but in this case we don't take any and don't need to accept a positional argument tuple or keyword argument dictionary. This method is equivalent to the Python method:

```
def name(self):
    return "%s %s" % (self.first, self.last)
```

Note that we have to check for the possibility that our `first` and `last` members are `NULL`. This is because they can be deleted, in which case they are set to `NULL`. It would be better to prevent deletion of these attributes and to restrict the attribute values to be strings. We'll see how to do that in the next section.

Now that we've defined the method, we need to create an array of method definitions:

```
static PyMethodDef Custom_methods[] = {
    {"name", (PyCFunction) Custom_name, METH_NOARGS,
     "Return the name, combining the first and last name"},
    {NULL} /* Sentinel */
};
```

(note that we used the `METH_NOARGS` flag to indicate that the method is expecting no arguments other than `self`) and assign it to the `tp_methods` slot:

```
.tp_methods = Custom_methods,
```

Finally, we'll make our type usable as a base class for subclassing. We've written our methods carefully so far so that they don't make any assumptions about the type of the object being created or used, so all we need to do is to add the `Py_TPFLAGS_BASETYPE` to our class flag definition:

```
.tp_flags = Py_TPFLAGS_DEFAULT | Py_TPFLAGS_BASETYPE,
```

We rename `PyInit_custom()` to `PyInit_custom2()`, update the module name in the `PyModuleDef` struct, and update the full class name in the `PyTypeObject` struct.

Finally, we update our `setup.py` file to include the new module,

```
from setuptools import Extension, setup
setup(ext_modules=[  
    Extension("custom", ["custom.c"]),
    Extension("custom2", ["custom2.c"]),
])
```

and then we re-install so that we can `import custom2`:

```
$ python -m pip install .
```

2.2.3 Providing finer control over data attributes

In this section, we'll provide finer control over how the `first` and `last` attributes are set in the `Custom` example. In the previous version of our module, the instance variables `first` and `last` could be set to non-string values or even deleted. We want to make sure that these attributes always contain strings.

```
#define PY_SSIZE_T_CLEAN
#include <Python.h>
#include <stddef.h> /* for offsetof() */

typedef struct {
    PyObject_HEAD
    PyObject *first; /* first name */
    PyObject *last; /* last name */
    int number;
} CustomObject;

static void
Custom_dealloc(CustomObject *self)
{
    Py_XDECREF(self->first);
    Py_XDECREF(self->last);
    Py_TYPE(self)->tp_free((PyObject *) self);
}

static PyObject *
Custom_new(PyTypeObject *type, PyObject *args, PyObject *kwds)
{
    CustomObject *self;
    self = (CustomObject *) type->tp_alloc(type, 0);
    if (self != NULL) {
        self->first = PyUnicode_FromString("");
        if (self->first == NULL) {
            Py_DECREF(self);
            return NULL;
        }
        self->last = PyUnicode_FromString("");
        if (self->last == NULL) {
            Py_DECREF(self);
            return NULL;
        }
        self->number = 0;
    }
}
```

(sonraki sayfaya devam)

(önceki sayfadan devam)

```

    return (PyObject *) self;
}

static int
Custom_init(CustomObject *self, PyObject *args, PyObject *kwds)
{
    static char *kwlist[] = {"first", "last", "number", NULL};
    PyObject *first = NULL, *last = NULL;

    if (!PyArg_ParseTupleAndKeywords(args, kwds, "|UUi",
                                    &first, &last,
                                    &self->number))
        return -1;

    if (first) {
        Py_SETREF(self->first, Py_NewRef(first));
    }
    if (last) {
        Py_SETREF(self->last, Py_NewRef(last));
    }
    return 0;
};

static PyMemberDef Custom_members[] = {
    {"number", Py_T_INT, offsetof(CustomObject, number), 0,
     "custom number"},
    {NULL} /* Sentinel */
};

static PyObject *
Custom_getfirst(CustomObject *self, void *closure)
{
    return Py_NewRef(self->first);
}

static int
Custom_setfirst(CustomObject *self, PyObject *value, void *closure)
{
    if (value == NULL) {
        PyErr_SetString(PyExc_TypeError, "Cannot delete the first attribute");
        return -1;
    }
    if (!PyUnicode_Check(value)) {
        PyErr_SetString(PyExc_TypeError,
                       "The first attribute value must be a string");
        return -1;
    }
    Py_SETREF(self->first, Py_NewRef(value));
    return 0;
};

static PyObject *
Custom_getlast(CustomObject *self, void *closure)
{
    return Py_NewRef(self->last);
}

```

(sonraki sayfaya devam)

(önceki sayfadan devam)

```

static int
Custom_setlast(CustomObject *self, PyObject *value, void *closure)
{
    if (value == NULL) {
        PyErr_SetString(PyExc_TypeError, "Cannot delete the last attribute");
        return -1;
    }
    if (!PyUnicode_Check(value)) {
        PyErr_SetString(PyExc_TypeError,
                       "The last attribute value must be a string");
        return -1;
    }
    Py_SETREF(self->last, Py_NewRef(value));
    return 0;
}

static PyGetSetDef Custom_getsetters[] = {
    {"first", (getter) Custom_getfirst, (setter) Custom_setfirst,
     "first name", NULL},
    {"last", (getter) Custom_getlast, (setter) Custom_setlast,
     "last name", NULL},
    {NULL} /* Sentinel */
};

static PyObject *
Custom_name(CustomObject *self, PyObject *Py_UNUSED(ignored))
{
    return PyUnicode_FromFormat("%s %s", self->first, self->last);
}

static PyMethodDef Custom_methods[] = {
    {"name", (PyCFunction) Custom_name, METH_NOARGS,
     "Return the name, combining the first and last name"
    },
    {NULL} /* Sentinel */
};

static PyTypeObject CustomType = {
    .ob_base = PyVarObject_HEAD_INIT(NULL, 0)
    .tp_name = "custom3.Custom",
    .tp_doc = PyDoc_STR("Custom objects"),
    .tp_basicsize = sizeof(CustomObject),
    .tp_itemsize = 0,
    .tp_flags = Py_TPFLAGS_DEFAULT | Py_TPFLAGS_BASETYPE,
    .tp_new = Custom_new,
    .tp_init = (initproc) Custom_init,
    .tp_dealloc = (destructor) Custom_dealloc,
    .tp_members = Custom_members,
    .tp_methods = Custom_methods,
    .tp_getset = Custom_getsetters,
};
}

static PyModuleDef custommodule = {
    .m_base = PyModuleDef_HEAD_INIT,
    .m_name = "custom3",
}

```

(sonraki sayfaya devam)

(önceki sayfadan devam)

```

.m_doc = "Example module that creates an extension type.",
.m_size = -1,
};

PyMODINIT_FUNC
PyInit_custom3(void)
{
    PyObject *m;
    if (PyType_Ready(&CustomType) < 0)
        return NULL;

    m = PyModule_Create(&custommodule);
    if (m == NULL)
        return NULL;

    if (PyModule_AddObjectRef(m, "Custom", (PyObject *) &CustomType) < 0) {
        Py_DECREF(m);
        return NULL;
    }

    return m;
}

```

To provide greater control over the `first` and `last` attributes, we'll use custom getter and setter functions. Here are the functions for getting and setting the `first` attribute:

```

static PyObject *
Custom_getfirst(CustomObject *self, void *closure)
{
    Py_INCREF(self->first);
    return self->first;
}

static int
Custom_setfirst(CustomObject *self, PyObject *value, void *closure)
{
    PyObject *tmp;
    if (value == NULL) {
        PyErr_SetString(PyExc_TypeError, "Cannot delete the first attribute");
        return -1;
    }
    if (!PyUnicode_Check(value)) {
        PyErr_SetString(PyExc_TypeError,
                       "The first attribute value must be a string");
        return -1;
    }
    tmp = self->first;
    Py_INCREF(value);
    self->first = value;
    Py_DECREF(tmp);
    return 0;
}

```

The getter function is passed a `Custom` object and a “closure”, which is a void pointer. In this case, the closure is ignored. (The closure supports an advanced usage in which definition data is passed to the getter and setter. This could, for example, be used to allow a single set of getter and setter functions that decide the attribute to get or set based on data in the closure.)

The setter function is passed the `Custom` object, the new value, and the closure. The new value may be `NULL`, in which case the attribute is being deleted. In our setter, we raise an error if the attribute is deleted or if its new value is not a string.

We create an array of `PyGetSetDef` structures:

```
static PyGetSetDef Custom_getsetters[] = {
    {"first", (getter) Custom_getfirst, (setter) Custom_setfirst,
     "first name", NULL},
    {"last", (getter) Custom_getlast, (setter) Custom_setlast,
     "last name", NULL},
    {NULL} /* Sentinel */
};
```

and register it in the `tp_getset` slot:

```
.tp_getset = Custom_getsetters,
```

The last item in a `PyGetSetDef` structure is the “closure” mentioned above. In this case, we aren’t using a closure, so we just pass `NULL`.

We also remove the member definitions for these attributes:

```
static PyMemberDef Custom_members[] = {
    {"number", Py_T_INT, offsetof(CustomObject, number), 0,
     "custom number"},
    {NULL} /* Sentinel */
};
```

We also need to update the `tp_init` handler to only allow strings³ to be passed:

```
static int
Custom_init(CustomObject *self, PyObject *args, PyObject *kwds)
{
    static char *kwlist[] = {"first", "last", "number", NULL};
    PyObject *first = NULL, *last = NULL, *tmp;

    if (!PyArg_ParseTupleAndKeywords(args, kwds, "|UUi", kwlist,
                                    &first, &last,
                                    &self->number))
        return -1;

    if (first) {
        tmp = self->first;
        Py_INCREF(first);
        self->first = first;
        Py_DECREF(tmp);
    }
    if (last) {
        tmp = self->last;
        Py_INCREF(last);
        self->last = last;
        Py_DECREF(tmp);
    }
    return 0;
}
```

³ We now know that the first and last members are strings, so perhaps we could be less careful about decrementing their reference counts, however, we accept instances of string subclasses. Even though deallocating normal strings won’t call back into our objects, we can’t guarantee that deallocating an instance of a string subclass won’t call back into our objects.

With these changes, we can assure that the `first` and `last` members are never `NULL` so we can remove checks for `NULL` values in almost all cases. This means that most of the `Py_XDECREF()` calls can be converted to `Py_DECREF()` calls. The only place we can't change these calls is in the `tp_dealloc` implementation, where there is the possibility that the initialization of these members failed in `tp_new`.

We also rename the module initialization function and module name in the initialization function, as we did before, and we add an extra definition to the `setup.py` file.

2.2.4 Supporting cyclic garbage collection

Python has a *cyclic garbage collector (GC)* that can identify unneeded objects even when their reference counts are not zero. This can happen when objects are involved in cycles. For example, consider:

```
>>> l = []
>>> l.append(l)
>>> del l
```

In this example, we create a list that contains itself. When we delete it, it still has a reference from itself. Its reference count doesn't drop to zero. Fortunately, Python's cyclic garbage collector will eventually figure out that the list is garbage and free it.

In the second version of the `Custom` example, we allowed any kind of object to be stored in the `first` or `last` attributes⁴. Besides, in the second and third versions, we allowed subclassing `Custom`, and subclasses may add arbitrary attributes. For any of those two reasons, `Custom` objects can participate in cycles:

```
>>> import custom3
>>> class Derived(custom3.Custom): pass
...
>>> n = Derived()
>>> n.some_attribute = n
```

To allow a `Custom` instance participating in a reference cycle to be properly detected and collected by the cyclic GC, our `Custom` type needs to fill two additional slots and to enable a flag that enables these slots:

```
#define PY_SSIZE_T_CLEAN
#include <Python.h>
#include <stddef.h> /* for offsetof() */

typedef struct {
    PyObject_HEAD
    PyObject *first; /* first name */
    PyObject *last; /* last name */
    int number;
} CustomObject;

static int
Custom_traverse(CustomObject *self, visitproc visit, void *arg)
{
    Py_VISIT(self->first);
    Py_VISIT(self->last);
    return 0;
}

static int
Custom_clear(CustomObject *self)
{
    Py_CLEAR(self->first);
```

(sonraki sayfaya devam)

⁴ Also, even with our attributes restricted to strings instances, the user could pass arbitrary `str` subclasses and therefore still create reference cycles.

(önceki sayfadan devam)

```

Py_CLEAR(self->last);
    return 0;
}

static void
Custom_dealloc(CustomObject *self)
{
    PyObject_GC_UnTrack(self);
    Custom_clear(self);
    Py_TYPE(self)->tp_free((PyObject *) self);
}

static PyObject *
Custom_new(PyTypeObject *type, PyObject *args, PyObject *kwds)
{
    CustomObject *self;
    self = (CustomObject *) type->tp_alloc(type, 0);
    if (self != NULL) {
        self->first = PyUnicode_FromString("");
        if (self->first == NULL) {
            Py_DECREF(self);
            return NULL;
        }
        self->last = PyUnicode_FromString("");
        if (self->last == NULL) {
            Py_DECREF(self);
            return NULL;
        }
        self->number = 0;
    }
    return (PyObject *) self;
}

static int
Custom_init(CustomObject *self, PyObject *args, PyObject *kwds)
{
    static char *kwlist[] = {"first", "last", "number", NULL};
    PyObject *first = NULL, *last = NULL;

    if (!PyArg_ParseTupleAndKeywords(args, kwds, "|UUi", kwlist,
                                    &first, &last,
                                    &self->number))
        return -1;

    if (first) {
        Py_SETREF(self->first, Py_NewRef(first));
    }
    if (last) {
        Py_SETREF(self->last, Py_NewRef(last));
    }
    return 0;
}

static PyMemberDef Custom_members[] = {
    {"number", Py_T_INT, offsetof(CustomObject, number), 0,
     "custom number"},
```

(sonraki sayfaya devam)

(önceki sayfadan devam)

```

    {NULL} /* Sentinel */
};

static PyObject *
Custom_getfirst(CustomObject *self, void *closure)
{
    return Py_NewRef(self->first);
}

static int
Custom_setfirst(CustomObject *self, PyObject *value, void *closure)
{
    if (value == NULL) {
        PyErr_SetString(PyExc_TypeError, "Cannot delete the first attribute");
        return -1;
    }
    if (!PyUnicode_Check(value)) {
        PyErr_SetString(PyExc_TypeError,
                       "The first attribute value must be a string");
        return -1;
    }
    Py_XSETREF(self->first, Py_NewRef(value));
    return 0;
}

static PyObject *
Custom_getlast(CustomObject *self, void *closure)
{
    return Py_NewRef(self->last);
}

static int
Custom_setlast(CustomObject *self, PyObject *value, void *closure)
{
    if (value == NULL) {
        PyErr_SetString(PyExc_TypeError, "Cannot delete the last attribute");
        return -1;
    }
    if (!PyUnicode_Check(value)) {
        PyErr_SetString(PyExc_TypeError,
                       "The last attribute value must be a string");
        return -1;
    }
    Py_XSETREF(self->last, Py_NewRef(value));
    return 0;
}

static PyGetSetDef Custom_getsetters[] = {
    {"first", (getter) Custom_getfirst, (setter) Custom_setfirst,
     "first name", NULL},
    {"last", (getter) Custom_getlast, (setter) Custom_setlast,
     "last name", NULL},
    {NULL} /* Sentinel */
};

static PyObject *

```

(sonraki sayfaya devam)

(önceki sayfadan devam)

```

Custom_name(CustomObject *self, PyObject *Py_UNUSED(ignored))
{
    return PyUnicode_FromFormat("%S %S", self->first, self->last);
}

static PyMethodDef Custom_methods[] = {
    {"name", (PyCFunction) Custom_name, METH_NOARGS,
     "Return the name, combining the first and last name"
    },
    {NULL} /* Sentinel */
};

static PyTypeObject CustomType = {
    .ob_base = PyVarObject_HEAD_INIT(NULL, 0)
    .tp_name = "custom4.Custom",
    .tp_doc = PyDoc_STR("Custom objects"),
    .tp_basicsize = sizeof(CustomObject),
    .tp_itemsize = 0,
    .tp_flags = Py_TPFLAGS_DEFAULT | Py_TPFLAGS_BASETYPE | Py_TPFLAGS_HAVE_GC,
    .tp_new = Custom_new,
    .tp_init = (initproc) Custom_init,
    .tp_dealloc = (destructor) Custom_dealloc,
    .tp_traverse = (traverseproc) Custom_traverse,
    .tp_clear = (inquiry) Custom_clear,
    .tp_members = Custom_members,
    .tp_methods = Custom_methods,
    .tp_getset = Custom_getsetters,
};

static PyModuleDef custommodule = {
    .m_base = PyModuleDef_HEAD_INIT,
    .m_name = "custom4",
    .m_doc = "Example module that creates an extension type.",
    .m_size = -1,
};

PyMODINIT_FUNC
PyInit_custom4(void)
{
    PyObject *m;
    if (PyType_Ready(&CustomType) < 0)
        return NULL;

    m = PyModule_Create(&custommodule);
    if (m == NULL)
        return NULL;

    if (PyModule_AddObjectRef(m, "Custom", (PyObject *) &CustomType) < 0) {
        Py_DECREF(m);
        return NULL;
    }

    return m;
}

```

First, the traversal method lets the cyclic GC know about subobjects that could participate in cycles:

```
static int
Custom_traverse(CustomObject *self, visitproc visit, void *arg)
{
    int vret;
    if (self->first) {
        vret = visit(self->first, arg);
        if (vret != 0)
            return vret;
    }
    if (self->last) {
        vret = visit(self->last, arg);
        if (vret != 0)
            return vret;
    }
    return 0;
}
```

For each subobject that can participate in cycles, we need to call the `visit()` function, which is passed to the traversal method. The `visit()` function takes as arguments the subobject and the extra argument `arg` passed to the traversal method. It returns an integer value that must be returned if it is non-zero.

Python provides a `Py_VISIT()` macro that automates calling `visit` functions. With `Py_VISIT()`, we can minimize the amount of boilerplate in `Custom_traverse`:

```
static int
Custom_traverse(CustomObject *self, visitproc visit, void *arg)
{
    Py_VISIT(self->first);
    Py_VISIT(self->last);
    return 0;
}
```

i Not

The `tp_traverse` implementation must name its arguments exactly `visit` and `arg` in order to use `Py_VISIT()`.

Second, we need to provide a method for clearing any subobjects that can participate in cycles:

```
static int
Custom_clear(CustomObject *self)
{
    Py_CLEAR(self->first);
    Py_CLEAR(self->last);
    return 0;
}
```

Notice the use of the `Py_CLEAR()` macro. It is the recommended and safe way to clear data attributes of arbitrary types while decrementing their reference counts. If you were to call `Py_XDECREF()` instead on the attribute before setting it to `NULL`, there is a possibility that the attribute's destructor would call back into code that reads the attribute again (*especially* if there is a reference cycle).

i Not

You could emulate `Py_CLEAR()` by writing:

```
PyObject *tmp;
tmp = self->first;
```

```
self->first = NULL;
Py_XDECREF(tmp);
```

Nevertheless, it is much easier and less error-prone to always use `Py_CLEAR()` when deleting an attribute. Don't try to micro-optimize at the expense of robustness!

The deallocator `Custom_dealloc` may call arbitrary code when clearing attributes. It means the circular GC can be triggered inside the function. Since the GC assumes reference count is not zero, we need to untrack the object from the GC by calling `PyObject_GC_UnTrack()` before clearing members. Here is our reimplemented deallocator using `PyObject_GC_UnTrack()` and `Custom_clear`:

```
static void
Custom_dealloc(CustomObject *self)
{
    PyObject_GC_UnTrack(self);
    Custom_clear(self);
    Py_TYPE(self)->tp_free((PyObject *) self);
}
```

Finally, we add the `Py_TPFLAGS_HAVE_GC` flag to the class flags:

```
.tp_flags = Py_TPFLAGS_DEFAULT | Py_TPFLAGS_BASETYPE | Py_TPFLAGS_HAVE_GC,
```

That's pretty much it. If we had written custom `tp_alloc` or `tp_free` handlers, we'd need to modify them for cyclic garbage collection. Most extensions will use the versions automatically provided.

2.2.5 Subclassing other types

It is possible to create new extension types that are derived from existing types. It is easiest to inherit from the built-in types, since an extension can easily use the `PyTypeObject` it needs. It can be difficult to share these `PyTypeObject` structures between extension modules.

In this example we will create a `SubList` type that inherits from the built-in `list` type. The new type will be completely compatible with regular lists, but will have an additional `increment()` method that increases an internal counter:

```
>>> import sublist
>>> s = sublist.SubList(range(3))
>>> s.extend(s)
>>> print(len(s))
6
>>> print(s.increment())
1
>>> print(s.increment())
2
```

```
#define PY_SSIZE_T_CLEAN
#include <Python.h>

typedef struct {
    PyListObject list;
    int state;
} SubListObject;

static PyObject *
SubList_increment(SubListObject *self, PyObject *unused)
{
```

(sonraki sayfaya devam)

(önceki sayfadan devam)

```

    self->state++;
    return PyLong_FromLong(self->state);
}

static PyMethodDef SubList_methods[] = {
    {"increment", (PyCFunction) SubList_increment, METH_NOARGS,
     PyDoc_STR("increment state counter")},
    {NULL},
};

static int
SubList_init(SubListObject *self, PyObject *args, PyObject *kwds)
{
    if (PyList_Type.tp_init((PyObject *) self, args, kwds) < 0)
        return -1;
    self->state = 0;
    return 0;
}

static PyTypeObject SubListType = {
    PyVarObject_HEAD_INIT(NULL, 0)
    .tp_name = "sublist.SubList",
    .tp_doc = PyDoc_STR("SubList objects"),
    .tp_basicsize = sizeof(SubListObject),
    .tp_itemsize = 0,
    .tp_flags = Py_TPFLAGS_DEFAULT | Py_TPFLAGS_BASETYPE,
    .tp_init = (initproc) SubList_init,
    .tp_methods = SubList_methods,
};
}

static PyModuleDef sublistmodule = {
    PyModuleDef_HEAD_INIT,
    .m_name = "sublist",
    .m_doc = "Example module that creates an extension type.",
    .m_size = -1,
};

PyMODINIT_FUNC
PyInit_sublist(void)
{
    PyObject *m;
    SubListType.tp_base = &PyList_Type;
    if (PyType_Ready(&SubListType) < 0)
        return NULL;

    m = PyModule_Create(&sublistmodule);
    if (m == NULL)
        return NULL;

    if (PyModule_AddObjectRef(m, "SubList", (PyObject *) &SubListType) < 0) {
        Py_DECREF(m);
        return NULL;
    }

    return m;
}

```

As you can see, the source code closely resembles the `Custom` examples in previous sections. We will break down the main differences between them.

```
typedef struct {
    PyObject list;
    int state;
} SubListObject;
```

The primary difference for derived type objects is that the base type's object structure must be the first value. The base type will already include the `PyObject_HEAD()` at the beginning of its structure.

When a Python object is a `SubList` instance, its `PyObject *` pointer can be safely cast to both `PyListObject *` and `SubListObject *`:

```
static int
SubList_init(SubListObject *self, PyObject *args, PyObject *kwds)
{
    if (PyList_Type.tp_init((PyObject *) self, args, kwds) < 0)
        return -1;
    self->state = 0;
    return 0;
}
```

We see above how to call through to the `__init__()` method of the base type.

This pattern is important when writing a type with custom `tp_new` and `tp_dealloc` members. The `tp_new` handler should not actually create the memory for the object with its `tp_alloc`, but let the base class handle it by calling its own `tp_new`.

The `PyTypeObject` struct supports a `tp_base` specifying the type's concrete base class. Due to cross-platform compiler issues, you can't fill that field directly with a reference to `PyList_Type`; it should be done later in the module initialization function:

```
PyMODINIT_FUNC
PyInit_sublist(void)
{
    PyObject* m;
    SubListType.tp_base = &PyList_Type;
    if (PyType_Ready(&SubListType) < 0)
        return NULL;

    m = PyModule_Create(&sublistmodule);
    if (m == NULL)
        return NULL;

    if (PyModule_AddObjectRef(m, "SubList", (PyObject *) &SubListType) < 0) {
        Py_DECREF(m);
        return NULL;
    }

    return m;
}
```

Before calling `PyType_Ready()`, the type structure must have the `tp_base` slot filled in. When we are deriving an existing type, it is not necessary to fill out the `tp_alloc` slot with `PyType_GenericNew()` – the allocation function from the base type will be inherited.

After that, calling `PyType_Ready()` and adding the type object to the module is the same as with the basic `Custom` examples.

2.3 Defining Extension Types: Assorted Topics

This section aims to give a quick fly-by on the various type methods you can implement and what they do.

Here is the definition of `PyTypeObject`, with some fields only used in debug builds omitted:

```
typedef struct _typeobject {
    PyObject_VAR_HEAD
    const char *tp_name; /* For printing, in format "<module>.<name>" */
    Py_ssize_t tp_basicsize, tp_itemsize; /* For allocation */

    /* Methods to implement standard operations */

    destructor tp_dealloc;
    Py_ssize_t tp_vectorcall_offset;
    getattrofunc tp_getattr;
    setattrofunc tp_setattr;
    PyAsyncMethods *tp_as_async; /* formerly known as tp_compare (Python 2)
                                  or tp_reserved (Python 3) */
    reprfunc tp_repr;

    /* Method suites for standard classes */

    PyNumberMethods *tp_as_number;
    PySequenceMethods *tp_as_sequence;
    PyMappingMethods *tp_as_mapping;

    /* More standard operations (here for binary compatibility) */

    hashfunc tp_hash;
    ternaryfunc tp_call;
    reprfunc tp_str;
    getattrofunc tp_getattro;
    setattrofunc tp_setattro;

    /* Functions to access object as input/output buffer */
    PyBufferProcs *tp_as_buffer;

    /* Flags to define presence of optional/expanded features */
    unsigned long tp_flags;

    const char *tp_doc; /* Documentation string */

    /* Assigned meaning in release 2.0 */
    /* call function for all accessible objects */
    traverseproc tp_traverse;

    /* delete references to contained objects */
    inquiry tp_clear;

    /* Assigned meaning in release 2.1 */
    /* rich comparisons */
    richcmpfunc tp_richcompare;

    /* weak reference enabler */
    Py_ssize_t tp_weaklistoffset;

    /* Iterators */
}
```

(sonraki sayfaya devam)

(önceki sayfadan devam)

```

getiterfunc tp_iter;
iternextfunc tp_iternext;

/* Attribute descriptor and subclassing stuff */
struct PyMethodDef *tp_methods;
struct PyMemberDef *tp_members;
struct PyGetSetDef *tp_getset;
// Strong reference on a heap type, borrowed reference on a static type
struct _typeobject *tp_base;
PyObject *tp_dict;
descrgetfunc tp_descr_get;
descrsetfunc tp_descr_set;
Py_ssize_t tp_dictoffset;
initproc tp_init;
allocfunc tp_alloc;
newfunc tp_new;
freefunc tp_free; /* Low-level free-memory routine */
inquiry tp_is_gc; /* For PyObject_IS_GC */
PyObject *tp_bases;
PyObject *tp_mro; /* method resolution order */
PyObject *tp_cache;
PyObject *tp_subclasses;
PyObject *tp_weaklist;
destructor tp_del;

/* Type attribute cache version tag. Added in version 2.6 */
unsigned int tp_version_tag;

destructor tp_finalize;
vectorcallfunc tp_vectorcall;

/* bitset of which type-watchers care about this type */
unsigned char tp_watched;
} PyTypeObject;

```

Now that's a *lot* of methods. Don't worry too much though – if you have a type you want to define, the chances are very good that you will only implement a handful of these.

As you probably expect by now, we're going to go over this and give more information about the various handlers. We won't go in the order they are defined in the structure, because there is a lot of historical baggage that impacts the ordering of the fields. It's often easiest to find an example that includes the fields you need and then change the values to suit your new type.

```
const char *tp_name; /* For printing */
```

The name of the type – as mentioned in the previous chapter, this will appear in various places, almost entirely for diagnostic purposes. Try to choose something that will be helpful in such a situation!

```
Py_ssize_t tp_basicsize, tp_itemsize; /* For allocation */
```

These fields tell the runtime how much memory to allocate when new objects of this type are created. Python has some built-in support for variable length structures (think: strings, tuples) which is where the `tp_itemsize` field comes in. This will be dealt with later.

```
const char *tp_doc;
```

Here you can put a string (or its address) that you want returned when the Python script references `obj.__doc__` to retrieve the doc string.

Now we come to the basic type methods – the ones most extension types will implement.

2.3.1 Finalization and De-allocation

```
destructor tp_dealloc;
```

This function is called when the reference count of the instance of your type is reduced to zero and the Python interpreter wants to reclaim it. If your type has memory to free or other clean-up to perform, you can put it here. The object itself needs to be freed here as well. Here is an example of this function:

```
static void
newdatatype_dealloc(newdatatypeobject *obj)
{
    free(obj->obj_UnderlyingDatatypePtr);
    Py_TYPE(obj)->tp_free((PyObject *)obj);
}
```

If your type supports garbage collection, the destructor should call `PyObject_GC_UnTrack()` before clearing any member fields:

```
static void
newdatatype_dealloc(newdatatypeobject *obj)
{
    PyObject_GC_UnTrack(obj);
    Py_CLEAR(obj->other_obj);
    ...
    Py_TYPE(obj)->tp_free((PyObject *)obj);
}
```

One important requirement of the deallocator function is that it leaves any pending exceptions alone. This is important since deallocated are frequently called as the interpreter unwinds the Python stack; when the stack is unwound due to an exception (rather than normal returns), nothing is done to protect the deallocated from seeing that an exception has already been set. Any actions which a deallocator performs which may cause additional Python code to be executed may detect that an exception has been set. This can lead to misleading errors from the interpreter. The proper way to protect against this is to save a pending exception before performing the unsafe action, and restoring it when done. This can be done using the `PyErr_Fetch()` and `PyErr_Restore()` functions:

```
static void
my_dealloc(PyObject *obj)
{
    MyObject *self = (MyObject *) obj;
    PyObject *cbresult;

    if (self->my_callback != NULL) {
        PyObject *err_type, *err_value, *err_traceback;

        /* This saves the current exception state */
        PyErr_Fetch(&err_type, &err_value, &err_traceback);

        cbresult = PyObject_CallNoArgs(self->my_callback);
        if (cbresult == NULL)
            PyErr_WriteUnraisable(self->my_callback);
        else
            Py_DECREF(cbresult);

        /* This restores the saved exception state */
        PyErr_Restore(err_type, err_value, err_traceback);
    }
}
```

(sonraki sayfaya devam)

(önceki sayfadan devam)

```

    Py_DECREF(self->my_callback);
}
Py_TYPE(obj)->tp_free((PyObject*)self);
}

```

i Not

There are limitations to what you can safely do in a deallocator function. First, if your type supports garbage collection (using `tp_traverse` and/or `tp_clear`), some of the object's members can have been cleared or finalized by the time `tp_dealloc` is called. Second, in `tp_dealloc`, your object is in an unstable state: its reference count is equal to zero. Any call to a non-trivial object or API (as in the example above) might end up calling `tp_dealloc` again, causing a double free and a crash.

Starting with Python 3.4, it is recommended not to put any complex finalization code in `tp_dealloc`, and instead use the new `tp_finalize` type method.

 **Ayrıca bakınız**

[PEP 442](#) explains the new finalization scheme.

2.3.2 Object Presentation

In Python, there are two ways to generate a textual representation of an object: the `repr()` function, and the `str()` function. (The `print()` function just calls `str()`.) These handlers are both optional.

```

reprfunc tp_repr;
reprfunc tp_str;

```

The `tp_repr` handler should return a string object containing a representation of the instance for which it is called. Here is a simple example:

```

static PyObject *
newdatatype_repr(newdatatypeobject *obj)
{
    return PyUnicode_FromFormat("Repr-ified_newdatatype{{size:%d}}",
                               obj->obj_UnderlyingDatatypePtr->size);
}

```

If no `tp_repr` handler is specified, the interpreter will supply a representation that uses the type's `tp_name` and a uniquely identifying value for the object.

The `tp_str` handler is to `str()` what the `tp_repr` handler described above is to `repr()`; that is, it is called when Python code calls `str()` on an instance of your object. Its implementation is very similar to the `tp_repr` function, but the resulting string is intended for human consumption. If `tp_str` is not specified, the `tp_repr` handler is used instead.

Here is a simple example:

```

static PyObject *
newdatatype_str(newdatatypeobject *obj)
{
    return PyUnicode_FromFormat("Stringified_newdatatype{{size:%d}}",
                               obj->obj_UnderlyingDatatypePtr->size);
}

```

2.3.3 Attribute Management

For every object which can support attributes, the corresponding type must provide the functions that control how the attributes are resolved. There needs to be a function which can retrieve attributes (if any are defined), and another to set attributes (if setting attributes is allowed). Removing an attribute is a special case, for which the new value passed to the handler is `NULL`.

Python supports two pairs of attribute handlers; a type that supports attributes only needs to implement the functions for one pair. The difference is that one pair takes the name of the attribute as a `char*`, while the other accepts a `PyObject*`. Each type can use whichever pair makes more sense for the implementation's convenience.

```
getattrofunc tp_getattro;           /* char * version */
setattrfunc tp_setattro;
/* ... */
getattrofunc tp_getattro;           /* PyObject * version */
setattrfunc tp_setattro;
```

If accessing attributes of an object is always a simple operation (this will be explained shortly), there are generic implementations which can be used to provide the `PyObject*` version of the attribute management functions. The actual need for type-specific attribute handlers almost completely disappeared starting with Python 2.2, though there are many examples which have not been updated to use some of the new generic mechanism that is available.

Generic Attribute Management

Most extension types only use *simple* attributes. So, what makes the attributes simple? There are only a couple of conditions that must be met:

1. The name of the attributes must be known when `PyType_Ready()` is called.
2. No special processing is needed to record that an attribute was looked up or set, nor do actions need to be taken based on the value.

Note that this list does not place any restrictions on the values of the attributes, when the values are computed, or how relevant data is stored.

When `PyType_Ready()` is called, it uses three tables referenced by the type object to create *descriptors* which are placed in the dictionary of the type object. Each descriptor controls access to one attribute of the instance object. Each of the tables is optional; if all three are `NULL`, instances of the type will only have attributes that are inherited from their base type, and should leave the `tp_getattro` and `tp_setattro` fields `NULL` as well, allowing the base type to handle attributes.

The tables are declared as three fields of the type object:

```
struct PyMethodDef *tp_methods;
struct PyMemberDef *tp_members;
struct PyGetSetDef *tp_getset;
```

If `tp_methods` is not `NULL`, it must refer to an array of `PyMethodDef` structures. Each entry in the table is an instance of this structure:

```
typedef struct PyMethodDef {
    const char *ml_name;           /* method name */
    PyCFunction ml_meth;           /* implementation function */
    int ml_flags;                 /* flags */
    const char *ml_doc;            /* docstring */
} PyMethodDef;
```

One entry should be defined for each method provided by the type; no entries are needed for methods inherited from a base type. One additional entry is needed at the end; it is a sentinel that marks the end of the array. The `ml_name` field of the sentinel must be `NULL`.

The second table is used to define attributes which map directly to data stored in the instance. A variety of primitive C types are supported, and access may be read-only or read-write. The structures in the table are defined as:

```
typedef struct PyMemberDef {
    const char *name;
    int type;
    int offset;
    int flags;
    const char *doc;
} PyMemberDef;
```

For each entry in the table, a *descriptor* will be constructed and added to the type which will be able to extract a value from the instance structure. The `type` field should contain a type code like `Py_T_INT` or `Py_T_DOUBLE`; the value will be used to determine how to convert Python values to and from C values. The `flags` field is used to store flags which control how the attribute can be accessed: you can set it to `Py_READONLY` to prevent Python code from setting it.

An interesting advantage of using the `tp_members` table to build descriptors that are used at runtime is that any attribute defined this way can have an associated doc string simply by providing the text in the table. An application can use the introspection API to retrieve the descriptor from the class object, and get the doc string using its `__doc__` attribute.

As with the `tp_methods` table, a sentinel entry with a `ml_name` value of `NULL` is required.

Type-specific Attribute Management

For simplicity, only the `char*` version will be demonstrated here; the type of the name parameter is the only difference between the `char*` and `PyObject*` flavors of the interface. This example effectively does the same thing as the generic example above, but does not use the generic support added in Python 2.2. It explains how the handler functions are called, so that if you do need to extend their functionality, you'll understand what needs to be done.

The `tp_getattr` handler is called when the object requires an attribute look-up. It is called in the same situations where the `__getattr__()` method of a class would be called.

Here is an example:

```
static PyObject *
newdatatype_getattr(newdatatypeobject *obj, char *name)
{
    if (strcmp(name, "data") == 0)
    {
        return PyLong_FromLong(obj->data);
    }

    PyErr_Format(PyExc_AttributeError,
                "'%.100s' object has no attribute '%.400s'",
                Py_TYPE(obj)->tp_name, name);
    return NULL;
}
```

The `tp_setattr` handler is called when the `__setattr__()` or `__delattr__()` method of a class instance would be called. When an attribute should be deleted, the third parameter will be `NULL`. Here is an example that simply raises an exception; if this were really all you wanted, the `tp_setattr` handler should be set to `NULL`.

```
static int
newdatatype_setattr(newdatatypeobject *obj, char *name, PyObject *v)
{
    PyErr_Format(PyExc_RuntimeError, "Read-only attribute: %s", name);
    return -1;
}
```

2.3.4 Object Comparison

```
richcmpfunc tp_richcompare;
```

The `tp_richcompare` handler is called when comparisons are needed. It is analogous to the rich comparison methods, like `__lt__()`, and also called by `PyObject_RichCompare()` and `PyObject_RichCompareBool()`.

This function is called with two Python objects and the operator as arguments, where the operator is one of `Py_EQ`, `Py_NE`, `Py_LE`, `Py_GE`, `Py_LT` or `Py_GT`. It should compare the two objects with respect to the specified operator and return `Py_True` or `Py_False` if the comparison is successful, `Py_NotImplemented` to indicate that comparison is not implemented and the other object's comparison method should be tried, or `NULL` if an exception was set.

Here is a sample implementation, for a datatype that is considered equal if the size of an internal pointer is equal:

```
static PyObject *
newdatatype_richcmp(newdatatypeobject *obj1, newdatatypeobject *obj2, int op)
{
    PyObject *result;
    int c, size1, size2;

    /* code to make sure that both arguments are of type
     newdatatype omitted */

    size1 = obj1->obj_UnderlyingDatatypePtr->size;
    size2 = obj2->obj_UnderlyingDatatypePtr->size;

    switch (op) {
    case Py_LT: c = size1 < size2; break;
    case Py_LE: c = size1 <= size2; break;
    case Py_EQ: c = size1 == size2; break;
    case Py_NE: c = size1 != size2; break;
    case Py_GT: c = size1 > size2; break;
    case Py_GE: c = size1 >= size2; break;
    }
    result = c ? Py_True : Py_False;
    Py_INCREF(result);
    return result;
}
```

2.3.5 Abstract Protocol Support

Python supports a variety of *abstract* ‘protocols;’ the specific interfaces provided to use these interfaces are documented in abstract.

A number of these abstract interfaces were defined early in the development of the Python implementation. In particular, the number, mapping, and sequence protocols have been part of Python since the beginning. Other protocols have been added over time. For protocols which depend on several handler routines from the type implementation, the older protocols have been defined as optional blocks of handlers referenced by the type object. For newer protocols there are additional slots in the main type object, with a flag bit being set to indicate that the slots are present and should be checked by the interpreter. (The flag bit does not indicate that the slot values are non-`NULL`. The flag may be set to indicate the presence of a slot, but a slot may still be unfilled.)

```
PyNumberMethods *tp_as_number;
PySequenceMethods *tp_as_sequence;
PyMappingMethods *tp_as_mapping;
```

If you wish your object to be able to act like a number, a sequence, or a mapping object, then you place the address of a structure that implements the C type `PyNumberMethods`, `PySequenceMethods`, or `PyMappingMethods`, respectively. It is up to you to fill in this structure with appropriate values. You can find examples of the use of each of these in the `Objects` directory of the Python source distribution.

```
hashfunc tp_hash;
```

This function, if you choose to provide it, should return a hash number for an instance of your data type. Here is a simple example:

```
static Py_hash_t  
newdatatype_hash(newdatatypeobject *obj)  
{  
    Py_hash_t result;  
    result = obj->some_size + 32767 * obj->some_number;  
    if (result == -1)  
        result = -2;  
    return result;  
}
```

`Py_hash_t` is a signed integer type with a platform-varying width. Returning `-1` from `tp_hash` indicates an error, which is why you should be careful to avoid returning it when hash computation is successful, as seen above.

```
ternaryfunc tp_call;
```

This function is called when an instance of your data type is “called”, for example, if `obj1` is an instance of your data type and the Python script contains `obj1('hello')`, the `tp_call` handler is invoked.

This function takes three arguments:

1. `self` is the instance of the data type which is the subject of the call. If the call is `obj1('hello')`, then `self` is `obj1`.
2. `args` is a tuple containing the arguments to the call. You can use `PyArg_ParseTuple()` to extract the arguments.
3. `kwds` is a dictionary of keyword arguments that were passed. If this is non-NULL and you support keyword arguments, use `PyArg_ParseTupleAndKeywords()` to extract the arguments. If you do not want to support keyword arguments and this is non-NULL, raise a `TypeError` with a message saying that keyword arguments are not supported.

Here is a toy `tp_call` implementation:

```
static PyObject *  
newdatatype_call(newdatatypeobject *obj, PyObject *args, PyObject *kwds)  
{  
    PyObject *result;  
    const char *arg1;  
    const char *arg2;  
    const char *arg3;  
  
    if (!PyArg_ParseTuple(args, "sss:call", &arg1, &arg2, &arg3)) {  
        return NULL;  
    }  
    result = PyUnicode_FromFormat(  
        "Returning -- value: [%d] arg1: [%s] arg2: [%s] arg3: [%s]\n",  
        obj->obj_UnderlyingDatatypePtr->size,  
        arg1, arg2, arg3);  
    return result;  
}
```

```
/* Iterators */  
getiterfunc tp_iter;  
iternextfunc tp_iternext;
```

These functions provide support for the iterator protocol. Both handlers take exactly one parameter, the instance for which they are being called, and return a new reference. In the case of an error, they should set an exception and return `NULL`. `tp_iter` corresponds to the Python `__iter__()` method, while `tp_iternext` corresponds to the Python `__next__()` method.

Any `iterable` object must implement the `tp_iter` handler, which must return an `iterator` object. Here the same guidelines apply as for Python classes:

- For collections (such as lists and tuples) which can support multiple independent iterators, a new iterator should be created and returned by each call to `tp_iter`.
- Objects which can only be iterated over once (usually due to side effects of iteration, such as file objects) can implement `tp_iter` by returning a new reference to themselves – and should also therefore implement the `tp_iternext` handler.

Any `iterator` object should implement both `tp_iter` and `tp_iternext`. An iterator's `tp_iter` handler should return a new reference to the iterator. Its `tp_iternext` handler should return a new reference to the next object in the iteration, if there is one. If the iteration has reached the end, `tp_iternext` may return `NULL` without setting an exception, or it may set `StopIteration` *in addition* to returning `NULL`; avoiding the exception can yield slightly better performance. If an actual error occurs, `tp_iternext` should always set an exception and return `NULL`.

2.3.6 Weak Reference Support

One of the goals of Python's weak reference implementation is to allow any type to participate in the weak reference mechanism without incurring the overhead on performance-critical objects (such as numbers).

Ayrıca bakınız

Documentation for the `weakref` module.

For an object to be weakly referenceable, the extension type must set the `Py_TPFLAGS_MANAGED_WEAKREF` bit of the `tp_flags` field. The legacy `tp_weaklistoffset` field should be left as zero.

Concretely, here is how the statically declared type object would look:

```
static PyTypeObject TrivialType = {
    PyVarObject_HEAD_INIT(NULL, 0)
    /* ... other members omitted for brevity ... */
    .tp_flags = Py_TPFLAGS_MANAGED_WEAKREF | ...,
};
```

The only further addition is that `tp_dealloc` needs to clear any weak references (by calling `PyObject_ClearWeakRefs()`):

```
static void
Trivial_dealloc(TrivialObject *self)
{
    /* Clear weakrefs first before calling any destructors */
    PyObject_ClearWeakRefs((PyObject *) self);
    /* ... remainder of destruction code omitted for brevity ... */
    Py_TYPE(self)->tp_free((PyObject *) self);
}
```

2.3.7 More Suggestions

In order to learn how to implement any specific method for your new data type, get the `C`Python source code. Go to the `Objects` directory, then search the C source files for `tp_` plus the function you want (for example, `tp_richcompare`). You will find examples of the function you want to implement.

When you need to verify that an object is a concrete instance of the type you are implementing, use the `PyObject_TypeCheck()` function. A sample of its use might be something like the following:

```
if (!PyObject_TypeCheck(some_object, &MyType)) {
    PyErr_SetString(PyExc_TypeError, "arg #1 not a mything");
    return NULL;
}
```

➡ Ayrıca bakınız

Download CPython source releases.

<https://www.python.org/downloads/source/>

The CPython project on GitHub, where the CPython source code is developed.

<https://github.com/python/cpython>

2.4 Building C and C++ Extensions

A C extension for CPython is a shared library (e.g. a .so file on Linux, .pyd on Windows), which exports an *initialization function*.

To be importable, the shared library must be available on `PYTHONPATH`, and must be named after the module name, with an appropriate extension. When using `setuptools`, the correct filename is generated automatically.

The initialization function has the signature:

```
PyObject *PyInit_modulename(void)
```

It returns either a fully initialized module, or a `PyModuleDef` instance. See `initializing-modules` for details.

For modules with ASCII-only names, the function must be named `PyInit_<modulename>`, with `<modulename>` replaced by the name of the module. When using multi-phase-initialization, non-ASCII module names are allowed. In this case, the initialization function name is `PyInitU_<modulename>`, with `<modulename>` encoded using Python's *punycode* encoding with hyphens replaced by underscores. In Python:

```
def initfunc_name(name):
    try:
        suffix = b'_' + name.encode('ascii')
    except UnicodeEncodeError:
        suffix = b'_U_' + name.encode('punycode').replace(b'-', b'_')
    return b'PyInit' + suffix
```

It is possible to export multiple modules from a single shared library by defining multiple initialization functions. However, importing them requires using symbolic links or a custom importer, because by default only the function corresponding to the filename is found. See the “*Multiple modules in one library*” section in [PEP 489](#) for details.

2.4.1 Building C and C++ Extensions with setuptools

Python 3.12 and newer no longer come with `distutils`. Please refer to the `setuptools` documentation at <https://setuptools.readthedocs.io/en/latest/setuptools.html> to learn more about how build and distribute C/C++ extensions with `setuptools`.

2.5 Windows'ta C ve C++ Uzantıları Oluşturmak

Bu bölüm, Microsoft Visual C++ kullanarak Python için bir Windows uzantı modülünün nasıl oluşturulacağını kısaca açıklar ve nasıl çalıştığını dair daha ayrıntılı arka plan bilgileri ile devam eder. Açıklayıcı materyal, hem Python uzantıları oluşturmayı öğrenen Windows programcısı hem de Windows üzerinde başarılı bir şekilde yazılım oluşturabilecek yazılım üretmekle ilgilenen Unix programcısı için yararlıdır.

Modül yazarları, bu bölümde açıklanan yaklaşım yerine, uzantı modülleri oluşturmak için distutils yaklaşımını kullanmaları önerilir. Yine de Python'u oluşturmak için kullanılan C derleyicisine ihtiyacınız olacaktır; tipik olarak Microsoft Visual C++.

Not

Bu bölümde, kodlanmış bir Python sürüm numarası içeren bir dizi dosya adından bahsedilmektedir. Bu dosya adları XY olarak gösterilen sürüm numarası ile temsil edilir; pratikte, 'X' büyük sürüm numarası ve 'Y' çalıştırığınız Python sürümünün küçük sürüm numarası olacaktır. Örneğin, Python 2.2.1 kullanıyorsanız, XY aslında 22 olacaktır.

2.5.1 Bir Yemek Kitabı Yaklaşımı

Unix'te olduğu gibi Windows'ta da uzantı modülleri oluşturmak için iki yaklaşım vardır: oluşturma işlemini kontrol etmek için `setuptools` paketini kullanın veya işleri manuel olarak yapın. `Setuptools` yaklaşımı çoğu uzantı için iyi çalışır; uzantı modüllerini oluşturmak ve paketlemek için `setuptools` kullanımına ilişkin belgeler [Building C and C+ Extensions with setuptools](#) içinde mevcuttur. Eğer işleri gerçekten elle yapmanız gerektiğini düşünüyorsanız, `winsound` standart kütüphane modülü için proje dosyasını incelemek öğretici olabilir.

2.5.2 Unix ve Windows Arasındaki Farklar

Unix ve Windows, kodun çalışma zamanında yüklenmesi için tamamen farklı paradigmalar kullanır. Dinamik olarak yüklenen bir modül oluşturmaya çalışmadan önce, sisteminizin nasıl çalıştığını farkında olun.

Unix'te, paylaşılan bir nesne (.so) dosyası, program tarafından kullanılacak kodu ve ayrıca programda bulmayı beklediği işlevlerin ve verilerin adlarını içerir. Dosya programa eklendiğinde, dosyanın kodundaki bu işlevlere ve verilere yapılan tüm referanslar, programdaki işlevlerin ve verilerin belleğe yerleştirildiği gerçek konumları gösterecek şekilde değiştirilir. Bu temelde bir bağlantı işlemidir.

Windows'ta, bir dinamik bağlantı kitabı (.dll) dosyasında sarkan referanslar yoktur. Bunun yerine, işlevlere veya verilere erişim bir arama tablosundan geçer. Dolayısıyla, DLL kodunun programın belleğine başvurmak için çalışma zamanında düzeltilmesi gerekmek; bunun yerine, kod zaten DLL'nin arama tablosunu kullanır ve arama tablosu çalışma zamanında işlevlere ve verilere işaret edecek şekilde değiştirilir.

Unix'te, birkaç nesne dosyasından (.o) kod içeren yalnızca bir tür kütüphane dosyası (.a) vardır. Paylaşılan bir nesne dosyası (.so) oluşturmak için bağlantı adımı sırasında, bağlayıcı bir tanımlayıcının nerede tanımlandığını bilmemiğini fark edebilir. Bağlayıcı bunu kütüphanelerdeki nesne dosyalarında arayacaktır; bulursa, o nesne dosyasındaki tüm kodu dahil edecektir.

Windows'ta iki tür kütüphane vardır: statik kütüphane ve içe aktarma kütüphanesi (her ikisi de .lib olarak adlandırılır). Stistik kütüphane Unix .a dosyası gibidir; gerektiğinde dahil edilecek kodu içerir. Bir içe aktarma kitabı temel olarak yalnızca bağlayıcıya belirli bir tanımlayıcının yasal olduğu ve DLL yüklenliğinde programda bulunacağı konusunda güvence vermek için kullanılır. Böylece bağlayıcı, DLL'de bulunmayan tanımlayıcıları kullanmak üzere arama tablosunu oluşturmak için içe aktarma kitaplığındaki bilgileri kullanır. Bir uygulama veya DLL bağlandığında, uygulama veya DLL'deki sembollere bağlı olan gelecekteki tüm DLL'ler için kullanılması gereken bir içe aktarma kitabı oluşturulabilir.

Başka bir A kod bloğunu paylaşması gereken B ve C olmak üzere iki dinamik yükleme modülü oluşturduğunuzu varsayıyalım. Unix'te B.so ve C.so için A.a dosyasını bağlayıcıya aktarmazsınız; bu, iki kez dahil edilmesine neden olur, böylece B ve C'nin her biri kendi kopyasına sahip olur. Windows'ta, A.dll dosyasını oluşturmak aynı zamanda A.lib dosyasını da oluşturacaktır. B ve C için bağlayıcıya A.lib dosyasını geçirirsiniz. A.lib kod içermez; sadece çalışma zamanında A'nın koduna erişmek için kullanılacak bilgileri içerir.

Windows'ta, bir içe aktarma kütüphanesi kullanmak `import spam` kullanmak gibidir; `spam`'ın adlarına erişmenizi sağlar, ancak ayrı bir kopya oluşturmaz. Unix'te, bir kütüphane ile bağlantı kurmak daha çok `from spam import *` gibidir; ayrı bir kopya oluşturur.

2.5.3 DLL'leri Uygulamada Kullanma

Windows Python Microsoft Visual C++ ile oluşturulmuştur; diğer derleyicileri kullanmak işe yarayabilir veya yaramayabilir. Bu bölümün geri kalanı MSVC++'a özeldir.

Windows'ta DLL oluştururken, bağlayıcıya `pythonXY.lib` komutunu geçirmelisiniz. İki DLL oluşturmak için, `spam` ve `ni` (`spam` içinde bulunan C fonksiyonlarını kullanır), şu komutları kullanabilirsiniz:

```
cl /LD /I:/python/include spam.c ..libs/pythonXY.lib  
cl /LD /I:/python/include ni.c spam.lib ..libs/pythonXY.lib
```

İlk komut üç dosya oluşturdu: `spam.obj`, `spam.dll` ve `spam.lib`. `Spam.dll` herhangi bir Python fonksiyonu içermiyor (örneğin `PyArg_ParseTuple()`), ancak `pythonXY.lib` sayesinde Python kodunu nasıl bulacağını biliyor.

İkinci komut, `spam`'den ve ayrıca Python çalıştırılabilir dosyasından gerekli işlevleri nasıl bulacağını bilen `ni.dll` (ve `.obj` ve `.lib`) oluşturdu.

Her tanımlayıcı arama tablosuna aktarılmaz. Diğer modüllerin (Python dahil) tanımlayıcılarını görmesini istiyorsanız, `void _declspec(dllexport) initspam(void)` veya `PyObject _declspec(dllexport) *NiGetSpamData(void)` gibi `_declspec(dllexport)` demeniz gereklidir.

Developer Studio, gerçekten ihtiyacınız olmayan birçok içe aktarma kütüphanesi ekleyerek çalıştırılabilir dosyanıza yaklaşık 100K kütüphane ekleyecektir. Bunlardan kurtulmak için Proje Ayarları iletişim kutusunu, Bağlantı sekmesini kullanarak *varsayılan kütüphaneleri yoksa* seçeneğini belirleyin. Kütüphaneler listesine doğru `msvcrtxx.lib` dosyasını ekleyin.

BÖLÜM 3

CPython çalışma zamanını daha büyük bir uygulamaya gömme

Bazen, ana uygulama olarak Python yorumlayıcısının içinde çalışan bir uzanti oluşturmak yerine, bunun yerine CPython çalışma zamanını daha büyük bir uygulamanın içine gömmek tercih edilir. Bu bölüm, bunu başarılı bir şekilde yapmakla ilgili bazı ayrıntıları içerir.

3.1 Python'ı Başka Bir Uygulamaya Gömme

Önceki bölümlerde Python'un nasıl genişletileceği, yani Python'a bir C fonksiyonları kitaplığı ekleyerek Python'un işlevsellüğünün nasıl genişletileceği tartışıldı. Bunu ayrıca tam tersi şekilde de yapmak mümkündür: Python'u içine gömerek C/C++ uygulamanızı zenginleştirir. Gömme işlemi, uygulamanıza bazı işlevlerini C veya C++ yerine Python'da uygulama yeteneği sağlar. Bu birçok amaç için kullanılabilir; bir örnek olarak kullanıcıların Python'da bazı komut dosyaları yazarak uygulamayı ihtiyaçlarına göre uyarlamalarına izin vermek olabilir. Bazı işlevler Python'da daha kolay yazılabilecekse kendiniz de kullanabilirsiniz.

Python'u gömmek, onu genişletmeye benzer, ancak tam olarak değil. Aralarındaki farksa Python'u genişlettiğinizde, uygulamanın ana programının hala Python yorumlayıcısı olması; Python'u gömerseniz, ana programın Python ile hiçbir ilgisi olmayabilmesidir — bunun yerine, uygulamanın bazı bölümleri bazı Python kodlarını çalıştırmak için zaman zaman Python yorumlayıcısını çağırır.

Yani Python'u gömüyorsanız, kendi ana programınızı sağlıyorsunuz demektir. Bu ana programın yapması gereken şeylerden biri Python yorumlayıcısını başlatmaktadır. En azından `Py_Initialize()` fonksiyonunu çağrırmalısınız. Python'a komut satırı argümanlarını iletmek için opsiyonel çağrılar vardır. Daha sonra uygulamanın herhangi bir yerinden yorumlayıcıyı çağrılabilirsiniz.

Yorumlayıcıyı çağrımanın birkaç farklı yolu vardır: Python deyimlerini içeren bir dizeyi `PyRun_SimpleString()` öğesine veya bir stdio dosya işaretçisini ve bir dosya adını (yalnızca hata mesajlarında tanımlama için) `PyRun_SimpleFile()`'a iletebilirsiniz. Python nesnelerini oluşturmak ve kullanmak için önceki bölümlerde açıklanan alt düzey işlemleri de çağrılabilirsiniz.

➡ Ayrıca bakınız

c-api-index

Python'un C arayüzünün detayları bu kılavuzda verilmiştir. Çok sayıda gerekli bilgi burada bulunabilir.

3.1.1 Çok Üst Düzey Gömme

Python'u gömmenin en basit şekli, çok yüksek seviyeli arayüzün kullanılmasıdır. Bu arabirim, uygulamaya doğrudan etkileşime girmeye gerek kalmadan bir Python betiği yürütmemi amaçlamaktadır. Bu örnek olarak bir dosya üzerinde bazı işlemler gerçekleştirmek için kullanılabilir.

```
#define PY_SSIZE_T_CLEAN
#include <Python.h>

int
main(int argc, char *argv[])
{
    PyStatus status;
    PyConfig config;
    PyConfig_InitPythonConfig(&config);

    /* optional but recommended */
    status = PyConfig_SetBytesString(&config, &config.program_name, argv[0]);
    if (PyStatus_Exception(status)) {
        goto exception;
    }

    status = Py_InitializeFromConfig(&config);
    if (PyStatus_Exception(status)) {
        goto exception;
    }
    PyConfig_Clear(&config);

    PyRun_SimpleString("from time import time,ctime\n"
                       "print('Today is', ctime(time()))\n");
    if (Py_FinalizeEx() < 0) {
        exit(120);
    }
    return 0;

exception:
    PyConfig_Clear(&config);
    Py_ExitStatusException(status);
}
```

Not

`#define PY_SSIZE_T_CLEAN` was used to indicate that `Py_ssize_t` should be used in some APIs instead of `int`. It is not necessary since Python 3.13, but we keep it here for backward compatibility. See `arg-parsing-string-and-buffers` for a description of this macro.

Setting `PyConfig.program_name` should be called before `Py_InitializeFromConfig()` to inform the interpreter about paths to Python run-time libraries. Next, the Python interpreter is initialized with `Py_Initialize()`, followed by the execution of a hard-coded Python script that prints the date and time. Afterwards, the `Py_FinalizeEx()` call shuts the interpreter down, followed by the end of the program. In a real program, you may want to get the Python script from another source, perhaps a text-editor routine, a file, or a database. Getting the Python code from a file can better be done by using the `PyRun_SimpleFile()` function, which saves you the trouble of allocating memory space and loading the file contents.

3.1.2 Çok Yüksek Düzeyde Gömmenin Ötesinde: Genel Bir Bakış

Yüksek seviyeli arayüz size uygulamanızdan rastgele Python kodu parçalarını yürütme yeteneği verir, ancak veri değerleri alışverişi en hafif tabirle oldukça zahmetlidir. Bunu istiyorsanız, daha düşük seviyeli aramalar kullanmalısınız. Daha fazla C kodu yazmak zorunda kalma pahasına neredeyse her şeyi başarabilirsiniz.

Farklı amaçlara rağmen Python'u genişletmek ve Python'u gömmek tamamen aynı aktivitedir. Önceki bölümlerde tartışılan konuların çoğu hala geçerlidir. Bunu göstermek için Python'dan C'ye uzantı kodunun gerçekten ne yaptığı düşünün:

1. Veri değerlerini Python'dan C'ye çevirin,
2. Çevrilen değerleri kullanarak bir C rutinine bir fonksiyon çağrıları yapın, ve
3. Çağrıdaki veri değerlerini C'den Python'a çevirin.

Python'u yerleştirirken, arayüz kodu şunları yapar:

1. Veri değerlerini C'den Python'a çevirin,
2. Çevrilen değerleri kullanarak bir Python arabirim rutinine bir fonksiyon çağrıları gerçekleştirin ve
3. Çağrıdaki veri değerlerini C'den Python'a dönüştürün.

Gördüğünüz gibi, veri dönüştürme adımları, diller arası aktarımın farklı yönüne uyum sağlamak için basitçe değişti- rilir. Tek fark, her iki veri dönüşümü arasında çağrıdığınız rutindir. Uzatırken C rutini çağrırsınız, gömerken Python rutini çağrırsınız.

Bu bölüm, verilerin Python'dan C'ye nasıl dönüştürüleceğini ve bunun tam tersini tartışmayacaktır. Ayrıca, referansların doğru kullanımı ve hataların ele alınmasının anlaşıldığı varsayılmaktadır. Bu hususlar, yorumlayıcının genişle- tilmesinden farklı olmadığı için, gerekli bilgiler için önceki bölümlere başvurabilirsiniz.

3.1.3 Saf Gömme

İlk program, bir Python betiğinde bir fonksiyonu çalıştırmayı amaçlar. Çok yüksek seviyeli arayüzle ilgili bölümde olduğu gibi, Python yorumlayıcısı uygulama ile doğrudan etkileşime girmez (ancak bu bir sonraki bölümde de-ğişectir).

Python betiğinde tanımlanan bir işlevi çalışma kodu:

```
#define PY_SSIZE_T_CLEAN
#include <Python.h>

int
main(int argc, char *argv[])
{
    PyObject *pName, *pModule, *pFunc;
    PyObject *pArgs, *pValue;
    int i;

    if (argc < 3) {
        fprintf(stderr, "Usage: call pythonfile funcname [args]\n");
        return 1;
    }

    Py_Initialize();
    pName = PyUnicode_DecodeFSDefault(argv[1]);
    /* Error checking of pName left out */

    pModule = PyImport_Import(pName);
    Py_DECREF(pName);

    if (pModule != NULL) {
```

(sonraki sayfaya devam)

(önceki sayfadan devam)

```

pFunc = PyObject_GetAttrString(pModule, argv[2]);
/* pFunc is a new reference */

if (pFunc && PyCallable_Check(pFunc)) {
    pArgs = PyTuple_New(argc - 3);
    for (i = 0; i < argc - 3; ++i) {
        pValue = PyLong_FromLong(atoi(argv[i + 3]));
        if (!pValue) {
            Py_DECREF(pArgs);
            Py_DECREF(pModule);
            fprintf(stderr, "Cannot convert argument\n");
            return 1;
        }
        /* pValue reference stolen here: */
        PyTuple_SetItem(pArgs, i, pValue);
    }
    pValue = PyObject_CallObject(pFunc, pArgs);
    Py_DECREF(pArgs);
    if (pValue != NULL) {
        printf("Result of call: %ld\n", PyLong_AsLong(pValue));
        Py_DECREF(pValue);
    }
    else {
        Py_DECREF(pFunc);
        Py_DECREF(pModule);
        PyErr_Print();
        fprintf(stderr, "Call failed\n");
        return 1;
    }
}
else {
    if (PyErr_Occurred())
        PyErr_Print();
    fprintf(stderr, "Cannot find function \"%s\"\n", argv[2]);
}
Py_XDECREF(pFunc);
Py_DECREF(pModule);
}
else {
    PyErr_Print();
    fprintf(stderr, "Failed to load \"%s\"\n", argv[1]);
    return 1;
}
if (Py_FinalizeEx() < 0) {
    return 120;
}
return 0;
}

```

Bu kod, argv[1] kullanarak bir Python betiği yükler ve argv[2] içinde adlandırılan fonksiyonu çağırır. Tamsayı argümanları, argv dizisinin diğer değerleridir. Bu programı *derler*, ve bağılsanız (bitmiş yürütülebilir dosyayı **call** olarak adlandırıralım) ve onu aşağıdaki gibi bir Python betğini çalıştırınmak için kullanırsanız:

```

def multiply(a,b):
    print("Will compute", a, "times", b)
    c = 0

```

(sonraki sayfaya devam)

(önceki sayfadan devam)

```
for i in range(0, a):
    c = c + b
return c
```

o zaman sonuç olmalıdır:

```
$ call multiply multiply 3 2
Will compute 3 times 2
Result of call: 6
```

Program işlevselligi açısından oldukça büyük olmasına rağmen, kodun çoğu Python ve C arasında veri dönüştürme ve hata raporlama içindir. Python'u gömmekle ilgili ilginç kısım şununla başlar

```
Py_Initialize();
pName = PyUnicode_DecodeFSDefault(argv[1]);
/* Error checking of pName left out */
pModule = PyImport_Import(pName);
```

Yorumlayıcıyı başlattıktan sonra komut dosyası `PyImport_Import()` kullanılarak yüklenir. Bu rutin, argümanı olarak `PyUnicode_FromString()` veri dönüştürme rutini kullanılarak oluşturulan bir Python dizesine ihtiyaç duyar.

```
pFunc = PyObject_GetAttrString(pModule, argv[2]);
/* pFunc is a new reference */

if (pFunc && PyCallable_Check(pFunc)) {
    ...
}
Py_XDECREF(pFunc);
```

Komut dosyası yükленikten sonra, aradığımız ad `PyObject_GetAttrString()` kullanılarak alınır. Ad varsa ve döndürülen nesne çağrılabilirse bunun bir fonksiyon olduğunu güvenle varsayıbilirsiniz. Program daha sonra normal olarak bir dizi argüman oluşturarak devam eder. Python işlevine yapılan çağrı şu şekilde yapılır:

```
pValue = PyObject_CallObject(pFunc, pArgs);
```

Fonksiyon döndürüldüğünde, `pValue` ya NULL olur ya da fonksiyonun dönüş değerine bir başvuru içerir. Değeri inceledikten sonra referans bırakığınızdan emin olun.

3.1.4 Gömülü Python'u Genişletme

Şimdiye kadar, gömülü Python yorumlayıcısının uygulamanın kendisinden işlevsellige erişimi yoktu. Python API, gömülü yorumlayıcıyı genişletecek buna izin verir. Yani, gömülü yorumlayıcı, uygulama tarafından sağlanan rutinlerle genişletilir. Kulağa karmaşık gelse de, o kadar da kötü değil. Uygulamanın Python yorumlayıcısını başlattığını bir süreliğine unutun. Bunun yerine, uygulamayı bir dizi altyordam olarak düşünün ve tipki normal bir Python uzantısı yazacağınız gibi, Python'un bu rutinlere erişmesini sağlayan bir tutkal kodu yazın. Örneğin:

```
static int numargs=0;

/* Return the number of arguments of the application command line */
static PyObject*
emb_numargs(PyObject *self, PyObject *args)
{
    if(!PyArg_ParseTuple(args, ":numargs"))
        return NULL;
    return PyLong_FromLong(numargs);
}
```

(sonraki sayfaya devam)

```

static PyMethodDef EmbMethods[] = {
    {"numargs", emb_numargs, METH_VARARGS,
     "Return the number of arguments received by the process."},
    {NULL, NULL, 0, NULL}
};

static PyModuleDef EmbModule = {
    PyModuleDef_HEAD_INIT, "emb", NULL, -1, EmbMethods,
    NULL, NULL, NULL, NULL
};

static PyObject*
PyInit_emb(void)
{
    return PyModule_Create(&EmbModule);
}

```

Yukarıdaki kodu `main()` fonksiyonunun hemen üstüne ekleyin. Ayrıca, `Py_Initialize()`: çağrılarından önce aşağıdaki iki ifadeyi ekleyin:

```

numargs = argc;
PyImport_AppendInittab("emb", &PyInit_emb);

```

These two lines initialize the `numargs` variable, and make the `emb.numargs()` function accessible to the embedded Python interpreter. With these extensions, the Python script can do things like

```

import emb
print("Number of arguments", emb.numargs())

```

Gerçek bir uygulamada, yöntemler uygulamanın API'sini Python'a gösterir.

3.1.5 Python'u C++'a Gömmek

Python'u bir C++ programına yerleştirmek de mümkündür; bunun tam olarak nasıl yapılacağı, kullanılan C++ sisteminin ayrıntılarına bağlı olacaktır; genel olarak ana programı C++ ile yazmanız ve programınızı derlemek ve bağlamak için C++ derleyicisini kullanmanız gerekecektir. Python'un kendisini C++ kullanarak yeniden derlemeye gerek yoktur.

3.1.6 Unix benzeri sistemler altında Derleme ve Bağlama

Python yorumlayıcısını uygulamaniza gömmek için derleyicinize (ve bağılayıcınıza) iletilecek doğru bayrakları bulmak mutlaka önemli değildir, özellikle Python'un C dinamik uzantıları buna karşı bağlantılı olan (.so dosyaları) olarak uygulanan kütüphane modüllerini yüklemesi gerekiğinden.

Gerekli derleyici ve bağılayıcı bayraklarını bulmak için, yükleme işleminin bir parçası olarak oluşturulan `pythonX.Y-config` betğini çalıştırabilirsiniz (bir `python3-config` betiği de mevcut olabilir). Bu komut dosyası, size doğrudan yardımcı olacak birkaç seçenek sahiptir:

- `pythonX.Y-config --cflags` derleme sırasında size önerilen bayrakları verecektir:

```

$ /opt/bin/python3.11-config --cflags
-I/opt/include/python3.11 -I/opt/include/python3.11 -Wsign-compare -DNDEBUG -
-g -fwrapv -O3 -Wall

```

- `pythonX.Y-config --ldflags --embed`, bağlantı kurarken size önerilen bayrakları verecektir:

```
$ /opt/bin/python3.11-config --ldflags --embed  
-L/opt/lib/python3.11/config-3.11-x86_64-linux-gnu -L/opt/lib -lpython3.11 -  
-lpthread -ldl -lutil -lm
```

i Not

Birkaç Python kurulumu arasında (ve özellikle sistem Python ile kendi derlenmiş Python'unuz arasında) karışıklığı önlemek için, yukarıdaki örnekte olduğu gibi mutlak `pythonX.Y-config` yolunu kullanmanız önerilir.

Bu prosedür sizin için işe yaramazsa (tüm Unix benzeri platformlar için çalışması garanti edilmez; ancak, memnuniyetle karşılıyoruz: hata raporları) dinamik hakkında sisteminizin belgelerini okumanız gerekecektir ve/veya Python'un `Makefile` (konumunu bulmak için `sysconfig.get_makefile_filename()` kullanın) ve derleme seçeneklerini bağlamayı inceleyin. Bu durumda, `sysconfig` modülü, birleştirmek isteyeceğiniz konfigürasyon değerlerini programlı olarak çıkarmak için kullanışlı bir araçtır. Örneğin:

```
>>> import sysconfig  
>>> sysconfig.get_config_var('LIBS')  
'-lpthread -ldl -lutil'  
>>> sysconfig.get_config_var('LINKFORSHARED')  
'-Xlinker -export-dynamic'
```

Sözlük

>>>

The default Python prompt of the *interactive* shell. Often seen for code examples which can be executed interactively in the interpreter.

...

Şunlara başvurabilir:

- The default Python prompt of the *interactive* shell when entering the code for an indented code block, when within a pair of matching left and right delimiters (parentheses, square brackets, curly braces or triple quotes), or after specifying a decorator.
- Ellipsis yerleşik sabiti.

soyut temel sınıf

Soyut temel sınıflar *duck-typing* ‘i, `hasattr()` gibi diğer teknikler beceriksiz veya tamamen yanlış olduğunda arayızları tanımlamanın bir yolunu sağlayarak tamamlar (örneğin sihirli yöntemlerle). ABC’ler, bir sınıfın miras almayan ancak yine de `isinstance()` ve `issubclass()` tarafından tanımlanmış sınıflar olan sanal alt sınıfları tanıtır; `abc` modül belgelerine bakın. Python comes with many built-in ABCs for data structures (in the `collections.abc` module), numbers (in the `numbers` module), streams (in the `io` module), import finders and loaders (in the `importlib.abc` module). `abc` modülü ile kendi ABC’lerinizi oluşturabilirsiniz.

dipnot

Bir değişkenle, bir sınıf niteliğiyle veya bir fonksiyon parametresiyle veya bir dönüş değeriyile ilişkilendirilen, gelenek olarak *type hint* biçiminde kullanılan bir etiket.

Yerel değişkenlerin açıklamalarına çalışma zamanında erişilemez, ancak global değişkenlerin, sınıf nitelikleri ve işlevlerin açıklamaları, sırasıyla modüllerin, sınıfların ve işlevlerin `__annotations__` özel özelliğinde saklanır.

Bu işlevi açıklayan *variable annotation*, *function annotation*, **PEP 484** ve **PEP 526**’e bakın. Ek açıklamalarla çalışmaya ilişkin en iyi uygulamalar için ayrıca bkz. `annotations`-howto.

argüman

Fonksiyon çağrılarında bir *function* ‘a (veya *method*) geçirilen bir değer. İki tür argüman vardır:

- *keyword argument*: bir işlev çağrılarında bir tanımlayıcının (ör. `ad =`) önüne geçen veya bir sözlükte `**` ile başlayan bir değer olarak geçirilen bir argüman. Örneğin, 3 ve 5, aşağıdaki `complex()` çağrılarında anahtar kelimenin argümanlarıdır:

```
complex(real=3, imag=5)
complex(**{'real': 3, 'imag': 5})
```

- *positional argument*: anahtar kelime argümanı olmayan bir argüman. Konumsal argümanlar, bir argüman listesinin başında görünebilir ve/veya * ile başlayan bir *iterable* ögesinin öğeleri olarak iletilebilir. Örneğin, 3 ve 5, aşağıdaki çağrırlarda konumsal argümanlardır:

```
complex(3, 5)
complex(*(3, 5))
```

Argümanlar, bir fonksiyon gövdesindeki adlandırılmış yerel değişkenlere atanır. Bu atamayı yöneten kurallar için calls bölümüne bakın. Sözdizimsel olarak, bir argümanı temsil etmek için herhangi bir ifade kullanılabilir; değerlendirilen değer yerel değişkene atanır.

Ayrıca *parameter* sözlüğü girişine, the difference between arguments and parameters hakkındaki SSS sorusuna ve [PEP 362](#) 'ye bakın.

asenkron bağlam yöneticisi

An object which controls the environment seen in an `async with` statement by defining `__aenter__()` and `__aexit__()` methods. Introduced by [PEP 492](#).

asenkron生成器

asynchronous generator iterator döndüren bir işlev. Bir `async for` döngüsünde kullanılabilen bir dizi değer üretmek için `yield` ifadeleri içermesi dışında `async def` ile tanımlanmış bir eşyordam işlevine benziyor.

Genellikle bir asenkron üreteç işlevine atıfta bulunur, ancak bazı bağlamlarda bir *asynchronous generator iterator* 'e karşılık gelebilir. Amaçlanan anlamın net olmadığı durumlarda, tam terimlerin kullanılması belirsizliği öner.

Bir asenkron üretici fonksiyonu, `await` ifadelerinin yanı sıra `async for` ve `async with` ifadeleri içerebilir.

asenkron生成器 yineleyici

Bir *asynchronous generator* işlevi tarafından oluşturulan bir nesne.

This is an *asynchronous iterator* which when called using the `__anext__()` method returns an awaitable object which will execute the body of the asynchronous generator function until the next `yield` expression.

Each `yield` temporarily suspends processing, remembering the location execution state (including local variables and pending try-statements). When the *asynchronous generator iterator* effectively resumes with another awaitable returned by `__anext__()`, it picks up where it left off. See [PEP 492](#) and [PEP 525](#).

eş zamansız yinelenebilir

An object, that can be used in an `async for` statement. Must return an *asynchronous iterator* from its `__aiter__()` method. Introduced by [PEP 492](#).

asenkron yineleyici

An object that implements the `__aiter__()` and `__anext__()` methods. `__anext__()` must return an *awaitable* object. `async for` resolves the awaitables returned by an asynchronous iterator's `__anext__()` method until it raises a `StopAsyncIteration` exception. Introduced by [PEP 492](#).

nitelik

Noktalı ifadeler kullanılarak adıyla başvurulan bir nesnede ilişkili değer. Örneğin, *o* nesnesinin *a* özniteliği varsa, bu nesneye *o.a* olarak başvurulur.

Bir nesneye, eğer nesne izin veriyorsa, örneğin `setattr()` kullanarak, adı identifiers tarafından tanımlandığı gibi tanımlayıcı olmayan bir öznitelik vermek mümkündür. Böyle bir öznitelijke noktalı bir ifade kullanılarak erişilemez ve bunun yerine `getattr()` ile alınması gereklidir.

beklenebilir

An object that can be used in an `await` expression. Can be a *coroutine* or an object with an `__await__()` method. See also [PEP 492](#).

BDFL

Benevolent Dictator For Life, nami diğer Guido van Rossum, Python'un yaratıcısı.

ikili dosya

A *file object* able to read and write *bytes-like objects*. Examples of binary files are files opened in binary mode ('rb', 'wb' or 'rb+'), `sys.stdin.buffer`, `sys.stdout.buffer`, and instances of `io.BytesIO` and `gzip.GzipFile`.

Ayrıca `str` nesnelerini okuyabilen ve yazabilen bir dosya nesnesi için `text file` 'a bakın.

ödünç alınan referans

In Python's C API, a borrowed reference is a reference to an object, where the code using the object does not own the reference. It becomes a dangling pointer if the object is destroyed. For example, a garbage collection can remove the last `strong reference` to the object and so destroy it.

`borrowed reference` üzerinde `Py_INCREF()` çağrılmak, nesnenin ödünç alınanın son kullanımından önce yok edilemediği durumlar dışında, onu yerinde bir `strong reference` 'a dönüştürmek için tavsiye edilir. referans. `Py_NewRef()` işlevi, yeni bir `strong reference` oluşturmak için kullanılabilir.

bayt benzeri nesne

`bufferobjects` 'i destekleyen ve bir C-*contiguous* arabelleğini dışa aktarabilen bir nesne. Bu, tüm `bytes`, `bytearray` ve `array.array` nesnelerinin yanı sıra birçok yaygın `memoryview` nesnesini içerir. Bayt benzeri nesneler, ikili verilerle çalışan çeşitli işlemler için kullanılabilir; bunlara sıkıştırma, ikili dosyaya kaydetme ve bir soket üzerinden gönderme dahildir.

Bazı işlemler, değişken olması için ikili verilere ihtiyaç duyar. Belgeler genellikle bunlara "okuma-yazma bayt benzeri nesneler" olarak atıfta bulunur. Örnek değiştirilebilir arabellek nesneleri `bytearray` ve bir `bytearray memoryview` içerir. Diğer işlemler, ikili verilerin değişmez nesnelerde ("salt okunur bayt benzeri nesneler") depolanmasını gerektirir; bunların örnekleri arasında `bytes` ve bir `bytes` nesnesinin `memoryview` bulunur.

bayt kodu

Python kaynak kodu, bir Python programının CPython yorumlayıcısındaki dahili temsili olan bayt kodunda derlenir. Bayt kodu ayrıca `.pyc` dosyalarında önbelleğe alınır, böylece aynı dosyanın ikinci kez çalıştırılması daha hızlı olur (kaynaktan bayt koduna yeniden derleme önlenebilir). Bu "ara dilin", her bir bayt koduna karşılık gelen makine kodunu yürüten bir `sanal makine` üzerinde çalıştığı söylenir. Bayt kodlarının farklı Python sanal makineleri arasında çalışması veya Python sürümleri arasında kararlı olması beklenmediğini unutmayın.

Bayt kodu talimatlarının bir listesi `bytecodes` dokümanında bulunabilir.

çağırılabilir

Bir çağrılabılır, muhtemelen bir dizi argümanla (bkz. `argument`) ve aşağıdaki sözdizimiyle çağrılabılır bir nesnedir:

```
callable(argument1, argument2, argumentN)
```

Bir `fonksiyon` ve uzantısı olarak bir `metot` bir çağrılabılır. `__call__()` yöntemini uygulayan bir sınıf örneği de bir çağrılabılır.

geri çağrırmak

Gelecekte bir noktada yürütülecek bir argüman olarak iletilen bir alt program işlevi.

sınıf

Kullanıcı tanımlı nesneler oluşturmak için bir şablon. Sınıf tanımları normalde sınıfın örnekleri üzerinde çalışan yöntem tanımlarını içerir.

sınıf değişkeni

Bir sınıfta tanımlanmış ve yalnızca sınıf düzeyinde (yani sınıfın bir örneğinde değil) değiştirilmesi amaçlanan bir değişken.

closure variable

A `free variable` referenced from a `nested scope` that is defined in an outer scope rather than being resolved at runtime from the `globals` or `builtin` namespaces. May be explicitly defined with the `nonlocal` keyword to allow write access, or implicitly defined if the variable is only being read.

For example, in the `inner` function in the following code, both `x` and `print` are `free variables`, but only `x` is a `closure variable`:

```
def outer():
    x = 0
    def inner():
        nonlocal x
```

(sonraki sayfaya devam)

(önceki sayfadan devam)

```
x += 1
print(x)
return inner
```

Due to the `codeobject.co_freevars` attribute (which, despite its name, only includes the names of closure variables rather than listing all referenced free variables), the more general *free variable* term is sometimes used even when the intended meaning is to refer specifically to closure variables.

karmaşık sayı

Tüm sayıların bir reel kısım ve bir sanal kısım toplamı olarak ifade edildiği bilinen gerçek sayı sisteminin bir uzantısı. Hayali sayılar, hayali birimin gerçek katlarıdır (-1^{i} in karekökü), genellikle matematikte i veya mühendislikte j ile yazılır. Python, bu son gösterimle yazılan karmaşık sayılar için yerleşik desteği sahiptir; hayali kısım bir j son ekiyle yazılır, örneğin $3+1j$. `math` modülünün karmaşık eş değerlerine erişmek için `cmath` kullanın. Karmaşık sayıların kullanımı oldukça gelişmiş bir matematiksel özelliktir. Onlara olan ihtiyacın farkında değilseniz, onları güvenle görmezden gelebileceğiniz neredeyse kesindir.

context

This term has different meanings depending on where and how it is used. Some common meanings:

- The temporary state or environment established by a *context manager* via a `with` statement.
- The collection of keyvalue bindings associated with a particular `contextvars.Context` object and accessed via `ContextVar` objects. Also see *context variable*.
- A `contextvars.Context` object. Also see *current context*.

context management protocol

The `__enter__()` and `__exit__()` methods called by the `with` statement. See [PEP 343](#).

bağlam yöneticisi

An object which implements the *context management protocol* and controls the environment seen in a `with` statement. See [PEP 343](#).

bağlam değişkeni

A variable whose value depends on which context is the *current context*. Values are accessed via `contextvars.ContextVar` objects. Context variables are primarily used to isolate state between concurrent asynchronous tasks.

bitişik

Bir arabellek, *C-bitmişik* veya *Fortran bitmişik* ise tam olarak bitişik olarak kabul edilir. Sıfır boyutlu arabellekler C ve Fortran bitişiktir. Tek boyutlu dizilerde, öğeler sıfırdan başlayarak artan dizinler sırasına göre bellekte yan yana yerleştirilmelidir. Çok boyutlu C-bitmişik dizilerde, öğeleri bellek adresi sırasına göre ziyaret ederken son dizin en hızlı şekilde değişir. Ancak, Fortran bitmişik dizilerinde, ilk dizin en hızlı şekilde değişir.

eşyordam

Eşyordamlar, altyordamların daha genelleştirilmiş bir biçimidir. Alt programlara bir noktada girilir ve başka bir noktada çıkarılır. Eşyordamlar birçok noktada girilebilir, çıkışabilir ve devam ettirilebilir. `async def` ifadesi ile uygulanabilirler. Ayrıca bakınız [PEP 492](#).

eşyordam işlevi

Bir `coroutine` nesnesi döndüren bir işlev. Bir eşyordam işlevi `async def` ifadesiyle tanımlanabilir ve `await`, `async for` ve `async with` anahtar kelimelerini içerebilir. Bunlar [PEP 492](#) tarafından tanıtıldı.

CPython

Python programlama dilinin python.org üzerinde dağıtıldığı şekliyle kurallı uygulaması. “CPython” terimi, gerektiğinde bu uygulamayı Jython veya IronPython gibi diğerlerinden ayırmak için kullanılır.

current context

The `context` (`contextvars.Context` object) that is currently used by `ContextVar` objects to access (get or set) the values of *context variables*. Each thread has its own current context. Frameworks for executing asynchronous tasks (see `asyncio`) associate each task with a context which becomes the current context whenever the task starts or resumes execution.

dekoratör

Genellikle `@wrapper` sözdizimi kullanılarak bir işlev dönüştürülmüş olarak uygulanan, başka bir işlevi döndüren bir işlev. Dekoratörler için yaygın örnekler şunlardır: `classmethod()` ve `staticmethod()`.

Dekoratör sözdizimi yalnızca sözdizimsel şekemdir, aşağıdaki iki işlev tanımı anlamsal olarak eş degerdir:

```
def f(arg):
    ...
f = staticmethod(f)

@staticmethod
def f(arg):
    ...
```

Aynı kavram sınıflar için de mevcuttur, ancak orada daha az kullanılır. Dekoratörler hakkında daha fazla bilgi için `function definitions` ve `class definitions` belgelerine bakın.

tanımlayıcı

Any object which defines the methods `__get__()`, `__set__()`, or `__delete__()`. When a class attribute is a descriptor, its special binding behavior is triggered upon attribute lookup. Normally, using `a.b` to get, set or delete an attribute looks up the object named `b` in the class dictionary for `a`, but if `b` is a descriptor, the respective descriptor method gets called. Understanding descriptors is a key to a deep understanding of Python because they are the basis for many features including functions, methods, properties, class methods, static methods, and reference to super classes.

Tanımlayıcıların yöntemleri hakkında daha fazla bilgi için, bkz. `descriptors` veya `Descriptor How To Guide`.

sözlük

An associative array, where arbitrary keys are mapped to values. The keys can be any object with `__hash__()` and `__eq__()` methods. Called a hash in Perl.

sözlük açıklama

Öğelerin tümünü veya bir kısmını yinelenebilir bir şekilde işlemenin ve sonuçları içeren bir sözlük döndürmenin kompakt bir yolu. `results = {n: n ** 2 for range(10)}`, `n ** 2` değerine eşlenmiş `n` anahtarını içeren bir sözlük oluşturur. Bkz. `comprehensions`.

sözlük görünümü

`dict.keys()`, `dict.values()` ve `dict.items()` ‘den döndürülen nesnelere sözlük görünümleri denir. Sözlüğün girişleri üzerinde dinamik bir görünüm sağlarlar; bu, sözlük değiştiğinde görünümün bu değişiklikleri yansıttığı anlamına gelir. Sözlük görünümünü tam liste olmaya zorlamak için `list(dictview)` kullanın. Bakınız `dict-views`.

belge dizisi

A string literal which appears as the first expression in a class, function or module. While ignored when the suite is executed, it is recognized by the compiler and put into the `__doc__` attribute of the enclosing class, function or module. Since it is available via introspection, it is the canonical place for documentation of the object.

ördek yazma

Doğu arayüze sahip olup olmadığını belirlemek için bir nesnenin türüne bakmayan bir programlama stil; bunun yerine, yöntem veya nitelik basitçe çağrılrı veya kullanılır (“Ördek gibi görünyorsa ve ördek gibi vakıhyorsa, ördek olmalıdır.”) İyi tasarlanmış kod, belirli türlerden ziyade arayüzleri vurgulayarak, polimorfik ikameye izin vererek esnekliğini artırır. Ördek yazma, `type()` veya `isinstance()` kullanan testleri öner. (Ancak, ördek yazmanın `abstract base class` ile tamamlanabileceğini unutmayın.) Bunun yerine, genellikle `hasattr()` testleri veya `EAFP` programlamasını kullanır.

EAFP

Af dilemek izin almaktan daha kolaydır. Bu yaygın Python kodlama stil, geçerli anahtarların veya niteliklerin varlığını varsayar ve varsayımlının yanlış çıkması durumunda istisnaları yakalar. Bu temiz ve hızlı stil, birçok `try` ve `except` ifadesinin varlığı ile karakterize edilir. Teknik, C gibi diğer birçok dilde ortak olan `LYBL` stilileyi çelişir.

ifade (değer döndürür)

Bir değere göre değerlendirilebilecek bir sözdizimi parçası. Başka bir deyişle, bir ifade, tümü bir değer döndüren sabit değerler, adlar, öznitelik erişimi, işleçler veya işlev çağrıları gibi ifade öğelerinin bir toplamıdır. Diğer birçok dilin aksine, tüm dil yapıları ifade değildir. Ayrıca `while` gibi kullanılmayan [ifadeler](#) de vardır. Atamalar da değer döndürmeyecek ifadelerdir (statement).

uzatma modülü

Çekirdekle ve kullanıcı koduyla etkileşim kurmak için Python'un C API'sini kullanan, C veya C++ ile yazılmış bir modül.

f-string

Ön eki '`f`' veya '`F`' olan dize değişmezleri genellikle "f-strings" olarak adlandırılır; bu, formatted string literals'in kısaltmasıdır. Ayrıca bkz. [PEP 498](#).

dosya nesnesi

An object exposing a file-oriented API (with methods such as `read()` or `write()`) to an underlying resource. Depending on the way it was created, a file object can mediate access to a real on-disk file or to another type of storage or communication device (for example standard input/output, in-memory buffers, sockets, pipes, etc.). File objects are also called *file-like objects* or *streams*.

Aslında üç dosya nesnesi kategorisi vardır: ham *binary files*, arabalığe alınmış *binary files* ve *text files*. Ara-yüzleri `io` modülünde tanımlanmıştır. Bir dosya nesnesi yaratmanın kurallı yolu `open()` işlevini kullanmaktır.

dosya benzeri nesne

[dosya nesnesi](#) ile eşanlamlıdır.

dosya sistemi kodlaması ve hata işleyicisi

Python tarafından işletim sistemindeki baytların kodunu çözmek ve Unicode'u işletim sistemine kodlamak için kullanılan kodlama ve hata işleyici.

Dosya sistemi kodlaması, 128'in altındaki tüm baytların kodunu başarıyla çözmeyi garanti etmelidir. Dosya sistemi kodlaması bu garantiyi sağlayamazsa, API işlevleri `UnicodeError` değerini yükseltebilir.

`sys.getfilesystemencoding()` ve `sys.getfilesystemencodeerrors()` işlevleri, dosya sistemi kodlamasını ve hata işleyicisini almak için kullanılabilir.

filesystem encoding and error handler Python başlangıcında `PyConfig_Read()` işleviyle yapılandırılır: bkz. `filesystem_encoding` ve `filesystem_errors` üyeleri `PyConfig`.

Ayrıca bkz. [locale encoding](#).

bulucu

İçe aktarılmakta olan bir modül için `loader` 'ı bulmaya çalışan bir nesne.

There are two types of finder: *meta path finders* for use with `sys.meta_path`, and *path entry finders* for use with `sys.path_hooks`.

See `finders-and-loaders` and `importlib` for much more detail.

kat bölümü

En yakın tam sayıya yuvarlayan matematiksel bölme. Kat bölüm operatörü `//` şeklindedir. Örneğin, `11 // 4` ifadesi, gerçek üzer bölmeye tarafından döndürülen `2.75` değerinin aksine `2` olarak değerlendirilir. `(-11) // 4` 'ün `-3` olduğuna dikkat edin, çünkü bu `-2.75` yuvarlatılmış *asağı*. Bakınız [PEP 238](#).

free threading

A threading model where multiple threads can run Python bytecode simultaneously within the same interpreter. This is in contrast to the *global interpreter lock* which allows only one thread to execute Python bytecode at a time. See [PEP 703](#).

free variable

Formally, as defined in the language execution model, a free variable is any variable used in a namespace which is not a local variable in that namespace. See [closure variable](#) for an example. Pragmatically, due to the name of the `codeobject.co_freevars` attribute, the term is also sometimes used as a synonym for [closure variable](#).

fonksiyon

Bir arayana bir değer döndüren bir dizi ifade. Ayrıca, gövdenin yürütülmesinde kullanılabilen sıfır veya daha fazla [argüman](#) iletilebilir. Ayrıca [parameter](#), [method](#) ve [function](#) bölümüne bakın.

fonksiyon açıklaması

Bir işlev parametresinin veya dönüş değerinin *ek açıklaması*.

İşlev ek açıklamaları genellikle *type hints* için kullanılır: örneğin, bu fonksiyonun iki `int` argüman alması ve ayrıca bir `int` dönüş değerine sahip olması beklenir

```
def sum_two_numbers(a: int, b: int) -> int:
    return a + b
```

İşlev açıklama sözdizimi `function` bölümünde açıklanmaktadır.

Bu işlevi açıklayan *variable annotation* ve [PEP 484](#) 'e bakın. Ek açıklamalarla çalışmaya ilişkin en iyi uygulamalar için ayrıca annotations-howto konusuna bakın.

__future__

Bir `future` ifadesi, `from __future__ import <feature>`, derleyiciyi, Python'un gelecekteki bir sürümünde standart hale gelecek olan sözdizimini veya semantığı kullanarak mevcut modülü derlemeye yönlendirir. `__future__` modülü, `feature`'in olası değerlerini belgeler. Bu modülü içe aktararak ve değişkenlerini değerlendirerek, dile ilk kez yeni bir özelliğin ne zaman eklendiğini ve ne zaman varsayılan olacağını (ya da yaptığı) görebilirsiniz:

```
>>> import __future__
>>> __future__.division
_Feature((2, 2, 0, 'alpha', 2), (3, 0, 0, 'alpha', 0), 8192)
```

çöp toplama

Artık kullanılmadığında belleği boşaltma işlemi. Python, referans sayımı ve referans döngülerini algılayıp kırabilen bir döngüsel çöp toplayıcı aracılığıyla çöp toplama gerçekleştirir. Çöp toplayıcı `gc` modülü kullanıcılar kontrol edilebilir.

jeneratör

Bir *generator iterator* döndüren bir işlev. Bir `for` döngüsünde kullanılabilen bir dizi değer üretmek için `yield` ifadeleri içermesi veya `next()` işleviyle birer birer alınabilmesi dışında normal bir işlevle benziyor.

Genellikle bir üretici işlevine atıfta bulunur, ancak bazı bağamlarda bir *jeneratör yineleyicisine* atıfta bulunabilir. Amaçlanan anlamanın net olmadığı durumlarda, tam terimlerin kullanılması belirsizliği önler.

jeneratör yineleyici

Bir *generator* işlevi tarafından oluşturulan bir nesne.

Her `yield`, konum yürütme durumunu hatırlayarak (yerel değişkenler ve bekleyen `try` ifadeleri dahil) işlemeyi geçici olarak askıya alır. *jeneratör yineleyici* devam ettiğinde, kaldığı yerden devam eder (her çağrıda yeniden başlayan işlevlerin aksine).

jeneratör ifadesi

An *expression* that returns an *iterator*. It looks like a normal expression followed by a `for` clause defining a loop variable, range, and an optional `if` clause. The combined expression generates values for an enclosing function:

```
>>> sum(i*i for i in range(10))          # sum of squares 0, 1, 4, ... 81
285
```

genel işlev

Farklı türler için aynı işlemi uygulayan birden çok işlevden oluşan bir işlev. Bir çağrı sırasında hangi uygulamanın kullanılması gerektiği, gönderme algoritması tarafından belirlenir.

Ayrıca *single dispatch* sözlük girdisine, `functools.singledispatch()` dekoratörüne ve [PEP 443](#) 'e bakın.

genel tip

Parametreleştirilebilen bir *type*; tipik olarak bir konteyner sınıfı, örneğin `list` veya `dict`. *type hint* ve *annotation* için kullanılır.

Daha fazla ayrıntı için generic alias types, [PEP 483](#), [PEP 484](#), [PEP 585](#) ve `typing` modülüne bakın.

GIL

Bakınız *global interpreter lock*.

genel tercüman kilidi

C_{Python} yorumlayıcısı tarafından aynı anda yalnızca bir iş parçacığının Python *bytecode* ‘u yürütmesini sağlamak için kullanılan mekanizma. Bu, nesne modelini (*dict* gibi kritik yerleşik türler dahil) eşzamanlı erişime karşı örtük olarak güvenli hale getirerek CPython uygulamasını basitleştirir. Tüm yorumlayıcıyı kilitlemek, çok işlemci makinelerin sağladığı paralelligin çoğu pahasına, yorumlayıcının çok iş parçacıklı olmasını kolaylaştırır.

Bununla birlikte, standart veya üçüncü taraf bazı genişletme modülleri, sıkıştırma veya karma gibi hesaplama açısından yoğun görevler yaparken GIL’yi serbest bırakacak şekilde tasarlanmıştır. Ayrıca, GIL, G/Ç yaparken her zaman serbest bırakılır.

As of Python 3.13, the GIL can be disabled using the `--disable-gil` build configuration. After building Python with this option, code must be run with `-X gil =0` or after setting the `PYTHON_GIL =0` environment variable. This feature enables improved performance for multi-threaded applications and makes it easier to use multi-core CPUs efficiently. For more details, see [PEP 703](#).

karma tabanlı pyc

Geçerliliğini belirlemek için ilgili kaynak dosyanın son değiştirilme zamanı yerine karma değerini kullanan bir bayt kodu önbellek dosyası. Bakınız *pyc-validation*.

yıkabilir

An object is *hashable* if it has a hash value which never changes during its lifetime (it needs a `__hash__()` method), and can be compared to other objects (it needs an `__eq__()` method). Hashable objects which compare equal must have the same hash value.

Hashability, bir nesneyi bir sözlük anahtarı ve bir set üyesi olarak kullanılabılır hale getirir, çünkü bu veri yapıları hash değerini dahili olarak kullanır.

Python’ın değişmez yerleşik nesnelerinin çoğu, yıkanabilir; değiştirilebilir kaplar (listeler veya sözlükler gibi) değildir; değişmez kaplar (tüpler ve donmuş kümeler gibi) yalnızca öğelerinin yıkanabilir olması durumunda yıkanabildir. Kullanıcı tanımlı sınıfların örnekleri olan nesneler varsayılan olarak hash edilebilirdir. Hepsi eşit olmayanı karşılaştırır (kendileriyle hariç) ve hash değerleri `id()` ‘lerinden türetilir.

BOŞTA

Python için Entegre Geliştirme Ortamı. `idle`, Python’ın standart dağıtımlıyla birlikte gelen temel bir düzenleyici ve yorumlayıcı ortamıdır.

immortal

Immortal objects are a CPython implementation detail introduced in [PEP 683](#).

If an object is immortal, its *reference count* is never modified, and therefore it is never deallocated while the interpreter is running. For example, `True` and `None` are immortal in CPython.

değişmez

Sabit değeri olan bir nesne. Değişmez nesneler arasında sayılar, dizeler ve demetler bulunur. Böyle bir nesne değiştirilemez. Farklı bir değerin saklanması gerekiyorsa yeni bir nesne oluşturulmalıdır. Örneğin bir sözlükte anahtar olarak, sabit bir karma değerinin bulunduğu yerlerde önemli bir rol oynarlar.

İçe aktarım yol

İçe aktarılacak modüller için *path based finder* tarafından aranan konumların (veya *path entries*) listesi. İçe aktarma sırasında, bu konum listesi genellikle `sys.path` adresinden gelir, ancak alt paketler için üst paketin `__path__` özelliğinden de gelebilir.

İçe aktarma

Bir modüldeki Python kodunun başka bir modüldeki Python koduna sunulması süreci.

İçe aktarıcı

Bir modülü hem bulan hem de yükleyen bir nesne; hem bir *finder* hem de *loader* nesnesi.

etkileşimli

Python has an interactive interpreter which means you can enter statements and expressions at the interpreter prompt, immediately execute them and see their results. Just launch `python` with no arguments (possibly by

selecting it from your computer's main menu). It is a very powerful way to test out new ideas or inspect modules and packages (remember `help(x)`). For more on interactive mode, see `tut-interac`.

yorumlanmış

Python, derlenmiş bir dilin aksine yorumlanmış bir dildir, ancak bayt kodu derleyicisinin varlığı nedeniyle ayrılmak olabilir. Bu, kaynak dosyaların daha sonra çalıştırılacak bir yürütülebilir dosya oluşturmadan doğrudan çalıştırılabileceği anlamına gelir. Yorumlanan diller genellikle derlenmiş dillerden daha kısa bir geliştirme/hata ayıklama döngüsüne sahiptir, ancak programları genellikle daha yavaş çalışır. Ayrıca bkz. [interactive](#).

tercüman kapatma

Kapatılması istendiğinde, Python yorumlayıcısı, modüller ve çeşitli kritik iç yapılar gibi tahsis edilen tüm kaynakları kademeeli olarak serbest bıraktığı özel bir aşamaya girer. Ayrıca *garbage collector* için birkaç çağrı yapar. Bu, kullanıcı tanımlı yıkıcılarda veya zayıf referans geri aramalarında kodun yürütülmesini tetikleyebilir. Kapatma aşamasında yürütülen kod, dayandığı kaynaklar artık çalışmaya bilinceinden çeşitli istisnalarla karşılaşabilir (yayın örnekler kütüphane modülleri veya uyarı makineleridir).

Yorumlayıcının kapatılmasının ana nedeni, `__main__` modülüne veya çalıştırılan betiğin yürütmemeyi bitirmiş olmasıdır.

yinelenebilir

An object capable of returning its members one at a time. Examples of iterables include all sequence types (such as `list`, `str`, and `tuple`) and some non-sequence types like `dict`, [file objects](#), and objects of any classes you define with an `__iter__()` method or with a `__getitem__()` method that implements [sequence](#) semantics.

Iterables can be used in a `for` loop and in many other places where a sequence is needed (`zip()`, `map()`, ...). When an iterable object is passed as an argument to the built-in function `iter()`, it returns an iterator for the object. This iterator is good for one pass over the set of values. When using iterables, it is usually not necessary to call `iter()` or deal with iterator objects yourself. The `for` statement does that automatically for you, creating a temporary unnamed variable to hold the iterator for the duration of the loop. See also [iterator](#), [sequence](#), and [generator](#).

yineleyici

An object representing a stream of data. Repeated calls to the iterator's `__next__()` method (or passing it to the built-in function `next()`) return successive items in the stream. When no more data are available a `StopIteration` exception is raised instead. At this point, the iterator object is exhausted and any further calls to its `__next__()` method just raise `StopIteration` again. Iterators are required to have an `__iter__()` method that returns the iterator object itself so every iterator is also iterable and may be used in most places where other iterables are accepted. One notable exception is code which attempts multiple iteration passes. A container object (such as a `list`) produces a fresh new iterator each time you pass it to the `iter()` function or use it in a `for` loop. Attempting this with an iterator will just return the same exhausted iterator object used in the previous iteration pass, making it appear like an empty container.

Daha fazla bilgi typeiter içinde bulunabilir.

C_{Python} uygulama ayrıntısı: CPython does not consistently apply the requirement that an iterator define `__iter__()`. And also please note that the free-threading CPython does not guarantee the thread-safety of iterator operations.

anahtar işlev

Anahtar işlevi veya harmanlama işlevi, sıralama veya sıralama için kullanılan bir değeri döndüren bir çağrılabılır. Örneğin, `locale.strxfrm()`, yerel ayara özgü sıralama kurallarının farkında olan bir sıralama anahtarı üretmek için kullanılır.

Python'daki bir dizi araç, öğelerin nasıl sıralandığını veya gruplandırıldığını kontrol etmek için temel işlevleri kabul eder. Bunlar `min()`, `max()`, `sorted()`, `list.sort()`, `heapq.merge()`, `heapq.nsmallest()`, `heapq.nlargest()` ve `itertools.groupby()`.

Bir tuş fonksiyonu oluşturmanın birkaç yolu vardır. Örneğin, `str.lower()` yöntemi, büyük/küçük harfe duyarlı sıralamalar için bir anahtar fonksiyonu işlevi görebilir. Alternatif olarak, `lambda r: (r[0], r[2])` gibi bir `lambda` ifadesinden bir anahtar işlevi oluşturulabilir. Ayrıca, `attrgetter()`, `itemgetter()` ve `methodcaller()` fonksiyonları üç anahtar fonksiyon kurucularıdır. Anahtar işlevlerin nasıl oluşturulacağı ve kullanılacağına ilişkin örnekler için Sorting HOW TO bölümünü bakın.

anahtar kelime argümanı

Bakınız [argument](#).

lambda

İşlev çağrılığında değerlendirilen tek bir [expression](#) ‘dan oluşan anonim bir satır içi işlev. Bir lambda işlevi oluşturmak için sözdizimi `lambda [parametreler]: ifade` şeklinde dir

LBYL

Ziplamadan önce Bak. Bu kodlama stili, arama veya arama yapmadan önce ön koşulları açıkça test eder. Bu stil, [EAFP](#) yaklaşımıyla çelişir ve birçok `if` ifadesinin varlığı ile karakterize edilir.

Çok iş parçacıklı bir ortamda, LBYL yaklaşımı “bakan” ve “sıçrayan” arasında bir yarış koşulu getirme riskini taşıyabilir. Örneğin, `if key in mapping: return mapping[key]` kodu, testten sonra, ancak aramadan önce başka bir iş parçacığı *eslemeden* `key` kaldırırsa başarısız olabilir. Bu sorun, kilitlerle veya EAFP yaklaşımı kullanılarak çözülebilir.

liste

A built-in Python [sequence](#). Despite its name it is more akin to an array in other languages than to a linked list since access to elements is $O(1)$.

liste anlama

Bir dizideki öğelerin tümünü veya bir kısmını işlemenin ve sonuçları içeren bir liste döndürmenin kompakt bir yolu. `sonuç = ['{:#04x}'.format(x) for x in range(256) if x % 2 == 0]`, dizinde çift onaltılık sayılar (0x..) içeren bir dizi listesi oluşturur. 0 ile 255 arasındadır. `if` yan tümcesi isteğe bağlıdır. Atlansrsa, “aralık(256)” içindeki tüm öğeler işlenir.

yükleyici

An object that loads a module. It must define a method named `load_module()`. A loader is typically returned by a [finder](#). See also:

- [finders-and-loaders](#)
- [importlib.abc.Loader](#)
- [PEP 302](#)

yerel kodlama

Unix’ta, `LC_CTYPE` yerel ayarının kodlamasıdır. `locale.setlocale(locale.LC_CTYPE, new_locale)` ile ayarlanabilir.

Windows’ta bu, ANSI kod sayfasıdır (ör. "cp1252").

Android ve VxWorks’ta Python, yerel kodlama olarak "utf-8" kullanır.

`locale.getencoding()` can be used to get the locale encoding.

Ayrıca [filesystem encoding and error handler](#) ‘ne bakın.

sihirli yöntem

[special method](#) için gayri resmi bir eşanalamlı.

haritalama

Keyfi anahtar aramalarını destekleyen ve Mapping veya MutableMapping collections-abstract-base-classes içinde belirtilen yöntemleri uygulayan bir kapsayıcı nesnesi. Örnekler arasında `dict`, `collections.defaultdict`, `collections.OrderedDict` ve `collections.Counter` sayılabilir.

meta yol bulucu

Bir [finder](#), `sys.meta_path` aramasıyla döndürülür. Meta yol bulucular, [yol girişi bulucuları](#) ile ilişkilidir, ancak onlardan farklıdır.

Meta yol bulucuların uyguladığı yöntemler için [importlib.abc.MetaPathFinder](#) bölümüne bakın.

metasınıf

Bir sınıfın sınıfı. Sınıf tanımları, bir sınıf adı, bir sınıf sözlüğü ve temel sınıfların bir listesini oluşturur. Metasınıf, bu üç argümanı almakta ve sınıfı oluşturmaktan sorumludur. Çoğu nesne yönelimli programlama dili, varsayılan bir uygulama sağlar. Python’u özel yapan şey, özel metasınıflar oluşturmanın mümkün olmasıdır. Çoğu kullanıcı bu araca hiçbir zaman ihtiyaç duymaz, ancak ihtiyaç duyulduğunda, metasınıflar güçlü ve zarif

çözümler sağlayabilir. Nitelik erişimini günlüğe kaydetmek, iş parçacığı güvenliği eklemek, nesne oluşturmayı izlemek, tekilleri uygulamak ve diğer birçok görev için kullanılmışlardır.

Daha fazla bilgi metaclasses içinde bulunabilir.

metot

Bir sınıf gövdesi içinde tanımlanan bir işlev. Bu sınıfın bir örneğinin özniteliği olarak çağrılsa, yöntem örnek nesnesini ilk *argument* (genellikle `self` olarak adlandırılır) olarak alır. Bkz. [function](#) ve [nested scope](#).

metot kalite sıralaması

Method Resolution Order is the order in which base classes are searched for a member during lookup. See [python_2.3_mro](#) for details of the algorithm used by the Python interpreter since the 2.3 release.

modül

Python kodunun kuruluş birimi olarak hizmet eden bir nesne. Modüller, rastgele Python nesneleri içeren bir ad alanına sahiptir. Modüller, [importing](#) işlemiyle Python'a yüklenir.

Ayrıca bakınız [package](#).

modül özelliği

Bir modülü yüklemek için kullanılan içe aktarmayla ilgili bilgileri içeren bir ad alanı. Bir `importlib.machinery.ModuleSpec` örneği.

See also [module-specs](#).

MRO

Bakınız [metot çözüm sırası](#).

değiştirilebilir

Değiştirilebilir (mutable) nesneler değerlerini değiştirebilir ancak `id`lerini koruyabilirler. Ayrıca bkz. [immutable](#).

adlandırılmış demet

“named tuple” terimi, demetten miras alan ve dizinlenebilir öğelerine de adlandırılmış nitelikler kullanılarak erişilebilen herhangi bir tür veya sınıf için geçerlidir. Tür veya sınıfın başka özellikleri de olabilir.

Ceşitli yerleşik türler, `time.localtime()` ve `os.stat()` tarafından döndürülen değerler de dahil olmak üzere, tanımlama grupları olarak adlandırılır. Başka bir örnek `sys.float_info`:

```
>>> sys.float_info[1]                      # indexed access
1024
>>> sys.float_info.max_exp               # named field access
1024
>>> isinstance(sys.float_info, tuple)    # kind of tuple
True
```

Some named tuples are built-in types (such as the above examples). Alternatively, a named tuple can be created from a regular class definition that inherits from `tuple` and that defines named fields. Such a class can be written by hand, or it can be created by inheriting `typing.NamedTuple`, or with the factory function `collections.namedtuple()`. The latter techniques also add some extra methods that may not be found in hand-written or built-in named tuples.

ad alanı

Değişkenin saklandığı yer. Ad alanları sözlükler olarak uygulanır. Nesnelerde (yöntemlerde) yerel, genel ve yerleşik ad alanlarının yanı sıra iç içe ad alanları vardır. Ad alanları, adlandırma çakışmalarını önleyerek modülerliği destekler. Örneğin, `builtins.open` ve `os.open()` işlevleri ad alanlarıyla ayırt edilir. Ad alanları, hangi modülün bir işlevi uyguladığını açıkça belirterek okunabilirliğe ve sürdürilebilirliğe de yardımcı olur. Örneğin, `random.seed()` veya `itertools.islice()` yazmak, bu işlevlerin sırasıyla `random` ve `itertools` modülleri tarafından uygulandığını açıkça gösterir.

ad alanı paketi

A [PEP 420 package](#), yalnızca alt paketler için bir kap olarak hizmet eder. Ad alanı paketlerinin hiçbir fiziksel temsili olmayabilir ve `__init__.py` dosyası olmadığından özellikle [regular package](#) gibi değildirler.

Ayrıca bkz. [module](#).

İç içe kapsam

Kapsamlı bir tanımdaki bir değişkene atfta bulunma yeteneği. Örneğin, başka bir fonksiyonun içinde tanımlanan bir fonksiyon, dış fonksiyondaki değişkenlere atfta bulunabilir. İç içe kapsamların varsayılan olarak yalnızca başvuru için çalıştığını ve atama için çalışmadığını unutmayın. Yerel değişkenler en içteki kapsamda hem okur hem de yazar. Benzer şekilde, global değişkenler global ad alanını okur ve yazar. `nonlocal`, dış kapsamlara yazmaya izin verir.

yeni stil sınıf

Old name for the flavor of classes now used for all class objects. In earlier Python versions, only new-style classes could use Python's newer, versatile features like `__slots__`, descriptors, properties, `__getattribute__()`, class methods, and static methods.

obje

Durum (öznitelikler veya değer) ve tanımlanmış davranış (yöntemler) içeren herhangi bir veri. Ayrıca herhangi bir [yeni tarz sınıfın](#) nihai temel sınıfı.

optimized scope

A scope where target local variable names are reliably known to the compiler when the code is compiled, allowing optimization of read and write access to these names. The local namespaces for functions, generators, coroutines, comprehensions, and generator expressions are optimized in this fashion. Note: most interpreter optimizations are applied to all scopes, only those relying on a known set of local and nonlocal variable names are restricted to optimized scopes.

paket

Alt modüller veya yinelemeli olarak alt paketler içerebilen bir Python [module](#). Teknik olarak bir paket, `__path__` özniteligi sahip bir Python modülüdür.

Ayrıca bkz. [regular package](#) ve [namespace package](#).

parametre

Bir [function](#) (veya yöntem) tanımında, işlevin kabul edebileceği bir [argument](#) (veya bazı durumlarda, argümanlar) belirten adlandırılmış bir varlık. Beş çeşit parametre vardır:

- *positional-or-keyword*: *pozisyonel* veya bir *keyword argümanı* olarak iletilebilen bir argüman belirtir. Bu, varsayılan parametre türüdür, örneğin aşağıdakilerde *foo* ve *bar*:

```
def func(foo, bar=None): ...
```

- *positional-only*: yalnızca konuma göre sağlanabilen bir argüman belirtir. Yalnızca konumsal parametreler, onlardan sonra fonksiyon tanımının parametre listesine bir / karakteri eklenerek tanımlanabilir, örneğin aşağıdakilerde *posonly1* ve *posonly2*:

```
def func(posonly1, posonly2, /, positional_or_keyword): ...
```

- *keyword-only*: sadece anahtar kelime ile sağlanabilen bir argüman belirtir. Yalnızca anahtar kelime (*keyword-only*) parametreleri, onlardan önceki fonksiyon tanımının parametre listesine tek bir değişken konumlu parametre veya çiplak * dahil edilerek tanımlanabilir, örneğin aşağıdakilerde *kw_only1* ve *kw_only2*:

```
def func(arg, *, kw_only1, kw_only2): ...
```

- *var-positional*: keyfi bir pozisyonel argüman dizisinin sağlanabileceğini belirtir (diğer parametreler tarafından zaten kabul edilmiş herhangi bir konumsal argümana ek olarak). Böyle bir parametre, parametre adının başına * eklenerek tanımlanabilir, örneğin aşağıdakilerde *args*:

```
def func(*args, **kwargs): ...
```

- *var-keyword*: keyfi olarak birçok anahtar kelime argümanının sağlanabileceğini belirtir (diğer parametreler tarafından zaten kabul edilen herhangi bir anahtar kelime argümanına ek olarak). Böyle bir parametre, parametre adının başına **, örneğin yukarıdaki örnekte *kwargs* eklenerek tanımlanabilir.

Parametreler, hem isteğe bağlı hem de gerekli argümanları ve ayrıca bazı isteğe bağlı bağımsız değişkenler için varsayılan değerleri belirtebilir.

Ayrıca bkz. [argüman](#), argümanlar ve parametreler arasındaki fark, `inspect.Parameter`, `function` ve [PEP 362](#).

yol girişi

path based finder içe aktarma modüllerini bulmak için başvurduğu [import path](#) üzerindeki tek bir konum.

yol girişi bulucu

Bir [finder](#) `sys.path_hooks` (yani bir [yol giriş kancası](#)) üzerinde bir çağrılabilebilir tarafından döndürülür ve [path entry](#) verilen modüllerin nasıl bulunacağını bilir.

Yol girişi bulucularının uyguladığı yöntemler için `importlib.abc.PathEntryFinder` bölümune bakın.

yol giriş kancası

A callable on the `sys.path_hooks` list which returns a [path entry finder](#) if it knows how to find modules on a specific [path entry](#).

yol tabanlı bulucu

Modüller için bir [import path](#) arayan varsayılan [meta yol bulucularından](#) biri.

yol benzeri nesne

Bir dosya sistemi yolunu temsil eden bir nesne. Yol benzeri bir nesne, bir yolu temsil eden bir `str` veya `bytes` nesnesi veya `os.PathLike` protokolünü uygulayan bir nesnedir. `os.PathLike` protokolünü destekleyen bir nesne, `os.fspath()` işlevi çağrılarak bir `str` veya `bytes` dosya sistemi yoluna dönüştürülebilir; `os.fsdecode()` ve `os.fsencode()`, bunun yerine sırasıyla `str` veya `bytes` sonucunu garanti etmek için kullanılabilir. [PEP 519](#) tarafından tanıtıldı.

PEP

Python Geliştirme Önerisi. PEP, Python topluluğuna bilgi sağlayan veya Python veya süreçleri ya da ortamı için yeni bir özelliği açıklayan bir tasarımcı belgesidir. PEP'ler, önerilen özellikler için özlü bir teknik şartname ve bir gereklilik sağlamalıdır.

PEP'lerin, önemli yeni özellikler önermek, bir sorun hakkında topluluk girdisi toplamak ve Python'a giren tasarım kararlarını belgelemek için birincil mekanizmalar olması amaçlanmıştır. PEP yazarı, topluluk içinde fikir birliği oluşturmaktan ve muhalif görüşleri belgelemekten sorumludur.

Bakınız [PEP 1](#).

kısım

[PEP 420](#) içinde tanımlandığı gibi, bir ad alanı paketine katkıda bulunan tek bir dizindeki (muhtemelen bir zip dosyasında depolanan) bir dizi dosya.

konumsal argüman

Bakınız [argument](#).

geçici API

Geçici bir API, standart kitaplığın geriye dönük uyumluluk garantilerinden kasıtlı olarak hariç tutulan bir API'dir. Bu tür arayüzlerde büyük değişiklikler beklenmese de, geçici olarak işaretlendikleri sürece, çekirdek geliştiriciler tarafından gerekliliği takdirde geriye dönük uyumsuz değişiklikler (arayüzün kaldırılmasına kadar ve buna kadar) meydana gelebilir. Bu tür değişiklikler karşısız yapılmayacaktır - bunlar yalnızca API'nin eklenmesinden önce gözden kaçan ciddi temel kusurlar ortaya çıkarsa gerçekleşecektir.

Geçici API'ler için bile, geriye dönük uyumsuz değişiklikler "son çare çözümü" olarak görülür - tanımlanan herhangi bir soruna geriye dönük uyumlu bir çözüm bulmak için her türlü girişimde bulunulacaktır.

Bu süreç, standart kitaplığın, uzun süreler boyunca sorunlu tasarım hatalarına kilitlenmeden zaman içinde gelişmeye devam etmesini sağlar. Daha fazla ayrıntı için bkz. [PEP 411](#).

geçici paket

Bakınız [provisional API](#).

Python 3000

Python 3.x sürüm satırının takma adı (uzun zaman önce sürüm 3'ün piyasaya sürülmesi uzak bir gelecekte olduğu zaman ortaya çıktı.) Bu aynı zamanda "Py3k" olarak da kısaltılır.

Pythonic

Diger dillerde ortak kavramları kullanarak kod uygulamak yerine Python dilinin en yaygın deyimlerini yakın- dan takip eden bir fikir veya kod parçası. Örneğin, Python'da yaygın bir deyim, bir `for` ifadesi kullanarak

yinelenebilir bir ögenin tüm öğeleri üzerinde döngü oluşturmaktır. Diğer birçok dilde bu tür bir yapı yoktur, bu nedenle Python'a aşina olmayan kişiler bazen bunun yerine sayısal bir sayaç kullanır:

```
for i in range(len(food)):  
    print(food[i])
```

Temizleyicinin aksine, Pythonic yöntemi:

```
for piece in food:  
    print(piece)
```

nitelikli isim

PEP 3155 içinde tanımlandığı gibi, bir modülün genel kapsamından o modülde tanımlanan bir sınıfı, işlev veya yönteme giden “yolu” gösteren noktalı ad. Üst düzey işlevler ve sınıflar için nitelikli ad, nesnenin adıyla aynıdır:

```
>>> class C:  
...     class D:  
...         def meth(self):  
...             pass  
...  
>>> C.__qualname__  
'C'  
>>> C.D.__qualname__  
'C.D'  
>>> C.D.meth.__qualname__  
'C.D.meth'
```

Modüllere atıfta bulunmak için kullanıldığında, *tam nitelenmiş ad*, herhangi bir üst paket de dahil olmak üzere, modüle giden tüm noktalı yol anlamına gelir, örn. `email.mime.text`:

```
>>> import email.mime.text  
>>> email.mime.text.__name__  
'email.mime.text'
```

referans sayısı

The number of references to an object. When the reference count of an object drops to zero, it is deallocated. Some objects are *immortal* and have reference counts that are never modified, and therefore the objects are never deallocated. Reference counting is generally not visible to Python code, but it is a key element of the *C*Python implementation. Programmers can call the `sys.getrefcount()` function to return the reference count for a particular object.

sürekli paketleme

`__init__.py` dosyası içeren bir dizin gibi geleneksel bir *package*.

Ayrıca bkz. *ad alanı paketi*.

REPL

An acronym for the “read–eval–print loop”, another name for the *interactive* interpreter shell.

slots

Örnek öznitelikleri için önceden yer bildirerek ve örnek sözlüklerini ortadan kaldırarak bellekten tasarruf sağlayan bir sınıf içindeki bildirim. Popüler olmasına rağmen, tekniğin doğru olması biraz zor ve en iyi, bellek açısından kritik bir uygulamada çok sayıda örneğin bulunduğu nadir durumlar için ayrılmıştır.

dizi

An *iterable* which supports efficient element access using integer indices via the `__getitem__()` special method and defines a `__len__()` method that returns the length of the sequence. Some built-in sequence types are `list`, `str`, `tuple`, and `bytes`. Note that `dict` also supports `__getitem__()` and `__len__()`, but is considered a mapping rather than a sequence because the lookups use arbitrary *hashable* keys rather than integers.

The `collections.abc.Sequence` abstract base class defines a much richer interface that goes beyond just `__getitem__()` and `__len__()`, adding `count()`, `index()`, `__contains__()`, and `__reversed__()`. Types that implement this expanded interface can be registered explicitly using `register()`. For more documentation on sequence methods generally, see Common Sequence Operations.

anlamak

Öğelerin tümünü veya bir kısmını yinelenebilir bir şekilde işlemenin ve sonuçlarla birlikte bir küme döndürmenin kompakt bir yolu. `results = {c for c in 'abracadabra' if c not in 'abc'}, {'r', 'd'}` dizelerini oluşturur. Bakınz comprehensions.

tek sevk

Uygulamanın tek bir argüman türüne göre seçildiği bir *generic function* gönderimi biçimini.

parçalamak

Genellikle bir *sequence* 'nin bir bölümünü içeren bir nesne. Bir dilim, örneğin `variable_name[1:3:5]` 'de olduğu gibi, birkaç tane verildiğinde, sayılar arasında iki nokta üst üste koyarak, `[]` alt simge gösterimi kullanılarak oluşturulur. Köşeli ayraç (alt simge) gösterimi, dahili olarak `slice` nesnelerini kullanır.

soft deprecated

A soft deprecated API should not be used in new code, but it is safe for already existing code to use it. The API remains documented and tested, but will not be enhanced further.

Soft deprecation, unlike normal deprecation, does not plan on removing the API and will not emit warnings.

See PEP 387: Soft Deprecation.

özel metod

Toplama gibi bir tür üzerinde belirli bir işlemi yürütmek için Python tarafından örtük olarak çağrılan bir yöntem. Bu tür yöntemlerin çift alt çizgi ile başlayan ve biten adları vardır. Özel yöntemler `specialnames` içinde belgelenmiştir.

ifade (değer döndürmez)

Bir ifade, bir paketin parçasıdır (kod “bloğu”). Bir ifade, bir *expression* veya `if`, `while` veya `for` gibi bir anahtar kelimeye sahip birkaç yapıdan biridir.

static type checker

An external tool that reads Python code and analyzes it, looking for issues such as incorrect types. See also `type hints` and the `typing` module.

güçlü referans

In Python's C API, a strong reference is a reference to an object which is owned by the code holding the reference. The strong reference is taken by calling `Py_INCREF()` when the reference is created and released with `Py_DECREF()` when the reference is deleted.

`Py_NewRef()` fonksiyonu, bir nesneye güçlü bir başvuru oluşturmak için kullanılabilir. Genellikle `Py_DECREF()` fonksiyonu, bir referansın sızmasını önlemek için güçlü referans kapsamından çıkmadan önce güçlü referansta çağrılmalıdır.

Ayrıca bkz. *ödiinç alınan referans*.

yazı çözümleme

Python'da bir dize, bir Unicode kod noktaları dizisidir (`U+0000–U+10FFFF` aralığında). Bir dizeyi depolamak veya aktarmak için, bir bayt dizisi olarak seri hale getirilmesi gereklidir.

Bir dizeyi bir bayt dizisi halinde seri hale getirmek “kodlama (encoding)” olarak bilinir ve dizeyi bayt dizisinden yeniden oluşturmak “kod çözme (decoding)” olarak bilinir.

Toplu olarak “metin kodlamaları” olarak adlandırılan çeşitli farklı metin serileştirme kodekleri vardır.

yazı dosyası

A `file object` `str` nesnelerini okuyabilir ve yazabilir. Çoğu zaman, bir metin dosyası asılarda bir bayt yönelimli veri akışına erişir ve otomatik olarak *text encoding* işler. Metin dosyalarına örnek olarak metin modunda açılan dosyalar ('`r`' veya '`w`'), `sys.stdin`, `sys.stdout` ve `io.StringIO` örnekleri verilebilir.

Ayrıca *ikili dosyaları* okuyabilen ve yazabilen bir dosya nesnesi için *bayt benzeri nesnelere* bakın.

üç tırnaklı dize

Üç tırnak işaretçi ("") veya kesme işaretçi ('') ile sınırlanan bir dize. Tek tırnaklı dizelerde bulunmayan herhangi bir işlevsellik sağlanmasalar da, birkaç nedenden dolayı faydalıdır. Bir dizeye çıkışsız tek ve çift tırnak eklemeniz gereklidir ve bunlar, devam karakterini kullanmadan birden çok satırda kullanılabilir, bu da onları özellikle belge dizileri yazarken kullanışlı hale getirir.

tip

The type of a Python object determines what kind of object it is; every object has a type. An object's type is accessible as its `__class__` attribute or can be retrieved with `type(obj)`.

tip takma adı

Bir tanımlayıcıya tür atanarak oluşturulan, bir tür için eş anlamlı.

Tür takma adları, *tür ipuçlarını* basitleştirmek için kullanışlıdır. Örneğin:

```
def remove_gray_shades(  
    colors: list[tuple[int, int, int]]) -> list[tuple[int, int, int]]:  
    pass
```

bu şekilde daha okunaklı hale getirilebilir:

```
Color = tuple[int, int, int]  
  
def remove_gray_shades(colors: list[Color]) -> list[Color]:  
    pass
```

Bu işlevi açıklayan `typing` ve [PEP 484](#) bölmelerine bakın.

tür ipucu

Bir değişken, bir sınıf niteliği veya bir işlev parametresi veya dönüş değeri için beklenen türü belirten bir *ek açıklama*.

Type hints are optional and are not enforced by Python but they are useful to *static type checkers*. They can also aid IDEs with code completion and refactoring.

Genel değişkenlerin, sınıf özniteliklerinin ve işlevlerin tür ipuçlarına, yerel değişkenlere değil, `typing.get_type_hints()` kullanılarak erişilebilir.

Bu işlevi açıklayan `typing` ve [PEP 484](#) bölmelerine bakın.

evrensel yeni satırlar

Aşağıdakilerin tümünün bir satırın bitisi olarak kabul edildiği metin akışlarını yorumlammanın bir yolu: Unix satır sonu kuralı '\n', Windows kuralı '\r\n', ve eski Macintosh kuralı '\r'. Ek bir kullanım için [PEP 278](#) ve [PEP 3116](#) ve ayrıca `bytes.splitlines()` bakın.

değişken açıklama

Bir değişkenin veya bir sınıf özniteliğinin *ek açıklaması*.

Bir değişkene veya sınıf niteliğine açıklama eklerken atama isteği bağlıdır:

```
class C:  
    field: 'annotation'
```

Değişken açıklamaları genellikle *tür ipuçları* için kullanılır: örneğin, bu değişkenin `int` değerlerini alması beklenir:

```
count: int = 0
```

Değişken açıklama sözdizimi `annassign` bölümünde açıklanmıştır.

Bu işlevi açıklayan; *function annotation*, [PEP 484](#) ve [PEP 526](#) bölmelerine bakın. Ek açıklamalarla çalışmaya ilişkin en iyi uygulamalar için ayrıca bkz. `annotations-howto`.

sanal ortam

Python kullanıcılarının ve uygulamalarının, aynı sistem üzerinde çalışan diğer Python uygulamalarının davranışına müdahale etmeden Python dağıtım paketlerini kurmasına ve yükseltmesine olanak tanıyan, işbirliği içinde yalıtılmış bir çalışma zamanı ortamı.

Ayrıca bakınız `venv`.

sanal makine

Tamamen yazılımla tanımlanmış bir bilgisayar. Python'un sanal makinesi, bayt kodu derleyicisi tarafından yayınlanan *bytecode* 'u çalıştırır.

Python'un Zen'i

Dili anlamaya ve kullanmaya yardımcı olan Python tasarım ilkeleri ve felsefelerinin listesi. Liste, etkileşimli komut isteminde “`import this`” yazarak bulunabilir.

Bu dokümanlar hakkında

Bu dokümanlar, Python dokümanları için özel olarak yazılmış bir doküman işlemcisi olan [Sphinx](#) tarafından `reStructuredText` kaynaklarından oluşturulur.

Dokümantasyonun ve araç zincirinin geliştirilmesi, tipki Python'un kendisi gibi tamamen gönüllü bir çabadır. Katkıda bulunmak istiyorsanız, nasıl yapacağınızla ilişkin bilgi için lütfen `reporting-bugs` sayfasına göz atın. Yeni gönüllülere her zaman açıgız!

Destekleri için teşekkürler:

- Fred L. Drake, Jr., orijinal Python dokümantasyon araç setinin yaratıcısı ve içeriğin çoğunu yazarı;
- [Docutils](#) projesi, `reStructuredText` ve `Docutils` paketini oluşturdukları için;
- Fredrik Lundh, [Sphinx](#)'in pek çok iyi fikir edindiği Alternatif Python Referansı projesi için.

B.1 Python Dokümantasyonuna Katkıda Bulunanlar

Birçok kişi Python diline, Python standart kütüphaneline ve Python dokümantasyonuna katkıda bulunmuştur. Katkıda bulunanların kısmi bir listesi için Python kaynak dağıtımında [Misc/ACKS](#) dosyasına bakın.

Python topluluğunun girdileri ve katkıları sayesinde böyle harika bir dokümantasyona sahibiz – Teşekkürler!

Tarihçe ve Lisans

C.1 Yazılımın tarihçesi

Python, 1990'ların başında Guido van Rossum tarafından Hollanda'da Stichting Mathematisch Centrum'da (CWI, bkz. <https://www.cwi.nl/>) ABC adlı bir dilin devamı olarak oluşturuldu. Guido, diğerlerinin oldukça katkısı olmasına rağmen, Python'un ana yazarı olmaya devam ediyor.

1995'te Guido, yazılımın çeşitli sürümlerini yayınladığı Virginia, Reston'daki Ulusal Araştırma Girişimleri Kuru mu'nda (CNRI, bkz. <https://www.cnri.reston.va.us/>) Python üzerindeki çalışmalarına devam etti.

Mayıs 2000'de, Guido ve Python çekirdek geliştirme ekibi, BeOpen PythonLabs ekibini oluşturmak için BeOpen.com'a taşındı. Aynı yılın Ekim ayında PythonLabs ekibi Digital Creations'a (şimdi Zope Corporation; bkz. <https://www.zope.org/>) taşındı. 2001 yılında, Python Yazılım Vakfı (PSF, bkz. <https://www.python.org/psf/>) kuruldu, özellikle Python ile ilgili Fikri Mülkiyete sahip olmak için oluşturulmuş kar amacı gütmeyen bir organizasyon. Zope Corporation, PSF'nin sponsor üyesidir.

Tüm Python sürümleri Açık Kaynaklıdır (Açık Kaynak Tanımı için bkz. <https://opensource.org/>). Tarihsel olarak, tümü olmasa da çoğu Python sürümleri de GPL uyumluyu du; aşağıdaki tablo çeşitli yayınları özetlemektedir.

Yayın	Şundan türedi:	Yıl	Sahibi	GPL uyumlu mu?
0.9.0'dan 1.2'ye	n/a	1991-1995	CWI	evet
1.3 'dan 1.5.2'ye	1.2	1995-1999	CNRI	evet
1.6	1.5.2	2000	CNRI	hayır
2.0	1.6	2000	BeOpen.com	hayır
1.6.1	1.6	2001	CNRI	hayır
2.1	2.0+1.6.1	2001	PSF	hayır
2.0.1	2.0+1.6.1	2001	PSF	evet
2.1.1	2.1+2.0.1	2001	PSF	evet
2.1.2	2.1.1	2002	PSF	evet
2.1.3	2.1.2	2002	PSF	evet
2.2 ve üzeri	2.1.1	2001-Günümüz	PSF	evet

i Not

GPL uyumlu olması, Python'u GPL kapsamında dağıttığımız anlamına gelmez. Tüm Python lisansları, GPL'den farklı olarak, değişikliklerinizi açık kaynak yapmadan değiştirilmiş bir sürümü dağıtmانıza izin verir. GPL

uyumlu lisanslar, Python'u GPL kapsamında yayınlanan diğer yazılımlarla birleştirmeyi mümkün kılar; diğerleri yapmaz.

Bu yayınları mümkün kılmak için Guido'nun yönetimi altında çalışan birçok gönüllüye teşekkürler.

C.2 Python'a erişmek veya başka bir şekilde kullanmak için şartlar ve koşullar

Python yazılımı ve belgeleri *PSF Lisans Anlaşması* kapsamında lisanslanmıştır.

Python 3.8.6'dan başlayarak, belgelerdeki örnekler, tarifler ve diğer kodlar, PSF Lisans Sözleşmesi ve *Zero-Clause BSD license* kapsamında çift lisanslıdır.

Python'a dahil edilen bazı yazılımlar farklı lisanslar altındadır. Lisanslar, bu lisansa giren kodla listelenir. Bu lisansların eksik listesi için bkz. *Tüzel Yazılımlar İçin Lisanslar ve Onaylar*.

C.2.1 PYTHON İÇİN PSF LİSANS ANLAŞMASI 3.13.0

1. This LICENSE AGREEMENT is between the Python Software Foundation ("PSF"), and the Individual or Organization ("Licensee") accessing and otherwise using Python 3.13.0 software in source or binary form and its associated documentation.
2. Subject to the terms and conditions of this License Agreement, PSF hereby grants Licensee a nonexclusive, royalty-free, world-wide license to reproduce, analyze, test, perform and/or display publicly, prepare derivative works, distribute, and otherwise use Python 3.13.0 alone or in any derivative version, provided, however, that PSF's License Agreement and PSF's notice of copyright, i.e., "Copyright © 2001-2024 Python Software Foundation; All Rights Reserved" are retained in Python 3.13.0 alone or in any derivative version prepared by Licensee.
3. In the event Licensee prepares a derivative work that is based on or incorporates Python 3.13.0 or any part thereof, and wants to make the derivative work available to others as provided herein, then Licensee hereby agrees to include in any such work a brief summary of the changes made to Python 3.13.0.
4. PSF is making Python 3.13.0 available to Licensee on an "AS IS" basis. PSF MAKES NO REPRESENTATIONS OR WARRANTIES, EXPRESS OR IMPLIED. BY WAY OF EXAMPLE, BUT NOT LIMITATION, PSF MAKES NO AND DISCLAIMS ANY REPRESENTATION OR WARRANTY OF MERCHANTABILITY OR FITNESS FOR ANY PARTICULAR PURPOSE OR THAT THE USE OF PYTHON 3.13.0 WILL NOT INFRINGE ANY THIRD PARTY RIGHTS.
5. PSF SHALL NOT BE LIABLE TO LICENSEE OR ANY OTHER USERS OF PYTHON 3.13.0 FOR ANY INCIDENTAL, SPECIAL, OR CONSEQUENTIAL DAMAGES OR LOSS AS A RESULT OF MODIFYING, DISTRIBUTING, OR OTHERWISE USING PYTHON 3.13.0, OR ANY DERIVATIVE THEREOF, EVEN IF ADVISED OF THE POSSIBILITY THEREOF.
6. This License Agreement will automatically terminate upon a material breach of its terms and conditions.
7. Nothing in this License Agreement shall be deemed to create any relationship of agency, partnership, or joint venture between PSF and Licensee. This License Agreement does not grant permission to use PSF trademarks or trade name in a trademark sense to endorse or promote products or services of Licensee, or any third party.

8. By copying, installing or otherwise using Python 3.13.0, Licensee agrees to be bound by the terms and conditions of this License Agreement.

C.2.2 PYTHON 2.0 İÇİN BEOPEN.COM LİSANS SÖZLEŞMESİ

BEOPEN PYTHON AÇIK KAYNAK LİSANS SÖZLEŞMESİ SÜRÜM 1

1. This LICENSE AGREEMENT is between BeOpen.com ("BeOpen"), having an office at 160 Saratoga Avenue, Santa Clara, CA 95051, and the Individual or Organization ("Licensee") accessing and otherwise using this software in source or binary form and its associated documentation ("the Software").
2. Subject to the terms and conditions of this BeOpen Python License Agreement, BeOpen hereby grants Licensee a non-exclusive, royalty-free, world-wide license to reproduce, analyze, test, perform and/or display publicly, prepare derivative works, distribute, and otherwise use the Software alone or in any derivative version, provided, however, that the BeOpen Python License is retained in the Software, alone or in any derivative version prepared by Licensee.
3. BeOpen is making the Software available to Licensee on an "AS IS" basis. BEOPEN MAKES NO REPRESENTATIONS OR WARRANTIES, EXPRESS OR IMPLIED. BY WAY OF EXAMPLE, BUT NOT LIMITATION, BEOPEN MAKES NO AND DISCLAIMS ANY REPRESENTATION OR WARRANTY OF MERCHANTABILITY OR FITNESS FOR ANY PARTICULAR PURPOSE OR THAT THE USE OF THE SOFTWARE WILL NOT INFRINGE ANY THIRD PARTY RIGHTS.
4. BEOPEN SHALL NOT BE LIABLE TO LICENSEE OR ANY OTHER USERS OF THE SOFTWARE FOR ANY INCIDENTAL, SPECIAL, OR CONSEQUENTIAL DAMAGES OR LOSS AS A RESULT OF USING, MODIFYING OR DISTRIBUTING THE SOFTWARE, OR ANY DERIVATIVE THEREOF, EVEN IF ADVISED OF THE POSSIBILITY THEREOF.
5. This License Agreement will automatically terminate upon a material breach of its terms and conditions.
6. This License Agreement shall be governed by and interpreted in all respects by the law of the State of California, excluding conflict of law provisions. Nothing in this License Agreement shall be deemed to create any relationship of agency, partnership, or joint venture between BeOpen and Licensee. This License Agreement does not grant permission to use BeOpen trademarks or trade names in a trademark sense to endorse or promote products or services of Licensee, or any third party. As an exception, the "BeOpen Python" logos available at <http://www.pythonglabs.com/logos.html> may be used according to the permissions granted on that web page.
7. By copying, installing or otherwise using the software, Licensee agrees to be bound by the terms and conditions of this License Agreement.

C.2.3 PYTHON 1.6.1 İÇİN CNRI LİSANS ANLAŞMASI

1. This LICENSE AGREEMENT is between the Corporation for National Research Initiatives, having an office at 1895 Preston White Drive, Reston, VA 20191 ("CNRI"), and the Individual or Organization ("Licensee") accessing and otherwise using Python 1.6.1 software in source or binary form and its associated documentation.
2. Subject to the terms and conditions of this License Agreement, CNRI hereby grants Licensee a nonexclusive, royalty-free, world-wide license to reproduce, analyze, test, perform and/or display publicly, prepare derivative works,

(sonraki sayfaya devam)

(önceki sayfadan devam)

distribute, and otherwise use Python 1.6.1 alone or in any derivative version, provided, however, that CNRI's License Agreement and CNRI's notice of copyright, i.e., "Copyright © 1995-2001 Corporation for National Research Initiatives; All Rights Reserved" are retained in Python 1.6.1 alone or in any derivative version prepared by Licensee. Alternately, in lieu of CNRI's License Agreement, Licensee may substitute the following text (omitting the quotes): "Python 1.6.1 is made available subject to the terms and conditions in CNRI's License Agreement. This Agreement together with Python 1.6.1 may be located on the internet using the following unique, persistent identifier (known as a handle): 1895.22/1013. This Agreement may also be obtained from a proxy server on the internet using the following URL: <http://hdl.handle.net/1895.22/1013>."

3. In the event Licensee prepares a derivative work that is based on or incorporates Python 1.6.1 or any part thereof, and wants to make the derivative work available to others as provided herein, then Licensee hereby agrees to include in any such work a brief summary of the changes made to Python 1.6.1.
4. CNRI is making Python 1.6.1 available to Licensee on an "AS IS" basis. CNRI MAKES NO REPRESENTATIONS OR WARRANTIES, EXPRESS OR IMPLIED. BY WAY OF EXAMPLE, BUT NOT LIMITATION, CNRI MAKES NO AND DISCLAIMS ANY REPRESENTATION OR WARRANTY OF MERCHANTABILITY OR FITNESS FOR ANY PARTICULAR PURPOSE OR THAT THE USE OF PYTHON 1.6.1 WILL NOT INFRINGE ANY THIRD PARTY RIGHTS.
5. CNRI SHALL NOT BE LIABLE TO LICENSEE OR ANY OTHER USERS OF PYTHON 1.6.1 FOR ANY INCIDENTAL, SPECIAL, OR CONSEQUENTIAL DAMAGES OR LOSS AS A RESULT OF MODIFYING, DISTRIBUTING, OR OTHERWISE USING PYTHON 1.6.1, OR ANY DERIVATIVE THEREOF, EVEN IF ADVISED OF THE POSSIBILITY THEREOF.
6. This License Agreement will automatically terminate upon a material breach of its terms and conditions.
7. This License Agreement shall be governed by the federal intellectual property law of the United States, including without limitation the federal copyright law, and, to the extent such U.S. federal law does not apply, by the law of the Commonwealth of Virginia, excluding Virginia's conflict of law provisions. Notwithstanding the foregoing, with regard to derivative works based on Python 1.6.1 that incorporate non-separable material that was previously distributed under the GNU General Public License (GPL), the law of the Commonwealth of Virginia shall govern this License Agreement only as to issues arising under or with respect to Paragraphs 4, 5, and 7 of this License Agreement. Nothing in this License Agreement shall be deemed to create any relationship of agency, partnership, or joint venture between CNRI and Licensee. This License Agreement does not grant permission to use CNRI trademarks or trade name in a trademark sense to endorse or promote products or services of Licensee, or any third party.
8. By clicking on the "ACCEPT" button where indicated, or by copying, installing or otherwise using Python 1.6.1, Licensee agrees to be bound by the terms and conditions of this License Agreement.

C.2.4 0.9.0 ARASI 1.2 PYTHON İÇİN CWI LİSANS SÖZLEŞMESİ

Copyright © 1991 - 1995, Stichting Mathematisch Centrum Amsterdam, The Netherlands. All rights reserved.

(sonraki sayfaya devam)

(önceki sayfadan devam)

Permission to use, copy, modify, and distribute this software and its documentation for any purpose and without fee is hereby granted, provided that the above copyright notice appear in all copies and that both that copyright notice and this permission notice appear in supporting documentation, and that the name of Stichting Mathematisch Centrum or CWI not be used in advertising or publicity pertaining to distribution of the software without specific, written prior permission.

STICHTING MATHEMATISCH CENTRUM DISCLAIMS ALL WARRANTIES WITH REGARD TO THIS SOFTWARE, INCLUDING ALL IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS, IN NO EVENT SHALL STICHTING MATHEMATISCH CENTRUM BE LIABLE FOR ANY SPECIAL, INDIRECT OR CONSEQUENTIAL DAMAGES OR ANY DAMAGES WHATSOEVER RESULTING FROM LOSS OF USE, DATA OR PROFITS, WHETHER IN AN ACTION OF CONTRACT, NEGLIGENCE OR OTHER TORTIOUS ACTION, ARISING OUT OF OR IN CONNECTION WITH THE USE OR PERFORMANCE OF THIS SOFTWARE.

C.2.5 PYTHON 3.13.0 BELGELERİNDEKİ KOD İÇİN SIFIR MADDE BSD LİSANSI

Permission to use, copy, modify, and/or distribute this software for any purpose with or without fee is hereby granted.

THE SOFTWARE IS PROVIDED "AS IS" AND THE AUTHOR DISCLAIMS ALL WARRANTIES WITH REGARD TO THIS SOFTWARE INCLUDING ALL IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS. IN NO EVENT SHALL THE AUTHOR BE LIABLE FOR ANY SPECIAL, DIRECT, INDIRECT, OR CONSEQUENTIAL DAMAGES OR ANY DAMAGES WHATSOEVER RESULTING FROM LOSS OF USE, DATA OR PROFITS, WHETHER IN AN ACTION OF CONTRACT, NEGLIGENCE OR OTHER TORTIOUS ACTION, ARISING OUT OF OR IN CONNECTION WITH THE USE OR PERFORMANCE OF THIS SOFTWARE.

C.3 Tüzel Yazılımlar için Lisanslar ve Onaylar

Bu bölüm, Python dağıtımına dahil edilmiş üçüncü taraf yazılımlar için tamamlanmamış ancak büyüyen bir lisans ve onay listesidir.

C.3.1 Mersenne Twister'i

`random` modülünün altyapısını oluşturan `_random` C uzantısı, <http://www.math.sci.hiroshima-u.ac.jp/~m-mat/MT/MT2002/emt19937ar.html> adresinden indirilen kodu temel alır. Orijinal koddan kelimesi kelimesine yorumlar aşağıdadır:

A C-program for MT19937, with initialization improved 2002/1/26.
Coded by Takuji Nishimura and Makoto Matsumoto.

Before using, initialize the state by using `init_genrand(seed)`
or `init_by_array(init_key, key_length)`.

Copyright (C) 1997 - 2002, Makoto Matsumoto and Takuji Nishimura,
All rights reserved.

Redistribution and use in source and binary forms, with or without modification, are permitted provided that the following conditions are met:

1. Redistributions of source code must retain the above copyright

(sonraki sayfaya devam)

(önceki sayfadan devam)

notice, this list of conditions and the following disclaimer.

2. Redistributions in binary form must reproduce the above copyright notice, this list of conditions and the following disclaimer in the documentation and/or other materials provided with the distribution.
3. The names of its contributors may not be used to endorse or promote products derived from this software without specific prior written permission.

THIS SOFTWARE IS PROVIDED BY THE COPYRIGHT HOLDERS AND CONTRIBUTORS "AS IS" AND ANY EXPRESS OR IMPLIED WARRANTIES, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE ARE DISCLAIMED. IN NO EVENT SHALL THE COPYRIGHT OWNER OR CONTRIBUTORS BE LIABLE FOR ANY DIRECT, INDIRECT, INCIDENTAL, SPECIAL, EXEMPLARY, OR CONSEQUENTIAL DAMAGES (INCLUDING, BUT NOT LIMITED TO, PROCUREMENT OF SUBSTITUTE GOODS OR SERVICES; LOSS OF USE, DATA, OR PROFITS; OR BUSINESS INTERRUPTION) HOWEVER CAUSED AND ON ANY THEORY OF LIABILITY, WHETHER IN CONTRACT, STRICT LIABILITY, OR TORT (INCLUDING NEGLIGENCE OR OTHERWISE) ARISING IN ANY WAY OUT OF THE USE OF THIS SOFTWARE, EVEN IF ADVISED OF THE POSSIBILITY OF SUCH DAMAGE.

Any feedback is very welcome.

<http://www.math.sci.hiroshima-u.ac.jp/~m-mat/MT/emt.html>
email: m-mat @ math.sci.hiroshima-u.ac.jp (remove space)

C.3.2 Soketler

socket modülü, <https://www.wide.ad.jp/> adresindeki WIDE Projesi'nden ayrı kaynak dosyalarında kodlanan getaddrinfo() ve getnameinfo() fonksiyonlarını kullanır.

Copyright (C) 1995, 1996, 1997, and 1998 WIDE Project.
All rights reserved.

Redistribution and use in source and binary forms, with or without modification, are permitted provided that the following conditions are met:

1. Redistributions of source code must retain the above copyright notice, this list of conditions and the following disclaimer.
2. Redistributions in binary form must reproduce the above copyright notice, this list of conditions and the following disclaimer in the documentation and/or other materials provided with the distribution.
3. Neither the name of the project nor the names of its contributors may be used to endorse or promote products derived from this software without specific prior written permission.

THIS SOFTWARE IS PROVIDED BY THE PROJECT AND CONTRIBUTORS ``AS IS'' AND ANY EXPRESS OR IMPLIED WARRANTIES, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE ARE DISCLAIMED. IN NO EVENT SHALL THE PROJECT OR CONTRIBUTORS BE LIABLE FOR ANY DIRECT, INDIRECT, INCIDENTAL, SPECIAL, EXEMPLARY, OR CONSEQUENTIAL DAMAGES (INCLUDING, BUT NOT LIMITED TO, PROCUREMENT OF SUBSTITUTE GOODS OR SERVICES; LOSS OF USE, DATA, OR PROFITS; OR BUSINESS INTERRUPTION) HOWEVER CAUSED AND ON ANY THEORY OF LIABILITY, WHETHER IN CONTRACT, STRICT LIABILITY, OR TORT (INCLUDING NEGLIGENCE OR OTHERWISE) ARISING IN ANY WAY

(sonraki sayfaya devam)

(önceki sayfadan devam)

OUT OF THE USE OF THIS SOFTWARE, EVEN IF ADVISED OF THE POSSIBILITY OF SUCH DAMAGE.

C.3.3 Asenkron soket hizmetleri

The `test.support.asyncchat` and `test.support.asyncore` modules contain the following notice:

Copyright 1996 by Sam Rushing

All Rights Reserved

Permission to use, copy, modify, and distribute this software and its documentation for any purpose and without fee is hereby granted, provided that the above copyright notice appear in all copies and that both that copyright notice and this permission notice appear in supporting documentation, and that the name of Sam Rushing not be used in advertising or publicity pertaining to distribution of the software without specific, written prior permission.

SAM RUSHING DISCLAIMS ALL WARRANTIES WITH REGARD TO THIS SOFTWARE, INCLUDING ALL IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS, IN NO EVENT SHALL SAM RUSHING BE LIABLE FOR ANY SPECIAL, INDIRECT OR CONSEQUENTIAL DAMAGES OR ANY DAMAGES WHATSOEVER RESULTING FROM LOSS OF USE, DATA OR PROFITS, WHETHER IN AN ACTION OF CONTRACT, NEGLIGENCE OR OTHER TORTIOUS ACTION, ARISING OUT OF OR IN CONNECTION WITH THE USE OR PERFORMANCE OF THIS SOFTWARE.

C.3.4 Çerez yönetimi

`http.cookies` modülü aşağıdaki uyarı içeri:

Copyright 2000 by Timothy O'Malley <timo@alum.mit.edu>

All Rights Reserved

Permission to use, copy, modify, and distribute this software and its documentation for any purpose and without fee is hereby granted, provided that the above copyright notice appear in all copies and that both that copyright notice and this permission notice appear in supporting documentation, and that the name of Timothy O'Malley not be used in advertising or publicity pertaining to distribution of the software without specific, written prior permission.

Timothy O'Malley DISCLAIMS ALL WARRANTIES WITH REGARD TO THIS SOFTWARE, INCLUDING ALL IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS, IN NO EVENT SHALL Timothy O'Malley BE LIABLE FOR ANY SPECIAL, INDIRECT OR CONSEQUENTIAL DAMAGES OR ANY DAMAGES WHATSOEVER RESULTING FROM LOSS OF USE, DATA OR PROFITS, WHETHER IN AN ACTION OF CONTRACT, NEGLIGENCE OR OTHER TORTIOUS ACTION, ARISING OUT OF OR IN CONNECTION WITH THE USE OR PERFORMANCE OF THIS SOFTWARE.

C.3.5 Çalıştırma izleme

trace modülü aşağıdaki uyarıyi içerir:

```
portions copyright 2001, Autonomous Zones Industries, Inc., all rights...
err... reserved and offered to the public under the terms of the
Python 2.2 license.
Author: Zooko O'Whielacronx
http://zooko.com/
mailto:zooko@zooko.com

Copyright 2000, Mojam Media, Inc., all rights reserved.
Author: Skip Montanaro

Copyright 1999, Bioreason, Inc., all rights reserved.
Author: Andrew Dalke

Copyright 1995-1997, Automatrix, Inc., all rights reserved.
Author: Skip Montanaro

Copyright 1991-1995, Stichting Mathematisch Centrum, all rights reserved.

Permission to use, copy, modify, and distribute this Python software and
its associated documentation for any purpose without fee is hereby
granted, provided that the above copyright notice appears in all copies,
and that both that copyright notice and this permission notice appear in
supporting documentation, and that the name of neither Automatrix,
Bioreason or Mojam Media be used in advertising or publicity pertaining to
distribution of the software without specific, written prior permission.
```

C.3.6 UUencode ve UUdecode fonksiyonları

The uu codec contains the following notice:

```
Copyright 1994 by Lance Ellinghouse
Cathedral City, California Republic, United States of America.
All Rights Reserved
Permission to use, copy, modify, and distribute this software and its
documentation for any purpose and without fee is hereby granted,
provided that the above copyright notice appear in all copies and that
both that copyright notice and this permission notice appear in
supporting documentation, and that the name of Lance Ellinghouse
not be used in advertising or publicity pertaining to distribution
of the software without specific, written prior permission.
LANCE ELLINGHOUSE DISCLAIMS ALL WARRANTIES WITH REGARD TO
THIS SOFTWARE, INCLUDING ALL IMPLIED WARRANTIES OF MERCHANTABILITY AND
FITNESS, IN NO EVENT SHALL LANCE ELLINGHOUSE CENTRUM BE LIABLE
FOR ANY SPECIAL, INDIRECT OR CONSEQUENTIAL DAMAGES OR ANY DAMAGES
WHATSOEVER RESULTING FROM LOSS OF USE, DATA OR PROFITS, WHETHER IN AN
ACTION OF CONTRACT, NEGLIGENCE OR OTHER TORTIOUS ACTION, ARISING OUT
OF OR IN CONNECTION WITH THE USE OR PERFORMANCE OF THIS SOFTWARE.
```

Modified by Jack Jansen, CWI, July 1995:

- Use binascii module to do the actual line-by-line conversion between ascii and binary. This results in a 1000-fold speedup. The C version is still 5 times faster, though.
- Arguments more compliant with Python standard

C.3.7 XML Uzaktan Yordam Çağrıları

`xmlrpclib.client` modülü aşağıdaki uyarıyı içerir:

```
The XML-RPC client interface is

Copyright (c) 1999-2002 by Secret Labs AB
Copyright (c) 1999-2002 by Fredrik Lundh

By obtaining, using, and/or copying this software and/or its
associated documentation, you agree that you have read, understood,
and will comply with the following terms and conditions:

Permission to use, copy, modify, and distribute this software and
its associated documentation for any purpose and without fee is
hereby granted, provided that the above copyright notice appears in
all copies, and that both that copyright notice and this permission
notice appear in supporting documentation, and that the name of
Secret Labs AB or the author not be used in advertising or publicity
pertaining to distribution of the software without specific, written
prior permission.

SECRET LABS AB AND THE AUTHOR DISCLAIMS ALL WARRANTIES WITH REGARD
TO THIS SOFTWARE, INCLUDING ALL IMPLIED WARRANTIES OF MERCHANT-
ABILITY AND FITNESS. IN NO EVENT SHALL SECRET LABS AB OR THE AUTHOR
BE LIABLE FOR ANY SPECIAL, INDIRECT OR CONSEQUENTIAL DAMAGES OR ANY
DAMAGES WHATSOEVER RESULTING FROM LOSS OF USE, DATA OR PROFITS,
WHETHER IN AN ACTION OF CONTRACT, NEGLIGENCE OR OTHER TORTIOUS
ACTION, ARISING OUT OF OR IN CONNECTION WITH THE USE OR PERFORMANCE
OF THIS SOFTWARE.
```

C.3.8 test_epoll

`test.test_epoll` modülü aşağıdaki uyarıyı içerir:

```
Copyright (c) 2001-2006 Twisted Matrix Laboratories.

Permission is hereby granted, free of charge, to any person obtaining
a copy of this software and associated documentation files (the
"Software"), to deal in the Software without restriction, including
without limitation the rights to use, copy, modify, merge, publish,
distribute, sublicense, and/or sell copies of the Software, and to
permit persons to whom the Software is furnished to do so, subject to
the following conditions:

The above copyright notice and this permission notice shall be
included in all copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND,
EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF
MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE AND
NONINFRINGEMENT. IN NO EVENT SHALL THE AUTHORS OR COPYRIGHT HOLDERS BE
LIABLE FOR ANY CLAIM, DAMAGES OR OTHER LIABILITY, WHETHER IN AN ACTION
OF CONTRACT, TORT OR OTHERWISE, ARISING FROM, OUT OF OR IN CONNECTION
WITH THE SOFTWARE OR THE USE OR OTHER DEALINGS IN THE SOFTWARE.
```

C.3.9 kqueue seçin

select modülü, kqueue arayüzü için aşağıdaki uyarı içerişir:

```
Copyright (c) 2000 Doug White, 2006 James Knight, 2007 Christian Heimes
All rights reserved.
```

Redistribution and use in source and binary forms, with or without modification, are permitted provided that the following conditions are met:

1. Redistributions of source code must retain the above copyright notice, this list of conditions and the following disclaimer.
2. Redistributions in binary form must reproduce the above copyright notice, this list of conditions and the following disclaimer in the documentation and/or other materials provided with the distribution.

THIS SOFTWARE IS PROVIDED BY THE AUTHOR AND CONTRIBUTORS ``AS IS'' AND ANY EXPRESS OR IMPLIED WARRANTIES, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE ARE DISCLAIMED. IN NO EVENT SHALL THE AUTHOR OR CONTRIBUTORS BE LIABLE FOR ANY DIRECT, INDIRECT, INCIDENTAL, SPECIAL, EXEMPLARY, OR CONSEQUENTIAL DAMAGES (INCLUDING, BUT NOT LIMITED TO, PROCUREMENT OF SUBSTITUTE GOODS OR SERVICES; LOSS OF USE, DATA, OR PROFITS; OR BUSINESS INTERRUPTION) HOWEVER CAUSED AND ON ANY THEORY OF LIABILITY, WHETHER IN CONTRACT, STRICT LIABILITY, OR TORT (INCLUDING NEGLIGENCE OR OTHERWISE) ARISING IN ANY WAY OUT OF THE USE OF THIS SOFTWARE, EVEN IF ADVISED OF THE POSSIBILITY OF SUCH DAMAGE.

C.3.10 SipHash24

Python/pyhash.c dosyası, Dan Bernstein'in SipHash24 algoritmasının Marek Majkowski uygulamasını içerir. Burada aşağıdaki not yer alır:

```
<MIT License>
```

```
Copyright (c) 2013 Marek Majkowski <marek@popcount.org>
```

Permission is hereby granted, free of charge, to any person obtaining a copy of this software and associated documentation files (the "Software"), to deal in the Software without restriction, including without limitation the rights to use, copy, modify, merge, publish, distribute, sublicense, and/or sell copies of the Software, and to permit persons to whom the Software is furnished to do so, subject to the following conditions:

The above copyright notice and this permission notice shall be included in all copies or substantial portions of the Software.

```
</MIT License>
```

Original location:

```
https://github.com/majek/csiphash/
```

Solution inspired by code from:

```
Samuel Neves (supercop/crypto_auth/siphash24/little)
```

```
djb (supercop/crypto_auth/siphash24/little2)
```

```
Jean-Philippe Aumasson (https://131002.net/siphash/siphash24.c)
```

C.3.11 strtod ve dtoa

C double'larının dizelere ve dizelerden dönüştürülmesi için dtoa ve strtod C fonksiyonlarını sağlayan Python/dtoa.c dosyası, şu anda <https://web.archive.org/web/20220517033456/http://www.netlib.org/fp/dtoa.c> 'den erişilebilen David M. Gay tarafından aynı adlı dosyadan türetilmiştir. 16 Mart 2009'da alınan orijinal dosya aşağıdaki telif hakkı ve lisans bildirimini içerir:

```
*****
*
* The author of this software is David M. Gay.
*
* Copyright (c) 1991, 2000, 2001 by Lucent Technologies.
*
* Permission to use, copy, modify, and distribute this software for any
* purpose without fee is hereby granted, provided that this entire notice
* is included in all copies of any software which is or includes a copy
* or modification of this software and in all copies of the supporting
* documentation for such software.
*
* THIS SOFTWARE IS BEING PROVIDED "AS IS", WITHOUT ANY EXPRESS OR IMPLIED
* WARRANTY. IN PARTICULAR, NEITHER THE AUTHOR NOR LUCENT MAKES ANY
* REPRESENTATION OR WARRANTY OF ANY KIND CONCERNING THE MERCHANTABILITY
* OF THIS SOFTWARE OR ITS FITNESS FOR ANY PARTICULAR PURPOSE.
*
*****
```

C.3.12 OpenSSL

The modules `hashlib`, `posix` and `ssl` use the OpenSSL library for added performance if made available by the operating system. Additionally, the Windows and macOS installers for Python may include a copy of the OpenSSL libraries, so we include a copy of the OpenSSL license here. For the OpenSSL 3.0 release, and later releases derived from that, the Apache License v2 applies:

```
Apache License
Version 2.0, January 2004
https://www.apache.org/licenses/
```

TERMS AND CONDITIONS FOR USE, REPRODUCTION, AND DISTRIBUTION

1. Definitions.

"License" shall mean the terms and conditions for use, reproduction, and distribution as defined by Sections 1 through 9 of this document.

"Licensor" shall mean the copyright owner or entity authorized by the copyright owner that is granting the License.

"Legal Entity" shall mean the union of the acting entity and all other entities that control, are controlled by, or are under common control with that entity. For the purposes of this definition, "control" means (i) the power, direct or indirect, to cause the direction or management of such entity, whether by contract or otherwise, or (ii) ownership of fifty percent (50%) or more of the outstanding shares, or (iii) beneficial ownership of such entity.

"You" (or "Your") shall mean an individual or Legal Entity exercising permissions granted by this License.

(sonraki sayfaya devam)

(önceki sayfadan devam)

"Source" form shall mean the preferred form for making modifications, including but not limited to software source code, documentation source, and configuration files.

"Object" form shall mean any form resulting from mechanical transformation or translation of a Source form, including but not limited to compiled object code, generated documentation, and conversions to other media types.

"Work" shall mean the work of authorship, whether in Source or Object form, made available under the License, as indicated by a copyright notice that is included in or attached to the work (an example is provided in the Appendix below).

"Derivative Works" shall mean any work, whether in Source or Object form, that is based on (or derived from) the Work and for which the editorial revisions, annotations, elaborations, or other modifications represent, as a whole, an original work of authorship. For the purposes of this License, Derivative Works shall not include works that remain separable from, or merely link (or bind by name) to the interfaces of, the Work and Derivative Works thereof.

"Contribution" shall mean any work of authorship, including the original version of the Work and any modifications or additions to that Work or Derivative Works thereof, that is intentionally submitted to Licenser for inclusion in the Work by the copyright owner or by an individual or Legal Entity authorized to submit on behalf of the copyright owner. For the purposes of this definition, "submitted" means any form of electronic, verbal, or written communication sent to the Licenser or its representatives, including but not limited to communication on electronic mailing lists, source code control systems, and issue tracking systems that are managed by, or on behalf of, the Licenser for the purpose of discussing and improving the Work, but excluding communication that is conspicuously marked or otherwise designated in writing by the copyright owner as "Not a Contribution."

"Contributor" shall mean Licensor and any individual or Legal Entity on behalf of whom a Contribution has been received by Licensor and subsequently incorporated within the Work.

2. Grant of Copyright License. Subject to the terms and conditions of this License, each Contributor hereby grants to You a perpetual, worldwide, non-exclusive, no-charge, royalty-free, irrevocable copyright license to reproduce, prepare Derivative Works of, publicly display, publicly perform, sublicense, and distribute the Work and such Derivative Works in Source or Object form.
3. Grant of Patent License. Subject to the terms and conditions of this License, each Contributor hereby grants to You a perpetual, worldwide, non-exclusive, no-charge, royalty-free, irrevocable (except as stated in this section) patent license to make, have made, use, offer to sell, sell, import, and otherwise transfer the Work, where such license applies only to those patent claims licensable by such Contributor that are necessarily infringed by their Contribution(s) alone or by combination of their Contribution(s) with the Work to which such Contribution(s) was submitted. If You

(sonraki sayfaya devam)

(önceki sayfadan devam)

institute patent litigation against any entity (including a cross-claim or counterclaim in a lawsuit) alleging that the Work or a Contribution incorporated within the Work constitutes direct or contributory patent infringement, then any patent licenses granted to You under this License for that Work shall terminate as of the date such litigation is filed.

4. Redistribution. You may reproduce and distribute copies of the Work or Derivative Works thereof in any medium, with or without modifications, and in Source or Object form, provided that You meet the following conditions:
 - (a) You must give any other recipients of the Work or Derivative Works a copy of this License; and
 - (b) You must cause any modified files to carry prominent notices stating that You changed the files; and
 - (c) You must retain, in the Source form of any Derivative Works that You distribute, all copyright, patent, trademark, and attribution notices from the Source form of the Work, excluding those notices that do not pertain to any part of the Derivative Works; and
 - (d) If the Work includes a "NOTICE" text file as part of its distribution, then any Derivative Works that You distribute must include a readable copy of the attribution notices contained within such NOTICE file, excluding those notices that do not pertain to any part of the Derivative Works, in at least one of the following places: within a NOTICE text file distributed as part of the Derivative Works; within the Source form or documentation, if provided along with the Derivative Works; or, within a display generated by the Derivative Works, if and wherever such third-party notices normally appear. The contents of the NOTICE file are for informational purposes only and do not modify the License. You may add Your own attribution notices within Derivative Works that You distribute, alongside or as an addendum to the NOTICE text from the Work, provided that such additional attribution notices cannot be construed as modifying the License.

You may add Your own copyright statement to Your modifications and may provide additional or different license terms and conditions for use, reproduction, or distribution of Your modifications, or for any such Derivative Works as a whole, provided Your use, reproduction, and distribution of the Work otherwise complies with the conditions stated in this License.

5. Submission of Contributions. Unless You explicitly state otherwise, any Contribution intentionally submitted for inclusion in the Work by You to the Licensor shall be under the terms and conditions of this License, without any additional terms or conditions. Notwithstanding the above, nothing herein shall supersede or modify the terms of any separate license agreement you may have executed with Licensor regarding such Contributions.

(sonraki sayfaya devam)

(önceki sayfadan devam)

6. Trademarks. This License does not grant permission to use the trade names, trademarks, service marks, or product names of the Licensor, except as required for reasonable and customary use in describing the origin of the Work and reproducing the content of the NOTICE file.
7. Disclaimer of Warranty. Unless required by applicable law or agreed to in writing, Licensor provides the Work (and each Contributor provides its Contributions) on an "AS IS" BASIS, WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied, including, without limitation, any warranties or conditions of TITLE, NON-INFRINGEMENT, MERCHANTABILITY, or FITNESS FOR A PARTICULAR PURPOSE. You are solely responsible for determining the appropriateness of using or redistributing the Work and assume any risks associated with Your exercise of permissions under this License.
8. Limitation of Liability. In no event and under no legal theory, whether in tort (including negligence), contract, or otherwise, unless required by applicable law (such as deliberate and grossly negligent acts) or agreed to in writing, shall any Contributor be liable to You for damages, including any direct, indirect, special, incidental, or consequential damages of any character arising as a result of this License or out of the use or inability to use the Work (including but not limited to damages for loss of goodwill, work stoppage, computer failure or malfunction, or any and all other commercial damages or losses), even if such Contributor has been advised of the possibility of such damages.
9. Accepting Warranty or Additional Liability. While redistributing the Work or Derivative Works thereof, You may choose to offer, and charge a fee for, acceptance of support, warranty, indemnity, or other liability obligations and/or rights consistent with this License. However, in accepting such obligations, You may act only on Your own behalf and on Your sole responsibility, not on behalf of any other Contributor, and only if You agree to indemnify, defend, and hold each Contributor harmless for any liability incurred by, or claims asserted against, such Contributor by reason of your accepting any such warranty or additional liability.

END OF TERMS AND CONDITIONS

C.3.13 expat

The `pyexpat` extension is built using an included copy of the expat sources unless the build is configured `--with-system-expat`:

Copyright (c) 1998, 1999, 2000 Thai Open Source Software Center Ltd
and Clark Cooper

Permission is hereby granted, free of charge, to any person obtaining a copy of this software and associated documentation files (the "Software"), to deal in the Software without restriction, including without limitation the rights to use, copy, modify, merge, publish, distribute, sublicense, and/or sell copies of the Software, and to permit persons to whom the Software is furnished to do so, subject to the following conditions:

(sonraki sayfaya devam)

(önceki sayfadan devam)

The above copyright notice and this permission notice shall be included in all copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND, EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE AND NONINFRINGEMENT. IN NO EVENT SHALL THE AUTHORS OR COPYRIGHT HOLDERS BE LIABLE FOR ANY CLAIM, DAMAGES OR OTHER LIABILITY, WHETHER IN AN ACTION OF CONTRACT, TORT OR OTHERWISE, ARISING FROM, OUT OF OR IN CONNECTION WITH THE SOFTWARE OR THE USE OR OTHER DEALINGS IN THE SOFTWARE.

C.3.14 libffi

`ctypes` modülünün altyapısını oluşturan `_ctypes` C uzantısı, --with-system-libffi olarak yapılandırılmıştır. Bu nedenle libffi kaynaklarının dahil edildiği bir kopya kullanılarak oluşturulur:

Copyright (c) 1996-2008 Red Hat, Inc and others.

Permission is hereby granted, free of charge, to any person obtaining a copy of this software and associated documentation files (the ``Software''), to deal in the Software without restriction, including without limitation the rights to use, copy, modify, merge, publish, distribute, sublicense, and/or sell copies of the Software, and to permit persons to whom the Software is furnished to do so, subject to the following conditions:

The above copyright notice and this permission notice shall be included in all copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED ``AS IS'', WITHOUT WARRANTY OF ANY KIND, EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE AND NONINFRINGEMENT. IN NO EVENT SHALL THE AUTHORS OR COPYRIGHT HOLDERS BE LIABLE FOR ANY CLAIM, DAMAGES OR OTHER LIABILITY, WHETHER IN AN ACTION OF CONTRACT, TORT OR OTHERWISE, ARISING FROM, OUT OF OR IN CONNECTION WITH THE SOFTWARE OR THE USE OR OTHER DEALINGS IN THE SOFTWARE.

C.3.15 zlib

`zlib` uzantısı, sistemde bulunan `zlib` sürümü derleme için kullanılamayacak kadar eskiyse, `zlib` kaynaklarının dahil edildiği bir kopya kullanılarak oluşturulur:

Copyright (C) 1995-2011 Jean-loup Gailly and Mark Adler

This software is provided 'as-is', without any express or implied warranty. In no event will the authors be held liable for any damages arising from the use of this software.

Permission is granted to anyone to use this software for any purpose, including commercial applications, and to alter it and redistribute it freely, subject to the following restrictions:

1. The origin of this software must not be misrepresented; you must not claim that you wrote the original software. If you use this software in a product, an acknowledgment in the product documentation would be

(sonraki sayfaya devam)

(önceki sayfadan devam)

appreciated but is not required.

2. Altered source versions must be plainly marked as such, and must not be misrepresented as being the original software.

3. This notice may not be removed or altered from any source distribution.

Jean-loup Gailly
jSoup@gzip.org

Mark Adler
madler@alumni.caltech.edu

C.3.16 cfuhash

tracemalloc tarafından kullanılan hash tablosunun uygulanması cfuhash projesine dayanmaktadır:

Copyright (c) 2005 Don Owens
All rights reserved.

This code is released under the BSD license:

Redistribution and use in source and binary forms, with or without modification, are permitted provided that the following conditions are met:

- * Redistributions of source code must retain the above copyright notice, this list of conditions and the following disclaimer.
- * Redistributions in binary form must reproduce the above copyright notice, this list of conditions and the following disclaimer in the documentation and/or other materials provided with the distribution.
- * Neither the name of the author nor the names of its contributors may be used to endorse or promote products derived from this software without specific prior written permission.

THIS SOFTWARE IS PROVIDED BY THE COPYRIGHT HOLDERS AND CONTRIBUTORS "AS IS" AND ANY EXPRESS OR IMPLIED WARRANTIES, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE ARE DISCLAIMED. IN NO EVENT SHALL THE COPYRIGHT OWNER OR CONTRIBUTORS BE LIABLE FOR ANY DIRECT, INDIRECT, INCIDENTAL, SPECIAL, EXEMPLARY, OR CONSEQUENTIAL DAMAGES (INCLUDING, BUT NOT LIMITED TO, PROCUREMENT OF SUBSTITUTE GOODS OR SERVICES; LOSS OF USE, DATA, OR PROFITS; OR BUSINESS INTERRUPTION) HOWEVER CAUSED AND ON ANY THEORY OF LIABILITY, WHETHER IN CONTRACT, STRICT LIABILITY, OR TORT (INCLUDING NEGLIGENCE OR OTHERWISE) ARISING IN ANY WAY OUT OF THE USE OF THIS SOFTWARE, EVEN IF ADVISED OF THE POSSIBILITY OF SUCH DAMAGE.

C.3.17 libmpdec

The `_decimal` C extension underlying the `decimal` module is built using an included copy of the libmpdec library unless the build is configured `--with-system-libmpdec`:

Copyright (c) 2008-2020 Stefan Krah. All rights reserved.

Redistribution and use in source and binary forms, with or without

(sonraki sayfaya devam)

(önceki sayfadan devam)

modification, are permitted provided that the following conditions are met:

1. Redistributions of source code must retain the above copyright notice, this list of conditions and the following disclaimer.
2. Redistributions in binary form must reproduce the above copyright notice, this list of conditions and the following disclaimer in the documentation and/or other materials provided with the distribution.

THIS SOFTWARE IS PROVIDED BY THE AUTHOR AND CONTRIBUTORS "AS IS" AND ANY EXPRESS OR IMPLIED WARRANTIES, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE ARE DISCLAIMED. IN NO EVENT SHALL THE AUTHOR OR CONTRIBUTORS BE LIABLE FOR ANY DIRECT, INDIRECT, INCIDENTAL, SPECIAL, EXEMPLARY, OR CONSEQUENTIAL DAMAGES (INCLUDING, BUT NOT LIMITED TO, PROCUREMENT OF SUBSTITUTE GOODS OR SERVICES; LOSS OF USE, DATA, OR PROFITS; OR BUSINESS INTERRUPTION) HOWEVER CAUSED AND ON ANY THEORY OF LIABILITY, WHETHER IN CONTRACT, STRICT LIABILITY, OR TORT (INCLUDING NEGLIGENCE OR OTHERWISE) ARISING IN ANY WAY OUT OF THE USE OF THIS SOFTWARE, EVEN IF ADVISED OF THE POSSIBILITY OF SUCH DAMAGE.

C.3.18 W3C C14N test paketi

test paketindeki C14N 2.0 test paketi (Lib/test/xmltestdata/c14n-20/), <https://www.w3.org/TR/xml-c14n2-testcases/> adresindeki W3C web sitesinden alınmıştır ve 3 maddeli BSD lisansı altında dağıtılmaktadır:

Copyright (c) 2013 W3C(R) (MIT, ERCIM, Keio, Beihang),
All Rights Reserved.

Redistribution and use in source and binary forms, with or without modification, are permitted provided that the following conditions are met:

- * Redistributions of works must retain the original copyright notice, this list of conditions and the following disclaimer.
- * Redistributions in binary form must reproduce the original copyright notice, this list of conditions and the following disclaimer in the documentation and/or other materials provided with the distribution.
- * Neither the name of the W3C nor the names of its contributors may be used to endorse or promote products derived from this work without specific prior written permission.

THIS SOFTWARE IS PROVIDED BY THE COPYRIGHT HOLDERS AND CONTRIBUTORS "AS IS" AND ANY EXPRESS OR IMPLIED WARRANTIES, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE ARE DISCLAIMED. IN NO EVENT SHALL THE COPYRIGHT OWNER OR CONTRIBUTORS BE LIABLE FOR ANY DIRECT, INDIRECT, INCIDENTAL, SPECIAL, EXEMPLARY, OR CONSEQUENTIAL DAMAGES (INCLUDING, BUT NOT LIMITED TO, PROCUREMENT OF SUBSTITUTE GOODS OR SERVICES; LOSS OF USE, DATA, OR PROFITS; OR BUSINESS INTERRUPTION) HOWEVER CAUSED AND ON ANY THEORY OF LIABILITY, WHETHER IN CONTRACT, STRICT LIABILITY, OR TORT (INCLUDING NEGLIGENCE OR OTHERWISE) ARISING IN ANY WAY OUT OF THE USE OF THIS SOFTWARE, EVEN IF ADVISED OF THE POSSIBILITY OF SUCH DAMAGE.

C.3.19 mimalloc

MIT License:

Copyright (c) 2018–2021 Microsoft Corporation, Daan Leijen

Permission is hereby granted, free of charge, to any person obtaining a copy of this software and associated documentation files (the "Software"), to deal in the Software without restriction, including without limitation the rights to use, copy, modify, merge, publish, distribute, sublicense, and/or sell copies of the Software, and to permit persons to whom the Software is furnished to do so, subject to the following conditions:

The above copyright notice and this permission notice shall be included in all copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND, EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE AND NONINFRINGEMENT. IN NO EVENT SHALL THE AUTHORS OR COPYRIGHT HOLDERS BE LIABLE FOR ANY CLAIM, DAMAGES OR OTHER LIABILITY, WHETHER IN AN ACTION OF CONTRACT, TORT OR OTHERWISE, ARISING FROM, OUT OF OR IN CONNECTION WITH THE SOFTWARE OR THE USE OR OTHER DEALINGS IN THE SOFTWARE.

C.3.20 asyncio

Parts of the `asyncio` module are incorporated from [uvloop 0.16](#), which is distributed under the MIT license:

Copyright (c) 2015–2021 MagicStack Inc. <http://magic.io>

Permission is hereby granted, free of charge, to any person obtaining a copy of this software and associated documentation files (the "Software"), to deal in the Software without restriction, including without limitation the rights to use, copy, modify, merge, publish, distribute, sublicense, and/or sell copies of the Software, and to permit persons to whom the Software is furnished to do so, subject to the following conditions:

The above copyright notice and this permission notice shall be included in all copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND, EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE AND NONINFRINGEMENT. IN NO EVENT SHALL THE AUTHORS OR COPYRIGHT HOLDERS BE LIABLE FOR ANY CLAIM, DAMAGES OR OTHER LIABILITY, WHETHER IN AN ACTION OF CONTRACT, TORT OR OTHERWISE, ARISING FROM, OUT OF OR IN CONNECTION WITH THE SOFTWARE OR THE USE OR OTHER DEALINGS IN THE SOFTWARE.

C.3.21 Global Unbounded Sequences (GUS)

The file `Python/qsbr.c` is adapted from FreeBSD's "Global Unbounded Sequences" safe memory reclamation scheme in `subr_smr.c`. The file is distributed under the 2-Clause BSD License:

Copyright (c) 2019,2020 Jeffrey Roberson <jeff@FreeBSD.org>

Redistribution and use in source and binary forms, with or without modification, are permitted provided that the following conditions

(sonraki sayfaya devam)

(önceki sayfadan devam)

are met:

1. Redistributions of source code must retain the above copyright notice unmodified, this list of conditions, and the following disclaimer.
2. Redistributions in binary form must reproduce the above copyright notice, this list of conditions and the following disclaimer in the documentation and/or other materials provided with the distribution.

THIS SOFTWARE IS PROVIDED BY THE AUTHOR ``AS IS'' AND ANY EXPRESS OR IMPLIED WARRANTIES, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE ARE DISCLAIMED. IN NO EVENT SHALL THE AUTHOR BE LIABLE FOR ANY DIRECT, INDIRECT, INCIDENTAL, SPECIAL, EXEMPLARY, OR CONSEQUENTIAL DAMAGES (INCLUDING, BUT NOT LIMITED TO, PROCUREMENT OF SUBSTITUTE GOODS OR SERVICES; LOSS OF USE, DATA, OR PROFITS; OR BUSINESS INTERRUPTION) HOWEVER CAUSED AND ON ANY THEORY OF LIABILITY, WHETHER IN CONTRACT, STRICT LIABILITY, OR TORT (INCLUDING NEGLIGENCE OR OTHERWISE) ARISING IN ANY WAY OUT OF THE USE OF THIS SOFTWARE, EVEN IF ADVISED OF THE POSSIBILITY OF SUCH DAMAGE.

Telif Hakkı

Python ve bu dokümantasyon:

Copyright © 2001-2024 Python Software Foundation. All rights reserved.

Telif Hakkı © 2000 BeOpen.com. Tüm hakları saklıdır.

Telif Hakkı © 1995-2000 Ulusal Araştırma Girişimleri Kurumu. Tüm hakları saklıdır.

Telif Hakkı © 1991-1995 Stichting Mathematisch Centrum. Tüm hakları saklıdır.

Bütün lisans ve izin bilgileri için [*Tarihçe ve Lisans*](#) ‘a göz atın.

Alfabetik olmayan

..., 67
>>>, 67
__future__, 73
__slots__, 80

A

ad alanı, 77
ad alanı paketi, 77
adlandırılmış demet, 77
anahtar işlev, 75
anahtar kelime argümanı, 76
anlamak, 81
argüman, 67
asenkron bağlam yöneticisi, 68
asenkron jeneratör, 68
asenkron jeneratör yineleyici, 68
asenkron yineleyici, 68

B

bağlam değişkeni, 70
bağlam yöneticisi, 70
bayt benzeri nesne, 69
bayt kodu, 69
BDFL, 68
beklenebilir, 68
belge dizisi, 71
bitişik, 70
BOŞTA, 74
built-in function
 repr, 50
bulucu, 72

C

C-contiguous, 70
closure variable, 69
context, 70
context management protocol, 70
CPython, 70
current context, 70

Ç

çağırlabilir, 69

çöp toplama, 73

D

deallocation, object, 49
değişken açıklaması, 82
değişmez, 74
değiştirilebilir, 77
dekoratör, 71
dipnot, 67
dizi, 80
dosya benzeri nesne, 72
dosya nesnesi, 72
dosya sistemi kodlaması ve hata
 işleyicisi, 72

E

EAFP, 71
eşyordam, 70
eşyordam işlevi, 70
eşzamansız yinelenebilir, 68
etkileşimli, 74
evrensel yeni satırlar, 82

F

f-string, 72
finalization, of objects, 49
fonksiyon, 72
fonksiyon açıklaması, 73
Fortran contiguous, 70
free threading, 72
free variable, 72

G

geçici API, 79
geçici paket, 79
genel işlev, 73
genel tercüman kılıdi, 74
genel tip, 73
geri çağrırmak, 69
GIL, 74
güçlü referans, 81

H

haritalama, 76

I

 iç içe kapsam, 78
 içe aktarıcı, 74
 içe aktarım yolu, 74
 içe aktarma, 74
 ifade (*değer döndürmez*), 81
 ifade (*değer döndürür*), 72
 ikili dosya, 68
 immortal, 74

J

 jeneratör, 73
 jeneratör ifadesi, 73
 jeneratör yineleyici, 73

K

 karma tabanlı pyc, 74
 karmaşık sayı, 70
 kat bölümü, 72
 kısım, 79
 konumsal argüman, 79

L

 lambda, 76
 LBYL, 76
 liste, 76
 liste anlama, 76

M

 magic
 metot, 76
 meta yol bulucu, 76
 metasınıf, 76
 metot, 77
 magic, 76
 special, 81
 metot kalite sıralaması, 77
 modül, 77
 modül özelliği, 77
 MRO, 77

N

 nitelik, 68
 nitelikli isim, 80

O

 obje, 78
 object
 deallocation, 49
 finalization, 49
 optimized scope, 78
 ortam değişkeni
 PYTHON_GIL, 74
 PYTHONPATH, 56

Ö

 ödünç alınan referans, 69

ördek yazma, 71
özel metod, 81

P

 paket, 78
 parametre, 78
 parçalamak, 81
 PEP, 79
 Philbrick, Geoff, 15
 PyArg_ParseTuple (*C function*), 13
 PyArg_ParseTupleAndKeywords (*C function*), 15
 PyErr_Fetch (*C function*), 49
 PyErr_Restore (*C function*), 49
 PyInit_modulename (*C function*), 56
 PyObject_CallObject (*C function*), 12
 Python 3000, 79
 Python Geliştirme Önerileri

 PEP 1, 79
 PEP 238, 72
 PEP 278, 82
 PEP 302, 76
 PEP 343, 70
 PEP 362, 68, 79
 PEP 411, 79
 PEP 420, 77, 79
 PEP 442, 50
 PEP 443, 73
 PEP 483, 73
 PEP 484, 67, 73, 82
 PEP 489, 11, 56
 PEP 492, 68, 70
 PEP 498, 72
 PEP 519, 79
 PEP 525, 68
 PEP 526, 67, 82
 PEP 585, 73
 PEP 683, 74
 PEP 703, 72, 74
 PEP 3116, 82
 PEP 3155, 80
 PYTHON_GIL, 74
 Pythonic, 79
 PYTHONPATH, 56
 Python'un Zen'i, 83

R

 referans sayısı, 80
 REPL, 80
 repr
 built-in function, 50

S

 sanal makine, 83
 sanal ortam, 83
 sınıf, 69
 sınıf değişkeni, 69
 sihirli yöntem, 76
 soft deprecated, 81

soyut temel sınıf, **67**
sözlük, **71**
sözlük anlama, **71**
sözlük görünümü, **71**
special
 metot, **81**
static type checker, **81**
string
 object representation, **50**
sürekli paketleme, **80**

T

tanımlayıcı, **71**
tek sevk, **81**
tercüman kapatma, **75**
tip, **82**
tip takma adı, **82**
tür ipucu, **82**

Ü

uzatma modülü, **72**

Ü

üç tırnaklı dize, **82**

Y

yazı çözümleme, **81**
yazı dosyası, **81**
yeni stil sınıf, **78**
yerel kodlama, **76**
yíkanabilir, **74**
yinelenebilir, **75**
yíneleyici, **75**
yol benzeri nesne, **79**
yol giriş kancası, **79**
yol giriþi, **79**
yol giriþi bulucu, **79**
yol tabanlı bulucu, **79**
yorumlanmış, **75**
yükleyici, **76**