

---

# 使用 GDB 调试 C API 扩展和 CPython 内部代码

发行版本 3.14.0a1

Guido van Rossum and the Python development team

十一月 13, 2024

Python Software Foundation  
Email: docs@python.org

## Contents

|   |   |
|---|---|
| 1 前提条件  | 2 |
| 1.1 使用从源代码构建的 Python 进行设置 . . . . .                     | 2 |
| 1.2 针对 Linux 发行版的 Python 设置 . . . . .                   | 2 |
| 2 使用调试构建和开发模式   | 2 |
| 3 使用 <code>python-gdb</code> 扩展                         | 3 |
| 3.1 美化打印 . . . . .                                      | 3 |
| 3.2 <code>py-list</code> . . . . .                      | 4 |
| 3.3 <code>py-up</code> 和 <code>py-down</code> . . . . . | 4 |
| 3.4 <code>py-bt</code> . . . . .                        | 6 |
| 3.5 <code>py-print</code> . . . . .                     | 7 |
| 3.6 <code>py-locals</code> . . . . .                    | 7 |
| 4 与 GDB 命令一起使用  | 7 |

---

本文档介绍了如何将 Python GDB 扩展 `python-gdb.py` 与 GDB 调试器一起使用以调试 CPython 扩展以及 CPython 解释器本身。

当调试低层级问题如崩溃或死锁时，低层级的调试器如 GDB 适合被用来诊断和修正错误。在默认情况下，GDB（或其任一种前端）并不支持 CPython 解释器专属的高层级信息。

`python-gdb.py` 扩展可向 GDB 添加 CPython 解释器信息。该扩展能协助对当前执行的 Python 函数栈进行内省。当给定一个由 `PyObject*` 指针代表的 Python 对象时，该扩展将展示对象的类型和值。

开发 CPython 扩展或处理 CPython 中用 C 语言编写的部分的开发人员可以通过本文档学习如何将 `python-gdb.py` 扩展与 GDB 一起使用。

### 备注

本文档假定你已熟悉 GDB 和 CPython C API 的基础知识。它对来自 devguide 和 Python wiki 的内容进行了整合。

# 1 前提条件

你需要有：

- GDB 7 或更高的版本。（对于较低版本的 GDB，请参阅 Python 3.11 或更低版本源代码中的 `Misc/gdbinit.`。）
- 针对 Python 和你正在调试的任何扩展的 GDB 兼容调试信息。
- `python-gdb.py` 扩展。

此扩展与 Python 一起构建，但可能单独发布或根本不发布。下面，我们将以几个常见系统为例进行说明。请注意即使这些说明与你的系统相匹配，它们也可能已经过时。

## 1.1 使用从源代码构建的 Python 进行设置

当你从源代码构建 CPython 时，调试信息应当是可用的，并且构建应当在你的代码库根目录中添加一个 `python-gdb.py` 文件。

要激活支持，你必须将包含 `python-gdb.py` 的目录添加到 GDB 的“auto-load-safe-path”中。如果你没有这样做，较新版本的 GDB 会打印一个警告来说明如何执行此操作。

### i 备注

如果你没有看到针对你的 GDB 版本的说明，请将以下内容放到你的配置文件中 (`~/.gdbinit` 或 `~/.config/gdb/gdbinit`)：

```
add-auto-load-safe-path /path/to/cpython
```

你还可以添加多个路径，以 : 分隔。

## 1.2 针对 Linux 发行版的 Python 设置

大多数 Linux 系统会在名为 `python-debuginfo`、`python-dbg` 或类似的包中提供系统 Python 的调试信息。例如：

- Fedora：

```
sudo dnf install gdb
sudo dnf debuginfo-install python3
```

- Ubuntu：

```
sudo apt install gdb python3-dbg
```

在一些最新的 Linux 系统上，GDB 可以使用 `debuginfod` 自动下载调试符号。不过，这并不会安装 `python-gdb.py` 扩展；你通常需要单独安装调试信息包。

# 2 使用调试构建和开发模式

为了方便调试，你可能需要：

- 使用 Python 的调试构建版。（当从源代码构建时，使用 `configure --with-pydebug`。在 Linux 发行版上，安装并运行 `python-debug` 或 `python-dbg` 之类的包，如果有的话。）
- 使用运行时开发模式 (`-X dev`)。

两者都将启用额外的断言并禁用某些优化。有时这会隐藏你想要查找的程序错误，但大多数情况下它们都能使调试过程更简单。

## 3 使用 python-gdb 扩展

当该扩展被加载时，它将提供两个主要特性：Python 值的美化打印，以及附加的命令。

### 3.1 美化打印

这是当此扩展被启用时 GDB 回溯信息的显示效果（截取部分）：

```
#0 0x0000000000041a6b1 in PyObject_Malloc (nbytes=Cannot access memory at address 0x7fffff7fe8)
) at Objects/obmalloc.c:748
#1 0x0000000000041b7c0 in _PyObject_DebugMallocApi (id=111 'o', nbytes=24) at Objects/obmalloc.c:1445
#2 0x0000000000041b717 in _PyObject_DebugMalloc (nbytes=24) at Objects/obmalloc.c:1412
#3 0x0000000000044060a in _PyUnicode_New (length=11) at Objects/unicodeobject.c:346
#4 0x000000000004466aa in PyUnicodeUCS2_DecodeUTF8Stateful (s=0x5c2b8d "__lltrace__", size=11, errors=0x0, consumed=0x0) at Objects/unicodeobject.c:2531
#5 0x00000000000446647 in PyUnicodeUCS2_DecodeUTF8 (s=0x5c2b8d "__lltrace__", size=11, errors=0x0) at Objects/unicodeobject.c:2495
#6 0x00000000000440d1b in PyUnicodeUCS2_FromStringAndSize (u=0x5c2b8d "__lltrace__", size=11) at Objects/unicodeobject.c:551
#7 0x00000000000440d94 in PyUnicodeUCS2_FromString (u=0x5c2b8d "__lltrace__") at Objects/unicodeobject.c:569
#8 0x00000000000584abd in PyDict_GetItemString (v={{'Yuck': <type at remote 0xad4730>, '__builtins__': <module at remote 0x7ffff7fd5ee8>, '__file__': 'Lib/test/crashers/nasty_eq_vs_dict.py', '__package__': None, 'y': <Yuck(i=0) at remote 0xaacd80>, 'dict': {0: 0, 1: 1, 2: 2, 3: 3}, '__cached__': None, '__name__': '__main__', 'z': <Yuck(i=0) at remote 0xaace60>, '__doc__': None}, key=0x5c2b8d "__lltrace__") at Objects/dictobject.c:2171
```

请注意传给 PyDict\_GetItemString 的字典参数被显示为其 `repr()`，而非不透明的 `PyObject *` 指针。该扩展通过为类型 `PyObject *` 的值提供自定义的打印例程来发挥作用。如果你需要访问一个对象的低层级细节，则要将原值投射为适当类型的指针。例如：

```
(gdb) p globals
$1 = {'__builtins__': <module at remote 0x7ffff7fb1868>, '__name__': '__main__', 'ctypes': <module at remote 0x7ffff7f14360>, '__doc__': None, '__package__': None}

(gdb) p *(PyDictObject*)globals
$2 = {ob_refcnt = 3, ob_type = 0x3dbdf85820, ma_fill = 5, ma_used = 5, ma_mask = 7, ma_table = 0x63d0f8, ma_lookup = 0x3dbdc7ea70
<lookdict_string>, ma_smalltable = {{me_hash = 7065186196740147912, me_key = '__builtins__', me_value = <module at remote 0x7ffff7fb1868>}, {me_hash = -368181376027291943, me_key = '__name__', me_value = '__main__'}, {me_hash = 0, me_key = 0x0, me_value = 0x0}, {me_hash = 0, me_key = 0x0, me_value = 0x0}, {me_hash = -9177857982131165996, me_key = 'ctypes', me_value = <module at remote 0x7ffff7f14360>}, {me_hash = -8518757509529533123, me_key = '__doc__', me_value = None}, {me_hash = 0, me_key = 0x0, me_value = 0x0}, {me_hash = 6614918939584953775, me_key = '__package__', me_value = None}}}
```

请注意美化打印并不会实际调用 `repr()`。对于基本类型，它将尝试尽量匹配其结果。

一个可能令人困惑的地方是某些类型的自定义打印效果很像是 GDB 针对标准类型的内置打印形式。例如，针对 Python `int (PyLongObject*)` 的美化打印表示形式与机器层级上常规的整数并无区别：

```
(gdb) p some_machine_integer  
$3 = 42  
  
(gdb) p some_python_integer  
$4 = 42
```

内部结构可通过投射为 `PyLongObject*` 来显示：

```
(gdb) p (PyLongObject*)some_python_integer $5 = {ob_base = {ob_base = {ob_refcnt = 8, ob_type = 0x3dad39f5e0}, ob_size = 1}, ob_digit = {42}}
```

类似的困惑也可能发生于 `str` 类型，这里的输出看起来很像 gdb 针对 `char *` 的内置打印形式：

```
(gdb) p ptr_to_python_str  
$6 = '__builtins__'
```

针对 `str` 实例的美化打印默认使用单引号（就像 Python 字符串的 `repr` 一样）而针对 `char *` 值的标准打印形式使用双引号并且包含一个十六进制的地址：

```
(gdb) p ptr_to_char_star  
$7 = 0x6d72c0 "hello world"
```

同样地，该实现细节可通过投射为 `PyUnicodeObject*` 来显示：

```
(gdb) p *(PyUnicodeObject*)$6  
$8 = {ob_base = {ob_refcnt = 33, ob_type = 0x3dad3a95a0}, length = 12,  
str = 0x7fffff2128500, hash = 7065186196740147912, state = 1, defenc = 0x0}
```

## 3.2 py-list

该扩展添加了一个 `py-list` 命令，它将列出选定的线程中当前帧的 Python 源代码（如果存在）。当前行将以一个”>”来标记：

```
(gdb) py-list  
901      if options.profile:  
902          options.profile = False  
903          profile_me()  
904          return  
905  
>906      u = UI()  
907      if not u.quit:  
908          try:  
909              gtk.main()  
910          except KeyboardInterrupt:  
911              # properly quit on a keyboard interrupt...
```

使用 `py-list START` 从不同的行号开始列出 Python 源代码，而 `py-list START,END` 则从列出指定行范围内的 Python 源代码。

## 3.3 py-up 和 py-down

`py-up` 和 `py-down` 命令类似于 GDB 的常规 `up` 和 `down` 命令，但会尝试在 CPython 帧而不是 C 帧的层级上移动。

GDB 并不总是能够读取相关的帧信息，这取决于编译 CPython 时的优化级别。在内部，这些命令会查找正在执行默认帧求值函数（即 CPython 内部的核心字节码解释器循环）的 C 帧并查找相关 `PyFrameObject *` 的值。

它们将发出线程内的帧编号（在 C 层级上）。

例如：

```
(gdb) py-up
#37 Frame 0x9420b04, for file /usr/lib/python2.6/site-packages/
gnome_sudoku/main.py, line 906, in start_game ()
    u = UI()
(gdb) py-up
#40 Frame 0x948e82c, for file /usr/lib/python2.6/site-packages/
gnome_sudoku/gnome_sudoku.py, line 22, in start_game(main=<module at remote_0xb71b7f4>)
    main.start_game()
(gdb) py-up
Unable to find an older python frame
```

这样我们位于 Python 栈的顶部。

帧编号对应于 GDB 的 backtrace 命令所显示的内容。该命令将跳过未在执行 Python 代码的 C 帧。

向下回退:

```
(gdb) py-down
#37 Frame 0x9420b04, for file /usr/lib/python2.6/site-packages/gnome_sudoku/main.
←py, line 906, in start_game ()
    u = UI()
(gdb) py-down
#34 (unable to read python frame information)
(gdb) py-down
#23 (unable to read python frame information)
(gdb) py-down
#19 (unable to read python frame information)
(gdb) py-down
#14 Frame 0x99262ac, for file /usr/lib/python2.6/site-packages/gnome_sudoku/game_
←selector.py, line 201, in run_swallowed_dialog (self=
←<NewOrSavedGameSelector(new_game_model=<gtk.ListStore at remote 0x98fab44>,_
←puzzle=None, saved_games=[{'gsd.auto_fills': 0, 'tracking': {}, 'trackers': {}},_
←'notes': [], 'saved_at': 1270084485, 'game': '7 8 0 0 0 0 5 6 0 0 9 0 8 0 1 0_
←0 0 4 6 0 0 0 0 7 0 6 5 0 0 0 4 7 9 2 0 0 0 9 0 1 0 0 0 3 9 7 6 0 0 0 1 8 0 6 0_
←0 0 0 2 8 0 0 0 5 0 4 0 6 0 0 2 1 0 0 0 0 4 5\n7 8 0 0 0 0 0 5 6 0 0 9 0 8 0_
←1 0 0 0 4 6 0 0 0 0 0 7 0 6 5 1 8 3 4 7 9 2 0 0 0 9 0 1 0 0 0 3 9 7 6 0 0 0 1 8 0_
←6 0 0 0 0 2 8 0 0 0 5 0 4 0 6 0 0 2 1 0 0 0 0 0 4 5', 'gsd.impossible_hints': 0,
←'timer.__absolute_start_time__': <float at remote 0x984b474>, 'gsd.hints': 0,
←'timer.active_time': <float at remote 0x984b494>, 'timer.total_time': <float at_
←remote 0x984b464>}], dialog=<gtk.Dialog at remote 0x98faaa4>, saved_game_model=
←<gtk.ListStore at remote 0x98fad24>, sudoku_maker=<SudokuMaker(terminated=False,
← played=[], batch_size...>(truncated)
    swallower.run_dialog(self.dialog)
(gdb) py-down
#11 Frame 0x9aead74, for file /usr/lib/python2.6/site-packages/gnome_sudoku/
←dialog_swallower.py, line 48, in run_dialog (self=<SwappableArea(running=<gtk.
←Dialog at remote 0x98faaa4>, main_page=0) at remote 0x98fa6e4>, d=<gtk.Dialog_
←at remote 0x98faaa4>)
    gtk.main()
(gdb) py-down
#8 (unable to read python frame information)
(gdb) py-down
Unable to find a newer python frame
```

现在我们位于 Python 栈的底部。

请注意在 Python 3.12 及更新的版本中，同一个 C 栈帧可被用于多个 Python 栈帧。这意味着 py-up 和 py-down 可以同时移动多个 Python 帧。例如:

```
(gdb) py-up
#6 Frame 0x7ffff7fb62b0, for file /tmp/rec.py, line 5, in recursive_function (n=0)
```

(续下页)

```

time.sleep(5)
#6 Frame 0x7ffff7fb6240, for file /tmp/rec.py, line 7, in recursive_function (n=1)
recursive_function(n-1)
#6 Frame 0x7ffff7fb61d0, for file /tmp/rec.py, line 7, in recursive_function (n=2)
recursive_function(n-1)
#6 Frame 0x7ffff7fb6160, for file /tmp/rec.py, line 7, in recursive_function (n=3)
recursive_function(n-1)
#6 Frame 0x7ffff7fb60f0, for file /tmp/rec.py, line 7, in recursive_function (n=4)
recursive_function(n-1)
#6 Frame 0x7ffff7fb6080, for file /tmp/rec.py, line 7, in recursive_function (n=5)
recursive_function(n-1)
#6 Frame 0x7ffff7fb6020, for file /tmp/rec.py, line 9, in <module> ()
recursive_function(5)
(gdb) py-up
Unable to find an older python frame

```

## 3.4 py-bt

py-bt 命令会尝试显示当前线程的 Python 层级回溯。

例如：

```

(gdb) py-bt
#8 (unable to read python frame information)
#11 Frame 0x9aeadd74, for file /usr/lib/python2.6/site-packages/gnome_sudoku/
    ↵dialog_swaller.py, line 48, in run_dialog (self=<SwappableArea(running=<gtk.
    ↵Dialog at remote 0x98faaa4>, main_page=0) at remote 0x98fa6e4>, d=<gtk.Dialog_
    ↵at remote 0x98faaa4>)
        gtk.main()
#14 Frame 0x99226ac, for file /usr/lib/python2.6/site-packages/gnome_sudoku/game_
    ↵selector.py, line 201, in run_swallowed_dialog (self=
    ↵<NewOrSavedGameSelector(new_game_model=<gtk.ListStore at remote 0x98fab44>,
    ↵puzzle=None, saved_games=[{'gsd.auto_fills': 0, 'tracking': {}, 'trackers': {}},
    ↵'notes': [], 'saved_at': 1270084485, 'game': '7 8 0 0 0 0 0 5 6 0 0 9 0 8 0 1 0
    ↵0 0 4 6 0 0 0 0 7 0 6 5 0 0 0 4 7 9 2 0 0 0 9 0 1 0 0 0 3 9 7 6 0 0 0 1 8 0 6 0
    ↵0 0 0 2 8 0 0 0 5 0 4 0 6 0 0 2 1 0 0 0 0 0 4 5\n7 8 0 0 0 0 0 5 6 0 0 9 0 8 0
    ↵1 0 0 0 4 6 0 0 0 0 7 0 6 5 1 8 3 4 7 9 2 0 0 0 9 0 1 0 0 0 3 9 7 6 0 0 0 1 8 0
    ↵6 0 0 0 0 2 8 0 0 0 5 0 4 0 6 0 0 2 1 0 0 0 0 0 4 5', 'gsd.impossible_hints': 0,
    ↵'timer.__absolute_start_time__': <float at remote 0x984b474>, 'gsd.hints': 0,
    ↵'timer.active_time': <float at remote 0x984b494>, 'timer.total_time': <float at
    ↵remote 0x984b464>]], dialog=<gtk.Dialog at remote 0x98faaa4>, saved_game_model=
    ↵<gtk.ListStore at remote 0x98fad24>, sudoku_maker=<SudokuMaker(terminated=False,
    ↵played=[], batch_size... (truncated)
        swaller.run_dialog(self.dialog)
#19 (unable to read python frame information)
#23 (unable to read python frame information)
#34 (unable to read python frame information)
#37 Frame 0x9420b04, for file /usr/lib/python2.6/site-packages/gnome_sudoku/main.
    ↵py, line 906, in start_game ()
        u = UI()
#40 Frame 0x948e82c, for file /usr/lib/python2.6/site-packages/gnome_sudoku/gnome_
    ↵sudoku.py, line 22, in start_game (main=<module at remote 0xb771b7f4>)
        main.start_game()

```

帧编号对应于 GDB 的 backtrace 命令所显示的内容。

### 3.5 py-print

py-print 命令会查找一个 Python 名称并尝试打印它。它将先在当前线程的 locals 中查找，然后是 globals，最后是 builtins:

```
(gdb) py-print self
local 'self' = <SwappableArea(running=<gtk.Dialog at remote 0x98faaa4>,
main_page=0) at remote 0x98fa6e4>
(gdb) py-print __name__
global '__name__' = 'gnome_sudoku.dialog_swaller'
(gdb) py-print len
builtin 'len' = <built-in function len>
(gdb) py-print scarlet_pimpernel
'scarlet_pimpernel' not found
```

如果当前 C 帧对应多个 Python 帧，则 py-print 只会考虑其中第一个。

### 3.6 py-locals

py-locals 命令会在选定的线程中查找当前 Python 帧内的所有 Python 的 locals，并打印它们的表示形式:

```
(gdb) py-locals
self = <SwappableArea(running=<gtk.Dialog at remote 0x98faaa4>,
main_page=0) at remote 0x98fa6e4>
d = <gtk.Dialog at remote 0x98faaa4>
```

如果当前 C 帧对应多个 Python 帧，同它们的所有 locals 都会被显示:

```
(gdb) py-locals
Locals for recursive_function
n = 0
Locals for recursive_function
n = 1
Locals for recursive_function
n = 2
Locals for recursive_function
n = 3
Locals for recursive_function
n = 4
Locals for recursive_function
n = 5
Locals for <module>
```

## 4 与 GDB 命令一起使用

这些扩展命令是对 GDB 的内置命令的补充。例如，你可以使用 py-bt 显示的帧编号与 frame 命令一起使用以转到所选线程中的特定帧，如下所示:

```
(gdb) py-bt
(output snipped)
#68 Frame 0xaa4560, for file Lib/test/regrtest.py, line 1548, in <module> ()
    main()
(gdb) frame 68
#68 0x0000000004cd1e6 in PyEval_EvalFrameEx (f=Frame 0xaa4560, for file Lib/test/regrtest.
->py, line 1548, in <module> (), throwflag=0) at Python/ceval.c:2665
2665                  x = call_function(&sp, oparg);
(gdb) py-list
1543      # Run the tests in a context manager that temporary changes the CWD to a
1544      # temporary and writable directory. If it's not possible to create or
```

(续下页)

```

1545     # change the CWD, the original CWD will be used. The original CWD is
1546     # available from test_support.SAVEDCWD.
1547     with test_support.temp_cwd(TESTCWD, quiet=True):
1548         main()

```

info threads 命令将向你提供进程内的线程列表，您还可以使用 thread 命令来选择不同的线程：

```

(gdb) info threads
 105 Thread 0x7ffffefa18710 (LWP 10260)  sem_wait () at ../nptl/sysdeps/unix/sysv/linux/x86_
↪64/sem_wait.S:86
 104 Thread 0x7ffffdf5fe710 (LWP 10259)  sem_wait () at ../nptl/sysdeps/unix/sysv/linux/x86_
↪64/sem_wait.S:86
* 1 Thread 0x7ffff7fe2700 (LWP 10145)  0x00000038e46d73e3 in select () at ../sysdeps/unix/
↪syscall-template.S:82

```

你可以使用 thread apply all COMMAND 或 (简短写法 t a a COMMAND) 在所有线程上运行一个命令。配合 py-bt，这将让你在 Python 层级上查看看到每个线程在做什么：

```

(gdb) t a a py-bt

Thread 105 (Thread 0x7ffffefa18710 (LWP 10260)):
#5 Frame 0x7ffffd00019d0, for file /home/david/coding/python-svn/Lib/threading.py, line 155,
↪in _acquire_restore (self=<_RLock(_Verbose__verbose=False, _RLock__owner=140737354016512, _RLock__block=<thread.lock at remote 0x858770>, _RLock__count=1) at remote 0xd7ff40>, count_=owner=(1, 140737213728528), count=1, owner=140737213728528)
    self.__block.acquire()
#8 Frame 0x7ffffac001640, for file /home/david/coding/python-svn/Lib/threading.py, line 269,
↪in wait (self=<_Condition(_Condition__lock=<_RLock(_Verbose__verbose=False, _RLock__owner=140737354016512, _RLock__block=<thread.lock at remote 0x858770>, _RLock__count=1) at remote 0xd7ff40>, acquire=<instancemethod at remote 0xd80260>, _is_owned=<instancemethod at remote 0xd80160>, _release_save=<instancemethod at remote 0xd803e0>, release=<instancemethod at remote 0xd802e0>, _acquire_restore=<instancemethod at remote 0xd7ee60>, _Verbose__verbose=False, _Condition__waiters=[]) at remote 0xd7fd10>, timeout=None, waiter=<thread.lock at remote 0x858a90>, saved_state=(1, 140737213728528))
    self.__acquire_restore(saved_state)
#12 Frame 0x7ffffb8001a10, for file /home/david/coding/python-svn/Lib/test/lock_tests.py,
↪line 348, in f ()
    cond.wait()
#16 Frame 0x7ffffb8001c40, for file /home/david/coding/python-svn/Lib/test/lock_tests.py,
↪line 37, in task (tid=140737213728528)
    f()

Thread 104 (Thread 0x7ffffdf5fe710 (LWP 10259)):
#5 Frame 0x7ffffe4001580, for file /home/david/coding/python-svn/Lib/threading.py, line 155,
↪in _acquire_restore (self=<_RLock(_Verbose__verbose=False, _RLock__owner=140737354016512, _RLock__block=<thread.lock at remote 0x858770>, _RLock__count=1) at remote 0xd7ff40>, count_=owner=(1, 140736940992272), count=1, owner=140736940992272)
    self.__block.acquire()
#8 Frame 0x7ffffc8002090, for file /home/david/coding/python-svn/Lib/threading.py, line 269,
↪in wait (self=<_Condition(_Condition__lock=<_RLock(_Verbose__verbose=False, _RLock__owner=140737354016512, _RLock__block=<thread.lock at remote 0x858770>, _RLock__count=1) at remote 0xd7ff40>, acquire=<instancemethod at remote 0xd80260>, _is_owned=<instancemethod at remote 0xd80160>, _release_save=<instancemethod at remote 0xd803e0>, release=<instancemethod at remote 0xd802e0>, _acquire_restore=<instancemethod at remote 0xd7ee60>, _Verbose__verbose=False, _Condition__waiters=[]) at remote 0xd7fd10>, timeout=None, waiter=<thread.lock at remote 0x858860>, saved_state=(1, 140736940992272))
    self.__acquire_restore(saved_state)
#12 Frame 0x7ffffac001c90, for file /home/david/coding/python-svn/Lib/test/lock_tests.py,
↪line 348, in f ()
    cond.wait()
#16 Frame 0x7ffffac0011c0, for file /home/david/coding/python-svn/Lib/test/lock_tests.py,
↪

```

```
→line 37, in task (tid=140736940992272)
    f()

Thread 1 (Thread 0xfffff7fe2700 (LWP 10145)):
#5 Frame 0xcb5380, for file /home/david/coding/python-svn/Lib/test/lock_tests.py, line 16,
→in _wait ()
    time.sleep(0.01)
#8 Frame 0x7ffd00024a0, for file /home/david/coding/python-svn/Lib/test/lock_tests.py, line
→378, in _check_notify (self=<ConditionTests(_testMethodName='test_notify', _resultForDoCleanups=<TestResult(_original_stdout=<cStringIO.StringO at remote 0xc191e0>, _skipped=[], _mirrorOutput=False, testsRun=39, buffer=False, _original_stderr=<file at remote 0x7fffff7fc6340>, _stdout_buffer=<cStringIO.StringO at remote 0xc9c7f8>, _stderr_buffer=<cStringIO.StringO at remote 0xc9c790>, _moduleSetUpFailed=False, _expectedFailures=[], errors=[], _previousTestClass=<type at remote 0x928310>, _unexpectedSuccesses=[], failures=[], shouldStop=False, failfast=False) at remote 0xc185a0>,
→_threads=(0,), _cleanups=[], _type_equality_funcs={<type at remote 0x7eba00>:
→<instancemethod at remote 0xd750e0>, <type at remote 0x7e7820>: <instancemethod at remote 0xd75160>, <type at remote 0x7e30e0>: <instancemethod at remote 0xd75060>, <type at remote 0x7e7d20>: <instancemethod at remote 0xd751e0>, <type at remote 0x7f19e0... (truncated)
    _wait()
```