

The Python/C API

發  3.10.11

Guido van Rossum
and the Python development team

5 月 24, 2023

Python Software Foundation
Email: docs@python.org

1	簡介	3
1.1	代碼標準	3
1.2	包含文件	3
1.3	有用的宏	4
1.4	對象、類型和引用計數	6
1.4.1	引用計數	6
1.4.2	類型	9
1.5	例外	9
1.6	嵌入式 Python	10
1.7	調試構建	11
2	C API 的穩定性	13
2.1	應用程序二進制接口的穩定版	13
2.1.1	受限 API 的作用域和性能	14
2.1.2	受限 API 警示	14
2.2	平台的考慮	14
2.3	受限 API 的內容	15
3	極高層級 API	39
4	參照計數	43
5	例外處理	45
5.1	打印和清理	45
5.2	拋出異常	46
5.3	發出警告	48
5.4	查詢錯誤指示器	49
5.5	信號處理	50
5.6	例外類	51
5.7	例外物件	52
5.8	Unicode 異常對象	52
5.9	遞歸控制	53
5.10	標準異常	54
5.11	標準警告類別	56
6	工具	57
6.1	作業系統工具	57
6.2	系統函式	59
6.3	行程 (Process) 控制	61
6.4	匯入模組	62
6.5	數據 marshal 操作支持	65

6.6	解析参数并构建值变量	66
6.6.1	解析参数	66
6.6.2	创建变量	71
6.7	字串轉碼與格式化	73
6.8	反射	74
6.9	编解码器注册与支持功能	75
6.9.1	Codec 查找 API	75
6.9.2	用于 Unicode 编码错误处理程序的注册表 API	76
7	抽象物件層 (Abstract Objects Layer)	77
7.1	对象协议	77
7.2	呼叫協定 (Call Protocol)	81
7.2.1	<i>tp_call</i> 協定	81
7.2.2	Vectorcall 協定	81
7.2.3	物件呼叫 API	82
7.2.4	呼叫支援 API	85
7.3	数字协议	85
7.4	序列协议	88
7.5	映射协议	89
7.6	迭代器协议	90
7.7	緩衝協定 (Buffer Protocol)	91
7.7.1	缓冲区结构	92
7.7.2	缓冲区请求的类型	93
7.7.3	复杂数组	95
7.7.4	缓冲区相关函数	96
7.8	舊式緩衝協定 (Buffer Protocol)	97
8	具体的对象层	99
8.1	基礎物件	99
8.1.1	类型对象	99
8.1.2	None 物件	102
8.2	數值物件	102
8.2.1	整數物件	102
8.2.2	Boolean (布林) 物件	105
8.2.3	浮點數 (Floating Point) 物件	106
8.2.4	复数对象	107
8.3	序列物件	108
8.3.1	bytes 对象	108
8.3.2	字节数组对象	110
8.3.3	Unicode 物件與編碼	111
8.3.4	元組 (Tuple) 物件	130
8.3.5	结构序列对象	131
8.3.6	List (串列) 物件	132
8.4	容器物件	133
8.4.1	字典物件	133
8.4.2	集合对象	136
8.5	函式物件	137
8.5.1	函式 (Function) 物件	137
8.5.2	實例方法物件 (Instance Method Objects)	138
8.5.3	方法物件 (Method Objects)	139
8.5.4	Cell 物件	139
8.5.5	代码对象	140
8.6	其他物件	140
8.6.1	檔案 (File) 物件	140
8.6.2	模組物件模組	141
8.6.3	迭代器 (Iterator) 物件	148
8.6.4	Descriptor (描述器) 物件	149
8.6.5	切片物件	149

8.6.6	Ellipsis 对象	151
8.6.7	MemoryView 物件	151
8.6.8	弱参照物件	151
8.6.9	Capsule 对象	152
8.6.10	生成器物件	154
8.6.11	Coroutine (协程) 物件	154
8.6.12	上下文变量对象	154
8.6.13	DateTime 物件	156
8.6.14	类型注解对象	159
9	初始化, 终结和线程	161
9.1	在 Python 初始化之前	161
9.2	全局配置变量	162
9.3	Initializing and finalizing the interpreter	164
9.4	Process-wide parameters	165
9.5	线程状态和全局解释器锁	168
9.5.1	Releasing the GIL from extension code	168
9.5.2	非 Python 创建的线程	169
9.5.3	Cautions about fork()	170
9.5.4	高阶 API	170
9.5.5	Low-level API	172
9.6	子解释器支持	175
9.6.1	错误和警告	176
9.7	异步通知	176
9.8	分析和跟踪	177
9.9	高级调试器支持	178
9.10	线程本地存储支持	178
9.10.1	Thread Specific Storage (TSS) API	179
9.10.2	Thread Local Storage (TLS) API	180
10	Python 初始化配置	181
10.1	范例	181
10.2	PyWideStringList	182
10.3	PyStatus	183
10.4	PyPreConfig	184
10.5	Preinitialize Python with PyPreConfig	185
10.6	PyConfig	186
10.7	Initialization with PyConfig	195
10.8	Isolated Configuration	197
10.9	Python Configuration	197
10.10	Python Path Configuration	197
10.11	Py_RunMain()	199
10.12	Py_GetArgcArgv()	199
10.13	Multi-Phase Initialization Private Provisional API	199
11	記憶體管理	201
11.1	總覽	201
11.2	分配器域	202
11.3	原始内存接口	202
11.4	内存接口	203
11.5	对象分配器	204
11.6	默认内存分配器	205
11.7	自定义内存分配器	205
11.8	Python 内存分配器的调试钩子	207
11.9	pymalloc 分配器	208
11.9.1	自定义 pymalloc Arena 分配器	208
11.10	tracemalloc C API	209
11.11	范例	209

12 对象实现支持	211
12.1 在堆上分配对象	211
12.2 通用物件結構	212
12.2.1 基本的对象类型和宏	212
12.2.2 Implementing functions and methods	214
12.2.3 Accessing attributes of extension types	216
12.3 类型对象	218
12.3.1 快速参考	218
12.3.2 PyTypeObject 定义	223
12.3.3 PyObject 槽位	224
12.3.4 PyVarObject 槽位	225
12.3.5 PyTypeObject 槽	225
12.3.6 Static Types	242
12.3.7 Heap Types	242
12.4 Number Object Structures	243
12.5 Mapping Object Structures	245
12.6 Sequence Object Structures	245
12.7 Buffer Object Structures	246
12.8 Async Object Structures	247
12.9 Slot Type typedefs	248
12.10 範例	249
12.11 使对象类型支持循环垃圾回收	251
12.11.1 控制垃圾回收器状态	253
13 API 和 ABI 版本管理	255
A 術語表	257
B 關於這些☐明文件	271
B.1 Python 文件的貢獻者們	271
C 沿革與授權	273
C.1 軟體沿革	273
C.2 關於存取或以其他方式使用 Python 的合約條款	274
C.2.1 用於 PYTHON 3.10.11 的 PSF 授權合約	274
C.2.2 用於 PYTHON 2.0 的 BEOPEN.COM 授權合約	275
C.2.3 用於 PYTHON 1.6.1 的 CNRI 授權合約	276
C.2.4 用於 PYTHON 0.9.0 至 1.2 的 CWI 授權合約	277
C.2.5 用於 PYTHON 3.10.11 ☐明文件☐程式碼的 ZERO-CLAUSE BSD 授權	277
C.3 被收☐軟體的授權與致謝	277
C.3.1 Mersenne Twister	278
C.3.2 Sockets	278
C.3.3 非同步 socket 服務	279
C.3.4 Cookie 管理	279
C.3.5 執行追☐	280
C.3.6 UUencode 與 UUdecode 函式	280
C.3.7 XML 遠端程序呼叫	281
C.3.8 test_epoll	281
C.3.9 Select kqueue	282
C.3.10 SipHash24	282
C.3.11 strtod 與 dtoa	283
C.3.12 OpenSSL	283
C.3.13 expat	286
C.3.14 libffi	286
C.3.15 zlib	287
C.3.16 cfuhash	287
C.3.17 libmpdec	288
C.3.18 W3C C14N 測試套件	288
C.3.19 Audioop	289

D 版權宣告	291
索引	293

對於想要編寫擴充模組或是嵌入 Python 的 C 和 C++ 程式設計師們，這份手冊記述了可使用的 API（應用程式介面）。在 `extending-index` 中也有相關的內容，它描述了編寫擴充的一般原則，但沒有詳細說明 API 函式。

簡介

Python 的应用编程接口 (API) 使得 C 和 C++ 程序员可以在多个层级上访问 Python 解释器。该 API 在 C++ 中同样可用，但为简化描述，通常将其称为 Python/C API。使用 Python/C API 有两个基本的理由。第一个理由是为了特定目的而编写扩展模块；它们是扩展 Python 解释器功能的 C 模块。这可能是最常见的使用场景。第二个理由是将 Python 用作更大规模应用的组件；这种技巧通常被称为在一个应用中 *embedding* Python。

编写扩展模块的过程相对来说更易于理解，可以通过“菜谱”的形式分步骤介绍。使用某些工具可在一定程度上自动化这一过程。虽然人们在其他应用中嵌入 Python 的做法早已有之，但嵌入 Python 的过程没有编写扩展模块那样方便直观。

许多 API 函数在你嵌入或是扩展 Python 这两种场景下都能发挥作用；此外，大多数嵌入 Python 的应用程序也需要提供自定义扩展，因此在尝试在实际应用中嵌入 Python 之前先熟悉编写扩展应该是个好主意。

1.1 代码标准

如果你想要编写可包含于 CPython 的 C 代码，你 **必须** 遵循在 **PEP 7** 中定义的指导原则和标准。这些指导原则适用于任何你所要扩展的 Python 版本。在编写你自己的第三方扩展模块时可以不必遵循这些规范，除非你准备在日后向 Python 贡献这些模块。

1.2 包含文件

使用 Python/C API 所需要的全部函数、类型和宏定义可通过下面这行语句包含到你的代码之中：

```
#define PY_SSIZE_T_CLEAN
#include <Python.h>
```

这意味着包含以下标准头文件：<stdio.h>，<string.h>，<errno.h>，<limits.h>，<assert.h> 和 <stdlib.h>（如果可用）。

備註： 由于 Python 可能会定义一些能在某些系统上影响标准头文件的预处理器定义，因此在包含任何标准头文件之前，你必须先包含 Python.h。

推荐总是在 `Python.h` 前定义 `PY_SSIZE_T_CLEAN`。查看[解析参数并构建值变量](#)来了解这个宏的更多内容。

`Python.h` 所定义的全部用户可见名称（由包含的标准头文件所定义的除外）都带有前缀 `Py` 或者 `_Py`。以 `_Py` 打头的名称是供 Python 实现内部使用的，不应被扩展编写者使用。结构成员名称没有保留前缀。

備註： 用户代码永远不应该定义以 `Py` 或 `_Py` 开头的名称。这会使读者感到困惑，并危及用户代码对未来 Python 版本的可移植性，这些版本可能会定义以这些前缀之一开头的其他名称。

The header files are typically installed with Python. On Unix, these are located in the directories `prefix/include/pythonversion/` and `exec_prefix/include/pythonversion/`, where `prefix` and `exec_prefix` are defined by the corresponding parameters to Python's **configure** script and `version` is `'%d.%d' % sys.version_info[:2]`. On Windows, the headers are installed in `prefix/include`, where `prefix` is the installation directory specified to the installer.

To include the headers, place both directories (if different) on your compiler's search path for includes. Do *not* place the parent directories on the search path and then use `#include <pythonX.Y/Python.h>`; this will break on multi-platform builds since the platform independent headers under `prefix` include the platform specific headers from `exec_prefix`.

C++ 用户应该注意，尽管 API 是完全使用 C 来定义的，但头文件正确地将入口点声明为 `extern "C"`，因此 API 在 C++ 中使用此 API 不必再做任何特殊处理。

1.3 有用的宏

Python 头文件中定义了一些有用的宏。许多是在靠近它们被使用的地方定义的（例如 `Py_RETURN_NONE`）。其他更为通用的则定义在这里。这里所显示的并不是一个完整的列表。

Py_UNREACHABLE()

这个可以在你有一个设计上无法到达的代码路径时使用。例如，当一个 `switch` 语句中所有可能的值都已被 `case` 子句覆盖了，就可将其用在 `default:` 子句中。当你非常想在某个位置放一个 `assert(0)` 或 `abort()` 调用时也可以用这个。

在 `release` 模式下，该宏帮助编译器优化代码，并避免发出不可到达代码的警告。例如，在 GCC 的 `release` 模式下，该宏使用 `__builtin_unreachable()` 实现。

`Py_UNREACHABLE()` 的一个用法是调用一个不会返回，但却没有声明 `_Py_NO_RETURN` 的函数之后。

如果一个代码路径不太可能是正常代码，但在特殊情况下可以到达，就不能使用该宏。例如，在低内存条件下，或者一个系统调用返回超出预期范围值，诸如此类，最好将错误报告给调用者。如果无法将错误报告给调用者，可以使用 `Py_FatalError()`。

3.7 版新加入。

Py_ABS(x)

回傳 `x` 的絕對值。

3.3 版新加入。

Py_MIN(x, y)

返回 `x` 和 `y` 当中的最小值。

3.3 版新加入。

Py_MAX(x, y)

返回 `x` 和 `y` 当中的最大值。

3.3 版新加入。

Py_STRINGIFY (*x*)

将 *x* 转换为 C 字符串。例如 `Py_STRINGIFY(123)` 返回 `"123"`。

3.4 版新加入。

Py_MEMBER_SIZE (*type*, *member*)

返回结构 (*type*) *member* 的大小，以字节表示。

3.6 版新加入。

Py_CHARMASK (*c*)

参数必须为 `[-128, 127]` 或 `[0, 255]` 范围内的字符或整数类型。这个宏将 *c* 强制转换为 unsigned char 返回。

Py_GETENV (*s*)

与 `getenv(s)` 类似，但是如果命令行上传递了 `-E`，则返回 `NULL`（即如果设置了 `Py_IgnoreEnvironmentFlag`）。

Py_UNUSED (*arg*)

用于函数定义中未使用的参数，从而消除编译器警告。例如：`int func(int a, int Py_UNUSED(b)) { return a; }`。

3.4 版新加入。

Py_DEPRECATED (*version*)

弃用声明。该宏必须放置在符号名称前。

範例：

```
Py_DEPRECATED(3.8) PyAPI_FUNC(int) Py_OldFunction(void);
```

3.8 版更變：添加了 MSVC 支持。

PyDoc_STRVAR (*name*, *str*)

创建一个可以在文档字符串中使用的，名字为 *name* 的变量。如果不和文档字符串一起构建 Python，该值将为空。

如 **PEP 7** 所述，使用 `PyDoc_STRVAR` 作为文档字符串，以支持不和文档字符串一起构建 Python 的情况。

範例：

```
PyDoc_STRVAR(pop_doc, "Remove and return the rightmost element.");

static PyMethodDef deque_methods[] = {
    // ...
    {"pop", (PyCFunction)deque_pop, METH_NOARGS, pop_doc},
    // ...
}
```

PyDoc_STR (*str*)

为给定的字符串输入创建一个文档字符串，或者当文档字符串被禁用时，创建一个空字符串。

如 **PEP 7** 所述，使用 `PyDoc_STR` 指定文档字符串，以支持不和文档字符串一起构建 Python 的情况。

範例：

```
static PyMethodDef sqlite_row_methods[] = {
    {"keys", (PyCFunction)sqlite_row_keys, METH_NOARGS,
     PyDoc_STR("Returns the keys of the row.")},
    {NULL, NULL}
};
```

1.4 对象、类型和引用计数

Most Python/C API functions have one or more arguments as well as a return value of type `PyObject*`. This type is a pointer to an opaque data type representing an arbitrary Python object. Since all Python object types are treated the same way by the Python language in most situations (e.g., assignments, scope rules, and argument passing), it is only fitting that they should be represented by a single C type. Almost all Python objects live on the heap: you never declare an automatic or static variable of type `PyObject`, only pointer variables of type `PyObject*` can be declared. The sole exception are the type objects; since these must never be deallocated, they are typically static `PyTypeObject` objects.

所有 Python 对象（甚至 Python 整数）都有一个 *type* 和一个 *reference count*。对象的类型确定它是什么类型的对象（例如整数、列表或用户定义函数；还有更多，如 `types` 中所述）。对于每个众所周知的类型，都有一个宏来检查对象是否属于该类型；例如，当（且仅当）*a* 所指的是 Python 列表时 `PyList_Check(a)` 为真。

1.4.1 引用计数

引用计数非常重要，因为现代计算机内存（通常十分）有限；它计算有多少不同的地方引用同一个对象。这样的地方可以是某个对象，或者是某个全局（或静态）C 变量，亦或是某个 C 函数的局部变量。当一个对象的引用计数变为 0，释放该对象。如果这个已释放的对象包含其它对象的引用计数，则递减这些对象的引用计数。如果这些对象的引用计数减少为零，则可以依次释放这些对象，依此类推。（这里有一个很明显的问题——对象之间相互引用；目前，解决方案是“不要那样做”。）

总是显式操作引用计数。通常的方法是使用宏 `Py_INCREF()` 来增加一个对象的引用计数，使用宏 `Py_DECREF()` 来减少一个对象的引用计数。宏 `Py_DECREF()` 必须检查引用计数是否为零，然后调用对象的释放器，因此它比 `incrcf` 宏复杂得多。释放器是一个包含在对象类型结构中的函数指针。如果对象是复合对象类型（例如列表），则类型特定的释放器负责递减包含在对象中的其他对象的引用计数，并执行所需的终结。引用计数不会溢出，至少用与虚拟内存中不同内存位置一样多的位用于保存引用计数（即 `sizeof(Py_ssize_t) >= sizeof(void*)`）。因此，引用计数递增是一个简单的操作。

没有必要为每个包含指向对象的指针的局部变量增加对象的引用计数。理论上，当变量指向对象时，对象的引用计数增加 1，当变量超出范围时，对象的引用计数减少 1。但是，这两者相互抵消，所以最后引用计数没有改变。使用引用计数的唯一真正原因是只要我们的变量指向它，就可以防止对象被释放。如果知道至少有一个对该对象的其他引用存活时间至少和我们的变量一样长，则没必要临时增加引用计数。一个典型的情形是，对象作为参数从 Python 中传递给被调用的扩展模块中的 C 函数时，调用机制会保证在调用期间持有对所有参数的引用。

但是，有一个常见的陷阱是从列表中提取一个对象，并将其持有一段时间，而不增加其引用计数。某些操作可能会从列表中删除某个对象，减少其引用计数，并有可能重新分配这个对象。真正的危险是，这个看似无害的操作可能会调用任意 Python 代码——也许有一个代码路径允许控制流从 `Py_DECREF()` 回到用户，因此在复合对象上的操作都存在潜在的风险。

一个安全的方式是始终使用泛型操作（名称以 `PyObject_`，`PyNumber_`，`PySequence_` 或 `PyMapping_` 开头的函数）。这些操作总是增加它们返回的对象的引用计数。这让调用者有责任在获得结果后调用 `Py_DECREF()`。习惯这种方式很简单。

引用计数细节

Python/C API 中函数引用计数行为最好是通过引用所有权来解释。所有权是关联到引用，而不是对象（对象没有所有权：它们总是会被共享）。“获得引用所有权”意味着当不再需要该引用时必须在其上调用 `Py_DECREF`。所有权也可以被转移，这意味着接受该引用所有权的代码当不再需要该引用时必须通过调用 `Py_DECREF()` 或 `Py_XDECREF()` 来最终撤销引用——或是将这个责任转移出去（通常是转给其调用方）。当一个函数将引用所有权转给其调用方时，则称调用方收到了一个新的引用。当所有权未被转移时，则称调用方 借入 该引用。对于 *borrowed reference* 来说不需任何额外操作。

相反地，当调用方函数传入一个对象的引用时，存在两种可能：该函数 窃取 了一个对象的引用，或是没有窃取。窃取引用意味着当你向一个函数传入引用时，该函数会假定它拥有该引用，而你不再对它负有责任。

很少有函数会窃取引用；两个重要的例外是 `PyList_SetItem()` 和 `PyTuple_SetItem()`，它们会窃取对条目的引用（但不是条目所在的元组或列表！）。这些函数被设计为会窃取引用是因为在使用新创建的对象来填充元组或列表时有一个通常的惯例；例如，创建元组 `(1, 2, "three")` 的代码看起来可以是这样的（暂时不要管错误处理；下面会显示更好的代码编写方式）：

```
PyObject *t;

t = PyTuple_New(3);
PyTuple_SetItem(t, 0, PyLong_FromLong(1L));
PyTuple_SetItem(t, 1, PyLong_FromLong(2L));
PyTuple_SetItem(t, 2, PyUnicode_FromString("three"));
```

在这里，`PyLong_FromLong()` 返回了一个新的引用并且它立即被 `PyTuple_SetItem()` 所窃取。当你想要继续使用一个对象而对它的引用将被窃取时，请在调用窃取引用的函数之前使用 `Py_INCREF()` 来抓取另一个引用。

顺便提一下，`PyTuple_SetItem()` 是设置元组条目的唯一方式；`PySequence_SetItem()` 和 `PyObject_SetItem()` 会拒绝这样做因为元组是不可变数据类型。你应当只对你自己创建的元组使用 `PyTuple_SetItem()`。

等价于填充一个列表的代码可以使用 `PyList_New()` 和 `PyList_SetItem()` 来编写。

然而，在实践中，你很少会使用这些创建和填充元组或列表的方式。有一个通用的函数 `Py_BuildValue()` 可以根据 C 值来创建大多数常用对象，由一个格式字符串来指明。例如，上面的两个代码块可以用下面的代码来代替（还会负责错误检测）：

```
PyObject *tuple, *list;

tuple = Py_BuildValue("(iis)", 1, 2, "three");
list = Py_BuildValue("[iis]", 1, 2, "three");
```

使用 `PyObject_SetItem()` 等来处理那些你只是借入引用的条目是更为常见的，例如传给你正在编写的函数的参数。在这种情况下，他们对于引用计数的行为会更为理智，因为你不需要递增引用计数以便你可以将引用计数转出去（“让它被窃取”）。例如，这个函数将一个列表（实例上是任何可变序列）中的所有项设置为一个给定的条目：

```
int
set_all(PyObject *target, PyObject *item)
{
    Py_ssize_t i, n;

    n = PyObject_Length(target);
    if (n < 0)
        return -1;
    for (i = 0; i < n; i++) {
        PyObject *index = PyLong_FromSsize_t(i);
        if (!index)
            return -1;
        if (PyObject_SetItem(target, index, item) < 0) {
            Py_DECREF(index);
            return -1;
        }
        Py_DECREF(index);
    }
    return 0;
}
```

对于函数返回值的情况略有不同。虽然向大多数函数传递一个引用不会改变你对该引用的所有权责任，但许多返回一个引用的函数会给你该引用的所有权。原因很简单：在许多情况下，返回的对象是临时创建的，而你得到的引用是对该对象的唯一引用。因此，返回对象引用的通用函数，如 `PyObject_GetItem()` 和 `PySequence_GetItem()`，将总是返回一个新的引用（调用方将成为该引用的所有者）。

一个需要了解的重点在于你是否拥有一个由函数返回的引用只取决于你所调用的函数 --- 附带物（作为参

数传给函数的对象的类型) 不会带来额外影响! 因此, 如果你使用 `PyList_GetItem()` 从一个列表提取条目, 你并不会拥有其引用 --- 但是如果你使用 `PySequence_GetItem()` (它恰好接受完全相同的参数) 从同一个列表获取同样的条目, 你就会拥有一个对所返回对象的引用。

下面是说明你要如何编写一个函数来计算一个整数列表中条目的示例; 一个是使用 `PyList_GetItem()`, 而另一个是使用 `PySequence_GetItem()`。

```
long
sum_list(PyObject *list)
{
    Py_ssize_t i, n;
    long total = 0, value;
    PyObject *item;

    n = PyList_Size(list);
    if (n < 0)
        return -1; /* Not a list */
    for (i = 0; i < n; i++) {
        item = PyList_GetItem(list, i); /* Can't fail */
        if (!PyLong_Check(item)) continue; /* Skip non-integers */
        value = PyLong_AsLong(item);
        if (value == -1 && PyErr_Occurred())
            /* Integer too big to fit in a C long, bail out */
            return -1;
        total += value;
    }
    return total;
}
```

```
long
sum_sequence(PyObject *sequence)
{
    Py_ssize_t i, n;
    long total = 0, value;
    PyObject *item;
    n = PySequence_Length(sequence);
    if (n < 0)
        return -1; /* Has no length */
    for (i = 0; i < n; i++) {
        item = PySequence_GetItem(sequence, i);
        if (item == NULL)
            return -1; /* Not a sequence, or other failure */
        if (PyLong_Check(item)) {
            value = PyLong_AsLong(item);
            Py_DECREF(item);
            if (value == -1 && PyErr_Occurred())
                /* Integer too big to fit in a C long, bail out */
                return -1;
            total += value;
        }
        else {
            Py_DECREF(item); /* Discard reference ownership */
        }
    }
    return total;
}
```

1.4.2 类型

There are few other data types that play a significant role in the Python/C API; most are simple C types such as `int`, `long`, `double` and `char*`. A few structure types are used to describe static tables used to list the functions exported by a module or the data attributes of a new object type, and another is used to describe the value of a complex number. These will be discussed together with the functions that use them.

type `Py_ssize_t`

Part of the Stable ABI. 一个使得 `sizeof(Py_ssize_t) == sizeof(size_t)` 的有符号整数类型。C99 没有直接定义这样的东西 (`size_t` 是一个无符号整数类型)。请参阅 [PEP 353](#) 了解详情。`PY_SSIZE_T_MAX` 是 `Py_ssize_t` 类型的最大正数值。

1.5 例外

Python 程序员只需要处理特定需要处理的错误异常；未处理的异常会自动传递给调用者，然后传递给调用者的调用者，依此类推，直到他们到达顶级解释器，在那里将它们报告给用户并伴随堆栈回溯。

然而，对于 C 程序员来说，错误检查必须总是显式进行的。Python/C API 中的所有函数都可以引发异常，除非在函数的文档中另外显式声明。一般来说，当一个函数遇到错误时，它会设置一个异常，丢弃它所拥有的任何对象引用，并返回一个错误标示。如果没有说明例外的文档，这个标示将为 `NULL` 或 `-1`，具体取决于函数的返回类型。有少量函数会返回一个布尔真/假结果值，其中假值表示错误。有极少的函数没有显式的错误标示或是具有不明确的返回值，并需要用 `PyErr_Occurred()` 来进行显式的检测。这些例外总是会被明确地记入文档中。

异常状态是在各个线程的存储中维护的（这相当于在一个无线程的应用中使用全局存储）。一个线程可以处在两种状态之一：异常已经发生，或者没有发生。函数 `PyErr_Occurred()` 可以被用来检查此状态：当异常发生时它将返回一个借入的异常类型对象的引用，在其他情况下则返回 `NULL`。有多个函数可以设置异常状态：`PyErr_SetString()` 是最常见的（尽管不是最通用的）设置异常状态的函数，而 `PyErr_Clear()` 可以清除异常状态。

完整的异常状态由三个对象组成（它们都可以为 `NULL`）：异常类型、相应的异常值，以及回溯信息。这些对象的含义与 Python 中 `sys.exc_info()` 的结果相同；然而，它们并不是一样的：Python 对象代表由 Python `try...except` 语句所处理的最后一个异常，而 C 层级的异常状态只在异常被传入到 C 函数或在它们之间传递时存在直至其到达 Python 字节码解释器的主事件循环，该事件循环会负责将其转移至 `sys.exc_info()` 等处。

请注意自 Python 1.5 开始，从 Python 代码访问异常状态的首选的、线程安全的方式是调用函数 `sys.exc_info()`，它将返回 Python 代码的分线程异常状态。此外，这两种访问异常状态的方式的语义都发生了变化因而捕获到异常的函数将保存并恢复其线程的异常状态以保留其调用方的异常状态。这将防止异常处理代码中由一个看起来很无辜的函数覆盖了正在处理的异常所造成的常见错误；它还减少了在回溯由栈帧所引用的对象的往往不被需要的生命其延长。

作为一般的原则，一个调用另一个函数来执行某些任务的函数应当检查被调用的函数是否引发了异常，并在引发异常时将异常状态传递给它调用方。它应当丢弃它所拥有的任何对象引用，并返回一个错误标示，但它不应设置另一个异常——那会覆盖刚引发的异常，并丢失有关错误确切原因的重要信息。

一个检测异常并传递它们的简单例子在上面的 `sum_sequence()` 示例中进行了演示。这个例子恰好在检测到错误时不需要清理所拥有的任何引用。下面的示例函数演示了一些错误清理操作。首先，为了向你提示 Python 的优势，我们展示了等效的 Python 代码：

```
def incr_item(dict, key):
    try:
        item = dict[key]
    except KeyError:
        item = 0
    dict[key] = item + 1
```

下面是对应的闪耀荣光的 C 代码：

```

int
incr_item(PyObject *dict, PyObject *key)
{
    /* Objects all initialized to NULL for Py_XDECREF */
    PyObject *item = NULL, *const_one = NULL, *incremented_item = NULL;
    int rv = -1; /* Return value initialized to -1 (failure) */

    item = PyObject_GetItem(dict, key);
    if (item == NULL) {
        /* Handle KeyError only: */
        if (!PyErr_ExceptionMatches(PyExc_KeyError))
            goto error;

        /* Clear the error and use zero: */
        PyErr_Clear();
        item = PyLong_FromLong(0L);
        if (item == NULL)
            goto error;
    }
    const_one = PyLong_FromLong(1L);
    if (const_one == NULL)
        goto error;

    incremented_item = PyNumber_Add(item, const_one);
    if (incremented_item == NULL)
        goto error;

    if (PyObject_SetItem(dict, key, incremented_item) < 0)
        goto error;
    rv = 0; /* Success */
    /* Continue with cleanup code */

error:
    /* Cleanup code, shared by success and failure path */

    /* Use Py_XDECREF() to ignore NULL references */
    Py_XDECREF(item);
    Py_XDECREF(const_one);
    Py_XDECREF(incremented_item);

    return rv; /* -1 for error, 0 for success */
}

```

这个例子代表了 C 语言中 `goto` 语句一种受到认可的用法！它说明了如何使用 `PyErr_ExceptionMatches()` 和 `PyErr_Clear()` 来处理特定的异常，以及如何使用 `Py_XDECREF()` 来处理可能为 `NULL` 的自有引用（注意名称中的 'X'；`Py_DECREF()` 在遇到 `NULL` 引用时将会崩溃）。重要的一点在于用来保存自有引用的变量要被初始化为 `NULL` 才能发挥作用；类似地，建议的返回值也要被初始化为 `-1`（失败）并且只有在最终执行的调用成功后才会被设置为成功。

1.6 嵌入式 Python

只有 Python 解释器的嵌入方（相对于扩展编写者而言）才需要担心的一项重要任务是它的初始化，可能还有它的最终化。解释器的大多数功能只有在解释器被初始化之后才能被使用。

基本的初始化函数是 `Py_Initialize()`。此函数将初始化已加载模块表，并创建基本模块 `builtins`，`__main__` 和 `sys`。它还将初始化模块搜索路径 (`sys.path`)。

`Py_Initialize()` 不会设置“脚本参数列表” (`sys.argv`)。如果随后将要执行的 Python 代码需要此变量，则必须在调用 `Py_Initialize()` 之后通过调用 `PySys_SetArgvEx(argc, argv, updatepath)` 来显式地设置它。

在大多数系统上（特别是 Unix 和 Windows，虽然在细节上有所不同），`Py_Initialize()` 将根据对标准 Python 解释器可执行文件的位置的最佳猜测来计算模块搜索路径，并设定 Python 库可在相对于 Python 解释器可执行文件的固定位置上找到。特别地，它将相对于在 shell 命令搜索路径（环境变量 `PATH`）上找到的名为 `python` 的可执行文件所在父目录中查找名为 `lib/pythonX.Y` 的目录。

举例来说，如果 Python 可执行文件位于 `/usr/local/bin/python`，它将假定库位于 `/usr/local/lib/pythonX.Y`。（实际上，这个特定路径还将成为“回退”位置，会在当无法在 `PATH` 中找到名为 `python` 的可执行文件时被使用。）用户可以通过设置环境变量 `PYTHONHOME`，或通过设置 `PYTHONPATH` 在标准路径之前插入额外的目录来覆盖此行为。

嵌入的应用程序可以通过在调用 `Py_Initialize()` 之前调用 `Py_SetProgramName(file)` 来改变搜索次序。请注意 `PYTHONHOME` 仍然会覆盖此设置并且 `PYTHONPATH` 仍然会被插入到标准路径之前。需要完全控制权的应用程序必须提供它自己的 `Py_GetPath()`、`Py_GetPrefix()`、`Py_GetExecPrefix()` 和 `Py_GetProgramFullPath()` 实现（这些函数均在 `Modules/getpath.c` 中定义）。

有时，还需要对 Python 进行“反初始化”。例如，应用程序可能想要重新启动（再次调用 `Py_Initialize()`）或者应用程序对 Python 的使用已经完成并想要释放 Python 所分配的内存。这可以通过调用 `Py_FinalizeEx()` 来实现。如果当前 Python 处于已初始化状态则 `Py_IsInitialized()` 函数将返回真值。有关这些函数的更多信息将在之后的章节中给出。请注意 `Py_FinalizeEx()` 不会释放所有由 Python 解释器所分配的内存，例如由扩展模块所分配的内存目前是不会被释放的。

1.7 调试构建

Python 可以附带某些宏来编译以启用对解释器和扩展模块的额外检查。这些检查会给运行时增加大量额外开销因此它们默认未被启用。

A full list of the various types of debugging builds is in the file `Misc/SpecialBuilds.txt` in the Python source distribution. Builds are available that support tracing of reference counts, debugging the memory allocator, or low-level profiling of the main interpreter loop. Only the most frequently used builds will be described in the remainder of this section.

附带定义 `Py_DEBUG` 宏来编译解释器将产生通常所称的 Python 调试编译版。`Py_DEBUG` 在 Unix 编译中启用是通过添加 `--with-pydebug` 到 `./configure` 命令来实现的。它也可通过提供非 Python 专属的 `_DEBUG` 宏来启用。当 `Py_DEBUG` 在 Unix 编译中启用时，编译器优化将被禁用。

除了下文描述的引用计数调试，还会执行额外检查，请参阅 `Python Debug Build`。

定义 `Py_TRACE_REFS` 将启用引用追踪（参见 `configure --with-trace-refs` 选项）。当定义了此宏时，将通过在每个 `PyObject` 上添加两个额外字段来维护一个活动对象的循环双链列表。总的分配量也会被追踪。在退出时，所有现存的引用将被打印出来。（在交互模式下这将在解释器运行每条语句之后发生）。

有关更多详细信息，请参阅 Python 源代码中的 `Misc/SpecialBuilds.txt`。

C API 的稳定性

Python 的 C 语言 API 包含于向下兼容政策 [PEP 387](#) 中。C API 会跟随小版本的发布而发生变化（比如 3.9 到 3.10 的时候），不过大多数变化都是源代码级兼容的，通常只会增加新的 API。已有 API 的修改或删除，只有在废止期过后或修复严重问题时才会进行。

CPython 的应用二进制接口（ABI）可以跨小版本实现前后兼容（只要以同样方式编译；参见下面的[平台的考虑](#)）。因此，用 Python 3.10.0 编译的代码可以在 3.10.8 上运行，反之亦然，但针对 3.9.x 和 3.10.x 则需分别进行编译。

带下划线前缀的是私有 API，如 `_Py_InternalState`，即便是补丁发布版本中也可能不加通知地进行改动。

2.1 应用程序二进制接口的稳定版

Python 3.2 引入了受限 API，Python 的 C API 的一个子集。只使用受限 API 的扩展可以被一次性编译而适用于多个 Python 版本。受限 API 的内容[如下所示](#)。

为了实现这一点，Python 提供了一个稳定 ABI：一个将在各 Python 3.x 版本中保持兼容性的符号集合。稳定 ABI 包含了在受限 API 中暴露的符号，但还包含其他符号—例如，支持旧版受限 API 所需的函数。

（简单起见，本文档只讨论了扩展，但受限 API 和稳定 ABI 对于 API 的所有用法都同样适用—例如，嵌入 Python 等。）

Py_LIMITED_API

请在包括 `Python.h` 之前定义这个宏以选择只使用受限 API，并选择受限 API 的版本。

将 `Py_LIMITED_API` 定义为对应你的扩展所支持的最低 Python 版本的 `PY_VERSION_HEX` 的值。扩展无需重编译即可适用于从指定版本开始的所有 Python 3 发布版，并可使用到该版本为止所引入的受限 API。

不直接使用 `PY_VERSION_HEX` 宏，而是编码一个最小的次要版本（例如 `0x030A0000` 表示 Python 3.10）以便在使用未来的 Python 版本进行编译时保持稳定。

你还可以将 `Py_LIMITED_API` 定义为 3。其效果与 `0x03020000` 相同（即 Python 3.2，引入受限 API 的版本）。

在 Windows 上，使用稳定 ABI 的扩展应当被链接到 `python3.dll` 而不是版本专属的库如 `python39.dll`。

在某些平台上，Python 将查找并载入名称中带有 `abi3` 标签的共享库文件（例如 `mymodule.abi3.so`）。它不会检查这样的扩展是否兼容稳定 ABI。使用方（或其打包工具）需要确保这一些，例如，基于 3.10+ 受限 API 编译的扩展不可被安装于更低版本的 Python 中。

稳定 ABI 中的所有函数都会作为 Python 的共享库中的函数存在，而不仅是作为宏。这使得它们可以在不使用 C 预处理器的语言中使用。

2.1.1 受限 API 的作用域和性能

受限 API 的目标是允许使用在完整 C API 中可用的任何东西，但可能会有性能上的损失。

例如，虽然 `PyList_GetItem()` 是可用的，但其“不安全的”宏版本 `PyList_GET_ITEM()` 则是不可用的。这个宏的运行速度更快因为它可以利用版本专属的列表对象实现细节。

在未定义 `Py_LIMITED_API` 的情况下，某些 C API 函数将由宏来执行内联或替换。定义 `Py_LIMITED_API` 会禁用这样的内联，允许提升 Python 的数据结构稳定性，但有可能降低性能。

通过省略 `Py_LIMITED_API` 定义，可以使基于版本专属的 ABI 来编译受限 API 扩展成为可能。这能提升其在相应 Python 版本上的性能，但也将限制其兼容性。基于 `Py_LIMITED_API` 进行编译将产生一个可在版本专属扩展不可用的场合分发的扩展—例如，针对即将发布的 Python 版本的预发布包。

2.1.2 受限 API 警示

请注意基于 `Py_LIMITED_API` 进行编译 不能完全保证代码兼容受限 API 或稳定 ABI。`Py_LIMITED_API` 仅涵盖了定义，但是一个 API 还包括其他因素，例如预期的语义等。

`Py_LIMITED_API` 不能处理的一个问题是附带在较低 Python 版本中无效的参数调用某个函数。例如，考虑一个接受 `NULL` 作为参数的函数。在 Python 3.9 中，`NULL` 现在会选择一个默认行为，但在 Python 3.8 中，该参数将被直接使用，导致一个 `NULL` 引用被崩溃。类似的参数也适用于结构体的字段。

另一个问题是当定义了 `Py_LIMITED_API` 时某些结构体字段目前不会被隐藏，即使它们是受限 API 的一部分。

出于这些原因，我们建议用要支持的所有 Python 小版本号来测试一个扩展，并最好是用其中最低的版本来编译它。

我们还建议查看所使用 API 的全部文档以检查其是否显式指明为受限 API 的一部分。即使定义了 `Py_LIMITED_API`，少数私有声明还是会出于技术原因（或者甚至是作为程序缺陷在无意中）被暴露出来。

还要注意受限 API 并不必然是稳定的：在 Python 3.8 上用 `Py_LIMITED_API` 编译扩展意味着该扩展能在 Python 3.12 上运行，但它将不一定能用 Python 3.12 编译。特别地，在稳定 ABI 保持稳定的情况下，部分受限 API 可能会被弃用并被移除。

2.2 平台的考虑

ABI 的稳定性不仅取决于 Python，还取决于所使用的编译器、低层库和编译器选项。对于稳定 ABI 的目标来说，这些细节定义了一个“平台”。它们通常会取决于 OS 类型和处理器架构。

确保在特定平台上的所有 Python 版本都以不破坏稳定 ABI 的方式构建是每个特定 Python 分发方的责任。来自 `python.org` 以及许多第三方分发商的 Windows 和 macOS 发布版都必于这种情况。

2.3 受限 API 的内容

目前, 受限 API 包括下面这些项:

- `PyAlter_Check()`
- `PyArg_Parse()`
- `PyArg_ParseTuple()`
- `PyArg_ParseTupleAndKeywords()`
- `PyArg_UnpackTuple()`
- `PyArg_VaParse()`
- `PyArg_VaParseTupleAndKeywords()`
- `PyArg_ValidateKeywordArguments()`
- `PyBaseObject_Type`
- `PyBool_FromLong()`
- `PyBool_Type`
- `PyByteArrayIter_Type`
- `PyByteArray_AsString()`
- `PyByteArray_Concat()`
- `PyByteArray_FromObject()`
- `PyByteArray_FromStringAndSize()`
- `PyByteArray_Resize()`
- `PyByteArray_Size()`
- `PyByteArray_Type`
- `PyBytesIter_Type`
- `PyBytes_AsString()`
- `PyBytes_AsStringAndSize()`
- `PyBytes_Concat()`
- `PyBytes_ConcatAndDel()`
- `PyBytes_DecodeEscape()`
- `PyBytes_FromFormat()`
- `PyBytes_FromFormatV()`
- `PyBytes_FromObject()`
- `PyBytes_FromString()`
- `PyBytes_FromStringAndSize()`
- `PyBytes_Repr()`
- `PyBytes_Size()`
- `PyBytes_Type`
- `PyCFunction`
- `PyCFunctionWithKeywords`
- `PyCFunction_Call()`

- `PyCFunction_GetFlags()`
- `PyCFunction_GetFunction()`
- `PyCFunction_GetSelf()`
- `PyCFunction_New()`
- `PyCFunction_NewEx()`
- `PyCFunction_Type`
- `PyCMethod_New()`
- `PyCallIter_New()`
- `PyCallIter_Type`
- `PyCallable_Check()`
- `PyCapsule_Destructor`
- `PyCapsule_GetContext()`
- `PyCapsule_GetDestructor()`
- `PyCapsule_GetName()`
- `PyCapsule_GetPointer()`
- `PyCapsule_Import()`
- `PyCapsule_IsValid()`
- `PyCapsule_New()`
- `PyCapsule_SetContext()`
- `PyCapsule_SetDestructor()`
- `PyCapsule_SetName()`
- `PyCapsule_SetPointer()`
- `PyCapsule_Type`
- `PyClassMethodDescr_Type`
- `PyCodec_BackslashReplaceErrors()`
- `PyCodec_Decode()`
- `PyCodec_Decoder()`
- `PyCodec_Encode()`
- `PyCodec_Encoder()`
- `PyCodec_IgnoreErrors()`
- `PyCodec_IncrementalDecoder()`
- `PyCodec_IncrementalEncoder()`
- `PyCodec_KnownEncoding()`
- `PyCodec_LookupError()`
- `PyCodec_NameReplaceErrors()`
- `PyCodec_Register()`
- `PyCodec_RegisterError()`
- `PyCodec_ReplaceErrors()`
- `PyCodec_StreamReader()`

- `PyCodec_StreamWriter()`
- `PyCodec_StrictErrors()`
- `PyCodec_Unregister()`
- `PyCodec_XMLCharRefReplaceErrors()`
- `PyComplex_FromDoubles()`
- `PyComplex_ImagAsDouble()`
- `PyComplex_RealAsDouble()`
- `PyComplex_Type`
- `PyDescr_NewClassMethod()`
- `PyDescr_NewGetSet()`
- `PyDescr_NewMember()`
- `PyDescr_NewMethod()`
- `PyDictItems_Type`
- `PyDictIterItem_Type`
- `PyDictIterKey_Type`
- `PyDictIterValue_Type`
- `PyDictKeys_Type`
- `PyDictProxy_New()`
- `PyDictProxy_Type`
- `PyDictRevIterItem_Type`
- `PyDictRevIterKey_Type`
- `PyDictRevIterValue_Type`
- `PyDictValues_Type`
- `PyDict_Clear()`
- `PyDict_Contains()`
- `PyDict_Copy()`
- `PyDict_DelItem()`
- `PyDict_DelItemString()`
- `PyDict_GetItem()`
- `PyDict_GetItemString()`
- `PyDict_GetItemWithError()`
- `PyDict_Items()`
- `PyDict_Keys()`
- `PyDict_Merge()`
- `PyDict_MergeFromSeq2()`
- `PyDict_New()`
- `PyDict_Next()`
- `PyDict_SetItem()`
- `PyDict_SetItemString()`

- `PyDict_Size()`
- `PyDict_Type`
- `PyDict_Update()`
- `PyDict_Values()`
- `PyEllipsis_Type`
- `PyEnum_Type`
- `PyErr_BadArgument()`
- `PyErr_BadInternalCall()`
- `PyErr_CheckSignals()`
- `PyErr_Clear()`
- `PyErr_Display()`
- `PyErr_ExceptionMatches()`
- `PyErr_Fetch()`
- `PyErr_Format()`
- `PyErr_FormatV()`
- `PyErr_GetExcInfo()`
- `PyErr_GivenExceptionMatches()`
- `PyErr_NewException()`
- `PyErr_NewExceptionWithDoc()`
- `PyErr_NoMemory()`
- `PyErr_NormalizeException()`
- `PyErr_Occurred()`
- `PyErr_Print()`
- `PyErr_PrintEx()`
- `PyErr_ProgramText()`
- `PyErr_ResourceWarning()`
- `PyErr_Restore()`
- `PyErr_SetExcFromWindowsErr()`
- `PyErr_SetExcFromWindowsErrWithFilename()`
- `PyErr_SetExcFromWindowsErrWithFilenameObject()`
- `PyErr_SetExcFromWindowsErrWithFilenameObjects()`
- `PyErr_SetExcInfo()`
- `PyErr_SetFromErrno()`
- `PyErr_SetFromErrnoWithFilename()`
- `PyErr_SetFromErrnoWithFilenameObject()`
- `PyErr_SetFromErrnoWithFilenameObjects()`
- `PyErr_SetFromWindowsErr()`
- `PyErr_SetFromWindowsErrWithFilename()`
- `PyErr_SetImportError()`

- `PyErr_SetImportErrorSubclass()`
- `PyErr_SetInterrupt()`
- `PyErr_SetInterruptEx()`
- `PyErr_SetNone()`
- `PyErr_SetObject()`
- `PyErr_SetString()`
- `PyErr_SyntaxLocation()`
- `PyErr_SyntaxLocationEx()`
- `PyErr_WarnEx()`
- `PyErr_WarnExplicit()`
- `PyErr_WarnFormat()`
- `PyErr_WriteUnraisable()`
- `PyEval_AcquireLock()`
- `PyEval_AcquireThread()`
- `PyEval_CallFunction()`
- `PyEval_CallMethod()`
- `PyEval_CallObjectWithKeywords()`
- `PyEval_EvalCode()`
- `PyEval_EvalCodeEx()`
- `PyEval_EvalFrame()`
- `PyEval_EvalFrameEx()`
- `PyEval_GetBuiltins()`
- `PyEval_GetFrame()`
- `PyEval_GetFuncDesc()`
- `PyEval_GetFuncName()`
- `PyEval_GetGlobals()`
- `PyEval_GetLocals()`
- `PyEval_InitThreads()`
- `PyEval_ReleaseLock()`
- `PyEval_ReleaseThread()`
- `PyEval_RestoreThread()`
- `PyEval_SaveThread()`
- `PyEval_ThreadsInitialized()`
- `PyExc_ArithmeticError`
- `PyExc_AssertionError`
- `PyExc_AttributeError`
- `PyExc_BaseException`
- `PyExc_BlockingIOError`
- `PyExc_BrokenPipeError`

- PyExc_BufferError
- PyExc_BytesWarning
- PyExc_ChildProcessError
- PyExc_ConnectionAbortedError
- PyExc_ConnectionError
- PyExc_ConnectionRefusedError
- PyExc_ConnectionResetError
- PyExc_DeprecationWarning
- PyExc_EOFError
- PyExc_EncodingWarning
- PyExc_EnvironmentError
- PyExc_Exception
- PyExc_FileExistsError
- PyExc_FileNotFoundError
- PyExc_FloatingPointError
- PyExc_FutureWarning
- PyExc_GeneratorExit
- PyExc_IOError
- PyExc_ImportError
- PyExc_ImportWarning
- PyExc_IndentationError
- PyExc_IndexError
- PyExc_InterruptedError
- PyExc_IsADirectoryError
- PyExc_KeyError
- PyExc_KeyboardInterrupt
- PyExc_LookupError
- PyExc_MemoryError
- PyExc_ModuleNotFoundError
- PyExc_NameError
- PyExc_NotADirectoryError
- PyExc_NotImplementedError
- PyExc_OSError
- PyExc_OverflowError
- PyExc_PendingDeprecationWarning
- PyExc_PermissionError
- PyExc_ProcessLookupError
- PyExc_RecursionError
- PyExc_ReferenceError

- `PyExc_ResourceWarning`
- `PyExc_RuntimeError`
- `PyExc_RuntimeWarning`
- `PyExc_StopAsyncIteration`
- `PyExc_StopIteration`
- `PyExc_SyntaxError`
- `PyExc_SyntaxWarning`
- `PyExc_SystemError`
- `PyExc_SystemExit`
- `PyExc_TabError`
- `PyExc_TimeoutError`
- `PyExc_TypeError`
- `PyExc_UnboundLocalError`
- `PyExc_UnicodeDecodeError`
- `PyExc_UnicodeEncodeError`
- `PyExc_UnicodeError`
- `PyExc_UnicodeTranslateError`
- `PyExc_UnicodeWarning`
- `PyExc_UserWarning`
- `PyExc_ValueError`
- `PyExc_Warning`
- `PyExc_WindowsError`
- `PyExc_ZeroDivisionError`
- `PyExceptionClass_Name()`
- `PyException_GetCause()`
- `PyException_GetContext()`
- `PyException_GetTraceback()`
- `PyException_SetCause()`
- `PyException_SetContext()`
- `PyException_SetTraceback()`
- `PyFile_FromFd()`
- `PyFile_GetLine()`
- `PyFile_WriteObject()`
- `PyFile_WriteString()`
- `PyFilter_Type`
- `PyFloat_AsDouble()`
- `PyFloat_FromDouble()`
- `PyFloat_FromString()`
- `PyFloat_GetInfo()`

- `PyFloat_GetMax()`
- `PyFloat_GetMin()`
- `PyFloat_Type`
- `PyFrameObject`
- `PyFrame_GetCode()`
- `PyFrame_GetLineNumber()`
- `PyFrozenSet_New()`
- `PyFrozenSet_Type`
- `PyGC_Collect()`
- `PyGC_Disable()`
- `PyGC_Enable()`
- `PyGC_IsEnabled()`
- `PyGILState_Ensure()`
- `PyGILState_GetThisThreadState()`
- `PyGILState_Release()`
- `PyGILState_STATE`
- `PyGetSetDef`
- `PyGetSetDescr_Type`
- `PyImport_AddModule()`
- `PyImport_AddModuleObject()`
- `PyImport_AppendInittab()`
- `PyImport_ExecCodeModule()`
- `PyImport_ExecCodeModuleEx()`
- `PyImport_ExecCodeModuleObject()`
- `PyImport_ExecCodeModuleWithPathnames()`
- `PyImport_GetImporter()`
- `PyImport_GetMagicNumber()`
- `PyImport_GetMagicTag()`
- `PyImport_GetModule()`
- `PyImport_GetModuleDict()`
- `PyImport_Import()`
- `PyImport_ImportFrozenModule()`
- `PyImport_ImportFrozenModuleObject()`
- `PyImport_ImportModule()`
- `PyImport_ImportModuleLevel()`
- `PyImport_ImportModuleLevelObject()`
- `PyImport_ImportModuleNoBlock()`
- `PyImport_ReloadModule()`
- `PyIndex_Check()`

- *PyInterpreterState*
- *PyInterpreterState_Clear()*
- *PyInterpreterState_Delete()*
- *PyInterpreterState_Get()*
- *PyInterpreterState_GetDict()*
- *PyInterpreterState_GetID()*
- *PyInterpreterState_New()*
- *PyIter_Check()*
- *PyIter_Next()*
- *PyIter_Send()*
- *PyListIter_Type*
- *PyListRevIter_Type*
- *PyList_Append()*
- *PyList_AsTuple()*
- *PyList_GetItem()*
- *PyList_GetSlice()*
- *PyList_Insert()*
- *PyList_New()*
- *PyList_Reverse()*
- *PyList_SetItem()*
- *PyList_SetSlice()*
- *PyList_Size()*
- *PyList_Sort()*
- *PyList_Type*
- *PyLongObject*
- *PyLongRangeIter_Type*
- *PyLong_AsDouble()*
- *PyLong_AsLong()*
- *PyLong_AsLongAndOverflow()*
- *PyLong_AsLongLong()*
- *PyLong_AsLongLongAndOverflow()*
- *PyLong_AsSize_t()*
- *PyLong_AsSsize_t()*
- *PyLong_AsUnsignedLong()*
- *PyLong_AsUnsignedLongLong()*
- *PyLong_AsUnsignedLongLongMask()*
- *PyLong_AsUnsignedLongMask()*
- *PyLong_AsVoidPtr()*
- *PyLong_FromDouble()*

- `PyLong_FromLong()`
- `PyLong_FromLongLong()`
- `PyLong_FromSize_t()`
- `PyLong_FromSsize_t()`
- `PyLong_FromString()`
- `PyLong_FromUnsignedLong()`
- `PyLong_FromUnsignedLongLong()`
- `PyLong_FromVoidPtr()`
- `PyLong_GetInfo()`
- `PyLong_Type`
- `PyMap_Type`
- `PyMapping_Check()`
- `PyMapping_GetItemString()`
- `PyMapping_HasKey()`
- `PyMapping_HasKeyString()`
- `PyMapping_Items()`
- `PyMapping_Keys()`
- `PyMapping_Length()`
- `PyMapping_SetItemString()`
- `PyMapping_Size()`
- `PyMapping_Values()`
- `PyMem_Calloc()`
- `PyMem_Free()`
- `PyMem_Malloc()`
- `PyMem_Realloc()`
- `PyMemberDef`
- `PyMemberDescr_Type`
- `PyMemoryView_FromMemory()`
- `PyMemoryView_FromObject()`
- `PyMemoryView_GetContiguous()`
- `PyMemoryView_Type`
- `PyMethodDef`
- `PyMethodDescr_Type`
- `PyModuleDef`
- `PyModuleDef_Base`
- `PyModuleDef_Init()`
- `PyModuleDef_Type`
- `PyModule_AddFunctions()`
- `PyModule_AddIntConstant()`

- `PyModule_AddObject()`
- `PyModule_AddObjectRef()`
- `PyModule_AddStringConstant()`
- `PyModule_AddType()`
- `PyModule_Create2()`
- `PyModule_ExecDef()`
- `PyModule_FromDefAndSpec2()`
- `PyModule_GetDef()`
- `PyModule_GetDict()`
- `PyModule_GetFilename()`
- `PyModule_GetFilenameObject()`
- `PyModule_GetName()`
- `PyModule_GetNameObject()`
- `PyModule_GetState()`
- `PyModule_New()`
- `PyModule_NewObject()`
- `PyModule_SetDocString()`
- `PyModule_Type`
- `PyNumber_Absolute()`
- `PyNumber_Add()`
- `PyNumber_And()`
- `PyNumber_AsSsize_t()`
- `PyNumber_Check()`
- `PyNumber_Divmod()`
- `PyNumber_Float()`
- `PyNumber_FloorDivide()`
- `PyNumber_InPlaceAdd()`
- `PyNumber_InPlaceAnd()`
- `PyNumber_InPlaceFloorDivide()`
- `PyNumber_InPlaceLshift()`
- `PyNumber_InPlaceMatrixMultiply()`
- `PyNumber_InPlaceMultiply()`
- `PyNumber_InPlaceOr()`
- `PyNumber_InPlacePower()`
- `PyNumber_InPlaceRemainder()`
- `PyNumber_InPlaceRshift()`
- `PyNumber_InPlaceSubtract()`
- `PyNumber_InPlaceTrueDivide()`
- `PyNumber_InPlaceXor()`

- `PyNumber_Index()`
- `PyNumber_Invert()`
- `PyNumber_Long()`
- `PyNumber_Lshift()`
- `PyNumber_MatrixMultiply()`
- `PyNumber_Multiply()`
- `PyNumber_Negative()`
- `PyNumber_Or()`
- `PyNumber_Positive()`
- `PyNumber_Power()`
- `PyNumber_Remainder()`
- `PyNumber_Rshift()`
- `PyNumber_Subtract()`
- `PyNumber_ToBase()`
- `PyNumber_TrueDivide()`
- `PyNumber_Xor()`
- `PyOS_AfterFork()`
- `PyOS_AfterFork_Child()`
- `PyOS_AfterFork_Parent()`
- `PyOS_BeforeFork()`
- `PyOS_CheckStack()`
- `PyOS_FSPath()`
- `PyOS_InputHook`
- `PyOS_InterruptOccurred()`
- `PyOS_double_to_string()`
- `PyOS_getsig()`
- `PyOS_mystricmp()`
- `PyOS_mystrnicmp()`
- `PyOS_setsig()`
- `PyOS_sighandler_t`
- `PyOS_snprintf()`
- `PyOS_string_to_double()`
- `PyOS_strtol()`
- `PyOS_strtoul()`
- `PyOS_vsnprintf()`
- `PyObject`
- `PyObject.ob_refcnt`
- `PyObject.ob_type`
- `PyObject_ASCII()`

- `PyObject_AsCharBuffer()`
- `PyObject_AsFileDescriptor()`
- `PyObject_AsReadBuffer()`
- `PyObject_AsWriteBuffer()`
- `PyObject_Bytes()`
- `PyObject_Call()`
- `PyObject_CallFunction()`
- `PyObject_CallFunctionObjArgs()`
- `PyObject_CallMethod()`
- `PyObject_CallMethodObjArgs()`
- `PyObject_CallNoArgs()`
- `PyObject_CallObject()`
- `PyObject_Calloc()`
- `PyObject_CheckReadBuffer()`
- `PyObject_ClearWeakRefs()`
- `PyObject_DelItem()`
- `PyObject_DelItemString()`
- `PyObject_Dir()`
- `PyObject_Format()`
- `PyObject_Free()`
- `PyObject_GC_Del()`
- `PyObject_GC_IsFinalized()`
- `PyObject_GC_IsTracked()`
- `PyObject_GC_Track()`
- `PyObject_GC_UnTrack()`
- `PyObject_GenericGetAttr()`
- `PyObject_GenericGetDict()`
- `PyObject_GenericSetAttr()`
- `PyObject_GenericSetDict()`
- `PyObject_GetAIter()`
- `PyObject_GetAttr()`
- `PyObject_GetAttrString()`
- `PyObject_GetItem()`
- `PyObject_GetIter()`
- `PyObject_HasAttr()`
- `PyObject_HasAttrString()`
- `PyObject_Hash()`
- `PyObject_HashNotImplemented()`
- `PyObject_Init()`

- `PyObject_InitVar()`
- `PyObject_IsInstance()`
- `PyObject_IsSubclass()`
- `PyObject_IsTrue()`
- `PyObject_Length()`
- `PyObject_Malloc()`
- `PyObject_Not()`
- `PyObject_Realloc()`
- `PyObject_Repr()`
- `PyObject_RichCompare()`
- `PyObject_RichCompareBool()`
- `PyObject_SelfIter()`
- `PyObject_SetAttr()`
- `PyObject_SetAttrString()`
- `PyObject_SetItem()`
- `PyObject_Size()`
- `PyObject_Str()`
- `PyObject_Type()`
- `PyProperty_Type`
- `PyRangeIter_Type`
- `PyRange_Type`
- `PyReversed_Type`
- `PySeqIter_New()`
- `PySeqIter_Type`
- `PySequence_Check()`
- `PySequence_Concat()`
- `PySequence_Contains()`
- `PySequence_Count()`
- `PySequence_DelItem()`
- `PySequence_DelSlice()`
- `PySequence_Fast()`
- `PySequence_GetItem()`
- `PySequence_GetSlice()`
- `PySequence_In()`
- `PySequence_InPlaceConcat()`
- `PySequence_InPlaceRepeat()`
- `PySequence_Index()`
- `PySequence_Length()`
- `PySequence_List()`

- `PySequence_Repeat()`
- `PySequence_SetItem()`
- `PySequence_SetSlice()`
- `PySequence_Size()`
- `PySequence_Tuple()`
- `PySetIter_Type`
- `PySet_Add()`
- `PySet_Clear()`
- `PySet_Contains()`
- `PySet_Discard()`
- `PySet_New()`
- `PySet_Pop()`
- `PySet_Size()`
- `PySet_Type`
- `PySlice_AdjustIndices()`
- `PySlice_GetIndices()`
- `PySlice_GetIndicesEx()`
- `PySlice_New()`
- `PySlice_Type`
- `PySlice_Unpack()`
- `PyState_AddModule()`
- `PyState_FindModule()`
- `PyState_RemoveModule()`
- `PyStructSequence_Desc`
- `PyStructSequence_Field`
- `PyStructSequence_GetItem()`
- `PyStructSequence_New()`
- `PyStructSequence_NewType()`
- `PyStructSequence_SetItem()`
- `PySuper_Type`
- `PySys_AddWarnOption()`
- `PySys_AddWarnOptionUnicode()`
- `PySys_AddXOption()`
- `PySys_FormatStderr()`
- `PySys_FormatStdout()`
- `PySys_GetObject()`
- `PySys_GetXOptions()`
- `PySys_HasWarnOptions()`
- `PySys_ResetWarnOptions()`

- `PySys_SetArgv()`
- `PySys_SetArgvEx()`
- `PySys_SetObject()`
- `PySys_SetPath()`
- `PySys_WriteStderr()`
- `PySys_WriteStdout()`
- `PyThreadState`
- `PyThreadState_Clear()`
- `PyThreadState_Delete()`
- `PyThreadState_Get()`
- `PyThreadState_GetDict()`
- `PyThreadState_GetFrame()`
- `PyThreadState_GetID()`
- `PyThreadState_GetInterpreter()`
- `PyThreadState_New()`
- `PyThreadState_SetAsyncExc()`
- `PyThreadState_Swap()`
- `PyThread_GetInfo()`
- `PyThread_ReInitTLS()`
- `PyThread_acquire_lock()`
- `PyThread_acquire_lock_timed()`
- `PyThread_allocate_lock()`
- `PyThread_create_key()`
- `PyThread_delete_key()`
- `PyThread_delete_key_value()`
- `PyThread_exit_thread()`
- `PyThread_free_lock()`
- `PyThread_get_key_value()`
- `PyThread_get_stacksize()`
- `PyThread_get_thread_ident()`
- `PyThread_get_thread_native_id()`
- `PyThread_init_thread()`
- `PyThread_release_lock()`
- `PyThread_set_key_value()`
- `PyThread_set_stacksize()`
- `PyThread_start_new_thread()`
- `PyThread_tss_alloc()`
- `PyThread_tss_create()`
- `PyThread_tss_delete()`

- `PyThread_tss_free()`
- `PyThread_tss_get()`
- `PyThread_tss_is_created()`
- `PyThread_tss_set()`
- `PyTraceBack_Here()`
- `PyTraceBack_Print()`
- `PyTraceBack_Type`
- `PyTupleIter_Type`
- `PyTuple_GetItem()`
- `PyTuple_GetSlice()`
- `PyTuple_New()`
- `PyTuple_Pack()`
- `PyTuple_SetItem()`
- `PyTuple_Size()`
- `PyTuple_Type`
- `PyTypeObject`
- `PyType_ClearCache()`
- `PyType_FromModuleAndSpec()`
- `PyType_FromSpec()`
- `PyType_FromSpecWithBases()`
- `PyType_GenericAlloc()`
- `PyType_GenericNew()`
- `PyType_GetFlags()`
- `PyType_GetModule()`
- `PyType_GetModuleState()`
- `PyType_GetSlot()`
- `PyType_IsSubtype()`
- `PyType_Modified()`
- `PyType_Ready()`
- `PyType_Slot`
- `PyType_Spec`
- `PyType_Type`
- `PyUnicodeDecodeError_Create()`
- `PyUnicodeDecodeError_GetEncoding()`
- `PyUnicodeDecodeError_GetEnd()`
- `PyUnicodeDecodeError_GetObject()`
- `PyUnicodeDecodeError_GetReason()`
- `PyUnicodeDecodeError_GetStart()`
- `PyUnicodeDecodeError_SetEnd()`

- `PyUnicodeDecodeError_SetReason()`
- `PyUnicodeDecodeError_SetStart()`
- `PyUnicodeEncodeError_GetEncoding()`
- `PyUnicodeEncodeError_GetEnd()`
- `PyUnicodeEncodeError_GetObject()`
- `PyUnicodeEncodeError_GetReason()`
- `PyUnicodeEncodeError_GetStart()`
- `PyUnicodeEncodeError_SetEnd()`
- `PyUnicodeEncodeError_SetReason()`
- `PyUnicodeEncodeError_SetStart()`
- `PyUnicodeIter_Type`
- `PyUnicodeTranslateError_GetEnd()`
- `PyUnicodeTranslateError_GetObject()`
- `PyUnicodeTranslateError_GetReason()`
- `PyUnicodeTranslateError_GetStart()`
- `PyUnicodeTranslateError_SetEnd()`
- `PyUnicodeTranslateError_SetReason()`
- `PyUnicodeTranslateError_SetStart()`
- `PyUnicode_Append()`
- `PyUnicode_AppendAndDel()`
- `PyUnicode_AsASCIIString()`
- `PyUnicode_AsCharmapString()`
- `PyUnicode_AsDecodedObject()`
- `PyUnicode_AsDecodedUnicode()`
- `PyUnicode_AsEncodedObject()`
- `PyUnicode_AsEncodedString()`
- `PyUnicode_AsEncodedUnicode()`
- `PyUnicode_AsLatin1String()`
- `PyUnicode_AsMBCSString()`
- `PyUnicode_AsRawUnicodeEscapeString()`
- `PyUnicode_AsUCS4()`
- `PyUnicode_AsUCS4Copy()`
- `PyUnicode_AsUTF16String()`
- `PyUnicode_AsUTF32String()`
- `PyUnicode_AsUTF8AndSize()`
- `PyUnicode_AsUTF8String()`
- `PyUnicode_AsUnicodeEscapeString()`
- `PyUnicode_AsWideChar()`
- `PyUnicode_AsWideCharString()`

- `PyUnicode_BuildEncodingMap()`
- `PyUnicode_Compare()`
- `PyUnicode_CompareWithASCIIString()`
- `PyUnicode_Concat()`
- `PyUnicode_Contains()`
- `PyUnicode_Count()`
- `PyUnicode_Decode()`
- `PyUnicode_DecodeASCII()`
- `PyUnicode_DecodeCharmap()`
- `PyUnicode_DecodeCodePageStateful()`
- `PyUnicode_DecodeFSDefault()`
- `PyUnicode_DecodeFSDefaultAndSize()`
- `PyUnicode_DecodeLatin1()`
- `PyUnicode_DecodeLocale()`
- `PyUnicode_DecodeLocaleAndSize()`
- `PyUnicode_DecodeMBCS()`
- `PyUnicode_DecodeMBCSStateful()`
- `PyUnicode_DecodeRawUnicodeEscape()`
- `PyUnicode_DecodeUTF16()`
- `PyUnicode_DecodeUTF16Stateful()`
- `PyUnicode_DecodeUTF32()`
- `PyUnicode_DecodeUTF32Stateful()`
- `PyUnicode_DecodeUTF7()`
- `PyUnicode_DecodeUTF7Stateful()`
- `PyUnicode_DecodeUTF8()`
- `PyUnicode_DecodeUTF8Stateful()`
- `PyUnicode_DecodeUnicodeEscape()`
- `PyUnicode_EncodeCodePage()`
- `PyUnicode_EncodeFSDefault()`
- `PyUnicode_EncodeLocale()`
- `PyUnicode_FSConverter()`
- `PyUnicode_FSDecoder()`
- `PyUnicode_Find()`
- `PyUnicode_FindChar()`
- `PyUnicode_Format()`
- `PyUnicode_FromEncodedObject()`
- `PyUnicode_FromFormat()`
- `PyUnicode_FromFormatV()`
- `PyUnicode_FromObject()`

- `PyUnicode_FromOrdinal()`
- `PyUnicode_FromString()`
- `PyUnicode_FromStringAndSize()`
- `PyUnicode_FromWideChar()`
- `PyUnicode_GetDefaultEncoding()`
- `PyUnicode_GetLength()`
- `PyUnicode_GetSize()`
- `PyUnicode_InternFromString()`
- `PyUnicode_InternImmortal()`
- `PyUnicode_InternInPlace()`
- `PyUnicode_IsIdentifier()`
- `PyUnicode_Join()`
- `PyUnicode_Partition()`
- `PyUnicode_RPartition()`
- `PyUnicode_RSplit()`
- `PyUnicode_ReadChar()`
- `PyUnicode_Replace()`
- `PyUnicode_Resize()`
- `PyUnicode_RichCompare()`
- `PyUnicode_Split()`
- `PyUnicode_Splitlines()`
- `PyUnicode_Substring()`
- `PyUnicode_Tailmatch()`
- `PyUnicode_Translate()`
- `PyUnicode_Type`
- `PyUnicode_WriteChar()`
- `PyVarObject`
- `PyVarObject.ob_base`
- `PyVarObject.ob_size`
- `PyWeakReference`
- `PyWeakref_GetObject()`
- `PyWeakref_NewProxy()`
- `PyWeakref_NewRef()`
- `PyWrapperDescr_Type`
- `PyWrapper_New()`
- `PyZip_Type`
- `Py_AddPendingCall()`
- `Py_AtExit()`
- `Py_BEGIN_ALLOW_THREADS`

- `Py_BLOCK_THREADS`
- `Py_BuildValue()`
- `Py_BytesMain()`
- `Py_CompileString()`
- `Py_DecRef()`
- `Py_DecodeLocale()`
- `Py_END_ALLOW_THREADS`
- `Py_EncodeLocale()`
- `Py_EndInterpreter()`
- `Py_EnterRecursiveCall()`
- `Py_Exit()`
- `Py_FatalError()`
- `Py_FileSystemDefaultEncodeErrors`
- `Py_FileSystemDefaultEncoding`
- `Py_Finalize()`
- `Py_FinalizeEx()`
- `Py_GenericAlias()`
- `Py_GenericAliasType`
- `Py_GetBuildInfo()`
- `Py_GetCompiler()`
- `Py_GetCopyright()`
- `Py_GetExecPrefix()`
- `Py_GetPath()`
- `Py_GetPlatform()`
- `Py_GetPrefix()`
- `Py_GetProgramFullPath()`
- `Py_GetProgramName()`
- `Py_GetPythonHome()`
- `Py_GetRecursionLimit()`
- `Py_GetVersion()`
- `Py_HasFileSystemDefaultEncoding`
- `Py_IncRef()`
- `Py_Initialize()`
- `Py_InitializeEx()`
- `Py_Is()`
- `Py_IsFalse()`
- `Py_IsInitialized()`
- `Py_IsNone()`
- `Py_IsTrue()`

- *Py_LeaveRecursiveCall()*
- *Py_Main()*
- *Py_MakePendingCalls()*
- *Py_NewInterpreter()*
- *Py_NewRef()*
- *Py_ReprEnter()*
- *Py_ReprLeave()*
- *Py_SetPath()*
- *Py_SetProgramName()*
- *Py_SetPythonHome()*
- *Py_SetRecursionLimit()*
- *Py_UCS4*
- *Py_UNBLOCK_THREADS*
- *Py_UTF8Mode*
- *Py_VaBuildValue()*
- *Py_XNewRef()*
- *Py_intptr_t*
- *Py_ssize_t*
- *Py_uintptr_t*
- *allocfunc*
- *binaryfunc*
- *descrgetfunc*
- *descrsetfunc*
- *destructor*
- *getattrfunc*
- *getattrofunc*
- *getiterfunc*
- *getter*
- *hashfunc*
- *initproc*
- *inquiry*
- *iternextfunc*
- *lenfunc*
- *newfunc*
- *objobjargproc*
- *objobjproc*
- *reprfunc*
- *richcmpfunc*
- *setattrfunc*

- *setattrofunc*
- *setter*
- *ssizeargfunc*
- *ssizeobjargproc*
- *ssizessizeargfunc*
- *ssizessizeobjargproc*
- *symtable*
- *ternaryfunc*
- *traverseproc*
- *unaryfunc*
- *visitproc*

极高层级 API

本章节的函数将允许你执行在文件或缓冲区中提供的 Python 源代码，但它们将不允许你在更细节化的方式与解释器进行交互。

这些函数中有几个可以接受特定的前缀语法符号作为形参。可用的前缀符号有 `Py_eval_input`, `Py_file_input` 以及 `Py_single_input`。这些符号会在接受它们作为形参的函数文档中加以说明。

Note also that several of these functions take `FILE*` parameters. One particular issue which needs to be handled carefully is that the `FILE` structure for different C libraries can be different and incompatible. Under Windows (at least), it is possible for dynamically linked extensions to actually use different libraries, so care should be taken that `FILE*` parameters are only passed to these functions if it is certain that they were created by the same library that the Python runtime is using.

int **Py_Main** (int *argc*, wchar_t ***argv*)

Part of the Stable ABI. 针对标准解释器的主程序。嵌入了 Python 的程序将可使用此程序。所提供的 *argc* 和 *argv* 形参应当与传给 C 程序的 `main()` 函数的形参相同（将根据用户的语言区域转换为）。一个重要的注意事项是参数列表可能会被修改（但参数列表中字符串所指向的内容不会被修改）。如果解释器正常退出（即未引发异常）则返回值将为 0，如果解释器因引发异常而退出则返回 1，或者如果形参列表不能表示有效的 Python 命令行则返回 2。

请注意如果引发了一个在其他场合下未处理的 `SystemExit`，此函数将不会返回 1，而是退出进程，只要 `Py_InspectFlag` 还未被设置。

int **Py_BytesMain** (int *argc*, char ***argv*)

Part of the Stable ABI since version 3.8. 类似于 `Py_Main()` 但 *argv* 是一个包含字节串的数组。

3.8 版新加入。

int **PyRun_AnyFile** (FILE **fp*, const char **filename*)

这是针对下面 `PyRun_AnyFileExFlags()` 的简化版接口，将 *closeit* 设为 0 而将 *flags* 设为 NULL。

int **PyRun_AnyFileFlags** (FILE **fp*, const char **filename*, *PyCompilerFlags* **flags*)

这是针对下面 `PyRun_AnyFileExFlags()` 的简化版接口，将 *closeit* 参数设为 0。

int **PyRun_AnyFileEx** (FILE **fp*, const char **filename*, int *closeit*)

这是针对下面 `PyRun_AnyFileExFlags()` 的简化版接口，将 *flags* 参数设为 NULL。

int **PyRun_AnyFileExFlags** (FILE **fp*, const char **filename*, int *closeit*, *PyCompilerFlags* **flags*)

如果 *fp* 指向一个关联到交互设备（控制台或终端输入或 Unix 伪终端）的文件，则返回 `PyRun_InteractiveLoop()` 的值，否则返回 `PyRun_SimpleFile()` 的结果。*filename* 会使用文件系统的编码格式 (`sys.getfilesystemencoding()`) 来解码。如果 *filename* 为 NULL，此

函数会使用 "???" 作为文件名。如果 *closeit* 为真值，文件会在 `PyRun_SimpleFileExFlags()` 返回之前被关闭。

int `PyRun_SimpleString(const char *command)`

This is a simplified interface to `PyRun_SimpleStringFlags()` below, leaving the `PyCompilerFlags*` argument set to NULL.

int `PyRun_SimpleStringFlags(const char *command, PyCompilerFlags *flags)`

根据 *flags* 参数，在 `__main__` 模块中执行 Python 源代码。如果 `__main__` 尚不存在，它将被创建。成功时返回 0，如果引发异常则返回 -1。如果发生错误，则将无法获得异常信息。对于 *flags* 的含义，请参阅下文。

请注意如果引发了一个在其他场合下未处理的 `SystemExit`，此函数将不会返回 -1，而是退出进程，只要 `Py_InspectFlag` 还未被设置。

int `PyRun_SimpleFile(FILE *fp, const char *filename)`

这是针对下面 `PyRun_SimpleFileExFlags()` 的简化版接口，将 *closeit* 设为 0 而将 *flags* 设为 NULL。

int `PyRun_SimpleFileEx(FILE *fp, const char *filename, int closeit)`

这是针对下面 `PyRun_SimpleFileExFlags()` 的简化版接口，将 *flags* 设为 NULL。

int `PyRun_SimpleFileExFlags(FILE *fp, const char *filename, int closeit, PyCompilerFlags *flags)`

类似于 `PyRun_SimpleStringFlags()`，但 Python 源代码是从 *fp* 读取而不是一个内存中的字符串。*filename* 应为文件名，它将使用 *filesystem encoding and error handler* 来解码。如果 *closeit* 为真值，则文件将在 `PyRun_SimpleFileExFlags()` 返回之前被关闭。

備註： 在 Windows 上，*fp* 应当以二进制模式打开（即 `fopen(filename, "rb")`）。否则，Python 可能无法正确地处理使用 LF 行结束符的脚本文件。

int `PyRun_InteractiveOne(FILE *fp, const char *filename)`

这是针对下面 `PyRun_InteractiveOneFlags()` 的简化版接口，将 *flags* 设为 NULL。

int `PyRun_InteractiveOneFlags(FILE *fp, const char *filename, PyCompilerFlags *flags)`

根据 *flags* 参数读取并执行来自与交互设备相关联的文件的一条语句。用户将得到使用 `sys.ps1` 和 `sys.ps2` 的提示。*filename* 将使用 *filesystem encoding and error handler* 来解码。

当输入被成功执行时返回 0，如果引发异常则返回 -1，或者如果存在解析错误则返回来自作为 Python 的组成部分发布的 `errcode.h` 包括文件的错误代码。（请注意 `errcode.h` 并未被 `Python.h` 所包括，因此如果需要则必须专门地包括。）

int `PyRun_InteractiveLoop(FILE *fp, const char *filename)`

这是针对下面 `PyRun_InteractiveLoopFlags()` 的简化版接口，将 *flags* 设为 NULL。

int `PyRun_InteractiveLoopFlags(FILE *fp, const char *filename, PyCompilerFlags *flags)`

读取并执行来自与交互设备相关联的语句直至到达 EOF。用户将得到使用 `sys.ps1` 和 `sys.ps2` 的提示。*filename* 将使用 *filesystem encoding and error handler* 来解码。当位于 EOF 时将返回 0，或者当失败时将返回一个负数。

int (*`PyOS_InputHook`)(void)

Part of the Stable ABI. 可以被设为指向一个原型为 `int func(void)` 的函数。该函数将在 Python 的解释器提示符即将空闲并等待用户从终端输入时被调用。返回值会被忽略。重载这个钩子可被用来将解释器的提示符集成到其他事件循环中，就像 Python 码中 `Modules/_tkinter.c` 所做的那样。

char (*`PyOS_ReadlineFunctionPointer`)(FILE*, FILE*, const char*)

可以被设为指向一个原型为 `char *func(FILE *stdin, FILE *stdout, char *prompt)` 的函数，重载被用来读取解释器提示符的一行输入的默认函数。该函数被预期为如果字符串 *prompt* 不为 NULL 就输出它，然后从所提供的标准输入文件读取一行输入，并返回结果字符串。例如，`readline` 模块将这个钩子设置为提供行编辑和 `tab` 键补全等功能。

结果必须是一个由 `PyMem_RawMalloc()` 或 `PyMem_RawRealloc()` 分配的字符串，或者如果发生错误则为 NULL。

3.4 版更變: 结果必须由 `PyMem_RawMalloc()` 或 `PyMem_RawRealloc()` 分配, 而不是由 `PyMem_Malloc()` 或 `PyMem_Realloc()` 分配。

PyObject *PyRun_String (**const** char *str, int start, PyObject *globals, PyObject *locals)

Return value: New reference. 这是针对下面 `PyRun_StringFlags()` 的简化版接口, 将 `flags` 设为 `NULL`。

PyObject *PyRun_StringFlags (**const** char *str, int start, PyObject *globals, PyObject *locals, PyCompilerFlags *flags)

Return value: New reference. 在由对象 `globals` 和 `locals` 指定的上下文中执行来自 `str` 的 Python 源代码, 并使用以 `flags` 指定的编译器旗标。 `globals` 必须是一个字典; `locals` 可以是任何实现了映射协议的对象。形参 `start` 指定了应当被用来解析源代码的起始形符。

返回将代码作为 Python 对象执行的结果, 或者如果引发了异常则返回 `NULL`。

PyObject *PyRun_File (FILE *fp, **const** char *filename, int start, PyObject *globals, PyObject *locals)

Return value: New reference. 这是针对下面 `PyRun_FileExFlags()` 的简化版接口, 将 `closeit` 设为 0 并将 `flags` 设为 `NULL`。

PyObject *PyRun_FileEx (FILE *fp, **const** char *filename, int start, PyObject *globals, PyObject *locals, int closeit)

Return value: New reference. 这是针对下面 `PyRun_FileExFlags()` 的简化版接口, 将 `flags` 设为 `NULL`。

PyObject *PyRun_FileFlags (FILE *fp, **const** char *filename, int start, PyObject *globals, PyObject *locals, PyCompilerFlags *flags)

Return value: New reference. 这是针对下面 `PyRun_FileExFlags()` 的简化版接口, 将 `closeit` 设为 0。

PyObject *PyRun_FileExFlags (FILE *fp, **const** char *filename, int start, PyObject *globals, PyObject *locals, int closeit, PyCompilerFlags *flags)

Return value: New reference. 类似于 `PyRun_StringFlags()`, 但 Python 源代码是从 `fp` 读取而不是一个内存中的字符串。 `filename` 应为文件名, 它将使用 *filesystem encoding and error handler* 来解码。如果 `closeit` 为真值, 则文件将在 `PyRun_FileExFlags()` 返回之前被关闭。

PyObject *Py_CompileString (**const** char *str, **const** char *filename, int start)

Return value: New reference. Part of the *Stable ABI*. 这是针对下面 `Py_CompileStringFlags()` 的简化版接口, 将 `flags` 设为 `NULL`。

PyObject *Py_CompileStringFlags (**const** char *str, **const** char *filename, int start, PyCompilerFlags *flags)

Return value: New reference. 这是针对下面 `Py_CompileStringExFlags()` 的简化版接口, 将 `optimize` 设为 -1。

PyObject *Py_CompileStringObject (**const** char *str, PyObject *filename, int start, PyCompilerFlags *flags, int optimize)

Return value: New reference. 解析并编译 `str` 中的 Python 源代码, 返回结果代码对象。开始形符由 `start` 给出; 这可被用来限制可被编译的代码并且应为 `Py_eval_input`, `Py_file_input` 或 `Py_single_input`。由 `filename` 指定的文件名会被用来构造代码对象并可能出现在回溯信息或 `SyntaxError` 异常消息中。如果代码无法被解析或编译则此函数将返回 `NULL`。

整数 `optimize` 指定编译器的优化级别; 值 -1 将选择与 -O 选项相同的解释器优化级别。显式级别为 0 (无优化; `__debug__` 为真值)、1 (断言被移除, `__debug__` 为假值) 或 2 (文档字符串也被移除)。

3.4 版新加入。

PyObject *Py_CompileStringExFlags (**const** char *str, **const** char *filename, int start, PyCompilerFlags *flags, int optimize)

Return value: New reference. 与 `Py_CompileStringObject()` 类似, 但 `filename` 是以 *filesystem encoding and error handler* 解码出的字节串。

3.2 版新加入。

PyObject *PyEval_EvalCode (PyObject *co, PyObject *globals, PyObject *locals)

Return value: New reference. Part of the *Stable ABI*. 这是针对 `PyEval_EvalCodeEx()` 的简化版接口,

只附带代码对象，以及全局和局部变量。其他参数均设为 NULL。

PyObject *PyEval_EvalCodeEx (PyObject *co, PyObject *globals, PyObject *locals, PyObject *const
*args, int argcount, PyObject *const *kws, int kwcount, PyObject
*const *defs, int defcount, PyObject *kwdefs, PyObject *closure)

Return value: New reference. Part of the [Stable ABI](#). 对一个预编译的代码对象求值，为其求值给出特定的环境。此环境由全局变量的字典，局部变量映射对象，参数、关键字和默认值的数组，[仅限关键字](#) 参数的默认值的字典和单元的封闭元组构成。

type PyFrameObject

Part of the [Limited API](#) (as an opaque struct). 用于描述帧对象的 C 对象结构体。此类型的字段可能在任何时候被改变。

PyObject *PyEval_EvalFrame (PyFrameObject *f)

Return value: New reference. Part of the [Stable ABI](#). 对一个执行帧求值。这是对 `PyEval_EvalFrameEx()` 的简化版接口，用于保持向下兼容性。

PyObject *PyEval_EvalFrameEx (PyFrameObject *f, int throwflag)

Return value: New reference. Part of the [Stable ABI](#). 这是 Python 解释运行不带修饰的主函数。与执行帧 `f` 相关联的代码对象将被执行，解释字节码并根据需要执行调用。额外的 `throwflag` 形参基本可以被忽略——如果为真值，则会导致立即抛出一个异常；这会被用于生成器对象的 `throw()` 方法。

3.4 版更變: 该函数现在包含一个调试断言，用以确保不会静默地丢弃活动的异常。

int PyEval_MergeCompilerFlags (PyCompilerFlags *cf)

此函数会修改当前求值帧的旗标，并在成功时返回真值，失败时返回假值。

int Py_eval_input

Python 语法中用于孤立表达式的起始符号；配合 `Py_CompileString()` 使用。

int Py_file_input

Python 语法中用于从文件或其他源读取语句序列的起始符号；配合 `Py_CompileString()` 使用。这是在编译任意长的 Python 源代码时要使用的符号。

int Py_single_input

Python 语法中用于单独语句的起始符号；配合 `Py_CompileString()` 使用。这是用于交互式解释器循环的符号。

struct PyCompilerFlags

这是用来存放编译器旗标的结构体。对于代码仅被编译的情况，它将作为 `int flags` 传入，而对于代码要被执行的情况，它将作为 `PyCompilerFlags *flags` 传入。在这种情况下，`from __future__ import` 可以修改 `flags`。

当 `PyCompilerFlags *flags` 为 NULL 时，`cf_flags` 将被当作等于 0 来处理，而任何 `from __future__ import` 所导致的修改都会被丢弃。

int cf_flags

编译器旗标。

int cf_feature_version

`cf_feature_version` 是 Python 的小版本号。它应当被初始化为 `PY_MINOR_VERSION`。

此字段默认会被忽略，当且仅当在 `cf_flags` 中设置了 `PyCF_ONLY_AST` 旗标它才会被使用。

3.8 版更變: 新增 `cf_feature_version` 欄位。

int CO_FUTURE_DIVISION

这个标志位可在 `flags` 中设置以使得除法运算符 `/` 被解读为 [PEP 238](#) 所规定的“真除法”。

本节介绍的宏被用于管理 Python 对象的引用计数。

void **Py_INCREF** (*PyObject *o*)

增加对象 *o* 的引用计数。

此函数通常被用来将 *borrowed reference* 原地转换为 *strong reference*。 *Py_NewRef()* 函数可被用来创建新的 *strong reference*。

此对象必须不为 NULL；如果你不能确定它不为 NULL，请使用 *Py_XINCREF()*。

void **Py_XINCREF** (*PyObject *o*)

增加对象 *o* 的引用计数。对象可以为 NULL，在此情况下该宏不产生任何效果。

另請見 *Py_XNewRef()*。

*PyObject ****Py_NewRef** (*PyObject *o*)

Part of the Stable ABI since version 3.10. 新建指向一个对象的 *strong reference*：增加对象 *o* 的引用计数并返回对象 *o*。

当不再需要这个 *strong reference* 时，应当在对象上调用 *Py_DECREF()* 来有减少该对象的引用计数。

对象 *o* 必须不为 NULL；如果 *o* 可以为 NULL 则应改用 *Py_XNewRef()*。

舉例來☐：

```
Py_INCREF(obj);
self->attr = obj;
```

可以寫成：

```
self->attr = Py_NewRef(obj);
```

另請參☐ *Py_INCREF()*。

3.10 版新加入。

*PyObject ****Py_XNewRef** (*PyObject *o*)

Part of the Stable ABI since version 3.10. 类似于 *Py_NewRef()*，但对象 *o* 可以为 NULL。

如果对象 *o* 为 NULL，该函数也 · 将返回 NULL。

3.10 版新加入。

void **Py_DECREF** (*PyObject *o*)

减少对象 *o* 的引用计数。

如果引用计数达到零，则会发起调用对象类型的撤销分配函数 (该函数必须不为 NULL)。

此函数通常被用于在退出作用域之前删除一个 *strong reference*。

此对象必须不为 NULL；如果你不能确定它不为 NULL，请使用 *Py_XDECREF()*。

警告： 释放函数可导致任意 Python 代码被发起调用（例如当一个带有 `__del__()` 方法的类实例被释放时就是如此）。虽然此类代码中的异常不会被传播，但被执行的代码能够自由访问所有 Python 全局变量。这意味着任何可通过全局变量获取的对象在 *Py_DECREF()* 被发起调用之前都应当处于完好状态。例如，从一个列表中删除对象的代码应当将被删除对象的引用拷贝到一个临时变量中，更新列表数据结构，然后再为临时变量调用 *Py_DECREF()*。

void **Py_XDECREF** (*PyObject *o*)

减少对象 *o* 的引用计数。对象可以为 NULL，在此情况下该宏不产生任何效果；在其他情况下其效果与 *Py_DECREF()* 相同，并会应用同样的警告。

void **Py_CLEAR** (*PyObject *o*)

减少对象 *o* 的引用计数。对象可以为 NULL，在此情况下该宏不产生任何效果；在其他情况下其效果与 *Py_DECREF()* 相同，区别在于其参数也会被设为 NULL。针对 *Py_DECREF()* 的警告不适用于所传递的对象，因为该宏会细心地使用一个临时变量并在减少其引用计数之前将参数设为 NULL。

每当要减少在垃圾回收期间可能会被遍历的对象的引用计数时，使用该宏是一个好主意。

void **Py_IncRef** (*PyObject *o*)

Part of the Stable ABI. 增加对象 *o* 的引用计数。 *Py_XINCREF()* 的函数版本。它可被用于 Python 的运行时动态嵌入。

void **Py_DecRef** (*PyObject *o*)

Part of the Stable ABI. 增加对象 *o* 的引用计数。 *Py_XDECREF()* 的函数版本。它可被用于 Python 的运行时动态嵌入。

以下函数或宏仅可在解释器核心内部使用： *_Py_Dealloc()*， *_Py_ForgetReference()*， *_Py_NewReference()* 以及全局变量 *_Py_RefTotal*。

例外處理

The functions described in this chapter will let you handle and raise Python exceptions. It is important to understand some of the basics of Python exception handling. It works somewhat like the POSIX `errno` variable: there is a global indicator (per thread) of the last error that occurred. Most C API functions don't clear this on success, but will set it to indicate the cause of the error on failure. Most C API functions also return an error indicator, usually `NULL` if they are supposed to return a pointer, or `-1` if they return an integer (exception: the `PyArg_*` functions return `1` for success and `0` for failure).

具体地说，错误指示器由三个对象指针组成：异常的类型，异常的值，和回溯对象。如果没有错误被设置，这些指针都可以是 `NULL`（尽管一些组合使禁止的，例如，如果异常类型是 `NULL`，你不能有一个非 `NULL` 的回溯）。

当一个函数由于它调用的某个函数失败而必须失败时，通常不会设置错误指示器；它调用的那个函数已经设置了它。而它负责处理错误和清理异常，或在清除其拥有的所有资源后返回（如对象应用或内存分配）。如果不准备处理异常，则不应该正常地继续。如果是由于一个错误返回，那么一定要向调用者表明已经设置了错误。如果错误没有得到处理或小心传播，对 Python/C API 的其它调用可能不会有预期的行为，并且可能会以某种神秘的方式失败。

備註：错误指示器 **不是** `sys.exc_info()` 的执行结果。前者对应尚未捕获的异常（异常还在传播），而后者在捕获异常后返回这个异常（异常已经停止传播）。

5.1 打印和清理

void **PyErr_Clear**()

Part of the Stable ABI. 清除错误指示器。如果没有设置错误指示器，则不会有作用。

void **PyErr_PrintEx**(int *set_sys_last_vars*)

Part of the Stable ABI. 将标准回溯打印到 `sys.stderr` 并清除错误指示器。**除非** 错误是 `SystemExit`，这种情况下不会打印回溯进程，且会退出 Python 进程，并显示 `SystemExit` 实例指定的错误代码。

只有在错误指示器被设置时才需要调用这个函数，否则这会导致错误！

如果 *set_sys_last_vars* 非零，则变量 `sys.last_type`, `sys.last_value` 和 `sys.last_traceback` 将分别设置为打印异常的类型，值和回溯。

void **PyErr_Print** ()

Part of the Stable ABI. `PyErr_PrintEx(1)` 的 名。

void **PyErr_WriteUnraisable** (*PyObject* *obj)

Part of the Stable ABI. 使用当前异常和 *obj* 参数调用 `sys.unraisablehook()`。

当设置了异常，但解释器不可能实际地触发异常时，这个实用函数向 `sys.stderr` 打印一个警告信息。例如，当 `__del__()` 方法中发生异常时使用这个函数。

该函数使用单个参数 *obj* 进行调用，该参数标识发生不可触发异常的上下文。如果可能，*obj* 的报告将打印在警告消息中。

调用此函数时必须设置一个异常。

5.2 抛出异常

这些函数可帮助你设置当前线程的错误指示器。为了方便起见，一些函数将始终返回 `NULL` 指针，以便于 `return` 语句。

void **PyErr_SetString** (*PyObject* *type, const char *message)

Part of the Stable ABI. 这是设置错误标记最常用的方式。第一个参数指定异常类型；它通常为某个标准异常，例如 `PyExc_RuntimeError`。你不需要增加它的引用计数。第二个参数是错误消息；它是用 `'utf-8'` 解码的。

void **PyErr_SetObject** (*PyObject* *type, *PyObject* *value)

Part of the Stable ABI. 此函数类似于 `PyErr_SetString()`，但是允许你为异常的“值”指定任意一个 Python 对象。

PyObject ***PyErr_Format** (*PyObject* *exception, const char *format, ...)

Return value: Always NULL. Part of the Stable ABI. 这个函数设置了一个错误指示器并且返回了 `NULL`，*exception* 应当是一个 Python 中的异常类。*format* 和随后的形参会帮助格式化这个错误的信息；它们与 `PyUnicode_FromFormat()` 有着相同的含义和值。*format* 是一个 ASCII 编码的字符串。

PyObject ***PyErr_FormatV** (*PyObject* *exception, const char *format, va_list vargs)

Return value: Always NULL. Part of the Stable ABI since version 3.5. 和 `PyErr_Format()` 相同，但它接受一个 *va_list* 类型的参数而不是可变数量的参数集。

3.5 版新加入。

void **PyErr_SetNone** (*PyObject* *type)

Part of the Stable ABI. 这是 `PyErr_SetObject(type, Py_None)` 的简写。

int **PyErr_BadArgument** ()

Part of the Stable ABI. 这是 `PyErr_SetString(PyExc_TypeError, message)` 的简写，其中 *message* 指出使用了非法参数调用内置操作。它主要用于内部使用。

PyObject ***PyErr_NoMemory** ()

Return value: Always NULL. Part of the Stable ABI. 这是 `PyErr_SetNone(PyExc_MemoryError)` 的简写；它返回 `NULL`，以便当内存耗尽时，对象分配函数可以写 `return PyErr_NoMemory()`；。

PyObject ***PyErr_SetFromErrno** (*PyObject* *type)

Return value: Always NULL. Part of the Stable ABI. 这是个便捷函数，当 C 库函数返回错误并设置 `errno` 时，这个函数会触发异常。它构造一个元组对象，其第一项是整数值 `errno`，第二项是相应的错误消息（从 `strerror()` 获取），然后调用 `PyErr_SetObject(type, object)`。在 Unix 上，当 `errno` 值是 `EINTR`，即中断的系统调用时，这个函数会调用 `PyErr_CheckSignals()`，如果设置了错误指示器，则将其设置为该值。该函数永远返回 `NULL`，因此当系统调用返回错误时，围绕系统调用的包装函数可以写成 `return PyErr_SetFromErrno(type);`。

PyObject ***PyErr_SetFromErrnoWithFilenameObject** (*PyObject* *type, *PyObject* *filenameObject)

Return value: Always NULL. Part of the Stable ABI. 类似于 `PyErr_SetFromErrno()`，附加的行为

是如果 `filenameObject` 不为 `NULL`，它将作为第三个参数传递给 `type` 的构造函数。举个例子，在 `OSError` 异常中，`filenameObject` 将用来定义异常实例的 `filename` 属性。

PyObject *PyErr_SetFromErrnoWithFilenameObjects (PyObject *type, PyObject *filenameObject, PyObject *filenameObject2)

Return value: Always `NULL`. Part of the [Stable ABI](#) since version 3.7. 类似于 `PyErr_SetFromErrnoWithFilenameObject()`，但接受第二个 `filename` 对象，用于当一个接受两个 `filename` 的函数失败时触发错误。

3.4 版新加入。

PyObject *PyErr_SetFromErrnoWithFilename (PyObject *type, const char *filename)

Return value: Always `NULL`. Part of the [Stable ABI](#). 类似于 `PyErr_SetFromErrnoWithFilenameObject()`，但文件名以 C 字符串形式给出。 `filename` 是用 *filesystem encoding and error handler* 解码的。

PyObject *PyErr_SetFromWindowsError (int ierr)

Return value: Always `NULL`. Part of the [Stable ABI](#) on Windows since version 3.7. This is a convenience function to raise `WindowsError`. If called with `ierr` of 0, the error code returned by a call to `GetLastError()` is used instead. It calls the Win32 function `FormatMessage()` to retrieve the Windows description of error code given by `ierr` or `GetLastError()`, then it constructs a tuple object whose first item is the `ierr` value and whose second item is the corresponding error message (gotten from `FormatMessage()`), and then calls `PyErr_SetObject(PyExc_WindowsError, object)`. This function always returns `NULL`.

適用：Windows。

PyObject *PyErr_SetExcFromWindowsError (PyObject *type, int ierr)

Return value: Always `NULL`. Part of the [Stable ABI](#) on Windows since version 3.7. 类似于 `PyErr_SetFromWindowsError()`，额外的参数指定要触发的异常类型。

適用：Windows。

PyObject *PyErr_SetFromWindowsErrorWithFilename (int ierr, const char *filename)

Return value: Always `NULL`. Part of the [Stable ABI](#) on Windows since version 3.7. 类似于 `PyErr_SetFromWindowsErrorWithFilenameObject()`，但是 `filename` 是以 C 字符串形式给出的。 `filename` 是从文件系统编码 (`os.fsdecode()`) 解码出来的。

適用：Windows。

PyObject *PyErr_SetExcFromWindowsErrorWithFilenameObject (PyObject *type, int ierr, PyObject *filename)

Return value: Always `NULL`. Part of the [Stable ABI](#) on Windows since version 3.7. 类似于 `PyErr_SetFromWindowsErrorWithFilenameObject()`，额外参数指定要触发的异常类型。

適用：Windows。

PyObject *PyErr_SetExcFromWindowsErrorWithFilenameObjects (PyObject *type, int ierr, PyObject *filename, PyObject *filename2)

Return value: Always `NULL`. Part of the [Stable ABI](#) on Windows since version 3.7. 类似于 `PyErr_SetExcFromWindowsErrorWithFilenameObject()`，但是接受第二个 `filename` 对象。

適用：Windows。

3.4 版新加入。

PyObject *PyErr_SetExcFromWindowsErrorWithFilename (PyObject *type, int ierr, const char *filename)

Return value: Always `NULL`. Part of the [Stable ABI](#) on Windows since version 3.7. 类似于 `PyErr_SetFromWindowsErrorWithFilename()`，额外参数指定要触发的异常类型。

適用：Windows。

PyObject *PyErr_SetImportError (PyObject *msg, PyObject *name, PyObject *path)

Return value: Always `NULL`. Part of the [Stable ABI](#) since version 3.7. 这是触发 `ImportError` 的便捷函

数。*msg* 将被设为异常的消息字符串。*name* 和 *path* , (都可以为 NULL), 将用来被设置 ImportError 对应的属性 *name* 和 *path*。

3.3 版新加入。

PyObject *PyErr_SetImportErrorSubclass (*PyObject* *exception, *PyObject* *msg, *PyObject* *name, *PyObject* *path)

Return value: Always NULL. Part of the [Stable ABI](#) since version 3.6. 和 `PyErr_SetImportError()` 很类似, 但这个函数允许指定一个 ImportError 的子类来触发。

3.6 版新加入。

void PyErr_SyntaxLocationObject (*PyObject* *filename, int lineno, int col_offset)

设置当前异常的文件, 行和偏移信息。如果当前异常不是 SyntaxError, 则它设置额外的属性, 使异常打印子系统认为异常是 SyntaxError。

3.4 版新加入。

void PyErr_SyntaxLocationEx (const char *filename, int lineno, int col_offset)

Part of the [Stable ABI](#) since version 3.7. 类似于 `PyErr_SyntaxLocationObject()`, 但 *filename* 是用 *filesystem encoding and error handler* 解码的字节串。

3.2 版新加入。

void PyErr_SyntaxLocation (const char *filename, int lineno)

Part of the [Stable ABI](#). 类似于 `PyErr_SyntaxLocationEx()`, 但省略了 *col_offset* parameter 形参。

void PyErr_BadInternalCall ()

Part of the [Stable ABI](#). 这是 `PyErr_SetString(PyExc_SystemError, message)` 的缩写, 其中 *message* 表示使用了非法参数调用内部操作 (例如, Python/C API 函数)。它主要用于内部使用。

5.3 发出警告

这些函数可以从 C 代码中发出警告。它们仿照了由 Python 模块 warnings 导出的那些函数。它们通常向 `sys.stderr` 打印一条警告信息; 当然, 用户也有可能已经指定将警告转换为错误, 在这种情况下, 它们将触发异常。也有可能由于警告机制出现问题, 使得函数触发异常。如果没有触发异常, 返回值为 0; 如果触发异常, 返回值为 -1。(无法确定是否实际打印了警告信息, 也无法确定异常触发的原因。这是故意为之)。如果触发了异常, 调用者应该进行正常的异常处理 (例如, `Py_DECREF()` 持有引用并返回一个错误值)。

int PyErr_WarnEx (*PyObject* *category, const char *message, *Py_ssize_t* stack_level)

Part of the [Stable ABI](#). 发出一个警告信息。参数 *category* 是一个警告类别 (见下面) 或 NULL; *message* 是一个 UTF-8 编码的字符串。*stack_level* 是一个给出栈帧数量的正数; 警告将从该栈帧中当前正在执行的代码行发出。*stack_level* 为 1 的是调用 `PyErr_WarnEx()` 的函数, 2 是在此之上的函数, 以此类推。

警告类别必须是 PyExc_Warning 的子类, PyExc_Warning 是 PyExc_Exception 的子类; 默认警告类别是 PyExc_RuntimeWarning。标准 Python 警告类别作为全局变量可用, 所有其名称见 [标准警告类别](#)。

有关警告控制的信息, 参见模块文档 warnings 和命令行文档中的 -W 选项。没有用于警告控制的 C API。

int PyErr_WarnExplicitObject (*PyObject* *category, *PyObject* *message, *PyObject* *filename, int lineno, *PyObject* *module, *PyObject* *registry)

发出一个对所有警告属性进行显式控制的警告消息。这是位于 Python 函数 warnings.warn_explicit() 外层的直接包装; 请查看其文档了解详情。*module* 和 *registry* 参数可被设为 NULL 以得到相关文档所描述的默认效果。

3.4 版新加入。

int PyErr_WarnExplicit (*PyObject* *category, **const** char *message, **const** char *filename, int lineno, **const** char *module, *PyObject* *registry)
Part of the Stable ABI. 类似于 `PyErr_WarnExplicitObject()` 不过 `message` 和 `module` 是 UTF-8 编码的字符串，而 `filename` 是由 *filesystem encoding and error handler* 解码的。

int PyErr_WarnFormat (*PyObject* *category, *Py_ssize_t* stack_level, **const** char *format, ...)
Part of the Stable ABI. 类似于 `PyErr_WarnEx()` 的函数，但使用 `PyUnicode_FromFormat()` 来格式化警告消息。`format` 是使用 ASCII 编码的字符串。

3.2 版新加入。

int PyErr_ResourceWarning (*PyObject* *source, *Py_ssize_t* stack_level, **const** char *format, ...)
Part of the Stable ABI since version 3.6. 类似于 `PyErr_WarnFormat()` 的函数，但 `category` 是 `ResourceWarning` 并且它会将 `source` 传给 `warnings.WarningMessage()`。

3.6 版新加入。

5.4 查询错误指示器

PyObject ***PyErr_Occurred** ()

Return value: Borrowed reference. Part of the Stable ABI. Test whether the error indicator is set. If set, return the exception type (the first argument to the last call to one of the `PyErr_Set*` functions or to `PyErr_Restore()`). If not set, return NULL. You do not own a reference to the return value, so you do not need to `Py_DECREF()` it.

呼叫者必须持有 GIL。

備註： 不要将返回值与特定的异常进行比较；请改为使用 `PyErr_ExceptionMatches()`，如下所示。（比较很容易失败因为对于类异常来说，异常可能是一个实例而不是类，或者它可能是预期的异常的一个子类。）

int PyErr_ExceptionMatches (*PyObject* *exc)

Part of the Stable ABI. 等价于 `PyErr_GivenExceptionMatches(PyErr_Occurred(), exc)`。此函数应当只在实际设置了异常时才被调用；如果没有任何异常被引发则将发生非法内存访问。

int PyErr_GivenExceptionMatches (*PyObject* *given, *PyObject* *exc)

Part of the Stable ABI. 如果 `given` 异常与 `exc` 中的异常类型相匹配则返回真值。如果 `exc` 是一个类对象，则当 `given` 是一个子类的实例时也将返回真值。如果 `exc` 是一个元组，则该元组（以及递归的子元组）中的所有异常类型都将被搜索进行匹配。

void PyErr_Fetch (*PyObject* **ptype, *PyObject* **pvalue, *PyObject* **ptraceback)

Part of the Stable ABI. 将错误指示符提取到三个变量中并传递其地址。如果未设置错误指示符，则将三个变量都设为 NULL。如果已设置，则将其清除并且你将得到对所提取的每个对象的引用。值和回溯对象可以为 NULL 即使类型对象不为空。

備註： 此函数通常只被需要捕获异常的代码或需要临时保存和恢复错误指示符的代码所使用，例如：

```
{
    PyObject *type, *value, *traceback;
    PyErr_Fetch(&type, &value, &traceback);

    /* ... code that might produce other errors ... */

    PyErr_Restore(type, value, traceback);
}
```

void **PyErr_Restore** (*PyObject *type, PyObject *value, PyObject *traceback*)

Part of the Stable ABI. 基于三个对象设置错误指示符。如果错误指示符已设置，它将首先被清除。如果三个对象均为 NULL，错误指示器将被清除。请不要传入 NULL 类型和非 NULL 值或回溯。异常类型应当是一个类。请不要传入无效的异常类型或值。（违反这些规则将导致微妙的后续问题。）此调用会带走对每个对象的引用：你必须在调用之前拥有对每个对象的引用且在调用之后你将不再拥有这些引用。（如果你不理解这一点，就不要使用此函数。勿谓言之不预。）

備註： 此函数通常只被需要临时保存和恢复错误指示符的代码所使用。请使用 `PyErr_Fetch()` 来保存当前的错误指示符。

void **PyErr_NormalizeException** (*PyObject **exc, PyObject **val, PyObject **tb*)

Part of the Stable ABI. 在特定情况下，下面 `PyErr_Fetch()` 所返回的值可以是“非正规化的”，即 `*exc` 是一个类对象而 `*val` 不是同一个类的实例。在这种情况下此函数可以被用来实例化类。如果值已经是正规化的，则不做任何操作。实现这种延迟正规化是为了提升性能。

備註： 此函数不会显式地在异常值上设置 `__traceback__` 属性。如果想要适当地设置回溯，还需要以下附加代码片段：

```
if (tb != NULL) {
    PyException_SetTraceback(val, tb);
}
```

void **PyErr_GetExcInfo** (*PyObject **ptype, PyObject **pvalue, PyObject **ptraceback*)

Part of the Stable ABI since version 3.7. 提取异常信息，即从 `sys.exc_info()` 所得到的。这是指一个已被捕获的异常，而不是刚被引发的异常。返回分别指向三个对象的新引用，其中任何一个均可以为 NULL。不会修改异常信息的状态。

備註： 此函数通常不会被需要处理异常的代码所使用。它被使用的场合是在代码需要临时保存并恢复异常状态的时候。请使用 `PyErr_SetExcInfo()` 来恢复或清除异常状态。

3.3 版新加入。

void **PyErr_SetExcInfo** (*PyObject *type, PyObject *value, PyObject *traceback*)

Part of the Stable ABI since version 3.7. 设置异常信息，即从 `sys.exc_info()` 所得到的。这是指一个已被捕获的异常，而不是刚被引发的异常。此函数会偷取对参数的引用。要清空异常状态，请为所有三个参数传入 NULL。对于有关三个参数的一般规则，请参阅 `PyErr_Restore()`。

備註： 此函数通常不会被需要处理异常的代码所使用。它被使用的场合是在代码需要临时保存并恢复异常状态的情况。请使用 `PyErr_GetExcInfo()` 来读取异常状态。

3.3 版新加入。

5.5 信号处理

int **PyErr_CheckSignals** ()

Part of the Stable ABI. 这个函数与 Python 的信号处理交互。

如果在主 Python 解释器下从主线程调用该函数，它将检查是否向进程发送了信号，如果是，则发起调用相应的信号处理句柄。如果支持 `signal` 模块，则可以发起调用以 Python 编写的信号处理句柄。

该函数会尝试处理所有待处理信号，然后返回 0。但是，如果 Python 信号处理句柄引发了异常，则设置错误指示符并且函数将立即返回 -1（这样其他待处理信号可能还没有被处理：它们将在下次发起调用 `PyErr_CheckSignals()` 时被处理）。

如果函数从非主线程调用，或在非主 Python 解释器下调用，则它不执行任何操作并返回 0。
这个函数可以由希望被用户请求（例如按 Ctrl-C）中断的长时间运行的 C 代码调用。

備 F: 针对 SIGINT 的默认 Python 信号处理句柄会引发 KeyboardInterrupt 异常。

void **PyErr_SetInterrupt** ()

Part of the [Stable ABI](#). 模拟一个 SIGINT 信号到达的效果。这等价于 `PyErr_SetInterruptEx(SIGINT)`。

備 F: 此函数是异步信号安全的。它可以不带 [GIL](#) 并由 C 信号处理句柄来调用。

int **PyErr_SetInterruptEx** (int *signum*)

Part of the [Stable ABI](#) since version 3.10. 模拟一个信号到达的效果。当下次 `PyErr_CheckSignals()` 被调用时，将会调用针对指定的信号编号的 Python 信号处理句柄。

此函数可由自行设置信号处理，并希望 Python 信号处理句柄会在请求中断时（例如当用户按下 Ctrl-C 来中断操作时）按照预期被发起调用的 C 代码来调用。

如果给定的信号不是由 Python 来处理的（即被设为 `signal.SIG_DFL` 或 `signal.SIG_IGN`），它将会被忽略。

如果 *signum* 在被允许的信号编号范围之外，将返回 -1。在其他情况下，则返回 0。错误指示符绝不会被此函数所修改。

備 F: 此函数是异步信号安全的。它可以不带 [GIL](#) 并由 C 信号处理句柄来调用。

3.10 版新加入。

int **PySignal_SetWakeupFd** (int *fd*)

这个工具函数指定了一个每当收到信号时将被作为以单个字节的形式写入信号编号的目标的文件描述符。*fd* 必须是非阻塞的。它将返回前一个这样的文件描述符。

设置值 -1 将禁用该特性；这是初始状态。这等价于 Python 中的 `signal.set_wakeup_fd()`，但是没有任何错误检查。*fd* 应当是一个有效的文件描述符。此函数应当只从主线程来调用。

3.5 版更變: 在 Windows 上，此函数现在也支持套接字处理。

5.6 例外類 F

PyObject ***PyErr_NewException** (const char **name*, *PyObject* **base*, *PyObject* **dict*)

Return value: New reference. Part of the [Stable ABI](#). 这个工具函数会创建并返回一个新的异常类。*name* 参数必须为新异常的名称，是 `module.classname` 形式的 C 字符串。*base* 和 *dict* 参数通常为 NULL。这将创建一个派生自 `Exception` 的类对象（在 C 中可以通过 `PyExc_Exception` 访问）。

新类的 `__module__` 属性将被设为 *name* 参数的前半部分（最后一个点号之前），而类名将被设为后半部分（最后一个点号之后）。*base* 参数可被用来指定替代基类；它可以是一个类或是一个由类组成的元组。*dict* 参数可被用来指定一个由类变量和方法组成的字典。

PyObject ***PyErr_NewExceptionWithDoc** (const char **name*, const char **doc*, *PyObject* **base*, *PyObject* **dict*)

Return value: New reference. Part of the [Stable ABI](#). 和 `PyErr_NewException()` 一样，除了可以轻松地为新的异常类一个文档字符串：如果 *doc* 属性非空，它将用作异常类的文档字符串。

3.2 版新加入。

5.7 例外物件

*PyObject ****PyException_GetTraceback** (*PyObject *ex*)

Return value: New reference. Part of the [Stable ABI](#). 将与异常相关联的回溯作为一个新引用返回，可以通过 `__traceback__` 在 Python 中访问。如果没有已关联的回溯，则返回 `NULL`。

int **PyException_SetTraceback** (*PyObject *ex, PyObject *tb*)

Part of the [Stable ABI](#). 将异常关联的回溯设置为 `tb`。使用 “Py_None” 清除它。

*PyObject ****PyException_GetContext** (*PyObject *ex*)

Return value: New reference. Part of the [Stable ABI](#). 将与异常相关联的上下文（在处理 `ex` 的过程中引发的另一个异常实例）作为一个新引用返回，可以通过 `__context__` 在 Python 中访问。如果没有已关联的上下文，则返回 `NULL`。

void **PyException_SetContext** (*PyObject *ex, PyObject *ctx*)

Part of the [Stable ABI](#). 将与异常相关联的上下文设置为 `ctx`。使用 `NULL` 来清空它。没有用来确保 `ctx` 是一个异常实例的类型检查。这将窃取一个指向 `ctx` 的引用。

*PyObject ****PyException_GetCause** (*PyObject *ex*)

Return value: New reference. Part of the [Stable ABI](#). 将与异常相关联的原因（一个异常实例，或是 `None`，由 `raise ... from ...` 设置）作为一个新引用返回，可在 Python 中通过 `__cause__` 来访问。

void **PyException_SetCause** (*PyObject *ex, PyObject *cause*)

Part of the [Stable ABI](#). 将与异常相关联的原因设置为 `cause`。使用 `NULL` 来清空它。它没有用来确保 `cause` 是一个异常实例或 `None` 的类型检查。这将窃取一个指向 `cause` 的引用。

`__suppress_context__` 会被此函数隐式地设为 `True`。

5.8 Unicode 异常对象

下列函数被用于创建和修改来自 C 的 Unicode 异常。

*PyObject ****PyUnicodeDecodeError_Create** (*const char *encoding, const char *object, Py_ssize_t length, Py_ssize_t start, Py_ssize_t end, const char *reason*)

Return value: New reference. Part of the [Stable ABI](#). 创建一个 `UnicodeDecodeError` 对象并附带 `encoding`, `object`, `length`, `start`, `end` 和 `reason` 等属性。`encoding` 和 `reason` 为 UTF-8 编码的字符串。

*PyObject ****PyUnicodeEncodeError_Create** (*const char *encoding, const Py_UNICODE *object, Py_ssize_t length, Py_ssize_t start, Py_ssize_t end, const char *reason*)

Return value: New reference. 创建一个 `UnicodeEncodeError` 对象并附带 `encoding`, `object`, `length`, `start`, `end` 和 `reason`。`encoding` 和 `reason` 都是以 UTF-8 编码的字符串。

3.3 版後已用: 3.11

`Py_UNICODE` 自 Python 3.3 起已被弃用。请迁移至 `PyObject_CallFunction(PyExc_UnicodeEncodeError, "sOnns", ...)`。

*PyObject ****PyUnicodeTranslateError_Create** (*const Py_UNICODE *object, Py_ssize_t length, Py_ssize_t start, Py_ssize_t end, const char *reason*)

Return value: New reference. 创建一个 `UnicodeTranslateError` 对象并附带 `object`, `length`, `start`, `end` 和 `reason`。`reason` 是一个以 UTF-8 编码的字符串。

3.3 版後已用: 3.11

`Py_UNICODE` 自 Python 3.3 起已被弃用。请迁移至 `PyObject_CallFunction(PyExc_UnicodeTranslateError, "Onns", ...)`。

*PyObject ****PyUnicodeDecodeError_GetEncoding** (*PyObject *exc*)

*PyObject ****PyUnicodeEncodeError_GetEncoding** (*PyObject *exc*)

Return value: New reference. Part of the [Stable ABI](#). 返回给定异常对象的 `encoding` 属性

```

PyObject *PyUnicodeDecodeError_GetObject (PyObject *exc)
PyObject *PyUnicodeEncodeError_GetObject (PyObject *exc)
PyObject *PyUnicodeTranslateError_GetObject (PyObject *exc)
    Return value: New reference. Part of the Stable ABI. 返回给定异常对象的 object 属性

int PyUnicodeDecodeError_GetStart (PyObject *exc, Py_ssize_t *start)
int PyUnicodeEncodeError_GetStart (PyObject *exc, Py_ssize_t *start)
int PyUnicodeTranslateError_GetStart (PyObject *exc, Py_ssize_t *start)
    Part of the Stable ABI. 获取给定异常对象的 start 属性并将其放入 *start。start 必须不为 NULL。成功
    时返回 0，失败时返回 -1。

int PyUnicodeDecodeError_SetStart (PyObject *exc, Py_ssize_t start)
int PyUnicodeEncodeError_SetStart (PyObject *exc, Py_ssize_t start)
int PyUnicodeTranslateError_SetStart (PyObject *exc, Py_ssize_t start)
    Part of the Stable ABI. 将给定异常对象的 start 属性设为 start。成功时返回 0，失败时返回 -1。

int PyUnicodeDecodeError_GetEnd (PyObject *exc, Py_ssize_t *end)
int PyUnicodeEncodeError_GetEnd (PyObject *exc, Py_ssize_t *end)
int PyUnicodeTranslateError_GetEnd (PyObject *exc, Py_ssize_t *end)
    Part of the Stable ABI. 获取给定异常对象的 end 属性并将其放入 *end。end 必须不为 NULL。成功时
    返回 0，失败时返回 -1。

int PyUnicodeDecodeError_SetEnd (PyObject *exc, Py_ssize_t end)
int PyUnicodeEncodeError_SetEnd (PyObject *exc, Py_ssize_t end)
int PyUnicodeTranslateError_SetEnd (PyObject *exc, Py_ssize_t end)
    Part of the Stable ABI. 将给定异常对象的 end 属性设为 end。成功时返回 0，失败时返回 -1。

PyObject *PyUnicodeDecodeError_GetReason (PyObject *exc)
PyObject *PyUnicodeEncodeError_GetReason (PyObject *exc)
PyObject *PyUnicodeTranslateError_GetReason (PyObject *exc)
    Return value: New reference. Part of the Stable ABI. 返回给定异常对象的 reason 属性

int PyUnicodeDecodeError_SetReason (PyObject *exc, const char *reason)
int PyUnicodeEncodeError_SetReason (PyObject *exc, const char *reason)
int PyUnicodeTranslateError_SetReason (PyObject *exc, const char *reason)
    Part of the Stable ABI. 将给定异常对象的 reason 属性设为 reason。成功时返回 0，失败时返回 -1。

```

5.9 递归控制

这两个函数提供了一种在 C 层级上进行安全的递归调用的方式，在核心模块与扩展模块中均适用。当递归代码不一定会发起调用 Python 代码（后者会自动跟踪其递归深度）时就需要用到它们。它们对于 *tp_call* 实现来说也无必要因为调用协议会负责递归处理。

```
int Py_EnterRecursiveCall (const char *where)
```

Part of the [Stable ABI](#) since version 3.9. 标记一个递归的 C 层级调用即将被执行的点。

如果定义了 `USE_STACKCHECK`，此函数会使用 `PyOS_CheckStack()` 来检查操作系统堆栈是否溢出。在这种情况下，它将设置一个 `MemoryError` 并返回非零值。

随后此函数将检查是否达到递归限制。如果是的话，将设置一个 `RecursionError` 并返回一个非零值。在其他情况下，则返回零。

where 应为一个 UTF-8 编码的字符串如 "in instance check"，它将与由递归深度限制所导致的 `RecursionError` 消息相拼接。

3.9 版更變: 此函数现在也在受限 API 中可用。

void **Py_LeaveRecursiveCall** (void)

Part of the Stable ABI since version 3.9. 结束一个 `Py_EnterRecursiveCall()`。必须针对 `Py_EnterRecursiveCall()` 的每个成功的发起调用操作执行一次调用。

3.9 版更變: 此函数现在也在受限 API 中可用。

正确地针对容器类型实现 `tp_repr` 需要特别的递归处理。在保护栈之外, `tp_repr` 还需要追踪对象以防止出现循环。以下两个函数将帮助完成此功能。从实际效果来说, 这两个函数是 C 中对应 `reprlib.recursive_repr()` 的等价物。

int **Py_ReprEnter** (*PyObject *object*)

Part of the Stable ABI. 在 `tp_repr` 实现的开头被调用以检测循环。

如果对象已经被处理, 此函数将返回一个正整数。在此情况下 `tp_repr` 实现应当返回一个指明发生循环的字符串对象。例如, `dict` 对象将返回 `{...}` 而 `list` 对象将返回 `[...]`。

如果已达到递归限制则此函数将返回一个负正数。在此情况下 `tp_repr` 实现通常应当返回 `NULL`。

在其他情况下, 此函数将返回零而 `tp_repr` 实现将可正常继续。

void **Py_ReprLeave** (*PyObject *object*)

Part of the Stable ABI. 结束一个 `Py_ReprEnter()`。必须针对每个返回零的 `Py_ReprEnter()` 的发起调用操作调用一次。

5.10 标准异常

All standard Python exceptions are available as global variables whose names are `PyExc_` followed by the Python exception name. These have the type `PyObject*`; they are all class objects. For completeness, here are all the variables:

C 名称	Python 名称	解
<code>PyExc_BaseException</code>	<code>BaseException</code>	1
<code>PyExc_Exception</code>	<code>Exception</code>	1
<code>PyExc_ArithmeticError</code>	<code>ArithmeticError</code>	1
<code>PyExc_AssertionError</code>	<code>AssertionError</code>	
<code>PyExc_AttributeError</code>	<code>AttributeError</code>	
<code>PyExc_BlockingIOError</code>	<code>BlockingIOError</code>	
<code>PyExc_BrokenPipeError</code>	<code>BrokenPipeError</code>	
<code>PyExc_BufferError</code>	<code>BufferError</code>	
<code>PyExc_ChildProcessError</code>	<code>ChildProcessError</code>	
<code>PyExc_ConnectionAbortedError</code>	<code>ConnectionAbortedError</code>	
<code>PyExc_ConnectionError</code>	<code>ConnectionError</code>	
<code>PyExc_ConnectionRefusedError</code>	<code>ConnectionRefusedError</code>	
<code>PyExc_ConnectionResetError</code>	<code>ConnectionResetError</code>	
<code>PyExc_EOFError</code>	<code>EOFError</code>	
<code>PyExc_FileExistsError</code>	<code>FileExistsError</code>	
<code>PyExc_FileNotFoundError</code>	<code>FileNotFoundError</code>	
<code>PyExc_FloatingPointError</code>	<code>FloatingPointError</code>	
<code>PyExc_GeneratorExit</code>	<code>GeneratorExit</code>	
<code>PyExc_ImportError</code>	<code>ImportError</code>	
<code>PyExc_IndentationError</code>	<code>IndentationError</code>	
<code>PyExc_IndexError</code>	<code>IndexError</code>	
<code>PyExc_InterruptedError</code>	<code>InterruptedError</code>	
<code>PyExc_IsADirectoryError</code>	<code>IsADirectoryError</code>	
<code>PyExc_KeyError</code>	<code>KeyError</code>	
<code>PyExc_KeyboardInterrupt</code>	<code>KeyboardInterrupt</code>	
<code>PyExc_LookupError</code>	<code>LookupError</code>	1
<code>PyExc_MemoryError</code>	<code>MemoryError</code>	

下页继续

表 1 - 繼續上一頁

C 名称	Python 名称	F解
PyExc_ModuleNotFoundError	ModuleNotFoundError	
PyExc_NameError	NameError	
PyExc_NotADirectoryError	NotADirectoryError	
PyExc_NotImplementedError	NotImplementedError	
PyExc_OSError	OSError	¹
PyExc_OverflowError	OverflowError	
PyExc_PermissionError	PermissionError	
PyExc_ProcessLookupError	ProcessLookupError	
PyExc_RecursionError	RecursionError	
PyExc_ReferenceError	ReferenceError	
PyExc_RuntimeError	RuntimeError	
PyExc_StopAsyncIteration	StopAsyncIteration	
PyExc_StopIteration	StopIteration	
PyExc_SyntaxError	SyntaxError	
PyExc_SystemError	SystemError	
PyExc_SystemExit	SystemExit	
PyExc_TabError	TabError	
PyExc_TimeoutError	TimeoutError	
PyExc_TypeError	TypeError	
PyExc_UnboundLocalError	UnboundLocalError	
PyExc_UnicodeDecodeError	UnicodeDecodeError	
PyExc_UnicodeEncodeError	UnicodeEncodeError	
PyExc_UnicodeError	UnicodeError	
PyExc_UnicodeTranslateError	UnicodeTranslateError	
PyExc_ValueError	ValueError	
PyExc_ZeroDivisionError	ZeroDivisionError	

3.3 版新加入: PyExc_BlockingIOError, PyExc_BrokenPipeError, PyExc_ChildProcessError, PyExc_ConnectionError, PyExc_ConnectionAbortedError, PyExc_ConnectionRefusedError, PyExc_ConnectionResetError, PyExc_FileExistsError, PyExc_FileNotFoundError, PyExc_InterruptedError, PyExc_IsADirectoryError, PyExc_NotADirectoryError, PyExc_PermissionError, PyExc_ProcessLookupError 和 PyExc_TimeoutError 是在 **PEP 3151** 被引入。

3.5 版新加入: PyExc_StopAsyncIteration 和 PyExc_RecursionError。

3.6 版新加入: PyExc_ModuleNotFoundError。

这些是兼容性别名 PyExc_OSError:

C 名称	F解
PyExc_EnvironmentError	
PyExc_IOError	
PyExc_WindowsError	²

3.3 版更變: 这些别名曾经是单独的异常类型。

F解:

¹ 这是其他标准异常的基类。
² 仅在 Windows 中定义; 检测是否定义了预处理程序宏 MS_WINDOWS , 以便保护用到它的代码。

5.11 标准警告类别

All standard Python warning categories are available as global variables whose names are `PyExc_` followed by the Python exception name. These have the type *PyObject**; they are all class objects. For completeness, here are all the variables:

C 名称	Python 名称	解
<code>PyExc_Warning</code>	<code>Warning</code>	³
<code>PyExc_BytesWarning</code>	<code>BytesWarning</code>	
<code>PyExc_DeprecationWarning</code>	<code>DeprecationWarning</code>	
<code>PyExc_FutureWarning</code>	<code>FutureWarning</code>	
<code>PyExc_ImportWarning</code>	<code>ImportWarning</code>	
<code>PyExc_PendingDeprecationWarning</code>	<code>PendingDeprecationWarning</code>	
<code>PyExc_ResourceWarning</code>	<code>ResourceWarning</code>	
<code>PyExc_RuntimeWarning</code>	<code>RuntimeWarning</code>	
<code>PyExc_SyntaxWarning</code>	<code>SyntaxWarning</code>	
<code>PyExc_UnicodeWarning</code>	<code>UnicodeWarning</code>	
<code>PyExc_UserWarning</code>	<code>UserWarning</code>	

3.2 版新加入: `PyExc_ResourceWarning`.

解:

³ 这是其他标准警告类别的基类。

本章中的函式可用來執行各種工具任務，包括幫助 C 程式碼提升跨平臺可移植性 (portable)、在 C 中使用 Python module (模組)、以及剖析函式引數基於 C 中的值來構建 Python 中的值等。

6.1 作業系統工具

PyObject *PyOS_FSPath (*PyObject* *path)

Return value: New reference. Part of the [Stable ABI](#) since version 3.6. 返回 *path* 在文件系统中的表示形式。如果该对象是一个 str 或 bytes 对象，则它的引用计数将会增加。如果该对象实现了 os.PathLike 接口，则只要它是一个 str 或 bytes 对象就将返回 __fspath__ ()。在其他情况下将引发 TypeError 并返回 NULL。

3.6 版新加入。

int Py_FdIsInteractive (FILE *fp, const char *filename)

如果名称为 *filename* 的标准 I/O 文件 *fp* 被确认为可交互的则返回真 (非零) 值。isatty (fileno (fp)) 为真值的文件均属于这种情况。如果全局旗标 [Py_InteractiveFlag](#) 为真值，此函数在 *filename* 指针为 NULL 或者其名称等于字符串 '<stdin>' 或 '???' 时也将返回真值。

void PyOS_BeforeFork ()

Part of the [Stable ABI](#) on platforms with fork() since version 3.7. 在进程分叉之前准备某些内部状态的函数。此函数应当在调用 fork () 或者任何类似的克隆当前进程的函数之前被调用。只适用于定义了 fork () 的系统。

警告： C fork () 调用应当只在“main”线程 (位于“main”解释器) 中进行。对于 PyOS_BeforeFork () 来说也是如此。

3.7 版新加入。

void PyOS_AfterFork_Parent ()

Part of the [Stable ABI](#) on platforms with fork() since version 3.7. 在进程分叉之后更新某些内部状态的函数。此函数应当在调用 fork () 或任何类似的克隆当前进程的函数之后被调用，无论进程克隆是否成功。只适用于定义了 fork () 的系统。

警告： C `fork()` 调用应当只在“main”线程（位于“main”解释器）中进行。对于 `PyOS_AfterFork_Parent()` 来说也是如此。

3.7 版新加入。

void **PyOS_AfterFork_Child()**

Part of the Stable ABI on platforms with fork() since version 3.7. 在进程分叉之后更新内部解释器状态的函数。此函数必须在调用 `fork()` 或任何类似的克隆当前进程的函数之后在子进程中被调用，如果该进程有机会回调到 Python 解释器的话。只适用于定义了 `fork()` 的系统。

警告： C `fork()` 调用应当只在“main”线程（位于“main”解释器）中进行。对于 `PyOS_AfterFork_Child()` 来说也是如此。

3.7 版新加入。

也参考：

`os.register_at_fork()` 允许注册可被 `PyOS_BeforeFork()`, `PyOS_AfterFork_Parent()` 和 `PyOS_AfterFork_Child()` 调用的自定义 Python 函数。

void **PyOS_AfterFork()**

Part of the Stable ABI on platforms with fork(). 在进程分叉之后更新某些内部状态的函数；如果要继续使用 Python 解释器则此函数应当在新进程中被调用。如果已将一个新的可执行文件载入到新进程中，则不需要调用此函数。

3.7 版後已用：此函数已被 `PyOS_AfterFork_Child()` 取代。

int **PyOS_CheckStack()**

Part of the Stable ABI on platforms with USE_STACKCHECK since version 3.7. 当解释器的栈空间耗尽时返回真值。这是一个可靠的检查，但仅在定义了 `USE_STACKCHECK` 时可用（目前在 Windows 上使用 Microsoft Visual C++ 编译器）。`USE_STACKCHECK` 将被自动定义；你绝不应该在你自己的代码中改变此定义。

`PyOS_sighandler_t` **PyOS_getsig**(int *i*)

Part of the Stable ABI. Return the current signal handler for signal *i*. This is a thin wrapper around either `sigaction()` or `signal()`. Do not call those functions directly! `PyOS_sighandler_t` is a typedef alias for `void (*)int`.

`PyOS_sighandler_t` **PyOS_setsig**(int *i*, `PyOS_sighandler_t` *h*)

Part of the Stable ABI. Set the signal handler for signal *i* to be *h*; return the old signal handler. This is a thin wrapper around either `sigaction()` or `signal()`. Do not call those functions directly! `PyOS_sighandler_t` is a typedef alias for `void (*)int`.

`wchar_t *`**Py_DecodeLocale**(const char **arg*, `size_t` **size*)

Part of the Stable ABI since version 3.7.

警告： 此函数不应当被直接调用：请使用 `PyConfig` API 以及可确保对 Python 进行预初始化的 `PyConfig_SetBytesString()` 函数。

此函数不可在 This function must not be called before 对 Python 进行预初始化之前被调用以便正确地配置 `LC_CTYPE` 语言区域：请参阅 `Py_PreInitialize()` 函数。

使用 *filesystem encoding and error handler* 来解码一个字节串。如果错误处理句柄为 `surrogateescape` 错误处理句柄，则不可解码的字节将被解码为 `U+DC80..U+DCFF` 范围内的字符；而如果一个字节序列可被解码为代理字符，则其中的字节会使用 `surrogateescape` 错误处理句柄来转义而不是解码它们。

返回一个指向新分配的由宽字符组成的字符串的指针，使用 `PyMem_RawFree()` 来释放内存。如果 `size` 不为 `NULL`，则将排除了 `null` 字符的宽字符数量写入到 *`size`

在解码错误或内存分配错误时返回 NULL。如果 *size* 不为 NULL，则 **size* 将在内存错误时设为 $(size_t)-1$ 或在解码错误时设为 $(size_t)-2$ 。

filesystem encoding and error handler 是由 `PyConfig_Read()` 来选择的：参见 *PyConfig* 的 *filesystem_encoding* 和 *filesystem_errors* 等成员。

解码错误绝对不应当发生，除非 C 库有程序缺陷。

请使用 `Py_EncodeLocale()` 函数来将字符串编码回字节串。

也参考：

`PyUnicode_DecodeFSDefaultAndSize()` 和 `PyUnicode_DecodeLocaleAndSize()` 函数。

3.5 版新加入。

3.7 版更變：现在此函数在 Python UTF-8 模式下将使用 UTF-8 编码格式。

3.8 版更變：现在如果在 Windows 上 `Py_LegacyWindowsFSEncodingFlag` 为零则此函数将使用 UTF-8 编码格式；

char ***Py_EncodeLocale** (const wchar_t *text, size_t *error_pos)

Part of the [Stable ABI](#) since version 3.7. 将一个由宽字符组成的字符串编码为 *filesystem encoding and error handler*。如果错误处理句柄为 `surrogateescape` 错误处理句柄，则在 U+DC80..U+DCFF 范围内的代理字符会被转换为字节值 0x80..0xFF。

返回一个指向新分配的字节串的指针，使用 `PyMem_Free()` 来释放内存。当发生编码错误或内存分配错误时返回 NULL。

如果 *error_pos* 不为 NULL，则成功时会将 **error_pos* 设为 $(size_t)-1$ ，或是在发生编码错误时设为无效字符的索引号。

filesystem encoding and error handler 是由 `PyConfig_Read()` 来选择的：参见 *PyConfig* 的 *filesystem_encoding* 和 *filesystem_errors* 等成员。

请使用 `Py_DecodeLocale()` 函数来将字节串解码回由宽字符组成的字符串。

警告： 此函数不可在 This function must not be called before 对 *Python* 进行预初始化之前被调用以便正确地配置 LC_CTYPE 语言区域：请参阅 `Py_PreInitialize()` 函数。

也参考：

`PyUnicode_EncodeFSDefault()` 和 `PyUnicode_EncodeLocale()` 函数。

3.5 版新加入。

3.7 版更變：现在此函数在 Python UTF-8 模式下将使用 UTF-8 编码格式。

3.8 版更變：现在如果在 Windows 上 `Py_LegacyWindowsFSEncodingFlag` 为零则此函数将使用 UTF-8 编码格式。

6.2 系統函式

这些是使来自 `sys` 模块的功能可以让 C 代码访问的工具函数。它们都可用于当前解释器线程的 `sys` 模块的字典，该字典包含在内部线程状态结构体中。

PyObject ***PySys_GetObject** (const char *name)

Return value: Borrowed reference. Part of the [Stable ABI](#). 返回来自 `sys` 模块的对象 *name* 或者如果它不存在则返回 NULL，并且不会设置异常。

int **PySys_SetObject** (const char *name, PyObject *v)

Part of the [Stable ABI](#). 将 `sys` 模块中的 *name* 设为 *v* 除非 *v* 为 NULL，在此情况下 *name* 将从 `sys` 模块中被删除。成功时返回 0，发生错误时返回 -1。

void **PySys_ResetWarnOptions** ()

Part of the Stable ABI. 将 `sys.warnoptions` 重置为空列表。此函数可在 `Py_Initialize()` 之前被调用。

void **PySys_AddWarnOption** (const wchar_t *s)

Part of the Stable ABI. 将 `s` 添加到 `sys.warnoptions`。此函数必须在 `Py_Initialize()` 之前被调用以便影响警告过滤器列表。

void **PySys_AddWarnOptionUnicode** (PyObject *unicode)

Part of the Stable ABI. 将 `unicode` 添加到 `sys.warnoptions`。

注意：目前此函数不可在 CPython 实现之外使用，因为它必须在 `Py_Initialize()` 中的 `warnings` 显式导入之前被调用，但是要等运行时已初始化到足以允许创建 Unicode 对象时才能被调用。

void **PySys_SetPath** (const wchar_t *path)

Part of the Stable ABI. 将 `sys.path` 设为由在 `path` 中找到的路径组成的列表对象，该参数应为使用特定平台的搜索路径分隔符（在 Unix 上为 `:`，在 Windows 上为 `;`）分隔的路径的列表。

void **PySys_WriteStdout** (const char *format, ...)

Part of the Stable ABI. 将以 `format` 描述的输出字符串写入到 `sys.stdout`。不会引发任何异常，即使发生了截断（见下文）。

`format` 应当将已格式化的输出字符串的总大小限制在 1000 字节以下 -- 超过 1000 字节后，输出字符串会被截断。特别地，这意味着不应出现不受限制的 `%s` 格式；它们应当使用 `%.<N>s` 来限制，其中 `<N>` 是一个经计算使得 `<N>` 与其他已格式化文本的最大尺寸之和不会超过 1000 字节的十进制数字。还要注意 `%f`，它可能为非常大的数字打印出数以百计的数位。

如果发生了错误，`sys.stdout` 会被清空，已格式化的消息将被写入到真正的 (C 层级) `stdout`。

void **PySys_WriteStderr** (const char *format, ...)

Part of the Stable ABI. 类似 `PySys_WriteStdout()`，但改为写入到 `sys.stderr` 或 `stderr`。

void **PySys_FormatStdout** (const char *format, ...)

Part of the Stable ABI. 类似 `PySys_WriteStdout()` 的函数将会使用 `PyUnicode_FromFormatV()` 来格式化消息并且不会将消息截短至任意长度。

3.2 版新加入。

void **PySys_FormatStderr** (const char *format, ...)

Part of the Stable ABI. 类似 `PySys_FormatStdout()`，但改为写入到 `sys.stderr` 或 `stderr`。

3.2 版新加入。

void **PySys_AddXOption** (const wchar_t *s)

Part of the Stable ABI since version 3.7. 将 `s` 解析为一个由 `-x` 选项组成的集合并将它们添加到 `PySys_GetXOptions()` 所返回的当前选项映射。此函数可以在 `Py_Initialize()` 之前被调用。

3.2 版新加入。

PyObject ***PySys_GetXOptions** ()

Return value: Borrowed reference. Part of the Stable ABI since version 3.7. 返回当前 `-x` 选项的字典，类似于 `sys._xoptions`。发生错误时，将返回 `NULL` 并设置一个异常。

3.2 版新加入。

int **PySys_Audit** (const char *event, const char *format, ...)

引发一个审计事件并附带任何激活的钩子。成功时返回零值或在失败时返回非零值并设置一个异常。

如果已添加了任何钩子，则将使用 `format` 和其他参数来构造一个传入的元组。除 `N` 以外，在 `Py_BuildValue()` 中使用的格式字符均可使用。如果构建的值不是一个元组，它将被添加到一个单元元素元组中。（格式选项 `N` 会消耗一个引用，但是由于没有办法知道此函数的参数是否将被消耗，因此使用它可能导致引用泄漏。）

请注意 # 格式字符应当总是被当作 `Py_ssize_t` 来处理，无论是否定义了 `PY_SSIZE_T_CLEAN`。

`sys.audit()` 会执行与来自 Python 代码的函数相同的操作。

3.8 版新加入。

3.8.2 版更變: 要求 `Py_ssize_t` 用于 # 格式字符。在此之前, 会引发一个不可避免的弃用警告。

int PySys_AddAuditHook (`Py_AuditHookFunction hook`, `void *userData`)

将可调用对象 `hook` 添加到激活的审计钩子列表。在成功时返回零而在失败时返回非零值。如果运行时已经被初始化, 还会在失败时设置一个错误。通过此 API 添加的钩子会针对在运行时创建的所有解释器被调用。

`userData` 指针会被传入钩子函数。因于钩子函数可能由不同的运行时调用, 该指针不应直接指向 Python 状态。

此函数可在 `Py_Initialize()` 之前被安全地调用。如果在运行时初始化之后被调用, 现有的审计钩子将得到通知并可能通过引发一个从 `Exception` 子类化的错误静默地放弃操作 (其他错误将不会被静默)。

The hook function is of type `int (*)const char *event, PyObject *args, void *userData`, where `args` is guaranteed to be a `PyTupleObject`. The hook function is always called with the GIL held by the Python interpreter that raised the event.

请参阅 [PEP 578](#) 了解有关审计的详细描述。在运行时和标准库中会引发审计事件的函数清单见 审计事件表。更多细节见每个函数的文档。

引发一个 审计事件 `sys.addaudithook`, 没有附带参数。

3.8 版新加入。

6.3 行程 (Process) 控制

void Py_FatalError (`const char *message`)

Part of the Stable ABI. 打印一个致命错误消息并杀掉进程。不会执行任何清理。此函数应当仅在检测到可能令继续使用 Python 解释器变得危险的条件时被发起调用; 例如, 当对象管理已被破坏的时候。在 Unix 上, 标准 C 库函数 `abort()` 会被调用并将由它来尝试产生一个 core 文件。

The `Py_FatalError()` function is replaced with a macro which logs automatically the name of the current function, unless the `Py_LIMITED_API` macro is defined.

3.9 版更變: 自动记录函数名称。

void Py_Exit (`int status`)

Part of the Stable ABI. 退出当前进程。这将调用 `Py_FinalizeEx()` 然后再调用标准 C 库函数 `exit(status)`。如果 `Py_FinalizeEx()` 提示错误, 退出状态将被设为 120。

3.6 版更變: 来自最终化的错误不会再被忽略。

int Py_AtExit (`void (*func)`)

Part of the Stable ABI. 注册一个由 `Py_FinalizeEx()` 调用的清理函数。调用清理函数将不传入任何参数且不应返回任何值。最多可以注册 32 个清理函数。当注册成功时, `Py_AtExit()` 将返回 0; 失败时, 它将返回 -1。最后注册的清理函数会最先被调用。每个清理函数将至多被调用一次。由于 Python 的内部最终化将在清理函数之前完成, 因此 Python API 不应被 `func` 调用。

6.4 匯入模組

PyObject *PyImport_ImportModule (const char *name)

Return value: New reference. Part of the [Stable ABI](#). 这是下面 `PyImport_ImportModuleEx()` 的简化版接口，将 `globals` 和 `locals` 参数设为 `NULL` 并将 `level` 设为 0。当 `name` 参数包含一个点号（即指定了一个包的子模块）时，`fromlist` 参数会被设为列表 `['*']` 这样返回值将为所指定的模块而不像在其他情况下那样为包含模块的最高层级包。（不幸的是，这在 `name` 实际上是指定一个子包而非子模块时将有一个额外的副作用：在包的 `__all__` 变量中指定的子模块会被加载。）返回一个对所导入模块的新引用，或是在导入失败时返回 `NULL` 并设置一个异常。模块导入失败同模块不会留在 `sys.modules` 中。

该函数总是使用绝对路径导入。

PyObject *PyImport_ImportModuleNoBlock (const char *name)

Return value: New reference. Part of the [Stable ABI](#). 该函数是 `PyImport_ImportModule()` 的一个被遗弃的别名。

3.3 版更變：在导入锁被另一线程掌控时此函数会立即失败。但是从 Python 3.3 起，锁方案在大多数情况下都已切换为针对每个模块加锁，所以此函数的特殊行为已无必要。

PyObject *PyImport_ImportModuleEx (const char *name, PyObject *globals, PyObject *locals, PyObject *fromlist)

Return value: New reference. 导入一个模块。请参阅内置 Python 函数 `__import__()` 获取完善的相关描述。

返回值是一个对所导入模块或最高层级包的新引用，或是在导入失败时则为 `NULL` 并设置一个异常。与 `__import__()` 类似，当请求一个包的子模块时返回值通常为该最高层级包，除非给出了一个非空的 `fromlist`。

导入失败将移动不完整的模块对象，就像 `PyImport_ImportModule()` 那样。

PyObject *PyImport_ImportModuleLevelObject (PyObject *name, PyObject *globals, PyObject *locals, PyObject *fromlist, int level)

Return value: New reference. Part of the [Stable ABI](#) since version 3.7. 导入一个模块。关于此函数的最佳说明请参考内置 Python 函数 `__import__()`，因为标准 `__import__()` 函数会直接调用此函数。

返回值是一个对所导入模块或最高层级包的新引用，或是在导入失败时则为 `NULL` 并设置一个异常。与 `__import__()` 类似，当请求一个包的子模块时返回值通常为该最高层级包，除非给出了一个非空的 `fromlist`。

3.3 版新加入。

PyObject *PyImport_ImportModuleLevel (const char *name, PyObject *globals, PyObject *locals, PyObject *fromlist, int level)

Return value: New reference. Part of the [Stable ABI](#). 类似于 `PyImport_ImportModuleLevelObject()`，但其名称为 UTF-8 编码的字符串而不是 Unicode 对象。

3.3 版更變：不再接受 `level` 为负数值。

PyObject *PyImport_Import (PyObject *name)

Return value: New reference. Part of the [Stable ABI](#). 这是一个调用了当前“导入钩子函数”的更高层级接口（显式指定 `level` 为 0，表示绝对导入）。它将发起调用当前全局作用域下 `__builtins__` 中的 `__import__()` 函数。这意味着将使用当前环境下安装的任何导入钩子来完成导入。

该函数总是使用绝对路径导入。

PyObject *PyImport_ReloadModule (PyObject *m)

Return value: New reference. Part of the [Stable ABI](#). 重载一个模块。返回一个指向被重载模块的新引用，或者在失败时返回 `NULL` 并设置一个异常（在此情况下模块仍然会存在）。

PyObject *PyImport_AddModuleObject (PyObject *name)

Return value: Borrowed reference. Part of the [Stable ABI](#) since version 3.7. 返回对应于某个模块名称的模块对象。`name` 参数的形式可以为 `package.module`。如果存在 `modules` 字典则首先检查该字典，如果找不到，则创建一个新模块并将其插入到 `modules` 字典。在失败时返回 `NULL` 并设置一个异常。

備註：此函数不会加载或导入指定模块；如果模块还未被加载，你将得到一个空的模块对象。请使用 `PyImport_ImportModule()` 或它的某个变体形式来导入模块。`name` 使用带点号名称的包结构如果尚不存在则不会被创建。

3.3 版新加入。

PyObject *PyImport_AddModule (const char *name)

Return value: Borrowed reference. Part of the Stable ABI. 类似于 `PyImport_AddModuleObject()`，但其名称为 UTF-8 编码的字符串而不是 Unicode 对象。object。

PyObject *PyImport_ExecCodeModule (const char *name, PyObject *co)

Return value: New reference. Part of the Stable ABI. 给定一个模块名称（可能为 `package.module` 形式）和一个从 Python 字节码文件读取或从内置函数 `compile()` 获取的代码对象，加载该模块。返回对该模块对象的新引用，或者如果发生错误则返回 NULL 并设置一个异常。在发生错误的情况下 `name` 会从 `sys.modules` 中被移除，即使 `name` 在进入 `PyImport_ExecCodeModule()` 时已存在于 `sys.modules` 中。在 `sys.modules` 中保留未完全初始化的模块是危险的，因为导入这样的模块没有办法知道模块对象是否处于一种未知的（对于模块作业的意图来说可能是已损坏的）状态。

模块的 `__spec__` 和 `__loader__` 如果尚未设置的话，将被设置为适当的值。相应 `spec` 的加载器（如果已设置）将被设为模块的 `__loader__` 而在其他情况下设为 `SourceFileLoader` 的实例。

模块的 `__file__` 属性将被设为代码对象的 `co_filename`。如果适用，`__cached__` 也将被设置。

如果模块已被导入则此函数将重载它。请参阅 `PyImport_ReloadModule()` 了解重载模块的预定方式。

如果 `name` 指向一个形式为 `package.module` 的带点号的名称，则任何尚未创建的包结构仍然不会被创建。

另请参阅 `PyImport_ExecCodeModuleEx()` 和 `PyImport_ExecCodeModuleWithPathnames()`。

PyObject *PyImport_ExecCodeModuleEx (const char *name, PyObject *co, const char *pathname)

Return value: New reference. Part of the Stable ABI. 类似于 `PyImport_ExecCodeModule()`，但如果 `pathname` 不为 NULL 则会被设为模块对象的 `__file__` 属性的值。

也請見 `PyImport_ExecCodeModuleWithPathnames()`。

PyObject *PyImport_ExecCodeModuleObject (PyObject *name, PyObject *co, PyObject *pathname, PyObject *cpathname)

Return value: New reference. Part of the Stable ABI since version 3.7. 类似于 `PyImport_ExecCodeModuleEx()`，但如果 `cpathname` 不为 NULL 则会被设为模块对象的 `__cached__` 值。在三个函数中，这是推荐使用的一个。

3.3 版新加入。

PyObject *PyImport_ExecCodeModuleWithPathnames (const char *name, PyObject *co, const char *pathname, const char *cpathname)

Return value: New reference. Part of the Stable ABI. 类似于 `PyImport_ExecCodeModuleObject()`，但 `name`, `pathname` 和 `cpathname` 为 UTF-8 编码的字符串。如果 `pathname` 也被设为 NULL 则还会尝试根据 `cpathname` 推断出前者的值。

3.2 版新加入。

3.3 版更變：如果只提供了字节码路径则会使用 `imp.source_from_cache()` 来计算源路径。

long PyImport_GetMagicNumber ()

Part of the Stable ABI. 返回 Python 字节码文件（即 `.pyc` 文件）的魔数。此魔数应当存在于字节码文件的开头四个字节中，按照小端字节序。出错时返回 -1。

3.3 版更變：當失敗時回傳 -1。

const char *PyImport_GetMagicTag()

Part of the Stable ABI. 针对 [PEP 3147](#) 格式的 Python 字节码文件名返回魔术标签字符串。请记住在 `sys.implementation.cache_tag` 上的值是应当被用来代替此函数的更权威的值。

3.2 版新加入。

PyObject *PyImport_GetModuleDict()

Return value: Borrowed reference. Part of the Stable ABI. 返回用于模块管理的字典 (即 `sys.modules`)。请注意这是针对每个解释器的变量。

PyObject *PyImport_GetModule(PyObject *name)

Return value: New reference. Part of the Stable ABI since version 3.8. 返回给定名称的已导入模块。如果模块尚未导入则返回 NULL 但不会设置错误。如果查找失败则返回 NULL 并设置错误。

3.7 版新加入。

PyObject *PyImport_GetImporter(PyObject *path)

Return value: New reference. Part of the Stable ABI. 返回针对一个 `sys.path/pkg.__path__` 中条目 `path` 的查找器对象，可能会通过 `sys.path_importer_cache` 字典来获取。如果它尚未被缓存，则会遍历 `sys.path_hooks` 直至找到一个能处理该 `path` 条目的钩子。如果没有可用的钩子则返回 None；这将告知调用方 *path based finder* 无法为该 `path` 条目找到查找器。结果将缓存到 `sys.path_importer_cache`。返回一个指向查找器对象的新引用。

int PyImport_ImportFrozenModuleObject(PyObject *name)

Part of the Stable ABI since version 3.7. 加载名称为 `name` 的已冻结模块。成功时返回 1，如果未找到模块则返回 0，如果初始化失败则返回 -1 并设置一个异常。要在加载成功后访问被导入的模块，请使用 `PyImport_ImportModule()`。(请注意此名称有误导性 --- 如果模块已被导入此函数将重载它。)

3.3 版新加入。

3.4 版更變: `__file__` 属性将不再在模块上设置。

int PyImport_ImportFrozenModule(const char *name)

Part of the Stable ABI. 类似于 `PyImport_ImportFrozenModuleObject()`，但其名称为 UTF-8 编码的字符串而不是 Unicode 对象。

struct _frozen

这是针对已冻结模块描述器的结构类型定义，与由 **freeze** 工具所生成的一致 (请参看 Python 源代码发行版中的 `Tools/freeze/`)。其定义可在 `Include/import.h` 中找到：

```
struct _frozen {
    const char *name;
    const unsigned char *code;
    int size;
};
```

const struct _frozen *PyImport_FrozenModules

This pointer is initialized to point to an array of `_frozen` records, terminated by one whose members are all NULL or zero. When a frozen module is imported, it is searched in this table. Third-party code could play tricks with this to provide a dynamically created collection of frozen modules.

int PyImport_AppendInittab(const char *name, PyObject *(*initfunc)) void

Part of the Stable ABI. 向现有的内置模块表添加一个模块。这是对 `PyImport_ExtendInittab()` 的便捷包装，如果无法扩展表则返回 -1。新的模块可使用名称 `name` 来导入，并使用函数 `initfunc` 作为在第一次尝试导入时调用的初始化函数。此函数应当在 `Py_Initialize()` 之前调用。

struct _inittab

描述内置模块列表中的一个条目的结构体。每个结构体都给出了内置在解释器中的某个模块的名称和初始化函数。名称是一个 ASCII 编码的字符串。嵌入了 Python 的程序可以使用该结构体的数组来与 `PyImport_ExtendInittab()` 相结合以提供额外的内置模块。该结构体在 `Include/import.h` 中被定义为：

```

struct _inittab {
    const char *name;           /* ASCII encoded string */
    PyObject* (*initfunc) (void);
};

```

int **PyImport_ExtendInittab**(struct _inittab *newtab)

将内置模块表添加一组模块。newtab 数组必须以一个包含以 NULL 作为 name 字段的岗哨条目结束；未能提供岗哨值会导致内存错误。成功时返回 0 或者如果无法分配足够内存来扩展内部表则返回 -1。当发生失败时，将不会添加模块到内部表。此函数必须在 `Py_Initialize()` 之前调用。

如果 Python 要被多次初始化，则 `PyImport_AppendInittab()` 或 `PyImport_ExtendInittab()` 必须在每次 Python 初始化之前调用。

6.5 数据 marshal 操作支持

这些例程允许 C 代码处理与 marshal 模块所用相同数据格式的序列化对象。其中有些函数可用来将数据写入这种序列化格式，另一些函数则可用来读取并恢复数据。用于存储 marshal 数据的文件必须以二进制模式打开。

数字值在存储时会最低位字节放在开头。

此模块支持两种数据格式版本：第 0 版为历史版本，第 1 版本会在文件和 marshal 反序列化中共享固化的字符串。第 2 版本会对浮点数使用二进制格式。Py_MARSHAL_VERSION 指明了当前文件的格式（当前取值为 2）。

void **PyMarshal_WriteLongToFile**(long value, FILE *file, int version)

Marshal a long integer, value, to file. This will only write the least-significant 32 bits of value; regardless of the size of the native long type. version indicates the file format.

void **PyMarshal_WriteObjectToFile**(PyObject *value, FILE *file, int version)

将一个 Python 对象 value 以 marshal 格式写入 file。version 指明文件格式的版本。

PyObject ***PyMarshal_WriteObjectToString**(PyObject *value, int version)

Return value: New reference. 返回一个包含 value 的 marshal 表示形式的字节串对象。version 指明文件格式的版本。

以下函数允许读取并恢复存储为 marshal 格式的值。

long **PyMarshal_ReadLongFromFile**(FILE *file)

Return a C long from the data stream in a FILE* opened for reading. Only a 32-bit value can be read in using this function, regardless of the native size of long.

发生错误时，将设置适当的异常 (EOFError) 并返回 -1。

int **PyMarshal_ReadShortFromFile**(FILE *file)

Return a C short from the data stream in a FILE* opened for reading. Only a 16-bit value can be read in using this function, regardless of the native size of short.

发生错误时，将设置适当的异常 (EOFError) 并返回 -1。

PyObject ***PyMarshal_ReadObjectFromFile**(FILE *file)

Return value: New reference. Return a Python object from the data stream in a FILE* opened for reading.

发生错误时，将设置适当的异常 (EOFError, ValueError 或 TypeError) 并返回 NULL。

PyObject ***PyMarshal_ReadLastObjectFromFile**(FILE *file)

Return value: New reference. Return a Python object from the data stream in a FILE* opened for reading. Unlike `PyMarshal_ReadObjectFromFile()`, this function assumes that no further objects will be read from the file, allowing it to aggressively load file data into memory so that the de-serialization can operate from data in memory rather than reading a byte at a time from the file. Only use these variant if you are certain that you won't be reading anything else from the file.

发生错误时，将设置适当的异常 (EOFError, ValueError 或 TypeError) 并返回 NULL。

PyObject *PyMarshal_ReadObjectFromString(const char *data, Py_ssize_t len)

Return value: New reference. 从包含指向 data 的 len 个字节的字节缓冲区对应的数据流返回一个 Python 对象。

发生错误时，将设置适当的异常 (EOFError, ValueError 或 TypeError) 并返回 NULL。

6.6 解析参数并构建值变量

在创建你自己的扩展函数和方法时，这些函数是有用的。其它的信息和样例见 `extending-index`。

这些函数描述的前三个，`PyArg_ParseTuple()`，`PyArg_ParseTupleAndKeywords()`，以及 `PyArg_Parse()`，它们都使用格式化字符串来将函数期待的参数告知函数。这些函数都使用相同语法规则的格式化字符串。

6.6.1 解析参数

一个格式化字符串包含 0 或者更多的格式单元。一个格式单元用来描述一个 Python 对象；它通常是一个字符或者由括号括起来的格式单元序列。除了少数例外，一个非括号序列的格式单元通常对应这些函数的具有单一地址的参数。在接下来的描述中，双引号内的表达式是格式单元；圆括号 () 内的是对应这个格式单元的 Python 对象类型；方括号 [] 内的是传递的 C 变量 (变量集) 类型。

字符串和缓存区

这些格式允许将对象按照连续的内存块形式进行访问。你没必要提供返回的 unicode 字符或者字节区的原始数据存储。

除非另有说明，缓冲区是不会以空终止的。

There are three ways strings and buffers can be converted to C:

- Formats such as `y*` and `s*` fill a `Py_buffer` structure. This locks the underlying buffer so that the caller can subsequently use the buffer even inside a `Py_BEGIN_ALLOW_THREADS` block without the risk of mutable data being resized or destroyed. As a result, **you have to call** `PyBuffer_Release()` after you have finished processing the data (or in any early abort case).
- The `es`, `es#`, `et` and `et#` formats allocate the result buffer. **You have to call** `PyMem_Free()` after you have finished processing the data (or in any early abort case).
- Other formats take a `str` or a read-only *bytes-like object*, such as `bytes`, and provide a `const char *` pointer to its buffer. In this case the buffer is "borrowed": it is managed by the corresponding Python object, and shares the lifetime of this object. You won't have to release any memory yourself.

To ensure that the underlying buffer may be safely borrowed, the object's `PyBufferProcs.bf_releasebuffer` field must be NULL. This disallows common mutable objects such as `bytearray`, but also some read-only objects such as `memoryview` of `bytes`.

Besides this `bf_releasebuffer` requirement, there is no check to verify whether the input object is immutable (e.g. whether it would honor a request for a writable buffer, or whether another thread can mutate the data).

備註：对于所有 # 格式的变体 (`s#`、`y#` 等)，宏 `PY_SSIZE_T_CLEAN` 必须在包含 Python 之前定义。h。在 Python 3.9 及更早版本上，如果定义了 `PY_SSIZE_T_CLEAN` 宏，则长度参数的类型为 `Py_ssize_t`，否则为 `int`。

s (str) [const char *] 将一个 Unicode 对象转换成一个指向字符串的 C 指针。一个指针指向一个已经存在的字符串，这个字符串存储的是传如的字符指针变量。C 字符串是已空结束的。Python 字符串不能包含嵌入的无效的代码点；如果由，一个 `ValueError` 异常会被引发。Unicode 对象被转化成 'utf-8' 编码的 C 字符串。如果转换失败，一个 `UnicodeError` 异常被引发。

備註: 这个表达式不接受 *bytes-like objects*。如果你想接受文件系统路径并将它们转化成 C 字符串, 建议使用 `O&` 表达式配合 `PyUnicode_FSConverter()` 作为转化函数。

3.5 版更變: 以前, 当 Python 字符串中遇到了嵌入的 null 代码点会引发 `TypeError`。

s* (str 或 bytes-like object) [Py_buffer] 这个表达式既接受 Unicode 对象也接受类字节类型对象。它为由调用者提供的 `Py_buffer` 结构赋值。这里结果的 C 字符串可能包含嵌入的 NUL 字节。Unicode 对象通过 'utf-8' 编码转化成 C 字符串。

s# (str, read-only bytes-like object) [const char *, Py_ssize_t] Like `s*`, except that it provides a *borrowed buffer*. The result is stored into two C variables, the first one a pointer to a C string, the second one its length. The string may contain embedded null bytes. Unicode objects are converted to C strings using 'utf-8' encoding.

z (str 或 None) [const char *] 与 `s` 类似, 但 Python 对象也可能为 `None`, 在这种情况下, C 指针设置为 `NULL`。

z* (str, bytes-like object 或 None) [Py_buffer] 与 `s*` 类似, 但 Python 对象也可能为 `None`, 在这种情况下, `Py_buffer` 结构的 `buf` 成员设置为 `NULL`。

z# (str, read-only bytes-like object 或者 None) [const char *, Py_ssize_t] 与 `s#` 类似, 但 Python 对象也可能为 `None`, 在这种情况下, C 指针设置为 `NULL`。

y (唯讀 bytes-like object) [const char *] This format converts a bytes-like object to a C pointer to a *borrowed* character string; it does not accept Unicode objects. The bytes buffer must not contain embedded null bytes; if it does, a `ValueError` exception is raised.

3.5 版更變: 以前, 当字节缓冲区中遇到了嵌入的 null 字节会引发 `TypeError`。

y* (bytes-like object) [Py_buffer] `s*` 的变式, 不接受 Unicode 对象, 只接受类字节类型变量。这是接受二进制数据的推荐方法。

y# (read-only bytes-like object) [const char *, Py_ssize_t] `s#` 的变式, 不接受 Unicode 对象, 只接受类字节类型变量。

S (bytes) [PyBytesObject *] Requires that the Python object is a `bytes` object, without attempting any conversion. Raises `TypeError` if the object is not a `bytes` object. The C variable may also be declared as `PyObject*`.

Y (bytearray) [PyByteArrayObject *] Requires that the Python object is a `bytearray` object, without attempting any conversion. Raises `TypeError` if the object is not a `bytearray` object. The C variable may also be declared as `PyObject*`.

u (str) [const Py_UNICODE *] 将一个 Python Unicode 对象转化成指向一个以空终止的 Unicode 字符缓冲区的指针。你必须传入一个 `Py_UNICODE` 指针变量的地址, 存储了一个指向已经存在的 Unicode 缓冲区的指针。请注意一个 `Py_UNICODE` 类型的字符宽度取决于编译选项 (16 位或者 32 位)。Python 字符串必须不能包含嵌入的 null 代码点; 如果有, 引发一个 `ValueError` 异常。

3.5 版更變: 以前, 当 Python 字符串中遇到了嵌入的 null 代码点会引发 `TypeError`。

自從版本 3.3 後不推薦使用, 將會自版本 3.12 中移除。: 这是旧版样式 `Py_UNICODE` API; 请迁移至 `PyUnicode_AsWideCharString()`。

u# (str) [const Py_UNICODE *, Py_ssize_t] `u` 的变式, 存储两个 C 变量, 第一个指针指向一个 Unicode 数据缓存区, 第二个是它的长度。它允许 null 代码点。

自從版本 3.3 後不推薦使用, 將會自版本 3.12 中移除。: 这是旧版样式 `Py_UNICODE` API; 请迁移至 `PyUnicode_AsWideCharString()`。

z (str 或 None) [const Py_UNICODE *] 与 `u` 类似, 但 Python 对象也可能为 `None`, 在这种情况下 `Py_UNICODE` 指针设置为 `NULL`。

自從版本 3.3 後不推薦使用, 將會自版本 3.12 中移除。: 这是旧版样式 `Py_UNICODE` API; 请迁移至 `PyUnicode_AsWideCharString()`。

z# (str 或 None) [const Py_UNICODE *, Py_ssize_t] 与 u# 类似, 但 Python 对象也可能为 None, 在这种情况下 `Py_UNICODE` 指针设置为 NULL。

自從版本 3.3 後不推薦使用, 將會自版本 3.12 中移除。: 这是旧版样式 `Py_UNICODE` API; 请迁移至 `PyUnicode_AsWideCharString()`。

U (str) [PyObject*] Requires that the Python object is a Unicode object, without attempting any conversion. Raises `TypeError` if the object is not a Unicode object. The C variable may also be declared as `PyObject*`.

w* (可讀寫 bytes-like object) [Py_buffer] 这个表达式接受任何实现可读写缓存区接口的对象。它为调用者提供的 `Py_buffer` 结构赋值。缓冲区可能存在嵌入的 null 字节。当缓冲区使用完后调用者需要调用 `PyBuffer_Release()`。

es (str) [const char *encoding, char **buffer] s 的变式, 它将编码后的 Unicode 字符存入字符缓冲区。它只处理没有嵌 NUL 字节的已编码数据。

This format requires two arguments. The first is only used as input, and must be a `const char*` which points to the name of an encoding as a NUL-terminated string, or NULL, in which case 'utf-8' encoding is used. An exception is raised if the named encoding is not known to Python. The second argument must be a `char**`; the value of the pointer it references will be set to a buffer with the contents of the argument text. The text will be encoded in the encoding specified by the first argument.

`PyArg_ParseTuple()` 会分配一个足够大小的缓冲区, 将编码后的数据拷贝进这个缓冲区并且设置 `*buffer` 引用这个新分配的内存空间。调用者有责任在使用后调用 `PyMem_Free()` 去释放已经分配的缓冲区。

et (str, bytes or bytearray) [const char *encoding, char **buffer] 和 es 相同, 除了不用重编码传入的字符串对象。相反, 它假设传入的参数是编码后的字符串类型。

es# (str) [const char *encoding, char **buffer, Py_ssize_t *buffer_length] s# 的变式, 它将已编码的 Unicode 字符存入字符缓冲区。不像 es 表达式, 它允许传入的数据包含 NUL 字符。

It requires three arguments. The first is only used as input, and must be a `const char*` which points to the name of an encoding as a NUL-terminated string, or NULL, in which case 'utf-8' encoding is used. An exception is raised if the named encoding is not known to Python. The second argument must be a `char**`; the value of the pointer it references will be set to a buffer with the contents of the argument text. The text will be encoded in the encoding specified by the first argument. The third argument must be a pointer to an integer; the referenced integer will be set to the number of bytes in the output buffer.

有两种操作方式:

如果 `*buffer` 指向 NULL 指针, 则函数将分配所需大小的缓冲区, 将编码的数据复制到此缓冲区, 并设置 `*buffer` 以引用新分配的存储。呼叫者负责调用 `PyMem_Free()` 以在使用后释放分配的缓冲区。

如果 `*buffer` 指向非 NULL 指针 (已分配的缓冲区), 则 `PyArg_ParseTuple()` 将使用此位置作为缓冲区, 并将 `*buffer_length` 的初始值解释为缓冲区大小。然后, 它将编码的数据复制到缓冲区, 并终止它。如果缓冲区不够大, 将设置一个 `ValueError`。

在这两个例子中, `*buffer_length` 被设置为编码后结尾不为 NUL 的数据的长度。

et# (str, bytes 或 bytearray) [const char *encoding, char **buffer, Py_ssize_t *buffer_length] 和 es# 相同, 除了不用重编码传入的字符串对象。相反, 它假设传入的参数是编码后的字符串类型。

數字

b(int) [unsigned char] Convert a nonnegative Python integer to an unsigned tiny int, stored in a C unsigned char.

B(int) [unsigned char] Convert a Python integer to a tiny int without overflow checking, stored in a C unsigned char.

h(int) [short int] 將一個 Python 整數轉成 C 的 short int。

H(int) [unsigned short int] 將一個 Python 整數轉成 C 的 unsigned short int, 轉過程無溢位檢查。

i(int) [int] 將一個 Python 整數轉成 C 的 int。

I(int) [unsigned int] 將一個 Python 整數轉成 C 的 unsigned int, 轉過程無溢位檢查。

l(int) [long int] 將一個 Python 整數轉成 C 的 long int。

k(int) [unsigned long] 將一個 Python 整數轉成 C 的 unsigned long, 轉過程無溢位檢查。

L(int) [long long] 將一個 Python 整數轉成 C 的 long long。

K(int) [unsigned long long] 將一個 Python 整數轉成 C 的 unsigned long long, 轉過程無溢位檢查。

n(int) [Py_ssize_t] 將一個 Python 整數轉成 C 的 Py_ssize_t。

c (bytes 或長度 1 的 bytearray) [char] Convert a Python byte, represented as a bytes or bytearray object of length 1, to a C char.

3.3 版更變: 允許 bytearray 物件。

C (長度 1 的 str) [int] Convert a Python character, represented as a str object of length 1, to a C int.

f(float) [float] 將一個 Python 浮點數轉成 C 的:c:type:float。

d(float) [double] 將一個 Python 浮點數轉成 C 的:c:type:double。

D(complex) [Py_complex] 將一個 Python 數轉成 C 的 Py_complex 結構。

其他物件

O (物件) [PyObject*] 將 Python 对象（不进行任何转换）存储在 C 对象指针中。因此，C 程序接收已传递的实际对象。对象的引用计数不会增加。存储的指针不是 NULL。

O! (物件) [typeobject, PyObject*] Store a Python object in a C object pointer. This is similar to O, but takes two C arguments: the first is the address of a Python type object, the second is the address of the C variable (of type *PyObject**) into which the object pointer is stored. If the Python object does not have the required type, *TypeError* is raised.

O& (物件) [converter, anything] Convert a Python object to a C variable through a *converter* function. This takes two arguments: the first is a function, the second is the address of a C variable (of arbitrary type), converted to *void**. The *converter* function in turn is called as follows:

```
status = converter(object, address);
```

where *object* is the Python object to be converted and *address* is the *void** argument that was passed to the *PyArg_Parse** function. The returned *status* should be 1 for a successful conversion and 0 if the conversion has failed. When the conversion fails, the *converter* function should raise an exception and leave the content of *address* unmodified.

如果 *converter* 返回 *Py_CLEANUP_SUPPORTED*, 则如果参数解析最终失败, 它可能会再次调用该函数, 从而使转换器有机会释放已分配的任何内存。在第二个调用中, *object* 参数将为 NULL; 因此, 该参数将为 NULL; 因此, 该参数将为 NULL, 因此, 该参数将为 NULL (如果值) 为 ``NULL` 的 *address* 的值与原始呼叫中的值相同。

3.1 版更變: 加入 *Py_CLEANUP_SUPPORTED*。

p (bool) [int] 测试传入的值是否为真（一个布尔判断）并且将结果转化为相对应的 C true/false 整型值。如果表达式为真置 1，假则置 0。它接受任何合法的 Python 值。参见 `truth` 获取更多关于 Python 如何测试值为真的信息。

3.3 版新加入。

(items) (tuple) [matching-items] 对象必须是 Python 序列，它的长度是 *items* 中格式单元的数量。C 参数必须对应 *items* 中每一个独立的格式单元。序列中的格式单元可能有嵌套。

传递“long”整型（整型的值超过了平台的 `LONG_MAX` 限制）是可能的，然而没有进行适当的范围检测——当接收字段太小而接收不到值时，最重要的位被静默地截断（实际上，C 语言会在语义继承的基础上强制类型转换——期望的值可能会发生变化）。

格式化字符串中还有一些其他的字符具有特殊的涵义。这些可能并不嵌套在圆括号中。它们是：

| 表明在 Python 参数列表中剩下的参数都是可选的。C 变量对应的可选参数需要初始化为默认值——当一个可选参数没有指定时，`PyArg_ParseTuple()` 不能访问相应的 C 变量（变量集）的内容。

\$ `PyArg_ParseTupleAndKeywords()` only: 表明在 Python 参数列表中剩下的参数都是强制关键字参数。当前，所有强制关键字参数都必须也是可选参数，所以格式化字符串中 | 必须一直在 \$ 前面。

3.3 版新加入。

: 格式单元的列表结束标志；冒号后的字符串被用来作为错误消息中的函数名（`PyArg_ParseTuple()` 函数引发的“关联值”异常）。

; 格式单元的列表结束标志；分号后的字符串被用来作为错误消息取代默认的错误消息。: 和 ; 相互排斥。

注意任何由调用者提供的 Python 对象引用是借来的引用；不要递减它们的引用计数！

传递给这些函数的附加参数必须是由格式化字符串确定的变量的地址；这些都是用来存储输入元组的值。有一些情况，如上面的格式单元列表中所描述的，这些参数作为输入值使用；在这种情况下，它们应该匹配指定的相应的格式单元。

For the conversion to succeed, the *arg* object must match the format and the format must be exhausted. On success, the `PyArg_Parse*` functions return true, otherwise they return false and raise an appropriate exception. When the `PyArg_Parse*` functions fail due to conversion failure in one of the format units, the variables at the addresses corresponding to that and the following format units are left untouched.

API 函数

`int PyArg_ParseTuple (PyObject *args, const char *format, ...)`

Part of the Stable ABI. 解析一个函数的参数，表达式中的参数按参数位置顺序存入局部变量中。成功返回 true；失败返回 false 并且引发相应的异常。

`int PyArg_VaParse (PyObject *args, const char *format, va_list vars)`

Part of the Stable ABI. 和 `PyArg_ParseTuple()` 相同，然而它接受一个 `va_list` 类型的参数而不是可变数量的参数集。

`int PyArg_ParseTupleAndKeywords (PyObject *args, PyObject *kw, const char *format, char *keywords[], ...)`

Part of the Stable ABI. 分析将位置参数和关键字参数同时转换为局部变量的函数的参数。*keywords* 参数是关键字参数名称的 NULL 终止数组。空名称表示 *positional-only parameters*。成功时返回 true；发生故障时，它将返回 false 并引发相应的异常。

3.6 版更變：添加了 *positional-only parameters* 的支持。

`int PyArg_VaParseTupleAndKeywords (PyObject *args, PyObject *kw, const char *format, char *keywords[], va_list vars)`

Part of the Stable ABI. 和 `PyArg_ParseTupleAndKeywords()` 相同，然而它接受一个 `va_list` 类型的参数而不是可变数量的参数集。

`int PyArg_ValidateKeywordArguments (PyObject*)`

Part of the [Stable ABI](#). 确保字典中的关键字参数都是字符串。这个函数只被使用于 `PyArg_ParseTupleAndKeywords()` 不被使用的情况下，后者已经不再做这样的检查。

3.2 版新加入。

`int PyArg_Parse (PyObject *args, const char *format, ...)`

Part of the [Stable ABI](#). 函数被用来析构“旧类型”函数的参数列表——这些函数使用的 `METH_OLDARGS` 参数解析方法已从 Python 3 中移除。这不被推荐用于新代码的参数解析，并且在标准解释器中的大多数代码已被修改，已不再用于该目的。它仍然方便于分解其他元组，然而可能因为这个目的被继续使用。

`int PyArg_UnpackTuple (PyObject *args, const char *name, Py_ssize_t min, Py_ssize_t max, ...)`

Part of the [Stable ABI](#). A simpler form of parameter retrieval which does not use a format string to specify the types of the arguments. Functions which use this method to retrieve their parameters should be declared as `METH_VARARGS` in function or method tables. The tuple containing the actual parameters should be passed as `args`; it must actually be a tuple. The length of the tuple must be at least `min` and no more than `max`; `min` and `max` may be equal. Additional arguments must be passed to the function, each of which should be a pointer to a `PyObject*` variable; these will be filled in with the values from `args`; they will contain [borrowed references](#). The variables which correspond to optional parameters not given by `args` will not be filled in; these should be initialized by the caller. This function returns true on success and false if `args` is not a tuple or contains the wrong number of elements; an exception will be set if there was a failure.

这是一个使用此函数的示例，取自 `_weakref` 帮助模块用来弱化引用的源代码：

```
static PyObject *
weakref_ref(PyObject *self, PyObject *args)
{
    PyObject *object;
    PyObject *callback = NULL;
    PyObject *result = NULL;

    if (PyArg_UnpackTuple(args, "ref", 1, 2, &object, &callback)) {
        result = PyWeakref_NewRef(object, callback);
    }
    return result;
}
```

这个例子中调用 `PyArg_UnpackTuple()` 完全等价于调用 `PyArg_ParseTuple()`：

```
PyArg_ParseTuple(args, "O|O:ref", &object, &callback)
```

6.6.2 创建变量

`PyObject *Py_BuildValue (const char *format, ...)`

Return value: New reference. Part of the [Stable ABI](#). Create a new value based on a format string similar to those accepted by the `PyArg_Parse*` family of functions and a sequence of values. Returns the value or `NULL` in the case of an error; an exception will be raised if `NULL` is returned.

`Py_BuildValue()` 并不一直创建一个元组。只有当它的格式化字符串包含两个或更多的格式单元才会创建一个元组。如果格式化字符串是空，它返回 `None`；如果它包含一个格式单元，它返回由格式单元描述的任一对象。用圆括号包裹格式化字符串可以强制它返回一个大小为 0 或者 1 的元组。

当内存缓存区的数据以参数形式传递用来构建对象时，如 `s` 和 `s#` 格式单元，会拷贝需要的数据。调用者提供的缓冲区从来都不会被由 `Py_BuildValue()` 创建的对象来引用。换句话说，如果你的代码调用 `malloc()` 并且将分配的内存空间传递给 `Py_BuildValue()`，你的代码就有责任在 `Py_BuildValue()` 返回时调用 `free()`。

在下面的描述中，双引号的表达式使格式单元；圆括号 `()` 内的是格式单元将要返回的 Python 对象类型；方括号 `[]` 内的是传递的 C 变量 (变量集) 的类型。

字符例如空格，制表符，冒号和逗号在格式化字符串中会被忽略 (但是不包括格式单元，如 `s#`)。这可以使很长的格式化字符串具有更好的可读性。

s (str 或 None) [const char *] 使用 'utf-8' 编码将空终止的 C 字符串转换为 Python str 对象。如果 C 字符串指针为 NULL，则使用 None。

s# (str 或 None) [const char *, Py_ssize_t] 使用 'utf-8' 编码将 C 字符串及其长度转换为 Python str 对象。如果 C 字符串指针为 NULL，则长度将被忽略，并返回 None。

y (bytes) [const char *] 这会将 C 字符串转换为 Python bytes 对象。如果 C 字符串指针为 NULL，则返回 None。

y# (bytes) [const char *, Py_ssize_t] 这会将 C 字符串及其长度转换为一个 Python 对象。如果该 C 字符串指针为 NULL，则返回 None。

z (str 或 None) [const char *] 和 s 相同。

z# (str 或 None) [const char *, Py_ssize_t] 和 s# 相同。

u (str) [const wchar_t *] Convert a null-terminated `wchar_t` buffer of Unicode (UTF-16 or UCS-4) data to a Python Unicode object. If the Unicode buffer pointer is NULL, None is returned.

u# (str) [const wchar_t *, Py_ssize_t] 将 Unicode (UTF-16 或 UCS-4) 数据缓冲区及其长度转换为 Python Unicode 对象。如果 Unicode 缓冲区指针为 NULL，则长度将被忽略，并返回 None。

U (str 或 None) [const char *] 和 s 相同。

U# (str 或 None) [const char *, Py_ssize_t] 和 s# 相同。

i (int) [int] 將一個 C 的 `int` 轉成 Python 整數物件。

b (int) [char] 將一個 C 的 `char` 轉成 Python 整數物件。

h (int) [short int] 將一個 C 的 `short int` 轉成 Python 整數物件。

l (int) [long int] 將一個 C 的 `long int` 轉成 Python 整數物件。

B (int) [unsigned char] 將一個 C 的 `unsigned char` 轉成 Python 整數物件。

H (int) [unsigned short int] 將一個 C 的 `unsigned short int` 轉成 Python 整數物件。

I (int) [unsigned int] 將一個 C 的 `unsigned int` 轉成 Python 整數物件。

k (int) [unsigned long] 將一個 C 的 `unsigned long` 轉成 Python 整數物件。

L (int) [long long] 將一個 C 的 `long long` 轉成 Python 整數物件。

K (int) [unsigned long long] 將一個 C 的 `unsigned long long` 轉成 Python 整數物件。

n (int) [Py_ssize_t] 將一個 C 的 `Py_ssize_t` 轉成 Python 整數。

c (長度 1 的 bytes) [char] 將一個 C 中代表一個位元組的 `int` 轉成 Python 中長度 1 的 bytes。

C (長度 1 的 str) [int] 將一個 C 中代表一個字元的 `int` 轉成 Python 中長度 1 的 str。

d (float) [double] 將一個 C 的 `double` 轉成 Python 浮點數。

f (float) [float] 將一個 C 的 `float` 轉成 Python 浮點數。

D (complex) [Py_complex *] 將一個 C 的 `Py_complex` 結構轉成 Python 複數。

o (物件) [PyObject *] 将 Python 对象传递不变 (其引用计数除外, 该计数由 1 递增)。如果传入的对象是 NULL 指针, 则假定这是由于生成参数的调用发现错误并设置异常而引起的。因此, `Py_BuildValue()` 将返回 NULL, 但不会引发异常。如果尚未引发异常, 则设置 `SystemError`。

s (物件) [PyObject *] 和 o 相同。

N (物件) [PyObject *] 和 o 相同, 然而它并不增加对象的引用计数。当通过调用参数列表中的对象构造器创建对象时很实用。

O& (物件) [converter, anything] Convert *anything* to a Python object through a *converter* function. The function is called with *anything* (which should be compatible with `void*`) as its argument and should return a "new" Python object, or `NULL` if an error occurred.

(items) (tuple) [matching-items] 将一个 C 变量序列转换成 Python 元组并保持相同的元素数量。

[items] (list) [matching-items] 将一个 C 变量序列转换成 Python 列表并保持相同的元素数量。

{items} (dict) [matching-items] 将一个 C 变量序列转换成 Python 字典。每一对连续的 C 变量对作为一个元素插入字典中，分别作为关键字和值。

如果格式字符串中出现错误，则设置 `SystemError` 异常并返回 `NULL`。

PyObject *Py_VaBuildValue (const char *format, va_list vars)

Return value: New reference. Part of the [Stable ABI](#). 和 `Py_BuildValue()` 相同，然而它接受一个 `va_list` 类型的参数而不是可变数量的参数集。

6.7 字串轉 與格式化

數字轉 函數和被格式化的字串輸出。

int PyOS_snprintf (char *str, size_t size, const char *format, ...)

Part of the [Stable ABI](#). 根据格式字符串 *format* 和额外参数，输出不超过 *size* 个字节到 *str*。参见 Unix 手册页面 `snprintf(3)`。

int PyOS_vsnprintf (char *str, size_t size, const char *format, va_list va)

Part of the [Stable ABI](#). 根据格式字符串 *format* 和变量参数列表 *va*，输出不超过 *size* 个字节到 *str*。参见 Unix 手册页面 `vsnprintf(3)`。

`PyOS_snprintf()` 和 `PyOS_vsnprintf()` 包装 C 标准库函数 `snprintf()` 和 `vsnprintf()`。它们的目的是保证在极端情况下的一致行为，而标准 C 的函数则不然。

The wrappers ensure that `str[size-1]` is always `'\0'` upon return. They never write more than *size* bytes (including the trailing `'\0'`) into *str*. Both functions require that `str != NULL`, `size > 0`, `format != NULL` and `size < INT_MAX`. Note that this means there is no equivalent to the C99 `n = snprintf(NULL, 0, ...)` which would determine the necessary buffer size.

當回傳值 (*rv*) 給這些函數應該被編譯如下：

- 当 $0 \leq rv < size$ 时，输出转换即成功并将 *rv* 个字符写入到 *str* (不包括末尾 `str[rv]` 位置的 `'\0'` 字节)。
- 当 $rv \geq size$ 时，输出转换会被截断并且需要一个具有 $rv + 1$ 字节的缓冲区才能成功执行。在此情况下 `str[size-1]` 为 `'\0'`。
- 当 $rv < 0$ 时，”会发生不好的事情。”在此情况下 `str[size-1]` 也为 `'\0'`，但 *str* 的其余部分是未定义的。错误的确切原因取决于底层平台。

以下函数提供与语言环境无关的字符串到数字转换。

double PyOS_string_to_double (const char *s, char **endptr, PyObject *overflow_exception)

Part of the [Stable ABI](#). Convert a string *s* to a double, raising a Python exception on failure. The set of accepted strings corresponds to the set of strings accepted by Python's `float()` constructor, except that *s* must not have leading or trailing whitespace. The conversion is independent of the current locale.

如果 *endptr* 是 `NULL`，转换整个字符串。引发 `ValueError` 并且返回 `-1.0` 如果字符串不是浮点数的有效的表达方式。

如果 *endptr* 不是 `NULL`，尽可能多的转换字符串并将 **endptr* 设置为指向第一个未转换的字符。如果字符串的初始段不是浮点数的有效的表达方式，将 **endptr* 设置为指向字符串的开头，引发 `ValueError` 异常，并且返回 `-1.0`。

如果 *s* 表示一个太大而不能存储在一个浮点数中的值（比方说，`"1e500"` 在许多平台上是一个字符串）然后如果 *overflow_exception* 是 `NULL` 返回 `Py_HUGE_VAL`（用适当的符号）并且不

设置任何异常。在其他方面，`overflow_exception` 必须指向一个 Python 异常对象；引发异常并返回 `-1.0`。在这两种情况下，设置 `*endptr` 指向转换值之后的第一个字符。

如果在转换期间发生任何其他错误（比如一个内存不足的错误），设置适当的 Python 异常并且返回 `-1.0`。

3.1 版新加入。

`char *PyOS_double_to_string` (`double val`, `char format_code`, `int precision`, `int flags`, `int *ptype`)

Part of the Stable ABI. Convert a `double val` to a string using supplied `format_code`, `precision`, and `flags`.

格式码必须是以下其中之一，`'e'`，`'E'`，`'f'`，`'F'`，`'g'`，`'G'` 或者 `'r'`。对于 `'r'`，提供的精度必须是 0。`'r'` 格式码指定了标准函数 `repr()` 格式。

`flags` 可以为零或者其他值 `Py_DTSF_SIGN`，`Py_DTSF_ADD_DOT_0` 或 `Py_DTSF_ALT` 或其组合：

- `Py_DTSF_SIGN` 表示总是在返回的字符串前附加一个符号字符，即使 `val` 为非负数。
- `Py_DTSF_ADD_DOT_0` 表示确保返回的字符串看起来不像是一个整数。
- `Py_DTSF_ALT` 表示应用“替代的”格式化规则。相关细节请参阅 `PyOS_snprintf()` `'#'` 定义文档。

如果 `ptype` 不为 `NULL`，则它指向的值将被设为 `Py_DTST_FINITE`，`Py_DTST_INFINITE` 或 `Py_DTST_NAN` 中的一个，分别表示 `val` 是一个有限数字、无限数字或非数字。

返回值是一个指向包含转换后字符串的 `buffer` 的指针，如果转换失败则为 `NULL`。调用方要负责调用 `PyMem_Free()` 来释放返回的字符串。

3.1 版新加入。

`int PyOS_stricmp` (`const char *s1`, `const char *s2`)

字符串不区分大小写。该函数几乎与 `strcmp()` 的工作方式相同，只是它忽略了大小写。

`int PyOS_strnicmp` (`const char *s1`, `const char *s2`, `Py_ssize_t size`)

字符串不区分大小写。该函数几乎与 `strncmp()` 的工作方式相同，只是它忽略了大小写。

6.8 反射

`PyObject *PyEval_GetBuiltins` (`void`)

Return value: Borrowed reference. Part of the Stable ABI. 返回当前执行帧中内置函数的字典，如果当前没有帧正在执行，则返回线程状态的解释器。

`PyObject *PyEval_GetLocals` (`void`)

Return value: Borrowed reference. Part of the Stable ABI. 返回当前执行帧中局部变量的字典，如果没有当前执行的帧则返回 `NULL`。

`PyObject *PyEval_GetGlobals` (`void`)

Return value: Borrowed reference. Part of the Stable ABI. 返回当前执行帧中全局变量的字典，如果没有当前执行的帧则返回 `NULL`。

`PyFrameObject *PyEval_GetFrame` (`void`)

Return value: Borrowed reference. Part of the Stable ABI. 返回当前线程状态的帧，如果没有当前执行的帧则返回 `NULL`。

另請見 `PyThreadState_GetFrame()`。

`PyFrameObject *PyFrame_GetBack` (`PyFrameObject *frame`)

获取 `frame` 为下一个外部帧。

参考返回一个 *strong reference*，或者如果 `frame` 没有外部帧则返回 `NULL`。

`frame` 不可为 `NULL`。

3.9 版新加入。

PyCodeObject *PyFrame_GetCode (*PyFrameObject* *frame)

Part of the Stable ABI since version 3.10. 获取 frame 的代码。

返回一个 strong reference。

frame 必须不为 NULL。结果（帧的代码）不能为 NULL。

3.9 版新加入。

int PyFrame_GetLineNumber (*PyFrameObject* *frame)

Part of the Stable ABI since version 3.10. 返回 frame 当前正在执行的行号。

frame 不可为 NULL。

const char *PyEval_GetFuncName (*PyObject* *func)

Part of the Stable ABI. 如果 func 是函数、类或实例对象，则返回它的名称，否则返回 func 的类型的名称。

const char *PyEval_GetFuncDesc (*PyObject* *func)

Part of the Stable ABI. 根据 func 的类型返回描述字符串。返回值包括函数和方法的“()”，“constructor”，“instance” 和 “object”。与 PyEval_GetFuncName() 的结果连接，结果将是 func 的描述。

6.9 编解码器注册与支持功能

int PyCodec_Register (*PyObject* *search_function)

Part of the Stable ABI. 注册一个新的编解码器搜索函数。

作为副作用，其尝试加载 encodings 包，如果尚未完成，请确保它始终位于搜索函数列表的第一位。

int PyCodec_Unregister (*PyObject* *search_function)

Part of the Stable ABI since version 3.10. 注销一个编解码器搜索函数并清空注册表缓存。如果指定搜索函数未被注册，则不做任何操作。成功时返回 0。出错时引发一个异常并返回 -1。

3.10 版新加入。

int PyCodec_KnownEncoding (const char *encoding)

Part of the Stable ABI. 根据注册的给定 encoding 的编解码器是否已存在而返回 1 或 0。此函数总能成功。

PyObject *PyCodec_Encode (*PyObject* *object, const char *encoding, const char *errors)

Return value: New reference. Part of the Stable ABI. 泛型编解码器基本编码 API。

object 使用由 errors 所定义的错误处理方法传递给 encoding 的编码器函数。errors 可以为 NULL 表示使用为编码器所定义的默认方法。如果找不到编码器则会引发 LookupError。

PyObject *PyCodec_Decode (*PyObject* *object, const char *encoding, const char *errors)

Return value: New reference. Part of the Stable ABI. 泛型编解码器基本解码 API。

object 使用由 errors 所定义的错误处理方法传递给 encoding 的解码器函数。errors 可以为 NULL 表示使用为编解码器所定义的默认方法。如果找不到编解码器则会引发 LookupError。

6.9.1 Codec 查找 API

在下列函数中，encoding 字符串会被查找并转换为小写字母形式，这使得通过此机制查找编码格式实际上对大小写不敏感。如果未找到任何编解码器，则将设置 KeyError 并返回 NULL。

PyObject *PyCodec_Encoder (const char *encoding)

Return value: New reference. Part of the Stable ABI. 为给定的 encoding 获取一个编码器函数。

PyObject *PyCodec_Decoder (const char *encoding)

Return value: New reference. Part of the Stable ABI. 为给定的 encoding 获取一个解码器函数。

PyObject *PyCodec_IncrementalEncoder (const char *encoding, const char *errors)

Return value: New reference. Part of the Stable ABI. 为给定的 encoding 获取一个 IncrementalEncoder 对象。

PyObject *PyCodec_IncrementalDecoder (const char *encoding, const char *errors)

Return value: New reference. Part of the Stable ABI. 为给定的 encoding 获取一个 IncrementalDecoder 对象。

PyObject *PyCodec_StreamReader (const char *encoding, PyObject *stream, const char *errors)

Return value: New reference. Part of the Stable ABI. 为给定的 encoding 获取一个 StreamReader 工厂函数。

PyObject *PyCodec_StreamWriter (const char *encoding, PyObject *stream, const char *errors)

Return value: New reference. Part of the Stable ABI. 为给定的 encoding 获取一个 StreamWriter 工厂函数。

6.9.2 用于 Unicode 编码错误处理程序的注册表 API

int PyCodec_RegisterError (const char *name, PyObject *error)

Part of the Stable ABI. 在给定的 name 之下注册错误处理回调函数 error。该回调函数将在一个编解码器遇到无法编码的字符/无法解码的字节数据并且 name 被指定为 encode/decode 函数调用的 error 形参时由该编解码器来调用。

该回调函数会接受一个 UnicodeEncodeError, UnicodeDecodeError 或 UnicodeTranslateError 的实例作为单独参数, 其中包含关于有问题字符或字节序列及其在原始序列的偏移量信息 (请参阅 [Unicode 异常对象](#) 了解提取此信息的函数详情)。该回调函数必须引发给定的异常, 或者返回一个包含有问题序列及相应替换序列的二元组, 以及一个表示偏移量的整数, 该整数指明应在什么位置上恢复编码/解码操作。

成功则返回 “0”, 失败则返回 “-1”

PyObject *PyCodec_LookupError (const char *name)

Return value: New reference. Part of the Stable ABI. 查找在 name 之下注册的错误处理回调函数。作为特例还可以传入 NULL, 在此情况下将返回针对 “strict” 的错误处理回调函数。

PyObject *PyCodec_StrictErrors (PyObject *exc)

Return value: Always NULL. Part of the Stable ABI. 引发 exc 作为异常。

PyObject *PyCodec_IgnoreErrors (PyObject *exc)

Return value: New reference. Part of the Stable ABI. 忽略 unicode 错误, 跳过错误的输入。

PyObject *PyCodec_ReplaceErrors (PyObject *exc)

Return value: New reference. Part of the Stable ABI. 使用 ? 或 U+FFFD 替换 unicode 编码错误。

PyObject *PyCodec_XMLCharRefReplaceErrors (PyObject *exc)

Return value: New reference. Part of the Stable ABI. 使用 XML 字符引用替换 unicode 编码错误。

PyObject *PyCodec_BackslashReplaceErrors (PyObject *exc)

Return value: New reference. Part of the Stable ABI. 使用反斜杠转义符 (\x, \u 和 \U) 替换 unicode 编码错误。

PyObject *PyCodec_NameReplaceErrors (PyObject *exc)

Return value: New reference. Part of the Stable ABI since version 3.7. 使用 \N{...} 转义符替换 unicode 编码错误。

3.5 版新加入。

抽象物件層 (Abstract Objects Layer)

本章中的函式與 Python 物件相互作用，無論其型別、或具有廣泛類別的物件型別（例如所有數值型別或所有序列型別）。當使用於不適用的物件型別時，他們會引發一個 Python 異常 (exception)。

這些函式是不可能用於未正確初始化的物件（例如一個由 `PyList_New()` 建立的 list 物件），而其中的項目有被設定一些非 NULL 的值。

7.1 对象协议

PyObject *Py_NotImplemented

NotImplemented 单例，用于标记某个操作没有针对给定类型组合的实现。

Py_RETURN_NOTIMPLEMENTED

C 函数内部应正确处理 *Py_NotImplemented* 的返回过程（即增加 NotImplemented 的引用计数并返回之）。

int PyObject_Print (PyObject *o, FILE *fp, int flags)

将对象 *o* 写入到文件 *fp*。出错时返回 -1。旗标参数被用于启用特定的输出选项。目前唯一支持的选项是 `Py_PRINT_RAW`；如果给出该选项，则将写入对象的 `str()` 而不是 `repr()`。

int PyObject_HasAttr (PyObject *o, PyObject *attr_name)

Part of the *Stable ABI*. 如果 *o* 带有属性 *attr_name*，则返回 1，否则返回 0。这相当于 Python 表达式 `hasattr(o, attr_name)`。此函数总是成功。

注意，在调用 `__getattr__()` 和 `__getattribute__()` 方法时发生的异常将被抑制。若要获得错误报告，请换用 *PyObject_GetAttr()*。

int PyObject_HasAttrString (PyObject *o, const char *attr_name)

Part of the *Stable ABI*. 如果 *o* 带有属性 *attr_name*，则返回 1，否则返回 0。这相当于 Python 表达式 `hasattr(o, attr_name)`。此函数总是成功。

注意，在调用 `__getattr__()` 和 `__getattribute__()` 方法并创建一个临时字符串对象时，异常将被抑制。若要获得错误报告，请换用 *PyObject_GetAttrString()*。

PyObject *PyObject_GetAttr (PyObject *o, PyObject *attr_name)

Return value: New reference. Part of the *Stable ABI*. 从对象 *o* 中读取名为 *attr_name* 的属性。成功返回属性值，失败则返回 NULL。这相当于 Python 表达式 `o.attr_name`。

PyObject *PyObject_GetAttrString(*PyObject* *o, const char *attr_name)

Return value: New reference. Part of the Stable ABI. 从对象 *o* 中读取一个名为 *attr_name* 的属性。成功时返回属性值，失败则返回 NULL。这相当于 Python 表达式 *o.attr_name*。

PyObject *PyObject_GenericGetAttr(*PyObject* *o, *PyObject* *name)

Return value: New reference. Part of the Stable ABI. 通用的属性获取函数，用于放入类型对象的 *tp_getattro* 槽中。它在类的字典中（位于对象的 MRO 中）查找某个描述符，并在对象的 *__dict__* 中查找某个属性。正如 *descriptors* 所述，数据描述符优先于实例属性，而非数据描述符则不优先。失败则会触发 *AttributeError*。

int PyObject_SetAttr(*PyObject* *o, *PyObject* *attr_name, *PyObject* *v)

Part of the Stable ABI. 将对象 *o* 中名为 *attr_name* 的属性值设为 *v*。失败时引发异常并返回 -1；成功时返回 “0”。这相当于 Python 语句 *o.attr_name = v*。

如果 *v* 为 NULL，该属性将被删除。此行为已被弃用而应改用 *PyObject_DelAttr()*，但目前还没有移除它的计划。

int PyObject_SetAttrString(*PyObject* *o, const char *attr_name, *PyObject* *v)

Part of the Stable ABI. 将对象 *o* 中名为 *attr_name* 的属性值设为 *v*。失败时引发异常并返回 -1；成功时返回 “0”。这相当于 Python 语句 *o.attr_name = v*。

如果 *v* 为 NULL，该属性将被删除，但是此功能已被弃用而应改用 *PyObject_DelAttrString()*。

int PyObject_GenericSetAttr(*PyObject* *o, *PyObject* *name, *PyObject* *value)

Part of the Stable ABI. 通用的属性设置和删除函数，用于放入类型对象的 *tp_setattro* 槽。它在类的字典中（位于对象的 MRO 中）查找数据描述器，如果找到，则将在实例字典中设置或删除属性优先执行。否则，该属性将在对象的 *__dict__* 中设置或删除。如果成功将返回 0，否则将引发 *AttributeError* 并返回 -1。

int PyObject_DelAttr(*PyObject* *o, *PyObject* *attr_name)

删除对象 *o* 中名为 *attr_name* 的属性。失败时返回 -1。这相当于 Python 语句 *del o.attr_name*。

int PyObject_DelAttrString(*PyObject* *o, const char *attr_name)

删除对象 *o* 中名为 *attr_name* 的属性。失败时返回 -1。这相当于 Python 语句 *del o.attr_name*。

PyObject *PyObject_GenericGetDict(*PyObject* *o, void *context)

Return value: New reference. Part of the Stable ABI since version 3.10. *__dict__* 描述符的获取函数的一种通用实现。必要时会创建该字典。

3.3 版新加入。

int PyObject_GenericSetDict(*PyObject* *o, *PyObject* *value, void *context)

Part of the Stable ABI since version 3.7. *__dict__* 描述符设置函数的一种通用实现。这里不允许删除该字典。

3.3 版新加入。

PyObject *PyObject_RichCompare(*PyObject* *o1, *PyObject* *o2, int opid)

Return value: New reference. Part of the Stable ABI. 用 *opid* 指定的操作比较 *o1* 和 *o2* 的值，必须是 *Py_LT*、*Py_LE*、*Py_EQ*、*Py_NE*、*Py_GT* 或 *Py_GE* 之一，分别对应于 “<”、“<=”、“=”、“!=”、“>” 或 “>=”。这相当于 Python 表达式 *o1 op o2*，其中 *op* 是对应于 *opid* 的操作符。成功时返回比较值，失败时返回 NULL。

int PyObject_RichCompareBool(*PyObject* *o1, *PyObject* *o2, int opid)

Part of the Stable ABI. 用 *opid* 指定的操作比较 *o1* 和 *o2* 的值，必须是 *Py_LT*、*Py_LE*、*Py_EQ*、*Py_NE*、*Py_GT* 或 *Py_GE* 之一，分别对应于 “<”、“<=”、“=”、“!=”、“>” 或 “>=”。错误时返回 -1，若结果为 false 则返回 0，否则返回 1。这相当于 Python 表达式 *o1 op o2*，其中 *op* 是对应于 *opid* 的操作符。

備註：如果 *o1* 和 *o2* 是同一个对象，*PyObject_RichCompareBool()* 为 *Py_EQ* 则返回 1，为 *Py_NE* 则返回 0。

PyObject*PyObject_Format (PyObject*obj, PyObject*format_spec)

Part of the [Stable ABI](#). Format *obj* using *format_spec*. This is equivalent to the Python expression `format(obj, format_spec)`.

format_spec may be NULL. In this case the call is equivalent to `format(obj)`. Returns the formatted string on success, NULL on failure.

PyObject*PyObject_Repr (PyObject*o)

Return value: New reference. Part of the [Stable ABI](#). 计算对象 *o* 的字符串形式。成功时返回字符串，失败时返回 NULL。这相当于 Python 表达式 `repr(o)`。由内置函数 `repr()` 调用。

3.4 版更變: 该函数现在包含一个调试断言，用以确保不会静默地丢弃活动的异常。

PyObject*PyObject_ASCII (PyObject*o)

Return value: New reference. Part of the [Stable ABI](#). 与 `PyObject_Repr()` 一样，计算对象 *o* 的字符串形式，但在 `PyObject_Repr()` 返回的字符串中用 `\x`、`\u` 或 `\U` 转义非 ASCII 字符。这将生成一个类似于 Python 2 中由 `PyObject_Repr()` 返回的字符串。由内置函数 `ascii()` 调用。

PyObject*PyObject_Str (PyObject*o)

Return value: New reference. Part of the [Stable ABI](#). 计算对象 *o* 的字符串形式。成功时返回字符串，失败时返回 NULL。这相当于 Python 表达式 `str(o)`。由内置函数 `str()` 调用，因此也由 `print()` 函数调用。

3.4 版更變: 该函数现在包含一个调试断言，用以确保不会静默地丢弃活动的异常。

PyObject*PyObject_Bytes (PyObject*o)

Return value: New reference. Part of the [Stable ABI](#). 计算对象 *o* 的字节形式。失败时返回 NULL，成功时返回一个字节串对象。这相当于 *o* 不是整数时的 Python 表达式 `bytes(o)`。与 `bytes(o)` 不同的是，当 *o* 是整数而不是初始为 0 的字节串对象时，会触发 `TypeError`。

int PyObject_IsSubclass (PyObject*derived, PyObject*cls)

Part of the [Stable ABI](#). 如果 *derived* 类与 *cls* 类相同或为其派生类，则返回 1，否则返回 0。如果出错则返回 -1。

如果 *cls* 是元组，则会对 *cls* 进行逐项检测。如果至少有一次检测返回 1，结果将为 1，否则将是 0。

正如 [PEP 3119](#) 所述，如果 *cls* 带有 `__subclasscheck__()` 方法，将会被调用以确定子类的状态。否则，如果 *derived* 是个直接或间接子类，即包含在 `cls.__mro__` 中，那么它就是 *cls* 的一个子类。

通常只有类对象才会被视为类，即 `type` 或派生类的实例。然而，对象可以通过拥有 `__bases__` 属性（必须是基类的元组）来覆盖这一点。

int PyObject_IsInstance (PyObject*inst, PyObject*cls)

Part of the [Stable ABI](#). 如果 *inst* 是 *cls* 类或其子类的实例，则返回 1，如果不是则返回“0”。如果出错则返回 -1 并设置一个异常。

如果 *cls* 是元组，则会对 *cls* 进行逐项检测。如果至少有一次检测返回 1，结果将为 1，否则将是 0。

正如 [PEP 3119](#) 所述，如果 *cls* 带有 `__subclasscheck__()` 方法，将会被调用以确定子类的状态。否则，如果 *derived* 是 *cls* 的子类，那么它就是 *cls* 的一个实例。

实例 *inst* 可以通过 `__class__` 属性来覆盖其所属类。

对象 *cls* 是否被认作类，以及基类是什么，均可通过 `__bases__` 属性（必须是基类的元组）进行覆盖。

Py_hash_t PyObject_Hash (PyObject*o)

Part of the [Stable ABI](#). 计算并返回对象的哈希值 *o*。失败时返回 -1。这相当于 Python 表达式 `hash(o)`。

3.2 版更變: 现在的返回类型是 `Py_hash_t`。这是一个大小与 `Py_ssize_t` 相同的有符号整数。

Py_hash_t PyObject_HashNotImplemented (PyObject*o)

Part of the [Stable ABI](#). Set a `TypeError` indicating that `type(o)` is not *hashable* and return -1. This function receives special treatment when stored in a `tp_hash` slot, allowing a type to explicitly indicate to the interpreter that it is not hashable.

int PyObject_IsTrue (PyObject *o)

Part of the Stable ABI. 如果对象 *o* 被认为是 true, 则返回 1, 否则返回 0。这相当于 Python 表达式 `not not o`。失败则返回 -1。

int PyObject_Not (PyObject *o)

Part of the Stable ABI. 如果对象 *o* 被认为是 true, 则返回 1, 否则返回 0。这相当于 Python 表达式 `not not o`。失败则返回 -1。

PyObject *PyObject_Type (PyObject *o)

Return value: New reference. Part of the Stable ABI. When *o* is non-NULL, returns a type object corresponding to the object type of object *o*. On failure, raises `SystemError` and returns NULL. This is equivalent to the Python expression `type(o)`. This function increments the reference count of the return value. There's really no reason to use this function instead of the `Py_TYPE()` function, which returns a pointer of type `PyTypeObject*`, except when the incremented reference count is needed.

int PyObject_TypeCheck (PyObject *o, PyTypeObject *type)

如果对象 *o* 是 *type* 类型或其子类型, 则返回非零, 否则返回 0。两个参数都必须非 NULL。

Py_ssize_t PyObject_Size (PyObject *o)

Py_ssize_t PyObject_Length (PyObject *o)

Part of the Stable ABI. 返回对象 *o* 的长度。如果对象 *o* 支持序列和映射协议, 则返回序列长度。出错时返回 -1。这等同于 Python 表达式 `len(o)`。

Py_ssize_t PyObject_LengthHint (PyObject *o, Py_ssize_t defaultvalue)

返回对象 *o* 的估计长度。首先尝试返回实际长度, 然后用 `__length_hint__()` 进行估计, 最后返回默认值。出错时返回 -1。这等同于 Python 表达式 `operator.length_hint(o, defaultvalue)`。

3.4 版新加入。

PyObject *PyObject_GetItem (PyObject *o, PyObject *key)

Return value: New reference. Part of the Stable ABI. 返回对象 *key* 对应的 *o* 元素, 或在失败时返回 NULL。这等同于 Python 表达式 `o[key]`。

int PyObject_SetItem (PyObject *o, PyObject *key, PyObject *v)

Part of the Stable ABI. 将对象 *key* 映射到值 *v*。失败时引发异常并返回 -1; 成功时返回 0。这相当于 Python 语句 `o[key] = v`。该函数不会偷取 *v* 的引用计数。

int PyObject_DelItem (PyObject *o, PyObject *key)

Part of the Stable ABI. 从对象 *o* 中移除对象 *key* 的映射。失败时返回 -1。这相当于 Python 语句 `del o[key]`。

PyObject *PyObject_Dir (PyObject *o)

Return value: New reference. Part of the Stable ABI. 相当于 Python 表达式 `dir(o)`, 返回一个 (可能为空) 适合对象参数的字符串列表, 如果出错则返回 NULL。如果参数为 NULL, 类似 Python 的 `dir()`, 则返回当前 locals 的名字; 这时如果没有活动的执行框架, 则返回 NULL, 但 `PyErr_Occurred()` 将返回 false。

PyObject *PyObject_GetIter (PyObject *o)

Return value: New reference. Part of the Stable ABI. 等同于 Python 表达式 `iter(o)`。为对象参数返回一个新的迭代器, 如果该对象已经是一个迭代器, 则返回对象本身。如果对象不能被迭代, 会引发 `TypeError`, 并返回 NULL。

PyObject *PyObject_GetAIter (PyObject *o)

Return value: New reference. Part of the Stable ABI since version 3.10. 等同于 Python 表达式 `aiter(o)`。接受一个 `AsyncIterable` 对象, 并为其返回一个 `AsyncIterator`。通常返回的是一个新迭代器, 但如果参数是一个 `AsyncIterator`, 将返回其自身。如果该对象不能被迭代, 会引发 `TypeError`, 并返回 NULL。

3.10 版新加入。

7.2 呼叫協定 (Call Protocol)

CPython 支援兩種不同的呼叫協定：*tp_call* 和 *vectorcall*（向量呼叫）。

7.2.1 *tp_call* 協定

設定 *tp_call* 的類之實例都是可呼叫的。該擴充槽 (slot) 的簽章：

```
PyObject *tp_call(PyObject *callable, PyObject *args, PyObject *kwargs);
```

要達成一個呼叫會使用一個 *tuple*（元組）表示位置引數、一個 *dict* 表示關鍵字引數，類似於 Python 程式碼中的 `callable(*args, **kwargs)`。*args* 必須不為 *NULL*（如果有引數，會使用一個空 *tuple*），但如果有關鍵字引數，*kwargs* 可以是 *NULL*。

這個慣例不僅會被 *tp_call* 使用，*tp_new* 和 *tp_init* 也這樣傳遞引數。

使用 *PyObject_Call()* 或其他呼叫 API 來呼叫一個物件。

7.2.2 *Vectorcall* 協定

3.9 版新加入。

Vectorcall 協定是在 **PEP 590** 被引入的，它是使函式呼叫更加有效率的附加協定。

經驗法則上，如果可呼叫物件有支援，CPython 於內部呼叫中會更傾向使用 *vectorcall*。然而，這不是一個硬性規定。此外，有些第三方擴充套件會直接使用 *tp_call*（而不是使用 *PyObject_Call()*）。因此，一個支援 *vectorcall* 的類也必須實作 *tp_call*。此外，無論使用哪種協定，可呼叫物件的行都必須是相同的。要達成這個目的的推薦做法是將 *tp_call* 設定為 *PyVectorcall_Call()*。這值得一再提醒：

警告： 一個支援 *vectorcall* 的類必須也實作具有相同語義的 *tp_call*。

如果一個類的 *vectorcall* 比 *tp_call* 慢，就不應該實作 *vectorcall*。例如，如果被呼叫者需要將引數轉為 *args tuple*（引數元組）和 *kwargs dict*（關鍵字引數字典），那實作 *vectorcall* 就有意義。

類可以透過用 *Py_TPFLAGS_HAVE_VECTORCALL* 旗標將 *tp_vectorcall_offset* 設定為物件結構中有出現 *vectorcallfunc* 的 *offset* 來實作 *vectorcall* 協定。這是一個指向具有以下簽章之函式的指標：

```
typedef PyObject *(*vectorcallfunc)(PyObject *callable, PyObject *const *args, size_t nargsf,
                                     PyObject *kwnames)
```

- *callable* 是指被呼叫的物件。
- *args* 是一個 C 語言陣列 (array)，包含位置引數與後面 關鍵字引數的值。如果有引數，這個值可以是 *NULL*。
- *nargsf* 是位置引數的數量加上可能會有的 *PY_VECTORCALL_ARGUMENTS_OFFSET* 旗標。如果要從 *nargsf* 獲得實際的位置引數數量，請使用 *PyVectorcall_NARGS()*。
- *kwnames* 是一個包含所有關鍵字引數名稱的 *tuple*；句話，就是 *kwargs* 字典的鍵。這些名字必須是字串 (*str* 或其子類的實例)，且它們必須是不重的。如果有關鍵字引數，那 *kwnames* 可以用 *NULL* 代替。

PY_VECTORCALL_ARGUMENTS_OFFSET

如果在 *vectorcall* 的 *nargsf* 引數中設定了此旗標，則允許被呼叫者臨時更改 *args[-1]* 的值。句話，*args* 指向向量中的引數 1（不是 0）。被呼叫方必須在回傳之前還原 *args[-1]* 的值。

對於 *PyObject_VectorcallMethod()*，這個旗標的改變意味著可能是 *args[0]* 被改變。

當可以以幾乎無代價的方式（無需據額外的記憶體）來達成，那會推薦呼叫者使用 *PY_VECTORCALL_ARGUMENTS_OFFSET*。這樣做會讓如 *bound method*（結方法）之類的可呼叫函式非常有效地繼續向前呼叫（這類函式包含一個在首位的 *self* 引數）。

要呼叫一個實作了 `vectorcall` 的物件，請就像其他可呼叫物件一樣使用呼叫 *API* 中的函式。`PyObject_Vectorcall()` 通常是最有效率的。

備註： 在 CPython 3.8 中，`vectorcall` API 和相關函式暫定以帶開頭底 `_` 的名稱提供：`_PyObject_Vectorcall`、`_Py_TPFLAGS_HAVE_VECTORCALL`、`_PyObject_VectorcallMethod`、`_PyVectorcall_Function`、`_PyObject_CallOneArg`、`_PyObject_CallMethodNoArgs`、`_PyObject_CallMethodOneArg`。此外，`PyObject_VectorcallDict` 也以 `_PyObject_FastCallDict` 名稱提供。這些舊名稱仍有被定義，做不帶底 `_` 的新名稱的 `__` 名。

遞迴控制

在使用 `tp_call` 時，被呼叫者不必擔心遞迴：CPython 對於使用 `tp_call` 的呼叫會使用 `Py_EnterRecursiveCall()` 和 `Py_LeaveRecursiveCall()`。

保證效率，這不適用於使用 `vectorcall` 的呼叫：被呼叫方在需要時應當使用 `Py_EnterRecursiveCall` 和 `Py_LeaveRecursiveCall`。

Vectorcall 支援 API

`Py_ssize_t PyVectorcall_NARGS (size_t nargsf)`

給定一個 `vectorcall` `nargsf` 引數，回傳引數的實際數量。目前等同於：

```
(Py_ssize_t)(nargsf & ~PY_VECTORCALL_ARGUMENTS_OFFSET)
```

然而，應使用 `PyVectorcall_NARGS` 函式以便將來需要擴充。

3.8 版新加入。

vectorcallfunc `PyVectorcall_Function (PyObject *op)`

如果 `op` 不支援 `vectorcall` 協定（因型不支援或特定實例不支援），就回傳 `NULL`。否則，回傳儲存在 `op` 中的 `vectorcall` 函式指標。這個函式不會引發例外。

這大多在檢查 `op` 是否支援 `vectorcall` 時能派上用場，可以透過檢查 `PyVectorcall_Function(op) != NULL` 來達成。

3.8 版新加入。

`PyObject *PyVectorcall_Call (PyObject *callable, PyObject *tuple, PyObject *dict)`

呼叫 `callable` 的 *vectorcallfunc*，其位置引數和關鍵字引數分以 `tuple` 和 `dict` 格式給定。

這是一個專門函式，其目的是被放入 `tp_call` 擴充槽或是用於 `tp_call` 的實作。它不會檢查 `PY_TPFLAGS_HAVE_VECTORCALL` 旗標且它不會退回 (fall back) 使用 `tp_call`。

3.8 版新加入。

7.2.3 物件呼叫 API

有多個函式可被用來呼叫 Python 物件。各個函式會將其引數轉成被呼叫物件所支援的慣用形式—可以是 `tp_call` 或 `vectorcall`。為了可能少轉的進行，請選擇一個適合你所擁有資料格式的函式。

下表總結了可用的函式；請參各個明文件以解詳情。

函式	callable	args	kwargs
<code>PyObject_Call()</code>	<code>PyObject *</code>	<code>tuple</code>	<code>dict/NULL</code>
<code>PyObject_CallNoArgs()</code>	<code>PyObject *</code>	---	---
<code>PyObject_CallOneArg()</code>	<code>PyObject *</code>	一個物件	---
<code>PyObject_CallObject()</code>	<code>PyObject *</code>	<code>tuple/NULL</code>	---
<code>PyObject_CallFunction()</code>	<code>PyObject *</code>	<code>format</code>	---
<code>PyObject_CallMethod()</code>	物件 + <code>char*</code>	<code>format</code>	---
<code>PyObject_CallFunctionObjArgs()</code>	<code>PyObject *</code>	可變引數	---
<code>PyObject_CallMethodObjArgs()</code>	物件 + 名稱	可變引數	---
<code>PyObject_CallMethodNoArgs()</code>	物件 + 名稱	---	---
<code>PyObject_CallMethodOneArg()</code>	物件 + 名稱	一個物件	---
<code>PyObject_Vectorcall()</code>	<code>PyObject *</code>	<code>vectorcall</code>	<code>vectorcall</code>
<code>PyObject_VectorcallDict()</code>	<code>PyObject *</code>	<code>vectorcall</code>	<code>dict/NULL</code>
<code>PyObject_VectorcallMethod()</code>	引數 + 名稱	<code>vectorcall</code>	<code>vectorcall</code>

`PyObject *``PyObject_Call` (`PyObject *``callable`, `PyObject *``args`, `PyObject *``kwargs`)

Return value: New reference. Part of the [Stable ABI](#). 呼叫一個可呼叫的 Python 物件 `callable`，附帶由 `tuple args` 所給定的引數及由字典 `kwargs` 所給定的關鍵字引數。

`args` 必須不為 `NULL`；如果不需要引數，請使用一個空 `tuple`。如果不需要關鍵字引數，則 `kwargs` 可以為 `NULL`。

成功時回傳結果，或在失敗時引發一個例外回傳 `NULL`。

這等價於 Python 運算式 `callable(*args, **kwargs)`。

`PyObject *``PyObject_CallNoArgs` (`PyObject *``callable`)

Part of the [Stable ABI](#) since version 3.10. 呼叫一個可呼叫的 Python 物件 `callable` 不附帶任何引數。這是不帶引數呼叫 Python 可呼叫物件的最有效方式。

成功時回傳結果，或在失敗時引發一個例外回傳 `NULL`。

3.9 版新加入。

`PyObject *``PyObject_CallOneArg` (`PyObject *``callable`, `PyObject *``arg`)

呼叫一個可呼叫的 Python 物件 `callable` 附帶正好一個位置引數 `arg` 而沒有關鍵字引數。

成功時回傳結果，或在失敗時引發一個例外回傳 `NULL`。

3.9 版新加入。

`PyObject *``PyObject_CallObject` (`PyObject *``callable`, `PyObject *``args`)

Return value: New reference. Part of the [Stable ABI](#). 呼叫一個可呼叫的 Python 物件 `callable`，附帶由 `tuple args` 所給定的引數。如果不需要傳入引數，則 `args` 可以為 `NULL`。

成功時回傳結果，或在失敗時引發一個例外回傳 `NULL`。

這等價於 Python 運算式 `callable(*args)`。

`PyObject *``PyObject_CallFunction` (`PyObject *``callable`, `const char *``format`, ...)

Return value: New reference. Part of the [Stable ABI](#). 呼叫一個可呼叫的 Python 物件 `callable`，附帶數量可變的 C 引數。這些 C 引數使用 `Py_BuildValue()` 風格的格式字串來描述。格式可以為 `NULL`，表示沒有提供任何引數。

成功時回傳結果，或在失敗時引發一個例外回傳 `NULL`。

這等價於 Python 運算式 `callable(*args)`。

注意，如果你只傳入 `PyObject *` 引數，則 `PyObject_CallFunctionObjArgs()` 是另一個更快的選擇。

3.4 版更變：這個 `format` 的型已從 `char *` 更改。

`PyObject *``PyObject_CallMethod` (`PyObject *``obj`, `const char *``name`, `const char *``format`, ...)

Return value: New reference. Part of the [Stable ABI](#). 呼叫 `obj` 物件中名為 `name` 的 method 附帶數量可變的 C 引數。這些 C 引數由 `Py_BuildValue()` 格式字串來描述，應生成一個 `tuple`。

格式可以 `NULL`，表示有提供任何引數。

成功時回傳結果，或在失敗時引發一個例外回傳 `NULL`。

這等價於 Python 運算式 `obj.name(arg1, arg2, ...)`。

注意，如果你只傳入 `PyObject*` 引數，則 `PyObject_CallMethodObjArgs()` 是另一個更快速的選擇。

3.4 版更變: `name` 和 `format` 的型已從 `char *` 更改。

`PyObject*PyObject_CallFunctionObjArgs(PyObject*callable, ...)`

Return value: New reference. Part of the [Stable ABI](#). 呼叫一個可呼叫的 Python 物件 `callable`，附帶數量可變的 `PyObject*` 引數。這些引數是以位置在 `NULL` 後面、數量可變的參數來提供。

成功時回傳結果，或在失敗時引發一個例外回傳 `NULL`。

這等價於 Python 運算式 `callable(arg1, arg2, ...)`。

`PyObject*PyObject_CallMethodObjArgs(PyObject*obj, PyObject*name, ...)`

Return value: New reference. Part of the [Stable ABI](#). 呼叫 Python 物件 `obj` 中的一個 method，其中 method 名稱由 `name` 中的 Python 字串物件給定。被呼叫時會附帶數量可變的 `PyObject*` 引數。這些引數是以位置在 `NULL` 後面、且數量可變的參數來提供。

成功時回傳結果，或在失敗時引發一個例外回傳 `NULL`。

`PyObject*PyObject_CallMethodNoArgs(PyObject*obj, PyObject*name)`

不附帶任何引數地呼叫 Python 物件 `obj` 中的一個 method，其中 method 名稱由 `name` 中的 Python 字串物件給定。

成功時回傳結果，或在失敗時引發一個例外回傳 `NULL`。

3.9 版新加入。

`PyObject*PyObject_CallMethodOneArg(PyObject*obj, PyObject*name, PyObject*arg)`

附帶一個位置引數 `arg` 地呼叫 Python 物件 `obj` 中的一個 method，其中 method 名稱由 `name` 中的 Python 字串物件給定。

成功時回傳結果，或在失敗時引發一個例外回傳 `NULL`。

3.9 版新加入。

`PyObject*PyObject_Vectorcall(PyObject*callable, PyObject*const*args, size_t nargsf, PyObject*kwnames)`

呼叫一個可呼叫的 Python 物件 `callable`。附帶引數與 `vectorcallfunc` 的相同。如果 `callable` 支援 `vectorcall`，則它會直接呼叫存放在 `callable` 中的 `vectorcall` 函式。

成功時回傳結果，或在失敗時引發一個例外回傳 `NULL`。

3.9 版新加入。

`PyObject*PyObject_VectorcallDict(PyObject*callable, PyObject*const*args, size_t nargsf, PyObject*kwdict)`

附帶與在 `vectorcall` 協定中傳入的相同位置引數來呼叫 `callable`，但會加上以字典 `kwdict` 格式傳入的關鍵字引數。`args` 陣列將只包含位置引數。

無論內部使用了哪一種協定，都會需要進行引數的轉。因此，此函式應該只有在呼叫方已經擁有一個要作關鍵字引數的字典、但有作位置引數的 tuple 時才被使用。

3.9 版新加入。

`PyObject*PyObject_VectorcallMethod(PyObject*name, PyObject*const*args, size_t nargsf, PyObject*kwnames)`

使用 `vectorcall` 呼叫慣例來呼叫一個 method。method 的名稱以 Python 字串 `name` 的格式給定。被呼叫 method 的物件在 `args[0]`，而 `args` 陣列從 `args[1]` 開始的部分則代表呼叫的引數。必須傳入至少一個位置引數。`nargsf` 包括 `args[0]` 在的位置引數的數量，如果 `args[0]` 的值可能被臨時改變則要再加上 `PY_VECTORCALL_ARGUMENTS_OFFSET`。關鍵字引數可以像在 `PyObject_Vectorcall()` 中一樣被傳入。

如果物件具有 `Py_TPFLAGS_METHOD_DESCRIPTOR` 特性，這將以完整的 `args` 向量作引數來呼叫 `unbound method`（未綁結方法）物件。

成功時回傳結果，或在失敗時引發一個例外回傳 `NULL`。

3.9 版新加入。

7.2.4 呼叫支援 API

`int PyCallable_Check(PyObject *o)`

Part of the Stable ABI. 判定物件 `o` 是否可呼叫的。如果物件是可呼叫物件則回傳 1，其他情況回傳 0。這個函式不會呼叫失敗。

7.3 數字協議

`int PyNumber_Check(PyObject *o)`

Part of the Stable ABI. 如果對象 `o` 提供數字的協議，返回真 1，否則返回假。這個函數不會調用失敗。

3.8 版更變：如果 `o` 是一個索引整數則返回 1。

`PyObject *PyNumber_Add(PyObject *o1, PyObject *o2)`

Return value: New reference. Part of the Stable ABI. 返回 `o1`、`o2` 相加的結果，如果失敗，返回 `NULL`。等價於 Python 表达式 `o1 + o2`。

`PyObject *PyNumber_Subtract(PyObject *o1, PyObject *o2)`

Return value: New reference. Part of the Stable ABI. 返回 `o1` 減去 `o2` 的結果，如果失敗，返回 `NULL`。等價於 Python 表达式 `o1 - o2`。

`PyObject *PyNumber_Multiply(PyObject *o1, PyObject *o2)`

Return value: New reference. Part of the Stable ABI. 返回 `o1`、`o2` 相乘的結果，如果失敗，返回 `NULL`。等價於 Python 表达式 `o1 * o2`。

`PyObject *PyNumber_MatrixMultiply(PyObject *o1, PyObject *o2)`

Return value: New reference. Part of the Stable ABI since version 3.7. 返回 `o1`、`o2` 做矩陣乘法的結果，如果失敗，返回 `NULL`。等價於 Python 表达式 `o1 @ o2`。

3.5 版新加入。

`PyObject *PyNumber_FloorDivide(PyObject *o1, PyObject *o2)`

Return value: New reference. Part of the Stable ABI. 返回 `o1` 除以 `o2` 向下取整的值，失敗時返回 `NULL`。這等價於 Python 表达式 `o1 // o2`。

`PyObject *PyNumber_TrueDivide(PyObject *o1, PyObject *o2)`

Return value: New reference. Part of the Stable ABI. 返回 `o1` 除以 `o2` 的數學值的合理近似值，或失敗時返回 `NULL`。返回的是“近似值”因為二進制浮點數本身就是近似值；不可能以二進制精確表示所有實數。此函數可以在傳入兩個整數時返回一個浮點值。此函數等價於 Python 表达式 `o1 / o2`。

`PyObject *PyNumber_Remainder(PyObject *o1, PyObject *o2)`

Return value: New reference. Part of the Stable ABI. 返回 `o1` 除以 `o2` 得到的余數，如果失敗，返回 `NULL`。等價於 Python 表达式 `o1 % o2`。

`PyObject *PyNumber_Divmod(PyObject *o1, PyObject *o2)`

Return value: New reference. Part of the Stable ABI. 參考內置函數 `divmod()`。如果失敗，返回 `NULL`。等價於 Python 表达式 `divmod(o1, o2)`。

`PyObject *PyNumber_Power(PyObject *o1, PyObject *o2, PyObject *o3)`

Return value: New reference. Part of the Stable ABI. 請參閱內置函數 `pow()`。如果失敗，返回 `NULL`。等價於 Python 中的表达式 `pow(o1, o2, o3)`，其中 `o3` 是可選的。如果要忽略 `o3`，則需傳入 `Py_None` 作為代替（如果傳入 `NULL` 會導致非法內存訪問）。

PyObject *PyNumber_Negative (PyObject *o)

Return value: New reference. Part of the Stable ABI. 返回 *o* 的负值，如果失败，返回 NULL。等价于 Python 表达式 `-o`。

PyObject *PyNumber_Positive (PyObject *o)

Return value: New reference. Part of the Stable ABI. 返回 *o*，如果失败，返回 NULL。等价于 Python 表达式 `+o`。

PyObject *PyNumber_Absolute (PyObject *o)

Return value: New reference. Part of the Stable ABI. 返回 *o* 的绝对值，如果失败，返回 NULL。等价于 Python 表达式 `abs(o)`。

PyObject *PyNumber_Invert (PyObject *o)

Return value: New reference. Part of the Stable ABI. 返回 *o* 的按位取反后的结果，如果失败，返回 NULL。等价于 Python 表达式 `~o`。

PyObject *PyNumber_Lshift (PyObject *o1, PyObject *o2)

Return value: New reference. Part of the Stable ABI. 返回 *o1* 左移 *o2* 个比特后的结果，如果失败，返回 NULL。等价于 Python 表达式 `o1 << o2`。

PyObject *PyNumber_Rshift (PyObject *o1, PyObject *o2)

Return value: New reference. Part of the Stable ABI. 返回 *o1* 右移 *o2* 个比特后的结果，如果失败，返回 NULL。等价于 Python 表达式 `o1 >> o2`。

PyObject *PyNumber_And (PyObject *o1, PyObject *o2)

Return value: New reference. Part of the Stable ABI. 返回 *o1* 和 *o2* “按位与”的结果，如果失败，返回 NULL。等价于 Python 表达式 `o1 & o2`。

PyObject *PyNumber_Xor (PyObject *o1, PyObject *o2)

Return value: New reference. Part of the Stable ABI. 返回 *o1* 和 *o2* “按位异或”的结果，如果失败，返回 NULL。等价于 Python 表达式 `o1 ^ o2`。

PyObject *PyNumber_Or (PyObject *o1, PyObject *o2)

Return value: New reference. Part of the Stable ABI. 返回 *o1* 和 *o2* “按位或”的结果，如果失败，返回 NULL。等价于 Python 表达式 `o1 | o2`。

PyObject *PyNumber_InPlaceAdd (PyObject *o1, PyObject *o2)

Return value: New reference. Part of the Stable ABI. 返回 *o1*、*o2* 相加的结果，如果失败，返回 NULL。当 *o1* 支持时，这个运算直接使用它储存结果。等价于 Python 语句 `o1 += o2`。

PyObject *PyNumber_InPlaceSubtract (PyObject *o1, PyObject *o2)

Return value: New reference. Part of the Stable ABI. 返回 *o1*、*o2* 相减的结果，如果失败，返回 NULL。当 *o1* 支持时，这个运算直接使用它储存结果。等价于 Python 语句 `o1 -= o2`。

PyObject *PyNumber_InPlaceMultiply (PyObject *o1, PyObject *o2)

Return value: New reference. Part of the Stable ABI. 返回 *o1*、*o2** 相乘的结果，如果失败，返回 “NULL”。当 *o1* 支持时，这个运算直接使用它储存结果。等价于 Python 语句 `o1 *= o2`。

PyObject *PyNumber_InPlaceMatrixMultiply (PyObject *o1, PyObject *o2)

Return value: New reference. Part of the Stable ABI since version 3.7. 返回 *o1*、*o2* 做矩阵乘法后的结果，如果失败，返回 NULL。当 *o1* 支持时，这个运算直接使用它储存结果。等价于 Python 语句 `o1 @= o2`。

3.5 版新加入。

PyObject *PyNumber_InPlaceFloorDivide (PyObject *o1, PyObject *o2)

Return value: New reference. Part of the Stable ABI. 返回 *o1* 除以 *o2* 后向下取整的结果，如果失败，返回 NULL。当 *o1* 支持时，这个运算直接使用它储存结果。等价于 Python 语句 `o1 //= o2`。

PyObject *PyNumber_InPlaceTrueDivide (PyObject *o1, PyObject *o2)

Return value: New reference. Part of the Stable ABI. 返回 *o1* 除以 *o2* 的数学值的合理近似值，或失败时返回 NULL。返回的是“近似值”因为二进制浮点数本身就是近似值；不可能以二进制精确表示所有实数。此函数可以在传入两个整数时返回一个浮点数。此运算在 *o1* 支持的时候会原地执行。此函数等价于 Python 语句 `o1 /= o2`。

PyObject *PyNumber_InPlaceRemainder (PyObject *o1, PyObject *o2)

Return value: New reference. Part of the [Stable ABI](#). 返回 *o1* 除以 *o2* 得到的余数, 如果失败, 返回 NULL。当 *o1* 支持时, 这个运算直接使用它储存结果。等价于 Python 语句 `o1 %= o2`。

PyObject *PyNumber_InPlacePower (PyObject *o1, PyObject *o2, PyObject *o3)

Return value: New reference. Part of the [Stable ABI](#). 请参阅内置函数 `pow()`。如果失败, 返回 NULL。当 *o1* 支持时, 这个运算直接使用它储存结果。当 *o3* 是 `Py_None` 时, 等价于 Python 语句 `o1 **= o2`; 否则等价于在原来位置储存结果的 `pow(o1, o2, o3)`。如果要忽略 *o3*, 则需传入 `Py_None` (传入 NULL 会导致非法内存访问)。

PyObject *PyNumber_InPlaceLshift (PyObject *o1, PyObject *o2)

Return value: New reference. Part of the [Stable ABI](#). 返回 *o1* 左移 *o2* 个比特后的结果, 如果失败, 返回 NULL。当 *o1* 支持时, 这个运算直接使用它储存结果。等价于 Python 语句 `o1 <<= o2`。

PyObject *PyNumber_InPlaceRshift (PyObject *o1, PyObject *o2)

Return value: New reference. Part of the [Stable ABI](#). 返回 *o1* 右移 *o2* 个比特后的结果, 如果失败, 返回 NULL。当 *o1* 支持时, 这个运算直接使用它储存结果。等价于 Python 语句 `o1 >>= o2`。

PyObject *PyNumber_InPlaceAnd (PyObject *o1, PyObject *o2)

Return value: New reference. Part of the [Stable ABI](#). 成功时返回 *o1* 和 *o2* ”按位与”的结果, 失败时返回 NULL。在 *o1* 支持的前提下该操作将 原地执行。等价与 Python 语句 `o1 &= o2`。

PyObject *PyNumber_InPlaceXor (PyObject *o1, PyObject *o2)

Return value: New reference. Part of the [Stable ABI](#). 成功时返回 *o1* 和 *o2* ”按位异或”的结果, 失败时返回 NULL。在 *o1* 支持的前提下该操作将 原地执行。等价与 Python 语句 `o1 ^= o2`。

PyObject *PyNumber_InPlaceOr (PyObject *o1, PyObject *o2)

Return value: New reference. Part of the [Stable ABI](#). 成功时返回 *o1* 和 *o2* ”按位或”的结果, 失败时返回 NULL。在 *o1* 支持的前提下该操作将 原地执行。等价于 Python 语句 `o1 |= o2`。

PyObject *PyNumber_Long (PyObject *o)

Return value: New reference. Part of the [Stable ABI](#). 成功时返回 *o* 转换为整数对象后的结果, 失败时返回 NULL。等价于 Python 表达式 `int(o)`。

PyObject *PyNumber_Float (PyObject *o)

Return value: New reference. Part of the [Stable ABI](#). 成功时返回 *o* 转换为浮点对象后的结果, 失败时返回 NULL。等价于 Python 表达式 `float(o)`。

PyObject *PyNumber_Index (PyObject *o)

Return value: New reference. Part of the [Stable ABI](#). 成功时返回 *o* 转换为 Python `int` 类型后的结果, 失败时返回 NULL 并引发 `TypeError` 异常。

3.10 版更變: 结果总是为 `int` 类型。在之前版本中, 结果可能为 `int` 的子类的实例。

PyObject *PyNumber_ToBase (PyObject *n, int base)

Return value: New reference. Part of the [Stable ABI](#). 返回整数 *n* 转换成以 *base* 为基数的字符串后的结果。这个 *base* 参数必须是 2, 8, 10 或者 16。对于基数 2, 8, 或 16, 返回的字符串将分别加上基数标识 `'0b'`, `'0o'`, 或 `'0x'`。如果 *n* 不是 Python 中的整数 `int` 类型, 就先通过 `PyNumber_Index()` 将它转换成整数类型。

Py_ssize_t PyNumber_AsSsize_t (PyObject *o, PyObject *exc)

Part of the [Stable ABI](#). 如果 *o* 可以被解读为一个整数则返回 *o* 转换成的 `Py_ssize_t` 值。如果调用失败, 则会引发一个异常并返回 -1。

如果 *o* 可以被转换为 Python 的 `int` 值但尝试转换为 `Py_ssize_t` 值则会引发 `OverflowError`, 则 *exc* 参数将为所引发的异常类型 (通常为 `IndexError` 或 `OverflowError`)。如果 *exc* 为 NULL, 则异常会被清除并且值会在为负整数时被裁剪为 `PY_SSIZE_T_MIN` 而在为正整数时被裁剪为 `PY_SSIZE_T_MAX`。

int PyIndex_Check (PyObject *o)

Part of the [Stable ABI since version 3.8](#). 返回 1 如果 *o* 是一个索引整数 (将 `nb_index` 槽位填充到 `tp_as_number` 结构体), 或者在其他情况下返回 0。此函数总是会成功执行。

7.4 序列协议

int PySequence_Check (PyObject *o)

Part of the Stable ABI. 如果对象提供了序列协议则返回 1，否则返回 0。请注意它将为具有 `__getitem__()` 方法的 Python 类返回 1，除非它们是 `dict` 的子类，因为在通常情况下无法确定这种类支持哪种键类型。此函数总是会成功执行。

Py_ssize_t PySequence_Size (PyObject *o)

Py_ssize_t PySequence_Length (PyObject *o)

Part of the Stable ABI. 成功时返回序列中 `*o` 的对象数，失败时返回 `-1`。相当于 Python 的 `len(o)` 表达式。

PyObject *PySequence_Concat (PyObject *o1, PyObject *o2)

Return value: New reference. Part of the Stable ABI. 成功时返回 `o1` 和 `o2` 的拼接，失败时返回 `NULL`。这等于 Python 表达式 `o1 + o2`。

PyObject *PySequence_Repeat (PyObject *o, Py_ssize_t count)

Return value: New reference. Part of the Stable ABI. 返回序列对象 `o` 重复 `count` 次的结果，失败时返回 `NULL`。这等于 Python 表达式 `o * count`。

PyObject *PySequence_InPlaceConcat (PyObject *o1, PyObject *o2)

Return value: New reference. Part of the Stable ABI. 成功时返回 `o1` 和 `o2` 的拼接，失败时返回 `NULL`。在 `o1` 支持的情况下操作将原地完成。这等于 Python 表达式 `o1 += o2`。

PyObject *PySequence_InPlaceRepeat (PyObject *o, Py_ssize_t count)

Return value: New reference. Part of the Stable ABI. Return the result of repeating sequence object 返回序列对象 `o` 重复 `count` 次的结果，失败时返回 `NULL`。在 `o` 支持的情况下该操作会原地完成。这等于 Python 表达式 `o *= count`。

PyObject *PySequence_GetItem (PyObject *o, Py_ssize_t i)

Return value: New reference. Part of the Stable ABI. 返回 `o` 中的第 `i` 号元素，失败时返回 `NULL`。这等于 Python 表达式 `o[i]`。

PyObject *PySequence_GetSlice (PyObject *o, Py_ssize_t i1, Py_ssize_t i2)

Return value: New reference. Part of the Stable ABI. 返回序列对象 `o` 的 `i1` 到 `i2` 的切片，失败时返回 `NULL`。这等于 Python 表达式 `o[i1:i2]`。

int PySequence_SetItem (PyObject *o, Py_ssize_t i, PyObject *v)

Part of the Stable ABI. 将对象 `v` 赋值给 `o` 的第 `i` 号元素。失败时会引发异常并返回 `-1`；成功时返回 `0`。这相当于 Python 语句 `o[i] = v`。此函数不会改变对 `v` 的引用。

如果 `v` 为 `NULL`，元素将被删除，但是此特性已被弃用而应改用 `PySequence_DelItem()`。

int PySequence_DelItem (PyObject *o, Py_ssize_t i)

Part of the Stable ABI. 删除对象 `o` 的第 `i` 号元素。失败时返回 `-1`。这相当于 Python 语句 `del o[i]`。

int PySequence_SetSlice (PyObject *o, Py_ssize_t i1, Py_ssize_t i2, PyObject *v)

Part of the Stable ABI. 将序列对象 `v` 赋值给序列对象 `o` 的从 `i1` 到 `i2` 切片。这相当于 Python 语句 `o[i1:i2] = v`。

int PySequence_DelSlice (PyObject *o, Py_ssize_t i1, Py_ssize_t i2)

Part of the Stable ABI. 删除序列对象 `o` 的从 `i1` 到 `i2` 的切片。失败时返回 `-1`。这相当于 Python 语句 `del o[i1:i2]`。

Py_ssize_t PySequence_Count (PyObject *o, PyObject *value)

Part of the Stable ABI. 返回 `value` 在 `o` 中出现的次数，即返回使得 `o[key] == value` 的键的数量。失败时返回 `-1`。这相当于 Python 表达式 `o.count(value)`。

int PySequence_Contains (PyObject *o, PyObject *value)

Part of the Stable ABI. 确定 `o` 是否包含 `value`。如果 `o` 中的某一项等于 `value`，则返回 1，否则返回 0。出错时，返回 `-1`。这相当于 Python 表达式 `value in o`。

Py_ssize_t PySequence_Index (PyObject *o, PyObject *value)

Part of the Stable ABI. 返回第一个索引 `*i`，其中 `o[i] == value`。出错时，返回 `-1`。相当于 Python 的 `o.index(value)` 表达式。

PyObject*PySequence_List(PyObject*o)

Return value: New reference. Part of the [Stable ABI](#). 返回一个列表对象，其内容与序列或可迭代对象 *o* 相同，失败时返回 NULL。返回的列表保证是一个新对象。这等价于 Python 表达式 `list(o)`。

PyObject*PySequence_Tuple(PyObject*o)

Return value: New reference. Part of the [Stable ABI](#). 返回一个元组对象，其内容与序列或可迭代对象 *o* 相同，失败时返回 NULL。如果 *o* 为元组，则将返回一个新的引用，在其他情况下将使用适当的内容构造一个元组。这等价于 Python 表达式 `tuple(o)`。

PyObject*PySequence_Fast(PyObject*o, const char*m)

Return value: New reference. Part of the [Stable ABI](#). 将序列或可迭代对象 *o* 作为其他 `PySequence_Fast*` 函数族可用的对象返回。如果该对象不是序列或可迭代对象，则会引发 `TypeError` 并将 *m* 作为消息文本。失败时返回 NULL。

`PySequence_Fast*` 函数之所以这样命名，是因为它们会假定 *o* 是一个 `PyTupleObject` 或 `PyListObject` 并直接访问 *o* 的数据字段。

作为 CPython 的实现细节，如果 *o* 已经是一个序列或列表，它将被直接返回。

Py_ssize_t PySequence_Fast_GET_SIZE(PyObject*o)

在 *o* 由 `PySequence_Fast()` 返回且 *o* 不为 NULL 的情况下返回 *o* 长度。也可以通过在 *o* 上调用 `PySequence_Size()` 来获取大小，但是 `PySequence_Fast_GET_SIZE()` 的速度更快因为它可以假定 *o* 为列表或元组。

PyObject*PySequence_Fast_GET_ITEM(PyObject*o, Py_ssize_t i)

Return value: Borrowed reference. 在 *o* 由 `PySequence_Fast()` 返回且 *o* 不为 NULL，并且 *i* 在索引范围内的情况下返回 *o* 的第 *i* 号元素。

PyObjectPySequence_Fast_ITEMS(PyObject*o)**

返回 `PyObject` 指针的底层数组。假设 *o* 由 `PySequence_Fast()` 返回且 *o* 不为 NULL。

请注意，如果列表调整大小，重新分配可能会重新定位 `items` 数组。因此，仅在序列无法更改的上下文中使用基础数组指针。

PyObject*PySequence_ITEM(PyObject*o, Py_ssize_t i)

Return value: New reference. 返回 *o* 的第 *i* 个元素或在失败时返回 NULL。此形式比 `PySequence_GetItem()` 理饌，但不会检查 *o* 上的 `PySequence_Check()` 是否为真值，也不会对负序号进行调整。

7.5 映射协议

参见 `PyObject_GetItem()`、`PyObject_SetItem()` 与 `PyObject_DelItem()`。

int PyMapping_Check(PyObject*o)

Part of the [Stable ABI](#). 如果对象提供了映射协议或是支持切片则返回 1，否则返回 0。请注意它将为具有 `__getitem__()` 方法的 Python 类返回 1，因为在通常情况下无法确定该类所支持的键类型。此函数总是会成功执行。

Py_ssize_t PyMapping_Size(PyObject*o)

Py_ssize_t PyMapping_Length(PyObject*o)

Part of the [Stable ABI](#). 成功时返回对象 *o* 中键的数量，失败时返回 -1。这相当于 Python 表达式 `len(o)`。

PyObject*PyMapping_GetItemString(PyObject*o, const char*key)

Return value: New reference. Part of the [Stable ABI](#). 返回 *o* 中对应于字符串 *key* 的元素，或者失败时返回 NULL。这相当于 Python 表达式 `o[key]`。另请参见 also `PyObject_GetItem()`。

int PyMapping_SetItemString(PyObject*o, const char*key, PyObject*v)

Part of the [Stable ABI](#). 在对象 *o* 中将字符串 *key* 映射到值 *v*。失败时返回 -1。这相当于 Python 语句 `o[key] = v`。另请参见 `PyObject_SetItem()`。此函数不会增加对 *v* 的引用。

int PyMapping_DelItem (*PyObject* *o, *PyObject* *key)

从对象 *o* 中移除对象 *key* 的映射。失败时返回 -1。这相当于 Python 语句 `del o[key]`。这是 *PyObject_DelItem()* 的一个别名。

int PyMapping_DelItemString (*PyObject* *o, *const char* *key)

从对象 *o* 中移除字符串 *key* 的映射。失败时返回 -1。这相当于 Python 语句 `del o[key]`。

int PyMapping_HasKey (*PyObject* *o, *PyObject* *key)

Part of the Stable ABI. 如果映射对象具有键 *key* 则返回 1，否则返回 0。这相当于 Python 表达式 `key in o`。此函数总是会成功执行。

请注意在调用 `__getitem__()` 方法期间发生的异常将会被屏蔽。要获取错误报告请改用 *PyObject_GetItem()*。

int PyMapping_HasKeyString (*PyObject* *o, *const char* *key)

Part of the Stable ABI. 如果映射对象具有键 *key* 则返回 1，否则返回 0。这相当于 Python 表达式 `key in o`。此函数总是会成功执行。

请注意在调用 `__getitem__()` 方法期间发生的异常将会被屏蔽。要获取错误报告请改用 *PyMapping_GetItemString()*。

PyObject ***PyMapping_Keys** (*PyObject* *o)

Return value: New reference. Part of the Stable ABI. 成功时，返回对象 *o* 中的键的列表。失败时，返回 NULL。

3.7 版更變: 在之前版本中，此函数返回一个列表或元组。

PyObject ***PyMapping_Values** (*PyObject* *o)

Return value: New reference. Part of the Stable ABI. 成功时，返回对象 *o* 中的值的列表。失败时，返回 NULL。

3.7 版更變: 在之前版本中，此函数返回一个列表或元组。

PyObject ***PyMapping_Items** (*PyObject* *o)

Return value: New reference. Part of the Stable ABI. 成功时，返回对象 *o* 中条目的列表，其中每个条目是一个包含键值对的元组。失败时，返回 NULL。

3.7 版更變: 在之前版本中，此函数返回一个列表或元组。

7.6 迭代器协议

迭代器有两个函数。

int PyIter_Check (*PyObject* *o)

Part of the Stable ABI since version 3.8. 如果对象 *o* 可以被安全地把传给 *PyIter_Next()* 则返回非零值，否则返回 0。此函数总是会成功执行。

int PyAsyncIter_Check (*PyObject* *o)

Part of the Stable ABI since version 3.10. 如果对象 *o* 提供了 `AsyncIterator` 协议则返回非零值，否则返回 0。此函数总是会成功执行。

3.10 版新加入。

PyObject ***PyIter_Next** (*PyObject* *o)

Return value: New reference. Part of the Stable ABI. 从迭代器 *o* 返回下一个值。对象必须可被 *PyIter_Check()* 确认为迭代器（需要调用方来负责检查）。如果没有剩余的值，则返回 NULL 并且不设置异常。如果在获取条目时发生了错误，则返回 NULL 并且传递异常。

要为迭代器编写一个循环，C 代码应该看起来像这样

```
PyObject *iterator = PyObject_GetIter(obj);
PyObject *item;

if (iterator == NULL) {
```

(下页继续)

(繼續上一頁)

```

    /* propagate error */
}

while ((item = PyIter_Next(iterator))) {
    /* do something with item */
    ...
    /* release reference when done */
    Py_DECREF(item);
}

Py_DECREF(iterator);

if (PyErr_Occurred()) {
    /* propagate error */
}
else {
    /* continue doing useful work */
}

```

type PySendResult

用于代表 `PyIter_Send()` 的不同结果的枚举值。

3.10 版新加入。

PySendResult PyIter_Send (*PyObject *iter, PyObject *arg, PyObject **presult*)

Part of the Stable ABI since version 3.10. 将 *arg* 值发送到迭代器 *iter*。返回:

- PYGEN_RETURN, 如果迭代器返回的话。返回值会通过 *presult* 来返回。
- PYGEN_NEXT, 如果迭代器生成值的话。生成的值会通过 *presult* 来返回。
- PYGEN_ERROR, 如果迭代器引发异常的话。*presult* 会被设为 NULL。

3.10 版新加入。

7.7 緩冲協定 (Buffer Protocol)

在 Python 中可使用一些对象来包装对底层内存数组或称 缓冲的访问。此类对象包括内置的 `bytes` 和 `bytearray` 以及一些如 `array.array` 这样的扩展类型。第三方库也可能会为了特殊的目的而定义它们自己的类型，例如用于图像处理 and 数值分析等。

虽然这些类型中的每一种都有自己的语义，但它们具有由可能较大的内存缓冲区支持的共同特征。在某些情况下，希望直接访问该缓冲区而无需中间复制。

Python 以 [缓冲协议](#) 的形式在 C 层级上提供这样的功能。此协议包括两个方面:

- 在生产者这一方面，该类型的协议可以导出一个“缓冲区接口”，允许公开它的底层缓冲区信息。该接口的描述信息在 [Buffer Object Structures](#) 一节中；
- 在消费者一侧，有几种方法可用于获得指向对象的原始底层数据的指针（例如一个方法的形参）。

一些简单的对象例如 `bytes` 和 `bytearray` 会以面向字节的形式公开它们的底层缓冲区。也可能会有其他形式；例如 `array.array` 所公开的元素可以是多字节值。

缓冲区接口的消费者的一个例子是文件对象的 `write()` 方法：任何可以输出为一系列字节流的对象可以被写入文件。然而 `write()` 方法只需要对于传入对象的只读权限，其他的方法，如 `readinto()` 需要参数内容的写入权限。缓冲区接口使得对象可以选择性地允许或拒绝读写或只读缓冲区的导出。

对于缓冲区接口的使用者而言，有两种方式来获取一个目的对象的缓冲:

- 使用正确的参数来调用 `PyObject_GetBuffer()` 函数；
- 调用 `PyArg_ParseTuple()` (或其同级对象之一) 并传入 `y*`, `w*` or `s*` 格式代码 中的一个。

在这两种情况下，当不再需要缓冲区时必须调用 `PyBuffer_Release()`。如果此操作失败，可能会导致各种问题，例如资源泄漏。

7.7.1 缓冲区结构

缓冲区结构（或者简单地称为“buffers”）对于将二进制数据从另一个对象公开给 Python 程序员非常有用。它们还可以用作零拷贝切片机。使用它们引用内存块的能力，可以很容易地将任何数据公开给 Python 程序员。内存可以是 C 扩展中的一个大的常量数组，也可以是在传递到操作系统库之前用于操作的原始内存块，或者可以用来传递本机内存格式的结构化数据。

与 Python 解释器公开的大多数数据类型不同，缓冲区不是 `PyObject` 指针而是简单的 C 结构。这使得它们可以非常简单地创建和复制。当需要为缓冲区加上泛型包装器时，可以创建一个内存视图对象。

有关如何编写并导出对象的简短说明，请参阅缓冲区对象结构。要获取缓冲区对象，请参阅 `PyObject_GetBuffer()`。

type `Py_buffer`

void *`buf`

指向由缓冲区字段描述的逻辑结构开始的指针。这可以是导出程序底层物理内存块中的任何位置。例如，使用负的 `strides` 值可能指向内存块的末尾。

对于 `contiguous`，‘邻接’数组，值指向内存块的开头。

`PyObject *``obj`

对导出对象的新引用。该引用归使用者所有，并由 `PyBuffer_Release()` 自动递减并设置为 NULL。该字段等于任何标准 C-API 函数的返回值。

作为一种特殊情况，对于由 `PyMemoryView_FromBuffer()` 或 `PyBuffer_FillInfo()` 包装的 `temporary` 缓冲区，此字段为 NULL。通常，导出对象不得使用此方案。

`Py_ssize_t` `len`

`product(shape) * itemsize`。对于连续数组，这是基础内存块的长度。对于非连续数组，如果逻辑结构复制到连续表示形式，则该长度将具有该长度。

仅当缓冲区是通过保证连续性的请求获取时，才访问 `((char *)buf)[0]` up to `((char *)buf)[len-1]` 时才有效。在大多数情况下，此类请求将为 `PyBUF_SIMPLE` 或 `PyBUF_WRITABLE`。

int `readonly`

缓冲区是否为只读的指示器。此字段由 `PyBUF_WRITABLE` 标志控制。

`Py_ssize_t` `itemsize`

单个元素的项大小（以字节为单位）。与 `struct.calcsize()` 调用非 NULL `format` 的值相同。

重要例外：如果使用者请求的缓冲区没有 `PyBUF_FORMAT` 标志，`format` 将设置为 NULL，但 `itemsize` 仍具有原始格式的值。

如果 `shape` 存在，则相等的 `product(shape) * itemsize == len` 仍然存在，使用者可以使用 `itemsize` 来导航缓冲区。

如果 `shape` 是 NULL，因为结果为 `PyBUF_SIMPLE` 或 `PyBUF_WRITABLE` 请求，则使用者必须忽略 `itemsize`，并假设 `itemsize == 1`。

const char *`format`

在 `struct` 模块样式语法中 `NUL` 字符串，描述单个项的内容。如果这是 NULL，则假定为“‘B’”（无符号字节）。

此字段由 `PyBUF_FORMAT` 标志控制。

int `ndim`

内存表示为 `n` 维数组的维数。如果是“0”，`buf` 指向表示标量的单个项目。在这种情况下，`shape`、`strides` 和 `suboffsets` 必须是“NULL”。

宏 `PyBUF_MAX_NDIM` 将最大维度数限制为 64。导出程序必须遵守这个限制，多维缓冲区的使用者应该能够处理最多 `PyBUF_MAX_NDIM` 维度。

`Py_ssize_t *shape`

一个长度为 `Py_ssize_t` 的数组 `ndim` 表示作为 `n` 维数组的内存形状。请注意，`shape[0] * ... * shape[ndim-1] * itemsize` 必须等于 `len`。

`Shape` 形状数组中的值被限定在 `shape[n] >= 0`。`shape[n] == 0` 这一情形需要特别注意。更多信息请参阅 [complex arrays](#)。

`shape` 数组对于使用者来说是只读的。

`Py_ssize_t *strides`

一个长度为 `Py_ssize_t` 的数组 `ndim` 给出要跳过的字节数以获取每个尺寸中的新元素。

`Stride` 步幅数组中的值可以为任何整数。对于常规数组，步幅通常为正数，但是使用者必须能够处理 `strides[n] <= 0` 的情况。更多信息请参阅 [complex arrays](#)。

`strides` 数组对用户来说是只读的。

`Py_ssize_t *suboffsets`

一个长度为 `ndim` 类型为 `Py_ssize_t` 的数组。如果 `suboffsets[n] >= 0`，则第 `n` 维存储的是指针，`suboffset` 值决定了解除引用时要给指针增加多少字节的偏移。`suboffset` 为负值，则表示不应解除引用（在连续内存块中移动）。

如果所有子偏移均为负（即无需取消引用），则此字段必须为 `NULL`（默认值）。

Python Imaging Library (PIL) 中使用了这种类型的数组表达方式。请参阅 [complex arrays](#) 来了解如何从这样一个数组中访问元素。

`suboffsets` 数组对于使用者来说是只读的。

`void *internal`

供输出对象内部使用。比如可能被输出程序重组为一个整数，用于存储一个标志，标明在缓冲区释放时是否必须释放 `shape`、`strides` 和 `suboffsets` 数组。消费者程序不得修改该值。

7.7.2 缓冲区请求的类型

通常，通过 `PyObject_GetBuffer()` 向输出对象发送缓冲区请求，即可获得缓冲区。由于内存的逻辑结构复杂，可能会有很大差异，缓冲区使用者可用 `flags` 参数指定其能够处理的缓冲区具体类型。

所有 `Py_buffer` 字段均由请求类型明确定义。

与请求无关的字段

以下字段不会被 `flags` 影响，并且必须总是用正确的值填充：`obj`, `buf`, `len`, `itemsize`, `ndim`。

只读，格式

`PyBUF_WRITABLE`

控制 `readonly` 字段。如果设置了，输出程序必须提供一个可写的缓冲区，否则报告失败。若未设置，输出程序可以提供只读或可写的缓冲区，但对所有消费者程序必须保持一致。

`PyBUF_FORMAT`

控制 `format` 字段。如果设置，则必须正确填写此字段。其他情况下，此字段必须为“NULL”。

`PyBUF_WRITABLE` 可以和下一节的所有标志联用。由于 `PyBUF_SIMPLE` 定义为 0，所以 `PyBUF_WRITABLE` 可以作为一个独立的标志，用于请求一个简单的可写缓冲区。

`PyBUF_FORMAT` 可以被设为除了 `PyBUF_SIMPLE` 之外的任何标志。后者已经按暗示了“B”(无符号字节串) 格式。

形状，步幅，子偏移量

控制内存逻辑结构的标志按照复杂度的递减顺序列出。注意，每个标志包含它下面的所有标志。

请求	形状	步幅	子偏移量
PyBUF_INDIRECT	是	是	如果需要的话
PyBUF_STRIDES	是	是	NULL
PyBUF_ND	是	NULL	NULL
PyBUF_SIMPLE	NULL	NULL	NULL

连续性的请求

可以显式地请求 C 或 Fortran 连续，不管有没有步幅信息。若没有步幅信息，则缓冲区必须是 C-连续的。

请求	形状	步幅	子偏移量	邻接
PyBUF_C_CONTIGUOUS	是	是	NULL	C
PyBUF_F_CONTIGUOUS	是	是	NULL	F
PyBUF_ANY_CONTIGUOUS	是	是	NULL	C 或 F
<i>PyBUF_ND</i>	是	NULL	NULL	C

复合请求

所有可能的请求都由上一节中某些标志的组合完全定义。为方便起见，缓冲区协议提供常用的组合作为单个标志。

在下表中，*U* 代表连续性未定义。消费者程序必须调用 `PyBuffer_IsContiguous()` 以确定连续性。

请求	形状	步幅	子偏移量	邻接	只读	format
PyBUF_FULL	是	是	如果需要的话	U	0	是
PyBUF_FULL_RO	是	是	如果需要的话	U	1 或 0	是
PyBUF_RECORDS	是	是	NULL	U	0	是
PyBUF_RECORDS_RO	是	是	NULL	U	1 或 0	是
PyBUF_STRIDED	是	是	NULL	U	0	NULL
PyBUF_STRIDED_RO	是	是	NULL	U	1 或 0	NULL
PyBUF_CONTIG	是	NULL	NULL	C	0	NULL
PyBUF_CONTIG_RO	是	NULL	NULL	C	1 或 0	NULL

7.7.3 复杂数组

NumPy-风格：形状和步幅

NumPy 风格数组的逻辑结构由 *itemsizesize*、*ndim*、*shape* 和 *strides* 定义。

如果 *ndim* == 0，*buf* 指向的内存位置被解释为大小为 *itemsizesize* 的标量。这时，*shape* 和 *strides* 都为 NULL。

如果 *strides* 为 NULL，则数组将被解释为一个标准的 *n* 维 C 语言数组。否则，消费者程序必须按如下方式访问 *n* 维数组：

```
ptr = (char *)buf + indices[0] * strides[0] + ... + indices[n-1] * strides[n-1];
item = *((typeof(item) *)ptr);
```

如上所述，*buf* 可以指向实际内存块中的任意位置。输出者程序可以用该函数检查缓冲区的有效性。

```
def verify_structure(memlen, itemsizesize, ndim, shape, strides, offset):
    """Verify that the parameters represent a valid array within
    the bounds of the allocated memory:
        char *mem: start of the physical memory block
        memlen: length of the physical memory block
        offset: (char *)buf - mem
    """
    if offset % itemsizesize:
        return False
    if offset < 0 or offset+itemsizesize > memlen:
        return False
    if any(v % itemsizesize for v in strides):
        return False

    if ndim <= 0:
        return ndim == 0 and not shape and not strides
    if 0 in shape:
        return True
```

(下页继续)

(繼續上一頁)

```

imin = sum(strides[j]*(shape[j]-1) for j in range(ndim)
        if strides[j] <= 0)
imax = sum(strides[j]*(shape[j]-1) for j in range(ndim)
        if strides[j] > 0)

return 0 <= offset+imin and offset+imax+itemsiz <= memlen

```

PIL-风格：形状，步幅和子偏移量

除了常规项之外，PIL 风格的数组还可以包含指针，必须跟随这些指针才能到达维度的下一个元素。例如，常规的三维 C 语言数组 `char v[2][2][3]` 可以看作是一个指向 2 个二维数组的 2 个指针：`char (*v[2])[2][3]`。在子偏移表示中，这两个指针可以嵌入在 `buf` 的开头，指向两个可以位于内存任何位置的 `char x[2][3]` 数组。

这是一个函数，当 `n` 维索引所指向的 N-D 数组中有“NULL”步长和子偏移量时，它返回一个指针

```

void *get_item_pointer(int ndim, void *buf, Py_ssize_t *strides,
                      Py_ssize_t *suboffsets, Py_ssize_t *indices) {
    char *pointer = (char*)buf;
    int i;
    for (i = 0; i < ndim; i++) {
        pointer += strides[i] * indices[i];
        if (suboffsets[i] >= 0) {
            pointer = *((char**)pointer) + suboffsets[i];
        }
    }
    return (void*)pointer;
}

```

7.7.4 缓冲区相关函数

`int PyObject_CheckBuffer (PyObject *obj)`

如果 `obj` 支持缓冲区接口，则返回 1，否则返回 0。返回 1 时不保证 `PyObject_GetBuffer()` 一定成功。本函数一定调用成功。

`int PyObject_GetBuffer (PyObject *exporter, Py_buffer *view, int flags)`

向输出器程序发送请求，按照 `flags` 指定的内容填充 `view`。如果输出器程序不能提供准确类型的缓冲区，必须触发 `PyExc_BufferError`，设置 `view->obj` 为 `NULL` 并返回 -1。

成功时，填充 `view`，将 `view->obj` 设为对 `exporter` 的新引用，并返回 0。当链式缓冲区提供程序将请求重定向到一个对象时，`view->obj` 可以引用该对象而不是 `exporter` (参见缓冲区对象结构)。

`PyObject_GetBuffer()` 必须与 `PyBuffer_Release()` 同时调用成功，类似于 `malloc()` 和 `free()`。因此，消费者程序用完缓冲区后，`PyBuffer_Release()` 必须保证被调用一次。

`void PyBuffer_Release (Py_buffer *view)`

释放缓冲区 `view` 并递减 `view->obj` 的引用计数。该函数必须在缓冲区不再使用时才能调用，否则可能会发生引用泄漏。

若该函数针对的缓冲区不是通过 `PyObject_GetBuffer()` 获得的，将会出错。

`Py_ssize_t PyBuffer_SizeFromFormat (const char *format)`

返回 `itemsiz` 中隐含的 `format`。如果出错，会触发异常并返回 -1。

3.9 版新加入。

`int PyBuffer_IsContiguous (Py_buffer *view, char order)`

如果 `view` 定义的内存是 C 风格 (`order` 为 'C') 或 Fortran 风格 (`order` 为 'F') `contiguous` 或其中之一 (`order` 是 'A')，则返回 1。否则返回 0。该函数总会成功。

`void *PyBuffer_GetPointer (Py_buffer *view, Py_ssize_t *indices)`

获取给定 `view` 内的 `indices` 所指向的内存区域。`indices` 必须指向一个 `view->ndim` 索引的数组。

`int PyBuffer_FromContiguous (Py_buffer *view, void *buf, Py_ssize_t len, char fort)`

从 `buf` 复制连续的 `len` 字节到 `view`。`fort` 可以是 'C' 或 'F' (对应于 C 风格或 Fortran 风格的顺序)。成功时返回 0, 错误时返回 -1。

`int PyBuffer_ToContiguous (void *buf, Py_buffer *src, Py_ssize_t len, char order)`

从 `src` 复制 `len` 字节到 `buf`, 成为连续字节串的形式。`order` 可以是 'C' 或 'F' 或 'A' (对应于 C 风格、Fortran 风格的顺序或其中任意一种)。成功时返回 0, 出错时返回 -1。

如果 `len != src->len` 则此函数将报错。

`void PyBuffer_FillContiguousStrides (int ndims, Py_ssize_t *shape, Py_ssize_t *strides, int item-size, char order)`

用给定形状的 `contiguous` 字节串数组 (如果 `order` 为 'C' 则为 C 风格, 如果 `order` 为 'F' 则为 Fortran 风格) 来填充 `strides` 数组, 每个元素具有给定的字节数。

`int PyBuffer_FillInfo (Py_buffer *view, PyObject *exporter, void *buf, Py_ssize_t len, int readonly, int flags)`

处理导出程序的缓冲区请求, 该导出程序要公开大小为 `len` 的 `buf`, 并根据 `readonly` 设置可写性。`bug` 被解释为一个无符号字节序列。

参数 `flags` 表示请求的类型。该函数总是按照 `flag` 指定的内容填入 `view`, 除非 `buf` 设为只读, 并且 `flag` 中设置了 `PyBUF_WRITABLE` 标志。

成功时, 将 `view->obj` 设为 `exporter` 的新引用, 并返回 0。否则, 引发 `PyExc_BufferError`, 将 `view->obj` 设为 NULL, 并返回 -1。

如果此函数用作 `getbufferproc` 的一部分, 则 `exporter` 必须设置为导出对象, 并且必须在未修改的情况下传递 `flags`。否则, `exporter` 必须是 NULL。

7.8 舊式緩沖協定 (Buffer Protocol)

3.0 版後已不用。

这些函数是 Python 2 中“旧缓冲协议”API 的组成部分。在 Python 3 中, 此协议已不复存在, 但这些函数仍然被公开以便移植 2.x 的代码。它们被用作新缓冲协议的兼容性包装器, 但它们并不会在缓冲被导出时向你提供对所获资源的生命周期控制。

因此, 推荐你调用 `PyObject_GetBuffer()` (或者配合 `PyArg_ParseTuple()` 函数族使用 `y*` 或 `w*` 格式码) 来获取一个对象的缓冲视图, 并在缓冲视图可被释放时调用 `PyBuffer_Release()`。

`int PyObject_AsCharBuffer (PyObject *obj, const char **buffer, Py_ssize_t *buffer_len)`

Part of the Stable ABI. 返回一个指向可用作基于字符的输入的只读内存地址的指针。`obj` 参数必须支持单段字符缓冲接口。成功时返回 0, 将 `buffer` 设为内存地址并将 `buffer_len` 设为缓冲区长度。出错时返回 -1 并设置一个 `TypeError`。

`int PyObject_AsReadBuffer (PyObject *obj, const void **buffer, Py_ssize_t *buffer_len)`

Part of the Stable ABI. 返回一个指向包含任意数据的只读内存地址的指针。`obj` 参数必须支持单段可读缓冲接口。成功时返回 0, 将 `buffer` 设为内存地址并将 `buffer_len` 设为缓冲区长度。出错时返回 -1 并设置一个 `TypeError`。

`int PyObject_CheckReadBuffer (PyObject *o)`

Part of the Stable ABI. 如果 `o` 支持单段可读缓冲接口则返回 1。否则返回 0。此函数总是会成功执行。

请注意此函数会尝试获取并释放一个缓冲区, 并且在调用对应函数期间发生的异常会被屏蔽。要获取错误报告则应改用 `PyObject_GetBuffer()`。

`int PyObject_AsWriteBuffer (PyObject *obj, void **buffer, Py_ssize_t *buffer_len)`

Part of the Stable ABI. 返回一个指向可写内存地址的指针。`obj` 必须支持单段字符缓冲接口。成功时返回 0, 将 `buffer` 设为内存地址并将 `buffer_len` 设为缓冲区长度。出错时返回 -1 并设置一个 `TypeError`。

具体的对象层

本章中的函数特定于某些 Python 对象类型。将错误类型的对象传递给它们并不是一个好主意；如果您从 Python 程序接收到一个对象，但不确定它是否具有正确的类型，则必须首先执行类型检查；例如，要检查对象是否为字典，请使用 `PyDict_Check()`。本章的结构类似于 Python 对象类型的“家族树”。

警告：虽然本章所描述的函数会仔细检查传入对象的类型，但是其中许多函数不会检查传入的对象是否为 NULL。允许传入 NULL 可能导致内存访问冲突和解释器的立即终止。

8.1 基础物件

本节描述 Python 类型对象和单一实例对象 `None`。

8.1.1 类型对象

type `PyTypeObject`

Part of the Limited API (as an opaque struct). 对象的 C 结构用于描述 built-in 类型。

PyTypeObject `PyType_Type`

Part of the Stable ABI. 这是属于 type 对象的 type object，它在 Python 层面和 `type` 是相同的对象。

`int PyType_Check (PyObject *o)`

如果对象 `o` 是一个类型对象，包括派生自标准类型对象的类型实例则返回非零值。在所有其它情况下都返回 0。此函数将总是成功执行。

`int PyType_CheckExact (PyObject *o)`

如果对象 `o` 是一个类型对象，但不是标准类型对象的子类型则返回非零值。在所有其它情况下都返回 0。此函数将总是成功执行。

`unsigned int PyType_ClearCache ()`

Part of the Stable ABI. 清空内部查找缓存。返回当前版本标签。

`unsigned long PyType_GetFlags (PyTypeObject *type)`

Part of the Stable ABI. Return the `tp_flags` member of `type`. This function is primarily meant for use with `Py_LIMITED_API`; the individual flag bits are guaranteed to be stable across Python releases, but access to `tp_flags` itself is not part of the limited API.

3.2 版新加入。

3.4 版更變: 返回类型现在是 unsigned long 而不是 long。

void **PyType_Modified** (PyTypeObject *type)

Part of the Stable ABI. 使该类型及其所有子类型的内部查找缓存失效。此函数必须在该类型的属性或基类进行任何手动修改之后调用。

int **PyType_HasFeature** (PyTypeObject *o, int feature)

如果类型对象 *o* 设置了特性 *feature* 则返回非零值。类型特性是用单个比特位旗标来表示的。

int **PyType_IS_GC** (PyTypeObject *o)

如果类型对象包括对循环检测器的支持则返回真值; 这会测试类型旗标 `Py_TPFLAGS_HAVE_GC`。

int **PyType_IsSubtype** (PyTypeObject *a, PyTypeObject *b)

Part of the Stable ABI. 如果 *a* 是 *b* 的子类型则返回真值。

此函数只检查实际的子类型, 这意味着 `__subclasscheck__()` 不会在 *b* 上被调用。请调用 `PyObject_IsSubclass()` 来执行与 `issubclass()` 所做的相同检查。

PyObject ***PyType_GenericAlloc** (PyTypeObject *type, Py_ssize_t nitems)

Return value: New reference. Part of the Stable ABI. 类型对象的 `tp_alloc` 槽位的通用处理句柄。请使用 Python 的默认内存分配机制来分配一个新的实例并将其所有内容初始化为 NULL。

PyObject ***PyType_GenericNew** (PyTypeObject *type, PyObject *args, PyObject *kwargs)

Return value: New reference. Part of the Stable ABI. 类型对象的 `tp_new` 槽位的通用处理句柄。请使用类型的 `tp_alloc` 槽位来创建一个新的实例。

int **PyType_Ready** (PyTypeObject *type)

Part of the Stable ABI. 最终化一个类型对象。这应当在所有类型对象上调用以完成它们的初始化。此函数会负责从一个类型的基类添加被继承的槽位。成功时返回 0, 或是在出错时返回 -1 并设置一个异常。

備註: 如果某些基类实现了 GC 协议并且所提供的类型的旗标中未包括 `Py_TPFLAGS_HAVE_GC`, 则将自动从其父类实现 GC 协议。相反地, 如果被创建的类型的旗标中未包括 `Py_TPFLAGS_HAVE_GC` 则它 **必须** 自己通过实现 `tp_traverse` 句柄来实现 GC 协议。

void ***PyType_GetSlot** (PyTypeObject *type, int slot)

Part of the Stable ABI since version 3.4. 返回存储在给定槽位中的函数指针。如果结果为 NULL, 则表示或者该槽位为 NULL, 或者该函数调用传入了无效的形参。调用方通常要将结果指针转换到适当的函数类型。

请参阅 `PyType_Slot.slot` 查看可用的 *slot* 参数值。

3.4 版新加入。

3.10 版更變: `PyType_GetSlot()` 现在可以接受所有类型。在此之前, 它被限制为堆类型。

PyObject ***PyType_GetModule** (PyTypeObject *type)

Part of the Stable ABI since version 3.10. 返回当使用 `PyType_FromModuleAndSpec()` 创建类型时关联到给定类型的模块对象。

如果没有关联到给定类型的模块, 则设置 `TypeError` 并返回 NULL。

此函数通常被用于获取方法定义所在的模块。请注意在这样的方法中, `PyType_GetModule(Py_TYPE(self))` 可能不会返回预期的结果。`Py_TYPE(self)` 可以是目标类的一个子类, 而子类并不一定是在与其上级类相同的模块中定义的。请参阅 `PyCMethod` 了解如何获取方法定义所在的类。

3.9 版新加入。

void ***PyType_GetModuleState** (PyTypeObject *type)

Part of the Stable ABI since version 3.10. 返回关联到给定类型的模块对象的状态。这是一个在 `PyType_GetModule()` 的结果上调用 `PyModule_GetState()` 的快捷方式。

如果没有关联到给定类型的模块, 则设置 `TypeError` 并返回 NULL。

如果 *type* 有关联的模块但其状态为 `NULL`，则返回 `NULL` 且不设置异常。

3.9 版新加入。

创建堆分配类型

下列函数和结构体可被用来创建堆类型。

***PyObject* *PyType_FromModuleAndSpec (*PyObject* *module, *PyType_Spec* *spec, *PyObject* *bases)**
Return value: New reference. Part of the Stable ABI since version 3.10. 根据 *spec* (*Py_TPFLAGS_HEAPTYPE*) 创建并返回一个堆类型。

bases 参数可被用来指定基类；它可以是单个类或由多个类组成的元组。如果 *bases* 为 `NULL`，则会改用 *Py_tp_bases* 槽位。如果该槽位也为 `NULL`，则会改用 *Py_tp_base* 槽位。如果该槽位同样为 `NULL`，则新类型将派生自 `object`。

module 参数可被用来记录新类定义所在的模块。它必须是一个模块对象或为 `NULL`。如果不为 `NULL`，则该模块会被关联到新类型并且可在之后通过 *PyType_GetModule()* 来获取。这个关联模块不可被子类继承；它必须为每个类单独指定。

此函数会在新类型上调用 *PyType_Ready()*。

3.9 版新加入。

3.10 版更變：此函数现在接受一个单独类作为 *bases* 参数并接受 `NULL` 作为 *tp_doc* 槽位。

***PyObject* *PyType_FromSpecWithBases (*PyType_Spec* *spec, *PyObject* *bases)**
Return value: New reference. Part of the Stable ABI since version 3.3. 等價於 *PyType_FromModuleAndSpec(NULL, spec, bases)*。

3.3 版新加入。

***PyObject* *PyType_FromSpec (*PyType_Spec* *spec)**
Return value: New reference. Part of the Stable ABI. 等價於 *PyType_FromSpecWithBases(spec, NULL)*。

type *PyType_Spec*

Part of the Stable ABI (including all members). 定义一个类型的行为的结构体。

const char *PyType_Spec.name
 类型的名称，用来设置 *PyTypeObject.tp_name*。

int PyType_Spec.basicsize

int PyType_Spec.itemsize
 以字节数表示的实例大小，用来设置 *PyTypeObject.tp_basicsize* 和 *PyTypeObject.tp_itemsize*。

int PyType_Spec.flags
 类型旗标，用来设置 *PyTypeObject.tp_flags*。

如果未设置 *Py_TPFLAGS_HEAPTYPE* 旗标，则 *PyType_FromSpecWithBases()* 会自动设置它。

***PyType_Slot* *PyType_Spec.slots**
PyType_Slot 结构体的数组。以特殊槽位值 {0, `NULL`} 来结束。

type *PyType_Slot*

Part of the Stable ABI (including all members). 定义一个类型的可选功能的结构体，包含一个槽位 ID 和一个值指针。

int PyType_Slot.slot

槽位 ID。

槽位 ID 的类名像是结构体 *PyTypeObject*, *PyNumberMethods*, *PySequenceMethods*, *PyMappingMethods* 和 *PyAsyncMethods* 的字段名附加一个 *Py_* 前缀。举例来说，使用：

- `Py_tp_dealloc` 设置 `PyTypeObject.tp_dealloc`
- `Py_nb_add` 设置 `PyNumberMethods.nb_add`
- `Py_sq_length` 设置 `PySequenceMethods.sq_length`

下列字段完全无法使得 `PyType_Spec` 和 `PyType_Slot` 来设置:

- `tp_dict`
- `tp_mro`
- `tp_cache`
- `tp_subclasses`
- `tp_weaklist`
- `tp_vectorcall`
- `tp_weaklistoffset` (参见 `PyMemberDef`)
- `tp_dictoffset` (参见 `PyMemberDef`)
- `tp_vectorcall_offset` (参见 `PyMemberDef`)

下列字段在受限 API 下无法使用 `PyType_Spec` 和 `PyType_Slot` 来设置:

- `bf_getbuffer`
- `bf_releasebuffer`

设置 `Py_tp_bases` 或 `Py_tp_base` 在某些平台上可能会有问题。为了避免问题, 请改用 `PyType_FromSpecWithBases()` 的 `bases` 参数。

3.9 版更變: `PyBufferProcs` 中的槽位可能会在不受限 API 中被设置。

`void *PyType_Slot.pfunc`

该槽位的预期值。在大多数情况下, 这将是一个指向函数的指针。

`Py_tp_doc` 以外的槽位均不可为 `NULL`。

8.1.2 None 物件

请注意, `None` 的 `PyTypeObject` 不会直接在 Python / C API 中公开。由于 `None` 是单例, 测试对象标识 (在 C 中使用 `==`) 就足够了。由于同样的原因, 没有 `PyNone_Check()` 函数。

PyObject ***Py_None**

Python `None` 对象, 表示缺乏值。这个对象没有方法。它需要像引用计数一样处理任何其他对象。

Py_RETURN_NONE

正确处理来自 C 函数内的 `Py_None` 返回 (也就是说, 增加 `None` 的引用计数并返回它。)

8.2 数值物件

8.2.1 整數物件

所有整数都实现为长度任意的长整数对象。

在出错时, 大多数 `PyLong_As*` API 都会返回 `(return type)-1`, 这与数字无法区分开。请采用 `PyErr_Occurred()` 来加以区分。

type `PyLongObject`

Part of the *Limited API* (as an opaque struct). 表示 Python 整数对象的 *PyObject* 子类型。

PyTypeObject PyLong_Type

Part of the Stable ABI. 这个 *PyTypeObject* 的实例表示 Python 的整数类型。与 Python 语言中的 `int` 相同。

int PyLong_Check (PyObject *p)

如果参数是 *PyLongObject* 或 *PyLongObject* 的子类型，则返回 `True`。该函数一定能够执行成功。

int PyLong_CheckExact (PyObject *p)

如果其参数属于 *PyLongObject*，但不是 *PyLongObject* 的子类型则返回真值。此函数总是会成功执行。

PyObject *PyLong_FromLong (long v)

Return value: New reference. Part of the Stable ABI. 由 `v` 返回一个新的 *PyLongObject* 对象，失败时返回 `NULL`。

当前的实现维护着一个整数对象数组，包含 -5 和 256 之间的所有整数对象。若创建一个位于该区间的 `int` 时，实际得到的将是对已有对象的引用。

PyObject *PyLong_FromUnsignedLong (unsigned long v)

Return value: New reference. Part of the Stable ABI. Return a new *PyLongObject* object from a C unsigned long, or `NULL` on failure.

PyObject *PyLong_FromSsize_t (Py_ssize_t v)

Return value: New reference. Part of the Stable ABI. 由 C `Py_ssize_t` 返回一个新的 *PyLongObject* 对象，失败时返回 `NULL`。

PyObject *PyLong_FromSize_t (size_t v)

Return value: New reference. Part of the Stable ABI. 由 C `size_t` 返回一个新的 *PyLongObject* 对象，失败则返回 `NULL`。

PyObject *PyLong_FromLongLong (long long v)

Return value: New reference. Part of the Stable ABI. Return a new *PyLongObject* object from a C long long, or `NULL` on failure.

PyObject *PyLong_FromUnsignedLongLong (unsigned long long v)

Return value: New reference. Part of the Stable ABI. Return a new *PyLongObject* object from a C unsigned long long, or `NULL` on failure.

PyObject *PyLong_FromDouble (double v)

Return value: New reference. Part of the Stable ABI. 由 `v` 的整数部分返回一个新的 *PyLongObject* 对象，失败则返回 `NULL`。

PyObject *PyLong_FromString (const char *str, char **pend, int base)

Return value: New reference. Part of the Stable ABI. 根据 `str` 字符串值返回一个新的 *PyLongObject*，`base` 指定了整数的基。如果 `pend` 不为 `NULL`，则 `*pend` 将指向 `str` 中表示数字部分后面的第一个字符。如果 `base` 为 0，`str` 将采用 `integers` 的定义进行解释；这时非零十进制数的前导零会触发 `ValueError`。如果 `base` 不为 0，则须位于 2 和 36 之间（含 2 和 36）。基之后及数字之间的前导空格、单下划线将被忽略。如果不存在数字，将触发 `ValueError`。

也参考：

Python methods `int.to_bytes()` and `int.from_bytes()` to convert a *PyLongObject* to/from an array of bytes in base 256. You can call those from C using `PyObject_CallMethod()`.

PyObject *PyLong_FromUnicodeObject (PyObject *u, int base)

Return value: New reference. 将字符串 `u` 中的 Unicode 数字序列转换为 Python 整数值。

3.3 版新加入。

PyObject *PyLong_FromVoidPtr (void *p)

Return value: New reference. Part of the Stable ABI. 从指针 `p` 创建一个 Python 整数。可以使用 `PyLong_AsVoidPtr()` 返回的指针值。

long PyLong_AsLong (PyObject *obj)

Part of the Stable ABI. Return a C long representation of `obj`. If `obj` is not an instance of *PyLongObject*, first call its `__index__()` method (if present) to convert it to a *PyLongObject*.

Raise `OverflowError` if the value of *obj* is out of range for a long.

出错则返回 -1。请用 `PyErr_Occurred()` 找出具体问题。

3.8 版更變: 如果可用将使用 `__index__()`。

3.10 版更變: 本函数不再使用 `__int__()`。

long **PyLong_AsLongAndOverflow** (*PyObject* **obj*, int **overflow*)

Part of the Stable ABI. Return a C long representation of *obj*. If *obj* is not an instance of `PyLongObject`, first call its `__index__()` method (if present) to convert it to a `PyLongObject`.

如果 *obj* 的值大于 `LONG_MAX` 或小于 `LONG_MIN`, 则会把 **overflow* 分别置为 “1” 或 -1, 并返回 1; 否则, 将 **overflow* 置为 0。如果发生其他异常, 则会按常规把 **overflow* 置为 0, 并返回 -1。

出错则返回 -1。请用 `PyErr_Occurred()` 找出具体问题。

3.8 版更變: 如果可用将使用 `__index__()`。

3.10 版更變: 本函数不再使用 `__int__()`。

long long **PyLong_AsLongLong** (*PyObject* **obj*)

Part of the Stable ABI. Return a C long long representation of *obj*. If *obj* is not an instance of `PyLongObject`, first call its `__index__()` method (if present) to convert it to a `PyLongObject`.

Raise `OverflowError` if the value of *obj* is out of range for a long long.

出错则返回 -1。请用 `PyErr_Occurred()` 找出具体问题。

3.8 版更變: 如果可用将使用 `__index__()`。

3.10 版更變: 本函数不再使用 `__int__()`。

long long **PyLong_AsLongLongAndOverflow** (*PyObject* **obj*, int **overflow*)

Part of the Stable ABI. Return a C long long representation of *obj*. If *obj* is not an instance of `PyLongObject`, first call its `__index__()` method (if present) to convert it to a `PyLongObject`.

如果 *obj* 的值大于 `LLONG_MAX` 或小于 `LLONG_MIN`, 则按常规将 **overflow* 分别置为 1 或 -1, 并返回 -1, 否则将 **overflow* 置为 0。如果触发其他异常则 **overflow* 置为 0 并返回 -1。

出错则返回 -1。请用 `PyErr_Occurred()` 找出具体问题。

3.2 版新加入。

3.8 版更變: 如果可用将使用 `__index__()`。

3.10 版更變: 本函数不再使用 `__int__()`。

Py_ssize_t **PyLong_AsSsize_t** (*PyObject* **pylong*)

Part of the Stable ABI. 返回 *pylong* 的 C 语言 `Py_ssize_t` 形式。 *pylong* 必须是 `PyLongObject` 的实例。

如果 *pylong* 的值超出了 `Py_ssize_t` 的取值范围则会引发 `OverflowError`。

出错则返回 -1。请用 `PyErr_Occurred()` 找出具体问题。

unsigned long **PyLong_AsUnsignedLong** (*PyObject* **pylong*)

Part of the Stable ABI. Return a C unsigned long representation of *pylong*. *pylong* must be an instance of `PyLongObject`.

Raise `OverflowError` if the value of *pylong* is out of range for a unsigned long.

出错时返回 (unsigned long)-1, 请利用 `PyErr_Occurred()` 辨别具体问题。

size_t **PyLong_AsSize_t** (*PyObject* **pylong*)

Part of the Stable ABI. 返回 *pylong* 的 C 语言 `size_t` 形式。 *pylong* 必须是 `PyLongObject` 的实例。

如果 *pylong* 的值超出了 `size_t` 的取值范围则会引发 `OverflowError`。

出错时返回 (size_t)-1, 请利用 `PyErr_Occurred()` 辨别具体问题。

unsigned long long **PyLong_AsUnsignedLongLong** (*PyObject* *pylong)

Part of the Stable ABI. Return a C unsigned long long representation of *pylong*. *pylong* must be an instance of *PyLongObject*.

Raise `OverflowError` if the value of *pylong* is out of range for an unsigned long long.

出错时返回 (unsigned long long)-1, 请利用 *PyErr_Occurred()* 辨别具体问题。

3.1 版更變: 现在 *pylong* 为负值会触发 `OverflowError`, 而不是 `TypeError`。

unsigned long **PyLong_AsUnsignedLongMask** (*PyObject* *obj)

Part of the Stable ABI. Return a C unsigned long representation of *obj*. If *obj* is not an instance of *PyLongObject*, first call its `__index__()` method (if present) to convert it to a *PyLongObject*.

If the value of *obj* is out of range for an unsigned long, return the reduction of that value modulo `ULONG_MAX + 1`.

出错时返回 (unsigned long)-1, 请利用 *PyErr_Occurred()* 辨别具体问题。

3.8 版更變: 如果可用将使用 `__index__()`。

3.10 版更變: 本函数不再使用 `__int__()`。

unsigned long long **PyLong_AsUnsignedLongLongMask** (*PyObject* *obj)

Part of the Stable ABI. Return a C unsigned long long representation of *obj*. If *obj* is not an instance of *PyLongObject*, first call its `__index__()` method (if present) to convert it to a *PyLongObject*.

If the value of *obj* is out of range for an unsigned long long, return the reduction of that value modulo `ULLONG_MAX + 1`.

出错时返回 (unsigned long long)-1, 请利用 *PyErr_Occurred()* 辨别具体问题。

3.8 版更變: 如果可用将使用 `__index__()`。

3.10 版更變: 本函数不再使用 `__int__()`。

double **PyLong_AsDouble** (*PyObject* *pylong)

Part of the Stable ABI. Return a C double representation of *pylong*. *pylong* must be an instance of *PyLongObject*.

Raise `OverflowError` if the value of *pylong* is out of range for a double.

出错时返回 -1.0, 请利用 *PyErr_Occurred()* 辨别具体问题。

void ***PyLong_AsVoidPtr** (*PyObject* *pylong)

Part of the Stable ABI. Convert a Python integer *pylong* to a C void pointer. If *pylong* cannot be converted, an `OverflowError` will be raised. This is only assured to produce a usable void pointer for values created with *PyLong_FromVoidPtr()*.

出错时返回 NULL, 请利用 *PyErr_Occurred()* 辨别具体问题。

8.2.2 Boolean (布林) 物件

Python 中的 boolean 是以整數子類化來實現的。只有 `Py_False` 和 `Py_True` 兩個 boolean。因此一般的建立和除函式不適用於 boolean。但下列巨集 (macro) 是可用的。

int **PyBool_Check** (*PyObject* *o)

如果 *o* 的型 `PyBool_Type` 則回傳真值。此函式總是會成功執行。

PyObject ***Py_False**

Python 的 False 物件。此物件有任何方法。在參照 (reference) 計數上必須有著和其他物件一樣的處理方式。

PyObject ***Py_True**

Python 的 True 物件。此物件有任何方法。在參照計數上必須有著和其他物件一樣的處理方式。

Py_RETURN_FALSE

從函式回傳 `Py_False`, 適當的增加它的參照計數。

Py_RETURN_TRUE

從函式回傳 `Py_True`, 適當的增加它的參照計數。

PyObject*PyBool_FromLong (long *v*)

Return value: New reference. Part of the [Stable ABI](#). 根據 *v* 的實際值來回傳一個 `Py_True` 或者 `Py_False` 的新參照。

8.2.3 浮點數 (Floating Point) 物件

type PyFloatObject

這個 C 類型 `PyObject` 的子類型代表一個 Python 浮點數對象。

PyTypeObject PyFloat_Type

Part of the [Stable ABI](#). 這是屬於 C 類型 `PyTypeObject` 的代表 Python 浮點類型的實例。在 Python 層面的類型 `float` 是同一個對象。

int PyFloat_Check (PyObject **p*)

如果它的參數是一個 `PyFloatObject` 或者 `PyFloatObject` 的子類型則返回真值。此函數總是會成功執行。

int PyFloat_CheckExact (PyObject **p*)

如果它的參數是一個 `PyFloatObject` 但不是 `PyFloatObject` 的子類型則返回真值。此函數總是會成功執行。

PyObject*PyFloat_FromString (PyObject **str*)

Return value: New reference. Part of the [Stable ABI](#). 根據字符串 *str* 的值創建一個 `PyFloatObject`, 失敗時返回 `NULL`。

PyObject*PyFloat_FromDouble (double *v*)

Return value: New reference. Part of the [Stable ABI](#). 根據 *v* 創建一個 `PyFloatObject` 對象, 失敗時返回 `NULL`。

double PyFloat_AsDouble (PyObject **pyfloat*)

Part of the [Stable ABI](#). Return a C double representation of the contents of *pyfloat*. If *pyfloat* is not a Python floating point object but has a `__float__()` method, this method will first be called to convert *pyfloat* into a float. If `__float__()` is not defined then it falls back to `__index__()`. This method returns `-1.0` upon failure, so one should call `PyErr_Occurred()` to check for errors.

3.8 版更變: 如果可用將使用 `__index__()`。

double PyFloat_AS_DOUBLE (PyObject **pyfloat*)

Return a C double representation of the contents of *pyfloat*, but without error checking.

PyObject*PyFloat_GetInfo (void)

Return value: New reference. Part of the [Stable ABI](#). 返回一個 `structseq` 實例, 其中包含有關 `float` 的精度、最小值和最大值的資訊。它是頭文件 `float.h` 的一個簡單包裝。

double PyFloat_GetMax ()

Part of the [Stable ABI](#). Return the maximum representable finite float `DBL_MAX` as C double.

double PyFloat_GetMin ()

Part of the [Stable ABI](#). Return the minimum normalized positive float `DBL_MIN` as C double.

8.2.4 复数对象

从 C API 看, Python 的复数对象由两个不同的部分实现: 一个是在 Python 程序使用的 Python 对象, 另外的是一个代表真正复数值的 C 结构体。API 提供了函数共同操作两者。

表示复数的 C 结构体

需要注意的是接受这些结构体的作为参数并当做结果返回的函数, 都是传递“值”而不是引用指针。此规则适用于整个 API。

type `Py_complex`

这是一个对应 Python 复数对象的值部分的 C 结构体。绝大部分处理复数对象的函数都用这类型的结构体作为输入或者输出值, 它可近似地定义为:

```
typedef struct {
    double real;
    double imag;
} Py_complex;
```

`Py_complex_Py_c_sum` (`Py_complex left`, `Py_complex right`)

返回两个复数的和, 用 C 类型 `Py_complex` 表示。

`Py_complex_Py_c_diff` (`Py_complex left`, `Py_complex right`)

返回两个复数的差, 用 C 类型 `Py_complex` 表示。

`Py_complex_Py_c_neg` (`Py_complex num`)

返回复数 `num` 的负值, 用 C `Py_complex` 表示。

`Py_complex_Py_c_prod` (`Py_complex left`, `Py_complex right`)

返回两个复数的乘积, 用 C 类型 `Py_complex` 表示。

`Py_complex_Py_c_quot` (`Py_complex dividend`, `Py_complex divisor`)

返回两个复数的商, 用 C 类型 `Py_complex` 表示。

如果 `divisor` 为空, 这个方法返回零并设置 `errno` 为 `EDOM`。

`Py_complex_Py_c_pow` (`Py_complex num`, `Py_complex exp`)

返回 `num` 的 `exp` 次幂, 用 C 类型 `Py_complex` 表示。

如果 `num` 为空且 `exp` 不是正实数, 这个方法返回零并设置 `errno` 为 `EDOM`。

表示复数的 Python 对象

type `PyComplexObject`

这个 C 类型 `PyObject` 的子类型代表一个 Python 复数对象。

`PyTypeObject` `PyComplex_Type`

Part of the Stable ABI. 这是个属于 `PyTypeObject` 的代表 Python 复数类型的实例。在 Python 层面的类型 `complex` 是同一个对象。

int `PyComplex_Check` (`PyObject *p`)

如果它的参数是一个 `PyComplexObject` 或者 `PyComplexObject` 的子类型则返回真值。此函数总是会成功执行。

int `PyComplex_CheckExact` (`PyObject *p`)

如果它的参数是一个 `PyComplexObject` 但不是 `PyComplexObject` 的子类型则返回真值。此函数总是会成功执行。

`PyObject *``PyComplex_FromCComplex` (`Py_complex v`)

Return value: New reference. 根据 C 类型 `Py_complex` 的值生成一个新的 Python 复数对象。

`PyObject *``PyComplex_FromDoubles` (double `real`, double `imag`)

Return value: New reference. Part of the Stable ABI. 根据 `real` 和 `imag` 返回一个新的 C 类型 `PyComplexObject` 对象。

double **PyComplex_RealAsDouble** (*PyObject* **op*)

Part of the Stable ABI. Return the real part of *op* as a C double.

double **PyComplex_ImagAsDouble** (*PyObject* **op*)

Part of the Stable ABI. Return the imaginary part of *op* as a C double.

Py_complex **PyComplex_AsCComplex** (*PyObject* **op*)

返回复数 *op* 的 C 类型 *Py_complex* 值。

如果 *op* 不是一个 Python 复数对象，但是具有 `__complex__()` 方法，此方法将首先被调用，将 *op* 转换为一个 Python 复数对象。如果 `__complex__()` 未定义则将回退至 `__float__()`，如果 `__float__()` 未定义则将回退至 `__index__()`。如果失败，此方法将返回 `-1.0` 作为实数值。

3.8 版更變: 如果可用将使用 `__index__()`。

8.3 序列物件

序列对象的一般操作在前一章中讨论过; 本节介绍 Python 语言固有的特定类型的序列对象。

8.3.1 bytes 对象

这些函数在期望附带一个字节串形参但却附带了一个非字节串形参被调用时会引发 `TypeError`。

type **PyBytesObject**

这种 *PyObject* 的子类型表示一个 Python 字节对象。

PyTypeObject **PyBytes_Type**

Part of the Stable ABI. *PyTypeObject* 的实例代表一个 Python 字节类型，在 Python 层面它与 `bytes` 是相同的对象。

int **PyBytes_Check** (*PyObject* **o*)

如果对象 *o* 是一个 `bytes` 对象或者 `bytes` 类型的子类型的实例则返回真值。此函数总是会成功执行。

int **PyBytes_CheckExact** (*PyObject* **o*)

如果对象 *o* 是一个 `bytes` 对象但不是 `bytes` 类型的子类型的实例则返回真值。此函数总是会成功执行。

PyObject ***PyBytes_FromString** (const char **v*)

Return value: New reference. *Part of the Stable ABI.* 成功时返回一个以字符串 *v* 的副本为值的新字节串对象，失败时返回 `NULL`。形参 *v* 不可为 `NULL`；它不会被检查。

PyObject ***PyBytes_FromStringAndSize** (const char **v*, *Py_ssize_t* *len*)

Return value: New reference. *Part of the Stable ABI.* 成功时返回一个以字符串 *v* 的副本为值且长度为 *len* 的新字节串对象，失败时返回 `NULL`。如果 *v* 为 `NULL`，则不初始化字节串对象的内容。

PyObject ***PyBytes_FromFormat** (const char **format*, ...)

Return value: New reference. *Part of the Stable ABI.* 接受一个 `C printf()` 风格的 *format* 字符串和可变数量的参数，计算结果 Python 字节串对象的大小并返回参数值经格式化后的字节串对象。可变数量的参数必须均为 C 类型并且必须恰好与 *format* 字符串中的格式字符相对应。允许使用下列格式字符串：

格式字符	类型	注释
%%	<i>n/a</i>	文字% 字符。
%c	int	一个字节, 被表示为一个 C 语言的整型
%d	int	等價於 <code>printf("%d").</code> ¹
%u	unsigned int	等價於 <code>printf("%u").</code> ¹
%ld	long	等價於 <code>printf("%ld").</code> ¹
%lu	unsigned long	等價於 <code>printf("%lu").</code> ¹
%zd	<code>Py_ssize_t</code>	等價於 <code>printf("%zd").</code> ¹
%zu	<code>size_t</code>	等價於 <code>printf("%zu").</code> ¹
%i	int	等價於 <code>printf("%i").</code> ¹
%x	int	等價於 <code>printf("%x").</code> ¹
%s	const char*	以 null 为终止符的 C 字符串数组。
%p	const void*	一个 C 指针的十六进制表示形式。基本等价于 <code>printf("%p")</code> 但它会确保以面值 0x 开头, 不论系统平台上 <code>printf</code> 的输出是什么。

无法识别的格式字符会导致将格式字符串的其余所有内容原样复制到结果对象, 并丢弃所有多余的参数。

PyObject* PyBytes_FromFormatV (const char *format, va_list vargs)

Return value: New reference. Part of the [Stable ABI](#). 与 `PyBytes_FromFormat()` 完全相同, 除了它需要两个参数。

PyObject* PyBytes_FromObject (PyObject *o)

Return value: New reference. Part of the [Stable ABI](#). 返回字节表示实现缓冲区协议的对象 *o*。

Py_ssize_t PyBytes_Size (PyObject *o)

Part of the [Stable ABI](#). 返回字节对象 *o* 中字节的长度。

Py_ssize_t PyBytes_GET_SIZE (PyObject *o)

宏版本的 `PyBytes_Size()` 但是不带错误检测。

char* PyBytes_AsString (PyObject *o)

Part of the [Stable ABI](#). 返回对应 *o* 的内容的指针。该指针指向 *o* 的内部缓冲区, 其中包含 `len(o) + 1` 个字节。缓冲区的最后一个字节总是为空, 不论是否存在其他空字节。该数据不可通过任何形式来修改, 除非是刚使用 `PyBytes_FromStringAndSize(NULL, size)` 创建该对象。它不可被撤销分配。如果 *o* 根本不是一个字节串对象, 则 `PyBytes_AsString()` 将返回 NULL 并引发 `TypeError`。

char* PyBytes_AS_STRING (PyObject *string)

宏版本的 `PyBytes_AsString()` 但是不带错误检测。

int PyBytes_AsStringAndSize (PyObject *obj, char **buffer, Py_ssize_t *length)

Part of the [Stable ABI](#). 通过输出变量 *buffer* 和 *length* 返回以 null 为终止符的对象 *obj* 的内容。

如果 *length* 为 NULL, 字节串对象就不包含嵌入的空字节; 如果包含, 则该函数将返回 -1 并引发 `ValueError`。

该缓冲区指向 *obj* 的内部缓冲, 它的末尾包含一个额外的空字节 (不算在 *length* 当中)。该数据不可通过任何方式来修改, 除非是刚使用 `PyBytes_FromStringAndSize(NULL, size)` 创建该对象。它不可被撤销分配。如果 *obj* 根本不是一个字节串对象, 则 `PyBytes_AsStringAndSize()` 将返回 -1 并引发 `TypeError`。

3.5 版更變: 以前, 当字节串对象中出现嵌入的空字节时将引发 `TypeError`。

void PyBytes_Concat (PyObject **bytes, PyObject *newpart)

Part of the [Stable ABI](#). 在 **bytes* 中创建新的字节串对象, 其中包含添加到 *bytes* 的 *newpart* 的内容; 调用者将获得新的引用。对 *bytes* 原值的引用将被收回。如果无法创建新对象, 对 *bytes* 的旧引用仍将被丢弃且 **bytes* 的值将被设为 NULL; 并将设置适当的异常。

¹ 对于整数说明符 (d, u, ld, lu, zd, zu, i, x): 当给出精度时, 0 转换标志是有效的。

void **PyBytes_ConcatAndDel** (*PyObject* ***bytes*, *PyObject* **newpart*)

Part of the Stable ABI. 在 **bytes* 中创建新的字节串对象，其中包含添加到 *bytes* 的 *newpart* 的内容。此版本会减少 *newpart* 的引用计数。

int **_PyBytes_Resize** (*PyObject* ***bytes*, *Py_ssize_t* *newsize*)

改变字节串大小的一种方式，即使其为“不可变对象”。此方式仅用于创建全新的字节串对象；如果字节串在代码的其他部分已知则不可使用此方式。如果输入字节串对象的引用计数不为1则调用此函数将报错。传入一个现有字节串对象的地址作为 *lvalue*（它可能会被写入），并传入希望的新大小。当成功时，**bytes* 将存放改变大小后的字节串对象并返回 0；**bytes* 中的地址可能与其输入值不同。如果重新分配失败，则 **bytes* 上的原字节串对象将被撤销分配，**bytes* 会被设为 NULL，同时设置 `MemoryError` 并返回 -1。

8.3.2 字节数组对象

type **PyByteArrayObject**

这个 *PyObject* 的子类型表示一个 Python 字节数组对象。

PyTypeObject **PyByteArray_Type**

Part of the Stable ABI. Python bytearray 类型表示为 *PyTypeObject* 的实例；这与 Python 层面的 bytearray 是相同的对象。

类型检查宏

int **PyByteArray_Check** (*PyObject* **o*)

如果对象 *o* 是一个 bytearray 对象或者 bytearray 类型的子类型的实例则返回真值。此函数总是会成功执行。

int **PyByteArray_CheckExact** (*PyObject* **o*)

如果对象 *o* 是一个 bytearray 对象但不是 bytearray 类型的子类型的实例则返回真值。此函数总是会成功执行。

直接 API 函数

PyObject ***PyByteArray_FromObject** (*PyObject* **o*)

Return value: New reference. *Part of the Stable ABI.* 根据任何实现了缓冲区协议的对象 *o*，返回一个新的字节数组对象。

PyObject ***PyByteArray_FromStringAndSize** (const char **string*, *Py_ssize_t* *len*)

Return value: New reference. *Part of the Stable ABI.* 根据 *string* 及其长度 *len* 创建一个新的 bytearray 对象。当失败时返回 NULL。

PyObject ***PyByteArray_Concat** (*PyObject* **a*, *PyObject* **b*)

Return value: New reference. *Part of the Stable ABI.* 连接字节数组 *a* 和 *b* 并返回一个带有结果的新的字节数组。

Py_ssize_t **PyByteArray_Size** (*PyObject* **bytearray*)

Part of the Stable ABI. 在检查 NULL 指针后返回 bytearray 的大小。

char ***PyByteArray_AsString** (*PyObject* **bytearray*)

Part of the Stable ABI. 在检查 NULL 指针后返回将 bytearray 返回为一个字符数组。返回的数组总是会附加一个额外的空字节。

int **PyByteArray_Resize** (*PyObject* **bytearray*, *Py_ssize_t* *len*)

Part of the Stable ABI. 将 bytearray 的内部缓冲区的大小调整为 *len*。

宏

这些宏减低安全性以换取性能，它们不检查指针。

`char *PyByteArray_AS_STRING (PyObject *bytearray)`
C 函数 `PyByteArray_AsString()` 的宏版本。

`Py_ssize_t PyByteArray_GET_SIZE (PyObject *bytearray)`
C 函数 `PyByteArray_Size()` 的宏版本。

8.3.3 Unicode 物件與編碼

Unicode 对象

自从 python3.3 中实现了 **PEP 393** 以来，Unicode 对象在内部使用各种表示形式，以便在保持内存效率的同时处理完整范围的 Unicode 字符。对于所有代码点都低于 128、256 或 65536 的字符串，有一些特殊情况；否则，代码点必须低于 1114112（这是完整的 Unicode 范围）。

`Py_UNICODE*` and UTF-8 representations are created on demand and cached in the Unicode object. The `Py_UNICODE*` representation is deprecated and inefficient.

Due to the transition between the old APIs and the new APIs, Unicode objects can internally be in two states depending on how they were created:

- "canonical" Unicode objects are all objects created by a non-deprecated Unicode API. They use the most efficient representation allowed by the implementation.
- "legacy" Unicode objects have been created through one of the deprecated APIs (typically `PyUnicode_FromUnicode()`) and only bear the `Py_UNICODE*` representation; you will have to call `PyUnicode_READY()` on them before calling any other API.

備註：The "legacy" Unicode object will be removed in Python 3.12 with deprecated APIs. All Unicode objects will be "canonical" since then. See **PEP 623** for more information.

Unicode 类型

These are the basic Unicode object types used for the Unicode implementation in Python:

type `Py_UCS4`

type `Py_UCS2`

type `Py_UCS1`

Part of the Stable ABI. These types are typedefs for unsigned integer types wide enough to contain characters of 32 bits, 16 bits and 8 bits, respectively. When dealing with single Unicode characters, use `Py_UCS4`.

3.3 版新加入。

type `Py_UNICODE`

This is a typedef of `wchar_t`, which is a 16-bit type or 32-bit type depending on the platform.

3.3 版更變: In previous versions, this was a 16-bit type or a 32-bit type depending on whether you selected a "narrow" or "wide" Unicode version of Python at build time.

type `PyASCIIObject`

type `PyCompactUnicodeObject`

type `PyUnicodeObject`

These subtypes of `PyObject` represent a Python Unicode object. In almost all cases, they shouldn't be used directly, since all API functions that deal with Unicode objects take and return `PyObject` pointers.

3.3 版新加入。

PyTypeObject PyUnicode_Type

Part of the *Stable ABI*. This instance of *PyTypeObject* represents the Python Unicode type. It is exposed to Python code as `str`.

The following APIs are really C macros and can be used to do fast checks and to access internal read-only data of Unicode objects:

int PyUnicode_Check (*PyObject* **o*)

Return true if the object *o* is a Unicode object or an instance of a Unicode subtype. This function always succeeds.

int PyUnicode_CheckExact (*PyObject* **o*)

Return true if the object *o* is a Unicode object, but not an instance of a subtype. This function always succeeds.

int PyUnicode_READY (*PyObject* **o*)

Ensure the string object *o* is in the "canonical" representation. This is required before using any of the access macros described below.

Returns 0 on success and -1 with an exception set on failure, which in particular happens if memory allocation fails.

3.3 版新加入。

自從版本 3.10 後不推薦使用，將會自版本 3.12 中移除。: This API will be removed with *PyUnicode_FromUnicode()*.

Py_ssize_t PyUnicode_GET_LENGTH (*PyObject* **o*)

Return the length of the Unicode string, in code points. *o* has to be a Unicode object in the "canonical" representation (not checked).

3.3 版新加入。

Py_UCS1 *PyUnicode_1BYTE_DATA (*PyObject* **o*)

Py_UCS2 *PyUnicode_2BYTE_DATA (*PyObject* **o*)

Py_UCS4 *PyUnicode_4BYTE_DATA (*PyObject* **o*)

Return a pointer to the canonical representation cast to UCS1, UCS2 or UCS4 integer types for direct character access. No checks are performed if the canonical representation has the correct character size; use *PyUnicode_KIND()* to select the right macro. Make sure *PyUnicode_READY()* has been called before accessing this.

3.3 版新加入。

PyUnicode_WCHAR_KIND

PyUnicode_1BYTE_KIND

PyUnicode_2BYTE_KIND

PyUnicode_4BYTE_KIND

返回 *PyUnicode_KIND()* 宏的值。

3.3 版新加入。

自從版本 3.10 後不推薦使用，將會自版本 3.12 中移除。: *PyUnicode_WCHAR_KIND* 已用。

unsigned int PyUnicode_KIND (*PyObject* **o*)

Return one of the PyUnicode kind constants (see above) that indicate how many bytes per character this Unicode object uses to store its data. *o* has to be a Unicode object in the "canonical" representation (not checked).

3.3 版新加入。

void *PyUnicode_DATA (*PyObject* **o*)

Return a void pointer to the raw Unicode buffer. *o* has to be a Unicode object in the "canonical" representation (not checked).

3.3 版新加入。

void PyUnicode_WRITE (int *kind*, void **data*, *Py_ssize_t* *index*, *Py_UCS4* *value*)

Write into a canonical representation *data* (as obtained with *PyUnicode_DATA()*). This macro does not

do any sanity checks and is intended for usage in loops. The caller should cache the *kind* value and *data* pointer as obtained from other macro calls. *index* is the index in the string (starts at 0) and *value* is the new code point value which should be written to that location.

3.3 版新加入.

Py_UCS4 **PyUnicode_READ** (int *kind*, void **data*, *Py_ssize_t* *index*)

Read a code point from a canonical representation *data* (as obtained with *PyUnicode_DATA*()). No checks or ready calls are performed.

3.3 版新加入.

Py_UCS4 **PyUnicode_READ_CHAR** (*PyObject* **o*, *Py_ssize_t* *index*)

Read a character from a Unicode object *o*, which must be in the "canonical" representation. This is less efficient than *PyUnicode_READ*() if you do multiple consecutive reads.

3.3 版新加入.

PyUnicode_MAX_CHAR_VALUE (*o*)

Return the maximum code point that is suitable for creating another string based on *o*, which must be in the "canonical" representation. This is always an approximation but more efficient than iterating over the string.

3.3 版新加入.

Py_ssize_t **PyUnicode_GET_SIZE** (*PyObject* **o*)

Return the size of the deprecated *Py_UNICODE* representation, in code units (this includes surrogate pairs as 2 units). *o* has to be a Unicode object (not checked).

自從版本 3.3 後不推薦使用，將會自版本 3.12 中移除。：旧式 Unicode API 的一部分，请迁移到使用 *PyUnicode_GET_LENGTH*()。

Py_ssize_t **PyUnicode_GET_DATA_SIZE** (*PyObject* **o*)

Return the size of the deprecated *Py_UNICODE* representation in bytes. *o* has to be a Unicode object (not checked).

自從版本 3.3 後不推薦使用，將會自版本 3.12 中移除。：旧式 Unicode API 的一部分，请迁移到使用 *PyUnicode_GET_LENGTH*()。

Py_UNICODE ***PyUnicode_AS_UNICODE** (*PyObject* **o*)

const char ***PyUnicode_AS_DATA** (*PyObject* **o*)

Return a pointer to a *Py_UNICODE* representation of the object. The returned buffer is always terminated with an extra null code point. It may also contain embedded null code points, which would cause the string to be truncated when used in most C functions. The *AS_DATA* form casts the pointer to **const char***. The *o* argument has to be a Unicode object (not checked).

3.3 版更變: This macro is now inefficient -- because in many cases the *Py_UNICODE* representation does not exist and needs to be created -- and can fail (return NULL with an exception set). Try to port the code to use the new *PyUnicode_nBYTE_DATA*() macros or use *PyUnicode_WRITE*() or *PyUnicode_READ*().

自從版本 3.3 後不推薦使用，將會自版本 3.12 中移除。：旧式 Unicode API 的一部分，请迁移到使用 *PyUnicode_nBYTE_DATA*() 宏族。

int **PyUnicode_IsIdentifier** (*PyObject* **o*)

Part of the *Stable ABI*. Return 1 if the string is a valid identifier according to the language definition, section identifiers. Return 0 otherwise.

3.9 版更變: The function does not call *Py_FatalError*() anymore if the string is not ready.

Unicode 字符属性

Unicode provides many different character properties. The most often needed ones are available through these macros which are mapped to C functions depending on the Python configuration.

`int Py_UNICODE_ISSPACE (Py_UCS4 ch)`
根据 *ch* 是否为空白字符返回 1 或 0。

`int Py_UNICODE_ISLOWER (Py_UCS4 ch)`
根据 *ch* 是否为小写字符返回 1 或 0。

`int Py_UNICODE_ISUPPER (Py_UCS4 ch)`
Return 1 or 0 depending on whether *ch* is an uppercase character.

`int Py_UNICODE_ISTITLE (Py_UCS4 ch)`
Return 1 or 0 depending on whether *ch* is a titlecase character.

`int Py_UNICODE_ISLINEBREAK (Py_UCS4 ch)`
Return 1 or 0 depending on whether *ch* is a linebreak character.

`int Py_UNICODE_ISDECIMAL (Py_UCS4 ch)`
Return 1 or 0 depending on whether *ch* is a decimal character.

`int Py_UNICODE_ISDIGIT (Py_UCS4 ch)`
Return 1 or 0 depending on whether *ch* is a digit character.

`int Py_UNICODE_ISNUMERIC (Py_UCS4 ch)`
Return 1 or 0 depending on whether *ch* is a numeric character.

`int Py_UNICODE_ISALPHA (Py_UCS4 ch)`
Return 1 or 0 depending on whether *ch* is an alphabetic character.

`int Py_UNICODE_ISALNUM (Py_UCS4 ch)`
Return 1 or 0 depending on whether *ch* is an alphanumeric character.

`int Py_UNICODE_ISPRINTABLE (Py_UCS4 ch)`
Return 1 or 0 depending on whether *ch* is a printable character. Nonprintable characters are those characters defined in the Unicode character database as "Other" or "Separator", excepting the ASCII space (0x20) which is considered printable. (Note that printable characters in this context are those which should not be escaped when `repr()` is invoked on a string. It has no bearing on the handling of strings written to `sys.stdout` or `sys.stderr`.)

These APIs can be used for fast direct character conversions:

`Py_UCS4 Py_UNICODE_TOLOWER (Py_UCS4 ch)`
Return the character *ch* converted to lower case.

3.3 版後已用: This function uses simple case mappings.

`Py_UCS4 Py_UNICODE_TOUPPER (Py_UCS4 ch)`
Return the character *ch* converted to upper case.

3.3 版後已用: This function uses simple case mappings.

`Py_UCS4 Py_UNICODE_TOTITLE (Py_UCS4 ch)`
Return the character *ch* converted to title case.

3.3 版後已用: This function uses simple case mappings.

`int Py_UNICODE_TODECIMAL (Py_UCS4 ch)`
Return the character *ch* converted to a decimal positive integer. Return -1 if this is not possible. This macro does not raise exceptions.

`int Py_UNICODE_TODIGIT (Py_UCS4 ch)`
Return the character *ch* converted to a single digit integer. Return -1 if this is not possible. This macro does not raise exceptions.

double **Py_UNICODE_TONUMERIC** (*Py_UCS4 ch*)

Return the character *ch* converted to a double. Return -1.0 if this is not possible. This macro does not raise exceptions.

These APIs can be used to work with surrogates:

Py_UNICODE_IS_SURROGATE (*ch*)

Check if *ch* is a surrogate ($0xD800 \leq ch \leq 0xDFFF$).

Py_UNICODE_IS_HIGH_SURROGATE (*ch*)

Check if *ch* is a high surrogate ($0xD800 \leq ch \leq 0xDBFF$).

Py_UNICODE_IS_LOW_SURROGATE (*ch*)

Check if *ch* is a low surrogate ($0xDC00 \leq ch \leq 0xDFFF$).

Py_UNICODE_JOIN_SURROGATES (*high, low*)

Join two surrogate characters and return a single *Py_UCS4* value. *high* and *low* are respectively the leading and trailing surrogates in a surrogate pair.

Creating and accessing Unicode strings

To create Unicode objects and access their basic sequence properties, use these APIs:

PyObject ***PyUnicode_New** (*Py_ssize_t size, Py_UCS4 maxchar*)

Return value: *New reference.* Create a new Unicode object. *maxchar* should be the true maximum code point to be placed in the string. As an approximation, it can be rounded up to the nearest value in the sequence 127, 255, 65535, 1114111.

This is the recommended way to allocate a new Unicode object. Objects created using this function are not resizable.

3.3 版新加入.

PyObject ***PyUnicode_FromKindAndData** (*int kind, const void *buffer, Py_ssize_t size*)

Return value: *New reference.* Create a new Unicode object with the given *kind* (possible values are *PyUnicode_1BYTE_KIND* etc., as returned by *PyUnicode_KIND()*). The *buffer* must point to an array of *size* units of 1, 2 or 4 bytes per character, as given by the *kind*.

3.3 版新加入.

PyObject ***PyUnicode_FromStringAndSize** (*const char *u, Py_ssize_t size*)

Return value: *New reference.* Part of the [Stable ABI](#). Create a Unicode object from the char buffer *u*. The bytes will be interpreted as being UTF-8 encoded. The buffer is copied into the new object. If the buffer is not *NULL*, the return value might be a shared object, i.e. modification of the data is not allowed.

If *u* is *NULL*, this function behaves like *PyUnicode_FromUnicode()* with the buffer set to *NULL*. This usage is deprecated in favor of *PyUnicode_New()*, and will be removed in Python 3.12.

PyObject ***PyUnicode_FromString** (*const char *u*)

Return value: *New reference.* Part of the [Stable ABI](#). Create a Unicode object from a UTF-8 encoded null-terminated char buffer *u*.

PyObject ***PyUnicode_FromFormat** (*const char *format, ...*)

Return value: *New reference.* Part of the [Stable ABI](#). Take a *C printf()*-style *format* string and a variable number of arguments, calculate the size of the resulting Python Unicode string and return a string with the values formatted into it. The variable arguments must be C types and must correspond exactly to the format characters in the *format* ASCII-encoded string. The following format characters are allowed:

格式字符	类型	注释
%%	<i>n/a</i>	文字% 字符。
%c	int	单个字符，表示为 C 语言的整型。
%d	int	等價於 <code>printf("%d").</code> ¹
%u	unsigned int	等價於 <code>printf("%u").</code> ¹
%ld	long	等價於 <code>printf("%ld").</code> ¹
%li	long	等價於 <code>printf("%li").</code> ¹
%lu	unsigned long	等價於 <code>printf("%lu").</code> ¹
%lld	long long	等價於 <code>printf("%lld").</code> ¹
%lli	long long	等價於 <code>printf("%lli").</code> ¹
%llu	unsigned long long	等價於 <code>printf("%llu").</code> ¹
%zd	<code>Py_ssize_t</code>	等價於 <code>printf("%zd").</code> ¹
%zi	<code>Py_ssize_t</code>	等價於 <code>printf("%zi").</code> ¹
%zu	<code>size_t</code>	等價於 <code>printf("%zu").</code> ¹
%i	int	等價於 <code>printf("%i").</code> ¹
%x	int	等價於 <code>printf("%x").</code> ¹
%s	const char*	以 null 为终止符的 C 字符数组。
%p	const void*	一个 C 指针的十六进制表示形式。基本等价于 <code>printf("%p")</code> 但它会确保以字面值 0x 开头，不论系统平台上 <code>printf</code> 的输出是什么。
%A	PyObject*	<code>ascii()</code> 调用的结果。
%U	PyObject*	一 Unicode 物件。
%V	PyObject*, const char*	A Unicode object (which may be NULL) and a null-terminated C character array as a second parameter (which will be used, if the first parameter is NULL).
%S	PyObject*	The result of calling <code>PyObject_Str()</code> .
%R	PyObject*	The result of calling <code>PyObject_Repr()</code> .

An unrecognized format character causes all the rest of the format string to be copied as-is to the result string, and any extra arguments discarded.

備 註: The width formatter unit is number of characters rather than bytes. The precision formatter unit is number of bytes for "%s" and "%V" (if the PyObject* argument is NULL), and a number of characters for "%A", "%U", "%S", "%R" and "%V" (if the PyObject* argument is not NULL).

3.2 版更變: Support for "%lld" and "%llu" added.

3.3 版更變: Support for "%li", "%lli" and "%zi" added.

3.4 版更變: Support width and precision formatter for "%s", "%A", "%U", "%V", "%S", "%R" added.

*PyObject** **PyUnicode_FromFormatV** (const char *format, va_list args)

Return value: New reference. Part of the [Stable ABI](#). Identical to `PyUnicode_FromFormat()` except that it takes exactly two arguments.

*PyObject** **PyUnicode_FromEncodedObject** (*PyObject** obj, const char *encoding, const char *errors)

Return value: New reference. Part of the [Stable ABI](#). Decode an encoded object *obj* to a Unicode object.

bytes, bytearray and other *bytes-like objects* are decoded according to the given *encoding* and using the error handling defined by *errors*. Both can be NULL to have the interface use the default values (see [Built-in Codecs](#) for details).

All other objects, including Unicode objects, cause a `TypeError` to be set.

The API returns NULL if there was an error. The caller is responsible for decref'ing the returned objects.

¹ For integer specifiers (d, u, ld, li, lu, lld, lli, llu, zd, zi, zu, i, x): the 0-conversion flag has effect even when a precision is given.

Py_ssize_t **PyUnicode_GetLength** (*PyObject* *unicode)

Part of the [Stable ABI](#) since version 3.7. Return the length of the Unicode object, in code points.

3.3 版新加入。

Py_ssize_t **PyUnicode_CopyCharacters** (*PyObject* *to, *Py_ssize_t* to_start, *PyObject* *from, *Py_ssize_t* from_start, *Py_ssize_t* how_many)

Copy characters from one Unicode object into another. This function performs character conversion when necessary and falls back to `memcpy()` if possible. Returns `-1` and sets an exception on error, otherwise returns the number of copied characters.

3.3 版新加入。

Py_ssize_t **PyUnicode_Fill** (*PyObject* *unicode, *Py_ssize_t* start, *Py_ssize_t* length, *Py_UCS4* fill_char)

Fill a string with a character: write `fill_char` into `unicode[start:start+length]`.

Fail if `fill_char` is bigger than the string maximum character, or if the string has more than 1 reference.

Return the number of written character, or return `-1` and raise an exception on error.

3.3 版新加入。

int **PyUnicode_WriteChar** (*PyObject* *unicode, *Py_ssize_t* index, *Py_UCS4* character)

Part of the [Stable ABI](#) since version 3.7. Write a character to a string. The string must have been created through `PyUnicode_New()`. Since Unicode strings are supposed to be immutable, the string must not be shared, or have been hashed yet.

This function checks that `unicode` is a Unicode object, that the index is not out of bounds, and that the object can be modified safely (i.e. that its reference count is one).

3.3 版新加入。

Py_UCS4 **PyUnicode_ReadChar** (*PyObject* *unicode, *Py_ssize_t* index)

Part of the [Stable ABI](#) since version 3.7. Read a character from a string. This function checks that `unicode` is a Unicode object and the index is not out of bounds, in contrast to the macro version `PyUnicode_READ_CHAR()`.

3.3 版新加入。

PyObject ***PyUnicode_Substring** (*PyObject* *str, *Py_ssize_t* start, *Py_ssize_t* end)

Return value: New reference. Part of the [Stable ABI](#) since version 3.7. Return a substring of `str`, from character index `start` (included) to character index `end` (excluded). Negative indices are not supported.

3.3 版新加入。

Py_UCS4 ***PyUnicode_AsUCS4** (*PyObject* *u, *Py_UCS4* *buffer, *Py_ssize_t* buflen, int copy_null)

Part of the [Stable ABI](#) since version 3.7. Copy the string `u` into a UCS4 buffer, including a null character, if `copy_null` is set. Returns `NULL` and sets an exception on error (in particular, a `SystemError` if `buflen` is smaller than the length of `u`). `buffer` is returned on success.

3.3 版新加入。

Py_UCS4 ***PyUnicode_AsUCS4Copy** (*PyObject* *u)

Part of the [Stable ABI](#) since version 3.7. Copy the string `u` into a new UCS4 buffer that is allocated using `PyMem_Malloc()`. If this fails, `NULL` is returned with a `MemoryError` set. The returned buffer always has an extra null code point appended.

3.3 版新加入。

Deprecated Py_UNICODE APIs

自從版本 3.3 後不推薦使用，將會自版本 3.12 中移除。

These API functions are deprecated with the implementation of **PEP 393**. Extension modules can continue using them, as they will not be removed in Python 3.x, but need to be aware that their use can now cause performance and memory hits.

PyObject ***PyUnicode_FromUnicode** (const *Py_UNICODE* **u*, *Py_ssize_t* *size*)

Return value: New reference. Create a Unicode object from the *Py_UNICODE* buffer *u* of the given size. *u* may be NULL which causes the contents to be undefined. It is the user's responsibility to fill in the needed data. The buffer is copied into the new object.

If the buffer is not NULL, the return value might be a shared object. Therefore, modification of the resulting Unicode object is only allowed when *u* is NULL.

If the buffer is NULL, *PyUnicode_READY()* must be called once the string content has been filled before using any of the access macros such as *PyUnicode_KIND()*.

自從版本 3.3 後不推薦使用，將會自版本 3.12 中移除。: Part of the old-style Unicode API, please migrate to using *PyUnicode_FromKindAndData()*, *PyUnicode_FromWideChar()*, or *PyUnicode_New()*.

Py_UNICODE ***PyUnicode_AsUnicode** (*PyObject* **unicode*)

Return a read-only pointer to the Unicode object's internal *Py_UNICODE* buffer, or NULL on error. This will create the *Py_UNICODE** representation of the object if it is not yet available. The buffer is always terminated with an extra null code point. Note that the resulting *Py_UNICODE* string may also contain embedded null code points, which would cause the string to be truncated when used in most C functions.

自從版本 3.3 後不推薦使用，將會自版本 3.12 中移除。: Part of the old-style Unicode API, please migrate to using *PyUnicode_AsUCS4()*, *PyUnicode_AsWideChar()*, *PyUnicode_ReadChar()* or similar new APIs.

PyObject ***PyUnicode_TransformDecimalToASCII** (*Py_UNICODE* **s*, *Py_ssize_t* *size*)

Return value: New reference. Create a Unicode object by replacing all decimal digits in *Py_UNICODE* buffer of the given *size* by ASCII digits 0--9 according to their decimal value. Return NULL if an exception occurs.

自從版本 3.3 後不推薦使用，將會自版本 3.11 中移除。: Part of the old-style *Py_UNICODE* API; please migrate to using *Py_UNICODE_TODECIMAL()*.

Py_UNICODE ***PyUnicode_AsUnicodeAndSize** (*PyObject* **unicode*, *Py_ssize_t* **size*)

Like *PyUnicode_AsUnicode()*, but also saves the *Py_UNICODE()* array length (excluding the extra null terminator) in *size*. Note that the resulting *Py_UNICODE** string may contain embedded null code points, which would cause the string to be truncated when used in most C functions.

3.3 版新加入。

自從版本 3.3 後不推薦使用，將會自版本 3.12 中移除。: Part of the old-style Unicode API, please migrate to using *PyUnicode_AsUCS4()*, *PyUnicode_AsWideChar()*, *PyUnicode_ReadChar()* or similar new APIs.

Py_ssize_t **PyUnicode_GetSize** (*PyObject* **unicode*)

Part of the Stable ABI. Return the size of the deprecated *Py_UNICODE* representation, in code units (this includes surrogate pairs as 2 units).

自從版本 3.3 後不推薦使用，將會自版本 3.12 中移除。: 旧式 Unicode API 的一部分，请迁移到使用 *PyUnicode_GET_LENGTH()*。

PyObject ***PyUnicode_FromObject** (*PyObject* **obj*)

Return value: New reference. *Part of the Stable ABI.* Copy an instance of a Unicode subtype to a new true Unicode object if necessary. If *obj* is already a true Unicode object (not a subtype), return the reference with incremented refcount.

Objects other than Unicode or its subtypes will cause a *TypeError*.

Locale Encoding

The current locale encoding can be used to decode text from the operating system.

PyObject*PyUnicode_DecodeLocaleAndSize(const char *str, Py_ssize_t len, const char *errors)

Return value: New reference. Part of the [Stable ABI](#) since version 3.7. Decode a string from UTF-8 on Android and VxWorks, or from the current locale encoding on other platforms. The supported error handlers are "strict" and "surrogateescape" ([PEP 383](#)). The decoder uses "strict" error handler if *errors* is NULL. *str* must end with a null character but cannot contain embedded null characters.

Use `PyUnicode_DecodeFSDefaultAndSize()` to decode a string from `Py_FileSystemDefaultEncoding` (the locale encoding read at Python startup).

This function ignores the Python UTF-8 Mode.

也参考:

`Py_DecodeLocale()` 函式。

3.3 版新加入。

3.7 版更變: The function now also uses the current locale encoding for the surrogateescape error handler, except on Android. Previously, `Py_DecodeLocale()` was used for the surrogateescape, and the current locale encoding was used for strict.

PyObject*PyUnicode_DecodeLocale(const char *str, const char *errors)

Return value: New reference. Part of the [Stable ABI](#) since version 3.7. Similar to `PyUnicode_DecodeLocaleAndSize()`, but compute the string length using `strlen()`.

3.3 版新加入。

PyObject*PyUnicode_EncodeLocale(PyObject *unicode, const char *errors)

Return value: New reference. Part of the [Stable ABI](#) since version 3.7. Encode a Unicode object to UTF-8 on Android and VxWorks, or to the current locale encoding on other platforms. The supported error handlers are "strict" and "surrogateescape" ([PEP 383](#)). The encoder uses "strict" error handler if *errors* is NULL. Return a bytes object. *unicode* cannot contain embedded null characters.

Use `PyUnicode_EncodeFSDefault()` to encode a string to `Py_FileSystemDefaultEncoding` (the locale encoding read at Python startup).

This function ignores the Python UTF-8 Mode.

也参考:

`Py_EncodeLocale()` 函式。

3.3 版新加入。

3.7 版更變: The function now also uses the current locale encoding for the surrogateescape error handler, except on Android. Previously, `Py_EncodeLocale()` was used for the surrogateescape, and the current locale encoding was used for strict.

文件系统编码格式

To encode and decode file names and other environment strings, `Py_FileSystemDefaultEncoding` should be used as the encoding, and `Py_FileSystemDefaultEncodeErrors` should be used as the error handler ([PEP 383](#) and [PEP 529](#)). To encode file names to bytes during argument parsing, the "O&" converter should be used, passing `PyUnicode_FSConverter()` as the conversion function:

int PyUnicode_FSConverter(PyObject *obj, void *result)

Part of the [Stable ABI](#). ParseTuple converter: encode str objects -- obtained directly or through the `os.PathLike` interface -- to bytes using `PyUnicode_EncodeFSDefault()`; bytes objects are output as-is. *result* must be a `PyBytesObject*` which must be released when it is no longer used.

3.1 版新加入。

3.6 版更變: 接受一个 *path-like object*。

To decode file names to `str` during argument parsing, the `"O&"` converter should be used, passing `PyUnicode_FSDecoder()` as the conversion function:

int PyUnicode_FSDecoder (*PyObject* *obj, void *result)

Part of the Stable ABI. ParseTuple converter: decode bytes objects -- obtained either directly or indirectly through the `os.PathLike` interface -- to `str` using `PyUnicode_DecodeFSDefaultAndSize()`; `str` objects are output as-is. *result* must be a *PyUnicodeObject** which must be released when it is no longer used.

3.2 版新加入.

3.6 版更變: 接受一个 *path-like object*。

PyObject ***PyUnicode_DecodeFSDefaultAndSize** (const char *s, *Py_ssize_t* size)

Return value: New reference. *Part of the Stable ABI.* Decode a string from the *filesystem encoding and error handler*.

If `Py_FileSystemDefaultEncoding` is not set, fall back to the locale encoding.

`Py_FileSystemDefaultEncoding` is initialized at startup from the locale encoding and cannot be modified later. If you need to decode a string from the current locale encoding, use `PyUnicode_DecodeLocaleAndSize()`.

也参考:

`Py_DecodeLocale()` 函式。

3.6 版更變: Use `Py_FileSystemDefaultEncodeErrors` error handler.

PyObject ***PyUnicode_DecodeFSDefault** (const char *s)

Return value: New reference. *Part of the Stable ABI.* Decode a null-terminated string from the *filesystem encoding and error handler*.

If `Py_FileSystemDefaultEncoding` is not set, fall back to the locale encoding.

Use `PyUnicode_DecodeFSDefaultAndSize()` if you know the string length.

3.6 版更變: Use `Py_FileSystemDefaultEncodeErrors` error handler.

PyObject ***PyUnicode_EncodeFSDefault** (*PyObject* *unicode)

Return value: New reference. *Part of the Stable ABI.* Encode a Unicode object to `Py_FileSystemDefaultEncoding` with the `Py_FileSystemDefaultEncodeErrors` error handler, and return bytes. Note that the resulting bytes object may contain null bytes.

If `Py_FileSystemDefaultEncoding` is not set, fall back to the locale encoding.

`Py_FileSystemDefaultEncoding` is initialized at startup from the locale encoding and cannot be modified later. If you need to encode a string to the current locale encoding, use `PyUnicode_EncodeLocale()`.

也参考:

`Py_EncodeLocale()` 函式。

3.2 版新加入.

3.6 版更變: Use `Py_FileSystemDefaultEncodeErrors` error handler.

wchar_t Support

wchar_t support for platforms which support it:

PyObject ***PyUnicode_FromWideChar** (**const** wchar_t *w, *Py_ssize_t* size)

Return value: New reference. *Part of the Stable ABI.* Create a Unicode object from the wchar_t buffer w of the given size. Passing -1 as the size indicates that the function must itself compute the length, using wcslen. Return NULL on failure.

Py_ssize_t **PyUnicode_AsWideChar** (*PyObject* *unicode, wchar_t *w, *Py_ssize_t* size)

Part of the Stable ABI. Copy the Unicode object contents into the wchar_t buffer w. At most size wchar_t characters are copied (excluding a possibly trailing null termination character). Return the number of wchar_t characters copied or -1 in case of an error. Note that the resulting wchar_t* string may or may not be null-terminated. It is the responsibility of the caller to make sure that the wchar_t* string is null-terminated in case this is required by the application. Also, note that the wchar_t* string might contain null characters, which would cause the string to be truncated when used with most C functions.

wchar_t ***PyUnicode_AsWideCharString** (*PyObject* *unicode, *Py_ssize_t* *size)

Part of the Stable ABI since version 3.7. Convert the Unicode object to a wide character string. The output string always ends with a null character. If size is not NULL, write the number of wide characters (excluding the trailing null termination character) into *size. Note that the resulting wchar_t string might contain null characters, which would cause the string to be truncated when used with most C functions. If size is NULL and the wchar_t* string contains null characters a ValueError is raised.

Returns a buffer allocated by PyMem_Alloc() (use PyMem_Free() to free it) on success. On error, returns NULL and *size is undefined. Raises a MemoryError if memory allocation is failed.

3.2 版新加入。

3.7 版更變: Raises a ValueError if size is NULL and the wchar_t* string contains null characters.

Built-in Codecs

Python provides a set of built-in codecs which are written in C for speed. All of these codecs are directly usable via the following functions.

Many of the following APIs take two arguments encoding and errors, and they have the same semantics as the ones of the built-in str() string object constructor.

Setting encoding to NULL causes the default encoding to be used which is UTF-8. The file system calls should use PyUnicode_FSConverter() for encoding file names. This uses the variable Py_FileSystemDefaultEncoding internally. This variable should be treated as read-only: on some systems, it will be a pointer to a static string, on others, it will change at run-time (such as when the application invokes setlocale).

Error handling is set by errors which may also be set to NULL meaning to use the default handling defined for the codec. Default error handling for all built-in codecs is "strict" (ValueError is raised).

The codecs all use a similar interface. Only deviations from the following generic ones are documented for simplicity.

Generic Codecs

These are the generic codec APIs:

PyObject ***PyUnicode_Ddecode** (**const** char *s, *Py_ssize_t* size, **const** char *encoding, **const** char *errors)

Return value: New reference. *Part of the Stable ABI.* Create a Unicode object by decoding size bytes of the encoded string s. encoding and errors have the same meaning as the parameters of the same name in the str() built-in function. The codec to be used is looked up using the Python codec registry. Return NULL if an exception was raised by the codec.

PyObject *PyUnicode_AsEncodedString (PyObject *unicode, const char *encoding, const char *errors)

Return value: New reference. Part of the [Stable ABI](#). Encode a Unicode object and return the result as Python bytes object. *encoding* and *errors* have the same meaning as the parameters of the same name in the `Unicode.encode()` method. The codec to be used is looked up using the Python codec registry. Return NULL if an exception was raised by the codec.

PyObject *PyUnicode_Encode (const Py_UNICODE *s, Py_ssize_t size, const char *encoding, const char *errors)

Return value: New reference. Encode the `Py_UNICODE` buffer *s* of the given *size* and return a Python bytes object. *encoding* and *errors* have the same meaning as the parameters of the same name in the `Unicode.encode()` method. The codec to be used is looked up using the Python codec registry. Return NULL if an exception was raised by the codec.

自從版本 3.3 後不推薦使用，將會自版本 3.11 中移除。: Part of the old-style `Py_UNICODE` API; please migrate to using `PyUnicode_AsEncodedString()`.

UTF-8 编解码器

以下是 UTF-8 编解码器 API:

PyObject *PyUnicode_DecodeUTF8 (const char *s, Py_ssize_t size, const char *errors)

Return value: New reference. Part of the [Stable ABI](#). Create a Unicode object by decoding *size* bytes of the UTF-8 encoded string *s*. Return NULL if an exception was raised by the codec.

PyObject *PyUnicode_DecodeUTF8Stateful (const char *s, Py_ssize_t size, const char *errors, Py_ssize_t *consumed)

Return value: New reference. Part of the [Stable ABI](#). If *consumed* is NULL, behave like `PyUnicode_DecodeUTF8()`. If *consumed* is not NULL, trailing incomplete UTF-8 byte sequences will not be treated as an error. Those bytes will not be decoded and the number of bytes that have been decoded will be stored in *consumed*.

PyObject *PyUnicode_AsUTF8String (PyObject *unicode)

Return value: New reference. Part of the [Stable ABI](#). Encode a Unicode object using UTF-8 and return the result as Python bytes object. Error handling is "strict". Return NULL if an exception was raised by the codec.

const char *PyUnicode_AsUTF8AndSize (PyObject *unicode, Py_ssize_t *size)

Part of the [Stable ABI](#) since version 3.10. Return a pointer to the UTF-8 encoding of the Unicode object, and store the size of the encoded representation (in bytes) in *size*. The *size* argument can be NULL; in this case no size will be stored. The returned buffer always has an extra null byte appended (not included in *size*), regardless of whether there are any other null code points.

In the case of an error, NULL is returned with an exception set and no *size* is stored.

This caches the UTF-8 representation of the string in the Unicode object, and subsequent calls will return a pointer to the same buffer. The caller is not responsible for deallocating the buffer. The buffer is deallocated and pointers to it become invalid when the Unicode object is garbage collected.

3.3 版新加入.

3.7 版更變: The return type is now `const char *` rather of `char *`.

3.10 版更變: This function is a part of the [limited API](#).

const char *PyUnicode_AsUTF8 (PyObject *unicode)

As `PyUnicode_AsUTF8AndSize()`, but does not store the size.

3.3 版新加入.

3.7 版更變: The return type is now `const char *` rather of `char *`.

PyObject *PyUnicode_EncodeUTF8 (const Py_UNICODE *s, Py_ssize_t size, const char *errors)

Return value: New reference. Encode the `Py_UNICODE` buffer *s* of the given *size* using UTF-8 and return a Python bytes object. Return NULL if an exception was raised by the codec.

自從版本 3.3 後不推薦使用，將會自版本 3.11 中移除。: Part of the old-style `Py_UNICODE` API; please migrate to using `PyUnicode_AsUTF8String()`, `PyUnicode_AsUTF8AndSize()` or `PyUnicode_AsEncodedString()`.

UTF-32 Codecs

These are the UTF-32 codec APIs:

PyObject*PyUnicode_DecodeUTF32 (const char *s, Py_ssize_t size, const char *errors, int *byteorder)

Return value: New reference. Part of the [Stable ABI](#). Decode size bytes from a UTF-32 encoded buffer string and return the corresponding Unicode object. errors (if non-NULL) defines the error handling. It defaults to "strict".

If byteorder is non-NULL, the decoder starts decoding using the given byte order:

```
*byteorder == -1: little endian
*byteorder == 0:  native order
*byteorder == 1:  big endian
```

If *byteorder is zero, and the first four bytes of the input data are a byte order mark (BOM), the decoder switches to this byte order and the BOM is not copied into the resulting Unicode string. If *byteorder is -1 or 1, any byte order mark is copied to the output.

After completion, *byteorder is set to the current byte order at the end of input data.

If byteorder is NULL, the codec starts in native order mode.

Return NULL if an exception was raised by the codec.

PyObject*PyUnicode_DecodeUTF32Stateful (const char *s, Py_ssize_t size, const char *errors, int *byteorder, Py_ssize_t *consumed)

Return value: New reference. Part of the [Stable ABI](#). If consumed is NULL, behave like `PyUnicode_DecodeUTF32()`. If consumed is not NULL, `PyUnicode_DecodeUTF32Stateful()` will not treat trailing incomplete UTF-32 byte sequences (such as a number of bytes not divisible by four) as an error. Those bytes will not be decoded and the number of bytes that have been decoded will be stored in consumed.

PyObject*PyUnicode_AsUTF32String (PyObject *unicode)

Return value: New reference. Part of the [Stable ABI](#). Return a Python byte string using the UTF-32 encoding in native byte order. The string always starts with a BOM mark. Error handling is "strict". Return NULL if an exception was raised by the codec.

PyObject*PyUnicode_EncodeUTF32 (const Py_UNICODE *s, Py_ssize_t size, const char *errors, int byteorder)

Return value: New reference. Return a Python bytes object holding the UTF-32 encoded value of the Unicode data in s. Output is written according to the following byte order:

```
byteorder == -1: little endian
byteorder == 0:  native byte order (writes a BOM mark)
byteorder == 1:  big endian
```

If byteorder is 0, the output string will always start with the Unicode BOM mark (U+FEFF). In the other two modes, no BOM mark is prepended.

If `Py_UNICODE_WIDE` is not defined, surrogate pairs will be output as a single code point.

Return NULL if an exception was raised by the codec.

自從版本 3.3 後不推薦使用，將會自版本 3.11 中移除。: Part of the old-style `Py_UNICODE` API; please migrate to using `PyUnicode_AsUTF32String()` or `PyUnicode_AsEncodedString()`.

UTF-16 Codecs

These are the UTF-16 codec APIs:

PyObject *PyUnicode_DecodeUTF16(**const** char *s, *Py_ssize_t* size, **const** char *errors, int *byteorder)

Return value: New reference. Part of the [Stable ABI](#). Decode size bytes from a UTF-16 encoded buffer string and return the corresponding Unicode object. errors (if non-NULL) defines the error handling. It defaults to "strict".

If byteorder is non-NULL, the decoder starts decoding using the given byte order:

```
*byteorder == -1: little endian
*byteorder == 0:  native order
*byteorder == 1:  big endian
```

If *byteorder is zero, and the first two bytes of the input data are a byte order mark (BOM), the decoder switches to this byte order and the BOM is not copied into the resulting Unicode string. If *byteorder is -1 or 1, any byte order mark is copied to the output (where it will result in either a \uffeff or a \uffffe character).

After completion, *byteorder is set to the current byte order at the end of input data.

If byteorder is NULL, the codec starts in native order mode.

Return NULL if an exception was raised by the codec.

PyObject *PyUnicode_DecodeUTF16Stateful(**const** char *s, *Py_ssize_t* size, **const** char *errors, int *byteorder, *Py_ssize_t* *consumed)

Return value: New reference. Part of the [Stable ABI](#). If consumed is NULL, behave like *PyUnicode_DecodeUTF16()*. If consumed is not NULL, *PyUnicode_DecodeUTF16Stateful()* will not treat trailing incomplete UTF-16 byte sequences (such as an odd number of bytes or a split surrogate pair) as an error. Those bytes will not be decoded and the number of bytes that have been decoded will be stored in consumed.

PyObject *PyUnicode_AsUTF16String(*PyObject* *unicode)

Return value: New reference. Part of the [Stable ABI](#). Return a Python byte string using the UTF-16 encoding in native byte order. The string always starts with a BOM mark. Error handling is "strict". Return NULL if an exception was raised by the codec.

PyObject *PyUnicode_EncodeUTF16(**const** *Py_UNICODE* *s, *Py_ssize_t* size, **const** char *errors, int byteorder)

Return value: New reference. Return a Python bytes object holding the UTF-16 encoded value of the Unicode data in s. Output is written according to the following byte order:

```
byteorder == -1: little endian
byteorder == 0:  native byte order (writes a BOM mark)
byteorder == 1:  big endian
```

If byteorder is 0, the output string will always start with the Unicode BOM mark (U+FEFF). In the other two modes, no BOM mark is prepended.

If *Py_UNICODE_WIDE* is defined, a single *Py_UNICODE* value may get represented as a surrogate pair. If it is not defined, each *Py_UNICODE* value is interpreted as a UCS-2 character.

Return NULL if an exception was raised by the codec.

自從版本 3.3 後不推薦使用，將會自版本 3.11 中移除。: Part of the old-style *Py_UNICODE* API; please migrate to using *PyUnicode_AsUTF16String()* or *PyUnicode_AsEncodedString()*.

UTF-7 Codecs

These are the UTF-7 codec APIs:

PyObject *PyUnicode_DecodeUTF7 (**const** char *s, *Py_ssize_t* size, **const** char *errors)
Return value: New reference. Part of the [Stable ABI](#). Create a Unicode object by decoding *size* bytes of the UTF-7 encoded string *s*. Return NULL if an exception was raised by the codec.

PyObject *PyUnicode_DecodeUTF7Stateful (**const** char *s, *Py_ssize_t* size, **const** char *errors, *Py_ssize_t* *consumed)
Return value: New reference. Part of the [Stable ABI](#). If *consumed* is NULL, behave like [PyUnicode_DecodeUTF7\(\)](#). If *consumed* is not NULL, trailing incomplete UTF-7 base-64 sections will not be treated as an error. Those bytes will not be decoded and the number of bytes that have been decoded will be stored in *consumed*.

PyObject *PyUnicode_EncodeUTF7 (**const** *Py_UNICODE* *s, *Py_ssize_t* size, int *base64SetO*, int *base64WhiteSpace*, **const** char *errors)
Return value: New reference. Encode the *Py_UNICODE* buffer of the given size using UTF-7 and return a Python bytes object. Return NULL if an exception was raised by the codec.

If *base64SetO* is nonzero, "Set O" (punctuation that has no otherwise special meaning) will be encoded in base-64. If *base64WhiteSpace* is nonzero, whitespace will be encoded in base-64. Both are set to zero for the Python "utf-7" codec.

自從版本 3.3 後不推薦使用，將會自版本 3.11 中移除。: Part of the old-style *Py_UNICODE* API; please migrate to using [PyUnicode_AsEncodedString\(\)](#).

Unicode-Escape 编解码器

These are the "Unicode Escape" codec APIs:

PyObject *PyUnicode_DecodeUnicodeEscape (**const** char *s, *Py_ssize_t* size, **const** char *errors)
Return value: New reference. Part of the [Stable ABI](#). Create a Unicode object by decoding *size* bytes of the Unicode-Escape encoded string *s*. Return NULL if an exception was raised by the codec.

PyObject *PyUnicode_AsUnicodeEscapeString (*PyObject* *unicode)
Return value: New reference. Part of the [Stable ABI](#). Encode a Unicode object using Unicode-Escape and return the result as a bytes object. Error handling is "strict". Return NULL if an exception was raised by the codec.

PyObject *PyUnicode_EncodeUnicodeEscape (**const** *Py_UNICODE* *s, *Py_ssize_t* size)
Return value: New reference. Encode the *Py_UNICODE* buffer of the given *size* using Unicode-Escape and return a bytes object. Return NULL if an exception was raised by the codec.

自從版本 3.3 後不推薦使用，將會自版本 3.11 中移除。: Part of the old-style *Py_UNICODE* API; please migrate to using [PyUnicode_AsUnicodeEscapeString\(\)](#).

Raw-Unicode-Escape Codecs

These are the "Raw Unicode Escape" codec APIs:

PyObject *PyUnicode_DecodeRawUnicodeEscape (**const** char *s, *Py_ssize_t* size, **const** char *errors)
Return value: New reference. Part of the [Stable ABI](#). Create a Unicode object by decoding *size* bytes of the Raw-Unicode-Escape encoded string *s*. Return NULL if an exception was raised by the codec.

PyObject *PyUnicode_AsRawUnicodeEscapeString (*PyObject* *unicode)
Return value: New reference. Part of the [Stable ABI](#). Encode a Unicode object using Raw-Unicode-Escape and return the result as a bytes object. Error handling is "strict". Return NULL if an exception was raised by the codec.

PyObject *PyUnicode_EncodeRawUnicodeEscape (const Py_UNICODE *s, Py_ssize_t size)

Return value: New reference. Encode the `Py_UNICODE` buffer of the given `size` using Raw-Unicode-Escape and return a bytes object. Return NULL if an exception was raised by the codec.

自從版本 3.3 後不推薦使用，將會自版本 3.11 中移除。: Part of the old-style `Py_UNICODE` API; please migrate to using `PyUnicode_AsRawUnicodeEscapeString()` or `PyUnicode_AsEncodedString()`.

Latin-1 Codecs

These are the Latin-1 codec APIs: Latin-1 corresponds to the first 256 Unicode ordinals and only these are accepted by the codecs during encoding.

PyObject *PyUnicode_DecodeLatin1 (const char *s, Py_ssize_t size, const char *errors)

Return value: New reference. Part of the [Stable ABI](#). Create a Unicode object by decoding `size` bytes of the Latin-1 encoded string `s`. Return NULL if an exception was raised by the codec.

PyObject *PyUnicode_AsLatin1String (PyObject *unicode)

Return value: New reference. Part of the [Stable ABI](#). Encode a Unicode object using Latin-1 and return the result as Python bytes object. Error handling is "strict". Return NULL if an exception was raised by the codec.

PyObject *PyUnicode_EncodeLatin1 (const Py_UNICODE *s, Py_ssize_t size, const char *errors)

Return value: New reference. Encode the `Py_UNICODE` buffer of the given `size` using Latin-1 and return a Python bytes object. Return NULL if an exception was raised by the codec.

自從版本 3.3 後不推薦使用，將會自版本 3.11 中移除。: Part of the old-style `Py_UNICODE` API; please migrate to using `PyUnicode_AsLatin1String()` or `PyUnicode_AsEncodedString()`.

ASCII Codecs

These are the ASCII codec APIs. Only 7-bit ASCII data is accepted. All other codes generate errors.

PyObject *PyUnicode_DecodeASCII (const char *s, Py_ssize_t size, const char *errors)

Return value: New reference. Part of the [Stable ABI](#). Create a Unicode object by decoding `size` bytes of the ASCII encoded string `s`. Return NULL if an exception was raised by the codec.

PyObject *PyUnicode_AsASCIIString (PyObject *unicode)

Return value: New reference. Part of the [Stable ABI](#). Encode a Unicode object using ASCII and return the result as Python bytes object. Error handling is "strict". Return NULL if an exception was raised by the codec.

PyObject *PyUnicode_EncodeASCII (const Py_UNICODE *s, Py_ssize_t size, const char *errors)

Return value: New reference. Encode the `Py_UNICODE` buffer of the given `size` using ASCII and return a Python bytes object. Return NULL if an exception was raised by the codec.

自從版本 3.3 後不推薦使用，將會自版本 3.11 中移除。: Part of the old-style `Py_UNICODE` API; please migrate to using `PyUnicode_AsASCIIString()` or `PyUnicode_AsEncodedString()`.

Character Map Codecs

This codec is special in that it can be used to implement many different codecs (and this is in fact what was done to obtain most of the standard codecs included in the `encodings` package). The codec uses mappings to encode and decode characters. The mapping objects provided must support the `__getitem__()` mapping interface; dictionaries and sequences work well.

These are the mapping codec APIs:

PyObject *PyUnicode_DecodeCharmap (const char *data, Py_ssize_t size, PyObject *mapping, const char *errors)

Return value: New reference. Part of the [Stable ABI](#). Create a Unicode object by decoding `size` bytes of the encoded string `s` using the given `mapping` object. Return NULL if an exception was raised by the codec.

If *mapping* is NULL, Latin-1 decoding will be applied. Else *mapping* must map bytes ordinals (integers in the range from 0 to 255) to Unicode strings, integers (which are then interpreted as Unicode ordinals) or None. Unmapped data bytes -- ones which cause a `LookupError`, as well as ones which get mapped to None, `0xFFFE` or `'\ufffe'`, are treated as undefined mappings and cause an error.

PyObject ***PyUnicode_AsCharmapString** (*PyObject* *unicode, *PyObject* *mapping)

Return value: New reference. Part of the [Stable ABI](#). Encode a Unicode object using the given *mapping* object and return the result as a bytes object. Error handling is "strict". Return NULL if an exception was raised by the codec.

The *mapping* object must map Unicode ordinal integers to bytes objects, integers in the range from 0 to 255 or None. Unmapped character ordinals (ones which cause a `LookupError`) as well as mapped to None are treated as "undefined mapping" and cause an error.

PyObject ***PyUnicode_EncodeCharmap** (**const** *Py_UNICODE* *s, *Py_ssize_t* size, *PyObject* *mapping, **const** char *errors)

Return value: New reference. Encode the *Py_UNICODE* buffer of the given *size* using the given *mapping* object and return the result as a bytes object. Return NULL if an exception was raised by the codec.

自從版本 3.3 後不推薦使用，將會自版本 3.11 中移除。: Part of the old-style *Py_UNICODE* API; please migrate to using *PyUnicode_AsCharmapString()* or *PyUnicode_AsEncodedString()*.

The following codec API is special in that maps Unicode to Unicode.

PyObject ***PyUnicode_Translate** (*PyObject* *str, *PyObject* *table, **const** char *errors)

Return value: New reference. Part of the [Stable ABI](#). Translate a string by applying a character mapping table to it and return the resulting Unicode object. Return NULL if an exception was raised by the codec.

The mapping table must map Unicode ordinal integers to Unicode ordinal integers or None (causing deletion of the character).

Mapping tables need only provide the `__getitem__()` interface; dictionaries and sequences work well. Unmapped character ordinals (ones which cause a `LookupError`) are left untouched and are copied as-is.

errors has the usual meaning for codecs. It may be NULL which indicates to use the default error handling.

PyObject ***PyUnicode_TranslateCharmap** (**const** *Py_UNICODE* *s, *Py_ssize_t* size, *PyObject* *mapping, **const** char *errors)

Return value: New reference. Translate a *Py_UNICODE* buffer of the given *size* by applying a character mapping table to it and return the resulting Unicode object. Return NULL when an exception was raised by the codec.

自從版本 3.3 後不推薦使用，將會自版本 3.11 中移除。: Part of the old-style *Py_UNICODE* API; please migrate to using *PyUnicode_Translate()* or *generic codec based API*

MBCS codecs for Windows

These are the MBCS codec APIs. They are currently only available on Windows and use the Win32 MBCS converters to implement the conversions. Note that MBCS (or DBCS) is a class of encodings, not just one. The target encoding is defined by the user settings on the machine running the codec.

PyObject ***PyUnicode_DecodeMBCS** (**const** char *s, *Py_ssize_t* size, **const** char *errors)

Return value: New reference. Part of the [Stable ABI](#) on Windows since version 3.7. Create a Unicode object by decoding *size* bytes of the MBCS encoded string *s*. Return NULL if an exception was raised by the codec.

PyObject ***PyUnicode_DecodeMBCSStateful** (**const** char *s, *Py_ssize_t* size, **const** char *errors, *Py_ssize_t* *consumed)

Return value: New reference. Part of the [Stable ABI](#) on Windows since version 3.7. If *consumed* is NULL, behave like *PyUnicode_DecodeMBCS()*. If *consumed* is not NULL, *PyUnicode_DecodeMBCSStateful()* will not decode trailing lead byte and the number of bytes that have been decoded will be stored in *consumed*.

PyObject ***PyUnicode_AsMBCSString** (*PyObject* *unicode)

Return value: New reference. Part of the [Stable ABI](#) on Windows since version 3.7. Encode a Unicode object

using MBCS and return the result as Python bytes object. Error handling is "strict". Return NULL if an exception was raised by the codec.

*PyObject** **PyUnicode_EncodeCodePage** (int *code_page*, *PyObject** *unicode*, const char **errors*)

Return value: New reference. Part of the [Stable ABI](#) on Windows since version 3.7. Encode the Unicode object using the specified code page and return a Python bytes object. Return NULL if an exception was raised by the codec. Use CP_ACP code page to get the MBCS encoder.

3.3 版新加入。

*PyObject** **PyUnicode_EncodeMBCS** (const *Py_UNICODE** *s*, *Py_ssize_t* *size*, const char **errors*)

Return value: New reference. Encode the *Py_UNICODE* buffer of the given *size* using MBCS and return a Python bytes object. Return NULL if an exception was raised by the codec.

自從版本 3.3 後不推薦使用，將會自版本 4.0 中移除。： Part of the old-style *Py_UNICODE* API; please migrate to using *PyUnicode_AsMBCSString()*, *PyUnicode_EncodeCodePage()* or *PyUnicode_AsEncodedString()*.

Methods & Slots

方法与槽位函数

The following APIs are capable of handling Unicode objects and strings on input (we refer to them as strings in the descriptions) and return Unicode objects or integers as appropriate.

They all return NULL or -1 if an exception occurs.

*PyObject** **PyUnicode_Concat** (*PyObject** *left*, *PyObject** *right*)

Return value: New reference. Part of the [Stable ABI](#). Concat two strings giving a new Unicode string.

*PyObject** **PyUnicode_Split** (*PyObject** *s*, *PyObject** *sep*, *Py_ssize_t* *maxsplit*)

Return value: New reference. Part of the [Stable ABI](#). Split a string giving a list of Unicode strings. If *sep* is NULL, splitting will be done at all whitespace substrings. Otherwise, splits occur at the given separator. At most *maxsplit* splits will be done. If negative, no limit is set. Separators are not included in the resulting list.

*PyObject** **PyUnicode_Splitlines** (*PyObject** *s*, int *keepend*)

Return value: New reference. Part of the [Stable ABI](#). Split a Unicode string at line breaks, returning a list of Unicode strings. CRLF is considered to be one line break. If *keepend* is 0, the line break characters are not included in the resulting strings.

*PyObject** **PyUnicode_Join** (*PyObject** *separator*, *PyObject** *seq*)

Return value: New reference. Part of the [Stable ABI](#). Join a sequence of strings using the given *separator* and return the resulting Unicode string.

Py_ssize_t **PyUnicode_Tailmatch** (*PyObject** *str*, *PyObject** *substr*, *Py_ssize_t* *start*, *Py_ssize_t* *end*, int *direction*)

Part of the [Stable ABI](#). Return 1 if *substr* matches *str*[*start*:*end*] at the given tail end (*direction* == -1 means to do a prefix match, *direction* == 1 a suffix match), 0 otherwise. Return -1 if an error occurred.

Py_ssize_t **PyUnicode_Find** (*PyObject** *str*, *PyObject** *substr*, *Py_ssize_t* *start*, *Py_ssize_t* *end*, int *direction*)

Part of the [Stable ABI](#). Return the first position of *substr* in *str*[*start*:*end*] using the given *direction* (*direction* == 1 means to do a forward search, *direction* == -1 a backward search). The return value is the index of the first match; a value of -1 indicates that no match was found, and -2 indicates that an error occurred and an exception has been set.

Py_ssize_t **PyUnicode_FindChar** (*PyObject** *str*, *Py_UCS4* *ch*, *Py_ssize_t* *start*, *Py_ssize_t* *end*, int *direction*)

Part of the [Stable ABI](#) since version 3.7. Return the first position of the character *ch* in *str*[*start*:*end*] using the given *direction* (*direction* == 1 means to do a forward search, *direction* == -1 a backward search). The return value is the index of the first match; a value of -1 indicates that no match was found, and -2 indicates that an error occurred and an exception has been set.

3.3 版新加入。

3.7 版更變: *start* and *end* are now adjusted to behave like `str[start:end]`.

Py_ssize_t **PyUnicode_Count** (*PyObject* **str*, *PyObject* **substr*, *Py_ssize_t* *start*, *Py_ssize_t* *end*)

Part of the Stable ABI. Return the number of non-overlapping occurrences of *substr* in `str[start:end]`. Return `-1` if an error occurred.

PyObject ***PyUnicode_Replace** (*PyObject* **str*, *PyObject* **substr*, *PyObject* **replstr*, *Py_ssize_t* *maxcount*)

Return value: New reference. Part of the Stable ABI. Replace at most *maxcount* occurrences of *substr* in *str* with *replstr* and return the resulting Unicode object. *maxcount* == `-1` means replace all occurrences.

int **PyUnicode_Compare** (*PyObject* **left*, *PyObject* **right*)

Part of the Stable ABI. Compare two strings and return `-1`, `0`, `1` for less than, equal, and greater than, respectively.

This function returns `-1` upon failure, so one should call *PyErr_Occurred()* to check for errors.

int **PyUnicode_CompareWithASCIIString** (*PyObject* **uni*, const char **string*)

Part of the Stable ABI. Compare a Unicode object, *uni*, with *string* and return `-1`, `0`, `1` for less than, equal, and greater than, respectively. It is best to pass only ASCII-encoded strings, but the function interprets the input string as ISO-8859-1 if it contains non-ASCII characters.

This function does not raise exceptions.

PyObject ***PyUnicode_RichCompare** (*PyObject* **left*, *PyObject* **right*, int *op*)

Return value: New reference. Part of the Stable ABI. 对两个 Unicode 字符串执行富比较并返回以下值之一:

- NULL in case an exception was raised
- Py_True or Py_False for successful comparisons
- Py_NotImplemented in case the type combination is unknown

Possible values for *op* are `Py_GT`, `Py_GE`, `Py_EQ`, `Py_NE`, `Py_LT`, and `Py_LE`.

PyObject ***PyUnicode_Format** (*PyObject* **format*, *PyObject* **args*)

Return value: New reference. Part of the Stable ABI. Return a new string object from *format* and *args*; this is analogous to `format % args`.

int **PyUnicode_Contains** (*PyObject* **container*, *PyObject* **element*)

Part of the Stable ABI. Check whether *element* is contained in *container* and return true or false accordingly.

element has to coerce to a one element Unicode string. `-1` is returned if there was an error.

void **PyUnicode_InternInPlace** (*PyObject* ***string*)

Part of the Stable ABI. Intern the argument *string* in place. The argument must be the address of a pointer variable pointing to a Python Unicode string object. If there is an existing interned string that is the same as *string*, it sets *string* to it (decrementing the reference count of the old string object and incrementing the reference count of the interned string object), otherwise it leaves *string* alone and interns it (incrementing its reference count). (Clarification: even though there is a lot of talk about reference counts, think of this function as reference-count-neutral; you own the object after the call if and only if you owned it before the call.)

PyObject ***PyUnicode_InternFromString** (const char **v*)

Return value: New reference. Part of the Stable ABI. A combination of *PyUnicode_FromString()* and *PyUnicode_InternInPlace()*, returning either a new Unicode string object that has been interned, or a new ("owned") reference to an earlier interned string object with the same value.

8.3.4 元組 (Tuple) 物件

type PyTupleObject

这个 *PyObject* 的子类型代表一个 Python 的元组对象。

PyObject **PyTuple_Type**

Part of the Stable ABI. *PyObject* 的实例代表一个 Python 元组类型，这与 Python 层面的 tuple 是相同的对象。

int **PyTuple_Check** (*PyObject* *p)

如果 *p* 是一个 tuple 对象或者 tuple 类型的子类型的实例则返回真值。此函数总是会成功执行。

int **PyTuple_CheckExact** (*PyObject* *p)

如果 *p* 是一个 tuple 对象但不是 tuple 类型的子类型的实例则返回真值。此函数总是会成功执行。

PyObject ***PyTuple_New** (*Py_ssize_t* len)

Return value: New reference. Part of the Stable ABI. 成功时返回一个新的元组对象，长度为 *len*，失败时返回 “NULL”。

PyObject ***PyTuple_Pack** (*Py_ssize_t* n, ...)

Return value: New reference. Part of the Stable ABI. 成功时返回一个新的元组对象，大小为 *n*，失败时返回 NULL。元组值初始化为指向 Python 对象的后续 *n* 个 C 参数。PyTuple_Pack(2, a, b) 和 Py_BuildValue("(OO)", a, b) 相等。

Py_ssize_t **PyTuple_Size** (*PyObject* *p)

Part of the Stable ABI. 获取指向元组对象的指针，并返回该元组的大小。

Py_ssize_t **PyTuple_GET_SIZE** (*PyObject* *p)

返回元组 *p* 的大小，它必须为非 NULL 并且指向一个元组；不执行错误检查。

PyObject ***PyTuple_GetItem** (*PyObject* *p, *Py_ssize_t* pos)

Return value: Borrowed reference. Part of the Stable ABI. 返回 *p* 所指向的元组中位于 *pos* 处的对象。如果 *pos* 为负值或超出范围，则返回 NULL 并设置一个 *IndexError* 异常。

PyObject ***PyTuple_GET_ITEM** (*PyObject* *p, *Py_ssize_t* pos)

Return value: Borrowed reference. 类似于 *PyTuple_GetItem()*，但不检查其参数。

PyObject ***PyTuple_GetSlice** (*PyObject* *p, *Py_ssize_t* low, *Py_ssize_t* high)

Return value: New reference. Part of the Stable ABI. 返回 *p* 所指向的元组的切片，在 *low* 和 *high* 之间，或者在失败时返回 NULL。这等同于 Python 表达式 *p*[*low*:*high*]。不支持从列表末尾索引。

int **PyTuple_SetItem** (*PyObject* *p, *Py_ssize_t* pos, *PyObject* *o)

Part of the Stable ABI. 在 *p* 指向的元组的 *pos* 位置插入对对象 *o* 的引用。成功时返回 0；如果 *pos* 越界，则返回 -1，并抛出一个 *IndexError* 异常。

備註：此函数会“窃取”对 *o* 的引用，并丢弃对元组中已在受影响位置的条目的引用。

void **PyTuple_SET_ITEM** (*PyObject* *p, *Py_ssize_t* pos, *PyObject* *o)

类似于 *PyTuple_SetItem()*，但不进行错误检查，并且应该只是被用来填充全新的元组。

備註：这个宏会“偷走”一个对 *o* 的引用，但与 *PyTuple_SetItem()* 不同，它不会丢弃对任何被替换项的引用；元组中位于 *pos* 位置的任何引用都将被泄漏。

int **PyTuple_Resize** (*PyObject* **p, *Py_ssize_t* newsize)

可以用于调整元组的大小。*newsize* 将是元组的新长度。因为元组被认为是不可变的，所以只有在对象仅有一个引用时，才应该使用它。如果元组已经被代码的其他部分所引用，请不要使用此项。元组在最后总是会增长或缩小。把它看作是销毁旧元组并创建一个新元组，只会更有效。成功时返回 0。客户端代码不应假定 **p* 的结果值将与调用此函数之前的值相同。如果替换了 **p* 引用的对象，则原始的 **p* 将被销毁。失败时，返回 “-1”，将 **p* 设置为 NULL，并引发 *MemoryError* 或者 *SystemError*。

8.3.5 结构序列对象

结构序列对象是等价于 `namedtuple()` 的 C 对象，即一个序列，其中的条目也可以通过属性访问。要创建结构序列，你首先必须创建特定的结构序列类型。

PyObject *PyStructSequence_NewType (PyStructSequence_Desc *desc)
Return value: New reference. Part of the Stable ABI. 根据 desc 中的数据创建一个新的结构序列类型，如下所述。可以使用 `PyStructSequence_New()` 创建结果类型的实例。

void PyStructSequence_InitType (PyObject *type, PyStructSequence_Desc *desc)
从 desc 就地初始化结构序列类型 type。

int PyStructSequence_InitType2 (PyObject *type, PyStructSequence_Desc *desc)
与 `PyStructSequence_InitType` 相同，但成功时返回 0，失败时返回 -1。

3.4 版新加入。

type PyStructSequence_Desc
Part of the Stable ABI (including all members). 包含要创建的结构序列类型的元信息。

域	C Type	含意
name	const char *	结构序列类型的名称
doc	const char *	指向要忽略类型的文档字符串或 NULL 的指针
fields	PyStructSequence_Field *	指向以 NULL 结尾的数组的指针，其字段名称为新类型
n_in_sequence	int	Python 侧可见的字段数（如果用作元组）

type PyStructSequence_Field
Part of the Stable ABI (including all members). Describes a field of a struct sequence. As a struct sequence is modeled as a tuple, all fields are typed as `PyObject*`. The index in the `fields` array of the `PyStructSequence_Desc` determines which field of the struct sequence is described.

域	C Type	含意
name	const char *	字段的名称或 NULL，若要结束命名字段的列表，请设置为 <code>PyStructSequence_UnnamedField</code> 以保留未命名字段
doc	const char *	要忽略的字段文档字符串或 NULL

const char *const PyStructSequence_UnnamedField
字段名的特殊值将保持未命名状态。

3.9 版更變: 这个类型已从 `char *` 更改。

PyObject *PyStructSequence_New (PyObject *type)
Return value: New reference. Part of the Stable ABI. 创建 type 的实例，该实例必须使用 `PyStructSequence_NewType()` 创建。

PyObject *PyStructSequence_GetItem (PyObject *p, Py_ssize_t pos)
Return value: Borrowed reference. Part of the Stable ABI. 返回 p 所指向的结构序列中，位于 pos 处的对象。不需要进行边界检查。

PyObject *PyStructSequence_GET_ITEM (PyObject *p, Py_ssize_t pos)
Return value: Borrowed reference. `PyStructSequence_GetItem()` 的宏版本。

void PyStructSequence_SetItem (PyObject *p, Py_ssize_t pos, PyObject *o)
Part of the Stable ABI. 将结构序列 p 的索引 pos 处的字段设置为值 o。与 `PyTuple_SET_ITEM()` 一样，它应该只用于填充全新的实例。

備註: 这个函数“窃取”了指向 o 的一个引用。

void **PyStructSequence_SET_ITEM** (*PyObject *p*, *Py_ssize_t *pos*, *PyObject *o*)
PyStructSequence_SetItem() 的宏版本。

備註：这个函数“窃取”了指向 *o* 的一个引用。

8.3.6 List（串列）物件

type PyObject

这个 C 类型 *PyObject* 的子类型代表一个 Python 列表对象。

PyTypeObject **PyList_Type**

Part of the Stable ABI. 这是个属于 *PyTypeObject* 的代表 Python 列表类型的实例。在 Python 层面和类型 `list` 是同一个对象。

int **PyList_Check** (*PyObject *p*)

如果 *p* 是一个 `list` 对象或者 `list` 类型的子类型的实例则返回真值。此函数总是会成功执行。

int **PyList_CheckExact** (*PyObject *p*)

如果 *p* 是一个 `list` 对象但不是 `list` 类型的子类型的实例则返回真值。此函数总是会成功执行。

*PyObject ****PyList_New** (*Py_ssize_t len*)

Return value: New reference. Part of the Stable ABI. 成功时返回一个长度为 *len* 的新列表，失败时返回 `NULL`。

備註：当 *len* 大于零时，被返回的列表对象项目被设成 `NULL`。因此你不能用类似 C 函数 *PySequence_SetItem()* 的抽象 API 或者用 C 函数 *PyList_SetItem()* 将所有项目设置成真实对象前对 Python 代码公开这个对象。

Py_ssize_t **PyList_Size** (*PyObject *list*)

Part of the Stable ABI. 返回 *list* 中列表对象的长度；这等于在列表对象调用 `len(list)`。

Py_ssize_t **PyList_GET_SIZE** (*PyObject *list*)

宏版本的 C 函数 *PyList_Size()*，没有错误检测。

*PyObject ****PyList_GetItem** (*PyObject *list*, *Py_ssize_t index*)

Return value: Borrowed reference. Part of the Stable ABI. 返回 *list* 所指向列表中 *index* 位置上的对象。位置值必须为非负数；不支持从列表末尾进行索引。如果 *index* 超出边界 (<0 or $\geq \text{len}(\text{list})$)，则返回 `NULL` 并设置 `IndexError` 异常。

*PyObject ****PyList_GET_ITEM** (*PyObject *list*, *Py_ssize_t i*)

Return value: Borrowed reference. 宏版本的 C 函数 *PyList_GetItem()*，没有错误检测。

int **PyList_SetItem** (*PyObject *list*, *Py_ssize_t index*, *PyObject *item*)

Part of the Stable ABI. 将列表中索引为 *index* 的项设为 *item*。成功时返回 0。如果 *index* 超出范围则返回 -1 并设定 `IndexError` 异常。

備註：此函数会“偷走”一个对 *item* 的引用并丢弃一个对列表中受影响位置上的已有条目的引用。

void **PyList_SET_ITEM** (*PyObject *list*, *Py_ssize_t i*, *PyObject *o*)

不带错误检测的宏版本 *PyList_SetItem()*。这通常只被用于新列表中之前没有内容的位置进行填充。

備註：该宏会“偷走”一个对 *item* 的引用，但与 *PyList_SetItem()* 不同的是它不会丢弃对任何被替换条目的引用；在 *list* 的 *i* 位置上的任何引用都将被泄露。

int PyList_Insert (*PyObject* *list, *Py_ssize_t* index, *PyObject* *item)
Part of the Stable ABI. 将条目 *item* 插入到列表 *list* 索引号 *index* 之前的位置。如果成功将返回 0；如果不成功则返回 -1 并设置一个异常。相当于 `list.insert(index, item)`。

int PyList_Append (*PyObject* *list, *PyObject* *item)
Part of the Stable ABI. 将对象 *item* 添加到列表 *list* 的末尾。如果成功将返回 0；如果不成功则返回 -1 并设置一个异常。相当于 `list.append(item)`。

***PyObject* *PyList_GetSlice** (*PyObject* *list, *Py_ssize_t* low, *Py_ssize_t* high)
Return value: New reference. Part of the Stable ABI. 返回一个对象列表，包含 *list* 当中位于 *low* 和 *high* 之间的对象。如果不成功则返回 NULL 并设置异常。相当于 `list[low:high]`。不支持从列表末尾进行索引。

int PyList_SetSlice (*PyObject* *list, *Py_ssize_t* low, *Py_ssize_t* high, *PyObject* *itemlist)
Part of the Stable ABI. 将 *list* 当中 *low* 与 *high* 之间的切片设为 *itemlist* 的内容。相当于 `list[low:high] = itemlist`。*itemlist* 可以为 NULL，表示赋值为一个空列表（删除切片）。成功时返回 0，失败时返回 -1。这里不支持从列表末尾进行索引。

int PyList_Sort (*PyObject* *list)
Part of the Stable ABI. 对 *list* 中的条目进行原地排序。成功时返回 0，失败时返回 -1。这等价于 `list.sort()`。

int PyList_Reverse (*PyObject* *list)
Part of the Stable ABI. 对 *list* 中的条目进行原地反转。成功时返回 0，失败时返回 -1。这等价于 `list.reverse()`。

***PyObject* *PyList_AsTuple** (*PyObject* *list)
Return value: New reference. Part of the Stable ABI. 返回一个新的元组对象，其中包含 *list* 的内容；等价于 `tuple(list)`。

8.4 容器物件

8.4.1 字典物件

type PyDictObject
PyObject 子型態代表一個 Python 字典物件。

***PyTypeObject* PyDict_Type**
Part of the Stable ABI. *PyTypeObject* 實例代表一個 Python 字典型態。此與 Python 層中的 `dict` 同一個物件。

int PyDict_Check (*PyObject* *p)
 若 *p* 是一個字典物件或字典的子型態實例則會回傳 `true`。此函式每次都會執行成功。

int PyDict_CheckExact (*PyObject* *p)
 若 *p* 是一個字典物件但不是一个字典子型態的實例，則回傳 `true`。此函式每次都會執行成功。

***PyObject* *PyDict_New** ()
Return value: New reference. Part of the Stable ABI. 返回一个新的空字典，失败时返回 NULL。

***PyObject* *PyDictProxy_New** (*PyObject* *mapping)
Return value: New reference. Part of the Stable ABI. 返回 `types.MappingProxyType` 对象，用于强制执行只读行为的映射。这通常用于创建视图以防止修改非动态类类型的字典。

void PyDict_Clear (*PyObject* *p)
Part of the Stable ABI. 清空现有字典的所有键值对。

int PyDict_Contains (*PyObject* *p, *PyObject* *key)
Part of the Stable ABI. 确定 *key* 是否包含在字典 *p* 中。如果 *key* 匹配上 *p* 的某一项，则返回 1，否则返回 0。返回 -1 表示出错。这等同于 Python 表达式 `key in p`。

***PyObject* *PyDict_Copy** (*PyObject* *p)
Return value: New reference. Part of the Stable ABI. 返回与 *p* 包含相同键值对的新字典。

int PyDict_SetItem (*PyObject* *p, *PyObject* *key, *PyObject* *val)

Part of the [Stable ABI](#). 使用 key 作为键将 val 插入字典 p。key 必须为 *hashable*；如果不是，则将引发 *TypeError*。成功时返回 0，失败时返回 -1。此函数 不会附带对 val 的引用。

int PyDict_SetItemString (*PyObject* *p, **const** char *key, *PyObject* *val)

Part of the [Stable ABI](#). Insert val into the dictionary p using key as a key. key should be a **const** char*. The key object is created using `PyUnicode_FromString(key)`. Return 0 on success or -1 on failure. This function *does not* steal a reference to val.

int PyDict_DelItem (*PyObject* *p, *PyObject* *key)

Part of the [Stable ABI](#). Remove the entry in dictionary p with key key. key must be *hashable*; if it isn't, *TypeError* is raised. If key is not in the dictionary, *KeyError* is raised. Return 0 on success or -1 on failure.

int PyDict_DelItemString (*PyObject* *p, **const** char *key)

Part of the [Stable ABI](#). 移除字典 p 中由字符串 key 指定的键的条目。如果字典中没有 key，则会引发 *KeyError*。成功时返回 0，失败时返回 -1。

PyObject ***PyDict_GetItem** (*PyObject* *p, *PyObject* *key)

Return value: Borrowed reference. Part of the [Stable ABI](#). 从字典 p 中返回以 key 为键的对象。如果键名 key 不存在但 没有设置一个异常则返回 NULL。

需要注意的是，调用 `__hash__()` 和 `__eq__()` 方法产生的异常不会被抛出。改用 `PyDict_GetItemWithError()` 获得错误报告。

3.10 版更變: 在不保持 *GIL* 的情况下调用此 API 曾因历史原因而被允许。现在已不再被允许。

PyObject ***PyDict_GetItemWithError** (*PyObject* *p, *PyObject* *key)

Return value: Borrowed reference. Part of the [Stable ABI](#). `PyDict_GetItem()` 的变种，它不会屏蔽异常。当异常发生时将返回 NULL 并且设置一个异常。如果键不存在则返回 NULL 并且不会设置一个异常。

PyObject ***PyDict_GetItemString** (*PyObject* *p, **const** char *key)

Return value: Borrowed reference. Part of the [Stable ABI](#). This is the same as `PyDict_GetItem()`, but key is specified as a **const** char*, rather than a *PyObject**.

需要注意的是，调用 `__hash__()`、`__eq__()` 方法和创建一个临时的字符串对象时产生的异常不会被抛出。改用 `PyDict_GetItemWithError()` 获得错误报告。

PyObject ***PyDict_SetDefault** (*PyObject* *p, *PyObject* *key, *PyObject* *defaultobj)

Return value: Borrowed reference. 这跟 Python 层面的 `dict.setdefault()` 一样。如果键 key 存在，它返回在字典 p 里面对应的值。如果键不存在，它会和值 defaultobj 一起插入并返回 defaultobj。这个函数只计算 key 的哈希函数一次，而不是在查找和插入时分别计算它。

3.4 版新加入。

PyObject ***PyDict_Items** (*PyObject* *p)

Return value: New reference. Part of the [Stable ABI](#). 返回一个包含字典中所有键值项的 *PyListObject*。

PyObject ***PyDict_Keys** (*PyObject* *p)

Return value: New reference. Part of the [Stable ABI](#). 返回一个包含字典中所有键 (keys) 的 *PyListObject*。

PyObject ***PyDict_Values** (*PyObject* *p)

Return value: New reference. Part of the [Stable ABI](#). 返回一个包含字典中所有值 (values) 的 *PyListObject*。

Py_ssize_t **PyDict_Size** (*PyObject* *p)

Part of the [Stable ABI](#). 返回字典中项目数，等价于对字典 p 使用 `len(p)`。

int PyDict_Next (*PyObject* *p, *Py_ssize_t* *ppos, *PyObject* **pkey, *PyObject* **pvalue)

Part of the [Stable ABI](#). Iterate over all key-value pairs in the dictionary p. The *Py_ssize_t* referred to by ppos must be initialized to 0 prior to the first call to this function to start the iteration; the function returns true for each pair in the dictionary, and false once all pairs have been reported. The parameters pkey and pvalue should either point to *PyObject** variables that will be filled in with each key and value, respectively, or may be NULL. Any references returned through them are borrowed. ppos should not be altered during iteration. Its

value represents offsets within the internal dictionary structure, and since the structure is sparse, the offsets are not consecutive.

舉例來：

```
PyObject *key, *value;
Py_ssize_t pos = 0;

while (PyDict_Next(self->dict, &pos, &key, &value)) {
    /* do something interesting with the values... */
    ...
}
```

字典 *p* 不应该在遍历期间发生改变。在遍历字典时，改变键中的值是安全的，但仅限于键的集合不发生改变。例如：

```
PyObject *key, *value;
Py_ssize_t pos = 0;

while (PyDict_Next(self->dict, &pos, &key, &value)) {
    long i = PyLong_AsLong(value);
    if (i == -1 && PyErr_Occurred()) {
        return -1;
    }
    PyObject *o = PyLong_FromLong(i + 1);
    if (o == NULL)
        return -1;
    if (PyDict_SetItem(self->dict, key, o) < 0) {
        Py_DECREF(o);
        return -1;
    }
    Py_DECREF(o);
}
```

int PyDict_Merge (*PyObject* **a*, *PyObject* **b*, int *override*)

Part of the Stable ABI. 对映射对象 *b* 进行迭代，将键值对添加到字典 *a*。*b* 可以是一个字典，或任何支持 *PyMapping_Keys()* 和 *PyObject_GetItem()* 的对象。如果 *override* 为真值，则如果在 *b* 中找到相同的键则 *a* 中已存在的相应键值对将被替换，否则如果在 *a* 中没有相同的键则只是添加键值对。当成功时返回 0 或者当引发异常时返回 -1。

int PyDict_Update (*PyObject* **a*, *PyObject* **b*)

Part of the Stable ABI. 这与 C 中的 *PyDict_Merge(a, b, 1)* 一样，也类似于 Python 中的 *a.update(b)*，差别在于 *PyDict_Update()* 在第二个参数没有“keys”属性时不会回退到迭代键值对的序列。当成功时返回 0 或者当引发异常时返回 -1。

int PyDict_MergeFromSeq2 (*PyObject* **a*, *PyObject* **seq2*, int *override*)

Part of the Stable ABI. 将 *seq2* 中的键值对更新或合并到字典 *a*。*seq2* 必须为产生长度为 2 的用作键值对的元素的可迭代对象。当存在重复的键时，如果 *override* 真值则最后出现的键胜出。当成功时返回 0 或者当引发异常时返回 -1。等价的 Python 代码（返回值除外）：

```
def PyDict_MergeFromSeq2(a, seq2, override):
    for key, value in seq2:
        if override or key not in a:
            a[key] = value
```

8.4.2 集合对象

这一节详细介绍了针对 `set` 和 `frozenset` 对象的公共 API。任何未在下面列出的功能最好是使用抽象对象协议 (包括 `PyObject_CallMethod()`, `PyObject_RichCompareBool()`, `PyObject_Hash()`, `PyObject_Repr()`, `PyObject_IsTrue()`, `PyObject_Print()` 以及 `PyObject_GetIter()`) 或者抽象数字协议 (包括 `PyNumber_And()`, `PyNumber_Subtract()`, `PyNumber_Or()`, `PyNumber_Xor()`, `PyNumber_InPlaceAnd()`, `PyNumber_InPlaceSubtract()`, `PyNumber_InPlaceOr()` 以及 `PyNumber_InPlaceXor()`)。

type `PySetObject`

这个 `PyObject` 的子类型被用来保存 `set` 和 `frozenset` 对象的内部数据。它类似于 `PyDictObject` 的地方在于对小尺寸集合来说它是固定大小的 (很像元组的存储方式), 而对于中等和大尺寸集合来说它将指向单独的可变大小的内存块 (很像列表的存储方式)。此结构体的字段不应被视为公有并且可能发生改变。所有访问都应当通过已写入文档的 API 来进行而不可通过直接操纵结构体中的值。

`PyTypeObject` `PySet_Type`

Part of the Stable ABI. 这是一个 `PyTypeObject` 实例, 表示 Python `set` 类型。

`PyTypeObject` `PyFrozenSet_Type`

Part of the Stable ABI. 这是一个 `PyTypeObject` 实例, 表示 Python `frozenset` 类型。

下列类型检查宏适用于指向任意 Python 对象的指针。类似地, 这些构造函数也适用于任意可迭代的 Python 对象。

`int` `PySet_Check` (`PyObject *p`)

如果 `p` 是一个 `set` 对象或者是其子类型的实例则返回真值。此函数总是会成功执行。

`int` `PyFrozenSet_Check` (`PyObject *p`)

如果 `p` 是一个 `frozenset` 对象或者是其子类型的实例则返回真值。此函数总是会成功执行。

`int` `PyAnySet_Check` (`PyObject *p`)

如果 `p` 是一个 `set` 对象、`frozenset` 对象或者是其子类型的实例则返回真值。此函数总是会成功执行。

`int` `PySet_CheckExact` (`PyObject *p`)

如果 `p` 是一个 `set` 对象但不是其子类型的实例则返回真值。此函数总是会成功执行。

3.10 版新加入。

`int` `PyAnySet_CheckExact` (`PyObject *p`)

如果 `p` 是一个 `set` 或 `frozenset` 对象但不是其子类型的实例则返回真值。此函数总是会成功执行。

`int` `PyFrozenSet_CheckExact` (`PyObject *p`)

如果 `p` 是一个 `frozenset` 对象但不是其子类型的实例则返回真值。此函数总是会成功执行。

`PyObject *` `PySet_New` (`PyObject *iterable`)

Return value: New reference. *Part of the Stable ABI.* 返回一个新的 `set`, 其中包含 `iterable` 所返回的对象。`iterable` 可以为 `NULL` 表示创建一个新的空集合。成功时返回新的集合, 失败时返回 `NULL`。如果 `iterable` 实际上不是可迭代对象则引发 `TypeError`。该构造器也适用于拷贝集合 (`c=set(s)`)。

`PyObject *` `PyFrozenSet_New` (`PyObject *iterable`)

Return value: New reference. *Part of the Stable ABI.* 返回一个新的 `frozenset`, 其中包含 `iterable` 所返回的对象。`iterable` 可以为 `NULL` 表示创建一个新的空冻结集合。成功时返回新的冻结集合, 失败时返回 `NULL`。如果 `iterable` 实际上不是可迭代对象则引发 `TypeError`。

下列函数和宏适用于 `set` 或 `frozenset` 的实例或是其子类型的实例。

`Py_ssize_t` `PySet_Size` (`PyObject *anyset`)

Part of the Stable ABI. 返回 `set` 或 `frozenset` 对象的长度。等价于 `len(anyset)`。如果 `anyset` 不是 `set`, `frozenset` 或其子类型的实例则会引发 `PyExc_SystemError`。

`Py_ssize_t` `PySet_GET_SIZE` (`PyObject *anyset`)

宏版本的 `PySet_Size()`, 不带错误检测。

int PySet_Contains (*PyObject* *anyset, *PyObject* *key)

Part of the Stable ABI. 如果找到返回 1，如果未找到返回 0，如果遇到错误则返回 -1。不同于 Python `__contains__()` 方法，此函数不会自动将不可哈希的集合转换为临时的冻结集合。如果 *key* 为不可哈希对象则会引发 `TypeError`。如果 *anyset* 不是 `set`, `frozenset` 或其子类型的实例则会引发 `PyExc_SystemError`。

int PySet_Add (*PyObject* *set, *PyObject* *key)

Part of the Stable ABI. 添加 *key* 到一个 `set` 实例。也可用于 `frozenset` 实例 (与 `PyTuple_SetItem()` 的类似之处是它也可被用来为全新的冻结集合在公开给其他代码之前填充全新的值)。成功时返回 0 而失败时返回 -1。如果 *key* 为不可哈希对象则会引发 `TypeError`。如果没有增长空间则会引发 `MemoryError`。如果 *set* 不是 `set` 或其子类型的实例则会引发 `SystemError`。

下列函数适用于 `set` 或其子类型的实例，但不可用于 `frozenset` 或其子类型的实例。

int PySet_Discard (*PyObject* *set, *PyObject* *key)

Part of the Stable ABI. 如果找到并移除返回 1，如果未找到（无操作）返回 0，如果遇到错误则返回 -1。对于不存在的键不会引发 `KeyError`。如果 *key* 为不可哈希对象则会引发 `TypeError`。不同于 Python `discard()` 方法，此函数不会自动将不可哈希的集合转换为临时的冻结集合。如果 *set* 不是 `set` 或其子类型的实例则会引发 `PyExc_SystemError`。

PyObject ***PySet_Pop** (*PyObject* *set)

Return value: New reference. Part of the Stable ABI. 返回 *set* 中任意对象的新引用，并从 *set* 中移除该对象。失败时返回 `NULL`。如果集合为空则会引发 `KeyError`。如果 *set* 不是 `set` 或其子类型的实例则会引发 `SystemError`。

int PySet_Clear (*PyObject* *set)

Part of the Stable ABI. 清空现有字典的所有键值对。

8.5 函式物件

8.5.1 函式 (Function) 物件

這有一些少數 Python 函數的於具體說明。

type PyFunctionObject

用于函数的 C 结构体。

PyObject **PyFunction_Type**

这是一个 *PyObject* 实例并表示 Python 函数类型。它作为 `types.FunctionType` 向 Python 程序员公开。

int PyFunction_Check (*PyObject* *o)

如果 *o* 是一个函数对象 (类型为 *PyFunction_Type*) 则返回真值。形参必须不为 `NULL`。此函数总是会成功执行。

PyObject ***PyFunction_New** (*PyObject* *code, *PyObject* *globals)

Return value: New reference. 返回与代码对象 *code* 关联的新函数对象。*globals* 必须是一个字典，该函数可以访问全局变量。

从代码对象中提取函数的文档字符串和名称。`__module__` 会从 *globals* 中提取。参数 `defaults`, `annotations` 和 `closure` 设为 `NULL`。`__qualname__` 设为与函数名称相同的值。

PyObject ***PyFunction_NewWithQualName** (*PyObject* *code, *PyObject* *globals, *PyObject* *qualname)

Return value: New reference. 类似 *PyFunction_New()*，但还允许设置函数对象的 `__qualname__` 属性。*qualname* 应当是 `unicode` 对象或 `NULL`；如果是 `NULL` 则 `__qualname__` 属性设为与其 `__name__` 属性相同的值。

3.3 版新加入。

PyObject ***PyFunction_GetCode** (*PyObject* *op)

Return value: Borrowed reference. 回傳與程式碼物件相關的函數物件 *op*。

PyObject *PyFunction_GetGlobals (*PyObject* *op)

Return value: Borrowed reference. 回傳與全域函數字典相關的函數物件 *op*。

PyObject *PyFunction_GetModule (*PyObject* *op)

Return value: Borrowed reference. 向函數對象 *op* 的 `__module__` 屬性返回一個 *borrowed reference*。該值可以為 NULL。

這通常為一個包含模塊名稱的字符串，但可以通过 Python 代碼設為任何其他對象。

PyObject *PyFunction_GetDefaults (*PyObject* *op)

Return value: Borrowed reference. 返回函數對象 *op* 的參數默認值。這可以是一個參數元組或 NULL。

int PyFunction_SetDefaults (*PyObject* *op, *PyObject* *defaults)

為函數對象 *op* 設置參數默認值。defaults 必須為 Py_None 或一個元組。

失敗時引發 SystemError 異常並返回 -1。

PyObject *PyFunction_GetClosure (*PyObject* *op)

Return value: Borrowed reference. 返回關聯到函數對象 *op* 的閉包。這可以是 NULL 或 cell 對象的元組。

int PyFunction_SetClosure (*PyObject* *op, *PyObject* *closure)

設置關聯到函數對象 *op* 的閉包。closure 必須為 Py_None 或 cell 對象的元組。

失敗時引發 SystemError 異常並返回 -1。

PyObject *PyFunction_GetAnnotations (*PyObject* *op)

Return value: Borrowed reference. 返回函數對象 *op* 的標注。這可以是一個可變字典或 NULL。

int PyFunction_SetAnnotations (*PyObject* *op, *PyObject* *annotations)

設置函數對象 *op* 的標注。annotations 必須為一個字典或 Py_None。

失敗時引發 SystemError 異常並返回 -1。

8.5.2 實例方法物件 (Instance Method Objects)

實例方法是 *PyCFunction* 的包裝器 (wrapper)，也是將 *PyCFunction* 綁 (bind) 到類物件的一種新方式。它替代了原先對 *PyMethod_New*(func, NULL, class) 的呼叫。

PyTypeObject PyInstanceMethod_Type

PyTypeObject 的實例代表 Python 實例方法型。它不會公開 (expose) 給 Python 程式。

int PyInstanceMethod_Check (*PyObject* *o)

如果 *o* 是一個實例方法物件 (型 *PyInstanceMethod_Type*) 則回傳 true。參數必須不為 NULL。此函式總是會成功執行。

PyObject *PyInstanceMethod_New (*PyObject* *func)

Return value: New reference. 回傳一個新的實例方法物件，*func* 為任意可呼叫物件，在實例方法被呼叫時 *func* 函式也會被呼叫。

PyObject *PyInstanceMethod_Function (*PyObject* *im)

Return value: Borrowed reference. 回傳關聯到實例方法 *im* 的函式物件。

PyObject *PyInstanceMethod_GET_FUNCTION (*PyObject* *im)

Return value: Borrowed reference. 巨集 (macro) 版本的 *PyInstanceMethod_Function()*，忽略了錯誤檢查。

8.5.3 方法物件 (Method Objects)

方法物件 (bound function) 物件。方法總是會被綁到一個使用者定義類的實例。未綁方法 (綁到一個類的方法) 已不可用。

PyObject **PyMethod_Type**

這個 *PyMethod_Type* 實例代表 Python 方法型。它作 `types.MethodType` 公開給 Python 程式。

int PyMethod_Check (*PyObject* *o)

如果 *o* 是一個方法物件 (型 `PyMethod_Type`) 則回傳 `true`。參數必須不為 `NULL`。此函式總是會成功執行。

PyObject ***PyMethod_New** (*PyObject* *func, *PyObject* *self)

Return value: New reference. 回傳一個新的方法物件, *func* 應為任意可呼叫物件, *self* 為該方法應綁的實例。在方法被呼叫時, *func* 函式也會被呼叫。*self* 必須不為 `NULL`。

PyObject ***PyMethod_Function** (*PyObject* *meth)

Return value: Borrowed reference. 回傳關聯到方法 *meth* 的函式物件。

PyObject ***PyMethod_GET_FUNCTION** (*PyObject* *meth)

Return value: Borrowed reference. 巨集版本的 `PyMethod_Function()`, 忽略了錯誤檢查。

PyObject ***PyMethod_Self** (*PyObject* *meth)

Return value: Borrowed reference. 回傳關聯到方法 *meth* 的實例。

PyObject ***PyMethod_GET_SELF** (*PyObject* *meth)

Return value: Borrowed reference. 巨集版本的 `PyMethod_Self()`, 忽略了錯誤檢查。

8.5.4 Cell 物件

“Cell” 對象用於實現由多個作用域引用的變量。對於每個這樣的變量，一個 “Cell” 對象為了存儲該值而被創建；引用該值的每個堆棧框架的局部變量包含同樣使用該變量的對外部作用域的 “Cell” 引用。訪問該值時，將使用 “Cell” 中包含的值而不是單元格對象本身。這種對 “Cell” 對象的非關聯化的引用需要支持生成的字節碼；訪問時不會自動非關聯化這些內容。“Cell” 對象在其他地方可能不太有用。

type PyCellObject

C 結構的 cell 物件

PyObject **PyCell_Type**

對應 cell 物件的物件型。

int PyCell_Check (ob)

如果 *ob* 是一個 cell 對象則返回真值；*ob* 必須不為 `NULL`。此函數總是會成功執行。

PyObject ***PyCell_New** (*PyObject* *ob)

Return value: New reference. 創建並返回一個包含值 *ob* 的新 cell 對象。形參可以為 `NULL`。

PyObject ***PyCell_Get** (*PyObject* *cell)

Return value: New reference. 回傳 cell 內容中的 *cell*。

PyObject ***PyCell_GET** (*PyObject* *cell)

Return value: Borrowed reference. 返回 cell 對象 *cell* 的內容，但是不檢測 *cell* 是否非 `NULL` 並且為一個 cell 對象。

int PyCell_Set (*PyObject* *cell, *PyObject* *value)

將 cell 對象 *cell* 的內容設為 *value*。這將釋放任何對 cell 對象當前內容的引用。*value* 可以為 `NULL`。*cell* 必須為非 `NULL`；如果它不是一個 cell 對象則將返回 `-1`。如果設置成功則將返回 `0`。

void PyCell_SET (*PyObject* *cell, *PyObject* *value)

將 cell 對象 *cell* 的值設為 *value*。不會調整引用計數，並且不會進行檢測以保證安全；*cell* 必須為非 `NULL` 並且為一個 cell 對象。

8.5.5 代码对象

代码对象是 CPython 实现的低级细节。每个代表一块尚未绑定到函数中的可执行代码。

type PyCodeObject

用于描述代码对象的对象的 C 结构。此类型字段可随时更改。

PyTypeObject **PyCode_Type**

这是一个 *PyTypeObject* 实例，其表示 Python 的 code 类型。

int **PyCode_Check** (*PyObject* *co)

如果 co 是一个 code 对象则返回真值。此函数总是会成功执行。

int **PyCode_GetNumFree** (*PyCodeObject* *co)

返回 co 中的自由变量数。

PyCodeObject ***PyCode_New** (int argcount, int kwnonlyargcount, int nlocals, int stacksize, int flags, *PyObject* *code, *PyObject* *consts, *PyObject* *names, *PyObject* *varnames, *PyObject* *freevars, *PyObject* *cellvars, *PyObject* *filename, *PyObject* *name, int firstlineno, *PyObject* *notab)

Return value: New reference. 返回一个新的代码对象。如果你需要一个虚拟代码对象来创建一个代码帧，请使用 *PyCode_NewEmpty*()。调用 *PyCode_New*() 直接可以绑定到准确的 Python 版本，因为字节码的定义经常变化。

PyCodeObject ***PyCode_NewWithPosOnlyArgs** (int argcount, int posonlyargcount, int kwnonlyargcount, int nlocals, int stacksize, int flags, *PyObject* *code, *PyObject* *consts, *PyObject* *names, *PyObject* *varnames, *PyObject* *freevars, *PyObject* *cellvars, *PyObject* *filename, *PyObject* *name, int firstlineno, *PyObject* *notab)

Return value: New reference. 类似于 *PyCode_New*()，但带有一个额外的“posonlyargcount”用于仅限位置参数。

3.8 版新加入。

PyCodeObject ***PyCode_NewEmpty** (const char *filename, const char *funcname, int firstlineno)

Return value: New reference. 返回具有指定文件名、函数名和第一行号的新空代码对象。对于 *exec*() 或 *eval*() 生成的代码对象是非法的。

int **PyCode_Addr2Line** (*PyCodeObject* *co, int byte_offset)

返回在 byte_offset 位置或之前以及之后发生的指令的行号。如果你只需要一个帧的行号，请改用 *PyFrame_GetLineNumber*()。

要高效地迭代一个代码对象中的行号，请使用 [PEP 626](#) 描述的 API。

8.6 其他物件

8.6.1 檔案 (File) 物件

These APIs are a minimal emulation of the Python 2 C API for built-in file objects, which used to rely on the buffered I/O (FILE*) support from the C standard library. In Python 3, files and streams use the new *io* module, which defines several layers over the low-level unbuffered I/O of the operating system. The functions described below are convenience C wrappers over these new APIs, and meant mostly for internal error reporting in the interpreter; third-party code is advised to access the *io* APIs instead.

PyObject ***PyFile_FromFd** (int fd, const char *name, const char *mode, int buffering, const char *encoding, const char *errors, const char *newline, int closefd)

Return value: New reference. Part of the [Stable ABI](#). 根据已打开文件 fd 的文件描述符创建一个 Python 文件对象。参数 name, encoding, errors 和 newline 可以为 NULL 表示使用默认值；buffering 可以为 -1 表示使用默认值。name 会被忽略仅保留用于向下兼容。失败时返回 NULL。有关参数的更全面描述，请参阅 *io.open*() 函数的文档。

警告： 由于 Python 流具有自己的缓冲层，因此将它们与 OS 级文件描述符混合会产生各种问题（例如数据的意外排序）。

3.2 版更變：忽略 *name* 屬性。

int PyObject_AsFileDescriptor (*PyObject* **p*)

Part of the Stable ABI. Return the file descriptor associated with *p* as an `int`. If the object is an integer, its value is returned. If not, the object's `fileno()` method is called if it exists; the method must return an integer, which is returned as the file descriptor value. Sets an exception and returns `-1` on failure.

PyObject *PyFile_GetLine (*PyObject* **p*, `int` *n*)

Return value: New reference. Part of the Stable ABI. 等价于 `p.readline([n])`，这个函数从对象 *p* 中读取一行。*p* 可以是文件对象或具有 `readline()` 方法的任何对象。如果 *n* 是 0，则无论该行的长度如何，都会读取一行。如果 *n* 大于“0”，则从文件中读取不超过 *n* 个字节；可以返回行的一部分。在这两种情况下，如果立即到达文件末尾，则返回空字符串。但是，如果 *n* 小于 0，则无论长度如何都会读取一行，但是如果立即到达文件末尾，则引发 `EOFError`。

int PyFile_SetOpenCodeHook (*Py_OpenCodeHookFunction* *handler*)

重载 `io.open_code()` 的正常行为，将其形参通过所提供的处理程序来传递。

The handler is a function of type `PyObject *(*)(PyObject *path, void *userData, where path is guaranteed to be PyUnicodeObject`.

userData 指针会被传入钩子函数。因于钩子函数可能由不同的运行时调用，该指针不应直接指向 Python 状态。

鉴于这个钩子专门在导入期间使用的，请避免在新模块执行期间进行导入操作，除非已知它们为冻结状态或者是在 `sys.modules` 中可用。

一旦钩子被设定，它就不能被移除或替换，之后对 `PyFile_SetOpenCodeHook()` 的调用也将失败，如果解释器已经被初始化，函数将返回 `-1` 并设置一个异常。

此函数可以安全地在 `Py_Initialize()` 之前调用。

引发一个 审计事件 `setopencodehook`，不附带任何参数。

3.8 版新加入。

int PyFile_WriteObject (*PyObject* **obj*, *PyObject* **p*, `int` *flags*)

Part of the Stable ABI. 将对象 *obj* 写入文件对象 *p*。*flags* 唯一支持的标志是 `Py_PRINT_RAW`；如果给定，则写入对象的 `str()` 而不是 `repr()`。成功时返回 0，失败时返回 `-1`。将设置适当的例外。

int PyFile_WriteString (`const char` **s*, *PyObject* **p*)

Part of the Stable ABI. 寫入字串 *s* 到檔案物件 *p*。當成功時回傳 0，而當失敗時回傳 `-1`，`ⓧ` 會設定合適的例外狀`ⓧ`。

8.6.2 模組物件模組

PyTypeObject PyModule_Type

Part of the Stable ABI. 这个 C 类型实例 `PyTypeObject` 用来表示 Python 中的模块类型。在 Python 程序中该实例被暴露为“`types.ModuleType`”。

int PyModule_Check (*PyObject* **p*)

当 *p* 为模块类型的对象，或是模块子类型的对象时返回真值。该函数永远有返回值。

int PyModule_CheckExact (*PyObject* **p*)

当 *p* 为模块类型的对象且不是 `PyModule_Type` 的子类型的对象时返回真值。该函数永远有返回值。

PyObject *PyModule_NewObject (*PyObject* **name*)

Return value: New reference. Part of the Stable ABI since version 3.7. 返回新的模块对象，其属性 `__name__` 为 *name*。模块的如下属性 `__name__`，`__doc__`，`__package__`，and `__loader__` 都会被自动填充。（所有属性除了 `__name__` 都被设为“None”）。调用时应当提供 `__file__` 属性。

3.3 版新加入。

3.4 版更變: `__package__` 和 `__loader__` 被設 `None`。

PyObject *PyModule_New (const char *name)

Return value: New reference. Part of the [Stable ABI](#). 这类似于 `PyModule_NewObject()`, 但其名称为 UTF-8 编码的字符串而不是 Unicode 对象。

PyObject *PyModule_GetDict (PyObject *module)

Return value: Borrowed reference. Part of the [Stable ABI](#). 返回实现 `module` 的命名空间的字典对象; 此对象与模块对象的 `__dict__` 属性相同。如果 `module` 不是一个模块对象 (或模块对象的子类型), 则会引发 `SystemError` 并返回 `NULL`。

It is recommended extensions use other `PyModule_*` and `PyObject_*` functions rather than directly manipulate a module's `__dict__`.

PyObject *PyModule_GetNameObject (PyObject *module)

Return value: New reference. Part of the [Stable ABI](#) since version 3.7. 返回 `module` 的 `__name__` 值。如果模块未提供该值, 或者如果它不是一个字符串, 则会引发 `SystemError` 并返回 `NULL`。

3.3 版新加入。

const char *PyModule_GetName (PyObject *module)

Part of the [Stable ABI](#). 类似于 `PyModule_GetNameObject()` 但返回 `'utf-8'` 编码的名称。

void *PyModule_GetState (PyObject *module)

Part of the [Stable ABI](#). 返回模块的“状态”, 也就是说, 返回指向在模块创建时分配的内存块的指针, 或者 `NULL`。参见 `PyModuleDef.m_size`。

PyModuleDef *PyModule_GetDef (PyObject *module)

Part of the [Stable ABI](#). 返回指向模块创建所使用的 `PyModuleDef` 结构体的指针, 或者如果模块不是使用结构体定义创建的则返回 `NULL`。

PyObject *PyModule_GetFilenameObject (PyObject *module)

Return value: New reference. Part of the [Stable ABI](#). 返回使用 `module` 的 `__file__` 属性所加载的模块的文件名。如果属性未定义, 或者如果它不是一个 Unicode 字符串, 则会引发 `SystemError` 并返回 `NULL`; 在其他情况下将返回一个指向 Unicode 对象的引用。

3.2 版新加入。

const char *PyModule_GetFilename (PyObject *module)

Part of the [Stable ABI](#). Similar to `PyModule_GetFilenameObject()` but return the filename encoded to `'utf-8'`.

3.2 版後已 `PyModule_GetFilename()` raises `UnicodeEncodeError` on unencodable filenames, use `PyModule_GetFilenameObject()` instead.

初始化 C 模块

Modules objects are usually created from extension modules (shared libraries which export an initialization function), or compiled-in modules (where the initialization function is added using `PyImport_AppendInittab()`). See building or extending-with-embedding for details.

The initialization function can either pass a module definition instance to `PyModule_Create()`, and return the resulting module object, or request “multi-phase initialization” by returning the definition struct itself.

type PyModuleDef

Part of the [Stable ABI](#) (including all members). The module definition struct, which holds all information needed to create a module object. There is usually only one statically initialized variable of this type for each module.

PyModuleDef_Base m_base

Always initialize this member to `PyModuleDef_HEAD_INIT`.

const char *m_name

新模块的名称。

const char *m_doc

Docstring for the module; usually a docstring variable created with *PyDoc_STRVAR* is used.

Py_ssize_t m_size

Module state may be kept in a per-module memory area that can be retrieved with *PyModule_GetState()*, rather than in static globals. This makes modules safe for use in multiple sub-interpreters.

This memory area is allocated based on *m_size* on module creation, and freed when the module object is deallocated, after the *m_free* function has been called, if present.

Setting *m_size* to -1 means that the module does not support sub-interpreters, because it has global state.

Setting it to a non-negative value means that the module can be re-initialized and specifies the additional amount of memory it requires for its state. Non-negative *m_size* is required for multi-phase initialization.

更多詳情請見 [PEP 3121](#)。

PyMethodDef *m_methods

A pointer to a table of module-level functions, described by *PyMethodDef* values. Can be NULL if no functions are present.

PyModuleDef_Slot *m_slots

An array of slot definitions for multi-phase initialization, terminated by a {0, NULL} entry. When using single-phase initialization, *m_slots* must be NULL.

3.5 版更變: Prior to version 3.5, this member was always set to NULL, and was defined as:

inquiry m_reload

traverseproc m_traverse

A traversal function to call during GC traversal of the module object, or NULL if not needed.

This function is not called if the module state was requested but is not allocated yet. This is the case immediately after the module is created and before the module is executed (*Py_mod_exec* function). More precisely, this function is not called if *m_size* is greater than 0 and the module state (as returned by *PyModule_GetState()*) is NULL.

3.9 版更變: No longer called before the module state is allocated.

inquiry m_clear

A clear function to call during GC clearing of the module object, or NULL if not needed.

This function is not called if the module state was requested but is not allocated yet. This is the case immediately after the module is created and before the module is executed (*Py_mod_exec* function). More precisely, this function is not called if *m_size* is greater than 0 and the module state (as returned by *PyModule_GetState()*) is NULL.

Like *PyTypeObject.tp_clear*, this function is not *always* called before a module is deallocated. For example, when reference counting is enough to determine that an object is no longer used, the cyclic garbage collector is not involved and *m_free* is called directly.

3.9 版更變: No longer called before the module state is allocated.

freefunc m_free

A function to call during deallocation of the module object, or NULL if not needed.

This function is not called if the module state was requested but is not allocated yet. This is the case immediately after the module is created and before the module is executed (*Py_mod_exec* function). More precisely, this function is not called if *m_size* is greater than 0 and the module state (as returned by *PyModule_GetState()*) is NULL.

3.9 版更變: No longer called before the module state is allocated.

Single-phase initialization

The module initialization function may create and return the module object directly. This is referred to as “single-phase initialization”, and uses one of the following two module creation functions:

*PyObject** **PyModule_Create** (*PyModuleDef* *def)

Return value: New reference. Create a new module object, given the definition in *def*. This behaves like *PyModule_Create2()* with *module_api_version* set to *PYTHON_API_VERSION*.

*PyObject** **PyModule_Create2** (*PyModuleDef* *def, int *module_api_version*)

Return value: New reference. Part of the [Stable ABI](#). Create a new module object, given the definition in *def*, assuming the API version *module_api_version*. If that version does not match the version of the running interpreter, a *RuntimeWarning* is emitted.

備 註: Most uses of this function should be using *PyModule_Create()* instead; only use this if you are sure you need it.

Before it is returned from in the initialization function, the resulting module object is typically populated using functions like *PyModule_AddObjectRef()*.

Multi-phase initialization

An alternate way to specify extensions is to request “multi-phase initialization”. Extension modules created this way behave more like Python modules: the initialization is split between the *creation phase*, when the module object is created, and the *execution phase*, when it is populated. The distinction is similar to the *__new__()* and *__init__()* methods of classes.

Unlike modules created using single-phase initialization, these modules are not singletons: if the *sys.modules* entry is removed and the module is re-imported, a new module object is created, and the old module is subject to normal garbage collection -- as with Python modules. By default, multiple modules created from the same definition should be independent: changes to one should not affect the others. This means that all state should be specific to the module object (using e.g. using *PyModule_GetState()*), or its contents (such as the module’s *__dict__* or individual classes created with *PyType_FromSpec()*).

All modules created using multi-phase initialization are expected to support *sub-interpreters*. Making sure multiple modules are independent is typically enough to achieve this.

To request multi-phase initialization, the initialization function (*PyInit_modulename*) returns a *PyModuleDef* instance with non-empty *m_slots*. Before it is returned, the *PyModuleDef* instance must be initialized with the following function:

*PyObject** **PyModuleDef_Init** (*PyModuleDef* *def)

Return value: Borrowed reference. Part of the [Stable ABI](#) since version 3.5. Ensures a module definition is a properly initialized Python object that correctly reports its type and reference count.

Returns *def* cast to *PyObject**, or *NULL* if an error occurred.

3.5 版新加入.

The *m_slots* member of the module definition must point to an array of *PyModuleDef_Slot* structures:

type *PyModuleDef_Slot*

int **slot**

A slot ID, chosen from the available values explained below.

void ***value**

Value of the slot, whose meaning depends on the slot ID.

3.5 版新加入.

The `m_slots` array must be terminated by a slot with id 0.

The available slot types are:

Py_mod_create

Specifies a function that is called to create the module object itself. The *value* pointer of this slot must point to a function of the signature:

PyObject ***create_module** (*PyObject* **spec*, *PyModuleDef* **def*)

The function receives a `ModuleSpec` instance, as defined in [PEP 451](#), and the module definition. It should return a new module object, or set an error and return `NULL`.

This function should be kept minimal. In particular, it should not call arbitrary Python code, as trying to import the same module again may result in an infinite loop.

Multiple `Py_mod_create` slots may not be specified in one module definition.

If `Py_mod_create` is not specified, the import machinery will create a normal module object using `PyModule_New()`. The name is taken from *spec*, not the definition, to allow extension modules to dynamically adjust to their place in the module hierarchy and be imported under different names through symlinks, all while sharing a single module definition.

There is no requirement for the returned object to be an instance of `PyModule_Type`. Any type can be used, as long as it supports setting and getting import-related attributes. However, only `PyModule_Type` instances may be returned if the `PyModuleDef` has non-NULL `m_traverse`, `m_clear`, `m_free`; non-zero `m_size`; or slots other than `Py_mod_create`.

Py_mod_exec

Specifies a function that is called to *execute* the module. This is equivalent to executing the code of a Python module: typically, this function adds classes and constants to the module. The signature of the function is:

int **exec_module** (*PyObject* **module*)

If multiple `Py_mod_exec` slots are specified, they are processed in the order they appear in the `m_slots` array.

See [PEP 489](#) for more details on multi-phase initialization.

Low-level module creation functions

The following functions are called under the hood when using multi-phase initialization. They can be used directly, for example when creating module objects dynamically. Note that both `PyModule_FromDefAndSpec` and `PyModule_ExecDef` must be called to fully initialize a module.

PyObject ***PyModule_FromDefAndSpec** (*PyModuleDef* **def*, *PyObject* **spec*)

Return value: New reference. Create a new module object, given the definition in *def* and the `ModuleSpec` *spec*. This behaves like `PyModule_FromDefAndSpec2()` with `module_api_version` set to `PYTHON_API_VERSION`.

3.5 版新加入.

PyObject ***PyModule_FromDefAndSpec2** (*PyModuleDef* **def*, *PyObject* **spec*, int *module_api_version*)

Return value: New reference. Part of the [Stable ABI](#) since version 3.7. Create a new module object, given the definition in *def* and the `ModuleSpec` *spec*, assuming the API version *module_api_version*. If that version does not match the version of the running interpreter, a `RuntimeWarning` is emitted.

備註: Most uses of this function should be using `PyModule_FromDefAndSpec()` instead; only use this if you are sure you need it.

3.5 版新加入.

int **PyModule_ExecDef** (*PyObject* **module*, *PyModuleDef* **def*)

Part of the [Stable ABI](#) since version 3.7. Process any execution slots (`Py_mod_exec`) given in *def*.

3.5 版新加入.

int **PyModule_SetDocString** (*PyObject* *module, const char *docstring)

Part of the [Stable ABI](#) since version 3.7. Set the docstring for *module* to *docstring*. This function is called automatically when creating a module from `PyModuleDef`, using either `PyModule_Create` or `PyModule_FromDefAndSpec`.

3.5 版新加入.

int **PyModule_AddFunctions** (*PyObject* *module, *PyMethodDef* *functions)

Part of the [Stable ABI](#) since version 3.7. Add the functions from the NULL terminated *functions* array to *module*. Refer to the [PyMethodDef](#) documentation for details on individual entries (due to the lack of a shared module namespace, module level "functions" implemented in C typically receive the module as their first parameter, making them similar to instance methods on Python classes). This function is called automatically when creating a module from `PyModuleDef`, using either `PyModule_Create` or `PyModule_FromDefAndSpec`.

3.5 版新加入.

Support functions

The module initialization function (if using single phase initialization) or a function called from a module execution slot (if using multi-phase initialization), can use the following functions to help initialize the module state:

int **PyModule_AddObjectRef** (*PyObject* *module, const char *name, *PyObject* *value)

Part of the [Stable ABI](#) since version 3.10. Add an object to *module* as *name*. This is a convenience function which can be used from the module's initialization function.

On success, return 0. On error, raise an exception and return -1.

Return NULL if *value* is NULL. It must be called with an exception raised in this case.

用法範例:

```
static int
add_spam(PyObject *module, int value)
{
    PyObject *obj = PyLong_FromLong(value);
    if (obj == NULL) {
        return -1;
    }
    int res = PyModule_AddObjectRef(module, "spam", obj);
    Py_DECREF(obj);
    return res;
}
```

The example can also be written without checking explicitly if *obj* is NULL:

```
static int
add_spam(PyObject *module, int value)
{
    PyObject *obj = PyLong_FromLong(value);
    int res = PyModule_AddObjectRef(module, "spam", obj);
    Py_XDECREF(obj);
    return res;
}
```

Note that `Py_XDECREF()` should be used instead of `Py_DECREF()` in this case, since *obj* can be NULL.

3.10 版新加入.

int **PyModule_AddObject** (*PyObject* *module, const char *name, *PyObject* *value)

Part of the [Stable ABI](#). Similar to `PyModule_AddObjectRef()`, but steals a reference to *value* on success (if it returns 0).

The new `PyModule_AddObjectRef()` function is recommended, since it is easy to introduce reference leaks by misusing the `PyModule_AddObject()` function.

備註: Unlike other functions that steal references, `PyModule_AddObject()` only decrements the reference count of *value* on success.

This means that its return value must be checked, and calling code must `Py_DECREF()` *value* manually on error.

用法範例:

```
static int
add_spam(PyObject *module, int value)
{
    PyObject *obj = PyLong_FromLong(value);
    if (obj == NULL) {
        return -1;
    }
    if (PyModule_AddObject(module, "spam", obj) < 0) {
        Py_DECREF(obj);
        return -1;
    }
    // PyModule_AddObject() stole a reference to obj:
    // Py_DECREF(obj) is not needed here
    return 0;
}
```

The example can also be written without checking explicitly if *obj* is NULL:

```
static int
add_spam(PyObject *module, int value)
{
    PyObject *obj = PyLong_FromLong(value);
    if (PyModule_AddObject(module, "spam", obj) < 0) {
        Py_XDECREF(obj);
        return -1;
    }
    // PyModule_AddObject() stole a reference to obj:
    // Py_DECREF(obj) is not needed here
    return 0;
}
```

Note that `Py_XDECREF()` should be used instead of `Py_DECREF()` in this case, since *obj* can be NULL.

int **PyModule_AddIntConstant** (*PyObject* *module, const char *name, long value)

Part of the Stable ABI. Add an integer constant to *module* as *name*. This convenience function can be used from the module's initialization function. Return -1 on error, 0 on success.

int **PyModule_AddStringConstant** (*PyObject* *module, const char *name, const char *value)

Part of the Stable ABI. Add a string constant to *module* as *name*. This convenience function can be used from the module's initialization function. The string *value* must be NULL-terminated. Return -1 on error, 0 on success.

int **PyModule_AddIntMacro** (*PyObject* *module, macro)

Add an int constant to *module*. The name and the value are taken from *macro*. For example `PyModule_AddIntMacro(module, AF_INET)` adds the int constant `AF_INET` with the value of `AF_INET` to *module*. Return -1 on error, 0 on success.

int **PyModule_AddStringMacro** (*PyObject* *module, macro)

Add a string constant to *module*.

int **PyModule_AddType** (*PyObject* *module, *PyTypeObject* *type)

Part of the Stable ABI since version 3.10. Add a type object to *module*. The type object is finalized by calling

internally `PyType_Ready()`. The name of the type object is taken from the last component of `tp_name` after dot. Return `-1` on error, `0` on success.

3.9 版新加入。

Module lookup

Single-phase initialization creates singleton modules that can be looked up in the context of the current interpreter. This allows the module object to be retrieved later with only a reference to the module definition.

These functions will not work on modules created using multi-phase initialization, since multiple such modules can be created from a single definition.

PyObject* `PyState_FindModule` (*PyModuleDef* *def)

Return value: Borrowed reference. Part of the [Stable ABI](#). Returns the module object that was created from *def* for the current interpreter. This method requires that the module object has been attached to the interpreter state with `PyState_AddModule()` beforehand. In case the corresponding module object is not found or has not been attached to the interpreter state yet, it returns `NULL`.

int `PyState_AddModule` (*PyObject* *module, *PyModuleDef* *def)

Part of the [Stable ABI](#) since version 3.3. Attaches the module object passed to the function to the interpreter state. This allows the module object to be accessible via `PyState_FindModule()`.

Only effective on modules created using single-phase initialization.

Python calls `PyState_AddModule` automatically after importing a module, so it is unnecessary (but harmless) to call it from module initialization code. An explicit call is needed only if the module's own init code subsequently calls `PyState_FindModule`. The function is mainly intended for implementing alternative import mechanisms (either by calling it directly, or by referring to its implementation for details of the required state updates).

调用时必须携带 GIL。

Return `0` on success or `-1` on failure.

3.3 版新加入。

int `PyState_RemoveModule` (*PyModuleDef* *def)

Part of the [Stable ABI](#) since version 3.3. Removes the module object created from *def* from the interpreter state. Return `0` on success or `-1` on failure.

调用时必须携带 GIL。

3.3 版新加入。

8.6.3 代器 (Iterator) 物件

Python 提供了两个通用迭代器对象。第一个是序列迭代器，它使用支持 `__getitem__()` 方法的任意序列。第二个使用可调对象和一个 sentinel 值，为序列中的每个项调用可调对象，并在返回 sentinel 值时结束迭代。

PyTypeObject `PySeqIter_Type`

Part of the [Stable ABI](#). `PySeqIter_New()` 返回迭代器对象的类型对象和内置序列类型内置函数 `iter()` 的单参数形式。

int `PySeqIter_Check` (op)

如果 *op* 的类型为 `PySeqIter_Type` 则返回真值。此函数总是会成功执行。

PyObject* `PySeqIter_New` (*PyObject* *seq)

Return value: New reference. Part of the [Stable ABI](#). 返回一个与常规序列对象一起使用的迭代器 *seq*。当序列订阅操作引发 `IndexError` 时，迭代结束。

PyTypeObject PyCallIter_Type

Part of the Stable ABI. 由函数 `PyCallIter_New()` 和 `iter()` 内置函数的双参数形式返回的迭代器对象类型对象。

int PyCallIter_Check (op)

如果 `op` 的类型为 `PyCallIter_Type` 则返回真值。此函数总是会成功执行。

PyObject *PyCallIter_New (PyObject *callable, PyObject *sentinel)

Return value: New reference. Part of the Stable ABI. 返回一个新的迭代器。第一个参数 `callable` 可以是任何可以在没有参数的情况下调用的 Python 可调用对象；每次调用都应该返回迭代中的下一个项目。当 `callable` 返回等于 `sentinel` 的值时，迭代将终止。

8.6.4 Descriptor (描述器) 物件

“Descriptor” 是描述物件某些属性的物件，它们存在于型物件的 dictionary (字典) 中。

PyTypeObject PyProperty_Type

Part of the Stable ABI. 建立 descriptor 型的物件。

PyObject *PyDescr_NewGetSet (PyTypeObject *type, struct PyGetSetDef *getset)

Return value: New reference. Part of the Stable ABI.

PyObject *PyDescr_NewMember (PyTypeObject *type, struct PyMemberDef *meth)

Return value: New reference. Part of the Stable ABI.

PyObject *PyDescr_NewMethod (PyTypeObject *type, struct PyMethodDef *meth)

Return value: New reference. Part of the Stable ABI.

PyObject *PyDescr_NewWrapper (PyTypeObject *type, struct wrapperbase *wrapper, void *wrapped)

Return value: New reference.

PyObject *PyDescr_NewClassMethod (PyTypeObject *type, PyMethodDef *method)

Return value: New reference. Part of the Stable ABI.

int PyDescr_IsData (PyObject *descr)

如果 descriptor 物件 `descr` 描述的是一個資料屬性則回傳非零值，或者如果它描述的是一個方法則返回 0。`descr` 必須是一個 descriptor 物件；有錯誤檢查。

PyObject *PyWrapper_New (PyObject*, PyObject*)

Return value: New reference. Part of the Stable ABI.

8.6.5 切片物件

PyTypeObject PySlice_Type

Part of the Stable ABI. 切片对象的类型对象。它与 Python 层面的 `slice` 是相同的对象。

int PySlice_Check (PyObject *ob)

如果 `ob` 是一个 slice 对象则返回真值；`ob` 必须不为 NULL。此函数总是会成功执行。

PyObject *PySlice_New (PyObject *start, PyObject *stop, PyObject *step)

Return value: New reference. Part of the Stable ABI. 返回一个具有给定值的新切片对象。`start`, `stop` 和 `step` 形参会被用作 slice 对象相应名称的属性的值。这些值中的任何一个都可以为 NULL，在这种情况下将使用 None 作为对应属性的值。如果新对象无法被分配则返回 NULL。

int PySlice_GetIndices (PyObject *slice, Py_ssize_t length, Py_ssize_t *start, Py_ssize_t *stop, Py_ssize_t *step)

Part of the Stable ABI. 从切片对象 `slice` 提取 `start`, `stop` 和 `step` 索引号，将序列长度视为 `length`。大于 `length` 的序列号将被当作错误。

成功时返回 0，出错时返回 -1 并且不设置异常（除非某个序列号不为 None 且无法被转换为整数，在这种情况下会返回 -1 并且设置一个异常）。

你可能不会打算使用此函数。

3.2 版更變: 之前 *slice* 形参的形参类型是 `PySliceObject*`。

int PySlice_GetIndicesEx(*PyObject* **slice*, *Py_ssize_t* *length*, *Py_ssize_t* **start*, *Py_ssize_t* **stop*, *Py_ssize_t* **step*, *Py_ssize_t* **slicelength*)

Part of the Stable ABI. `PySlice_GetIndicesEx()` 的可用替代。从切片对象 *slice* 提取 *start*, *stop* 和 *step* 索引号, 将序列长度视为 *length*, 并将切片的长度保存在 *slicelength* 中, 超出范围的索引号会以与普通切片一致的方式进行剪切。

成功时返回 0, 出错时返回 -1 并且不设置异常。

備註: 此函数对于可变大小序列来说是不安全的。对它的调用应被替换为 `PySlice_Unpack()` 和 `PySlice_AdjustIndices()` 的组合, 其中

```
if (PySlice_GetIndicesEx(slice, length, &start, &stop, &step, &slicelength) < 0) {
    // return error
}
```

会被替换为

```
if (PySlice_Unpack(slice, &start, &stop, &step) < 0) {
    // return error
}
slicelength = PySlice_AdjustIndices(length, &start, &stop, step);
```

3.2 版更變: 之前 *slice* 形参的形参类型是 `PySliceObject*`。

3.6.1 版更變: 如果 `PY_LIMITED_API` 未设置或设置为 `0x03050400` 与 `0x03060000` 之间的值 (不包括边界) 或 `0x03060100` 或更大则 `PySlice_GetIndicesEx()` 会被实现为一个使用 `PySlice_Unpack()` 和 `PySlice_AdjustIndices()` 的宏。参数 *start*, *stop* 和 *step* 会被多被求值。

3.6.1 版後已弃用: 如果 `PY_LIMITED_API` 设置为小于 `0x03050400` 或 `0x03060000` 与 `0x03060100` 之间的值 (不包括边界) 则 `PySlice_GetIndicesEx()` 为已弃用的函数。

int PySlice_Unpack(*PyObject* **slice*, *Py_ssize_t* **start*, *Py_ssize_t* **stop*, *Py_ssize_t* **step*)

Part of the Stable ABI since version 3.7. 从切片对象中将 *start*, *stop* 和 *step* 数据成员提取为 C 整数。会静默地将大于 `PY_SSIZE_T_MAX` 的值减小为 `PY_SSIZE_T_MAX`, 静默地将小于 `PY_SSIZE_T_MIN` 的 *start* 和 *stop* 值增大为 `PY_SSIZE_T_MIN`, 并静默地将小于 `-PY_SSIZE_T_MAX` 的 *step* 值增大为 `-PY_SSIZE_T_MAX`。

出错时返回 -1, 成功时返回 0。

3.6.1 版新加入。

***Py_ssize_t* PySlice_AdjustIndices**(*Py_ssize_t* *length*, *Py_ssize_t* **start*, *Py_ssize_t* **stop*, *Py_ssize_t* **step*)

Part of the Stable ABI since version 3.7. 将 *start/end* 切片索引号根据指定的序列长度进行调整。超出范围的索引号会以与普通切片一致的方式进行剪切。

返回切片的长度。此操作总是会成功。不会调用 Python 代码。

3.6.1 版新加入。

8.6.6 Ellipsis 对象

PyObject *Py_Ellipsis

Python 的 Ellipsis 对象。该对象没有任何方法。它必须与任何其他对象一样的方式遵循引用计数。它与 *Py_None* 一样属于单例对象。

8.6.7 MemoryView 物件

一个 memoryview 对象 C 级别的缓冲区接口 暴露为一个可以像任何其他对象一样传递的 Python 对象。

PyObject *PyMemoryView_FromObject (*PyObject* *obj)

Return value: New reference. Part of the [Stable ABI](#). 从提供缓冲区接口的对象创建 memoryview 对象。如果 obj 支持可写缓冲区导出, 则 memoryview 对象将可以被读/写, 否则它可能是只读的, 也可以是导出器自行决定的读/写。

PyObject *PyMemoryView_FromMemory (char *mem, *Py_ssize_t* size, int flags)

Return value: New reference. Part of the [Stable ABI](#) since version 3.7. 使用 mem 作为底层缓冲区创建一个 memoryview 对象。flags 可以是 PyBUF_READ 或者 PyBUF_WRITE 之一。

3.3 版新加入。

PyObject *PyMemoryView_FromBuffer (*Py_buffer* *view)

Return value: New reference. 创建一个包含给定缓冲区结构 view 的 memoryview 对象。对于简单的字节缓冲区, *PyMemoryView_FromMemory()* 是首选函数。

PyObject *PyMemoryView_GetContiguous (*PyObject* *obj, int buffertype, char order)

Return value: New reference. Part of the [Stable ABI](#). 从定义缓冲区接口的对象创建一个 memoryview 对象 contiguous 内存块 (在 'C' 或 'Fortran order' 中)。如果内存是连续的, 则 memoryview 对象指向原始内存。否则, 复制并且 memoryview 指向新的 bytes 对象。

int PyMemoryView_Check (*PyObject* *obj)

如果 obj 是一个 memoryview 对象则返回真值。目前不允许创建 memoryview 的子类。此函数总是会成功执行。

Py_buffer *PyMemoryView_GET_BUFFER (*PyObject* *mview)

返回指向 memoryview 的导出缓冲区私有副本的指针。mview 必须是一个 memoryview 实例; 这个宏不检查它的类型, 你必须自己检查, 否则你将面临崩溃风险。

PyObject *PyMemoryView_GET_BASE (*PyObject* *mview)

返回 memoryview 所基于的导出对象的指针, 或者如果 memoryview 已由函数 *PyMemoryView_FromMemory()* 或 *PyMemoryView_FromBuffer()* 创建则返回 NULL。mview 必须是一个 memoryview 实例。

8.6.8 弱参照物件

Python 支持“弱引用”作为一类对象。具体来说, 有两种直接实现弱引用的对象。第一种就是简单的引用对象, 第二种尽可能地作用为一个原对象的代理。

int PyWeakref_Check (ob)

如果 ob 是一个引用或代理对象则返回真值。此函数总是会成功执行。

int PyWeakref_CheckRef (ob)

如果 ob 是一个引用对象则返回真值。此函数总是会成功执行。

int PyWeakref_CheckProxy (ob)

如果 ob 是一个代理对象则返回真值。此函数总是会成功执行。

PyObject *PyWeakref_NewRef (*PyObject* *ob, *PyObject* *callback)

Return value: New reference. Part of the [Stable ABI](#). Return a weak reference object for the object ob. This will always return a new reference, but is not guaranteed to create a new object; an existing reference object may be returned. The second parameter, callback, can be a callable object that receives notification when ob is garbage collected; it should accept a single parameter, which will be the weak reference object itself. callback

may also be None or NULL. If *ob* is not a weakly referencable object, or if *callback* is not callable, None, or NULL, this will return NULL and raise `TypeError`.

PyObject ***PyWeakref_NewProxy** (*PyObject* **ob*, *PyObject* **callback*)

Return value: New reference. Part of the [Stable ABI](#). Return a weak reference proxy object for the object *ob*. This will always return a new reference, but is not guaranteed to create a new object; an existing proxy object may be returned. The second parameter, *callback*, can be a callable object that receives notification when *ob* is garbage collected; it should accept a single parameter, which will be the weak reference object itself. *callback* may also be None or NULL. If *ob* is not a weakly referencable object, or if *callback* is not callable, None, or NULL, this will return NULL and raise `TypeError`.

PyObject ***PyWeakref_GetObject** (*PyObject* **ref*)

Return value: Borrowed reference. Part of the [Stable ABI](#). 返回弱引用对象 *ref* 的被引用对象。如果被引用对象不再存在，则返回 `Py_None`。

備註： 该函数返回被引用对象的一个 *borrowed reference*。这意味着应该总是在该对象上调用 `Py_INCREF()`，除非是当它在借入引用的最后一次被使用之前无法被销毁的时候。

PyObject ***PyWeakref_GET_OBJECT** (*PyObject* **ref*)

Return value: Borrowed reference. 类似 `PyWeakref_GetObject()`，但实现为一个不做类型检查的宏。

void **PyObject_ClearWeakRefs** (*PyObject* **object*)

Part of the [Stable ABI](#). This function is called by the `tp_dealloc` handler to clear weak references.

This iterates through the weak references for *object* and calls callbacks for those references which have one. It returns when all callbacks have been attempted.

8.6.9 Capsule 对象

有关使用这些对象的更多信息请参阅 `using-capsules`。

3.1 版新加入。

type **PyCapsule**

This subtype of *PyObject* represents an opaque value, useful for C extension modules who need to pass an opaque value (as a `void*` pointer) through Python code to other C code. It is often used to make a C function pointer defined in one module available to other modules, so the regular import mechanism can be used to access C APIs defined in dynamically loaded modules.

type **PyCapsule_Destructor**

Part of the [Stable ABI](#). Capsule 的析构器回调的类型。定义如下：

```
typedef void (*PyCapsule_Destructor) (PyObject *);
```

参阅 `PyCapsule_New()` 来获取 `PyCapsule_Destructor` 返回值的语义。

int **PyCapsule_CheckExact** (*PyObject* **p*)

如果参数是一个 `PyCapsule` 则返回真值。此函数总是会成功执行。

PyObject ***PyCapsule_New** (void **pointer*, const char **name*, *PyCapsule_Destructor* *destructor*)

Return value: New reference. Part of the [Stable ABI](#). 创建一个封装了 *pointer* 的 `PyCapsule`。 *pointer* 参考可以不为 NULL。

在失败时设置一个异常并返回 NULL。

字符串 *name* 可以是 NULL 或是一个指向有效的 C 字符串的指针。如果不为 NULL，则此字符串必须比 capsule 长（虽然也允许在 *destructor* 中释放它。）

如果 *destructor* 参数不为 NULL，则当它被销毁时将附带 capsule 作为参数来调用。

如果此 capsule 将被保存为一个模块的属性，则 *name* 应当被指定为 `modulename.attribute`。这将允许其他模块使用 `PyCapsule_Import()` 来导入此 capsule。

void ***PyCapsule_GetPointer** (*PyObject* *capsule, const char *name)

Part of the Stable ABI. 提取保存在 capsule 中的 pointer。在失败时设置一个异常并返回 NULL。

name 形参必须与保存在 capsule 中的名称进行精确比较。如果保存在 capsule 中的名称为 NULL，则传入的 name 也必须为 NULL。Python 会使用 C 函数 strcmp() 来比较 capsule 名称。

PyCapsule_Destructor **PyCapsule_GetDestructor** (*PyObject* *capsule)

Part of the Stable ABI. 返回保存在 capsule 中的当前析构器。在失败时设置一个异常并返回 NULL。

capsule 具有 NULL 析构器是合法的。这会使得 NULL 返回码有些歧义；请使用 *PyCapsule_IsValid()* 或 *PyErr_Occurred()* 来消除歧义。

void ***PyCapsule_GetContext** (*PyObject* *capsule)

Part of the Stable ABI. 返回保存在 capsule 中的当前上下文。在失败时设置一个异常并返回 NULL。

capsule 具有 NULL 上下文是全法的。这会使得 NULL 返回码有些歧义；请使用 *PyCapsule_IsValid()* 或 *PyErr_Occurred()* 来消除歧义。

const char ***PyCapsule_GetName** (*PyObject* *capsule)

Part of the Stable ABI. 返回保存在 capsule 中的当前名称。在失败时设置一个异常并返回 NULL。

capsule 具有 NULL 名称是合法的。这会使得 NULL 返回码有些歧义；请使用 *PyCapsule_IsValid()* 或 *PyErr_Occurred()* 来消除歧义。

void ***PyCapsule_Import** (const char *name, int no_block)

Part of the Stable ABI. 从一个模块的 capsule 属性导入指向 C 对象的指针。name 形参应当指定属性的完整名称，与 module.attribute 中的一致。保存在 capsule 中的 name 必须完全匹配此字符串。如果 no_block 为真值，则以无阻塞模式导入模块 (使用 *PyImport_ImportModuleNoBlock()*)。如果 no_block 为假值，则以传统模式导入模块 (使用 *PyImport_ImportModule()*)。

成功时返回 capsule 的内部指针。在失败时设置一个异常并返回 NULL。

int **PyCapsule_IsValid** (*PyObject* *capsule, const char *name)

Part of the Stable ABI. 确定 capsule 是否是一个有效的。有效的 capsule 必须不为 NULL，传递 *PyCapsule_CheckExact()*，在其中存储一个不为 NULL 的指针，并且其内部名称与 name 形参相匹配。(请参阅 *PyCapsule_GetPointer()* 了解如何对 capsule 名称进行比较的有关信息。)

换句话说，如果 *PyCapsule_IsValid()* 返回真值，则任何对访问器 (以 *PyCapsule_Get()* 开头的任何函数) 的调用都保证会成功。

如果对象有效并且匹配传入的名称则返回非零值。否则返回 0。此函数一定不会失败。

int **PyCapsule_SetContext** (*PyObject* *capsule, void *context)

Part of the Stable ABI. 将 capsule 内部的上下文指针设为 context。

成功时返回 0。失败时返回非零值并设置一个异常。

int **PyCapsule_SetDestructor** (*PyObject* *capsule, *PyCapsule_Destructor* destructor)

Part of the Stable ABI. 将 capsule 内部的析构器设为 destructor。

成功时返回 0。失败时返回非零值并设置一个异常。

int **PyCapsule_SetName** (*PyObject* *capsule, const char *name)

Part of the Stable ABI. 将 capsule 内部的名称设为 name。如果不为 NULL，则名称的存在期必须比 capsule 更长。如果之前保存在 capsule 中的 name 不为 NULL，则不会尝试释放它。

成功时返回 0。失败时返回非零值并设置一个异常。

int **PyCapsule_SetPointer** (*PyObject* *capsule, void *pointer)

Part of the Stable ABI. 将 capsule 内部的空指针设为 pointer。指针不可为 NULL。

成功时返回 0。失败时返回非零值并设置一个异常。

8.6.10 生成器物件

生成器对象是 Python 用来实现生成器迭代器的对象。它们通常通过迭代产生值的函数来创建，而不是显式调用 `PyGen_New()` 或 `PyGen_NewWithQualName()`。

type PyGenObject

用于生成器对象的 C 结构体。

PyTypeObject PyGen_Type

与生成器对象对应的类型对象。

int PyGen_Check (PyObject *ob)

如果 `ob` 是一个 generator 对象则返回真值；`ob` 必须不为 NULL。此函数总是会成功执行。

int PyGen_CheckExact (PyObject *ob)

如果 `ob` 的类型是 `PyGen_Type` 则返回真值；`ob` 必须不为 NULL。此函数总是会成功执行。

PyObject *PyGen_New (PyFrameObject *frame)

Return value: New reference. 基于 `frame` 对象创建并返回一个新的生成器对象。此函数会取走一个对 `frame` 的引用。参数必须不为 NULL。

PyObject *PyGen_NewWithQualName (PyFrameObject *frame, PyObject *name, PyObject *qualname)

Return value: New reference. 基于 `frame` 对象创建并返回一个新的生成器对象，其中 `__name__` 和 `__qualname__` 设为 `name` 和 `qualname`。此函数会取走一个对 `frame` 的引用。`frame` 参数必须不为 NULL。

8.6.11 Coroutine (協程) 物件

3.5 版新加入。

Coroutine 物件是那些以 `async` 關鍵字來宣告的函式所回傳的物件。

type PyCoroObject

用於 coroutine 物件的 C 結構。

PyTypeObject PyCoro_Type

與 coroutine 物件對應的型物件。

int PyCoro_CheckExact (PyObject *ob)

如果 `ob` 的型是 `PyCoro_Type` 則回傳真值；`ob` 必須不為 NULL。此函式總是會執行成功。

PyObject *PyCoro_New (PyFrameObject *frame, PyObject *name, PyObject *qualname)

Return value: New reference. 基於 `frame` 物件來建立一個回傳一個新的 coroutine 物件，其中 `__name__` 和 `__qualname__` 被設為 `name` 和 `qualname`。此函式會取得一個對 `frame` 的參照 (reference)。`frame` 引數必須不為 NULL。

8.6.12 上下文变量对象

備註: 3.7.1 版更變: 在 Python 3.7.1 中，所有上下文变量 C API 的签名被 更改为使用 `PyObject` 指针而不是 `PyContext`, `PyContextVar` 以及 `PyContextToken`，例如:

```
// in 3.7.0:
PyContext *PyContext_New(void);

// in 3.7.1+:
PyObject *PyContext_New(void);
```

更多細節請見 bpo-34762。

3.7 版新加入。

本节深入介绍了 contextvars 模块的公用 C API。

type PyContext

用于表示 contextvars.Context 对象的 C 结构体。

type PyContextVar

用于表示 contextvars.ContextVar 对象的 C 结构体。

type PyContextToken

用于表示 contextvars.Token 对象的 C 结构体。

PyObject **PyContext_Type**

表示 context 类型的类型对象。

PyObject **PyContextVar_Type**

表示 context variable 类型的类型对象。

PyObject **PyContextToken_Type**

表示 context variable token 类型的类型对象。

类型检查宏：

int PyContext_CheckExact (PyObject *o)

如果 *o* 的类型为 *PyContext_Type* 则返回真值。*o* 必须不为 NULL。此函数总是会成功执行。

int PyContextVar_CheckExact (PyObject *o)

如果 *o* 的类型为 *PyContextVar_Type* 则返回真值。*o* 必须不为 NULL。此函数总是会成功执行。

int PyContextToken_CheckExact (PyObject *o)

如果 *o* 的类型为 *PyContextToken_Type* 则返回真值。*o* 必须不为 NULL。此函数总是会成功执行。

上下文对象管理函数：

PyObject ***PyContext_New** (void)

Return value: New reference. 创建一个新的空上下文对象。如果发生错误则返回 NULL。

PyObject ***PyContext_Copy** (PyObject *ctx)

Return value: New reference. 创建所传入的 *ctx* 上下文对象的浅拷贝。如果发生错误则返回 NULL。

PyObject ***PyContext_CopyCurrent** (void)

Return value: New reference. 创建当前线程上下文的浅拷贝。如果发生错误则返回 NULL。

int PyContext_Enter (PyObject *ctx)

将 *ctx* 设为当前线程的当前上下文。成功时返回 0，出错时返回 -1。

int PyContext_Exit (PyObject *ctx)

取消激活 *ctx* 上下文并将之前的上下文恢复为当前线程的当前上下文。成功时返回 0，出错时返回 -1。

上下文变量函数：

PyObject ***PyContextVar_New** (const char *name, PyObject *def)

Return value: New reference. 创建一个新的 ContextVar 对象。形参 *name* 用于自我检查和调试目的。形参 *def* 为上下文变量指定默认值，或为 NULL 表示无默认值。如果发生错误，这个函数会返回 NULL。

int PyContextVar_Get (PyObject *var, PyObject *default_value, PyObject **value)

获取上下文变量的值。如果在查找过程中发生错误，返回 '-1'，如果没有发生错误，无论是否找到值，都返回 '0'，

如果找到上下文变量，*value* 将是指向它的指针。如果上下文变量没有找到，*value* 将指向：

- *default_value*，如果非 "NULL"；
- *var* 的默认值，如果不是 NULL；
- NULL

除了返回 NULL，这个函数会返回一个新的引用。

PyObject *PyContextVar_Set (*PyObject* *var, *PyObject* *value)

Return value: New reference. 在当前上下文中将 *var* 设为 *value*。返回针对此修改的新凭据对象，或者如果发生错误则返回 NULL。

int PyContextVar_Reset (*PyObject* *var, *PyObject* *token)

将上下文变量 *var* 的状态重置为它在返回 *token* 的 *PyContextVar_Set()* 被调用之前的状态。此函数成功时返回 0，出错时返回 -1。

8.6.13 DateTime 物件

datetime 模块提供了各种日期和时间对象。在使用任何这些函数之前，必须在你的源码中包含头文件 datetime.h (请注意此文件并未包含在 Python.h 中)，并且宏 PyDateTime_IMPORT 必须被发起调用，通常是作为模块初始化函数的一部分。这个宏会将指向特定 C 结构的指针放入一个静态变量 PyDateTimeAPI 中，它会由下面的宏来使用。

宏访问 UTC 单例:

PyObject *PyDateTime_TimeZone_UTC

返回表示 UTC 的时区单例，与 datetime.timezone.utc 为同一对象。

3.7 版新加入。

类型检查宏:

int PyDate_Check (*PyObject* *ob)

如果 *ob* 为 PyDateTime_DateType 类型或 PyDateTime_DateType 的某个子类型则返回真值。*ob* 不能为 NULL。此函数总是会成功执行。

int PyDate_CheckExact (*PyObject* *ob)

如果 *ob* 为 PyDateTime_DateType 类型则返回真值。*ob* 不能为 NULL。此函数总是会成功执行。

int PyDateTime_Check (*PyObject* *ob)

如果 *ob* 为 PyDateTime_DateTimeType 类型或 PyDateTime_DateTimeType 的某个子类型则返回真值。*ob* 不能为 NULL。此函数总是会成功执行。

int PyDateTime_CheckExact (*PyObject* *ob)

如果 *ob* 为 PyDateTime_DateTimeType 类型则返回真值。*ob* 不能为 NULL。此函数总是会成功执行。

int PyTime_Check (*PyObject* *ob)

如果 *ob* 的类型是 PyDateTime_TimeType 或是 PyDateTime_TimeType 的子类型则返回真值。*ob* 必须不为 NULL。此函数总是会成功执行。

int PyTime_CheckExact (*PyObject* *ob)

如果 *ob* 为 PyDateTime_TimeType 类型则返回真值。*ob* 不能为 NULL。此函数总是会成功执行。

int PyDelta_Check (*PyObject* *ob)

如果 *ob* 为 PyDateTime_DeltaType 类型或 PyDateTime_DeltaType 的某个子类型则返回真值。*ob* 不能为 NULL。此函数总是会成功执行。

int PyDelta_CheckExact (*PyObject* *ob)

如果 *ob* 为 PyDateTime_DeltaType 类型则返回真值。*ob* 不能为 NULL。此函数总是会成功执行。

int PyTZInfo_Check (*PyObject* *ob)

如果 *ob* 的类型是 PyDateTime_TZInfoType 或是 PyDateTime_TZInfoType 的子类型则返回真值。*ob* 必须不为 NULL。此函数总是会成功执行。

int PyTZInfo_CheckExact (*PyObject* *ob)

如果 *ob* 为 PyDateTime_TZInfoType 类型则返回真值。*ob* 不能为 NULL。此函数总是会成功执行。

用于创建对象的宏:

PyObject *PyDate_FromDate (int year, int month, int day)

Return value: New reference. 返回指定年、月、日的 datetime.date 对象。

PyObject *PyDateTime_FromDateAndTime (int year, int month, int day, int hour, int minute, int second, int usecond)

Return value: New reference. 返回具有指定 year, month, day, hour, minute, second 和 microsecond 属性的 datetime.datetime 对象。

PyObject *PyDateTime_FromDateAndTimeAndFold (int year, int month, int day, int hour, int minute, int second, int usecond, int fold)

Return value: New reference. 返回具有指定 year, month, day, hour, minute, second, microsecond 和 fold 属性的 datetime.datetime 对象。

3.6 版新加入。

PyObject *PyTime_FromTime (int hour, int minute, int second, int usecond)

Return value: New reference. 返回具有指定 hour, minute, second 和 microsecond 属性的 datetime.time 对象。

PyObject *PyTime_FromTimeAndFold (int hour, int minute, int second, int usecond, int fold)

Return value: New reference. 返回具有指定 hour, minute, second, microsecond 和 fold 属性的 datetime.time 对象。

3.6 版新加入。

PyObject *PyDelta_FromDSU (int days, int seconds, int useconds)

Return value: New reference. 返回代表给定天、秒和微秒数的 datetime.timedelta 对象。将执行正规化操作以使最终的微秒和秒数处在 datetime.timedelta 对象的文档指明的区间之内。

PyObject *PyTimeZone_FromOffset (PyDateTime_DeltaType *offset)

Return value: New reference. 返回一个 datetime.timezone 对象，该对象具有以 offset 参数表示的未命名固定时差。

3.7 版新加入。

PyObject *PyTimeZone_FromOffsetAndName (PyDateTime_DeltaType *offset, PyUnicode *name)

Return value: New reference. 返回一个 datetime.timezone 对象，该对象具有以 offset 参数表示的固定时差和时区名称 name。

3.7 版新加入。

一些用来从 date 对象中提取字段的宏。参数必须是 PyDateTime_Date 包括其子类 (例如 PyDateTime_DateTime) 的实例。参数必须不为 NULL，并且类型不会被检查：

int **PyDateTime_GET_YEAR** (PyDateTime_Date *o)

回傳年份，正整數。

int **PyDateTime_GET_MONTH** (PyDateTime_Date *o)

回傳月份，正整數，從 1 到 12。

int **PyDateTime_GET_DAY** (PyDateTime_Date *o)

回傳日期，正整數，從 1 到 31。

一些用来从 datetime 对象中提取字段的宏。参数必须是 PyDateTime_DateTime 包括其子类的实例。参数必须不为 NULL，并且类型不会被检查：

int **PyDateTime_DATE_GET_HOUR** (PyDateTime_DateTime *o)

回傳小時，正整數，從 0 到 23。

int **PyDateTime_DATE_GET_MINUTE** (PyDateTime_DateTime *o)

回傳分鐘，正整數，從 0 到 59。

int **PyDateTime_DATE_GET_SECOND** (PyDateTime_DateTime *o)

回傳秒，正整數，從 0 到 59。

int **PyDateTime_DATE_GET_MICROSECOND** (PyDateTime_DateTime *o)

回傳微秒，正整數，從 0 到 999999。

int **PyDateTime_DATE_GET_FOLD** (PyDateTime_DateTime *o)

回傳 fold，0 或 1 的正整數。

3.6 版新加入。

PyObject *PyDateTime_DATE_GET_TZINFO (PyDateTime_DateTime *o)

返回 tzinfo (可以为 None)。

3.10 版新加入。

一些用来从 time 对象中提取字段的宏。参数必须是 PyDateTime_Time 包括其子类的实例。参数必须不为 NULL，并且类型不会被检查：

int PyDateTime_TIME_GET_HOUR (PyDateTime_Time *o)

回傳小時，正整數，從 0 到 23。

int PyDateTime_TIME_GET_MINUTE (PyDateTime_Time *o)

回傳分鐘，正整數，從 0 到 59。

int PyDateTime_TIME_GET_SECOND (PyDateTime_Time *o)

回傳秒，正整數，從 0 到 59。

int PyDateTime_TIME_GET_MICROSECOND (PyDateTime_Time *o)

回傳微秒，正整數，從 0 到 999999。

int PyDateTime_TIME_GET_FOLD (PyDateTime_Time *o)

回傳 fold，0 或 1 的正整數。

3.6 版新加入。

PyObject *PyDateTime_TIME_GET_TZINFO (PyDateTime_Time *o)

返回 tzinfo (可以为 None)。

3.10 版新加入。

一些用来从 timedelta 对象中提取字段的宏。参数必须是 PyDateTime_Delta 包括其子类的实例。参数必须不为 NULL，并且类型不会被检查：

int PyDateTime_DELTA_GET_DAYS (PyDateTime_Delta *o)

返回天数，从 -999999999 到 999999999 的整数。

3.3 版新加入。

int PyDateTime_DELTA_GET_SECONDS (PyDateTime_Delta *o)

返回秒数，从 0 到 86399 的整数。

3.3 版新加入。

int PyDateTime_DELTA_GET_MICROSECONDS (PyDateTime_Delta *o)

返回微秒数，从 0 到 999999 的整数。

3.3 版新加入。

一些便于模块实现 DB API 的宏：

PyObject *PyDateTime_FromTimestamp (*PyObject* *args)

Return value: New reference. 创建并返回一个给定元组参数的新 datetime.datetime 对象，适合传给 datetime.datetime.fromtimestamp()。

PyObject *PyDate_FromTimestamp (*PyObject* *args)

Return value: New reference. 创建并返回一个给定元组参数的新 datetime.date 对象，适合传给 datetime.date.fromtimestamp()。

8.6.14 类型注解对象

提供几种用于类型提示的内置类型。目前存在两种类型 -- `GenericAlias` 和 `Union`。只有 `GenericAlias` 会向 C 开放。

`PyObject*Py_GenericAlias(PyObject*origin, PyObject*args)`

Part of the Stable ABI since version 3.9. Create a `GenericAlias` object. Equivalent to calling the Python class `types.GenericAlias`. The *origin* and *args* arguments set the `GenericAlias`'s `__origin__` and `__args__` attributes respectively. *origin* should be a `PyTypeObject*`, and *args* can be a `PyTupleObject*` or any `PyObject*`. If *args* passed is not a tuple, a 1-tuple is automatically constructed and `__args__` is set to `(args,)`. Minimal checking is done for the arguments, so the function will succeed even if *origin* is not a type. The `GenericAlias`'s `__parameters__` attribute is constructed lazily from `__args__`. On failure, an exception is raised and `NULL` is returned.

下面是一个如何创建一个扩展类型泛型的例子:

```
...
static PyMethodDef my_obj_methods[] = {
    // Other methods.
    ...
    {"__class_getitem__", (PyCFunction)Py_GenericAlias, METH_O|METH_CLASS,
↪ "See PEP 585"}
    ...
}
```

也参考:

数据模型的方法 `__class_getitem__()`。

3.9 版新加入。

`PyTypeObject Py_GenericAliasType`

Part of the Stable ABI since version 3.9. 由 `Py_GenericAlias()` 所返回的对象的 C 类型。等价于 Python 中的 `types.GenericAlias`。

3.9 版新加入。

初始化，终结和线程

请参阅Python 初始化配置。

9.1 在 Python 初始化之前

在一个植入了 Python 的应用程序中，`Py_Initialize()` 函数必须在任何其他 Python/C API 函数之前被调用；例外的只有个别函数和全局配置变量。

在初始化 Python 之前，可以安全地调用以下函数：

- 配置函数：

- `PyImport_AppendInittab()`
- `PyImport_ExtendInittab()`
- `PyInitFrozenExtensions()`
- `PyMem_SetAllocator()`
- `PyMem_SetupDebugHooks()`
- `PyObject_SetArenaAllocator()`
- `Py_SetPath()`
- `Py_SetProgramName()`
- `Py_SetPythonHome()`
- `Py_SetStandardStreamEncoding()`
- `PySys_AddWarnOption()`
- `PySys_AddXOption()`
- `PySys_ResetWarnOptions()`

- 信息函数：

- `Py_IsInitialized()`
- `PyMem_GetAllocator()`
- `PyObject_GetArenaAllocator()`

- `Py_GetBuildInfo()`
- `Py_GetCompiler()`
- `Py_GetCopyright()`
- `Py_GetPlatform()`
- `Py_GetVersion()`

- 工具

- `Py_DecodeLocale()`

- 内存分配器:

- `PyMem_RawMalloc()`
 - `PyMem_RawRealloc()`
 - `PyMem_RawCalloc()`
 - `PyMem_RawFree()`

備 註: 以下函数不应该在 `Py_Initialize()`: `Py_EncodeLocale()`, `Py_GetPath()`, `Py_GetPrefix()`, `Py_GetExecPrefix()`, `Py_GetProgramFullPath()`, `Py_GetPythonHome()`, `Py_GetProgramName()` 和 `PyEval_InitThreads()` 前调用。

9.2 全局配置变量

Python 有负责控制全局配置中不同特性和选项的变量。这些标志默认被 命令行选项。

当一个选项设置一个旗标时, 该旗标的值将是设置选项的次数。例如, `-b` 会将 `Py_BytesWarningFlag` 设为 1 而 `-bb` 会将 `Py_BytesWarningFlag` 设为 2。

int `Py_BytesWarningFlag`

Issue a warning when comparing bytes or bytearray with str or bytes with int. Issue an error if greater or equal to 2.

由 `-b` 选项设置。

int `Py_DebugFlag`

开启解析器调试输出 (限专家使用, 依赖于编译选项)。

由 `-d` 选项和 `PYTHONDEBUG` 环境变量设置。

int `Py_DontWriteBytecodeFlag`

如果设置为非零, Python 不会在导入源代码时尝试写入 `.pyc` 文件

由 `-B` 选项和 `PYTHONDONTWRITEBYTECODE` 环境变量设置。

int `Py_FrozenFlag`

Suppress error messages when calculating the module search path in `Py_GetPath()`.

Private flag used by `_freeze_importlib` and `frozenmain` programs.

int `Py_HashRandomizationFlag`

Set to 1 if the `PYTHONHASHSEED` environment variable is set to a non-empty string.

If the flag is non-zero, read the `PYTHONHASHSEED` environment variable to initialize the secret hash seed.

int `Py_IgnoreEnvironmentFlag`

忽略所有 `PYTHON*` 环境变量, 例如, 已设置的 `PYTHONPATH` 和 `PYTHONHOME`。

由 `-E` 和 `-I` 选项设置。

int Py_InspectFlag

When a script is passed as first argument or the `-c` option is used, enter interactive mode after executing the script or the command, even when `sys.stdin` does not appear to be a terminal.

Set by the `-i` option and the `PYTHONINSPECT` environment variable.

int Py_InteractiveFlag

由 `-i` 选项设置。

int Py_IsolatedFlag

Run Python in isolated mode. In isolated mode `sys.path` contains neither the script's directory nor the user's site-packages directory.

由 `-I` 选项设置。

3.4 版新加入。

int Py_LegacyWindowsFSEncodingFlag

If the flag is non-zero, use the `mbcs` encoding with `replace` error handler, instead of the UTF-8 encoding with `surrogatepass` error handler, for the *filesystem encoding and error handler*.

Set to 1 if the `PYTHONLEGACYWINDOWSFSENCODING` environment variable is set to a non-empty string.

更多詳情請見 [PEP 529](#)。

適用：Windows。

int Py_LegacyWindowsStdioFlag

If the flag is non-zero, use `io.FileIO` instead of `WindowsConsoleIO` for `sys` standard streams.

Set to 1 if the `PYTHONLEGACYWINDOWSSTDIO` environment variable is set to a non-empty string.

更多詳情請見 [PEP 528](#)。

適用：Windows。

int Py_NoSiteFlag

禁用 `site` 的导入及其所附带的基于站点对 `sys.path` 的操作。如果 `site` 会在稍后被显式地导入也会禁用这些操作 (如果你希望触发它们则应调用 `site.main()`)。

由 `-S` 选项设置。

int Py_NoUserSiteDirectory

不要将用户 `site-packages` 目录添加到 `sys.path`。

Set by the `-s` and `-I` options, and the `PYTHONNOUSERSITE` environment variable.

int Py_OptimizeFlag

Set by the `-O` option and the `PYTHONOPTIMIZE` environment variable.

int Py_QuietFlag

即使在交互模式下也不显示版权和版本信息。

由 `-q` 选项设置。

3.2 版新加入。

int Py_UnbufferedStdioFlag

强制 `stdout` 和 `stderr` 流不带缓冲。

Set by the `-u` option and the `PYTHONUNBUFFERED` environment variable.

int Py_VerboseFlag

Print a message each time a module is initialized, showing the place (filename or built-in module) from which it is loaded. If greater or equal to 2, print a message for each file that is checked for when searching for a module. Also provides information on module cleanup at exit.

Set by the `-v` option and the `PYTHONVERBOSE` environment variable.

9.3 Initializing and finalizing the interpreter

void **Py_Initialize**()

Part of the Stable ABI. Initialize the Python interpreter. In an application embedding Python, this should be called before using any other Python/C API functions; see *Before Python Initialization* for the few exceptions.

This initializes the table of loaded modules (`sys.modules`), and creates the fundamental modules `builtins`, `__main__` and `sys`. It also initializes the module search path (`sys.path`). It does not set `sys.argv`; use `PySys_SetArgvEx()` for that. This is a no-op when called for a second time (without calling `Py_FinalizeEx()` first). There is no return value; it is a fatal error if the initialization fails.

備註: 在 Windows 上, 将控制台模式从 `O_TEXT` 改为 `O_BINARY`, 这还将影响使用 C 运行时的非 Python 的控制台使用。

void **Py_InitializeEx**(int *initsigs*)

Part of the Stable ABI. This function works like `Py_Initialize()` if *initsigs* is 1. If *initsigs* is 0, it skips initialization registration of signal handlers, which might be useful when Python is embedded.

int **Py_IsInitialized**()

Part of the Stable ABI. Return true (nonzero) when the Python interpreter has been initialized, false (zero) if not. After `Py_FinalizeEx()` is called, this returns false until `Py_Initialize()` is called again.

int **Py_FinalizeEx**()

Part of the Stable ABI since version 3.6. Undo all initializations made by `Py_Initialize()` and subsequent use of Python/C API functions, and destroy all sub-interpreters (see `Py_NewInterpreter()` below) that were created and not yet destroyed since the last call to `Py_Initialize()`. Ideally, this frees all memory allocated by the Python interpreter. This is a no-op when called for a second time (without calling `Py_Initialize()` again first). Normally the return value is 0. If there were errors during finalization (flushing buffered data), -1 is returned.

This function is provided for a number of reasons. An embedding application might want to restart Python without having to restart the application itself. An application that has loaded the Python interpreter from a dynamically loadable library (or DLL) might want to free all memory allocated by Python before unloading the DLL. During a hunt for memory leaks in an application a developer might want to free all memory allocated by Python before exiting from the application.

Bugs and caveats: The destruction of modules and objects in modules is done in random order; this may cause destructors (`__del__()` methods) to fail when they depend on other objects (even functions) or modules. Dynamically loaded extension modules loaded by Python are not unloaded. Small amounts of memory allocated by the Python interpreter may not be freed (if you find a leak, please report it). Memory tied up in circular references between objects is not freed. Some memory allocated by extension modules may not be freed. Some extensions may not work properly if their initialization routine is called more than once; this can happen if an application calls `Py_Initialize()` and `Py_FinalizeEx()` more than once.

Raises an auditing event `cpython._PySys_ClearAuditHooks` with no arguments.

3.6 版新加入。

void **Py_Finalize**()

Part of the Stable ABI. This is a backwards-compatible version of `Py_FinalizeEx()` that disregards the return value.

9.4 Process-wide parameters

int **Py_SetStandardStreamEncoding**(const char *encoding, const char *errors)

This function should be called before `Py_Initialize()`, if it is called at all. It specifies which encoding and error handling to use with standard IO, with the same meanings as in `str.encode()`.

It overrides `PYTHONIOENCODING` values, and allows embedding code to control IO encoding when the environment variable does not work.

encoding and/or errors may be `NULL` to use `PYTHONIOENCODING` and/or default values (depending on other settings).

Note that `sys.stderr` always uses the "backslashreplace" error handler, regardless of this (or any other) setting.

If `Py_FinalizeEx()` is called, this function will need to be called again in order to affect subsequent calls to `Py_Initialize()`.

Returns 0 if successful, a nonzero value on error (e.g. calling after the interpreter has already been initialized).

3.4 版新加入。

void **Py_SetProgramName**(const wchar_t *name)

Part of the Stable ABI. This function should be called before `Py_Initialize()` is called for the first time, if it is called at all. It tells the interpreter the value of the `argv[0]` argument to the `main()` function of the program (converted to wide characters). This is used by `Py_GetPath()` and some other functions below to find the Python run-time libraries relative to the interpreter executable. The default value is 'python'. The argument should point to a zero-terminated wide character string in static storage whose contents will not change for the duration of the program's execution. No code in the Python interpreter will change the contents of this storage.

Use `Py_DecodeLocale()` to decode a bytes string to get a `wchar_*` string.

wchar_t ***Py_GetProgramName**()

Part of the Stable ABI. Return the program name set with `Py_SetProgramName()`, or the default. The returned string points into static storage; the caller should not modify its value.

This function should not be called before `Py_Initialize()`, otherwise it returns `NULL`.

3.10 版更變: It now returns `NULL` if called before `Py_Initialize()`.

wchar_t ***Py_GetPrefix**()

Part of the Stable ABI. Return the *prefix* for installed platform-independent files. This is derived through a number of complicated rules from the program name set with `Py_SetProgramName()` and some environment variables; for example, if the program name is '/usr/local/bin/python', the prefix is '/usr/local'. The returned string points into static storage; the caller should not modify its value. This corresponds to the `prefix` variable in the top-level Makefile and the `--prefix` argument to the `configure` script at build time. The value is available to Python code as `sys.prefix`. It is only useful on Unix. See also the next function.

This function should not be called before `Py_Initialize()`, otherwise it returns `NULL`.

3.10 版更變: It now returns `NULL` if called before `Py_Initialize()`.

wchar_t ***Py_GetExecPrefix**()

Part of the Stable ABI. Return the *exec-prefix* for installed platform-dependent files. This is derived through a number of complicated rules from the program name set with `Py_SetProgramName()` and some environment variables; for example, if the program name is '/usr/local/bin/python', the *exec-prefix* is '/usr/local'. The returned string points into static storage; the caller should not modify its value. This corresponds to the `exec_prefix` variable in the top-level Makefile and the `--exec-prefix` argument to the `configure` script at build time. The value is available to Python code as `sys.exec_prefix`. It is only useful on Unix.

Background: The *exec-prefix* differs from the *prefix* when platform dependent files (such as executables and shared libraries) are installed in a different directory tree. In a typical installation, platform dependent files

may be installed in the `/usr/local/plat` subtree while platform independent may be installed in `/usr/local`.

Generally speaking, a platform is a combination of hardware and software families, e.g. Sparc machines running the Solaris 2.x operating system are considered the same platform, but Intel machines running Solaris 2.x are another platform, and Intel machines running Linux are yet another platform. Different major revisions of the same operating system generally also form different platforms. Non-Unix operating systems are a different story; the installation strategies on those systems are so different that the prefix and exec-prefix are meaningless, and set to the empty string. Note that compiled Python bytecode files are platform independent (but not independent from the Python version by which they were compiled!).

System administrators will know how to configure the **mount** or **automount** programs to share `/usr/local` between platforms while having `/usr/local/plat` be a different filesystem for each platform.

This function should not be called before `Py_Initialize()`, otherwise it returns NULL.

3.10 版更變: It now returns NULL if called before `Py_Initialize()`.

`wchar_t *Py_GetProgramFullPath()`

Part of the Stable ABI. Return the full program name of the Python executable; this is computed as a side-effect of deriving the default module search path from the program name (set by `Py_SetProgramName()` above). The returned string points into static storage; the caller should not modify its value. The value is available to Python code as `sys.executable`.

This function should not be called before `Py_Initialize()`, otherwise it returns NULL.

3.10 版更變: It now returns NULL if called before `Py_Initialize()`.

`wchar_t *Py_GetPath()`

Part of the Stable ABI. Return the default module search path; this is computed from the program name (set by `Py_SetProgramName()` above) and some environment variables. The returned string consists of a series of directory names separated by a platform dependent delimiter character. The delimiter character is ':' on Unix and macOS, ';' on Windows. The returned string points into static storage; the caller should not modify its value. The list `sys.path` is initialized with this value on interpreter startup; it can be (and usually is) modified later to change the search path for loading modules.

This function should not be called before `Py_Initialize()`, otherwise it returns NULL.

3.10 版更變: It now returns NULL if called before `Py_Initialize()`.

`void Py_SetPath(const wchar_t*)`

Part of the Stable ABI since version 3.7. Set the default module search path. If this function is called before `Py_Initialize()`, then `Py_GetPath()` won't attempt to compute a default search path but uses the one provided instead. This is useful if Python is embedded by an application that has full knowledge of the location of all modules. The path components should be separated by the platform dependent delimiter character, which is ':' on Unix and macOS, ';' on Windows.

This also causes `sys.executable` to be set to the program full path (see `Py_GetProgramFullPath()`) and for `sys.prefix` and `sys.exec_prefix` to be empty. It is up to the caller to modify these if required after calling `Py_Initialize()`.

Use `Py_DecodeLocale()` to decode a bytes string to get a `wchar_t*` string.

The path argument is copied internally, so the caller may free it after the call completes.

3.8 版更變: The program full path is now used for `sys.executable`, instead of the program name.

`const char *Py_GetVersion()`

Part of the Stable ABI. Return the version of this Python interpreter. This is a string that looks something like

```
"3.0a5+ (py3k:63103M, May 12 2008, 00:53:55) \n[GCC 4.2.3]"
```

The first word (up to the first space character) is the current Python version; the first characters are the major and minor version separated by a period. The returned string points into static storage; the caller should not modify its value. The value is available to Python code as `sys.version`.

const char *Py_GetPlatform()

Part of the [Stable ABI](#). Return the platform identifier for the current platform. On Unix, this is formed from the “official” name of the operating system, converted to lower case, followed by the major revision number; e.g., for Solaris 2.x, which is also known as SunOS 5.x, the value is 'sunos5'. On macOS, it is 'darwin'. On Windows, it is 'win'. The returned string points into static storage; the caller should not modify its value. The value is available to Python code as `sys.platform`.

const char *Py_GetCopyright()

Part of the [Stable ABI](#). Return the official copyright string for the current Python version, for example

```
'Copyright 1991-1995 Stichting Mathematisch Centrum, Amsterdam'
```

The returned string points into static storage; the caller should not modify its value. The value is available to Python code as `sys.copyright`.

const char *Py_GetCompiler()

Part of the [Stable ABI](#). Return an indication of the compiler used to build the current Python version, in square brackets, for example:

```
"[GCC 2.7.2.2]"
```

The returned string points into static storage; the caller should not modify its value. The value is available to Python code as part of the variable `sys.version`.

const char *Py_BuildInfo()

Part of the [Stable ABI](#). Return information about the sequence number and build date and time of the current Python interpreter instance, for example

```
"#67, Aug 1 1997, 22:34:28"
```

The returned string points into static storage; the caller should not modify its value. The value is available to Python code as part of the variable `sys.version`.

void PySys_SetArgvEx (int argc, wchar_t **argv, int updatepath)

Part of the [Stable ABI](#). Set `sys.argv` based on `argc` and `argv`. These parameters are similar to those passed to the program’s `main()` function with the difference that the first entry should refer to the script file to be executed rather than the executable hosting the Python interpreter. If there isn’t a script that will be run, the first entry in `argv` can be an empty string. If this function fails to initialize `sys.argv`, a fatal condition is signalled using `Py_FatalError()`.

If `updatepath` is zero, this is all the function does. If `updatepath` is non-zero, the function also modifies `sys.path` according to the following algorithm:

- If the name of an existing script is passed in `argv[0]`, the absolute path of the directory where the script is located is prepended to `sys.path`.
- Otherwise (that is, if `argc` is 0 or `argv[0]` doesn’t point to an existing file name), an empty string is prepended to `sys.path`, which is the same as prepending the current working directory (".").

Use `Py_DecodeLocale()` to decode a bytes string to get a `wchar_t*` string.

備註: It is recommended that applications embedding the Python interpreter for purposes other than executing a single script pass 0 as `updatepath`, and update `sys.path` themselves if desired. See [CVE-2008-5983](#).

On versions before 3.1.3, you can achieve the same effect by manually popping the first `sys.path` element after having called `PySys_SetArgv()`, for example using:

```
PyRun_SimpleString("import sys; sys.path.pop(0)\n");
```

3.1.3 版新加入.

void PySys_SetArgv (int argc, wchar_t **argv)

Part of the [Stable ABI](#). This function works like `PySys_SetArgvEx()` with `updatepath` set to 1 unless the `python` interpreter was started with the `-I`.

Use `Py_DecodeLocale()` to decode a bytes string to get a `wchar_t*` string.

3.4 版更變: The `updatepath` value depends on `-I`.

void **Py_SetPythonHome** (const `wchar_t*` *home*)

Part of the Stable ABI. Set the default "home" directory, that is, the location of the standard Python libraries. See `PYTHONHOME` for the meaning of the argument string.

The argument should point to a zero-terminated character string in static storage whose contents will not change for the duration of the program's execution. No code in the Python interpreter will change the contents of this storage.

Use `Py_DecodeLocale()` to decode a bytes string to get a `wchar_t*` string.

`wchar_t*` **Py_GetPythonHome** ()

Part of the Stable ABI. Return the default "home", that is, the value set by a previous call to `Py_SetPythonHome()`, or the value of the `PYTHONHOME` environment variable if it is set.

This function should not be called before `Py_Initialize()`, otherwise it returns `NULL`.

3.10 版更變: It now returns `NULL` if called before `Py_Initialize()`.

9.5 线程状态和全局解释器锁

The Python interpreter is not fully thread-safe. In order to support multi-threaded Python programs, there's a global lock, called the *global interpreter lock* or *GIL*, that must be held by the current thread before it can safely access Python objects. Without the lock, even the simplest operations could cause problems in a multi-threaded program: for example, when two threads simultaneously increment the reference count of the same object, the reference count could end up being incremented only once instead of twice.

Therefore, the rule exists that only the thread that has acquired the *GIL* may operate on Python objects or call Python/C API functions. In order to emulate concurrency of execution, the interpreter regularly tries to switch threads (see `sys.setswitchinterval()`). The lock is also released around potentially blocking I/O operations like reading or writing a file, so that other Python threads can run in the meantime.

The Python interpreter keeps some thread-specific bookkeeping information inside a data structure called *PyThreadState*. There's also one global variable pointing to the current *PyThreadState*: it can be retrieved using `PyThreadState_Get()`.

9.5.1 Releasing the GIL from extension code

Most extension code manipulating the *GIL* has the following simple structure:

```
Save the thread state in a local variable.
Release the global interpreter lock.
... Do some blocking I/O operation ...
Reacquire the global interpreter lock.
Restore the thread state from the local variable.
```

This is so common that a pair of macros exists to simplify it:

```
Py_BEGIN_ALLOW_THREADS
... Do some blocking I/O operation ...
Py_END_ALLOW_THREADS
```

The `Py_BEGIN_ALLOW_THREADS` macro opens a new block and declares a hidden local variable; the `Py_END_ALLOW_THREADS` macro closes the block.

上面的代码块可扩展为下面的代码:

```
PyThreadState *_save;

_save = PyEval_SaveThread();
... Do some blocking I/O operation ...
PyEval_RestoreThread(_save);
```

Here is how these functions work: the global interpreter lock is used to protect the pointer to the current thread state. When releasing the lock and saving the thread state, the current thread state pointer must be retrieved before the lock is released (since another thread could immediately acquire the lock and store its own thread state in the global variable). Conversely, when acquiring the lock and restoring the thread state, the lock must be acquired before storing the thread state pointer.

備註： Calling system I/O functions is the most common use case for releasing the GIL, but it can also be useful before calling long-running computations which don't need access to Python objects, such as compression or cryptographic functions operating over memory buffers. For example, the standard `zlib` and `hashlib` modules release the GIL when compressing or hashing data.

9.5.2 非 Python 创建的线程

When threads are created using the dedicated Python APIs (such as the `threading` module), a thread state is automatically associated to them and the code showed above is therefore correct. However, when threads are created from C (for example by a third-party library with its own thread management), they don't hold the GIL, nor is there a thread state structure for them.

If you need to call Python code from these threads (often this will be part of a callback API provided by the aforementioned third-party library), you must first register these threads with the interpreter by creating a thread state data structure, then acquiring the GIL, and finally storing their thread state pointer, before you can start using the Python/C API. When you are done, you should reset the thread state pointer, release the GIL, and finally free the thread state data structure.

The `PyGILState_Ensure()` and `PyGILState_Release()` functions do all of the above automatically. The typical idiom for calling into Python from a C thread is:

```
PyGILState_STATE gstate;
gstate = PyGILState_Ensure();

/* Perform Python actions here. */
result = CallSomeFunction();
/* evaluate result or handle exception */

/* Release the thread. No Python API allowed beyond this point. */
PyGILState_Release(gstate);
```

Note that the `PyGILState_*` functions assume there is only one global interpreter (created automatically by `Py_Initialize()`). Python supports the creation of additional interpreters (using `Py_NewInterpreter()`), but mixing multiple interpreters and the `PyGILState_*` API is unsupported.

9.5.3 Cautions about fork()

Another important thing to note about threads is their behaviour in the face of the C `fork()` call. On most systems with `fork()`, after a process forks only the thread that issued the fork will exist. This has a concrete impact both on how locks must be handled and on all stored state in CPython's runtime.

The fact that only the "current" thread remains means any locks held by other threads will never be released. Python solves this for `os.fork()` by acquiring the locks it uses internally before the fork, and releasing them afterwards. In addition, it resets any lock-objects in the child. When extending or embedding Python, there is no way to inform Python of additional (non-Python) locks that need to be acquired before or reset after a fork. OS facilities such as `pthread_atfork()` would need to be used to accomplish the same thing. Additionally, when extending or embedding Python, calling `fork()` directly rather than through `os.fork()` (and returning to or calling into Python) may result in a deadlock by one of Python's internal locks being held by a thread that is defunct after the fork. `PyOS_AfterFork_Child()` tries to reset the necessary locks, but is not always able to.

The fact that all other threads go away also means that CPython's runtime state there must be cleaned up properly, which `os.fork()` does. This means finalizing all other `PyThreadState` objects belonging to the current interpreter and all other `PyInterpreterState` objects. Due to this and the special nature of the "main" interpreter, `fork()` should only be called in that interpreter's "main" thread, where the CPython global runtime was originally initialized. The only exception is if `exec()` will be called immediately after.

9.5.4 高阶 API

These are the most commonly used types and functions when writing C extension code, or when embedding the Python interpreter:

type `PyInterpreterState`

Part of the Limited API (as an opaque struct). This data structure represents the state shared by a number of cooperating threads. Threads belonging to the same interpreter share their module administration and a few other internal items. There are no public members in this structure.

Threads belonging to different interpreters initially share nothing, except process state like available memory, open file descriptors and such. The global interpreter lock is also shared by all threads, regardless of to which interpreter they belong.

type `PyThreadState`

Part of the Limited API (as an opaque struct). This data structure represents the state of a single thread. The only public data member is `interp` (`PyInterpreterState*`), which points to this thread's interpreter state.

void `PyEval_InitThreads()`

Part of the Stable ABI. Deprecated function which does nothing.

在 Python 3.6 及更老的版本中，此函数会在 GIL 不存在时创建它。

3.9 版更變: The function now does nothing.

3.7 版更變: This function is now called by `Py_Initialize()`, so you don't have to call it yourself anymore.

3.2 版更變: This function cannot be called before `Py_Initialize()` anymore.

自從版本 3.9 後不推薦使用，將會自版本 3.11 中移除。

int `PyEval_ThreadsInitialized()`

Part of the Stable ABI. Returns a non-zero value if `PyEval_InitThreads()` has been called. This function can be called without holding the GIL, and therefore can be used to avoid calls to the locking API when running single-threaded.

3.7 版更變: The GIL is now initialized by `Py_Initialize()`.

自從版本 3.9 後不推薦使用，將會自版本 3.11 中移除。

`PyThreadState*` `PyEval_SaveThread()`

Part of the Stable ABI. Release the global interpreter lock (if it has been created) and reset the thread state to

NULL, returning the previous thread state (which is not NULL). If the lock has been created, the current thread must have acquired it.

void **PyEval_RestoreThread** (*PyThreadState* *tstate)

Part of the Stable ABI. Acquire the global interpreter lock (if it has been created) and set the thread state to *tstate*, which must not be NULL. If the lock has been created, the current thread must not have acquired it, otherwise deadlock ensues.

備註: Calling this function from a thread when the runtime is finalizing will terminate the thread, even if the thread was not created by Python. You can use `_Py_IsFinalizing()` or `sys.is_finalizing()` to check if the interpreter is in process of being finalized before calling this function to avoid unwanted termination.

PyThreadState ***PyThreadState_Get** ()

Part of the Stable ABI. Return the current thread state. The global interpreter lock must be held. When the current thread state is NULL, this issues a fatal error (so that the caller needn't check for NULL).

PyThreadState ***PyThreadState_Swap** (*PyThreadState* *tstate)

Part of the Stable ABI. Swap the current thread state with the thread state given by the argument *tstate*, which may be NULL. The global interpreter lock must be held and is not released.

The following functions use thread-local storage, and are not compatible with sub-interpreters:

PyGILState_STATE **PyGILState_Ensure** ()

Part of the Stable ABI. Ensure that the current thread is ready to call the Python C API regardless of the current state of Python, or of the global interpreter lock. This may be called as many times as desired by a thread as long as each call is matched with a call to `PyGILState_Release()`. In general, other thread-related APIs may be used between `PyGILState_Ensure()` and `PyGILState_Release()` calls as long as the thread state is restored to its previous state before the `Release()`. For example, normal usage of the `Py_BEGIN_ALLOW_THREADS` and `Py_END_ALLOW_THREADS` macros is acceptable.

The return value is an opaque "handle" to the thread state when `PyGILState_Ensure()` was called, and must be passed to `PyGILState_Release()` to ensure Python is left in the same state. Even though recursive calls are allowed, these handles *cannot* be shared - each unique call to `PyGILState_Ensure()` must save the handle for its call to `PyGILState_Release()`.

When the function returns, the current thread will hold the GIL and be able to call arbitrary Python code. Failure is a fatal error.

備註: Calling this function from a thread when the runtime is finalizing will terminate the thread, even if the thread was not created by Python. You can use `_Py_IsFinalizing()` or `sys.is_finalizing()` to check if the interpreter is in process of being finalized before calling this function to avoid unwanted termination.

void **PyGILState_Release** (*PyGILState_STATE*)

Part of the Stable ABI. Release any resources previously acquired. After this call, Python's state will be the same as it was prior to the corresponding `PyGILState_Ensure()` call (but generally this state will be unknown to the caller, hence the use of the GILState API).

Every call to `PyGILState_Ensure()` must be matched by a call to `PyGILState_Release()` on the same thread.

PyThreadState ***PyGILState_GetThisThreadState** ()

Part of the Stable ABI. Get the current thread state for this thread. May return NULL if no GILState API has been used on the current thread. Note that the main thread always has such a thread-state, even if no auto-thread-state call has been made on the main thread. This is mainly a helper/diagnostic function.

int **PyGILState_Check** ()

Return 1 if the current thread is holding the GIL and 0 otherwise. This function can be called from any thread at any time. Only if it has had its Python thread state initialized and currently is holding the GIL will it return 1. This is mainly a helper/diagnostic function. It can be useful for example in callback contexts or memory

allocation functions when knowing that the GIL is locked can allow the caller to perform sensitive actions or otherwise behave differently.

3.4 版新加入.

The following macros are normally used without a trailing semicolon; look for example usage in the Python source distribution.

Py_BEGIN_ALLOW_THREADS

Part of the Stable ABI. This macro expands to `{ PyThreadState *_save; _save = PyEval_SaveThread();`. Note that it contains an opening brace; it must be matched with a following `Py_END_ALLOW_THREADS` macro. See above for further discussion of this macro.

Py_END_ALLOW_THREADS

Part of the Stable ABI. 此宏扩展为 `PyEval_RestoreThread(_save); }`。注意它包含一个右花括号; 它必须与之前的 `Py_BEGIN_ALLOW_THREADS` 宏匹配。请参阅上文以进一步讨论此宏。

Py_BLOCK_THREADS

Part of the Stable ABI. This macro expands to `PyEval_RestoreThread(_save);`; it is equivalent to `Py_END_ALLOW_THREADS` without the closing brace.

Py_UNBLOCK_THREADS

Part of the Stable ABI. This macro expands to `_save = PyEval_SaveThread();`; it is equivalent to `Py_BEGIN_ALLOW_THREADS` without the opening brace and variable declaration.

9.5.5 Low-level API

All of the following functions must be called after `Py_Initialize()`.

3.7 版更變: `Py_Initialize()` now initializes the *GIL*.

PyInterpreterState ***PyInterpreterState_New**()

Part of the Stable ABI. Create a new interpreter state object. The global interpreter lock need not be held, but may be held if it is necessary to serialize calls to this function.

Raises an auditing event `cpython.PyInterpreterState_New` with no arguments.

void **PyInterpreterState_Clear**(*PyInterpreterState* *interp)

Part of the Stable ABI. Reset all information in an interpreter state object. The global interpreter lock must be held.

Raises an auditing event `cpython.PyInterpreterState_Clear` with no arguments.

void **PyInterpreterState_Delete**(*PyInterpreterState* *interp)

Part of the Stable ABI. Destroy an interpreter state object. The global interpreter lock need not be held. The interpreter state must have been reset with a previous call to `PyInterpreterState_Clear()`.

PyThreadState ***PyThreadState_New**(*PyInterpreterState* *interp)

Part of the Stable ABI. Create a new thread state object belonging to the given interpreter object. The global interpreter lock need not be held, but may be held if it is necessary to serialize calls to this function.

void **PyThreadState_Clear**(*PyThreadState* *tstate)

Part of the Stable ABI. Reset all information in a thread state object. The global interpreter lock must be held.

3.9 版更變: This function now calls the `PyThreadState.on_delete` callback. Previously, that happened in `PyThreadState_Delete()`.

void **PyThreadState_Delete**(*PyThreadState* *tstate)

Part of the Stable ABI. Destroy a thread state object. The global interpreter lock need not be held. The thread state must have been reset with a previous call to `PyThreadState_Clear()`.

void **PyThreadState_DeleteCurrent**(void)

Destroy the current thread state and release the global interpreter lock. Like `PyThreadState_Delete()`, the global interpreter lock need not be held. The thread state must have been reset with a previous call to `PyThreadState_Clear()`.

PyFrameObject ***PyThreadState_GetFrame** (*PyThreadState* *tstate)

Part of the [Stable ABI](#) since version 3.10. Get the current frame of the Python thread state tstate.

Return a *strong reference*. Return NULL if no frame is currently executing.

也請見 *PyEval_GetFrame()*。

tstate 不可 [F] NULL。

3.9 版新加入。

uint64_t **PyThreadState_GetID** (*PyThreadState* *tstate)

Part of the [Stable ABI](#) since version 3.10. Get the unique thread state identifier of the Python thread state tstate.

tstate 不可 [F] NULL。

3.9 版新加入。

PyInterpreterState ***PyThreadState_GetInterpreter** (*PyThreadState* *tstate)

Part of the [Stable ABI](#) since version 3.10. Get the interpreter of the Python thread state tstate.

tstate 不可 [F] NULL。

3.9 版新加入。

PyInterpreterState ***PyInterpreterState_Get** (void)

Part of the [Stable ABI](#) since version 3.9. 获取当前解释器。

Issue a fatal error if there no current Python thread state or no current interpreter. It cannot return NULL.

呼叫者必须持有 GIL。

3.9 版新加入。

int64_t **PyInterpreterState_GetID** (*PyInterpreterState* *interp)

Part of the [Stable ABI](#) since version 3.7. Return the interpreter's unique ID. If there was any error in doing so then -1 is returned and an error is set.

呼叫者必须持有 GIL。

3.7 版新加入。

PyObject ***PyInterpreterState_GetDict** (*PyInterpreterState* *interp)

Part of the [Stable ABI](#) since version 3.8. Return a dictionary in which interpreter-specific data may be stored. If this function returns NULL then no exception has been raised and the caller should assume no interpreter-specific dict is available.

This is not a replacement for *PyModule_GetState()*, which extensions should use to store interpreter-specific state information.

3.8 版新加入。

typedef *PyObject* *(***_PyFrameEvalFunction**) (*PyThreadState* *tstate, *PyFrameObject* *frame, int throwflag)

Type of a frame evaluation function.

The *throwflag* parameter is used by the *throw()* method of generators: if non-zero, handle the current exception.

3.9 版更變: 此函数现在可接受一个 tstate 形参。

_PyFrameEvalFunction **_PyInterpreterState_GetEvalFrameFunc** (*PyInterpreterState* *interp)

Get the frame evaluation function.

See the [PEP 523](#) "Adding a frame evaluation API to CPython".

3.9 版新加入。

void **_PyInterpreterState_SetEvalFrameFunc** (*PyInterpreterState* *interp, *_PyFrameEvalFunction* eval_frame)

Set the frame evaluation function.

See the [PEP 523](#) "Adding a frame evaluation API to CPython".

3.9 版新加入.

PyObject ***PyThreadState_GetDict** ()

Return value: Borrowed reference. Part of the [Stable ABI](#). Return a dictionary in which extensions can store thread-specific state information. Each extension should use a unique key to use to store state in the dictionary. It is okay to call this function when no current thread state is available. If this function returns NULL, no exception has been raised and the caller should assume no current thread state is available.

int **PyThreadState_SetAsyncExc** (unsigned long *id*, *PyObject* **exc*)

Part of the [Stable ABI](#). Asynchronously raise an exception in a thread. The *id* argument is the thread id of the target thread; *exc* is the exception object to be raised. This function does not steal any references to *exc*. To prevent naive misuse, you must write your own C extension to call this. Must be called with the GIL held. Returns the number of thread states modified; this is normally one, but will be zero if the thread id isn't found. If *exc* is NULL, the pending exception (if any) for the thread is cleared. This raises no exceptions.

3.7 版更變: The type of the *id* parameter changed from long to unsigned long.

void **PyEval_AcquireThread** (*PyThreadState* **tstate*)

Part of the [Stable ABI](#). Acquire the global interpreter lock and set the current thread state to *tstate*, which must not be NULL. The lock must have been created earlier. If this thread already has the lock, deadlock ensues.

備註: Calling this function from a thread when the runtime is finalizing will terminate the thread, even if the thread was not created by Python. You can use `_Py_IsFinalizing()` or `sys.is_finalizing()` to check if the interpreter is in process of being finalized before calling this function to avoid unwanted termination.

3.8 版更變: Updated to be consistent with `PyEval_RestoreThread()`, `Py_END_ALLOW_THREADS()`, and `PyGILState_Ensure()`, and terminate the current thread if called while the interpreter is finalizing.

`PyEval_RestoreThread()` is a higher-level function which is always available (even when threads have not been initialized).

void **PyEval_ReleaseThread** (*PyThreadState* **tstate*)

Part of the [Stable ABI](#). Reset the current thread state to NULL and release the global interpreter lock. The lock must have been created earlier and must be held by the current thread. The *tstate* argument, which must not be NULL, is only used to check that it represents the current thread state --- if it isn't, a fatal error is reported.

`PyEval_SaveThread()` is a higher-level function which is always available (even when threads have not been initialized).

void **PyEval_AcquireLock** ()

Part of the [Stable ABI](#). Acquire the global interpreter lock. The lock must have been created earlier. If this thread already has the lock, a deadlock ensues.

3.2 版後已用: This function does not update the current thread state. Please use `PyEval_RestoreThread()` or `PyEval_AcquireThread()` instead.

備註: Calling this function from a thread when the runtime is finalizing will terminate the thread, even if the thread was not created by Python. You can use `_Py_IsFinalizing()` or `sys.is_finalizing()` to check if the interpreter is in process of being finalized before calling this function to avoid unwanted termination.

3.8 版更變: Updated to be consistent with `PyEval_RestoreThread()`, `Py_END_ALLOW_THREADS()`, and `PyGILState_Ensure()`, and terminate the current thread if called while the interpreter is finalizing.

void **PyEval_ReleaseLock** ()

Part of the [Stable ABI](#). Release the global interpreter lock. The lock must have been created earlier.

3.2 版 後 已 用: This function does not update the current thread state. Please use `PyEval_SaveThread()` or `PyEval_ReleaseThread()` instead.

9.6 子解释器支持

While in most uses, you will only embed a single Python interpreter, there are cases where you need to create several independent interpreters in the same process and perhaps even in the same thread. Sub-interpreters allow you to do that.

The “main” interpreter is the first one created when the runtime initializes. It is usually the only Python interpreter in a process. Unlike sub-interpreters, the main interpreter has unique process-global responsibilities like signal handling. It is also responsible for execution during runtime initialization and is usually the active interpreter during runtime finalization. The `PyInterpreterState_Main()` function returns a pointer to its state.

You can switch between sub-interpreters using the `PyThreadState_Swap()` function. You can create and destroy them using the following functions:

`PyThreadState *Py_NewInterpreter()`

Part of the Stable ABI. Create a new sub-interpreter. This is an (almost) totally separate environment for the execution of Python code. In particular, the new interpreter has separate, independent versions of all imported modules, including the fundamental modules `builtins`, `__main__` and `sys`. The table of loaded modules (`sys.modules`) and the module search path (`sys.path`) are also separate. The new environment has no `sys.argv` variable. It has new standard I/O stream file objects `sys.stdin`, `sys.stdout` and `sys.stderr` (however these refer to the same underlying file descriptors).

The return value points to the first thread state created in the new sub-interpreter. This thread state is made in the current thread state. Note that no actual thread is created; see the discussion of thread states below. If creation of the new interpreter is unsuccessful, `NULL` is returned; no exception is set since the exception state is stored in the current thread state and there may not be a current thread state. (Like all other Python/C API functions, the global interpreter lock must be held before calling this function and is still held when it returns; however, unlike most other Python/C API functions, there needn't be a current thread state on entry.)

Extension modules are shared between (sub-)interpreters as follows:

- For modules using multi-phase initialization, e.g. `PyModule_FromDefAndSpec()`, a separate module object is created and initialized for each interpreter. Only C-level static and global variables are shared between these module objects.
- For modules using single-phase initialization, e.g. `PyModule_Create()`, the first time a particular extension is imported, it is initialized normally, and a (shallow) copy of its module's dictionary is squirreled away. When the same extension is imported by another (sub-)interpreter, a new module is initialized and filled with the contents of this copy; the extension's `init` function is not called. Objects in the module's dictionary thus end up shared across (sub-)interpreters, which might cause unwanted behavior (see *Bugs and caveats* below).

Note that this is different from what happens when an extension is imported after the interpreter has been completely re-initialized by calling `Py_FinalizeEx()` and `Py_Initialize()`; in that case, the extension's `inittestmodule` function is called again. As with multi-phase initialization, this means that only C-level static and global variables are shared between these modules.

`void Py_EndInterpreter(PyThreadState *tstate)`

Part of the Stable ABI. Destroy the (sub-)interpreter represented by the given thread state. The given thread state must be the current thread state. See the discussion of thread states below. When the call returns, the current thread state is `NULL`. All thread states associated with this interpreter are destroyed. (The global interpreter lock must be held before calling this function and is still held when it returns.) `Py_FinalizeEx()` will destroy all sub-interpreters that haven't been explicitly destroyed at that point.

9.6.1 错误和警告

Because sub-interpreters (and the main interpreter) are part of the same process, the insulation between them isn't perfect --- for example, using low-level file operations like `os.close()` they can (accidentally or maliciously) affect each other's open files. Because of the way extensions are shared between (sub-)interpreters, some extensions may not work properly; this is especially likely when using single-phase initialization or (static) global variables. It is possible to insert objects created in one sub-interpreter into a namespace of another (sub-)interpreter; this should be avoided if possible.

Special care should be taken to avoid sharing user-defined functions, methods, instances or classes between sub-interpreters, since import operations executed by such objects may affect the wrong (sub-)interpreter's dictionary of loaded modules. It is equally important to avoid sharing objects from which the above are reachable.

Also note that combining this functionality with `PyGILState_*` APIs is delicate, because these APIs assume a bijection between Python thread states and OS-level threads, an assumption broken by the presence of sub-interpreters. It is highly recommended that you don't switch sub-interpreters between a pair of matching `PyGILState_Ensure()` and `PyGILState_Release()` calls. Furthermore, extensions (such as `ctypes`) using these APIs to allow calling of Python code from non-Python created threads will probably be broken when using sub-interpreters.

9.7 异步通知

A mechanism is provided to make asynchronous notifications to the main interpreter thread. These notifications take the form of a function pointer and a void pointer argument.

int **Py_AddPendingCall** (int (**func*)) void*

, void **arg* Part of the [Stable ABI](#). Schedule a function to be called from the main interpreter thread. On success, 0 is returned and *func* is queued for being called in the main thread. On failure, -1 is returned without setting any exception.

When successfully queued, *func* will be *eventually* called from the main interpreter thread with the argument *arg*. It will be called asynchronously with respect to normally running Python code, but with both these conditions met:

- on a *bytecode* boundary;
- with the main thread holding the *global interpreter lock* (*func* can therefore use the full C API).

func must return 0 on success, or -1 on failure with an exception set. *func* won't be interrupted to perform another asynchronous notification recursively, but it can still be interrupted to switch threads if the global interpreter lock is released.

This function doesn't need a current thread state to run, and it doesn't need the global interpreter lock.

To call this function in a subinterpreter, the caller must hold the GIL. Otherwise, the function *func* can be scheduled to be called from the wrong interpreter.

警告: This is a low-level function, only useful for very special cases. There is no guarantee that *func* will be called as quick as possible. If the main thread is busy executing a system call, *func* won't be called before the system call returns. This function is generally **not** suitable for calling Python code from arbitrary C threads. Instead, use the [PyGILState API](#).

3.9 版更變: If this function is called in a subinterpreter, the function *func* is now scheduled to be called from the subinterpreter, rather than being called from the main interpreter. Each subinterpreter now has its own list of scheduled calls.

3.1 版新加入.

9.8 分析和跟踪

The Python interpreter provides some low-level support for attaching profiling and execution tracing facilities. These are used for profiling, debugging, and coverage analysis tools.

This C interface allows the profiling or tracing code to avoid the overhead of calling through Python-level callable objects, making a direct C function call instead. The essential attributes of the facility have not changed; the interface allows trace functions to be installed per-thread, and the basic events reported to the trace function are the same as had been reported to the Python-level trace functions in previous versions.

typedef int (*Py_tracefunc) (PyObject *obj, PyFrameObject *frame, int what, PyObject *arg)

The type of the trace function registered using `PyEval_SetProfile()` and `PyEval_SetTrace()`. The first parameter is the object passed to the registration function as *obj*, *frame* is the frame object to which the event pertains, *what* is one of the constants `PyTrace_CALL`, `PyTrace_EXCEPTION`, `PyTrace_LINE`, `PyTrace_RETURN`, `PyTrace_C_CALL`, `PyTrace_C_EXCEPTION`, `PyTrace_C_RETURN`, or `PyTrace_OPCODE`, and *arg* depends on the value of *what*:

<i>what</i> 的值	<i>arg</i> 的含义
<code>PyTrace_CALL</code>	总是 <code>Py_None</code> .
<code>PyTrace_EXCEPTION</code>	<code>sys.exc_info()</code> 返回的异常信息。
<code>PyTrace_LINE</code>	总是 <code>Py_None</code> .
<code>PyTrace_RETURN</code>	返回给调用方的值, 或者如果是由异常导致的则返回 <code>NULL</code> 。
<code>PyTrace_C_CALL</code>	正在调用函数对象。
<code>PyTrace_C_EXCEPTION</code>	正在调用函数对象。
<code>PyTrace_C_RETURN</code>	正在调用函数对象。
<code>PyTrace_OPCODE</code>	总是 <code>Py_None</code> .

int `PyTrace_CALL`

The value of the *what* parameter to a `Py_tracefunc` function when a new call to a function or method is being reported, or a new entry into a generator. Note that the creation of the iterator for a generator function is not reported as there is no control transfer to the Python bytecode in the corresponding frame.

int `PyTrace_EXCEPTION`

The value of the *what* parameter to a `Py_tracefunc` function when an exception has been raised. The callback function is called with this value for *what* when after any bytecode is processed after which the exception becomes set within the frame being executed. The effect of this is that as exception propagation causes the Python stack to unwind, the callback is called upon return to each frame as the exception propagates. Only trace functions receives these events; they are not needed by the profiler.

int `PyTrace_LINE`

The value passed as the *what* parameter to a `Py_tracefunc` function (but not a profiling function) when a line-number event is being reported. It may be disabled for a frame by setting `f_trace_lines` to 0 on that frame.

int `PyTrace_RETURN`

The value for the *what* parameter to `Py_tracefunc` functions when a call is about to return.

int `PyTrace_C_CALL`

The value for the *what* parameter to `Py_tracefunc` functions when a C function is about to be called.

int `PyTrace_C_EXCEPTION`

The value for the *what* parameter to `Py_tracefunc` functions when a C function has raised an exception.

int `PyTrace_C_RETURN`

The value for the *what* parameter to `Py_tracefunc` functions when a C function has returned.

int `PyTrace_OPCODE`

The value for the *what* parameter to `Py_tracefunc` functions (but not profiling functions) when a new opcode is about to be executed. This event is not emitted by default: it must be explicitly requested by setting `f_trace_opcodes` to 1 on the frame.

void **PyEval_SetProfile** (*Py_tracefunc func*, *PyObject *obj*)

Set the profiler function to *func*. The *obj* parameter is passed to the function as its first parameter, and may be any Python object, or NULL. If the profile function needs to maintain state, using a different value for *obj* for each thread provides a convenient and thread-safe place to store it. The profile function is called for all monitored events except `PyTrace_LINE`, `PyTrace_OPCODE` and `PyTrace_EXCEPTION`.

The caller must hold the *GIL*.

void **PyEval_SetTrace** (*Py_tracefunc func*, *PyObject *obj*)

Set the tracing function to *func*. This is similar to `PyEval_SetProfile()`, except the tracing function does receive line-number events and per-opcode events, but does not receive any event related to C function objects being called. Any trace function registered using `PyEval_SetTrace()` will not receive `PyTrace_C_CALL`, `PyTrace_C_EXCEPTION` or `PyTrace_C_RETURN` as a value for the *what* parameter.

The caller must hold the *GIL*.

9.9 高级调试器支持

These functions are only intended to be used by advanced debugging tools.

PyInterpreterState ***PyInterpreterState_Head** ()

Return the interpreter state object at the head of the list of all such objects.

PyInterpreterState ***PyInterpreterState_Main** ()

Return the main interpreter state object.

PyInterpreterState ***PyInterpreterState_Next** (*PyInterpreterState *interp*)

Return the next interpreter state object after *interp* from the list of all such objects.

PyThreadState ***PyInterpreterState_ThreadHead** (*PyInterpreterState *interp*)

Return the pointer to the first *PyThreadState* object in the list of threads associated with the interpreter *interp*.

PyThreadState ***PyThreadState_Next** (*PyThreadState *tstate*)

Return the next thread state object after *tstate* from the list of all such objects belonging to the same *PyInterpreterState* object.

9.10 线程本地存储支持

The Python interpreter provides low-level support for thread-local storage (TLS) which wraps the underlying native TLS implementation to support the Python-level thread local storage API (`threading.local`). The CPython C level APIs are similar to those offered by pthreads and Windows: use a thread key and functions to associate a `void*` value per thread.

The GIL does *not* need to be held when calling these functions; they supply their own locking.

Note that `Python.h` does not include the declaration of the TLS APIs, you need to include `pythread.h` to use thread-local storage.

備 註: None of these API functions handle memory management on behalf of the `void*` values. You need to allocate and deallocate them yourself. If the `void*` values happen to be *PyObject**, these functions don't do refcount operations on them either.

9.10.1 Thread Specific Storage (TSS) API

TSS API is introduced to supersede the use of the existing TLS API within the CPython interpreter. This API uses a new type `Py_tss_t` instead of `int` to represent thread keys.

3.7 版新加入.

也参考:

”A New C-API for Thread-Local Storage in CPython” (PEP 539)

type `Py_tss_t`

This data structure represents the state of a thread key, the definition of which may depend on the underlying TLS implementation, and it has an internal field representing the key’s initialization state. There are no public members in this structure.

When `Py_LIMITED_API` is not defined, static allocation of this type by `Py_tss_NEEDS_INIT` is allowed.

`Py_tss_NEEDS_INIT`

This macro expands to the initializer for `Py_tss_t` variables. Note that this macro won’t be defined with `Py_LIMITED_API`.

Dynamic Allocation

Dynamic allocation of the `Py_tss_t`, required in extension modules built with `Py_LIMITED_API`, where static allocation of this type is not possible due to its implementation being opaque at build time.

`Py_tss_t *PyThread_tss_alloc()`

Part of the Stable ABI since version 3.7. Return a value which is the same state as a value initialized with `Py_tss_NEEDS_INIT`, or `NULL` in the case of dynamic allocation failure.

void `PyThread_tss_free(Py_tss_t *key)`

Part of the Stable ABI since version 3.7. Free the given `key` allocated by `PyThread_tss_alloc()`, after first calling `PyThread_tss_delete()` to ensure any associated thread locals have been unassigned. This is a no-op if the `key` argument is `NULL`.

備[Ⓕ]: A freed key becomes a dangling pointer. You should reset the key to `NULL`.

方法

The parameter `key` of these functions must not be `NULL`. Moreover, the behaviors of `PyThread_tss_set()` and `PyThread_tss_get()` are undefined if the given `Py_tss_t` has not been initialized by `PyThread_tss_create()`.

int `PyThread_tss_is_created(Py_tss_t *key)`

Part of the Stable ABI since version 3.7. Return a non-zero value if the given `Py_tss_t` has been initialized by `PyThread_tss_create()`.

int `PyThread_tss_create(Py_tss_t *key)`

Part of the Stable ABI since version 3.7. Return a zero value on successful initialization of a TSS key. The behavior is undefined if the value pointed to by the `key` argument is not initialized by `Py_tss_NEEDS_INIT`. This function can be called repeatedly on the same key -- calling it on an already initialized key is a no-op and immediately returns success.

void `PyThread_tss_delete(Py_tss_t *key)`

Part of the Stable ABI since version 3.7. Destroy a TSS key to forget the values associated with the key across all threads, and change the key’s initialization state to uninitialized. A destroyed key is able to be initialized again by `PyThread_tss_create()`. This function can be called repeatedly on the same key -- calling it on an already destroyed key is a no-op.

int **PyThread_tss_set** (*Py_tss_t* *key, void *value)

Part of the [Stable ABI](#) since version 3.7. Return a zero value to indicate successfully associating a void* value with a TSS key in the current thread. Each thread has a distinct mapping of the key to a void* value.

void ***PyThread_tss_get** (*Py_tss_t* *key)

Part of the [Stable ABI](#) since version 3.7. Return the void* value associated with a TSS key in the current thread. This returns NULL if no value is associated with the key in the current thread.

9.10.2 Thread Local Storage (TLS) API

3.7 版後已 用: This API is superseded by *Thread Specific Storage (TSS) API*.

備 注: This version of the API does not support platforms where the native TLS key is defined in a way that cannot be safely cast to int. On such platforms, *PyThread_create_key()* will return immediately with a failure status, and the other TLS functions will all be no-ops on such platforms.

由于上面提到的兼容性问题，不应在新代码中使用此版本的 API。

int **PyThread_create_key** ()

Part of the [Stable ABI](#).

void **PyThread_delete_key** (int key)

Part of the [Stable ABI](#).

int **PyThread_set_key_value** (int key, void *value)

Part of the [Stable ABI](#).

void ***PyThread_get_key_value** (int key)

Part of the [Stable ABI](#).

void **PyThread_delete_key_value** (int key)

Part of the [Stable ABI](#).

void **PyThread_ReInitTLS** ()

Part of the [Stable ABI](#).

Python 初始化配置

3.8 版新加入.

Python 可以使用 `Py_InitializeFromConfig()` 和 `PyConfig` 结构体来初始化。它可以使用 `Py_PreInitialize()` 和 `PyPreConfig` 结构体来预初始化。

有两种配置方式:

- The *Python Configuration* can be used to build a customized Python which behaves as the regular Python. For example, environment variables and command line arguments are used to configure Python.
- The *Isolated Configuration* can be used to embed Python into an application. It isolates Python from the system. For example, environment variables are ignored, the LC_CTYPE locale is left unchanged and no signal handler is registered.

`Py_RunMain()` 函数可被用来编写定制的 Python 程序。

参见 *Initialization, Finalization, and Threads*.

也参考:

PEP 587 "Python 初始化配置".

10.1 范例

定制的 Python 的示例总是会以隔离模式运行:

```
int main(int argc, char **argv)
{
    PyStatus status;

    PyConfig config;
    PyConfig_InitPythonConfig(&config);
    config.isolated = 1;

    /* Decode command line arguments.
       Implicitly preinitialize Python (in isolated mode). */
    status = PyConfig_SetBytesArgv(&config, argc, argv);
    if (PyStatus_Exception(status)) {
        goto exception;
    }
}
```

(下页继续)

(繼續上一頁)

```

}

status = Py_InitializeFromConfig(&config);
if (PyStatus_Exception(status)) {
    goto exception;
}
PyConfig_Clear(&config);

return Py_RunMain();

exception:
PyConfig_Clear(&config);
if (PyStatus_IsExit(status)) {
    return status.exitcode;
}
/* Display the error message and exit the process with
   non-zero exit code */
Py_ExitStatusException(status);
}

```

10.2 PyWideStringList

type **PyWideStringList**

由 `wchar_t*` 字符串组成的列表。

如果 *length* 为非零值，则 *items* 必须不为 NULL 并且所有字符串均必须不为 NULL。

方法

PyStatus **PyWideStringList_Append** (*PyWideStringList* **list*, **const** *wchar_t* **item*)

将 *item* 添加到 *list*。

Python 必须被预初始化以便调用此函数。

PyStatus **PyWideStringList_Insert** (*PyWideStringList* **list*, *Py_ssize_t* *index*, **const** *wchar_t* **item*)

将 *item* 插入到 *list* 的 *index* 位置上。

如果 *index* 大于等于 *list* 的长度，则将 *item* 添加到 *list*。

index must be greater than or equal to 0.

Python 必须被预初始化以便调用此函数。

Structure fields:

Py_ssize_t **length**

List 长度。

wchar_t ****items**

列表项目。

10.3 PyStatus

type **PyStatus**

Structure to store an initialization function status: success, error or exit.

For an error, it can store the C function name which created the error.

Structure fields:

int **exitcode**

Exit code. Argument passed to `exit()`.

const char ***err_msg**

錯誤訊息。

const char ***func**

Name of the function which created an error, can be NULL.

Functions to create a status:

PyStatus **PyStatus_Ok** (void)

完成。

PyStatus **PyStatus_Error** (const char **err_msg*)

Initialization error with a message.

err_msg 不可_F NULL。

PyStatus **PyStatus_NoMemory** (void)

Memory allocation failure (out of memory).

PyStatus **PyStatus_Exit** (int *exitcode*)

以指定的退出代碼退出 Python。

Functions to handle a status:

int **PyStatus_Exception** (*PyStatus* *status*)

Is the status an error or an exit? If true, the exception must be handled; by calling *Py_ExitStatusException()* for example.

int **PyStatus_IsError** (*PyStatus* *status*)

結果錯誤嗎?

int **PyStatus_IsExit** (*PyStatus* *status*)

結果是否退出?

void **Py_ExitStatusException** (*PyStatus* *status*)

Call `exit(exitcode)` if *status* is an exit. Print the error message and exit with a non-zero exit code if *status* is an error. Must only be called if `PyStatus_Exception(status)` is non-zero.

備_F: Internally, Python uses macros which set `PyStatus.func`, whereas functions to create a status set `func` to NULL.

範例:

```
PyStatus alloc(void **ptr, size_t size)
{
    *ptr = PyMem_RawMalloc(size);
    if (*ptr == NULL) {
        return PyStatus_NoMemory();
    }
    return PyStatus_Ok();
}

int main(int argc, char **argv)
```

(下页继续)

(繼續上一頁)

```

{
    void *ptr;
    PyStatus status = alloc(&ptr, 16);
    if (PyStatus_Exception(status)) {
        Py_ExitStatusException(status);
    }
    PyMem_Free(ptr);
    return 0;
}

```

10.4 PyPreConfig

type **PyPreConfig**

Structure used to preinitialize Python.

Function to initialize a preconfiguration:

void **PyPreConfig_InitPythonConfig** (*PyPreConfig *preconfig*)

Initialize the preconfiguration with *Python Configuration*.

void **PyPreConfig_InitIsolatedConfig** (*PyPreConfig *preconfig*)

Initialize the preconfiguration with *Isolated Configuration*.

Structure fields:

int **allocator**

Name of the Python memory allocators:

- PYMEM_ALLOCATOR_NOT_SET (0): don't change memory allocators (use defaults).
- PYMEM_ALLOCATOR_DEFAULT (1): *default memory allocators*.
- PYMEM_ALLOCATOR_DEBUG (2): *default memory allocators with debug hooks*.
- PYMEM_ALLOCATOR_MALLOC (3): use `malloc()` of the C library.
- PYMEM_ALLOCATOR_MALLOC_DEBUG (4): force usage of `malloc()` with *debug hooks*.
- PYMEM_ALLOCATOR_PYMALLOC (5): *Python pymalloc memory allocator*.
- PYMEM_ALLOCATOR_PYMALLOC_DEBUG (6): *Python pymalloc memory allocator with debug hooks*.

PYMEM_ALLOCATOR_PYMALLOC and PYMEM_ALLOCATOR_PYMALLOC_DEBUG are not supported if Python is configured using `--without-pymalloc`.

請見記憶體管理。

預設: PYMEM_ALLOCATOR_NOT_SET。

int **configure_locale**

Set the LC_CTYPE locale to the user preferred locale.

If equals to 0, set *coerce_c_locale* and *coerce_c_locale_warn* members to 0.

請見*locale encoding*。

Default: 1 in Python config, 0 in isolated config.

int **coerce_c_locale**

If equals to 2, coerce the C locale.

If equals to 1, read the LC_CTYPE locale to decide if it should be coerced.

請見*locale encoding*。

Default: -1 in Python config, 0 in isolated config.

int **coerce_c_locale_warn**

If non-zero, emit a warning if the C locale is coerced.

Default: -1 in Python config, 0 in isolated config.

int **dev_mode**

If non-zero, enables the Python Development Mode: see *PyConfig.dev_mode*.

Default: -1 in Python mode, 0 in isolated mode.

int **isolated**

Isolated mode: see *PyConfig.isolated*.

Default: 0 in Python mode, 1 in isolated mode.

int **legacy_windows_fs_encoding**

如果不 0:

- 將 *PyPreConfig.utf8_mode* 設 0、
- 將 *PyConfig.filesystem_encoding* 設 "mbcs"、
- 將 *PyConfig.filesystem_errors* 設 "replace"。

Initialized the from PYTHONLEGACYWINDOWSFSENCODING environment variable value.

Only available on Windows. #ifdef MS_WINDOWS macro can be used for Windows specific code.

預設: 0。

int **parse_argv**

If non-zero, *Py_PreInitializeFromArgs()* and *Py_PreInitializeFromBytesArgs()* parse their argv argument the same way the regular Python parses command line arguments: see Command Line Arguments.

Default: 1 in Python config, 0 in isolated config.

int **use_environment**

Use environment variables? See *PyConfig.use_environment*.

Default: 1 in Python config and 0 in isolated config.

int **utf8_mode**

If non-zero, enable the Python UTF-8 Mode.

Set by the -X utf8 command line option and the PYTHONUTF8 environment variable.

Default: -1 in Python config and 0 in isolated config.

10.5 Preinitialize Python with PyPreConfig

The preinitialization of Python:

- Set the Python memory allocators (*PyPreConfig allocator*)
- Configure the LC_CTYPE locale (*locale encoding*)
- Set the Python UTF-8 Mode (*PyPreConfig.utf8_mode*)

The current preconfiguration (PyPreConfig type) is stored in *_PyRuntime.preconfig*.

Functions to preinitialize Python:

PyStatus **Py_PreInitialize** (const *PyPreConfig* *preconfig)

Preinitialize Python from *preconfig* preconfiguration.

preconfig 不可 NULL。

PyStatus **Py_PreInitializeFromBytesArgs** (*const PyPreConfig *preconfig*, *int argc*, *char *const *argv*)

Preinitialize Python from *preconfig* preconfiguration.

Parse *argv* command line arguments (bytes strings) if *parse_argv* of *preconfig* is non-zero.

preconfig 不可 `NULL`。

PyStatus **Py_PreInitializeFromArgs** (*const PyPreConfig *preconfig*, *int argc*, *wchar_t *const *argv*)

Preinitialize Python from *preconfig* preconfiguration.

Parse *argv* command line arguments (wide strings) if *parse_argv* of *preconfig* is non-zero.

preconfig 不可 `NULL`。

The caller is responsible to handle exceptions (error or exit) using `PyStatus_Exception()` and `Py_ExitStatusException()`.

For *Python Configuration* (`PyPreConfig_InitPythonConfig()`), if Python is initialized with command line arguments, the command line arguments must also be passed to preinitialize Python, since they have an effect on the pre-configuration like encodings. For example, the `-X utf8` command line option enables the Python UTF-8 Mode.

`PyMem_SetAllocator()` can be called after `Py_PreInitialize()` and before `Py_InitializeFromConfig()` to install a custom memory allocator. It can be called before `Py_PreInitialize()` if `PyPreConfig.allocator` is set to `PYMEM_ALLOCATOR_NOT_SET`.

Python memory allocation functions like `PyMem_RawMalloc()` must not be used before the Python preinitialization, whereas calling directly `malloc()` and `free()` is always safe. `Py_DecodeLocale()` must not be called before the Python preinitialization.

Example using the preinitialization to enable the Python UTF-8 Mode:

```
PyStatus status;
PyPreConfig preconfig;
PyPreConfig_InitPythonConfig(&preconfig);

preconfig.utf8_mode = 1;

status = Py_PreInitialize(&preconfig);
if (PyStatus_Exception(status)) {
    Py_ExitStatusException(status);
}

/* at this point, Python speaks UTF-8 */

Py_Initialize();
/* ... use Python API here ... */
Py_Finalize();
```

10.6 PyConfig

type **PyConfig**

Structure containing most parameters to configure Python.

When done, the `PyConfig_Clear()` function must be used to release the configuration memory.

Structure methods:

void **PyConfig_InitPythonConfig** (*PyConfig *config*)

Initialize configuration with the *Python Configuration*.

void **PyConfig_InitIsolatedConfig** (*PyConfig *config*)

Initialize configuration with the *Isolated Configuration*.

PyStatus PyConfig_SetString (*PyConfig* *config, wchar_t *const *config_str, const wchar_t *str)

Copy the wide character string *str* into *config_str.

Preinitialize Python if needed.

PyStatus PyConfig_SetBytesString (*PyConfig* *config, wchar_t *const *config_str, const char *str)

Decode *str* using *Py_DecodeLocale*() and set the result into *config_str.

Preinitialize Python if needed.

PyStatus PyConfig_SetArgv (*PyConfig* *config, int argc, wchar_t *const *argv)

Set command line arguments (*argv* member of *config*) from the *argv* list of wide character strings.

Preinitialize Python if needed.

PyStatus PyConfig_SetBytesArgv (*PyConfig* *config, int argc, char *const *argv)

Set command line arguments (*argv* member of *config*) from the *argv* list of bytes strings. Decode bytes using *Py_DecodeLocale*() .

Preinitialize Python if needed.

PyStatus PyConfig_SetWideStringList (*PyConfig* *config, *PyWideStringList* *list, *Py_ssize_t* length, wchar_t **items)

Set the list of wide strings *list* to *length* and *items*.

Preinitialize Python if needed.

PyStatus PyConfig_Read (*PyConfig* *config)

Read all Python configuration.

Fields which are already initialized are left unchanged.

The *PyConfig_Read*() function only parses *PyConfig.argv* arguments once: *PyConfig.parse_argv* is set to 2 after arguments are parsed. Since Python arguments are stripped from *PyConfig.argv*, parsing arguments twice would parse the application options as Python options.

Preinitialize Python if needed.

3.10 版 更 變: The *PyConfig.argv* arguments are now only parsed once, *PyConfig.parse_argv* is set to 2 after arguments are parsed, and arguments are only parsed if *PyConfig.parse_argv* equals 1.

void PyConfig_Clear (*PyConfig* *config)

Release configuration memory.

Most *PyConfig* methods *preinitialize Python* if needed. In that case, the Python preinitialization configuration (*PyPreConfig*) is based on the *PyConfig*. If configuration fields which are in common with *PyPreConfig* are tuned, they must be set before calling a *PyConfig* method:

- *PyConfig.dev_mode*
- *PyConfig.isolated*
- *PyConfig.parse_argv*
- *PyConfig.use_environment*

Moreover, if *PyConfig_SetArgv*() or *PyConfig_SetBytesArgv*() is used, this method must be called before other methods, since the preinitialization configuration depends on command line arguments (if *parse_argv* is non-zero).

The caller of these methods is responsible to handle exceptions (error or exit) using *PyStatus_Exception*() and *Py_ExitStatusException*() .

Structure fields:

PyWideStringList **argv**

Command line arguments: *sys.argv*.

Set `parse_argv` to 1 to parse `argv` the same way the regular Python parses Python command line arguments and then to strip Python arguments from `argv`.

If `argv` is empty, an empty string is added to ensure that `sys.argv` always exists and is never empty.

預設值: `NULL`。

See also the `orig_argv` member.

`wchar_t *base_exec_prefix`
`sys.base_exec_prefix`。

預設值: `NULL`。

Part of the *Python Path Configuration* output.

`wchar_t *base_executable`
Python base executable: `sys._base_executable`.

Set by the `__PYENVN__LAUNCHER__` environment variable.

Set from `PyConfig.executable` if `NULL`.

預設值: `NULL`。

Part of the *Python Path Configuration* output.

`wchar_t *base_prefix`
`sys.base_prefix`。

預設值: `NULL`。

Part of the *Python Path Configuration* output.

`int buffered_stdio`

If equals to 0 and `configure_c_stdio` is non-zero, disable buffering on the C streams `stdout` and `stderr`.

Set to 0 by the `-u` command line option and the `PYTHONUNBUFFERED` environment variable.

`stdin` is always opened in buffered mode.

預設值: 1。

`int bytes_warning`

If equals to 1, issue a warning when comparing `bytes` or `bytearray` with `str`, or comparing `bytes` with `int`.

If equal or greater to 2, raise a `BytesWarning` exception in these cases.

Incremented by the `-b` command line option.

預設: 0。

`int warn_default_encoding`

If non-zero, emit a `EncodingWarning` warning when `io.TextIOWrapper` uses its default encoding. See `io-encoding-warning` for details.

預設: 0。

3.10 版新加入。

`wchar_t *check_hash_pycs_mode`

Control the validation behavior of hash-based `.pyc` files: value of the `--check-hash-based-pycs` command line option.

Valid values:

- `L"always"`: Hash the source file for invalidation regardless of value of the `'check_source'` flag.
- `L"never"`: Assume that hash-based pycs always are valid.
- `L"default"`: The `'check_source'` flag in hash-based pycs determines invalidation.

預設: `L"default"`。

参见 [PEP 552](#) "Deterministic pycs"。

int `configure_c_stdio`

If non-zero, configure C standard streams:

- On Windows, set the binary mode (`O_BINARY`) on `stdin`, `stdout` and `stderr`.
- If `buffered_stdio` equals zero, disable buffering of `stdin`, `stdout` and `stderr` streams.
- If `interactive` is non-zero, enable stream buffering on `stdin` and `stdout` (only `stdout` on Windows).

Default: 1 in Python config, 0 in isolated config.

int `dev_mode`

If non-zero, enable the Python Development Mode.

Default: -1 in Python mode, 0 in isolated mode.

int `dump_refs`

转储 Python 引用?

If non-zero, dump all objects which are still alive at exit.

Set to 1 by the `PYTHONDUMPREFS` environment variable.

Need a special build of Python with the `Py_TRACE_REFS` macro defined: see the `configure --with-trace-refs` option.

預設: 0。

wchar_t *`exec_prefix`

The site-specific directory prefix where the platform-dependent Python files are installed: `sys.exec_prefix`.

預設值: `NULL`。

Part of the *Python Path Configuration* output.

wchar_t *`executable`

The absolute path of the executable binary for the Python interpreter: `sys.executable`.

預設值: `NULL`。

Part of the *Python Path Configuration* output.

int `faulthandler`

Enable `faulthandler`?

If non-zero, call `faulthandler.enable()` at startup.

Set to 1 by `-X faulthandler` and the `PYTHONFAULTHANDLER` environment variable.

Default: -1 in Python mode, 0 in isolated mode.

wchar_t *`filesystem_encoding`

Filesystem encoding: `sys.getfilesystemencoding()`.

On macOS, Android and VxWorks: use "utf-8" by default.

On Windows: use "utf-8" by default, or "mbcs" if *legacy_windows_fs_encoding* of *PyPreConfig* is non-zero.

Default encoding on other platforms:

- "utf-8" if *PyPreConfig.utf8_mode* is non-zero.
- "ascii" if Python detects that `nl_langinfo(CODESET)` announces the ASCII encoding, whereas the `mbstowcs()` function decodes from a different encoding (usually Latin1).
- "utf-8" if `nl_langinfo(CODESET)` returns an empty string.

- Otherwise, use the *locale encoding*: `nl_langinfo(CODESET)` result.

At Python startup, the encoding name is normalized to the Python codec name. For example, "ANSI_X3.4-1968" is replaced with "ascii".

参见 *filesystem_errors* 的成员。

`wchar_t *filesystem_errors`

Filesystem error handler: `sys.getfilesystemencodeerrors()`.

On Windows: use "surrogatepass" by default, or "replace" if *legacy_windows_fs_encoding* of *PyPreConfig* is non-zero.

On other platforms: use "surrogateescape" by default.

Supported error handlers:

- "strict"
- "surrogateescape"
- "surrogatepass" (仅支持 UTF-8 编码格式)

参见 *filesystem_encoding* 的成员。

unsigned long **hash_seed**

int **use_hash_seed**

Randomized hash function seed.

If *use_hash_seed* is zero, a seed is chosen randomly at Python startup, and *hash_seed* is ignored.

Set by the PYTHONHASHSEED environment variable.

Default *use_hash_seed* value: -1 in Python mode, 0 in isolated mode.

`wchar_t *home`

Python home directory.

If *Py_SetPythonHome()* has been called, use its argument if it is not NULL.

Set by the PYTHONHOME environment variable.

預設值: NULL。

Part of the *Python Path Configuration* input.

int **import_time**

If non-zero, profile import time.

Set the 1 by the `-X importtime` option and the PYTHONPROFILEIMPORTTIME environment variable.

預設: 0。

int **inspect**

Enter interactive mode after executing a script or a command.

If greater than 0, enable inspect: when a script is passed as first argument or the `-c` option is used, enter interactive mode after executing the script or the command, even when `sys.stdin` does not appear to be a terminal.

Incremented by the `-i` command line option. Set to 1 if the PYTHONINSPECT environment variable is non-empty.

預設: 0。

int **install_signal_handlers**

Install Python signal handlers?

Default: 1 in Python mode, 0 in isolated mode.

int interactive

If greater than 0, enable the interactive mode (REPL).

Incremented by the `-i` command line option.

預設: 0。

int isolated

If greater than 0, enable isolated mode:

- `sys.path` contains neither the script's directory (computed from `argv[0]` or the current directory) nor the user's site-packages directory.
- Python REPL doesn't import `readline` nor enable default readline configuration on interactive prompts.
- Set `use_environment` and `user_site_directory` to 0.

Default: 0 in Python mode, 1 in isolated mode.

也請見 `PyPreConfig.isolated`。

int legacy_windows_stdio

If non-zero, use `io.FileIO` instead of `io.WindowsConsoleIO` for `sys.stdin`, `sys.stdout` and `sys.stderr`.

Set to 1 if the `PYTHONLEGACYWINDOWSSTDIO` environment variable is set to a non-empty string.

Only available on Windows. `#ifdef MS_WINDOWS` macro can be used for Windows specific code.

預設: 0。

See also the [PEP 528](#) (Change Windows console encoding to UTF-8).

int malloc_stats

If non-zero, dump statistics on *Python pymalloc memory allocator* at exit.

Set to 1 by the `PYTHONMALLOCSTATS` environment variable.

The option is ignored if Python is configured using the `--without-pymalloc` option.

預設: 0。

wchar_t *platlibdir

Platform library directory name: `sys.platlibdir`.

Set by the `PYTHONPLATLIBDIR` environment variable.

Default: value of the `PLATLIBDIR` macro which is set by the configure `--with-platlibdir` option (default: "lib").

Part of the *Python Path Configuration* input.

3.9 版新加入。

wchar_t *pythonpath_env

Module search paths (`sys.path`) as a string separated by `DELIM` (`os.path.pathsep`).

Set by the `PYTHONPATH` environment variable.

預設值: `NULL`。

Part of the *Python Path Configuration* input.

PyWideStringList* module_search_paths*int module_search_paths_set**

Module search paths: `sys.path`.

If `module_search_paths_set` is equal to 0, the function calculating the *Python Path Configuration* overrides the `module_search_paths` and sets `module_search_paths_set` to 1.

Default: empty list (`module_search_paths`) and 0 (`module_search_paths_set`).

Part of the *Python Path Configuration* output.

int **optimization_level**

Compilation optimization level:

- 0: Peephole optimizer, set `__debug__` to True.
- 1: Level 0, remove assertions, set `__debug__` to False.
- 2: Level 1, strip docstrings.

Incremented by the `-O` command line option. Set to the `PYTHONOPTIMIZE` environment variable value.

預設: 0。

PyWideStringList **orig_argv**

The list of the original command line arguments passed to the Python executable: `sys.orig_argv`.

If `orig_argv` list is empty and `argv` is not a list only containing an empty string, `PyConfig_Read()` copies `argv` into `orig_argv` before modifying `argv` (if `parse_argv` is non-zero).

See also the `argv` member and the `Py_GetArgcArgv()` function.

Default: empty list.

3.10 版新加入。

int **parse_argv**

Parse command line arguments?

If equals to 1, parse `argv` the same way the regular Python parses command line arguments, and strip Python arguments from `argv`.

The `PyConfig_Read()` function only parses `PyConfig.argv` arguments once: `PyConfig.parse_argv` is set to 2 after arguments are parsed. Since Python arguments are stripped from `PyConfig.argv`, parsing arguments twice would parse the application options as Python options.

Default: 1 in Python mode, 0 in isolated mode.

3.10 版更變: The `PyConfig.argv` arguments are now only parsed if `PyConfig.parse_argv` equals to 1.

int **parser_debug**

Parser debug mode. If greater than 0, turn on parser debugging output (for expert only, depending on compilation options).

Incremented by the `-d` command line option. Set to the `PYTHONDEBUG` environment variable value.

預設: 0。

int **pathconfig_warnings**

On Unix, if non-zero, calculating the *Python Path Configuration* can log warnings into `stderr`. If equals to 0, suppress these warnings.

It has no effect on Windows.

Default: 1 in Python mode, 0 in isolated mode.

Part of the *Python Path Configuration* input.

wchar_t ***prefix**

The site-specific directory prefix where the platform independent Python files are installed: `sys.prefix`.

預設值: NULL。

Part of the *Python Path Configuration* output.

wchar_t *program_name

Program name used to initialize *executable* and in early error messages during Python initialization.

- If `Py_SetProgramName()` has been called, use its argument.
- On macOS, use `PYTHONEXECUTABLE` environment variable if set.
- If the `WITH_NEXT_FRAMEWORK` macro is defined, use `__PYENVV_LAUNCHER__` environment variable if set.
- Use `argv[0]` of *argv* if available and non-empty.
- Otherwise, use `L"python"` on Windows, or `L"python3"` on other platforms.

預設值: `NULL`。

Part of the *Python Path Configuration* input.

wchar_t *pycache_prefix

Directory where cached `.pyc` files are written: `sys.pycache_prefix`.

Set by the `-X pycache_prefix=PATH` command line option and the `PYTHONPYCACHEPREFIX` environment variable.

If `NULL`, `sys.pycache_prefix` is set to `None`.

預設值: `NULL`。

int quiet

Quiet mode. If greater than 0, don't display the copyright and version at Python startup in interactive mode.

Incremented by the `-q` command line option.

預設: 0。

wchar_t *run_command

Value of the `-c` command line option.

Used by *Py_RunMain()*.

預設值: `NULL`。

wchar_t *run_filename

Filename passed on the command line: trailing command line argument without `-c` or `-m`.

For example, it is set to `script.py` by the `python3 script.py arg` command.

Used by *Py_RunMain()*.

預設值: `NULL`。

wchar_t *run_module

Value of the `-m` command line option.

Used by *Py_RunMain()*.

預設值: `NULL`。

int show_ref_count

Show total reference count at exit?

Set to 1 by `-X showrefcount` command line option.

Need a debug build of Python (the `PY_REF_DEBUG` macro must be defined).

預設: 0。

int site_import

Import the `site` module at startup?

If equal to zero, disable the import of the module `site` and the site-dependent manipulations of `sys.path` that it entails.

Also disable these manipulations if the `site` module is explicitly imported later (call `site.main()` if you want them to be triggered).

Set to 0 by the `-S` command line option.

`sys.flags.no_site` is set to the inverted value of `site_import`.

預設值: 1。

int skip_source_first_line

If non-zero, skip the first line of the `PyConfig.run_filename` source.

It allows the usage of non-Unix forms of `#!cmd`. This is intended for a DOS specific hack only.

Set to 1 by the `-x` command line option.

預設: 0。

wchar_t *stdio_encoding

wchar_t *stdio_errors

Encoding and encoding errors of `sys.stdin`, `sys.stdout` and `sys.stderr` (but `sys.stderr` always uses "backslashreplace" error handler).

If `Py_SetStandardStreamEncoding()` has been called, use its `error` and `errors` arguments if they are not NULL.

Use the `PYTHONIOENCODING` environment variable if it is non-empty.

Default encoding:

- "UTF-8" if `PyPreConfig.utf8_mode` is non-zero.
- Otherwise, use the *locale encoding*.

Default error handler:

- On Windows: use "surrogateescape".
- "surrogateescape" if `PyPreConfig.utf8_mode` is non-zero, or if the `LC_CTYPE` locale is "C" or "POSIX".
- "strict" otherwise.

int tracemalloc

Enable tracemalloc?

If non-zero, call `tracemalloc.start()` at startup.

Set by `-X tracemalloc=N` command line option and by the `PYTHONTRACEMALLOC` environment variable.

Default: -1 in Python mode, 0 in isolated mode.

int use_environment

Use environment variables?

If equals to zero, ignore the environment variables.

Default: 1 in Python config and 0 in isolated config.

int user_site_directory

If non-zero, add the user site directory to `sys.path`.

Set to 0 by the `-s` and `-I` command line options.

Set to 0 by the `PYTHONNOUSERSITE` environment variable.

Default: 1 in Python mode, 0 in isolated mode.

int verbose

Verbose mode. If greater than 0, print a message each time a module is imported, showing the place (filename or built-in module) from which it is loaded.

If greater or equal to 2, print a message for each file that is checked for when searching for a module. Also provides information on module cleanup at exit.

Incremented by the `-v` command line option.

Set to the `PYTHONVERBOSE` environment variable value.

預設: 0。

PyWideStringList **warnoptions**

Options of the `warnings` module to build warnings filters, lowest to highest priority: `sys.warnoptions`.

The `warnings` module adds `sys.warnoptions` in the reverse order: the last *PyConfig.warnoptions* item becomes the first item of `warnings.filters` which is checked first (highest priority).

The `-W` command line options adds its value to *warnoptions*, it can be used multiple times.

The `PYTHONWARNINGS` environment variable can also be used to add warning options. Multiple options can be specified, separated by commas (,).

Default: empty list.

int write_bytecode

If equal to 0, Python won't try to write `.pyc` files on the import of source modules.

Set to 0 by the `-B` command line option and the `PYTHONDONTWRITEBYTECODE` environment variable.

`sys.dont_write_bytecode` is initialized to the inverted value of *write_bytecode*.

預設值: 1。

PyWideStringList **xoptions**

Values of the `-X` command line options: `sys._xoptions`.

Default: empty list.

If *parse_argv* is non-zero, *argv* arguments are parsed the same way the regular Python parses command line arguments, and Python arguments are stripped from *argv*.

The *xoptions* options are parsed to set other options: see the `-X` command line option.

3.9 版更變: The `show_alloc_count` field has been removed.

10.7 Initialization with PyConfig

Function to initialize Python:

PyStatus **Py_InitializeFromConfig**(**const** *PyConfig* **config*)

Initialize Python from *config* configuration.

The caller is responsible to handle exceptions (error or exit) using `PyStatus_Exception()` and `Py_ExitStatusException()`.

If `PyImport_FrozenModules()`, `PyImport_AppendInittab()` or `PyImport_ExtendInittab()` are used, they must be set or called after Python preinitialization and before the Python initialization. If Python is initialized multiple times, `PyImport_AppendInittab()` or `PyImport_ExtendInittab()` must be called before each Python initialization.

The current configuration (*PyConfig* type) is stored in `PyInterpreterState.config`.

Example setting the program name:

```

void init_python(void)
{
    PyStatus status;

    PyConfig config;
    PyConfig_InitPythonConfig(&config);

    /* Set the program name. Implicitly preinitialize Python. */
    status = PyConfig_SetString(&config, &config.program_name,
                               L"/path/to/my_program");
    if (PyStatus_Exception(status)) {
        goto exception;
    }

    status = Py_InitializeFromConfig(&config);
    if (PyStatus_Exception(status)) {
        goto exception;
    }
    PyConfig_Clear(&config);
    return;

exception:
    PyConfig_Clear(&config);
    Py_ExitStatusException(status);
}

```

More complete example modifying the default configuration, read the configuration, and then override some parameters:

```

PyStatus init_python(const char *program_name)
{
    PyStatus status;

    PyConfig config;
    PyConfig_InitPythonConfig(&config);

    /* Set the program name before reading the configuration
       (decode byte string from the locale encoding).

       Implicitly preinitialize Python. */
    status = PyConfig_SetBytesString(&config, &config.program_name,
                                     program_name);
    if (PyStatus_Exception(status)) {
        goto done;
    }

    /* Read all configuration at once */
    status = PyConfig_Read(&config);
    if (PyStatus_Exception(status)) {
        goto done;
    }

    /* Append our custom search path to sys.path */
    status = PyWideStringList_Append(&config.module_search_paths,
                                     L"/path/to/more/modules");
    if (PyStatus_Exception(status)) {
        goto done;
    }

    /* Override executable computed by PyConfig_Read() */
    status = PyConfig_SetString(&config, &config.executable,
                               L"/path/to/my_executable");
}

```

(下页继续)

(繼續上一頁)

```

    if (PyStatus_Exception(status)) {
        goto done;
    }

    status = Py_InitializeFromConfig(&config);

done:
    PyConfig_Clear(&config);
    return status;
}

```

10.8 Isolated Configuration

`PyPreConfig_InitIsolatedConfig()` and `PyConfig_InitIsolatedConfig()` functions create a configuration to isolate Python from the system. For example, to embed Python into an application.

This configuration ignores global configuration variables, environment variables, command line arguments (`PyConfig.argv` is not parsed) and user site directory. The C standard streams (ex: `stdout`) and the `LC_CTYPE` locale are left unchanged. Signal handlers are not installed.

Configuration files are still used with this configuration. Set the *Python Path Configuration* ("output fields") to ignore these configuration files and avoid the function computing the default path configuration.

10.9 Python Configuration

`PyPreConfig_InitPythonConfig()` and `PyConfig_InitPythonConfig()` functions create a configuration to build a customized Python which behaves as the regular Python.

Environments variables and command line arguments are used to configure Python, whereas global configuration variables are ignored.

This function enables C locale coercion (**PEP 538**) and Python UTF-8 Mode (**PEP 540**) depending on the `LC_CTYPE` locale, `PYTHONUTF8` and `PYTHONCOERCECLOCALE` environment variables.

10.10 Python Path Configuration

`PyConfig` contains multiple fields for the path configuration:

- 路徑配置輸入：
 - `PyConfig.home`
 - `PyConfig.platlibdir`
 - `PyConfig.pathconfig_warnings`
 - `PyConfig.program_name`
 - `PyConfig.pythonpath_env`
 - current working directory: to get absolute paths
 - `PATH` environment variable to get the program full path (from `PyConfig.program_name`)
 - `__PYENV_LAUNCHER__` 環境變數
 - (Windows only) Application paths in the registry under "SoftwarePythonPythonCoreX.YPythonPath" of `HKEY_CURRENT_USER` and `HKEY_LOCAL_MACHINE` (where X.Y is the Python version).

- Path configuration output fields:

- `PyConfig.base_exec_prefix`
- `PyConfig.base_executable`
- `PyConfig.base_prefix`
- `PyConfig.exec_prefix`
- `PyConfig.executable`
- `PyConfig.module_search_paths_set`, `PyConfig.module_search_paths`
- `PyConfig.prefix`

If at least one "output field" is not set, Python calculates the path configuration to fill unset fields. If `module_search_paths_set` is equal to 0, `module_search_paths` is overridden and `module_search_paths_set` is set to 1.

It is possible to completely ignore the function calculating the default path configuration by setting explicitly all path configuration output fields listed above. A string is considered as set even if it is non-empty. `module_search_paths` is considered as set if `module_search_paths_set` is set to 1. In this case, path configuration input fields are ignored as well.

Set `pathconfig_warnings` to 0 to suppress warnings when calculating the path configuration (Unix only, Windows does not log any warning).

If `base_prefix` or `base_exec_prefix` fields are not set, they inherit their value from `prefix` and `exec_prefix` respectively.

`Py_RunMain()` and `Py_Main()` modify `sys.path`:

- If `run_filename` is set and is a directory which contains a `__main__.py` script, prepend `run_filename` to `sys.path`.
- If `isolated` is zero:
 - If `run_module` is set, prepend the current directory to `sys.path`. Do nothing if the current directory cannot be read.
 - If `run_filename` is set, prepend the directory of the filename to `sys.path`.
 - Otherwise, prepend an empty string to `sys.path`.

If `site_import` is non-zero, `sys.path` can be modified by the `site` module. If `user_site_directory` is non-zero and the user's site-package directory exists, the `site` module appends the user's site-package directory to `sys.path`.

The following configuration files are used by the path configuration:

- `pyvenv.cfg`
- `python._pth` (仅 Windows)
- `pybuilddir.txt` (仅 Unix)

The `__PYENVN_LAUNCHER__` environment variable is used to set `PyConfig.base_executable`

10.11 Py_RunMain()

int **Py_RunMain** (void)

Execute the command (*PyConfig.run_command*), the script (*PyConfig.run_filename*) or the module (*PyConfig.run_module*) specified on the command line or in the configuration.

By default and when if `-i` option is used, run the REPL.

Finally, finalizes Python and returns an exit status that can be passed to the `exit()` function.

See *Python Configuration* for an example of customized Python always running in isolated mode using *Py_RunMain()*.

10.12 Py_GetArgcArgv()

void **Py_GetArgcArgv** (int *argc, wchar_t ***argv)

Get the original command line arguments, before Python modified them.

See also *PyConfig.orig_argv* member.

10.13 Multi-Phase Initialization Private Provisional API

This section is a private provisional API introducing multi-phase initialization, the core feature of **PEP 432**:

- "Core" initialization phase, "bare minimum Python":
 - Builtin types;
 - Builtin exceptions;
 - Builtin and frozen modules;
 - The `sys` module is only partially initialized (ex: `sys.path` doesn't exist yet).
- "Main" initialization phase, Python is fully initialized:
 - Install and configure `importlib`;
 - Apply the *Path Configuration*;
 - Install signal handlers;
 - Finish `sys` module initialization (ex: create `sys.stdout` and `sys.path`);
 - Enable optional features like `faulthandler` and `tracemalloc`;
 - Import the `site` module;
 - 等等.

私有临时 API:

- `PyConfig._init_main`: if set to 0, *Py_InitializeFromConfig()* stops at the "Core" initialization phase.
- `PyConfig._isolated_interpreter`: if non-zero, disallow threads, subprocesses and fork.

PyStatus **_Py_InitializeMain** (void)

Move to the "Main" initialization phase, finish the Python initialization.

No module is imported during the "Core" phase and the `importlib` module is not configured: the *Path Configuration* is only applied during the "Main" phase. It may allow to customize Python in Python to override or tune the *Path Configuration*, maybe install a custom `sys.meta_path` importer or an import hook, etc.

It may become possible to calculate the *Path Configuration* in Python, after the Core phase and before the Main phase, which is one of the **PEP 432** motivation.

The "Core" phase is not properly defined: what should be and what should not be available at this phase is not specified yet. The API is marked as private and provisional: the API can be modified or even be removed anytime until a proper public API is designed.

Example running Python code between "Core" and "Main" initialization phases:

```
void init_python(void)
{
    PyStatus status;

    PyConfig config;
    PyConfig_InitPythonConfig(&config);
    config._init_main = 0;

    /* ... customize 'config' configuration ... */

    status = Py_InitializeFromConfig(&config);
    PyConfig_Clear(&config);
    if (PyStatus_Exception(status)) {
        Py_ExitStatusException(status);
    }

    /* Use sys.stderr because sys.stdout is only created
       by _Py_InitializeMain() */
    int res = PyRun_SimpleString(
        "import sys; "
        "print('Run Python code before _Py_InitializeMain', "
        "file=sys.stderr)");
    if (res < 0) {
        exit(1);
    }

    /* ... put more configuration code here ... */

    status = _Py_InitializeMain();
    if (PyStatus_Exception(status)) {
        Py_ExitStatusException(status);
    }
}
```

11.1 總覽

在 Python 中，内存管理涉及到一个包含所有 Python 对象和数据结构的私有堆（heap）。这个私有堆的管理由内部的 Python 内存管理器（*Python memory manager*）保证。Python 内存管理器有不同的组件来处理各种动态存储管理方面的问题，如共享、分割、预分配或缓存。

在最底层，一个原始内存分配器通过与操作系统的内存管理器交互，确保私有堆中有足够的空间来存储所有与 Python 相关的数据。在原始内存分配器的基础上，几个对象特定的分配器在同一堆上运行，并根据每种对象类型的特点实现不同的内存管理策略。例如，整数对象在堆内的管理方式不同于字符串、元组或字典，因为整数需要不同的存储需求和速度与空间的权衡。因此，Python 内存管理器将一些工作分配给对象特定分配器，但确保后者在私有堆的范围内运行。

Python 堆内存的管理是由解释器来执行，用户对它没有控制权，即使他们经常操作指向堆内内存块的对象指针，理解这一点十分重要。Python 对象和其他内部缓冲区的堆空间分配是由 Python 内存管理器按需通过本文档中列出的 Python/C API 函数进行的。

为了避免内存破坏，扩展的作者永远不应该试图用 C 库函数导出的函数来对 Python 对象进行操作，这些函数包括：`malloc()`、`calloc()`、`realloc()` 和 `free()`。这将导致 C 分配器和 Python 内存管理器之间的混用，引发严重后果，这是由于它们实现了不同的算法，并在不同的堆上操作。但是，我们可以安全地使用 C 库分配器为单独的目的分配和释放内存块，如下例所示：

```
PyObject *res;
char *buf = (char *) malloc(BUFSIZ); /* for I/O */

if (buf == NULL)
    return PyErr_NoMemory();
...Do some I/O operation involving buf...
res = PyBytes_FromString(buf);
free(buf); /* malloc'ed */
return res;
```

在这个例子中，I/O 缓冲区的内存请求是由 C 库分配器处理的。Python 内存管理器只参与了分配作为结果返回的字节对象。

In most situations, however, it is recommended to allocate memory from the Python heap specifically because the latter is under control of the Python memory manager. For example, this is required when the interpreter is extended with new object types written in C. Another reason for using the Python heap is the desire to *inform* the Python memory manager about the memory needs of the extension module. Even when the requested memory is used

exclusively for internal, highly specific purposes, delegating all memory requests to the Python memory manager causes the interpreter to have a more accurate image of its memory footprint as a whole. Consequently, under certain circumstances, the Python memory manager may or may not trigger appropriate actions, like garbage collection, memory compaction or other preventive procedures. Note that by using the C library allocator as shown in the previous example, the allocated memory for the I/O buffer escapes completely the Python memory manager.

也参考:

环境变量 `PYTHONMALLOC` 可被用来配置 Python 所使用的内存分配器。

环境变量 `PYTHONMALLOCSTATS` 可以用来在每次创建和关闭新的 `pymalloc` 对象区域时打印 `pymalloc` 内存分配器的统计数据。

11.2 分配器域

所有分配函数都属于三个不同的“分配器域”之一（见 `PyMemAllocatorDomain`）。这些域代表了不同的分配策略，并为不同目的进行了优化。每个域如何分配内存和每个域调用哪些内部函数的具体细节被认为是实现细节，但是出于调试目的，可以在[此处](#)找到一张简化的表格。没有硬性要求将属于给定域的分配函数返回的内存，仅用于该域提示的目的（虽然这是推荐的做法）。例如，你可以将 `PyMem_RawMalloc()` 返回的内存用于分配 Python 对象，或者将 `PyObject_Malloc()` 返回的内存用作缓冲区。

三个分配域分别是：

- 原始域：用于为通用内存缓冲区分配内存，分配 * 必须 * 转到系统分配器并且分配器可以在没有 `GIL` 的情况下运行。内存直接请求自系统。
- “Mem”域：用于为 Python 缓冲区和通用内存缓冲区分配内存，分配时必须持有 `GIL`。内存取自于 Python 私有堆。
- 对象域：用于分配属于 Python 对象的内存。内存取自于 Python 私有堆。

当释放属于给定域的分配函数先前分配的内存时，必须使用对应的释放函数。例如，`PyMem_Free()` 来释放 `PyMem_Malloc()` 分配的内存。

11.3 原始内存接口

以下函数集封装了系统分配器。这些函数是线程安全的，不需要持有全局解释器锁。

default raw memory allocator 使用这些函数：`malloc()`、`calloc()`、`realloc()` 和 `free()`；申请零字节时则调用 `malloc(1)`（或 `calloc(1, 1)`）

3.4 版新加入。

void ***PyMem_RawMalloc** (size_t *n*)

Allocates *n* bytes and returns a pointer of type `void*` to the allocated memory, or `NULL` if the request fails.

请求零字节可能返回一个独特的非 `NULL` 指针，就像调用了 `PyMem_RawMalloc(1)` 一样。但是内存不会以任何方式被初始化。

void ***PyMem_RawCalloc** (size_t *nelem*, size_t *elsize*)

Allocates *nelem* elements each whose size in bytes is *elsize* and returns a pointer of type `void*` to the allocated memory, or `NULL` if the request fails. The memory is initialized to zeros.

请求零字节可能返回一个独特的非 `NULL` 指针，就像调用了 `PyMem_RawCalloc(1, 1)` 一样。

3.5 版新加入。

void ***PyMem_RawRealloc** (void **p*, size_t *n*)

将 *p* 指向的内存块大小调整为 *n* 字节。以新旧内存块大小中的最小值为准，其中内容保持不变，

如果 *p* 是 `NULL`，则相当于调用 `PyMem_RawMalloc(n)`；如果 *n* 等于 0，则内存块大小会被调整，但不会被释放，返回非 `NULL` 指针。

除非 p 是 `NULL`，否则它必须是之前调用 `PyMem_RawMalloc()`、`PyMem_RawRealloc()` 或 `PyMem_RawCalloc()` 所返回的。

如果请求失败，`PyMem_RawRealloc()` 返回 `NULL`， p 仍然是指向先前内存区域的有效指针。

void **PyMem_RawFree** (void * p)

释放 p 指向的内存块。 p 必须是之前调用 `PyMem_RawMalloc()`、`PyMem_RawRealloc()` 或 `PyMem_RawCalloc()` 所返回的指针。否则，或在 `PyMem_RawFree(p)` 之前已经调用过的情况下，未定义的行为会发生。

如果 p 是 `NULL`，那么什么操作也不会进行。

11.4 内存接口

以下函数集，仿照 ANSI C 标准，并指定了请求零字节时的行为，可用于从 Python 堆分配和释放内存。

默认内存分配器使用了 `pymalloc` 内存分配器。

警告： 在使用这些函数时，必须持有全局解释器锁（*GIL*）。

3.6 版更變：现在默认的分配器是 `pymalloc` 而非系统的 `malloc()`。

void ***PyMem_Malloc** (size_t n)

Part of the Stable ABI. Allocates n bytes and returns a pointer of type `void*` to the allocated memory, or `NULL` if the request fails.

请求零字节可能返回一个独特的非 `NULL` 指针，就像调用了 `PyMem_Malloc(1)` 一样。但是内存不会以任何方式被初始化。

void ***PyMem_Calloc** (size_t $nelem$, size_t $elsize$)

Part of the Stable ABI since version 3.7. Allocates $nelem$ elements each whose size in bytes is $elsize$ and returns a pointer of type `void*` to the allocated memory, or `NULL` if the request fails. The memory is initialized to zeros.

请求零字节可能返回一个独特的非 `NULL` 指针，就像调用了 `PyMem_Calloc(1, 1)` 一样。

3.5 版新加入。

void ***PyMem_Realloc** (void * p , size_t n)

Part of the Stable ABI. 将 p 指向的内存块大小调整为 n 字节。以新旧内存块大小中的最小值为准，其中内容保持不变，

如果 p 是 `NULL`，则相当于调用 `PyMem_Malloc(n)`；如果 n 等于 0，则内存块大小会被调整，但不会被释放，返回非 `NULL` 指针。

除非 p 是 `NULL`，否则它必须是之前调用 `PyMem_Malloc()`、`PyMem_Realloc()` 或 `PyMem_Calloc()` 所返回的。

如果请求失败，`PyMem_Realloc()` 返回 `NULL`， p 仍然是指向先前内存区域的有效指针。

void **PyMem_Free** (void * p)

Part of the Stable ABI. 释放 p 指向的内存块。 p 必须是之前调用 `PyMem_Malloc()`、`PyMem_Realloc()` 或 `PyMem_Calloc()` 所返回的指针。否则，或在 `PyMem_Free(p)` 之前已经调用过的情况下，未定义的行为会发生。

如果 p 是 `NULL`，那么什么操作也不会进行。

以下面向类型的宏为方便而提供。注意 *TYPE* 可以指任何 C 类型。

TYPE ***PyMem_New** (TYPE, size_t n)

Same as `PyMem_Malloc()`, but allocates $(n * \text{sizeof}(\text{TYPE}))$ bytes of memory. Returns a pointer cast to `TYPE*`. The memory will not have been initialized in any way.

TYPE *PyMem_Resize (void *p, TYPE, size_t n)

Same as *PyMem_Realloc()*, but the memory block is resized to (n * sizeof(TYPE)) bytes. Returns a pointer cast to TYPE*. On return, p will be a pointer to the new memory area, or NULL in the event of failure.

这是一个 C 预处理宏，p 总是被重新赋值。请保存 p 的原始值，以避免在处理错误时丢失内存。

void PyMem_Del (void *p)

和 *PyMem_Free()* 相同。

此外，我们还提供了以下宏集用于直接调用 Python 内存分配器，而不涉及上面列出的 C API 函数。但是请注意，使用它们并不能保证跨 Python 版本的二进制兼容性，因此在扩展模块被弃用。

- PyMem_MALLOC (size)
- PyMem_NEW (type, size)
- PyMem_REALLOC (ptr, size)
- PyMem_RESIZE (ptr, type, size)
- PyMem_FREE (ptr)
- PyMem_DEL (ptr)

11.5 对象分配器

以下函数集，仿照 ANSI C 标准，并指定了请求零字节时的行为，可用于从 Python 堆分配和释放内存。

備註：当通过自定义内存分配器部分描述的方法拦截该域中的分配函数时，无法保证这些分配器返回的内存可以被成功地转换成 Python 对象。

默认对象分配器使用 *pymalloc* 内存分配器。

警告：在使用这些函数时，必须持有全局解释器锁 (GIL)。

void *PyObject_Malloc (size_t n)

Part of the *Stable ABI*. Allocates n bytes and returns a pointer of type void* to the allocated memory, or NULL if the request fails.

请求零字节可能返回一个独特的非 NULL 指针，就像调用了 PyObject_Malloc(1) 一样。但是内存不会以任何方式被初始化。

void *PyObject_Calloc (size_t nelem, size_t elsize)

Part of the *Stable ABI* since version 3.7. Allocates nelem elements each whose size in bytes is elsize and returns a pointer of type void* to the allocated memory, or NULL if the request fails. The memory is initialized to zeros.

请求零字节可能返回一个独特的非 NULL 指针，就像调用了 PyObject_Calloc(1, 1) 一样。

3.5 版新加入。

void *PyObject_Realloc (void *p, size_t n)

Part of the *Stable ABI*. 将 p 指向的内存块大小调整为 n 字节。以新旧内存块大小中的最小值为准，其中内容保持不变，

如果 *p* 是“NULL”，则相当于调用 PyObject_Malloc(n)；如果 n 等于 0，则内存块大小会被调整，但不会被释放，返回非 NULL 指针。

除非 p 是 NULL，否则它必须是之前调用 *PyObject_Malloc()*、*PyObject_Realloc()* 或 *PyObject_Calloc()* 所返回的。

如果请求失败，*PyObject_Realloc()* 返回 NULL，p 仍然是指向先前内存区域的有效指针。

`void PyObject_Free (void *p)`
Part of the Stable ABI. 释放 *p* 指向的内存块。*p* 必须是之前调用 `PyObject_Malloc()`、`PyObject_Realloc()` 或 `PyObject_Calloc()` 所返回的指针。否则，或在 `PyObject_Free(p)` 之前已经调用过的情况下，未定义行为会发生。
如果 *p* 是 `NULL`，那么什么操作也不会进行。

11.6 默认内存分配器

默认内存分配器：

配置	名称	PyMem_RawMalloc	PyMem_Malloc	PyOb- ject_Malloc
发布版本	"pymalloc"	malloc	pymalloc	pymalloc
调试构建	"pymalloc_debug"	malloc + debug	pymalloc + de- bug	pymalloc + de- bug
没有 pymalloc 的发布 版本	"malloc"	malloc	malloc	malloc
没有 pymalloc 的调试 构建	"malloc_debug"	malloc + debug	malloc + debug	malloc + debug

- 说明：
- 名称：PYTHONMALLOC 环境变量的值。
 - malloc：来自 C 标准库的系统分配器，C 函数：`malloc()`、`calloc()`、`realloc()` 和 `free()`。
 - pymalloc：*pymalloc* 内存分配器。
 - "+ debug"：附带 *Python* 内存分配器的调试钩子。
 - “调试构建”：调试模式下的 Python 构建。

11.7 自定义内存分配器

3.4 版新加入。

`type PyMemAllocatorEx`
用于描述内存块分配器的结构体。该结构体下列字段：

域	含意
<code>void *ctx</code>	作为第一个参数传入的用户上下文
<code>void* malloc(void *ctx, size_t size)</code>	分配一个内存块
<code>void* calloc(void *ctx, size_t nelem, size_t elsize)</code>	分配一个初始化为 0 的内存块
<code>void* realloc(void *ctx, void *ptr, size_t new_size)</code>	分配一个内存块或调整其大小
<code>void free(void *ctx, void *ptr)</code>	释放一个内存块

3.5 版更變: The `PyMemAllocator` structure was renamed to *PyMemAllocatorEx* and a new `calloc` field was added.

`type PyMemAllocatorDomain`
用来识别分配器域的枚举类。域有：

`PYMEM_DOMAIN_RAW`
函式：

- `PyMem_RawMalloc()`
- `PyMem_RawRealloc()`
- `PyMem_RawCalloc()`
- `PyMem_RawFree()`

PYMEM_DOMAIN_MEM

函式:

- `PyMem_Malloc()`,
- `PyMem_Realloc()`
- `PyMem_Calloc()`
- `PyMem_Free()`

PYMEM_DOMAIN_OBJ

函式:

- `PyObject_Malloc()`
- `PyObject_Realloc()`
- `PyObject_Calloc()`
- `PyObject_Free()`

void **PyMem_GetAllocator** (*PyMemAllocatorDomain domain, PyMemAllocatorEx *allocator*)

获取指定域的内存块分配器。

void **PyMem_SetAllocator** (*PyMemAllocatorDomain domain, PyMemAllocatorEx *allocator*)

设置指定域的内存块分配器。

当请求零字节时，新的分配器必须返回一个独特的非 NULL 指针。

对于 PYMEM_DOMAIN_RAW 域，分配器必须是线程安全的：当分配器被调用时，不持有全局解释器锁。

如果新的分配器不是钩子（不调用之前的分配器），必须调用 `PyMem_SetupDebugHooks()` 函数在新分配器上重新安装调试钩子。

警告: `PyMem_SetAllocator()` does have the following contract:

- It can be called after `Py_PreInitialize()` and before `Py_InitializeFromConfig()` to install a custom memory allocator. There are no restrictions over the installed allocator other than the ones imposed by the domain (for instance, the Raw Domain allows the allocator to be called without the GIL held). See [the section on allocator domains](#) for more information.
- If called after Python has finish initializing (after `Py_InitializeFromConfig()` has been called) the allocator **must** wrap the existing allocator. Substituting the current allocator for some other arbitrary one is **not supported**.

void **PyMem_SetupDebugHooks** (void)

设置Python 内存分配器的调试钩子 以检测内存错误。

11.8 Python 内存分配器的调试钩子

当 Python 在调试模式下构建，`PyMem_SetupDebugHooks()` 函数在 Python 预初始化时被调用，以在 Python 内存分配器上设置调试钩子以检测内存错误。

PYTHONMALLOC 环境变量可被用于在以发行模式下编译的 Python 上安装调试钩子（例如：PYTHONMALLOC=debug）。

`PyMem_SetupDebugHooks()` 函数可被用于在调用了 `PyMem_SetAllocator()` 之后设置调试钩子。

这些调试钩子用特殊的、可辨认的位模式填充动态分配的内存块。新分配的内存用字节 `0xCD`（`PYMEM_CLEANBYTE`）填充，释放的内存用字节 `0xDD`（`PYMEM_DEADBYTE`）填充。内存块被填充了字节 `0xFD`（`PYMEM_FORBIDDENBYTE`）的“禁止字节”包围。这些字节串不太可能是合法的地址、浮点数或 ASCII 字符串

运行时检查：

- 检测对 API 的违反。例如：检测对 `PyMem_Malloc()` 分配的内存块调用 `PyObject_Free()`。
- 检测缓冲区起始位置前的写入（缓冲区下溢）。
- 检测缓冲区终止位置后的写入（缓冲区溢出）。
- 检测当调用 `PYMEM_DOMAIN_OBJ`（如：`PyObject_Malloc()`）和 `PYMEM_DOMAIN_MEM`（如：`PyMem_Malloc()`）域的分配器函数时 GIL 已被持有。

在出错时，调试钩子使用 `tracemalloc` 模块来回溯内存块被分配的位置。只有当 `tracemalloc` 正在追踪 Python 内存分配，并且内存块被追踪时，才会显示回溯。

让 $S = \text{sizeof}(\text{size_t})$ 。将 $2 \times S$ 个字节添加到每个被请求的 N 字节数据块的两端。内存的布局像是这样，其中 p 代表由类似 `malloc` 或类似 `realloc` 的函数所返回的地址（ $p[i:j]$ 表示从 $*(p+i)$ 左侧开始到 $*(p+j)$ 左侧止的字节数据切片；请注意对负索引号的处理与 Python 切片是不同的）：

$p[-2 \times S:-S]$ 最初所要求的字节数。这是一个 `size_t`，为大端序（易于在内存转储中读取）。

$p[-S]$ API 标识符（ASCII 字符）：

- 'r' 表示 `PYMEM_DOMAIN_RAW`。
- 'm' 表示 `PYMEM_DOMAIN_MEM`。
- 'o' 表示 `PYMEM_DOMAIN_OBJ`。

$p[-S+1:0]$ `PYMEM_FORBIDDENBYTE` 的副本。用于捕获下层的写入和读取。

$p[0:N]$ 所请求的内存，用 `PYMEM_CLEANBYTE` 的副本填充，用于捕获对未初始化内存的引用。当调用 `realloc` 之类的函数来请求更大的内存块时，额外新增的字节也会用 `PYMEM_CLEANBYTE` 来填充。当调用 `free` 之类的函数时，这些字节会用 `PYMEM_DEADBYTE` 来重写，以捕获对已释放内存的引用。当调用 `realloc` 之类的函数来请求更小的内存块时，多余的旧字节也会用 `PYMEM_DEADBYTE` 来填充。

$p[N:N+S]$ `PYMEM_FORBIDDENBYTE` 的副本。用于捕获超限的写入和读取。

$p[N+S:N+2 \times S]$ 仅当定义了 `PYMEM_DEBUG_SERIALNO` 宏时会被使用（默认情况下将不定义）。

一个序列号，每次调用 `malloc` 之类或 `realloc` 之类的函数时自增 1。大端序的 `size_t`。如果之后检测到了“被破坏的内存”，此序列号提供了一个很好的手段用来在下次运行时设置中断点，以捕获该内存块被破坏的瞬间。`obmalloc.c` 中的静态函数 `bumpserialno()` 是此序列号会发生自增的唯一地方，它的存在使你可以方便地设置这样的中断点。

一个 `realloc` 之类或 `free` 之类的函数会先检查两端的 `PYMEM_FORBIDDENBYTE` 字节是否完好。如果它们被改变了，则会将诊断输出写入到 `stderr`，并且程序将通过 `Py_FatalError()` 中止。另一种主要的失败模式是当程序读到某种特殊的比特模式并试图将其用作地址时触发内存错误。如果你随即进入调试器并查看该对象，你很可能会看到它已完全被填充为 `PYMEM_DEADBYTE`（意味着已释放的内存被使用）或 `PYMEM_CLEANBYTE`（意味着未初始货摊内存被使用）。

3.6 版更變: `PyMem_SetupDebugHooks()` 函数现在也能在使用发布模式编译的 Python 上工作。当发生错误时, 调试钩子现在会使用 `tracemalloc` 来获取已分配内存块的回溯信息。调试钩子现在还会在 `PYMEM_DOMAIN_OBJ` 和 `PYMEM_DOMAIN_MEM` 作用域的函数被调用时检查是否持有 GIL。

3.8 版更變: 字节模式 `0xCB` (`PYMEM_CLEANBYTE`)、`0xDB` (`PYMEM_DEADBYTE`) 和 `0xFB` (`PYMEM_FORBIDDENBYTE`) 已被 `0xCD`、`0xDD` 和 `0xFD` 替代以使用与 Windows CRT 调试 `malloc()` 和 `free()` 相同的值。

11.9 pymalloc 分配器

Python 有为具有短生命周期的小对象 (小于或等于 512 字节) 优化的 `pymalloc` 分配器。它使用固定大小为 256 KiB 的称为“arenas”的内存映射。对于大于 512 字节的分配, 它回到使用 `PyMem_RawMalloc()` 和 `PyMem_RawRealloc()`。

`pymalloc` 是 `PYMEM_DOMAIN_MEM` (例如: `PyMem_Malloc()`) 和 `PYMEM_DOMAIN_OBJ` (例如: `PyObject_Malloc()`) 域的默认分配器。

arena 分配器使用以下函数:

- Windows 上的 `VirtualAlloc()` 和 `VirtualFree()`,
- `mmap()` 和 `munmap()`, 如果可用,
- 否则, `malloc()` 和 `free()`。

如果 Python 配置了 `--without-pymalloc` 选项, 那么此分配器将被禁用。也可以在运行时使用 `PYTHONMALLOC` (例如: ```PYTHONMALLOC=malloc```) 环境变量来禁用它。

11.9.1 自定义 pymalloc Arena 分配器

3.4 版新加入。

type `PyObjectArenaAllocator`

用来描述一个 arena 分配器的结构体。这个结构体有三个字段:

域	含意
<code>void *ctx</code>	作为第一个参数传入的用户上下文
<code>void* alloc(void *ctx, size_t size)</code>	分配一块 <code>size</code> 字节的区域
<code>void free(void *ctx, void *ptr, size_t size)</code>	释放一块区域

`void PyObject_GetArenaAllocator (PyObjectArenaAllocator *allocator)`
获取 arena 分配器

`void PyObject_SetArenaAllocator (PyObjectArenaAllocator *allocator)`
设置 arena 分配器

11.10 tracemalloc C API

3.7 版新加入。

`int PyTraceMalloc_Track (unsigned int domain, uintptr_t ptr, size_t size)`

在 `tracemalloc` 模块中跟踪一个已分配的内存块。

成功时返回 0，出错时返回 -1 (无法分配内存来保存跟踪信息)。如果禁用了 `tracemalloc` 则返回 -2。

如果内存块已被跟踪，则更新现有跟踪信息。

`int PyTraceMalloc_Untrack (unsigned int domain, uintptr_t ptr)`

在 `tracemalloc` 模块中取消跟踪一个已分配的内存块。如果内存块未被跟踪则不执行任何操作。

如果 `tracemalloc` 被禁用则返回 -2，否则返回 0。

11.11 范例

以下是来自總覽 小节的示例，经过重写以使 I/O 缓冲区是通过使用第一个函数集从 Python 堆中分配的：

```
PyObject *res;
char *buf = (char *) PyMem_Malloc(BUFSIZ); /* for I/O */

if (buf == NULL)
    return PyErr_NoMemory();
/* ...Do some I/O operation involving buf... */
res = PyBytes_FromString(buf);
PyMem_Free(buf); /* allocated with PyMem_Malloc */
return res;
```

使用面向类型函数集的不同代码：

```
PyObject *res;
char *buf = PyMem_New(char, BUFSIZ); /* for I/O */

if (buf == NULL)
    return PyErr_NoMemory();
/* ...Do some I/O operation involving buf... */
res = PyBytes_FromString(buf);
PyMem_Del(buf); /* allocated with PyMem_New */
return res;
```

请注意在以上两个示例中，缓冲区总是通过归属于相同集的函数来操纵的。事实上，对于一个给定的内存块必须使用相同的内存 API 族，以便使得混合不同分配器的风险减至最低。以下代码序列包含两处错误，其中一个被标记为 *fatal* 因为它混合了两种在不同堆上操作的不同分配器。

```
char *buf1 = PyMem_New(char, BUFSIZ);
char *buf2 = (char *) malloc(BUFSIZ);
char *buf3 = (char *) PyMem_Malloc(BUFSIZ);
...
PyMem_Del(buf3); /* Wrong -- should be PyMem_Free() */
free(buf2);      /* Right -- allocated via malloc() */
free(buf1);      /* Fatal -- should be PyMem_Del() */
```

除了旨在处理来自 Python 堆的原始内存块的函数之外，Python 中的对象是通过 `PyObject_New()`，`PyObject_NewVar()` 和 `PyObject_Del()` 来分配和释放的。

这些将在有关如何在 C 中定义和实现新对象类型的下一章中讲解。

本章描述了定义新对象类型时所使用的函数、类型和宏。

12.1 在堆上分配对象

PyObject ***_PyObject_New** (*PyTypeObject* **type*)

Return value: New reference.

PyVarObject ***_PyObject_NewVar** (*PyTypeObject* **type*, *Py_ssize_t* *size*)

Return value: New reference.

PyObject ***PyObject_Init** (*PyObject* **op*, *PyTypeObject* **type*)

Return value: Borrowed reference. Part of the [Stable ABI](#). Initialize a newly allocated object *op* with its type and initial reference. Returns the initialized object. If *type* indicates that the object participates in the cyclic garbage detector, it is added to the detector's set of observed objects. Other fields of the object are not affected.

PyVarObject ***PyObject_InitVar** (*PyVarObject* **op*, *PyTypeObject* **type*, *Py_ssize_t* *size*)

Return value: Borrowed reference. Part of the [Stable ABI](#). 它的功能和 `PyObject_Init()` 一样，并且会初始化变量大小对象的长度信息。

TYPE ***PyObject_New** (*TYPE*, *PyTypeObject* **type*)

Return value: New reference. 使用 C 结构类型 *TYPE* 和 Python 类型对象 *type* 分配一个新的 Python 对象。未在该 Python 对象标头中定义的字段不会被初始化；对象的引用计数将为一。内存分配大小由 *type* 对象的 `tp_basicsize` 字段来确定。

TYPE ***PyObject_NewVar** (*TYPE*, *PyTypeObject* **type*, *Py_ssize_t* *size*)

Return value: New reference. 使用 C 的数据结构类型 *TYPE* 和 Python 的类型对象 *type* 分配一个新的 Python 对象。Python 对象头文件中没有定义的字段不会被初始化。被分配的内存空间预留了 *TYPE* 结构加 *type* 对象中 `tp_itemsize` 字段提供的 *size* 字段的值。这对于实现类似元组这种能够在构造期决定自己大小的对象是很实用的。将字段的数组嵌入到相同的内存分配中可以减少内存分配的次数，这提高了内存分配的效率。

void **PyObject_Del** (void **op*)

释放由 `PyObject_New()` 或者 `PyObject_NewVar()` 分配内存的对象。这通常由对象的 *type* 字段定义的 `tp_dealloc` 处理函数来调用。调用这个函数以后 *op* 对象中的字段都不可以被访问，因为原分配的内存空间已不再是一个有效的 Python 对象。

PyObject_Py_NoneStruct

这个对象是像 `None` 一样的 Python 对象。它可以使用 `Py_None` 宏访问，该宏的拿到指向该对象的指针。

也参考:

`PyModule_Create()` 分配内存和创建扩展模块

12.2 通用物件結構

大量的结构体被用于定义 Python 的对象类型。这一节描述了这些的结构体和它们的使用方法。

12.2.1 基本的对象类型和宏

所有的 Python 对象都在对象的内存表示的开始部分共享少量的字段。这些字段用 `PyObject` 或 `PyVarObject` 类型来表示，这些类型又由一些宏定义，这些宏也直接或间接地用于所有其他 Python 对象的定义。

type PyObject

Part of the Limited API. (Only some members are part of the stable ABI.) All object types are extensions of this type. This is a type which contains the information Python needs to treat a pointer to an object as an object. In a normal "release" build, it contains only the object's reference count and a pointer to the corresponding type object. Nothing is actually declared to be a `PyObject`, but every pointer to a Python object can be cast to a `PyObject*`. Access to the members must be done by using the macros `Py_REFCNT` and `Py_TYPE`.

type PyVarObject

Part of the Limited API. (Only some members are part of the stable ABI.) This is an extension of `PyObject` that adds the `ob_size` field. This is only used for objects that have some notion of *length*. This type does not often appear in the Python/C API. Access to the members must be done by using the macros `Py_REFCNT`, `Py_TYPE`, and `Py_SIZE`.

PyObject_HEAD

This is a macro used when declaring new types which represent objects without a varying length. The `PyObject_HEAD` macro expands to:

```
PyObject ob_base;
```

See documentation of `PyObject` above.

PyObject_VAR_HEAD

This is a macro used when declaring new types which represent objects with a length that varies from instance to instance. The `PyObject_VAR_HEAD` macro expands to:

```
PyVarObject ob_base;
```

参见上面 `PyVarObject` 的文档。

int Py_Is (const PyObject *x, const PyObject *y)

Part of the Stable ABI since version 3.10. 测试 `x` 是否为 `y` 对象，与 Python 中的 `x is y` 相同。

3.10 版新加入。

int Py_IsNone (const PyObject *x)

Part of the Stable ABI since version 3.10. 测试一个对象是否为 `None` 单例，与 Python 中的 `x is None` 相同。

3.10 版新加入。

int Py_IsTrue (const PyObject *x)

Part of the Stable ABI since version 3.10. 测试一个对象是否为 `True` 单例，与 Python 中的 `x is True` 相同。

3.10 版新加入。

int **Py_IsFalse** (const *PyObject* *x)

Part of the [Stable ABI](#) since version 3.10. 测试一个对象是否为 False 单例，与 Python 中的 `x is False` 相同。

3.10 版新加入。

PyTypeObject ***Py_TYPE** (const *PyObject* *o)

获取 Python 对象 *o* 的类型。

返回一个 *borrowed reference*。

Use the `Py_SET_TYPE()` function to set an object type.

int **Py_IS_TYPE** (*PyObject* *o, *PyTypeObject* *type)

Return non-zero if the object *o* type is *type*. Return zero otherwise. Equivalent to: `Py_TYPE(o) == type`.

3.9 版新加入。

void **Py_SET_TYPE** (*PyObject* *o, *PyTypeObject* *type)

Set the object *o* type to *type*.

3.9 版新加入。

Py_ssize_t **Py_REFCNT** (const *PyObject* *o)

Get the reference count of the Python object *o*.

3.10 版更變: `Py_REFCNT()` is changed to the inline static function. Use `Py_SET_REFCNT()` to set an object reference count.

void **Py_SET_REFCNT** (*PyObject* *o, *Py_ssize_t* refcnt)

Set the object *o* reference counter to *refcnt*.

3.9 版新加入。

Py_ssize_t **Py_SIZE** (const *PyVarObject* *o)

Get the size of the Python object *o*.

Use the `Py_SET_SIZE()` function to set an object size.

void **Py_SET_SIZE** (*PyVarObject* *o, *Py_ssize_t* size)

Set the object *o* size to *size*.

3.9 版新加入。

PyObject_HEAD_INIT (type)

This is a macro which expands to initialization values for a new *PyObject* type. This macro expands to:

```
_PyObject_EXTRA_INIT
1, type,
```

PyVarObject_HEAD_INIT (type, size)

This is a macro which expands to initialization values for a new *PyVarObject* type, including the `ob_size` field. This macro expands to:

```
_PyObject_EXTRA_INIT
1, type, size,
```

12.2.2 Implementing functions and methods

type `PyCFunction`

Part of the [Stable ABI](#). Type of the functions used to implement most Python callables in C. Functions of this type take two `PyObject*` parameters and return one such value. If the return value is `NULL`, an exception shall have been set. If not `NULL`, the return value is interpreted as the return value of the function as exposed in Python. The function must return a new reference.

The function signature is:

```
PyObject *PyCFunction(PyObject *self,
                      PyObject *args);
```

type `PyCFunctionWithKeywords`

Part of the [Stable ABI](#). Type of the functions used to implement Python callables in C with signature `METH_VARARGS | METH_KEYWORDS`. The function signature is:

```
PyObject *PyCFunctionWithKeywords(PyObject *self,
                                   PyObject *args,
                                   PyObject *kwargs);
```

type `_PyCFunctionFast`

Type of the functions used to implement Python callables in C with signature `METH_FASTCALL`. The function signature is:

```
PyObject *_PyCFunctionFast(PyObject *self,
                           PyObject *const *args,
                           Py_ssize_t nargs);
```

type `_PyCFunctionFastWithKeywords`

Type of the functions used to implement Python callables in C with signature `METH_FASTCALL | METH_KEYWORDS`. The function signature is:

```
PyObject *_PyCFunctionFastWithKeywords(PyObject *self,
                                       PyObject *const *args,
                                       Py_ssize_t nargs,
                                       PyObject *kwnames);
```

type `PyMethod`

Type of the functions used to implement Python callables in C with signature `METH_METHOD | METH_FASTCALL | METH_KEYWORDS`. The function signature is:

```
PyObject *PyMethod(PyObject *self,
                   PyTypeObject *defining_class,
                   PyObject *const *args,
                   Py_ssize_t nargs,
                   PyObject *kwnames)
```

3.9 版新加入.

type `PyMethodDef`

Part of the [Stable ABI](#) (including all members). Structure used to describe a method of an extension type. This structure has four fields:

const char *`ml_name`
name of the method

PyCFunction **`ml_meth`**
pointer to the C implementation

int **`ml_flags`**
flags bits indicating how the call should be constructed

```
const char *ml_doc
    points to the contents of the docstring
```

The `ml_meth` is a C function pointer. The functions may be of different types, but they always return `PyObject*`. If the function is not of the `PyCFunction`, the compiler will require a cast in the method table. Even though `PyCFunction` defines the first parameter as `PyObject*`, it is common that the method implementation uses the specific C type of the `self` object.

The `ml_flags` field is a bitfield which can include the following flags. The individual flags indicate either a calling convention or a binding convention.

There are these calling conventions:

METH_VARARGS

This is the typical calling convention, where the methods have the type `PyCFunction`. The function expects two `PyObject*` values. The first one is the `self` object for methods; for module functions, it is the module object. The second parameter (often called `args`) is a tuple object representing all arguments. This parameter is typically processed using `PyArg_ParseTuple()` or `PyArg_UnpackTuple()`.

METH_VARARGS | METH_KEYWORDS

Methods with these flags must be of type `PyCFunctionWithKeywords`. The function expects three parameters: `self`, `args`, `kwargs` where `kwargs` is a dictionary of all the keyword arguments or possibly NULL if there are no keyword arguments. The parameters are typically processed using `PyArg_ParseTupleAndKeywords()`.

METH_FASTCALL

Fast calling convention supporting only positional arguments. The methods have the type `_PyCFunctionFast`. The first parameter is `self`, the second parameter is a C array of `PyObject*` values indicating the arguments and the third parameter is the number of arguments (the length of the array).

3.7 版新加入。

3.10 版更變: `METH_FASTCALL` is now part of the stable ABI.

METH_FASTCALL | METH_KEYWORDS

Extension of `METH_FASTCALL` supporting also keyword arguments, with methods of type `_PyCFunctionFastWithKeywords`. Keyword arguments are passed the same way as in the *vectorcall protocol*: there is an additional fourth `PyObject*` parameter which is a tuple representing the names of the keyword arguments (which are guaranteed to be strings) or possibly NULL if there are no keywords. The values of the keyword arguments are stored in the `args` array, after the positional arguments.

3.7 版新加入。

METH_METHOD | METH_FASTCALL | METH_KEYWORDS

Extension of `METH_FASTCALL | METH_KEYWORDS` supporting the *defining class*, that is, the class that contains the method in question. The defining class might be a superclass of `Py_TYPE(self)`.

The method needs to be of type `PyCMethod`, the same as for `METH_FASTCALL | METH_KEYWORDS` with `defining_class` argument added after `self`.

3.9 版新加入。

METH_NOARGS

Methods without parameters don't need to check whether arguments are given if they are listed with the `METH_NOARGS` flag. They need to be of type `PyCFunction`. The first parameter is typically named `self` and will hold a reference to the module or object instance. In all cases the second parameter will be NULL.

METH_O

Methods with a single object argument can be listed with the `METH_O` flag, instead of invoking `PyArg_ParseTuple()` with a "O" argument. They have the type `PyCFunction`, with the `self` parameter, and a `PyObject*` parameter representing the single argument.

These two constants are not used to indicate the calling convention but the binding when use with methods of classes. These may not be used for functions defined for modules. At most one of these flags may be set for any given method.

METH_CLASS

The method will be passed the type object as the first parameter rather than an instance of the type. This is used to create *class methods*, similar to what is created when using the `classmethod()` built-in function.

METH_STATIC

The method will be passed `NULL` as the first parameter rather than an instance of the type. This is used to create *static methods*, similar to what is created when using the `staticmethod()` built-in function.

One other constant controls whether a method is loaded in place of another definition with the same method name.

METH_COEXIST

The method will be loaded in place of existing definitions. Without *METH_COEXIST*, the default is to skip repeated definitions. Since slot wrappers are loaded before the method table, the existence of a *sq_contains* slot, for example, would generate a wrapped method named `__contains__()` and preclude the loading of a corresponding `PyCFunction` with the same name. With the flag defined, the `PyCFunction` will be loaded in place of the wrapper object and will co-exist with the slot. This is helpful because calls to `PyCFunctions` are optimized more than wrapper object calls.

12.2.3 Accessing attributes of extension types

type PyMemberDef

Part of the [Stable ABI](#) (including all members). Structure which describes an attribute of a type which corresponds to a C struct member. Its fields are:

域	C Type	含意
name	const char *	name of the member
type	int	the type of the member in the C struct
offset	Py_ssize_t	the offset in bytes that the member is located on the type's object struct
flags	int	flag bits indicating if the field should be read-only or writable
doc	const char *	points to the contents of the docstring

`type` can be one of many `T_` macros corresponding to various C types. When the member is accessed in Python, it will be converted to the equivalent Python type.

Macro name	C 类型
<code>T_SHORT</code>	short
<code>T_INT</code>	int
<code>T_LONG</code>	long
<code>T_FLOAT</code>	float
<code>T_DOUBLE</code>	double
<code>T_STRING</code>	const char *
<code>T_OBJECT</code>	PyObject *
<code>T_OBJECT_EX</code>	PyObject *
<code>T_CHAR</code>	char
<code>T_BYTE</code>	char
<code>T_UBYTE</code>	unsigned char
<code>T_UINT</code>	unsigned int
<code>T_USHORT</code>	unsigned short
<code>T_ULONG</code>	unsigned long
<code>T_BOOL</code>	char
<code>T_LONGLONG</code>	long long
<code>T_ULONGLONG</code>	unsigned long long
<code>T_PYSSIZET</code>	Py_ssize_t

`T_OBJECT` and `T_OBJECT_EX` differ in that `T_OBJECT` returns `None` if the member is `NULL` and `T_OBJECT_EX` raises an `AttributeError`. Try to use `T_OBJECT_EX` over `T_OBJECT` because `T_OBJECT_EX` handles use of the `del` statement on that attribute more correctly than `T_OBJECT`.

flags can be 0 for write and read access or READONLY for read-only access. Using T_STRING for type implies READONLY. T_STRING data is interpreted as UTF-8. Only T_OBJECT and T_OBJECT_EX members can be deleted. (They are set to NULL).

Heap allocated types (created using `PyType_FromSpec()` or similar), `PyMemberDef` may contain definitions for the special members `__dictoffset__`, `__weaklistoffset__` and `__vectorcalloffset__`, corresponding to `tp_dictoffset`, `tp_weaklistoffset` and `tp_vectorcall_offset` in type objects. These must be defined with T_PYSSIZET and READONLY, for example:

```
static PyMemberDef spam_type_members[] = {
    {"__dictoffset__", T_PYSSIZET, offsetof(Spam_object, dict), READONLY},
    {NULL} /* Sentinel */
};
```

PyObject *PyMember_GetOne (const char *obj_addr, struct PyMemberDef *m)

Get an attribute belonging to the object at address *obj_addr*. The attribute is described by `PyMemberDef` *m*. Returns NULL on error.

int PyMember_SetOne (char *obj_addr, struct PyMemberDef *m, PyObject *o)

Set an attribute belonging to the object at address *obj_addr* to object *o*. The attribute to set is described by `PyMemberDef` *m*. Returns 0 if successful and a negative value on failure.

type PyGetSetDef

Part of the [Stable ABI](#) (including all members). Structure to define property-like access for a type. See also description of the `PyTypeObject.tp_getset` slot.

域	C Type	含意
名称	const char *	attribute name
get	getter	C function to get the attribute
set	setter	optional C function to set or delete the attribute, if omitted the attribute is readonly
doc	const char *	optional docstring
closure	void *	optional function pointer, providing additional data for getter and setter

The get function takes one *PyObject** parameter (the instance) and a function pointer (the associated closure):

```
typedef PyObject *(*getter) (PyObject *, void *);
```

It should return a new reference on success or NULL with a set exception on failure.

set functions take two *PyObject** parameters (the instance and the value to be set) and a function pointer (the associated closure):

```
typedef int (*setter) (PyObject *, PyObject *, void *);
```

In case the attribute should be deleted the second parameter is NULL. Should return 0 on success or -1 with a set exception on failure.

12.3 类型对象

Perhaps one of the most important structures of the Python object system is the structure that defines a new type: the *PyTypeObject* structure. Type objects can be handled using any of the *PyObject_** or *PyType_** functions, but do not offer much that's interesting to most Python applications. These objects are fundamental to how objects behave, so they are very important to the interpreter itself and to any extension module that implements new types.

与大多数标准类型相比，类型对象相当大。这么大的原因是每个类型对象存储了大量的值，大部分是 C 函数指针，每个指针实现了类型功能的一小部分。本节将详细描述类型对象的字段。这些字段将按照它们在结构中出现的顺序进行描述。

除了下面的快速参考，[範例](#) 小节提供了快速了解 *PyTypeObject* 的含义和用法的例子。

12.3.1 快速参考

“tp_ 方法槽”

PyTypeObject 槽 ¹	Type	特殊方法/属性	信息 ²				
			O	T	D	I	
<R> <i>tp_name</i>	const char *	__name__	X	X			
<i>tp_basicsize</i>	<i>Py_ssize_t</i>		X	X			X
<i>tp_itemsize</i>	<i>Py_ssize_t</i>			X			X
<i>tp_dealloc</i>	destructor		X	X			X
<i>tp_vectorcall_offset</i>	<i>Py_ssize_t</i>			X			X
(<i>tp_getattr</i>)	<i>getattrfunc</i>	__getattribute__, __getattr__					G
(<i>tp_setattr</i>)	<i>setattrfunc</i>	__setattr__, __delattr__					G
<i>tp_as_async</i>	<i>PyAsyncMethods</i> *	子方法槽 (方法域)					%
<i>tp_repr</i>	<i>reprfunc</i>	__repr__	X	X			X
<i>tp_as_number</i>	<i>PyNumberMethods</i> *	子方法槽 (方法域)					%
<i>tp_as_sequence</i>	<i>PySequenceMethods</i> *	子方法槽 (方法域)					%
<i>tp_as_mapping</i>	<i>PyMappingMethods</i> *	子方法槽 (方法域)					%
<i>tp_hash</i>	<i>hashfunc</i>	__hash__	X				G
<i>tp_call</i>	<i>ternaryfunc</i>	__call__		X			X
<i>tp_str</i>	<i>reprfunc</i>	__str__	X				X
<i>tp_getattro</i>	<i>getattrofunc</i>	__getattribute__, __getattr__	X	X			G
<i>tp_setattro</i>	<i>setattrofunc</i>	__setattr__, __delattr__	X	X			G
<i>tp_as_buffer</i>	<i>PyBufferProcs</i> *						%
<i>tp_flags</i>	unsigned long		X	X			?
<i>tp_doc</i>	const char *	__doc__	X	X			
<i>tp_traverse</i>	<i>traverseproc</i>			X			G
<i>tp_clear</i>	<i>inquiry</i>			X			G
<i>tp_richcompare</i>	<i>richcmpfunc</i>	__lt__, __le__, __eq__, __ne__, __gt__, __ge__	X				G
<i>tp_weaklistoffset</i>	<i>Py_ssize_t</i>			X			?
<i>tp_iter</i>	<i>getiterfunc</i>	__iter__					X
<i>tp_iternext</i>	<i>iternextfunc</i>	__next__					X
<i>tp_methods</i>	<i>PyMethodDef</i> []		X	X			
<i>tp_members</i>	<i>PyMemberDef</i> []			X			
<i>tp_getset</i>	<i>PyGetSetDef</i> []		X	X			
<i>tp_base</i>	<i>PyTypeObject</i> *	__base__				X	
<i>tp_dict</i>	<i>PyObject</i> *	__dict__				?	
<i>tp_descr_get</i>	<i>descrgetfunc</i>	__get__					X
<i>tp_descr_set</i>	<i>descrsetfunc</i>	__set__, __delete__					X

下页继续

表 1 – 繼續上一頁

PyTypeObject 槽 ¹	Type	特殊方法/属性	信息 ²				
			O	T	D	I	
<code>tp_dictoffset</code>	<code>Py_ssize_t</code>			X		?	
<code>tp_init</code>	<code>initproc</code>	<code>__init__</code>	X	X		X	
<code>tp_alloc</code>	<code>allocfunc</code>		X		?	?	
<code>tp_new</code>	<code>newfunc</code>	<code>__new__</code>	X	X	?	?	
<code>tp_free</code>	<code>freefunc</code>		X	X	?	?	
<code>tp_is_gc</code>	<code>inquiry</code>			X		X	
<code><tp_bases></code>	<code>PyObject *</code>	<code>__bases__</code>			~		
<code><tp_mro></code>	<code>PyObject *</code>	<code>__mro__</code>			~		
<code>[tp_cache]</code>	<code>PyObject *</code>						
<code>[tp_subclasses]</code>	<code>PyObject *</code>	<code>__subclasses__</code>					
<code>[tp_weaklist]</code>	<code>PyObject *</code>						
<code>(tp_del)</code>	<code>destructor</code>						
<code>[tp_version_tag]</code>	<code>unsigned int</code>						
<code>tp_finalize</code>	<code>destructor</code>	<code>__del__</code>					X
<code>tp_vectorcall</code>	<code>vectorcallfunc</code>						

子方法槽（方法域）

方法槽	Type	特殊方法
<code>am_await</code>	<code>unaryfunc</code>	<code>__await__</code>
<code>am_aiter</code>	<code>unaryfunc</code>	<code>__aiter__</code>
<code>am_anext</code>	<code>unaryfunc</code>	<code>__anext__</code>
<code>am_send</code>	<code>sendfunc</code>	
<code>nb_add</code>	<code>binaryfunc</code>	<code>__add__</code> <code>__radd__</code>
<code>nb_inplace_add</code>	<code>binaryfunc</code>	<code>__iadd__</code>
<code>nb_subtract</code>	<code>binaryfunc</code>	<code>__sub__</code> <code>__rsub__</code>
<code>nb_inplace_subtract</code>	<code>binaryfunc</code>	<code>__isub__</code>
<code>nb_multiply</code>	<code>binaryfunc</code>	<code>__mul__</code> <code>__rmul__</code>
<code>nb_inplace_multiply</code>	<code>binaryfunc</code>	<code>__imul__</code>
<code>nb_remainder</code>	<code>binaryfunc</code>	<code>__mod__</code> <code>__rmod__</code>
<code>nb_inplace_remainder</code>	<code>binaryfunc</code>	<code>__imod__</code>

下页继续

¹ (): A slot name in parentheses indicates it is (effectively) deprecated.

<>: Names in angle brackets should be initially set to NULL and treated as read-only.

[]: Names in square brackets are for internal use only.

<R> (as a prefix) means the field is required (must be non-NULL).

² 列:

"O": PyBaseObject_Type 必须设置

"T": PyType_Type 必须设置

"D": 默认设置 (如果方法槽被设置为 NULL)

X - PyTypeReady sets this value if it is NULL

~ - PyTypeReady always sets this value (it should be NULL)

? - PyTypeReady may set this value depending on other slots

Also see the inheritance column ("I").

"I": 继承

X - type slot is inherited via *PyTypeReady* if defined with a *NULL* value

% - the slots of the sub-struct are inherited individually

G - inherited, but only in combination with other slots; see the slot's description

? - it's complicated; see the slot's description

注意, 有些方法槽是通过普通属性查找链有效继承的。

表 2 - 繼續上一頁

方法槽	Type	特殊方法
<i>nb_divmod</i>	<i>binaryfunc</i>	<code>__divmod__</code> <code>__rdivmod__</code>
<i>nb_power</i>	<i>ternaryfunc</i>	<code>__pow__</code> <code>__rpow__</code>
<i>nb_inplace_power</i>	<i>ternaryfunc</i>	<code>__ipow__</code>
<i>nb_negative</i>	<i>unaryfunc</i>	<code>__neg__</code>
<i>nb_positive</i>	<i>unaryfunc</i>	<code>__pos__</code>
<i>nb_absolute</i>	<i>unaryfunc</i>	<code>__abs__</code>
<i>nb_bool</i>	<i>inquiry</i>	<code>__bool__</code>
<i>nb_invert</i>	<i>unaryfunc</i>	<code>__invert__</code>
<i>nb_lshift</i>	<i>binaryfunc</i>	<code>__lshift__</code> <code>__rlshift__</code>
<i>nb_inplace_lshift</i>	<i>binaryfunc</i>	<code>__ilshift__</code>
<i>nb_rshift</i>	<i>binaryfunc</i>	<code>__rshift__</code> <code>__rrshift__</code>
<i>nb_inplace_rshift</i>	<i>binaryfunc</i>	<code>__irshift__</code>
<i>nb_and</i>	<i>binaryfunc</i>	<code>__and__</code> <code>__rand__</code>
<i>nb_inplace_and</i>	<i>binaryfunc</i>	<code>__iand__</code>
<i>nb_xor</i>	<i>binaryfunc</i>	<code>__xor__</code> <code>__rxor__</code>
<i>nb_inplace_xor</i>	<i>binaryfunc</i>	<code>__ixor__</code>
<i>nb_or</i>	<i>binaryfunc</i>	<code>__or__</code> <code>__ror__</code>
<i>nb_inplace_or</i>	<i>binaryfunc</i>	<code>__ior__</code>
<i>nb_int</i>	<i>unaryfunc</i>	<code>__int__</code>
<i>nb_reserved</i>	void *	
<i>nb_float</i>	<i>unaryfunc</i>	<code>__float__</code>
<i>nb_floor_divide</i>	<i>binaryfunc</i>	<code>__floordiv__</code>
<i>nb_inplace_floor_divide</i>	<i>binaryfunc</i>	<code>__ifloordiv__</code>
<i>nb_true_divide</i>	<i>binaryfunc</i>	<code>__truediv__</code>
<i>nb_inplace_true_divide</i>	<i>binaryfunc</i>	<code>__itruediv__</code>
<i>nb_index</i>	<i>unaryfunc</i>	<code>__index__</code>
<i>nb_matrix_multiply</i>	<i>binaryfunc</i>	<code>__matmul__</code> <code>__rmatmul__</code>
<i>nb_inplace_matrix_multiply</i>	<i>binaryfunc</i>	<code>__imatmul__</code>
<i>mp_length</i>	<i>lenfunc</i>	<code>__len__</code>
<i>mp_subscript</i>	<i>binaryfunc</i>	<code>__getitem__</code>
<i>mp_ass_subscript</i>	<i>objobjargproc</i>	<code>__setitem__</code> , <code>__delitem__</code>
<i>sq_length</i>	<i>lenfunc</i>	<code>__len__</code>
<i>sq_concat</i>	<i>binaryfunc</i>	<code>__add__</code>
<i>sq_repeat</i>	<i>ssizeargfunc</i>	<code>__mul__</code>
<i>sq_item</i>	<i>ssizeargfunc</i>	<code>__getitem__</code>
<i>sq_ass_item</i>	<i>ssizeobjargproc</i>	<code>__setitem__</code> <code>__delitem__</code>
<i>sq_contains</i>	<i>objobjproc</i>	<code>__contains__</code>
<i>sq_inplace_concat</i>	<i>binaryfunc</i>	<code>__iadd__</code>
<i>sq_inplace_repeat</i>	<i>ssizeargfunc</i>	<code>__imul__</code>
<i>bf_getbuffer</i>	<i>getbufferproc()</i>	
<i>bf_releasebuffer</i>	<i>releasebufferproc()</i>	

槽位 typedef

typedef	参数类型	返回类型
<i>allocfunc</i>	<i>PyObject</i> * <i>Py_ssize_t</i>	<i>PyObject</i> *
<i>destructor</i>	void *	void
<i>freefunc</i>	void *	void
<i>traverseproc</i>	void * <i>visitproc</i> void *	int
<i>newfunc</i>	<i>PyObject</i> * <i>PyObject</i> * <i>PyObject</i> *	<i>PyObject</i> *
<i>initproc</i>	<i>PyObject</i> * <i>PyObject</i> * <i>PyObject</i> *	int
<i>reprfunc</i>	<i>PyObject</i> *	<i>PyObject</i> *
<i>getattrfunc</i>	<i>PyObject</i> * const char *	<i>PyObject</i> *
<i>setattrfunc</i>	<i>PyObject</i> * const char * <i>PyObject</i> *	int
<i>getattrofunc</i>	<i>PyObject</i> * <i>PyObject</i> *	<i>PyObject</i> *
<i>setattrofunc</i>	<i>PyObject</i> * <i>PyObject</i> * <i>PyObject</i> *	int
<i>descrgetfunc</i>	<i>PyObject</i> * <i>PyObject</i> * <i>PyObject</i> *	<i>PyObject</i> *
<i>descrsetfunc</i>	<i>PyObject</i> * <i>PyObject</i> *	int
222	<i>PyObject</i> *	Chapter 12. 对象实现支持
<i>hashfunc</i>	<i>PyObject</i> *	Py_hash_t
<i>richcmpfunc</i>		<i>PyObject</i> *

更多細節請見下方的 *Slot Type typedefs*。

12.3.2 PyObject 定义

PyObject 的结构定义可以在 `Include/object.h` 中找到。为了方便参考，此处复述了其中的定义：

```
typedef struct _typeobject {
    PyObject_VAR_HEAD
    const char *tp_name; /* For printing, in format "<module>.<name>" */
    Py_ssize_t tp_basicsize, tp_itemsize; /* For allocation */

    /* Methods to implement standard operations */

    destructor tp_dealloc;
    Py_ssize_t tp_vectorcall_offset;
    getattrofunc tp_getattr;
    setattrofunc tp_setattr;
    PyAsyncMethods *tp_as_async; /* formerly known as tp_compare (Python 2)
                                   or tp_reserved (Python 3) */
    reprfunc tp_repr;

    /* Method suites for standard classes */

    PyNumberMethods *tp_as_number;
    PySequenceMethods *tp_as_sequence;
    PyMappingMethods *tp_as_mapping;

    /* More standard operations (here for binary compatibility) */

    hashfunc tp_hash;
    ternaryfunc tp_call;
    reprfunc tp_str;
    getattrofunc tp_getattro;
    setattrofunc tp_setattro;

    /* Functions to access object as input/output buffer */
    PyBufferProcs *tp_as_buffer;

    /* Flags to define presence of optional/expanded features */
    unsigned long tp_flags;

    const char *tp_doc; /* Documentation string */

    /* Assigned meaning in release 2.0 */
    /* call function for all accessible objects */
    traverseproc tp_traverse;

    /* delete references to contained objects */
    inquiry tp_clear;

    /* Assigned meaning in release 2.1 */
    /* rich comparisons */
    richcmpfunc tp_richcompare;

    /* weak reference enabler */
    Py_ssize_t tp_weaklistoffset;

    /* Iterators */
    getiterfunc tp_iter;
    iternextfunc tp_iternext;
}
```

(下页继续)

```

/* Attribute descriptor and subclassing stuff */
struct PyMethodDef *tp_methods;
struct PyMemberDef *tp_members;
struct PyGetSetDef *tp_getset;
// Strong reference on a heap type, borrowed reference on a static type
struct _typeobject *tp_base;
PyObject *tp_dict;
descrgetfunc tp_descr_get;
descrsetfunc tp_descr_set;
Py_ssize_t tp_dictoffset;
initproc tp_init;
allocfunc tp_alloc;
newfunc tp_new;
freefunc tp_free; /* Low-level free-memory routine */
inquiry tp_is_gc; /* For PyObject_IS_GC */
PyObject *tp_bases;
PyObject *tp_mro; /* method resolution order */
PyObject *tp_cache;
PyObject *tp_subclasses;
PyObject *tp_weaklist;
destructor tp_del;

/* Type attribute cache version tag. Added in version 2.6 */
unsigned int tp_version_tag;

destructor tp_finalize;
vectorcallfunc tp_vectorcall;
} PyTypeObject;

```

12.3.3 PyObject 槽位

类型对象结构扩展了 *PyVarObject* 结构。ob_size 字段用于动态类型 (由 *type_new()* 创建, 通常通过类语句来调用)。注意 *PyType_Type* (元类型) 会初始化 *tp_itemsize*, 这意味着它的实例 (即类型对象) 必须具有 ob_size 字段。

Py_ssize_t PyObject.ob_refcnt

Part of the Stable ABI. 这是类型对象的引用计数, 由 *PyObject_HEAD_INIT* 宏初始化为 1。请注意对于静态分配的类型对象, 类型的实例 (对象的 ob_type 指回该类型) 不会被加入引用计数。但对于动态分配的类型对象, 实例 确实会被算作引用。

继承:

子类型不继承此字段。

*PyTypeObject *PyObject.ob_type*

Part of the Stable ABI. This is the type's type, in other words its metatype. It is initialized by the argument to the *PyObject_HEAD_INIT* macro, and its value should normally be *&PyType_Type*. However, for dynamically loadable extension modules that must be usable on Windows (at least), the compiler complains that this is not a valid initializer. Therefore, the convention is to pass NULL to the *PyObject_HEAD_INIT* macro and to initialize this field explicitly at the start of the module's initialization function, before doing anything else. This is typically done like this:

```
Foo_Type.ob_type = &PyType_Type;
```

This should be done before any instances of the type are created. *PyType_Ready()* checks if ob_type is NULL, and if so, initializes it to the ob_type field of the base class. *PyType_Ready()* will not change this field if it is non-zero.

继承:

此字段会被子类型继承。

`PyObject *PyObject._ob_next`

`PyObject *PyObject._ob_prev`

These fields are only present when the macro `Py_TRACE_REFS` is defined (see the configure `--with-trace-refs` option).

Their initialization to NULL is taken care of by the `PyObject_HEAD_INIT` macro. For *statically allocated objects*, these fields always remain NULL. For *dynamically allocated objects*, these two fields are used to link the object into a doubly linked list of *all* live objects on the heap.

This could be used for various debugging purposes; currently the only uses are the `sys.getobjects()` function and to print the objects that are still alive at the end of a run when the environment variable `PYTHONDUMPREFS` is set.

继承:

这些字段不会被子类型继承。

12.3.4 PyVarObject 槽位

`Py_ssize_t PyVarObject.ob_size`

Part of the Stable ABI. For *statically allocated type objects*, this should be initialized to zero. For *dynamically allocated type objects*, this field has a special internal meaning.

继承:

子类型不继承此字段。

12.3.5 PyTypeObject 槽

Each slot has a section describing inheritance. If `PyType_Ready()` may set a value when the field is set to NULL then there will also be a "Default" section. (Note that many fields set on `PyBaseObject_Type` and `PyType_Type` effectively act as defaults.)

`const char *PyTypeObject.tp_name`

Pointer to a NUL-terminated string containing the name of the type. For types that are accessible as module globals, the string should be the full module name, followed by a dot, followed by the type name; for built-in types, it should be just the type name. If the module is a submodule of a package, the full package name is part of the full module name. For example, a type named `T` defined in module `M` in subpackage `Q` in package `P` should have the `tp_name` initializer `"P.Q.M.T"`.

For *dynamically allocated type objects*, this should just be the type name, and the module name explicitly stored in the type dict as the value for key `'__module__'`.

For *statically allocated type objects*, the `tp_name` field should contain a dot. Everything before the last dot is made accessible as the `__module__` attribute, and everything after the last dot is made accessible as the `__name__` attribute.

If no dot is present, the entire `tp_name` field is made accessible as the `__name__` attribute, and the `__module__` attribute is undefined (unless explicitly set in the dictionary, as explained above). This means your type will be impossible to pickle. Additionally, it will not be listed in module documentations created with `pydoc`.

This field must not be NULL. It is the only required field in `PyTypeObject()` (other than potentially `tp_itemsize`).

继承:

子类型不继承此字段。

`Py_ssize_t PyTypeObject.tp_basicsize`

Py_ssize_t *PyTypeObject.tp_itemsize*

These fields allow calculating the size in bytes of instances of the type.

There are two kinds of types: types with fixed-length instances have a zero *tp_itemsize* field, types with variable-length instances have a non-zero *tp_itemsize* field. For a type with fixed-length instances, all instances have the same size, given in *tp_basicsize*.

For a type with variable-length instances, the instances must have an *ob_size* field, and the instance size is *tp_basicsize* plus N times *tp_itemsize*, where N is the “length” of the object. The value of N is typically stored in the instance’s *ob_size* field. There are exceptions: for example, ints use a negative *ob_size* to indicate a negative number, and N is *abs(ob_size)* there. Also, the presence of an *ob_size* field in the instance layout doesn’t mean that the instance structure is variable-length (for example, the structure for the list type has fixed-length instances, yet those instances have a meaningful *ob_size* field).

The basic size includes the fields in the instance declared by the macro *PyObject_HEAD* or *PyObject_VAR_HEAD* (whichever is used to declare the instance struct) and this in turn includes the *_ob_prev* and *_ob_next* fields if they are present. This means that the only correct way to get an initializer for the *tp_basicsize* is to use the *sizeof* operator on the struct used to declare the instance layout. The basic size does not include the GC header size.

A note about alignment: if the variable items require a particular alignment, this should be taken care of by the value of *tp_basicsize*. Example: suppose a type implements an array of double. *tp_itemsize* is *sizeof(double)*. It is the programmer’s responsibility that *tp_basicsize* is a multiple of *sizeof(double)* (assuming this is the alignment requirement for double).

For any type with variable-length instances, this field must not be NULL.

继承:

These fields are inherited separately by subtypes. If the base type has a non-zero *tp_itemsize*, it is generally not safe to set *tp_itemsize* to a different non-zero value in a subtype (though this depends on the implementation of the base type).

destructor *PyTypeObject.tp_dealloc*

A pointer to the instance destructor function. This function must be defined unless the type guarantees that its instances will never be deallocated (as is the case for the singletons None and Ellipsis). The function signature is:

```
void tp_dealloc(PyObject *self);
```

The destructor function is called by the *Py_DECREF()* and *Py_XDECREF()* macros when the new reference count is zero. At this point, the instance is still in existence, but there are no references to it. The destructor function should free all references which the instance owns, free all memory buffers owned by the instance (using the freeing function corresponding to the allocation function used to allocate the buffer), and call the type’s *tp_free* function. If the type is not subtypable (doesn’t have the *Py_TPFLAGS_BASETYPE* flag bit set), it is permissible to call the object deallocator directly instead of via *tp_free*. The object deallocator should be the one used to allocate the instance; this is normally *PyObject_Del()* if the instance was allocated using *PyObject_New()* or *PyObject_VarNew()*, or *PyObject_GC_Del()* if the instance was allocated using *PyObject_GC_New()* or *PyObject_GC_NewVar()*.

If the type supports garbage collection (has the *Py_TPFLAGS_HAVE_GC* flag bit set), the destructor should call *PyObject_GC_UnTrack()* before clearing any member fields.

```
static void foo_dealloc(foo_object *self) {
    PyObject_GC_UnTrack(self);
    Py_CLEAR(self->ref);
    Py_TYPE(self)->tp_free((PyObject *)self);
}
```

Finally, if the type is heap allocated (*Py_TPFLAGS_HEAPTYPE*), the deallocator should decrement the reference count for its type object after calling the type deallocator. In order to avoid dangling pointers, the recommended way to achieve this is:

```
static void foo_dealloc(foo_object *self) {
    PyTypeObject *tp = Py_TYPE(self);
    // free references and buffers here
    tp->tp_free(self);
    Py_DECREF(tp);
}
```

继承:

此字段会被子类型继承。

Py_ssize_t *PyTypeObject*.**tp_vectorcall_offset**

An optional offset to a per-instance function that implements calling the object using the *vectorcall protocol*, a more efficient alternative of the simpler *tp_call*.

This field is only used if the flag *Py_TPFLAGS_HAVE_VECTORCALL* is set. If so, this must be a positive integer containing the offset in the instance of a *vectorcallfunc* pointer.

The *vectorcallfunc* pointer may be NULL, in which case the instance behaves as if *Py_TPFLAGS_HAVE_VECTORCALL* was not set: calling the instance falls back to *tp_call*.

Any class that sets *Py_TPFLAGS_HAVE_VECTORCALL* must also set *tp_call* and make sure its behaviour is consistent with the *vectorcallfunc* function. This can be done by setting *tp_call* to *PyVectorcall_Call()*.

警告: It is not recommended for *heap types* to implement the vectorcall protocol. When a user sets *__call__* in Python code, only *tp_call* is updated, likely making it inconsistent with the vectorcall function.

3.8 版更變: Before version 3.8, this slot was named *tp_print*. In Python 2.x, it was used for printing to a file. In Python 3.0 to 3.7, it was unused.

继承:

This field is always inherited. However, the *Py_TPFLAGS_HAVE_VECTORCALL* flag is not always inherited. If it's not, then the subclass won't use *vectorcall*, except when *PyVectorcall_Call()* is explicitly called. This is in particular the case for *heap types* (including subclasses defined in Python).

getattrfunc *PyTypeObject*.**tp_getattr**

An optional pointer to the get-attribute-string function.

This field is deprecated. When it is defined, it should point to a function that acts the same as the *tp_getattro* function, but taking a C string instead of a Python string object to give the attribute name.

继承:

分组: *tp_getattr*, *tp_getattro*

This field is inherited by subtypes together with *tp_getattro*: a subtype inherits both *tp_getattr* and *tp_getattro* from its base type when the subtype's *tp_getattr* and *tp_getattro* are both NULL.

setattrfunc *PyTypeObject*.**tp_setattr**

An optional pointer to the function for setting and deleting attributes.

This field is deprecated. When it is defined, it should point to a function that acts the same as the *tp_setattro* function, but taking a C string instead of a Python string object to give the attribute name.

继承:

Group: *tp_setattr*, *tp_setattro*

This field is inherited by subtypes together with *tp_setattro*: a subtype inherits both *tp_setattr* and *tp_setattro* from its base type when the subtype's *tp_setattr* and *tp_setattro* are both NULL.

PyAsyncMethods **PyTypeObject*.**tp_as_async**

Pointer to an additional structure that contains fields relevant only to objects which implement *awaitable* and *asynchronous iterator* protocols at the C-level. See *Async Object Structures* for details.

3.5 版新加入: Formerly known as `tp_compare` and `tp_reserved`.

继承:

The `tp_as_async` field is not inherited, but the contained fields are inherited individually.

reprfunc *PyTypeObject*.**tp_repr**

An optional pointer to a function that implements the built-in function `repr()`.

The signature is the same as for *PyObject_Repr()*:

```
PyObject *tp_repr(PyObject *self);
```

The function must return a string or a Unicode object. Ideally, this function should return a string that, when passed to `eval()`, given a suitable environment, returns an object with the same value. If this is not feasible, it should return a string starting with '`<`' and ending with '`>`' from which both the type and the value of the object can be deduced.

继承:

此字段会被子类型继承。

预设:

When this field is not set, a string of the form `< %s object at %p >` is returned, where `%s` is replaced by the type name, and `%p` by the object's memory address.

PyNumberMethods **PyTypeObject*.**tp_as_number**

Pointer to an additional structure that contains fields relevant only to objects which implement the number protocol. These fields are documented in *Number Object Structures*.

继承:

The `tp_as_number` field is not inherited, but the contained fields are inherited individually.

PySequenceMethods **PyTypeObject*.**tp_as_sequence**

Pointer to an additional structure that contains fields relevant only to objects which implement the sequence protocol. These fields are documented in *Sequence Object Structures*.

继承:

The `tp_as_sequence` field is not inherited, but the contained fields are inherited individually.

PyMappingMethods **PyTypeObject*.**tp_as_mapping**

Pointer to an additional structure that contains fields relevant only to objects which implement the mapping protocol. These fields are documented in *Mapping Object Structures*.

继承:

The `tp_as_mapping` field is not inherited, but the contained fields are inherited individually.

hashfunc *PyTypeObject*.**tp_hash**

An optional pointer to a function that implements the built-in function `hash()`.

The signature is the same as for *PyObject_Hash()*:

```
Py_hash_t tp_hash(PyObject *);
```

The value `-1` should not be returned as a normal return value; when an error occurs during the computation of the hash value, the function should set an exception and return `-1`.

When this field is not set (and `tp_richcompare` is not set), an attempt to take the hash of the object raises `TypeError`. This is the same as setting it to *PyObject_HashNotImplemented()*.

This field can be set explicitly to *PyObject_HashNotImplemented()* to block inheritance of the hash method from a parent type. This is interpreted as the equivalent of `__hash__ = None` at the Python

level, causing `isinstance(o, collections.Hashable)` to correctly return `False`. Note that the converse is also true - setting `__hash__ = None` on a class at the Python level will result in the `tp_hash` slot being set to `PyObject_HashNotImplemented()`.

继承:

Group: `tp_hash`, `tp_richcompare`

This field is inherited by subtypes together with `tp_richcompare`: a subtype inherits both of `tp_richcompare` and `tp_hash`, when the subtype's `tp_richcompare` and `tp_hash` are both `NULL`.

ternaryfunc `PyTypeObject.tp_call`

An optional pointer to a function that implements calling the object. This should be `NULL` if the object is not callable. The signature is the same as for `PyObject_Call()`:

```
PyObject *tp_call(PyObject *self, PyObject *args, PyObject *kwargs);
```

继承:

此字段会被子类型继承。

reprfunc `PyTypeObject.tp_str`

An optional pointer to a function that implements the built-in operation `str()`. (Note that `str` is a type now, and `str()` calls the constructor for that type. This constructor calls `PyObject_Str()` to do the actual work, and `PyObject_Str()` will call this handler.)

The signature is the same as for `PyObject_Str()`:

```
PyObject *tp_str(PyObject *self);
```

The function must return a string or a Unicode object. It should be a "friendly" string representation of the object, as this is the representation that will be used, among other things, by the `print()` function.

继承:

此字段会被子类型继承。

预设:

When this field is not set, `PyObject_Repr()` is called to return a string representation.

getattrfunc `PyTypeObject.tp_getattro`

An optional pointer to the get-attribute function.

The signature is the same as for `PyObject_GetAttr()`:

```
PyObject *tp_getattro(PyObject *self, PyObject *attr);
```

It is usually convenient to set this field to `PyObject_GenericGetAttr()`, which implements the normal way of looking for object attributes.

继承:

分组: `tp_getattr`, `tp_getattro`

This field is inherited by subtypes together with `tp_getattr`: a subtype inherits both `tp_getattr` and `tp_getattro` from its base type when the subtype's `tp_getattr` and `tp_getattro` are both `NULL`.

预设:

`PyBaseObject_Type` uses `PyObject_GenericGetAttr()`.

setattrfunc `PyTypeObject.tp_setattro`

An optional pointer to the function for setting and deleting attributes.

The signature is the same as for `PyObject_SetAttr()`:

```
int tp_setattro(PyObject *self, PyObject *attr, PyObject *value);
```

In addition, setting *value* to NULL to delete an attribute must be supported. It is usually convenient to set this field to `PyObject_GenericSetAttr()`, which implements the normal way of setting object attributes.

繼承:

Group: `tp_setattr`, `tp_setattro`

This field is inherited by subtypes together with `tp_setattr`: a subtype inherits both `tp_setattr` and `tp_setattro` from its base type when the subtype's `tp_setattr` and `tp_setattro` are both NULL.

預設:

`PyBaseObject_Type` 使用 `PyObject_GenericSetAttr()`.

PyBufferProcs *`PyTypeObject.tp_as_buffer`

Pointer to an additional structure that contains fields relevant only to objects which implement the buffer interface. These fields are documented in *Buffer Object Structures*.

繼承:

The `tp_as_buffer` field is not inherited, but the contained fields are inherited individually.

unsigned long `PyTypeObject.tp_flags`

This field is a bit mask of various flags. Some flags indicate variant semantics for certain situations; others are used to indicate that certain fields in the type object (or in the extension structures referenced via `tp_as_number`, `tp_as_sequence`, `tp_as_mapping`, and `tp_as_buffer`) that were historically not always present are valid; if such a flag bit is clear, the type fields it guards must not be accessed and must be considered to have a zero or NULL value instead.

繼承:

Inheritance of this field is complicated. Most flag bits are inherited individually, i.e. if the base type has a flag bit set, the subtype inherits this flag bit. The flag bits that pertain to extension structures are strictly inherited if the extension structure is inherited, i.e. the base type's value of the flag bit is copied into the subtype together with a pointer to the extension structure. The `Py_TPFLAGS_HAVE_GC` flag bit is inherited together with the `tp_traverse` and `tp_clear` fields, i.e. if the `Py_TPFLAGS_HAVE_GC` flag bit is clear in the subtype and the `tp_traverse` and `tp_clear` fields in the subtype exist and have NULL values.

預設:

`PyBaseObject_Type` uses `Py_TPFLAGS_DEFAULT | Py_TPFLAGS_BASETYPE`.

Bit Masks:

The following bit masks are currently defined; these can be ORed together using the `|` operator to form the value of the `tp_flags` field. The macro `PyType_HasFeature()` takes a type and a flags value, *tp* and *f*, and checks whether `tp->tp_flags & f` is non-zero.

Py_TPFLAGS_HEAPTYPE

This bit is set when the type object itself is allocated on the heap, for example, types created dynamically using `PyType_FromSpec()`. In this case, the `ob_type` field of its instances is considered a reference to the type, and the type object is INCREf'ed when a new instance is created, and DECREf'ed when an instance is destroyed (this does not apply to instances of subtypes; only the type referenced by the instance's `ob_type` gets INCREf'ed or DECREf'ed).

繼承:

???

Py_TPFLAGS_BASETYPE

This bit is set when the type can be used as the base type of another type. If this bit is clear, the type cannot be subtyped (similar to a "final" class in Java).

繼承:

???

Py_TPFLAGS_READY

This bit is set when the type object has been fully initialized by `PyType_Ready()`.

继承:

???

Py_TPFLAGS_READYING

This bit is set while *PyType_Ready()* is in the process of initializing the type object.

继承:

???

Py_TPFLAGS_HAVE_GC

This bit is set when the object supports garbage collection. If this bit is set, instances must be created using *PyObject_GC_New()* and destroyed using *PyObject_GC_Del()*. More information in section 使对象类型支持循环垃圾回收. This bit also implies that the GC-related fields *tp_traverse* and *tp_clear* are present in the type object.

继承:

Group: *Py_TPFLAGS_HAVE_GC*, *tp_traverse*, *tp_clear*

The *Py_TPFLAGS_HAVE_GC* flag bit is inherited together with the *tp_traverse* and *tp_clear* fields, i.e. if the *Py_TPFLAGS_HAVE_GC* flag bit is clear in the subtype and the *tp_traverse* and *tp_clear* fields in the subtype exist and have NULL values.

Py_TPFLAGS_DEFAULT

This is a bitmask of all the bits that pertain to the existence of certain fields in the type object and its extension structures. Currently, it includes the following bits: *Py_TPFLAGS_HAVE_STACKLESS_EXTENSION*.

继承:

???

Py_TPFLAGS_METHOD_DESCRIPTOR

This bit indicates that objects behave like unbound methods.

If this flag is set for type (*meth*), then:

- *meth.__get__(obj, cls)(*args, **kwds)* (with *obj* not None) must be equivalent to *meth(obj, *args, **kwds)*.
- *meth.__get__(None, cls)(*args, **kwds)* must be equivalent to *meth(*args, **kwds)*.

This flag enables an optimization for typical method calls like *obj.meth()*: it avoids creating a temporary "bound method" object for *obj.meth*.

3.8 版新加入.

继承:

This flag is never inherited by *heap types*. For extension types, it is inherited whenever *tp_descr_get* is inherited.

Py_TPFLAGS_LONG_SUBCLASS

Py_TPFLAGS_LIST_SUBCLASS

Py_TPFLAGS_TUPLE_SUBCLASS

Py_TPFLAGS_BYTES_SUBCLASS

Py_TPFLAGS_UNICODE_SUBCLASS

Py_TPFLAGS_DICT_SUBCLASS

Py_TPFLAGS_BASE_EXC_SUBCLASS

Py_TPFLAGS_TYPE_SUBCLASS

These flags are used by functions such as `PyLong_Check()` to quickly determine if a type is a subclass of a built-in type; such specific checks are faster than a generic check, like `PyObject_IsInstance()`. Custom types that inherit from built-ins should have their `tp_flags` set appropriately, or the code that interacts with such types will behave differently depending on what kind of check is used.

Py_TPFLAGS_HAVE_FINALIZE

This bit is set when the `tp_finalize` slot is present in the type structure.

3.4 版新加入。

3.8 版後已 用: This flag isn't necessary anymore, as the interpreter assumes the `tp_finalize` slot is always present in the type structure.

Py_TPFLAGS_HAVE_VECTORCALL

This bit is set when the class implements the *vectorcall protocol*. See `tp_vectorcall_offset` for details.

继承:

This bit is inherited for *static subtypes* if `tp_call` is also inherited. *Heap types* do not inherit `Py_TPFLAGS_HAVE_VECTORCALL`.

3.9 版新加入。

Py_TPFLAGS_IMMUTABLETYPE

This bit is set for type objects that are immutable: type attributes cannot be set nor deleted.

`PyType_Ready()` automatically applies this flag to *static types*.

继承:

This flag is not inherited.

3.10 版新加入。

Py_TPFLAGS_DISALLOW_INSTANTIATION

Disallow creating instances of the type: set `tp_new` to NULL and don't create the `__new__` key in the type dictionary.

The flag must be set before creating the type, not after. For example, it must be set before `PyType_Ready()` is called on the type.

The flag is set automatically on *static types* if `tp_base` is NULL or `&PyBaseObject_Type` and `tp_new` is NULL.

继承:

This flag is not inherited. However, subclasses will not be instantiable unless they provide a non-NULL `tp_new` (which is only possible via the C API).

備 用: To disallow instantiating a class directly but allow instantiating its subclasses (e.g. for an *abstract base class*), do not use this flag. Instead, make `tp_new` only succeed for subclasses.

3.10 版新加入。

Py_TPFLAGS_MAPPING

This bit indicates that instances of the class may match mapping patterns when used as the subject of a match block. It is automatically set when registering or subclassing `collections.abc.Mapping`, and unset when registering `collections.abc.Sequence`.

備 用: `Py_TPFLAGS_MAPPING` and `Py_TPFLAGS_SEQUENCE` are mutually exclusive; it is an error to enable both flags simultaneously.

继承:

This flag is inherited by types that do not already set `Py_TPFLAGS_SEQUENCE`.

也参考:

PEP 634 —— 结构化模式匹配: 规范

3.10 版新加入.

Py_TPFLAGS_SEQUENCE

This bit indicates that instances of the class may match sequence patterns when used as the subject of a match block. It is automatically set when registering or subclassing `collections.abc.Sequence`, and unset when registering `collections.abc.Mapping`.

備 註: `Py_TPFLAGS_MAPPING` and `Py_TPFLAGS_SEQUENCE` are mutually exclusive; it is an error to enable both flags simultaneously.

继承:

This flag is inherited by types that do not already set `Py_TPFLAGS_MAPPING`.

也参考:

PEP 634 —— 结构化模式匹配: 规范

3.10 版新加入.

const char *PyTypeObject.tp_doc

An optional pointer to a NUL-terminated C string giving the docstring for this type object. This is exposed as the `__doc__` attribute on the type and instances of the type.

继承:

This field is *not* inherited by subtypes.

traverseproc PyTypeObject.tp_traverse

An optional pointer to a traversal function for the garbage collector. This is only used if the `Py_TPFLAGS_HAVE_GC` flag bit is set. The signature is:

```
int tp_traverse(PyObject *self, visitproc visit, void *arg);
```

More information about Python's garbage collection scheme can be found in section [使对象类型支持循环垃圾回收](#).

The `tp_traverse` pointer is used by the garbage collector to detect reference cycles. A typical implementation of a `tp_traverse` function simply calls `Py_VISIT()` on each of the instance's members that are Python objects that the instance owns. For example, this is function `local_traverse()` from the `_thread` extension module:

```
static int
local_traverse(localobject *self, visitproc visit, void *arg)
{
    Py_VISIT(self->args);
    Py_VISIT(self->kw);
    Py_VISIT(self->dict);
    return 0;
}
```

Note that `Py_VISIT()` is called only on those members that can participate in reference cycles. Although there is also a `self->key` member, it can only be NULL or a Python string and therefore cannot be part of a reference cycle.

On the other hand, even if you know a member can never be part of a cycle, as a debugging aid you may want to visit it anyway just so the `gc` module's `get_referents()` function will include it.

警告: When implementing `tp_traverse`, only the members that the instance *owns* (by having *strong references* to them) must be visited. For instance, if an object supports weak references via the `tp_weaklist` slot, the pointer supporting the linked list (what `tp_weaklist` points to) must **not** be visited as the instance does not directly own the weak references to itself (the weakreference list is there to support the weak reference machinery, but the instance has no strong reference to the elements inside it, as they are allowed to be removed even if the instance is still alive).

Note that `Py_VISIT()` requires the `visit` and `arg` parameters to `local_traverse()` to have these specific names; don't name them just anything.

Instances of *heap-allocated types* hold a reference to their type. Their traversal function must therefore either visit `Py_TYPE(self)`, or delegate this responsibility by calling `tp_traverse` of another heap-allocated type (such as a heap-allocated superclass). If they do not, the type object may not be garbage-collected.

3.9 版更變: Heap-allocated types are expected to visit `Py_TYPE(self)` in `tp_traverse`. In earlier versions of Python, due to [bug 40217](#), doing this may lead to crashes in subclasses.

繼承:

Group: `Py_TPFLAGS_HAVE_GC`, `tp_traverse`, `tp_clear`

This field is inherited by subtypes together with `tp_clear` and the `Py_TPFLAGS_HAVE_GC` flag bit: the flag bit, `tp_traverse`, and `tp_clear` are all inherited from the base type if they are all zero in the subtype.

inquiry `PyTypeObject.tp_clear`

An optional pointer to a clear function for the garbage collector. This is only used if the `Py_TPFLAGS_HAVE_GC` flag bit is set. The signature is:

```
int tp_clear(PyObject *);
```

The `tp_clear` member function is used to break reference cycles in cyclic garbage detected by the garbage collector. Taken together, all `tp_clear` functions in the system must combine to break all reference cycles. This is subtle, and if in any doubt supply a `tp_clear` function. For example, the tuple type does not implement a `tp_clear` function, because it's possible to prove that no reference cycle can be composed entirely of tuples. Therefore the `tp_clear` functions of other types must be sufficient to break any cycle containing a tuple. This isn't immediately obvious, and there's rarely a good reason to avoid implementing `tp_clear`.

Implementations of `tp_clear` should drop the instance's references to those of its members that may be Python objects, and set its pointers to those members to NULL, as in the following example:

```
static int
local_clear(localobject *self)
{
    Py_CLEAR(self->key);
    Py_CLEAR(self->args);
    Py_CLEAR(self->kw);
    Py_CLEAR(self->dict);
    return 0;
}
```

The `Py_CLEAR()` macro should be used, because clearing references is delicate: the reference to the contained object must not be decremented until after the pointer to the contained object is set to NULL. This is because decrementing the reference count may cause the contained object to become trash, triggering a chain of reclamation activity that may include invoking arbitrary Python code (due to finalizers, or weakref callbacks, associated with the contained object). If it's possible for such code to reference *self* again, it's important that the pointer to the contained object be NULL at that time, so that *self* knows the contained object can no longer be used. The `Py_CLEAR()` macro performs the operations in a safe order.

Note that `tp_clear` is not *always* called before an instance is deallocated. For example, when reference counting is enough to determine that an object is no longer used, the cyclic garbage collector is not involved and `tp_dealloc` is called directly.

Because the goal of `tp_clear` functions is to break reference cycles, it's not necessary to clear contained objects like Python strings or Python integers, which can't participate in reference cycles. On the other hand, it may be convenient to clear all contained Python objects, and write the type's `tp_dealloc` function to invoke `tp_clear`.

More information about Python's garbage collection scheme can be found in section 使对象类型支持循环垃圾回收.

继承:

Group: `Py_TPFLAGS_HAVE_GC`, `tp_traverse`, `tp_clear`

This field is inherited by subtypes together with `tp_traverse` and the `Py_TPFLAGS_HAVE_GC` flag bit: the flag bit, `tp_traverse`, and `tp_clear` are all inherited from the base type if they are all zero in the subtype.

richcmpfunc `PyObject.tp_richcompare`

An optional pointer to the rich comparison function, whose signature is:

```
PyObject *tp_richcompare(PyObject *self, PyObject *other, int op);
```

The first parameter is guaranteed to be an instance of the type that is defined by `PyObject`.

The function should return the result of the comparison (usually `Py_True` or `Py_False`). If the comparison is undefined, it must return `Py_NotImplemented`, if another error occurred it must return `NULL` and set an exception condition.

The following constants are defined to be used as the third argument for `tp_richcompare` and for `PyObject_RichCompare()`:

常數	对照
<code>Py_LT</code>	<code><</code>
<code>Py_LE</code>	<code><=</code>
<code>Py_EQ</code>	<code>==</code>
<code>Py_NE</code>	<code>!=</code>
<code>Py_GT</code>	<code>></code>
<code>Py_GE</code>	<code>>=</code>

定义以下宏是为了简化编写丰富的比较函数:

Py_RETURN_RICHCOMPARE (`VAL_A`, `VAL_B`, `op`)

Return `Py_True` or `Py_False` from the function, depending on the result of a comparison. `VAL_A` and `VAL_B` must be orderable by C comparison operators (for example, they may be C ints or floats). The third argument specifies the requested operation, as for `PyObject_RichCompare()`.

The return value's reference count is properly incremented.

On error, sets an exception and returns `NULL` from the function.

3.7 版新加入.

继承:

Group: `tp_hash`, `tp_richcompare`

This field is inherited by subtypes together with `tp_hash`: a subtype inherits `tp_richcompare` and `tp_hash` when the subtype's `tp_richcompare` and `tp_hash` are both `NULL`.

預設:

`PyBaseObject_Type` provides a `tp_richcompare` implementation, which may be inherited. However, if only `tp_hash` is defined, not even the inherited function is used and instances of the type will not be able to participate in any comparisons.

Py_ssize_t `PyObject.tp_weaklistoffset`

If the instances of this type are weakly referenceable, this field is greater than zero and contains the offset in

the instance structure of the weak reference list head (ignoring the GC header, if present); this offset is used by `PyObject_ClearWeakRefs()` and the `PyWeakref_*` functions. The instance structure needs to include a field of type `PyObject*` which is initialized to `NULL`.

Do not confuse this field with `tp_weaklist`; that is the list head for weak references to the type object itself.

继承:

This field is inherited by subtypes, but see the rules listed below. A subtype may override this offset; this means that the subtype uses a different weak reference list head than the base type. Since the list head is always found via `tp_weaklistoffset`, this should not be a problem.

When a type defined by a class statement has no `__slots__` declaration, and none of its base types are weakly referenceable, the type is made weakly referenceable by adding a weak reference list head slot to the instance layout and setting the `tp_weaklistoffset` of that slot's offset.

When a type's `__slots__` declaration contains a slot named `__weakref__`, that slot becomes the weak reference list head for instances of the type, and the slot's offset is stored in the type's `tp_weaklistoffset`.

When a type's `__slots__` declaration does not contain a slot named `__weakref__`, the type inherits its `tp_weaklistoffset` from its base type.

getterfunc `PyTypeObject.tp_iter`

An optional pointer to a function that returns an *iterator* for the object. Its presence normally signals that the instances of this type are *iterable* (although sequences may be iterable without this function).

This function has the same signature as `PyObject_GetIter()`:

```
PyObject *tp_iter(PyObject *self);
```

继承:

此字段会被子类型继承。

iternextfunc `PyTypeObject.tp_iternext`

An optional pointer to a function that returns the next item in an *iterator*. The signature is:

```
PyObject *tp_iternext(PyObject *self);
```

When the iterator is exhausted, it must return `NULL`; a `StopIteration` exception may or may not be set. When another error occurs, it must return `NULL` too. Its presence signals that the instances of this type are iterators.

Iterator types should also define the `tp_iter` function, and that function should return the iterator instance itself (not a new iterator instance).

This function has the same signature as `PyIter_Next()`.

继承:

此字段会被子类型继承。

struct `PyMethodDef *PyTypeObject.tp_methods`

An optional pointer to a static `NULL`-terminated array of `PyMethodDef` structures, declaring regular methods of this type.

For each entry in the array, an entry is added to the type's dictionary (see `tp_dict` below) containing a method descriptor.

继承:

This field is not inherited by subtypes (methods are inherited through a different mechanism).

struct `PyMemberDef *PyTypeObject.tp_members`

An optional pointer to a static `NULL`-terminated array of `PyMemberDef` structures, declaring regular data members (fields or slots) of instances of this type.

For each entry in the array, an entry is added to the type's dictionary (see `tp_dict` below) containing a member descriptor.

继承:

This field is not inherited by subtypes (members are inherited through a different mechanism).

struct *PyGetSetDef* **PyTypeObject*.*tp_getset*

An optional pointer to a static NULL-terminated array of *PyGetSetDef* structures, declaring computed attributes of instances of this type.

For each entry in the array, an entry is added to the type's dictionary (see *tp_dict* below) containing a getset descriptor.

继承:

This field is not inherited by subtypes (computed attributes are inherited through a different mechanism).

PyTypeObject* **PyTypeObject*.*tp_base

An optional pointer to a base type from which type properties are inherited. At this level, only single inheritance is supported; multiple inheritance require dynamically creating a type object by calling the metatype.

備註: Slot initialization is subject to the rules of initializing globals. C99 requires the initializers to be "address constants". Function designators like *PyType_GenericNew()*, with implicit conversion to a pointer, are valid C99 address constants.

However, the unary '&' operator applied to a non-static variable like *PyBaseObject_Type()* is not required to produce an address constant. Compilers may support this (gcc does), MSVC does not. Both compilers are strictly standard conforming in this particular behavior.

Consequently, *tp_base* should be set in the extension module's init function.

继承:

This field is not inherited by subtypes (obviously).

預設:

This field defaults to *&PyBaseObject_Type* (which to Python programmers is known as the type object).

PyObject* **PyTypeObject*.*tp_dict

The type's dictionary is stored here by *PyType_Ready()*.

This field should normally be initialized to NULL before *PyType_Ready* is called; it may also be initialized to a dictionary containing initial attributes for the type. Once *PyType_Ready()* has initialized the type, extra attributes for the type may be added to this dictionary only if they don't correspond to overloaded operations (like *__add__()*).

继承:

This field is not inherited by subtypes (though the attributes defined in here are inherited through a different mechanism).

預設:

If this field is NULL, *PyType_Ready()* will assign a new dictionary to it.

警告: It is not safe to use *PyDict_SetItem()* on or otherwise modify *tp_dict* with the dictionary C-API.

descrgetfunc* *PyTypeObject*.*tp_descr_get

An optional pointer to a "descriptor get" function.

The function signature is:

```
PyObject * tp_descr_get(PyObject *self, PyObject *obj, PyObject *type);
```

继承:

此字段会被子类型继承。

descrsetfunc *PyObject*.**tp_descr_set**

An optional pointer to a function for setting and deleting a descriptor's value.

The function signature is:

```
int tp_descr_set(PyObject *self, PyObject *obj, PyObject *value);
```

The *value* argument is set to NULL to delete the value.

继承:

此字段会被子类型继承。

Py_ssize_t *PyObject*.**tp_dictoffset**

If the instances of this type have a dictionary containing instance variables, this field is non-zero and contains the offset in the instances of the type of the instance variable dictionary; this offset is used by *PyObject_GenericGetAttr()*.

Do not confuse this field with *tp_dict*; that is the dictionary for attributes of the type object itself.

If the value of this field is greater than zero, it specifies the offset from the start of the instance structure. If the value is less than zero, it specifies the offset from the *end* of the instance structure. A negative offset is more expensive to use, and should only be used when the instance structure contains a variable-length part. This is used for example to add an instance variable dictionary to subtypes of *str* or *tuple*. Note that the *tp_basicsize* field should account for the dictionary added to the end in that case, even though the dictionary is not included in the basic object layout. On a system with a pointer size of 4 bytes, *tp_dictoffset* should be set to -4 to indicate that the dictionary is at the very end of the structure.

The real dictionary offset in an instance can be computed from a negative *tp_dictoffset* as follows:

```
dictoffset = tp_basicsize + abs(ob_size)*tp_itemsize + tp_dictoffset
if dictoffset is not aligned on sizeof(void*):
    round up to sizeof(void*)
```

where *tp_basicsize*, *tp_itemsize* and *tp_dictoffset* are taken from the type object, and *ob_size* is taken from the instance. The absolute value is taken because ints use the sign of *ob_size* to store the sign of the number. (There's never a need to do this calculation yourself; it is done for you by *_PyObject_GetDictPtr()*.)

继承:

This field is inherited by subtypes, but see the rules listed below. A subtype may override this offset; this means that the subtype instances store the dictionary at a difference offset than the base type. Since the dictionary is always found via *tp_dictoffset*, this should not be a problem.

When a type defined by a class statement has no *__slots__* declaration, and none of its base types has an instance variable dictionary, a dictionary slot is added to the instance layout and the *tp_dictoffset* is set to that slot's offset.

When a type defined by a class statement has a *__slots__* declaration, the type inherits its *tp_dictoffset* from its base type.

(Adding a slot named *__dict__* to the *__slots__* declaration does not have the expected effect, it just causes confusion. Maybe this should be added as a feature just like *__weakref__* though.)

预设:

This slot has no default. For *static types*, if the field is NULL then no *__dict__* gets created for instances.

initproc *PyObject*.**tp_init**

An optional pointer to an instance initialization function.

This function corresponds to the `__init__()` method of classes. Like `__init__()`, it is possible to create an instance without calling `__init__()`, and it is possible to reinitialize an instance by calling its `__init__()` method again.

The function signature is:

```
int tp_init(PyObject *self, PyObject *args, PyObject *kwargs);
```

The `self` argument is the instance to be initialized; the `args` and `kwargs` arguments represent positional and keyword arguments of the call to `__init__()`.

The `tp_init` function, if not `NULL`, is called when an instance is created normally by calling its type, after the type's `tp_new` function has returned an instance of the type. If the `tp_new` function returns an instance of some other type that is not a subtype of the original type, no `tp_init` function is called; if `tp_new` returns an instance of a subtype of the original type, the subtype's `tp_init` is called.

Returns 0 on success, -1 and sets an exception on error.

继承:

此字段会被子类型继承。

預設:

For *static types* this field does not have a default.

allocfunc `PyTypeObject.tp_alloc`

An optional pointer to an instance allocation function.

The function signature is:

```
PyObject *tp_alloc(PyTypeObject *self, Py_ssize_t nitems);
```

继承:

This field is inherited by static subtypes, but not by dynamic subtypes (subtypes created by a class statement).

預設:

For dynamic subtypes, this field is always set to `PyType_GenericAlloc()`, to force a standard heap allocation strategy.

For static subtypes, `PyBaseObject_Type` uses `PyType_GenericAlloc()`. That is the recommended value for all statically defined types.

newfunc `PyTypeObject.tp_new`

An optional pointer to an instance creation function.

The function signature is:

```
PyObject *tp_new(PyTypeObject *subtype, PyObject *args, PyObject *kwargs);
```

The `subtype` argument is the type of the object being created; the `args` and `kwargs` arguments represent positional and keyword arguments of the call to the type. Note that `subtype` doesn't have to equal the type whose `tp_new` function is called; it may be a subtype of that type (but not an unrelated type).

The `tp_new` function should call `subtype->tp_alloc(subtype, nitems)` to allocate space for the object, and then do only as much further initialization as is absolutely necessary. Initialization that can safely be ignored or repeated should be placed in the `tp_init` handler. A good rule of thumb is that for immutable types, all initialization should take place in `tp_new`, while for mutable types, most initialization should be deferred to `tp_init`.

Set the `Py_TPFLAGS_DISALLOW_INSTANTIATION` flag to disallow creating instances of the type in Python.

继承:

This field is inherited by subtypes, except it is not inherited by *static types* whose *tp_base* is NULL or `&PyBaseObject_Type`.

預設:

For *static types* this field has no default. This means if the slot is defined as NULL, the type cannot be called to create new instances; presumably there is some other way to create instances, like a factory function.

freefunc `PyTypeObject.tp_free`

An optional pointer to an instance deallocation function. Its signature is:

```
void tp_free(void *self);
```

An initializer that is compatible with this signature is `PyObject_Free()`.

繼承:

This field is inherited by static subtypes, but not by dynamic subtypes (subtypes created by a class statement)

預設:

In dynamic subtypes, this field is set to a deallocator suitable to match `PyType_GenericAlloc()` and the value of the `Py_TPFLAGS_HAVE_GC` flag bit.

For static subtypes, `PyBaseObject_Type` uses `PyObject_Del`.

inquiry `PyTypeObject.tp_is_gc`

An optional pointer to a function called by the garbage collector.

The garbage collector needs to know whether a particular object is collectible or not. Normally, it is sufficient to look at the object's type's *tp_flags* field, and check the `Py_TPFLAGS_HAVE_GC` flag bit. But some types have a mixture of statically and dynamically allocated instances, and the statically allocated instances are not collectible. Such types should define this function; it should return 1 for a collectible instance, and 0 for a non-collectible instance. The signature is:

```
int tp_is_gc(PyObject *self);
```

(The only example of this are types themselves. The metatype, `PyType_Type`, defines this function to distinguish between statically and *dynamically allocated types*.)

繼承:

此字段会被子类型继承。

預設:

This slot has no default. If this field is NULL, `Py_TPFLAGS_HAVE_GC` is used as the functional equivalent.

*PyObject** `PyTypeObject.tp_bases`

Tuple of base types.

This field should be set to NULL and treated as read-only. Python will fill it in when the type is *initialized*.

For dynamically created classes, the `Py_tp_bases` slot can be used instead of the *bases* argument of `PyType_FromSpecWithBases()`. The argument form is preferred.

警告: Multiple inheritance does not work well for statically defined types. If you set `tp_bases` to a tuple, Python will not raise an error, but some slots will only be inherited from the first base.

繼承:

This field is not inherited.

*PyObject** `PyTypeObject.tp_mro`

Tuple containing the expanded set of base types, starting with the type itself and ending with `object`, in Method Resolution Order.

This field should be set to `NULL` and treated as read-only. Python will fill it in when the type is *initialized*.

继承:

This field is not inherited; it is calculated fresh by `PyType_Ready()`.

`PyObject *PyTypeObject.tp_cache`

Unused. Internal use only.

继承:

This field is not inherited.

`PyObject *PyTypeObject.tp_subclasses`

List of weak references to subclasses. Internal use only.

继承:

This field is not inherited.

`PyObject *PyTypeObject.tp_weaklist`

Weak reference list head, for weak references to this type object. Not inherited. Internal use only.

继承:

This field is not inherited.

`destructor PyTypeObject.tp_del`

This field is deprecated. Use `tp_finalize` instead.

`unsigned int PyTypeObject.tp_version_tag`

Used to index into the method cache. Internal use only.

继承:

This field is not inherited.

`destructor PyTypeObject.tp_finalize`

An optional pointer to an instance finalization function. Its signature is:

```
void tp_finalize(PyObject *self);
```

If `tp_finalize` is set, the interpreter calls it once when finalizing an instance. It is called either from the garbage collector (if the instance is part of an isolated reference cycle) or just before the object is deallocated. Either way, it is guaranteed to be called before attempting to break reference cycles, ensuring that it finds the object in a sane state.

`tp_finalize` should not mutate the current exception status; therefore, a recommended way to write a non-trivial finalizer is:

```
static void
local_finalize(PyObject *self)
{
    PyObject *error_type, *error_value, *error_traceback;

    /* Save the current exception, if any. */
    PyErr_Fetch(&error_type, &error_value, &error_traceback);

    /* ... */

    /* Restore the saved exception. */
    PyErr_Restore(error_type, error_value, error_traceback);
}
```

Also, note that, in a garbage collected Python, `tp_dealloc` may be called from any Python thread, not just the thread which created the object (if the object becomes part of a refcount cycle, that cycle might be collected by a garbage collection on any thread). This is not a problem for Python API calls, since the thread on which `tp_dealloc` is called will own the Global Interpreter Lock (GIL). However, if the object being destroyed in turn

destroys objects from some other C or C++ library, care should be taken to ensure that destroying those objects on the thread which called `tp_dealloc` will not violate any assumptions of the library.

继承:

此字段会被子类型继承。

3.4 版新加入。

3.8 版更變: Before version 3.8 it was necessary to set the `Py_TPFLAGS_HAVE_FINALIZE` flags bit in order for this field to be used. This is no longer required.

也参考:

”Safe object finalization” ([PEP 442](#))

vectorcallfunc `PyObject.tp_vectorcall`

Vectorcall function to use for calls of this type object. In other words, it is used to implement *vectorcall* for `type.__call__`. If `tp_vectorcall` is NULL, the default call implementation using `__new__` and `__init__` is used.

继承:

This field is never inherited.

3.9 版新加入: (the field exists since 3.8 but it's only used since 3.9)

12.3.6 Static Types

Traditionally, types defined in C code are *static*, that is, a static `PyObject` structure is defined directly in code and initialized using `PyType_Ready()`.

This results in types that are limited relative to types defined in Python:

- Static types are limited to one base, i.e. they cannot use multiple inheritance.
- Static type objects (but not necessarily their instances) are immutable. It is not possible to add or modify the type object's attributes from Python.
- Static type objects are shared across *sub-interpreters*, so they should not include any subinterpreter-specific state.

Also, since `PyObject` is only part of the *Limited API* as an opaque struct, any extension modules using static types must be compiled for a specific Python minor version.

12.3.7 Heap Types

An alternative to *static types* is *heap-allocated types*, or *heap types* for short, which correspond closely to classes created by Python's `class` statement. Heap types have the `Py_TPFLAGS_HEAPTYPE` flag set.

This is done by filling a `PyType_Spec` structure and calling `PyType_FromSpec()`, `PyType_FromSpecWithBases()`, or `PyType_FromModuleAndSpec()`.

12.4 Number Object Structures

type PyNumberMethods

This structure holds pointers to the functions which an object uses to implement the number protocol. Each function is used by the function of similar name documented in the [数字协议](#) section.

Here is the structure definition:

```
typedef struct {
    binaryfunc nb_add;
    binaryfunc nb_subtract;
    binaryfunc nb_multiply;
    binaryfunc nb_remainder;
    binaryfunc nb_divmod;
    ternaryfunc nb_power;
    unaryfunc nb_negative;
    unaryfunc nb_positive;
    unaryfunc nb_absolute;
    inquiry nb_bool;
    unaryfunc nb_invert;
    binaryfunc nb_lshift;
    binaryfunc nb_rshift;
    binaryfunc nb_and;
    binaryfunc nb_xor;
    binaryfunc nb_or;
    unaryfunc nb_int;
    void *nb_reserved;
    unaryfunc nb_float;

    binaryfunc nb_inplace_add;
    binaryfunc nb_inplace_subtract;
    binaryfunc nb_inplace_multiply;
    binaryfunc nb_inplace_remainder;
    ternaryfunc nb_inplace_power;
    binaryfunc nb_inplace_lshift;
    binaryfunc nb_inplace_rshift;
    binaryfunc nb_inplace_and;
    binaryfunc nb_inplace_xor;
    binaryfunc nb_inplace_or;

    binaryfunc nb_floor_divide;
    binaryfunc nb_true_divide;
    binaryfunc nb_inplace_floor_divide;
    binaryfunc nb_inplace_true_divide;

    unaryfunc nb_index;

    binaryfunc nb_matrix_multiply;
    binaryfunc nb_inplace_matrix_multiply;
} PyNumberMethods;
```

備[Ⓕ]: Binary and ternary functions must check the type of all their operands, and implement the necessary conversions (at least one of the operands is an instance of the defined type). If the operation is not defined for the given operands, binary and ternary functions must return `Py_NotImplemented`, if another error occurred they must return `NULL` and set an exception.

備[Ⓕ]: The `nb_reserved` field should always be `NULL`. It was previously called `nb_long`, and was renamed in Python 3.0.1.

binaryfunc *PyNumberMethods*.nb_add
binaryfunc *PyNumberMethods*.nb_subtract
binaryfunc *PyNumberMethods*.nb_multiply
binaryfunc *PyNumberMethods*.nb_remainder
binaryfunc *PyNumberMethods*.nb_divmod
ternaryfunc *PyNumberMethods*.nb_power
unaryfunc *PyNumberMethods*.nb_negative
unaryfunc *PyNumberMethods*.nb_positive
unaryfunc *PyNumberMethods*.nb_absolute
inquiry *PyNumberMethods*.nb_bool
unaryfunc *PyNumberMethods*.nb_invert
binaryfunc *PyNumberMethods*.nb_lshift
binaryfunc *PyNumberMethods*.nb_rshift
binaryfunc *PyNumberMethods*.nb_and
binaryfunc *PyNumberMethods*.nb_xor
binaryfunc *PyNumberMethods*.nb_or
unaryfunc *PyNumberMethods*.nb_int
*void ***PyNumberMethods*.nb_reserved
unaryfunc *PyNumberMethods*.nb_float
binaryfunc *PyNumberMethods*.nb_inplace_add
binaryfunc *PyNumberMethods*.nb_inplace_subtract
binaryfunc *PyNumberMethods*.nb_inplace_multiply
binaryfunc *PyNumberMethods*.nb_inplace_remainder
ternaryfunc *PyNumberMethods*.nb_inplace_power
binaryfunc *PyNumberMethods*.nb_inplace_lshift
binaryfunc *PyNumberMethods*.nb_inplace_rshift
binaryfunc *PyNumberMethods*.nb_inplace_and
binaryfunc *PyNumberMethods*.nb_inplace_xor
binaryfunc *PyNumberMethods*.nb_inplace_or
binaryfunc *PyNumberMethods*.nb_floor_divide
binaryfunc *PyNumberMethods*.nb_true_divide
binaryfunc *PyNumberMethods*.nb_inplace_floor_divide
binaryfunc *PyNumberMethods*.nb_inplace_true_divide
unaryfunc *PyNumberMethods*.nb_index
binaryfunc *PyNumberMethods*.nb_matrix_multiply
binaryfunc *PyNumberMethods*.nb_inplace_matrix_multiply

12.5 Mapping Object Structures

type `PyMappingMethods`

This structure holds pointers to the functions which an object uses to implement the mapping protocol. It has three members:

lenfunc `PyMappingMethods.mp_length`

This function is used by `PyMapping_Size()` and `PyObject_Size()`, and has the same signature. This slot may be set to `NULL` if the object has no defined length.

binaryfunc `PyMappingMethods.mp_subscript`

This function is used by `PyObject_GetItem()` and `PySequence_GetSlice()`, and has the same signature as `PyObject_GetItem()`. This slot must be filled for the `PyMapping_Check()` function to return 1, it can be `NULL` otherwise.

objobjargproc `PyMappingMethods.mp_ass_subscript`

This function is used by `PyObject_SetItem()`, `PyObject_DelItem()`, `PyObject_SetSlice()` and `PyObject_DelSlice()`. It has the same signature as `PyObject_SetItem()`, but `v` can also be set to `NULL` to delete an item. If this slot is `NULL`, the object does not support item assignment and deletion.

12.6 Sequence Object Structures

type `PySequenceMethods`

This structure holds pointers to the functions which an object uses to implement the sequence protocol.

lenfunc `PySequenceMethods.sq_length`

This function is used by `PySequence_Size()` and `PyObject_Size()`, and has the same signature. It is also used for handling negative indices via the `sq_item` and the `sq_ass_item` slots.

binaryfunc `PySequenceMethods.sq_concat`

This function is used by `PySequence_Concat()` and has the same signature. It is also used by the `+` operator, after trying the numeric addition via the `nb_add` slot.

ssizeargfunc `PySequenceMethods.sq_repeat`

This function is used by `PySequence_Repeat()` and has the same signature. It is also used by the `*` operator, after trying numeric multiplication via the `nb_multiply` slot.

ssizeargfunc `PySequenceMethods.sq_item`

This function is used by `PySequence_GetItem()` and has the same signature. It is also used by `PyObject_GetItem()`, after trying the subscription via the `mp_subscript` slot. This slot must be filled for the `PySequence_Check()` function to return 1, it can be `NULL` otherwise.

Negative indexes are handled as follows: if the `sq_length` slot is filled, it is called and the sequence length is used to compute a positive index which is passed to `sq_item`. If `sq_length` is `NULL`, the index is passed as is to the function.

ssizeobjargproc `PySequenceMethods.sq_ass_item`

This function is used by `PySequence_SetItem()` and has the same signature. It is also used by `PyObject_SetItem()` and `PyObject_DelItem()`, after trying the item assignment and deletion via the `mp_ass_subscript` slot. This slot may be left to `NULL` if the object does not support item assignment and deletion.

objobjproc `PySequenceMethods.sq_contains`

This function may be used by `PySequence_Contains()` and has the same signature. This slot may be left to `NULL`, in this case `PySequence_Contains()` simply traverses the sequence until it finds a match.

binaryfunc `PySequenceMethods.sq_inplace_concat`

This function is used by `PySequence_InPlaceConcat()` and has the same signature. It should modify its first operand, and return it. This slot may be left to `NULL`, in this case

`PySequence_InPlaceConcat()` will fall back to `PySequence_Concat()`. It is also used by the augmented assignment `+=`, after trying numeric in-place addition via the `nb_inplace_add` slot.

ssizeargfunc `PySequenceMethods.sq_inplace_repeat`

This function is used by `PySequence_InPlaceRepeat()` and has the same signature. It should modify its first operand, and return it. This slot may be left to NULL, in this case `PySequence_InPlaceRepeat()` will fall back to `PySequence_Repeat()`. It is also used by the augmented assignment `*=`, after trying numeric in-place multiplication via the `nb_inplace_multiply` slot.

12.7 Buffer Object Structures

type `PyBufferProcs`

This structure holds pointers to the functions required by the *Buffer protocol*. The protocol defines how an exporter object can expose its internal data to consumer objects.

getterproc `PyBufferProcs.bf_getbuffer`

The signature of this function is:

```
int (PyObject *exporter, Py_buffer *view, int flags);
```

Handle a request to *exporter* to fill in *view* as specified by *flags*. Except for point (3), an implementation of this function MUST take these steps:

- (1) Check if the request can be met. If not, raise `PyExc_BufferError`, set `view->obj` to NULL and return -1.
- (2) Fill in the requested fields.
- (3) Increment an internal counter for the number of exports.
- (4) Set `view->obj` to *exporter* and increment `view->obj`.
- (5) Return 0.

If *exporter* is part of a chain or tree of buffer providers, two main schemes can be used:

- Re-export: Each member of the tree acts as the exporting object and sets `view->obj` to a new reference to itself.
- Redirect: The buffer request is redirected to the root object of the tree. Here, `view->obj` will be a new reference to the root object.

The individual fields of *view* are described in section *Buffer structure*, the rules how an exporter must react to specific requests are in section *Buffer request types*.

All memory pointed to in the `Py_buffer` structure belongs to the exporter and must remain valid until there are no consumers left. *format*, *shape*, *strides*, *suboffsets* and *internal* are read-only for the consumer.

`PyBuffer_FillInfo()` provides an easy way of exposing a simple bytes buffer while dealing correctly with all request types.

`PyObject_GetBuffer()` is the interface for the consumer that wraps this function.

releasebufferproc `PyBufferProcs.bf_releasebuffer`

The signature of this function is:

```
void (PyObject *exporter, Py_buffer *view);
```

Handle a request to release the resources of the buffer. If no resources need to be released, `PyBufferProcs.bf_releasebuffer` may be NULL. Otherwise, a standard implementation of this function will take these optional steps:

- (1) Decrement an internal counter for the number of exports.

(2) If the counter is 0, free all memory associated with *view*.

The exporter MUST use the *internal* field to keep track of buffer-specific resources. This field is guaranteed to remain constant, while a consumer MAY pass a copy of the original buffer as the *view* argument.

This function MUST NOT decrement *view->obj*, since that is done automatically in *PyBuffer_Release()* (this scheme is useful for breaking reference cycles).

PyBuffer_Release() is the interface for the consumer that wraps this function.

12.8 Async Object Structures

3.5 版新加入.

type *PyAsyncMethods*

This structure holds pointers to the functions required to implement *awaitable* and *asynchronous iterator* objects.

Here is the structure definition:

```
typedef struct {
    unaryfunc am_await;
    unaryfunc am_aiter;
    unaryfunc am_anext;
    sendfunc am_send;
} PyAsyncMethods;
```

unaryfunc *PyAsyncMethods.am_await*

The signature of this function is:

```
PyObject *am_await(PyObject *self);
```

The returned object must be an *iterator*, i.e. *PyIter_Check()* must return 1 for it.

This slot may be set to NULL if an object is not an *awaitable*.

unaryfunc *PyAsyncMethods.am_aiter*

The signature of this function is:

```
PyObject *am_aiter(PyObject *self);
```

必须返回一个 *asynchronous iterator* 对象。请参阅 *__anext__()* 了解详情。

This slot may be set to NULL if an object does not implement asynchronous iteration protocol.

unaryfunc *PyAsyncMethods.am_anext*

The signature of this function is:

```
PyObject *am_anext(PyObject *self);
```

Must return an *awaitable* object. See *__anext__()* for details. This slot may be set to NULL.

sendfunc *PyAsyncMethods.am_send*

The signature of this function is:

```
PySendResult am_send(PyObject *self, PyObject *arg, PyObject **result);
```

See *PyIter_Send()* for details. This slot may be set to NULL.

3.10 版新加入.

12.9 Slot Type typedefs

typedef *PyObject* **allocfunc** (*PyTypeObject* *cls, *Py_ssize_t* nitems)

Part of the Stable ABI. The purpose of this function is to separate memory allocation from memory initialization. It should return a pointer to a block of memory of adequate length for the instance, suitably aligned, and initialized to zeros, but with `ob_refcnt` set to 1 and `ob_type` set to the type argument. If the type's `tp_itemsize` is non-zero, the object's `ob_size` field should be initialized to `nitems` and the length of the allocated memory block should be `tp_basicsize + nitems*tp_itemsize`, rounded up to a multiple of `sizeof(void*)`; otherwise, `nitems` is not used and the length of the block should be `tp_basicsize`.

This function should not do any other instance initialization, not even to allocate additional memory; that should be done by `tp_new`.

typedef void **destructor** (*PyObject**)

Part of the Stable ABI.

typedef void **freefunc** (void*)

請見 `tp_free`。

typedef *PyObject* **newfunc** (*PyObject**, *PyObject**, *PyObject**)

Part of the Stable ABI. 請見 `tp_new`。

typedef int **initproc** (*PyObject**, *PyObject**, *PyObject**)

Part of the Stable ABI. 請見 `tp_init`。

typedef *PyObject* **reprfunc** (*PyObject**)

Part of the Stable ABI. 請見 `tp_repr`。

typedef *PyObject* **getattrfunc** (*PyObject* *self, char *attr)

Part of the Stable ABI. Return the value of the named attribute for the object.

typedef int **setattrfunc** (*PyObject* *self, char *attr, *PyObject* *value)

Part of the Stable ABI. Set the value of the named attribute for the object. The value argument is set to NULL to delete the attribute.

typedef *PyObject* **getattrofunc** (*PyObject* *self, *PyObject* *attr)

Part of the Stable ABI. Return the value of the named attribute for the object.

請見 `tp_getattro`。

typedef int **setattrofunc** (*PyObject* *self, *PyObject* *attr, *PyObject* *value)

Part of the Stable ABI. Set the value of the named attribute for the object. The value argument is set to NULL to delete the attribute.

請見 `tp_setattro`。

typedef *PyObject* **descrgetfunc** (*PyObject**, *PyObject**, *PyObject**)

Part of the Stable ABI. 請見 `tp_descr_get`。

typedef int **descrsetfunc** (*PyObject**, *PyObject**, *PyObject**)

Part of the Stable ABI. 請見 `tp_descr_set`。

typedef *Py_hash_t* **hashfunc** (*PyObject**)

Part of the Stable ABI. 請見 `tp_hash`。

typedef *PyObject* **richcmpfunc** (*PyObject**, *PyObject**, int)

Part of the Stable ABI. 請見 `tp_richcompare`。

typedef *PyObject* **getiterfunc** (*PyObject**)

Part of the Stable ABI. 請見 `tp_iter`。

typedef *PyObject* **iternextfunc** (*PyObject**)

Part of the Stable ABI. 請見 `tp_iternext`。

typedef *Py_ssize_t* **lenfunc** (*PyObject**)

Part of the Stable ABI.

```

typedef int (*getbufferproc) (PyObject*, Py_buffer*, int)
typedef void (*releasebufferproc) (PyObject*, Py_buffer*)
typedef PyObject* (*unaryfunc) (PyObject*)
    Part of the Stable ABI.
typedef PyObject* (*binaryfunc) (PyObject*, PyObject*)
    Part of the Stable ABI.
typedef PySendResult (*sendfunc) (PyObject*, PyObject*, PyObject**)
    請見 am_send.
typedef PyObject* (*ternaryfunc) (PyObject*, PyObject*, PyObject*)
    Part of the Stable ABI.
typedef PyObject* (*ssizeargfunc) (PyObject*, Py_ssize_t)
    Part of the Stable ABI.
typedef int (*ssizeobjargproc) (PyObject*, Py_ssize_t, PyObject*)
    Part of the Stable ABI.
typedef int (*objobjproc) (PyObject*, PyObject*)
    Part of the Stable ABI.
typedef int (*objobjargproc) (PyObject*, PyObject*, PyObject*)
    Part of the Stable ABI.

```

12.10 范例

The following are simple examples of Python type definitions. They include common usage you may encounter. Some demonstrate tricky corner cases. For more examples, practical info, and a tutorial, see [defining-new-types](#) and [new-types-topics](#).

A basic *static type*:

```

typedef struct {
    PyObject_HEAD
    const char *data;
} MyObject;

static PyTypeObject MyObject_Type = {
    PyVarObject_HEAD_INIT(NULL, 0)
    .tp_name = "mymod.MyObject",
    .tp_basicsize = sizeof(MyObject),
    .tp_doc = PyDoc_STR("My objects"),
    .tp_new = myobj_new,
    .tp_dealloc = (destructor)myobj_dealloc,
    .tp_repr = (reprfunc)myobj_repr,
};

```

You may also find older code (especially in the CPython code base) with a more verbose initializer:

```

static PyTypeObject MyObject_Type = {
    PyVarObject_HEAD_INIT(NULL, 0)
    "mymod.MyObject",           /* tp_name */
    sizeof(MyObject),           /* tp_basicsize */
    0,                           /* tp_itemsize */
    (destructor)myobj_dealloc,   /* tp_dealloc */
    0,                           /* tp_vectorcall_offset */
    0,                           /* tp_getattr */
    0,                           /* tp_setattr */
    0,                           /* tp_as_async */

```

(下页继续)

(繼續上一頁)

```

(reprfunc)myobj_repr,          /* tp_repr */
0,                             /* tp_as_number */
0,                             /* tp_as_sequence */
0,                             /* tp_as_mapping */
0,                             /* tp_hash */
0,                             /* tp_call */
0,                             /* tp_str */
0,                             /* tp_getattro */
0,                             /* tp_setattro */
0,                             /* tp_as_buffer */
0,                             /* tp_flags */
PyDoc_STR("My objects"),      /* tp_doc */
0,                             /* tp_traverse */
0,                             /* tp_clear */
0,                             /* tp_richcompare */
0,                             /* tp_weaklistoffset */
0,                             /* tp_iter */
0,                             /* tp_iternext */
0,                             /* tp_methods */
0,                             /* tp_members */
0,                             /* tp_getset */
0,                             /* tp_base */
0,                             /* tp_dict */
0,                             /* tp_descr_get */
0,                             /* tp_descr_set */
0,                             /* tp_dictoffset */
0,                             /* tp_init */
0,                             /* tp_alloc */
myobj_new,                    /* tp_new */
};

```

A type that supports weakrefs, instance dicts, and hashing:

```

typedef struct {
    PyObject_HEAD
    const char *data;
    PyObject *inst_dict;
    PyObject *weakreflist;
} PyObject;

static PyTypeObject PyObject_Type = {
    PyVarObject_HEAD_INIT(NULL, 0)
    .tp_name = "mymod.MyObject",
    .tp_basicsize = sizeof(PyObject),
    .tp_doc = PyDoc_STR("My objects"),
    .tp_weaklistoffset = offsetof(PyObject, weakreflist),
    .tp_dictoffset = offsetof(PyObject, inst_dict),
    .tp_flags = Py_TPFLAGS_DEFAULT | Py_TPFLAGS_BASETYPE | Py_TPFLAGS_HAVE_GC,
    .tp_new = myobj_new,
    .tp_traverse = (traverseproc)myobj_traverse,
    .tp_clear = (inquiry)myobj_clear,
    .tp_alloc = PyType_GenericNew,
    .tp_dealloc = (destructor)myobj_dealloc,
    .tp_repr = (reprfunc)myobj_repr,
    .tp_hash = (hashfunc)myobj_hash,
    .tp_richcompare = PyBaseObject_Type.tp_richcompare,
};

```

A str subclass that cannot be subclassed and cannot be called to create instances (e.g. uses a separate factory func) using `Py_TPFLAGS_DISALLOW_INSTANTIATION` flag:

```
typedef struct {
    PyUnicodeObject raw;
    char *extra;
} MyStr;

static PyTypeObject MyStr_Type = {
    PyVarObject_HEAD_INIT(NULL, 0)
    .tp_name = "mymod.MyStr",
    .tp_basicsize = sizeof(MyStr),
    .tp_base = NULL, // set to &PyUnicode_Type in module init
    .tp_doc = PyDoc_STR("my custom str"),
    .tp_flags = Py_TPFLAGS_DEFAULT | Py_TPFLAGS_DISALLOW_INSTANTIATION,
    .tp_repr = (reprfunc)myobj_repr,
};
```

The simplest *static type* with fixed-length instances:

```
typedef struct {
    PyObject_HEAD
} MyObject;

static PyTypeObject MyObject_Type = {
    PyVarObject_HEAD_INIT(NULL, 0)
    .tp_name = "mymod.MyObject",
};
```

The simplest *static type* with variable-length instances:

```
typedef struct {
    PyObject_VAR_HEAD
    const char *data[1];
} MyObject;

static PyTypeObject MyObject_Type = {
    PyVarObject_HEAD_INIT(NULL, 0)
    .tp_name = "mymod.MyObject",
    .tp_basicsize = sizeof(MyObject) - sizeof(char *),
    .tp_itemsize = sizeof(char *),
};
```

12.11 使对象类型支持循环垃圾回收

Python 对循环引用的垃圾检测与回收需要“容器”对象类型的支持，此类型的容器对象中可能包含其它容器对象。不保存其它对象的引用的类型，或者只保存原子类型（如数字或字符串）的引用的类型，不需要显式提供垃圾回收的支持。

若要创建一个容器类，类型对象的 `tp_flags` 字段必须包含 `Py_TPFLAGS_HAVE_GC` 并提供一个 `tp_traverse` 处理的实现。如果该类型的实例是可变的，还需要实现 `tp_clear`。

Py_TPFLAGS_HAVE_GC

设置了此标志位的类型的对象必须符合此处记录的规则。为方便起见，下文把这些对象称为容器对象。

容器类型的构造函数必须符合两个规则：

1. 必须使用 `PyObject_GC_New()` 或 `PyObject_GC_NewVar()` 为这些对象分配内存。
2. 初始化了所有可能包含其他容器的引用的字段后，它必须调用 `PyObject_GC_Track()`。

同样的，对象的释放器必须符合两个类似的规则：

1. 在引用其它容器的字段失效前，必须调用 `PyObject_GC_UnTrack()`。

2. 必须使用 `PyObject_GC_Del()` 释放对象的内存。

警告： 如果一个类型添加了 `Py_TPFLAGS_HAVE_GC`，则它 必须实现至少一个 `tp_traverse` 句柄或显式地使用来自其一个或多个子类的句柄。

当调用 `PyType_Ready()` 或者 API 中某些间接调用它的函数例如 `PyType_FromSpecWithBases()` 或 `PyType_FromSpec()` 时解释器就自动填充 `tp_flags`, `tp_traverse` 和 `tp_clear` 字段，如果该类型是继承自实现了垃圾回收器协议的类并且该子类没有包括 `Py_TPFLAGS_HAVE_GC` 旗标的话。

TYPE *PyObject_GC_New (TYPE, *PyTypeObject* *type)

类似于 `PyObject_New()`，适用于设置了 `Py_TPFLAGS_HAVE_GC` 标签的容器对象。

TYPE *PyObject_GC_NewVar (TYPE, *PyTypeObject* *type, *Py_ssize_t* size)

类似于 `PyObject_NewVar()`，适用于设置了 `Py_TPFLAGS_HAVE_GC` 标签的容器对象。

TYPE *PyObject_GC_Resize (TYPE, *PyVarObject* *op, *Py_ssize_t* newsize)

为 `PyObject_NewVar()` 所分配对象重新调整大小。返回调整大小后的对象或在失败时返回 `NULL`。op 必须尚未被垃圾回收器追踪。

void PyObject_GC_Track (*PyObject* *op)

Part of the Stable ABI. 把对象 op 加入到垃圾回收器跟踪的容器对象中。对象在被回收器跟踪时必须保持有效的，因为回收器可能在任何时候开始运行。在 `tp_traverse` 处理前的所有字段变为有效后，必须调用此函数，通常在靠近构造函数末尾的位置。

int PyObject_IS_GC (*PyObject* *obj)

如果对象实现了垃圾回收器协议则返回非零值，否则返回 0。

如果此函数返回 0 则对象无法被垃圾回收器追踪。

int PyObject_GC_IsTracked (*PyObject* *op)

Part of the Stable ABI since version 3.9. 如果 op 对象的类型实现了 GC 协议且 op 目前正被垃圾回收器追踪则返回 1，否则返回 0。

这类似于 Python 函数 `gc.is_tracked()`。

3.9 版新加入。

int PyObject_GC_IsFinalized (*PyObject* *op)

Part of the Stable ABI since version 3.9. 如果 op 对象的类型实现了 GC 协议且 op 已经被垃圾回收器终结则返回 1，否则返回 0。

这类似于 Python 函数 `gc.is_finalized()`。

3.9 版新加入。

void PyObject_GC_Del (void *op)

Part of the Stable ABI. 释放对象的内存，该对象初始化时由 `PyObject_GC_New()` 或 `PyObject_GC_NewVar()` 分配内存。

void PyObject_GC_UnTrack (void *op)

Part of the Stable ABI. 从回收器跟踪的容器对象集合中移除 op 对象。请注意可以在此对象上再次调用 `PyObject_GC_Track()` 以将其加回到被跟踪对象集合。释放器 (`tp_dealloc` 句柄) 应当在 `tp_traverse` 句柄所使用的任何字段失效之前为对象调用此函数。

3.8 版更變: `_PyObject_GC_TRACK()` 和 `_PyObject_GC_UNTRACK()` 宏已从公有 C API 中移除。

`tp_traverse` 处理接收以下类型的函数形参。

typedef int (*visitproc) (*PyObject* *object, void *arg)

Part of the Stable ABI. 传给 `tp_traverse` 处理的访问函数的类型。object 是容器中需要被遍历的一个对象，第三个形参对应于 `tp_traverse` 处理的 arg。Python 核心使用多个访问者函数实现循环引用的垃圾检测，不需要用户自行实现访问者函数。

`tp_traverse` 处理必须是以下类型：

typedef int (*traverseproc) (PyObject *self, visitproc visit, void *arg)

Part of the Stable ABI. 用于容器对象的遍历函数。它的实现必须对 *self* 所直接包含的每个对象调用 *visit* 函数，*visit* 的形参为所包含对象和传给处理程序的 *arg* 值。*visit* 函数调用不可附带 NULL 对象作为参数。如果 *visit* 返回非零值，则该值应当被立即返回。

为了简化 *tp_traverse* 处理的实现，Python 提供了一个 *Py_VISIT()* 宏。若要使用这个宏，必须把 *tp_traverse* 的参数命名为 *visit* 和 *arg*。

void Py_VISIT (PyObject *o)

如果 *o* 不为 NULL，则调用 *visit* 回调函数，附带参数 *o* 和 *arg*。如果 *visit* 返回一个非零值，则返回该值。使用此宏之后，*tp_traverse* 处理程序的形式如下：

```
static int
my_traverse(Noddy *self, visitproc visit, void *arg)
{
    Py_VISIT(self->foo);
    Py_VISIT(self->bar);
    return 0;
}
```

tp_clear 处理程序必须为 *inquiry* 类型，如果对象不可变则为 NULL。

typedef int (*inquiry) (PyObject *self)

Part of the Stable ABI. 丢弃产生循环引用的引用。不可变对象不需要声明此方法，因为他们不可能直接产生循环引用。需要注意的是，对象在调用此方法后必须仍是有效的（不能对引用只调用 *Py_DECREF()* 方法）。当垃圾回收器检测到该对象在循环引用中时，此方法会被调用。

12.11.1 控制垃圾回收器状态

这个 C-API 提供了以下函数用于控制垃圾回收的运行。

Py_ssize_t PyGC_Collect (void)

Part of the Stable ABI. 执行完全的垃圾回收，如果垃圾回收器已启用的话。（请注意 *gc.collect()* 会无条件地执行它。）

返回已回收的 + 无法回收的不可获取对象的数量。如果垃圾回收器被禁用或已在执行回收，则立即返回 0。在垃圾回收期间发生的错误会被传给 *sys.unraisablehook*。此函数不会引发异常。

int PyGC_Enable (void)

Part of the Stable ABI since version 3.10. 启用垃圾回收器：类似于 *gc.enable()*。返回之前的状态，0 为禁用而 1 为启用。

3.10 版新加入。

int PyGC_Disable (void)

Part of the Stable ABI since version 3.10. 禁用垃圾回收器：类似于 *gc.disable()*。返回之前的状态，0 为禁用而 1 为启用。

3.10 版新加入。

int PyGC_IsEnabled (void)

Part of the Stable ABI since version 3.10. 查询垃圾回收器的状态：类似于 *gc.isenabled()*。返回当前的状态，0 为禁用而 1 为启用。

3.10 版新加入。

API 和 ABI 版本管理

CPython 透過以下巨集 (macro) 公開其版本號。請注意，對應到的是**建置 (built)** 所用到的版本，`__`不一定是**運行時期 (run time)**所使用的版本。

關於跨版本 API 和 ABI 穩定性的討論，請見 *C API 的穩定性*。

PY_MAJOR_VERSION

在 3.4.1a2 中的 3。

PY_MINOR_VERSION

在 3.4.1a2 中的 4。

PY_MICRO_VERSION

在 3.4.1a2 中的 1。

PY_RELEASE_LEVEL

在 3.4.1a2 中的 a。0xA 代表 alpha 版本、0xB 代表 beta 版本、0xC `__`發布候選版本、0xF 則`__`最終版。

PY_RELEASE_SERIAL

在 3.4.1a2 中的 2。零則`__`最終發布版本。

PY_VERSION_HEX

被編碼`__`單一整數的 Python 版本號。

所代表的版本資訊可以用以下規則將其看做是一個 32 位元數字來獲得：

位 元 組 串	位元 (大端位元組序 (big endian order))	意義	3.4.1a2 中的值
1	1-8	PY_MAJOR_VERSION	0x03
2	9-16	PY_MINOR_VERSION	0x04
3	17-24	PY_MICRO_VERSION	0x01
4	25-28	PY_RELEASE_LEVEL	0xA
	29-32	PY_RELEASE_SERIAL	0x2

因此 3.4.1a2 代表 hexversion 0x030401a2、3.10.0 代表 hexversion 0x030a00f0。

所有提到的巨集都定義在 `Include/patchlevel.h`。

術語表

>>> 互動式 shell 的預設 Python 提示字元。常見於能在直譯器中以互動方式被執行的程式碼範例。

... 可以表示：

- 在一個被縮排的程式碼區塊、在一對匹配的左右定界符 (delimiter, 例如括號、方括號、花括號或三引號) 內部, 或是在指定一個裝飾器 (decorator) 之後, 要輸入程式碼時, 互動式 shell 顯示的預設 Python 提示字元。
- 建立常數 Ellipsis。

2to3 一個試著將 Python 2.x 程式碼轉換成 Python 3.x 程式碼的工具, 它是透過處理大部分的不相容性來達成此目的, 而這些不相容性能透過剖析原始碼和遍歷剖析樹而被檢測出來。

2to3 在標準函式庫中以 `lib2to3` 被使用; 它提供了一個獨立的入口點, 在 `Tools/scripts/2to3`。請參閱 [2to3-reference](#)。

abstract base class (抽象基底類) 抽象基底類 (又稱 ABC) 提供了一種定義介面的方法, 作為 [duck-typing](#) (鴨子型) 的補充。其他類似的技術, 像是 `hasattr()`, 則顯得笨拙或是帶有細微的錯誤 (例如使用魔術方法 (magic method))。ABC 是用擬的 subclass (子類), 它們不繼承自另一個 class (類), 但仍可被 `isinstance()` 及 `issubclass()` 辨識; 請參閱 [abc 模組的說明文件](#)。Python 有許多建立的 ABC, 用於資料結構 (在 `collections.abc` 模組)、數字 (在 `numbers` 模組)、串流 (在 `io` 模組) 及 import 尋檢器和載入器 (在 `importlib.abc` 模組)。你可以使用 `abc` 模組建立自己的 ABC。

annotation (註釋) 一個與變數、class 屬性、函式的參數或回傳值相關聯的標記。照慣例, 它被用來作 [type hint](#) (型提示)。

在運行時 (runtime), 區域變數的註釋無法被存取, 但全域變數、class 屬性和函式的註釋, 會分別被儲存在模組、class 和函式的 `__annotations__` 特殊屬性中。

請參閱 [variable annotation](#)、[function annotation](#)、[PEP 484](#) 和 [PEP 526](#), 這些章節皆有此功能的說明。關於註釋的最佳實踐方法也請參閱 [annotations-howto](#)。

argument (引數) 呼叫函式時被傳遞給 [function](#) (或 [method](#)) 的值。引數有兩種：

- 關鍵字引數 (*keyword argument*): 在函式呼叫中, 以識別字 (identifier, 例如 `name=`) 開頭的引數, 或是以 `**` 後面 dictionary (字典) 的值被傳遞的引數。例如, 3 和 5 都是以下 `complex()` 呼叫中的關鍵字引數：

```
complex(real=3, imag=5)
complex(**{'real': 3, 'imag': 5})
```

- 位置引數 (*positional argument*): 不是關鍵字引數的引數。位置引數可在一個引數列表的起始處出現, 和 (或) 作 `*` 之後的 *iterable* (可代物件) 中的元素被傳遞。例如, 3 和 5 都是以下呼叫中的位置引數:

```
complex(3, 5)
complex(*(3, 5))
```

引數會被指定給函式主體中的附名區域變數。關於支配這個指定過程的規則, 請參 [calls](#) 章節。在語法上, 任何運算式都可以被用來表示一個引數; 其評估值會被指定給區域變數。

另請參術語表的 *parameter* (參數) 條目、常見問題中的引數和參數之間的差別, 以及 [PEP 362](#)。

asynchronous context manager (非同步情境管理器) 一個可以控制 `async with` 陳述式中所見環境的物件, 而它是透過定義 `__aenter__()` 和 `__aexit__()` method (方法) 來控制的。由 [PEP 492](#) 引入。

asynchronous generator (非同步生成器) 一個會回傳 *asynchronous generator iterator* (非同步生成器代器) 的函式。它看起來像一個以 `async def` 定義的協程函式 (coroutine function), 但不同的是它包含了 `yield` 運算式, 能生成一系列可用於 `async for` 圈的值。

這個術語通常用來表示一個非同步生成器函式, 但在某些情境中, 也可能是表示非同步生成器代器 (*asynchronous generator iterator*)。萬一想表達的意思不清楚, 那就使用完整的術語, 以避免歧義。

一個非同步生成器函式可能包含 `await` 運算式, 以及 `async for` 和 `async with` 陳述式。

asynchronous generator iterator (非同步生成器代器) 一個由 *asynchronous generator* (非同步生成器) 函式所建立的物件。

這是一個 *asynchronous iterator* (非同步代器), 當它以 `__anext__()` method 被呼叫時, 會回傳一個可等待物件 (awaitable object), 該物件將執行非同步生成器的函式主體, 直到遇到下一個 `yield` 運算式。

每個 `yield` 會暫停處理程序, 記住位置執行狀態 (包括區域變數及擱置中的 `try` 陳述式)。當非同步生成器代器以另一個被 `__anext__()` 回傳的可等待物件有效地回復時, 它會從停止的地方繼續執行。請參 [PEP 492](#) 和 [PEP 525](#)。

asynchronous iterable (非同步可代物件) 一個物件, 它可以在 `async for` 陳述式中被使用。必須從它的 `__aiter__()` method 回傳一個 *asynchronous iterator* (非同步代器)。由 [PEP 492](#) 引入。

asynchronous iterator (非同步代器) 一個實作 `__aiter__()` 和 `__anext__()` method 的物件。`__anext__` 必須回傳一個 *awaitable* (可等待物件)。 `async for` 會解析非同步代器的 `__anext__()` method 所回傳的可等待物件, 直到它引發 `StopAsyncIteration` 例外。由 [PEP 492](#) 引入。

attribute (屬性) 一個與某物件相關聯的值, 該值大多能透過使用點分隔運算式 (dotted expression) 的名稱被參照。例如, 如果物件 `o` 有一個屬性 `a`, 則該屬性能以 `o.a` 被參照。

如果一個物件允許, 給予該物件一個名稱不是由 `identifiers` 所定義之識別符 (identifier) 的屬性是有可能的, 例如使用 `setattr()`。像這樣的屬性將無法使用點分隔運算式來存取, 而是需要使用 `getattr()` 來取得它。

awaitable (可等待物件) 一個可以在 `await` 運算式中被使用的物件。它可以是一個 *coroutine* (協程), 或是一個有 `__await__()` method 的物件。另請參 [PEP 492](#)。

BDFL Benevolent Dictator For Life (終身仁慈獨裁者), 又名 [Guido van Rossum](#), Python 的創造者。

binary file (二進制檔案) 一個能讀取和寫入 *bytes-like objects* (類位元組串物件) 的 *file object* (檔案物件)。二進制檔案的例子有: 以二進制模式 ('rb', 'wb' 或 'rb+') 開的檔案、`sys.stdin.buffer`、`sys.stdout.buffer`, 以及 `io.BytesIO` 和 `gzip.GzipFile` 實例。

另請參 *text file* (文字檔案), 它是一個能讀取和寫入 `str` 物件的檔案物件。

borrowed reference (借用參照) 在 Python 的 C API 中, 借用參照是一個對物件的參照。它不會修改該物件的參照計數 (reference count)。如果該物件被銷, 它會成一個迷途指標 (dangling pointer)。例如, 一次垃圾回收 (garbage collection) 可以移除對物件的最後一個 *strong reference* (參照), 而將該物件銷。

對 *borrowed reference* 呼叫 `Py_INCREF()` 以將它原地 (in-place) 轉成 *strong reference* 是被建議的做法，除非該物件不能在最後一次使用借用參照之前被銷毀。`Py_NewRef()` 函式可用於建立一個新的 *strong reference*。

bytes-like object (類位元組串物件) 一個支援緩衝協定 (*Buffer Protocol*) 且能匯出 C-contiguous 緩衝區的物件。這包括所有的 `bytes`、`bytearray` 和 `array.array` 物件，以及許多常見的 `memoryview` 物件。類位元組串物件可用於處理二進制資料的各種運算；這些運算包括壓縮、儲存至二進制檔案和透過 `socket` (插座) 發送。

有些運算需要二進制資料是可變的。明文文件通常會將這些物件稱作「可讀寫的類位元組串物件」。可變緩衝區的物件包括 `bytearray`，以及 `bytearray` 的 `memoryview`。其他的運算需要讓二進制資料被儲存在不可變物件 (「唯讀的類位元組串物件」) 中；這些物件包括 `bytes`，以及 `bytes` 物件的 `memoryview`。

bytecode (位元組碼) Python 的原始碼會被編譯成位元組碼，它是 Python 程式在 CPython 直譯器中的內部表示法。該位元組碼也會被暫存在 `.pyc` 檔案中，以便第二次執行同一個檔案時能更快 (可以不用從原始碼重新編譯位元組碼)。這種「中間語言 (intermediate language)」據說是運行在一個 *virtual machine* (虛擬機器) 上，該虛擬機器會執行與每個位元組碼對應的機器碼 (machine code)。要注意的是，位元組碼理論上是無法在不同的 Python 虛擬機器之間運作的，也不能在不同版本的 Python 之間保持穩定。

位元組碼的指令列表可以在 `dis` 模組的明文文件中找到。

callable (可呼叫物件) 一個 callable 是可以被呼叫的物件，呼叫時可能以下列形式帶有一組引數 (請見 *argument*):

```
callable(argument1, argument2, ...)
```

一個 *function* 與其延伸的 *method* 都是 callable。一個有實作 `__call__()` 方法的 class 之實例也是個 callable。

callback (回呼) 作引數被傳遞的一個副程式 (subroutine) 函式，會在未來的某個時間點被執行。

class (類) 一個用於建立使用者定義物件的模板。Class 的定義通常會包含 *method* 的定義，這些 *method* 可以在 class 的實例上進行操作。

class variable (類變數) 一個在 class 中被定義，且應該只能在 class 層次 (意即不是在 class 的實例中) 被修改的變數。

coercion (強制轉型) 在涉及兩個不同型引數的操作過程中，將某一種型引數的實例轉成另一種型的隱式轉 (implicit conversion) 過程。例如，`int(3.15)` 會將浮點數轉成整數 3，但在 `3+4.5` 中，每個引數是不同的型 (一個 `int`，一個 `float`)，而這兩個引數必須在被轉成相同的型之後才能相加，否則就會引發 `TypeError`。如果有強制轉型，即使所有的引數型皆相容，它們都必須由程式設計師正規化 (normalize) 成相同的值，例如，要用 `float(3)+4.5` 而不能只是 `3+4.5`。

complex number (複數) 一個我們熟悉的實數系統的擴充，在此所有數字都會被表示成一個實部和一個虛部之和。複數就是虛數單位 (-1 的平方根) 的實數倍，此單位通常在數學中被寫成 i ，在工程學中被寫成 j 。Python 提供了對複數的支援，它是用後者的記法來表示複數；虛部會帶著一個後綴的 j 被編寫，例如 `3+1j`。若要將 `math` 模組的工具等效地用於複數，請使用 `cmath` 模組。複數的使用是一個相當進階的數學功能。如果你有察覺到對它們的需求，那你幾乎能確定你可以安全地忽略它們。

context manager (情境管理器) 一個可以控制 `with` 陳述式中所見環境的物件，而它是透過定義 `__enter__()` 和 `__exit__()` *method* 來控制的。請參 PEP 343。

context variable (情境變數) 一個變數，其值可以根據上下文的情境而有所不同。這類似執行緒區域儲存區 (Thread-Local Storage)，在其中，一個變數在每個執行緒可能具有不同的值。然而，關於情境變數，在一個執行緒中可能會有多个情境，而情境變數的主要用途，是在行的非同步任務 (concurrent asynchronous task) 中，對於變數狀態的追蹤。請參 `contextvars`。

contiguous (連續的) 如果一個緩衝區是 C-contiguous 或是 Fortran contiguous，則它會確切地被視為連續的。零維 (zero-dimensional) 的緩衝區都是 C 及 Fortran contiguous。在一維 (one-dimensional) 陣列中，各項目必須在記憶體中彼此相鄰地排列，而其索引順序是從零開始遞增。在多維的 (multidimensional) C-contiguous 陣列中，按記憶體位址的順序訪問各個項目時，最後一個索引的變化最快。然而，在 Fortran contiguous 陣列中，第一個索引的變化最快。

coroutine (協程) 協程是副程式 (subroutine) 的一種更廣義的形式。副程式是在某個時間點被進入，在另一個時間點被退出。協程可以在許多不同的時間點被進入、退出和回復。它們能以 `async def` 陳述式被實作。另請參 PEP 492。

coroutine function (協程函式) 一個回傳 *coroutine* (協程) 物件的函式。一個協程函式能以 `async def` 陳述式被定義，可能包含 `await`、`async for` 和 `async with` 關鍵字。這些關鍵字由 PEP 492 引入。

CPython Python 程式語言的標準實作 (canonical implementation)，被發布在 python.org 上。「CPython」這個術語在必要時被使用，以區分此實作與其它語言的實作，例如 Jython 或 IronPython。

decorator (裝飾器) 一個函式，它會回傳另一個函式，通常它會使用 `@wrapper` 語法，被應用一種函式的變 (function transformation)。裝飾器的常見範例是 `classmethod()` 和 `staticmethod()`。

裝飾器語法只是語法糖。以下兩個函式定義在語義上是等效的：

```
def f(arg):
    ...
f = staticmethod(f)

@staticmethod
def f(arg):
    ...
```

Class 也存在相同的概念，但在那比較不常用。關於裝飾器的更多內容，請參函式定義和 class 定義的說明文件。

descriptor (描述器) 任何定義了 `__get__()`、`__set__()` 或 `__delete__()` method 的物件。當一個 class 屬性是一個描述器時，它的特殊連結行會在屬性查找時被觸發。通常，使用 `a.b` 來取得、設定或刪除某個屬性時，會在 `a` 的 class 字典中查找名稱 `b` 的物件，但如果 `b` 是一個描述器，則相對應的描述器 method 會被呼叫。對描述器的理解是深入理解 Python 的關鍵，因它們是許多功能的基礎，這些功能包括函式、method、屬性 (property)、class method、態 method，以及對 super class (父類) 的參照。

關於描述器 method 的更多資訊，請參 descriptors 或描述器使用指南。

dictionary (字典) 一個關聯陣列 (associative array)，其中任意的鍵會被映射到值。鍵可以是任何帶有 `__hash__()` 和 `__eq__()` method 的物件。在 Perl 中被稱雜 (hash)。

dictionary comprehension (字典綜合運算) 一種緊密的方法，用來處理一個可代物件中的全部或部分元素，將處理結果以一個字典回傳。`results = {n: n ** 2 for n in range(10)}` 會生一個字典，它包含了鍵 `n` 映射到值 `n ** 2`。請參 comprehensions。

dictionary view (字典檢視) 從 `dict.keys()`、`dict.values()` 及 `dict.items()` 回傳的物件被稱字典檢視。它們提供了字典中項目的動態檢視，這表示當字典有變動時，該檢視會反映這些變動。若要制將字典檢視轉完整的 list (串列)，須使用 `list(dictview)`。請參 dict-views。

docstring (明字串) 一個在 class、函式或模組中，作第一個運算式出現的字串文本。雖然它在套件執行時會被忽略，但它會被編譯器辨識，被放入所屬 class、函式或模組的 `__doc__` 屬性中。由於明字串可以透過省 (introspection) 來覽，因此它是物件的說明文件存放的標準位置。

duck-typing (鴨子型) 一種程式設計風格，它不是藉由檢查一個物件的型來確定它是否具有正確的介面；取而代之的是，method 或屬性會單純地被呼叫或使用。（「如果它看起來像一鴨子而且叫起來像一鴨子，那它一定是一鴨子。」）因調介面而非特定型，精心設計的程式碼能讓多形替代 (polymorphic substitution) 來增進它的靈活性。鴨子型要避免使用 `type()` 或 `isinstance()` 進行測試。（但是請注意，鴨子型可以用抽象基底類 (abstract base class) 來補充。）然而，它通常會用 `hasattr()` 測試，或是 EAFP 程式設計風格。

EAFP Easier to ask for forgiveness than permission. (請求寬恕比請求許可更容易。) 這種常見的 Python 編碼風格會先假設有效的鍵或屬性的存在，在該假設被推翻時再捕獲例外。這種乾且快速的風格，其特色是存在許多的 `try` 和 `except` 陳述式。該技術與許多其他語言 (例如 C) 常見的 LBYL 風格形成了對比。

expression (運算式) 一段可以被評估求值的語法。句話，一個運算式就是文字、名稱、屬性存取、運算子或函式呼叫等運算式元件的累積，而這些元件都能回傳一個值。與許多其他語言不同的

是，並非所有的 Python 語言構造都是運算式。另外有一些 *statement*（陳述式）不能被用作運算式，例如 `while`。賦值 (assignment) 也是陳述式，而不是運算式。

extension module（擴充模組） 一個以 C 或 C++ 編寫的模組，它使用 Python 的 C API 來與核心及使用者程式碼進行互動。

f-string（f 字串） 以 'f' 或 'F' 前綴的字串文本通常被稱「f 字串」，它是格式化的字串文本的縮寫。另請參 [PEP 498](#)。

file object（檔案物件） 一個讓使用者透過檔案導向 (file-oriented) API（如 `read()` 或 `write()` 等 method）來操作底層資源的物件。根據檔案物件被建立的方式，它能協調對真實磁碟檔案或是其他類型的儲存器或通訊裝置（例如標準輸入 / 輸出、記憶體緩衝區、socket（插座）、管（pipe）等）的存取。檔案物件也被稱類檔案物件 (*file-like object*) 或串流 (*stream*)。

實際上，有三種檔案物件：原始的二進制檔案、緩衝的二進制檔案和文字檔案。它們的介面在 `io` 模組中被定義。建立檔案物件的標準方法是使用 `open()` 函式。

file-like object（類檔案物件） *file object*（檔案物件）的同義字。

filesystem encoding and error handler（檔案系統編碼和錯誤處理函式） Python 所使用的一種編碼和錯誤處理函式，用來解碼來自作業系統的位元組，以及將 Unicode 編碼到作業系統。

檔案系統編碼必須保證能成功解碼所有小於 128 的位元組。如果檔案系統編碼無法提供此保證，則 API 函式會引發 `UnicodeError`。

`sys.getfilesystemencoding()` 和 `sys.getfilesystemencodeerrors()` 函式可用於取得檔案系統編碼和錯誤處理函式。

filesystem encoding and error handler（檔案系統編碼和錯誤處理函式）會在 Python 啟動時由 `PyConfig_Read()` 函式來配置：請參 [filesystem_encoding](#)，以及 `PyConfig` 的成員 [filesystem_errors](#)。

另請參 [locale encoding](#)（區域編碼）。

finder（尋檢器） 一個物件，它會嘗試正在被 `import` 的模組尋找 *loader*（載入器）。

從 Python 3.3 開始，有兩種類型的尋檢器：*元路徑尋檢器* (*meta path finder*) 會使用 `sys.meta_path`，而 *路徑項目尋檢器* (*path entry finder*) 會使用 `sys.path_hooks`。

請參 [PEP 302](#)、[PEP 420](#) 和 [PEP 451](#) 以了解更多細節。

floor division（向下取整除法） 向下無條件舍去到最接近整數的數學除法。向下取整除法的運算子是 `//`。例如，運算式 `11 // 4` 的計算結果 2，與 `float`（浮點數）真除法所回傳的 2.75 不同。請注意，`(-11) // 4` 的結果是 -3，因為是 -2.75 被向下無條件舍去。請參 [PEP 238](#)。

function（函式） 一連串的陳述式，它能向呼叫者回傳一些值。它也可以被傳遞零個或多個引數，這些引數可被使用於函式本體的執行。另請參 [parameter](#)（參數）、[method](#)（方法），以及 [function](#) 章節。

function annotation（函式釋） 函式參數或回傳值的一個 *annotation*（釋）。

函式釋通常被使用於 [型提示](#)：例如，這個函式預期會得到兩個 `int` 引數，會有一個 `int` 回傳值：

```
def sum_two_numbers(a: int, b: int) -> int:
    return a + b
```

函式釋的語法在 [function](#) 章節有詳細解釋。

請參 [variable annotation](#) 和 [PEP 484](#)，皆有此功能的描述。關於釋的最佳實踐方法，另請參 [annotations-howto](#)。

__future__ future 陳述式 `from __future__ import <feature>`，會指示編譯器使用那些在 Python 未來的發布版本中將成標準的語法或語義，來編譯當前的模組。而 `__future__` 模組則記了 *feature*（功能）可能的值。透過 `import` 此模組對其變數求值，你可以看見一個新的功能是何時首次被新增到此語言中，以及它何時將會（或已經）成預設的功能：

```
>>> import __future__
>>> __future__.division
_Feature((2, 2, 0, 'alpha', 2), (3, 0, 0, 'alpha', 0), 8192)
```

garbage collection (垃圾回收) 當記憶體不再被使用時，將其釋放的過程。Python 執行垃圾回收，是透過參照計數 (reference counting)，以及一個能檢測和中斷參照循環 (reference cycle) 的循環垃圾回收器 (cyclic garbage collector) 來完成。垃圾回收器可以使用 gc 模組對其進行控制。

generator (生成器) 一個會回傳 *generator iterator* (生成器迭代器) 的函式。它看起來像一個正常的函式，但不同的是它包含了 yield 運算式，能生成一系列的值得，這些值可用於 for 圈，或是以 next() 函式，每次檢索其中的一個值。

這個術語通常用來表示一個生成器函式，但在某些情境中，也可能是表示生成器迭代器。萬一想表達的意思不清楚，那就使用完整的術語，以避免歧義。

generator iterator (生成器迭代器) 一個由 *generator* (生成器) 函式所建立的物件。

每個 yield 會暫停處理程序，記住位置執行狀態 (包括區域變數及擱置中的 try 陳述式)。當生成器迭代器回復時，它會從停止的地方繼續執行 (與那些每次調用時都要重新開始的函式有所不同)。

generator expression (生成器運算式) 一個會回傳迭代器的運算式。它看起來像一個正常的運算式，後面接著一個 for 子句，該子句定義了圈變數、範圍以及一個選擇性的 if 子句。該組合運算式會在外層函數生成多個值：

```
>>> sum(i*i for i in range(10))          # sum of squares 0, 1, 4, ... 81
285
```

generic function (泛型函式) 一個由多個函式組成的函式，該函式會對不同的型實作相同的運算。呼叫期間應該使用哪種實作，是由調度演算法 (dispatch algorithm) 來固定。

另請參 *single dispatch* (單一調度) 術語表條目、functools.singledispatch() 裝飾器和 PEP 443。

generic type (泛型型) 一個能被參數化 (parameterized) 的 *type* (型)；通常是一個容器型，像是 list 和 dict。它被用於型提示和解釋。

詳情請參泛型名、PEP 483、PEP 484、PEP 585 和 typing 模組。

GIL 請參 *global interpreter lock* (全域直譯器鎖)。

global interpreter lock (全域直譯器鎖) CPython 直譯器所使用的機制，用以確保每次都只有一個執行緒能執行 Python 的 *bytecode* (位元組碼)。透過使物件模型 (包括關鍵的建型，如 dict) 自動地避免行存取 (concurrent access) 的危險，此機制可以簡化 CPython 的實作。鎖定整個直譯器，會使直譯器更容易成多執行緒 (multi-threaded)，但代價是會犧牲掉多處理器的機器能提供的一大部分平行性 (parallelism)。

然而，有些擴充模組，無論是標準的或是第三方的，它們被設計成在執行壓縮或雜等計算密集 (computationally intensive) 的任務時，可以解除 GIL。另外，在執行 I/O 時，GIL 總是會被解除。

過去對於建立「無限制執行緒」直譯器 (以更高的精細度鎖定共享資料的直譯器) 的努力未成功，因在一般的單一處理器情況下，效能會有所損失。一般認為，若要克服這個效能問題，會使實作變得雜許多，進而付出更高的維護成本。

hash-based pyc (雜架構的 pyc) 一個位元組碼 (bytecode) 暫存檔，它使用雜值而不是對應原始檔案的最後修改時間，來確定其有效性。請參 pyc-invalidation。

hashable (可雜的) 如果一個物件有一個雜值，該值在其生命期中永不改變 (它需要一個 __hash__() method)，且可與其他物件互相比較 (它需要一個 __eq__() method)，那麼它就是一個可雜物件。比較結果相等的多個可雜物件，它們必須擁有相同的雜值。

可雜性 (hashability) 使一個物件可用作 dictionary (字典) 的鍵和 set (集合) 的成員，因這些資料結構都在其內部使用了雜值。

大多數的 Python 不可變建物件都是可雜的；可變的容器 (例如 list 或 dictionary) 不是；而不可變的容器 (例如 tuple (元組) 和 frozenset)，只有當它們的元素是可雜的，它們本身才是可雜

的。若物件是使用者自定 class 的實例，則這些物件會被預設可雜的。它們在互相比較時都是不相等的（除非它們與自己比較），而它們的雜值則是衍生自它們的 `id()`。

IDLE Python 的 Integrated Development and Learning Environment（整合開發與學習環境）。idle 是一個基本的編輯器和直譯器環境，它和 Python 的標準發行版本一起被提供。

immutable（不可變物件） 一個具有固定值的物件。不可變物件包括數字、字串和 tuple（元組）。這類物件是不能被改變的。如果一個不同的值必須被儲存，則必須建立一個新的物件。它們在需要固定雜值的地方，扮演重要的角色，例如 dictionary（字典）中的一個鍵。

import path（匯入路徑） 一個位置（或路徑項目）的列表，而那些位置就是在 import 模組時，會被 *path based finder*（基於路徑的尋檢器）搜尋模組的位置。在 import 期間，此位置列表通常是來自 `sys.path`，但對於子套件（subpackage）而言，它也可能是來自父套件的 `__path__` 屬性。

importing（匯入） 一個過程。一個模組中的 Python 程式碼可以透過此過程，被另一個模組中的 Python 程式碼使用。

importer（匯入器） 一個能尋找及載入模組的物件；它既是 *finder*（尋檢器）也是 *loader*（載入器）物件。

interactive（互動的） Python 有一個互動式直譯器，這表示你可以在直譯器的提示字元輸入陳述式和運算式，立即執行它們且看到它們的結果。只要互動 `python`，不需要任何引數（可能藉由從你的電腦的主選單選擇它）。這是測試新想法或檢查模塊和包的非常大的方法（請記住 `help(x)`）。

interpreted（直譯的） Python 是一種直譯語言，而不是編譯語言，不過這個區分可能有些模糊，因為有位元組碼（bytecode）編譯器的存在。這表示原始檔案可以直接被運行，而不需明確地建立另一個執行檔，然後再執行它。直譯語言通常比編譯語言有更短的開發 / 除錯期，不過它們的程式通常也運行得較慢。另請參閱 *interactive*（互動的）。

interpreter shutdown（直譯器關閉） 當 Python 直譯器被要求關閉時，它會進入一個特殊階段，在此它逐漸釋放所有被配置的資源，例如模組和各種關鍵部結構。它也會多次呼叫垃圾回收器（*garbage collector*）。這能觸發使用者自定的解構函式（*destructor*）或弱引用的回呼（*weakref callback*），執行其中的程式碼。在關閉階段被執行的程式碼會遇到各種例外，因為它所依賴的資源可能不再有作用了（常見的例子是函式庫模組或是警告機制）。

直譯器關閉的主要原因，是 `__main__` 模組或正被運行的本已經執行完成。

iterable（可代物件） 一種能一次回傳一個其中成員的物件。可代物件的例子包括所有的序列型（像是 `list`、`str` 和 `tuple`）和某些非序列型，像是 `dict`、檔案物件，以及你所定義的任何 class 物件，只要那些 class 有 `__iter__()` method 或是實作 *Sequence*（序列）語意的 `__getitem__()` method，該物件就是可代物件。

可代物件可用於 `for` 圈和許多其他需要一個序列的地方（`zip()`、`map()`...）。當一個可代物件作引數被傳遞給建函式 `iter()` 時，它會該物件回傳一個代器。此代器適用於針對一組值進行一遍（*one pass*）運算。使用代器時，通常不一定要呼叫 `iter()` 或自行處理代器物件。`for` 陳述式會自動地你處理這些事，它會建立一個暫時性的未命名變數，用於在圈期間保有該代器。另請參閱 *iterator*（代器）、*sequence*（序列）和 *generator*（生器）。

iterator（代器） 一個表示資料流的物件。重地呼叫代器的 `__next__()` method（或是將它傳遞給建函式 `next()`）會依序回傳資料流中的各項目。當不再有資料時，則會引發 `StopIteration` 例外。此時，該代器物件已被用盡，而任何對其 `__next__()` method 的進一步呼叫，都只會再次引發 `StopIteration`。代器必須有一個 `__iter__()` method，它會回傳代器物件本身，所以每個代器也都是可代物件，且可以用於大多數適用其他可代物件的場合。一個明顯的例外，是嘗試多遍代（*multiple iteration passes*）的程式碼。一個容器物件（像是 `list`）在每次你將它傳遞給 `iter()` 函式或在 `for` 圈中使用它時，都會生一個全新的代器。使用代器嘗試此事（多遍代）時，只會回傳在前一遍代中被用過的、同一個已被用盡的代器物件，使其看起來就像一個空的容器。

在 `typeiter` 文中可以找到更多資訊。

CPython 實作細節： CPython 不是始終如一地都會檢查「代器有定義 `__iter__()`」這個規定。

key function（鍵函式） 鍵函式或理序函式（*collation function*）是一個可呼叫（*callable*）函式，它會回傳一個用於排序（*sorting*）或定序（*ordering*）的值。例如，`locale.strxfrm()` 被用來生一個了解區域特定排序慣例的排序鍵。

Python 中的許多工具，都接受以鍵函式來控制元素被定序或分組的方式。它們包括 `min()`、`max()`、`sorted()`、`list.sort()`、`heapq.merge()`、`heapq.nsmallest()`、`heapq.nlargest()` 和 `itertools.groupby()`。

有幾種方法可以建立一個鍵函式。例如，`str.lower()` method 可以作不分大小寫排序的鍵函式。或者，一個鍵函式也可以從 `lambda` 運算式被建造，例如 `lambda r: (r[0], r[2])`。另外，`operator` 模組提供了三個鍵函式的建構函式 (constructor): `attrgetter()`、`itemgetter()` 和 `methodcaller()`。關於如何建立和使用鍵函式的範例，請參如何排序。

keyword argument (關鍵字引數) 請參 `argument` (引數)。

lambda 由單一 *expression* (運算式) 所組成的一個匿名行函式 (inline function)，於該函式被呼叫時求值。建立 `lambda` 函式的語法是 `lambda [parameters]: expression`

LBYL Look before you leap. (三思而後行。) 這種編碼風格會在進行呼叫或查找之前，明確地測試先條件。這種風格與 *EAFP* 方式形成對比，且它的特色是會有許多 `if` 陳述式的存在。

在一個多執行緒環境中，LBYL 方式有在「三思」和「後行」之間引入了競條件 (race condition) 的風險。例如以下程式碼 `if key in mapping: return mapping[key]`，如果另一個執行緒在測試之後但在查找之前，從 *mapping* 中移除了 *key*，則該程式碼就會失效。這個問題可以用鎖 (lock) 或使用 *EAFP* 編碼方式來解。

locale encoding (區域編碼) 在 Unix 上，它是 `LC_CTYPE` 區域設定的編碼。它可以用 `locale.setlocale(locale.LC_CTYPE, new_locale)` 來設定。

在 Windows 上，它是 ANSI 代碼頁 (code page，例如 `cp1252`)。

`locale.getpreferredencoding(False)` 可以用來取得區域編碼。

Python 使用 *filesystem encoding and error handler* (檔案系統編碼和錯誤處理函式) 在 Unicode 檔案名稱和位元組檔案名稱之間進行轉。

list (串列) 一個 Python 建的 *sequence* (序列)。管它的名字是 `list`，它其實更類似其他語言中的一個陣列 (array) 而較不像一個鏈結串列 (linked list)，因存取元素的時間複雜度是 $O(1)$ 。

list comprehension (串列綜合運算) 一種用來處理一個序列中的全部或部分元素，將處理結果以一個 `list` 回傳的簡要方法。`result = ['{:04x}'.format(x) for x in range(256) if x % 2 == 0]` 會生一個字串 `list`，其中包含 0 到 255 範圍，所有偶數的十六進位數 (0x.)。 `if` 子句是選擇性的。如果省略它，則 `range(256)` 中的所有元素都會被處理。

loader (載入器) 一個能載入模組的物件。它必須定義一個名 `load_module()` 的 method (方法)。載入器通常是被 *finder* (尋檢器) 回傳。更多細節請參 **PEP 302**，關於 *abstract base class* (抽象基底類)，請參 `importlib.abc.Loader`。

magic method (魔術方法) *special method* (特殊方法) 的一個非正式同義詞。

mapping (對映) 一個容器物件，它支援任意鍵的查找，且能實作 *abstract base classes* (抽象基底類) 中，`Mapping` 或 `MutableMapping` 所指定的 method。範例包括 `dict`、`collections.defaultdict`、`collections.OrderedDict` 和 `collections.Counter`。

meta path finder (元路徑尋檢器) 一種經由搜尋 `sys.meta_path` 而回傳的 *finder* (尋檢器)。元路徑尋檢器與路徑項目尋檢器 (*path entry finder*) 相關但是不同。

關於元路徑尋檢器實作的 method，請參 `importlib.abc.MetaPathFinder`。

metaclass (元類) 一種 `class` 的 `class`。`Class` 定義過程會建立一個 `class` 名稱、一個 `class` dictionary (字典)，以及一個 `base class` (基底類) 的列表。`Metaclass` 負責接受這三個引數，建立該 `class`。大多數的物件導向程式語言會提供一個預設的實作。Python 的特之處在於它能建立自訂的 *metaclass*。大部分的使用者從未需要此工具，但是當需要時，*metaclass* 可以提供大且優雅的解方案。它們已被用於記屬性存取、增加執行緒安全性、追物件建立、實作單例模式 (singleton)，以及許多其他的任務。

更多資訊可以在 *metaclasses* 章節中找到。

method (方法) 一個在 `class` 本體被定義的函式。如果 method 作其 `class` 實例的一個屬性被呼叫，則它將會得到該實例物件成它的第一個 *argument* (引數) (此引數通常被稱 `self`)。請參 *function* (函式) 和 *nested scope* (巢狀作用域)。

method resolution order (方法解析順序) 方法解析順序是在查找某個成員的過程中，base class (基底類) 被搜尋的順序。關於第 2.3 版至今，Python 直譯器所使用的演算法細節，請參 Python 2.3 版方法解析順序。

module (模組) 一個擔任 Python 程式碼的組織單位 (organizational unit) 的物件。模組有一個命名空間，它包含任意的 Python 物件。模組是藉由 *importing* 的過程，被載入至 Python。

另請參 *package* (套件)。

module spec (模組規格) 一個命名空間，它包含用於載入模組的 import 相關資訊。它是 `importlib.machinery.ModuleSpec` 的一個實例。

MRO 請參 *method resolution order* (方法解析順序)。

mutable (可變物件) 可變物件可以改變它們的值，但維持它們的 `id()`。另請參 *immutable* (不可變物件)。

named tuple (附名元組) 術語「named tuple (附名元組)」是指從 tuple 繼承的任何型或 class，且它的可索引 (indexable) 元素也可以用附名屬性來存取。這些型或 class 也可以具有其他的特性。

有些建型是 named tuple，包括由 `time.localtime()` 和 `os.stat()` 回傳的值。另一個例子是 `sys.float_info`：

```
>>> sys.float_info[1]                # indexed access
1024
>>> sys.float_info.max_exp           # named field access
1024
>>> isinstance(sys.float_info, tuple) # kind of tuple
True
```

有些 named tuple 是建型 (如上例)。或者，一個 named tuple 也可以從一個正規的 class 定義來建立，只要該 class 是繼承自 tuple，且定義了附名欄位 (named field) 即可。這類的 class 可以手工編寫，也可以使用工廠函式 (factory function) `collections.namedtuple()` 來建立。後者技術也增加了一些額外的 method，這些 method 可能是在手寫或建的 named tuple 中，無法找到的。

namespace (命名空間) 變數被儲存的地方。命名空間是以 dictionary (字典) 被實作。有區域的、全域的及建的命名空間，而在物件中 (在 method 中) 也有巢狀的命名空間。命名空間藉由防止命名衝突，來支援模組化。例如，函式 `builtins.open` 和 `os.open()` 是透過它們的命名空間來區分彼此。命名空間也藉由明確地區分是哪個模組在實作一個函式，來增進可讀性及可維護性。例如，寫出 `random.seed()` 或 `itertools.islice()` 明確地表示，這些函式分是由 `random` 和 `itertools` 模組在實作。

namespace package (命名空間套件) 一個 **PEP 420 package** (套件)，它只能作子套件 (subpackage) 的一個容器。命名空間套件可能沒有實體的表示法，而且具體來它們不像是一個 *regular package* (正規套件)，因它們有 `__init__.py` 這個檔案。

另請參 *module* (模組)。

nested scope (巢狀作用域) 能參照外層定義 (enclosing definition) 中的變數的能力。舉例來，一個函式如果是在另一個函式中被定義，則它便能參照外層函式中的變數。請注意，在預設情況下，巢狀作用域僅適用於參照，而無法用於賦值。區域變數能在最層作用域中讀取及寫入。同樣地，全域變數是在全域命名空間中讀取及寫入。`nonlocal` 容許對外層作用域進行寫入。

new-style class (新式類) 一個舊名，它是指現在所有的 class 物件所使用的 class 風格。在早期的 Python 版本中，只有新式 class 才能使用 Python 較新的、多樣的功能，像是 `__slots__`、描述器 (descriptor)、屬性 (property)、`__getattr__()`、class method (類方法) 和 static method (態方法)。

object (物件) 具有狀態 (屬性或值) 及被定義的行 (method) 的任何資料。它也是任何 *new-style class* (新式類) 的最終 base class (基底類)。

package (套件) A Python *module* which can contain submodules or recursively, subpackages. Technically, a package is a Python module with a `__path__` attribute.

另請參 *regular package* (正規套件) 和 *namespace package* (命名空間套件)。

parameter (參數) 在 *function* (函式) 或 *method* 定義中的一個命名實體 (named entity), 它指明該函式能接受的一個 *argument* (引數), 或在某些情況下指示多個引數。共有五種不同的參數類型:

- *positional-or-keyword* (位置或關鍵字): 指明一個可以按位置或是作關鍵字引數被傳遞的引數。這是參數的預設類型, 例如以下的 *foo* 和 *bar*:

```
def func(foo, bar=None): ...
```

- *positional-only* (僅限位置): 指明一個只能按照位置被提供的引數。在函式定義的參數列表中包含一個 `/` 字元, 就可以在該字元前面定義僅限位置參數, 例如以下的 *posonly1* 和 *posonly2*:

```
def func(posonly1, posonly2, /, positional_or_keyword): ...
```

- *keyword-only* (僅限關鍵字): 指明一個只能以關鍵字被提供的引數。在函式定義的參數列表中, 包含一個任意數量位置參數 (var-positional parameter) 或是單純的 `*` 字元, 可以在其後方定義僅限關鍵字參數, 例如以下的 *kw_only1* 和 *kw_only2*:

```
def func(arg, *, kw_only1, kw_only2): ...
```

- *var-positional* (任意數量位置): 指明一串能以任意序列被提供的位置引數 (在已被其他參數接受的任何位置引數之外)。這類參數是透過在其參數名稱字首加上 `*` 來定義的, 例如以下的 *args*:

```
def func(*args, **kwargs): ...
```

- *var-keyword* (任意數量關鍵字): 指明可被提供的任意數量關鍵字引數 (在已被其他參數接受的任何關鍵字引數之外)。這類參數是透過在其參數名稱字首加上 `**` 來定義的, 例如上面範例中的 *kwargs*。

參數可以指明引數是選擇性的或必需的, 也可以一些選擇性的引數指定預設值。

另請參術語表的 *argument* (引數) 條目、常見問題中的引數和參數之間的差別、*inspect*、*Parameter class*、*function* 章節, 以及 **PEP 362**。

path entry (路徑項目) 在 *import path* (匯入路徑) 中的一個位置, 而 *path based finder* (基於路徑的尋檢器) 會參考該位置來尋找要 *import* 的模組。

path entry finder (路徑項目尋檢器) 被 *sys.path_hooks* 中的一個可呼叫物件 (callable) (意即一個 *path entry hook*) 所回傳的一種 *finder*, 它知道如何以一個 *path entry* 定位模組。

關於路徑項目尋檢器實作的 *method*, 請參 `importlib.abc.PathEntryFinder`。

path entry hook (路徑項目) 在 *sys.path_hook* 列表中的一個可呼叫物件 (callable), 若它知道如何在一個特定的 *path entry* 中尋找模組, 則會回傳一個 *path entry finder* (路徑項目尋檢器)。

path based finder (基於路徑的尋檢器) 預設的元路徑尋檢器 (*meta path finder*) 之一, 它會在一個 *import path* 中搜尋模組。

path-like object (類路徑物件) 一個表示檔案系統路徑的物件。類路徑物件可以是一個表示路徑的 *str* 或 *bytes* 物件, 或是一個實作 *os.PathLike* 協定的物件。透過呼叫 *os.fspath()* 函式, 一個支援 *os.PathLike* 協定的物件可以被轉成 *str* 或 *bytes* 檔案系統路徑; 而 *os.fsdecode()* 及 *os.fsencode()* 則分別可用於確保 *str* 及 *bytes* 的結果。由 **PEP 519** 引入。

PEP Python Enhancement Proposal (Python 增提案)。PEP 是一份設計明文件, 它能 Python 社群提供資訊, 或是描述 Python 的一個新功能或該功能的程序和環境。PEP 應該要提供簡潔的技術規範以及被提案功能的運作原理。

PEP 的存在目的, 是要成重大新功能的提案、社群中關於某個問題的意見收集, 以及已納入 Python 的設計策的記, 這些過程的主要機制。PEP 的作者要負責在社群建立共識反對意見。

請參 **PEP 1**。

portion (部分) 在單一目中的一組檔案 (也可能儲存在一個 *zip* 檔中), 這些檔案能對一個命名空間套件 (namespace package) 有所貢獻, 如同 **PEP 420** 中的定義。

positional argument (位置引數) 請參閱 [argument \(引數\)](#)。

provisional API (暫行 API) 暫行 API 是指，從標準函式庫的向後相容性 (backwards compatibility) 保證中，故意被排除的 API。雖然此類介面，只要它們被標示為暫行的，理論上不會有重大的變更，但如果核心開發人員認為有必要，也可能會出現向後不相容的變更（甚至包括移除該介面）。這種變更不會無端地發生——只有 API 被納入之前未察覺的嚴重基本缺陷被揭露時，它們才會發生。

即使對於暫行 API，向後不相容的變更也會被視為「最後的解決方案」——對於任何被發現的問題，仍然會盡可能找出一個向後相容的解決方案。

這個過程使得標準函式庫能隨著時間不斷進化，而避免耗費過長的時間去鎖定有問題的設計錯誤。請參閱 [PEP 411](#) 了解更多細節。

provisional package (暫行套件) 請參閱 [provisional API \(暫行 API\)](#)。

Python 3000 Python 3.x 系列版本的暱稱（很久以前創造的，當時第 3 版的發布是在很遠的未來。）也可以縮寫為「Py3k」。

Pythonic (Python 風格的) 一個想法或一段程式碼，它應用了 Python 語言最常見的慣用語，而不是使用其他語言常見的概念來實作程式碼。例如，Python 中常見的一種習慣用法，是使用一個 `for` 陳述式，對一個可迭代物件的所有元素進行遍歷。許多其他語言也有這種類型的架構，所以不熟悉 Python 的人有時會使用一個數值計數器來代替：

```
for i in range(len(food)):
    print(food[i])
```

相較之下，以下方法更簡潔、更具有 Python 風格：

```
for piece in food:
    print(piece)
```

qualified name (限定名稱) 一個「點分隔名稱」，它顯示從一個模組的全域作用域到該模組中定義的 `class`、函式或 `method` 的「路徑」，如 [PEP 3155](#) 中的定義。對於頂層的函式和 `class` 而言，限定名稱與其物件名稱相同：

```
>>> class C:
...     class D:
...         def meth(self):
...             pass
...
>>> C.__qualname__
'C'
>>> C.D.__qualname__
'C.D'
>>> C.D.meth.__qualname__
'C.D.meth'
```

當用於引用模組時，完全限定名 (*fully qualified name*) 是表示該模組的完整點分隔路徑，包括任何的父套件，例如 `email.mime.text`：

```
>>> import email.mime.text
>>> email.mime.text.__name__
'email.mime.text'
```

reference count (參照計數) 對於一個物件的參照次數。當一個物件的參照計數下降到零時，它會被解除配置 (deallocated)。參照計數通常在 Python 程式碼中看不到，但它 [是 CPython 實作的一個關鍵元素](#)。`sys` 模組定義了一個 `getrefcount()` 函式，程序設計師可以呼叫該函式來回傳一個特定物件的參照計數。

regular package (正規套件) 一個傳統的 *package* (套件)，例如一個包含 `__init__.py` 檔案的目錄。

另請參閱 [namespace package \(命名空間套件\)](#)。

__slots__ 在 class 的一個宣告，它藉由預先宣告實例屬性的空間，以及消除實例 dictionary（字典），來節省記憶體。雖然該技術很普遍，但它有點難以正確地使用，最好保留給那種在一個記憶體關鍵（memory-critical）的應用程式中存在大量實例的罕見情況。

sequence（序列） 一個 *iterable*（可迭代物件），它透過 `__getitem__()` special method（特殊方法），使用整數索引來支援高效率的元素存取，它定義了一個 `__len__()` method 來回傳該序列的長度。一些 Python 建序列型包括 `list`、`str`、`tuple` 和 `bytes`。請注意，雖然 `dict` 也支援 `__getitem__()` 和 `__len__()`，但它被視為對映（mapping）而不是序列，因為其查找方式是使用任意的 *immutable* 鍵，而不是整數。

抽象基底類（abstract base class）`collections.abc.Sequence` 定義了一個更加豐富的介面，不僅止於 `__getitem__()` 和 `__len__()`，還增加了 `count()`、`index()`、`__contains__()` 和 `__reversed__()`。實作此擴充介面的型，可以使用 `register()` 被明確地註冊。

set comprehension（集合綜合運算） 一種緊密的方法，用來處理一個可迭代物件中的全部或部分元素，它將處理結果以一個 `set` 回傳。`results = {c for c in 'abracadabra' if c not in 'abc'}` 會生成一個字串 `set: {'r', 'd'}`。請參閱 *comprehensions*。

single dispatch（單一調度） *generic function*（泛型函式）調度的一種形式，在此，實作的選擇是基於單一引數的型。

slice（切片） 一個物件，它通常包含一段 *sequence*（序列）的某一部分。建立一段切片的方法是使用下標符號（subscript notation）`[]`，若要給出多個數字，則在數字之間使用冒號，例如 `variable_name[1:3:5]`。在括號（下標）符號的內部，會使用 `slice` 物件。

special method（特殊方法） 一種會被 Python 自動呼叫的 `method`，用於對某種型執行某種運算，例如加法。這種 `method` 的名稱會在開頭和結尾有兩個下底線。Special method 在 `specialnames` 中有詳細說明。

statement（陳述式） 陳述式是一個套組（suite，一個程式碼「區塊」）中的一部分。陳述式可以是一個 *expression*（運算式），或是含有關鍵字（例如 `if`、`while` 或 `for`）的多種結構之一。

strong reference（強參照） 在 Python 的 C API 中，強參照是一個對物件的參照，在它被建立時會增加該物件的參照計數（reference count），在它被刪除時則會減少該物件的參照計數。

`Py_NewRef()` 函式可用於建立一個對物件的強參照。通常，在退出強參照的作用域之前，必須在該強參照上呼叫 `Py_DECREF()` 函式，以避免洩漏一個參照。

另請參閱 *borrowed reference*（借用參照）。

text encoding（文字編碼） Python 中的字串是一個 Unicode 碼點（code point）的序列（範圍在 `U+0000` -- `U+10FFFF` 之間）。若要儲存或傳送一個字串，它必須被序列化為一個位元組序列。

將一個字串序列化為位元組序列，稱為「編碼」，而從位元組序列重新建立該字串則稱為「解碼（decoding）」。

有多種不同的文字序列化編解碼器（codecs），它們被統稱為「文字編碼」。

text file（文字檔案） 一個能讀取和寫入 `str` 物件的一個 *file object*（檔案物件）。通常，文字檔案實際上是存取位元組導向的資料流（byte-oriented datastream）會自動處理 *text encoding*（文字編碼）。文字檔案的例子有：以文字模式（`'r'` 或 `'w'`）開啟的檔案、`sys.stdin`、`sys.stdout` 以及 `io.StringIO` 的實例。

另請參閱 *binary file*（二進制檔案），它是一個能讀取和寫入類位元組串物件（*bytes-like object*）的檔案物件。

triple-quoted string（三引號字串） 由三個雙引號（`"`）或單引號（`'`）的作邊界的一個字串。雖然它們沒有提供於單引號字串的任何額外功能，但基於許多原因，它們仍是很有用的。它們讓你可以字串中包含未跳脫（unescaped）的單引號和雙引號，而且它們不需使用連續字元（continuation character）就可以跨越多行，這使得它們在編寫明文字串時特別有用。

type（型） 一個 Python 物件的型定義了它是什麼類型的物件；每個物件都有一個型。一個物件的型可以用它的 `__class__` 屬性來存取，或以 `type(obj)` 來檢索。

type alias（型別名） 一個型的同義詞，透過將型指定給一個識別符（identifier）來建立。

型別名對於簡化型提示（*type hint*）很有用。例如：

```
def remove_gray_shades(
    colors: list[tuple[int, int, int]]) -> list[tuple[int, int, int]]:
    pass
```

可以寫成這樣，更具有可讀性：

```
Color = tuple[int, int, int]

def remove_gray_shades(colors: list[Color]) -> list[Color]:
    pass
```

請參閱 [typing](#) 和 [PEP 484](#)，有此功能的描述。

type hint (型提示) 一種 *annotation* (釋)，它指定一個變數、一個 class 屬性或一個函式的參數或回傳值的預期型。

型提示是選擇性的，而不是被 Python 制的，但它們對態型分析工具很有用，能協助 IDE 完成程式碼的補全 (completion) 和重構 (refactoring)。

全域變數、class 屬性和函式 (不含區域變數) 的型提示，都可以使用 `typing.get_type_hints()` 來存取。

請參閱 [typing](#) 和 [PEP 484](#)，有此功能的描述。

universal newlines (通用行字元) 一種解譯文字流 (text stream) 的方式，會將以下所有的情識一行的結束：Unix 行尾慣例 '\n'、Windows 慣例 '\r\n' 和舊的 Macintosh 慣例 '\r'。請參閱 [PEP 278](#) 和 [PEP 3116](#)，以及用於 `bytes.splitlines()` 的附加用途。

variable annotation (變數釋) 一個變數或 class 屬性的 *annotation* (釋)。

釋變數或 class 屬性時，賦值是選擇性的：

```
class C:
    field: 'annotation'
```

變數釋通常用於型提示 (*type hint*)：例如，這個變數預期會取得 `int` (整數) 值：

```
count: int = 0
```

變數釋的語法在 [annassign](#) 章節有詳細的解釋。

請參閱 [function annotation](#) (函式釋)、[PEP 484](#) 和 [PEP 526](#)，皆有此功能的描述。關於釋的最佳實踐方法，另請參閱 [annotations-howto](#)。

virtual environment (擬環境) 一個協作隔離 (cooperatively isolated) 的執行環境，能讓 Python 的使用者和應用程式得以安裝和升級 Python 發套件，而不會對同一個系統上運行的其他 Python 應用程式的行生干擾。

另請參閱 [venv](#)。

virtual machine (擬機器) 一部完全由軟體所定義的電腦 (computer)。Python 的擬機器會執行由 *bytecode* (位元組碼) 編譯器所發出的位元組碼。

Zen of Python (Python 之) Python 設計原則與哲學的列表，其容有助於理解和使用此語言。此列表可以透過在互動式提示字元後輸入 `import this` 來找到它。

關於這些📄明文件

這些📄明文件是透過 [Sphinx](#)（一個專📄 Python 📄明文件所撰寫的文件處理器）將使用 [reStructuredText](#) 撰寫的原始檔轉📄而成。

如同 Python 自身，透過自願者的努力下📄出文件與封裝後自動化執行工具。若想要回報臭蟲，請見 [reporting-bugs](#) 頁面，📄含相關資訊。我們永遠歡迎新的自願者加入！

致謝：

- Fred L. Drake, Jr.，原始 Python 文件工具集的創造者以及一大部份📄容的作者；
- 創造 [reStructuredText](#) 和 [Docutils](#) 工具組的 [Docutils](#) 專案；
- Fredrik Lundh 先生，[Sphinx](#) 從他的 [Alternative Python Reference](#) 計劃中獲得許多的好主意。

B.1 Python 文件的貢獻者們

許多人都曾📄 Python 這門語言、Python 標準函式庫和 Python 📄明文件貢獻過。Python 所發📄的原始碼中含有部份貢獻者的清單，請見 [Misc/ACKS](#)。

正因📄 Python 社群的撰寫與貢獻才有這份這📄棒的📄明文件 -- 感謝所有貢獻過的人們！

沿革與授權

C.1 軟體沿革

Python 是由荷蘭數學和計算機科學研究學會（CWI，見 <https://www.cwi.nl/>）的 Guido van Rossum 於 1990 年代早期所創造，目的是作一種稱作 ABC 語言的後繼者。儘管 Python 包含了許多來自其他人的貢獻，Guido 仍是其主要作者。

1995 年，Guido 在維吉尼亞州雷斯頓的國家創新研究公司（CNRI，見 <https://www.cnri.reston.va.us/>）繼續他在 Python 的工作，在那發行了該軟體的多個版本。

2000 年五月，Guido 和 Python 核心開發團隊轉移到 BeOpen.com 成立了 BeOpen PythonLabs 團隊。同年十月，PythonLabs 團隊轉移到 Digital Creations（現 Zope Corporation；見 <https://www.zope.org/>）。2001 年，Python 軟體基金會（PSF，見 <https://www.python.org/psf/>）成立，這是一個專擁有 Python 相關的智慧財產權而創立的非營利組織。Zope Corporation 是 PSF 的一個贊助會員。

所有的 Python 版本都是開源的（有關開源的定義，參見 <https://opensource.org/>）。歷史上，大多數但非全部的 Python 版本，也是 GPL 相容的；以下表格總結各個版本的差異。

發行版本	源自	年份	擁有者	GPL 相容性？
0.9.0 至 1.2	不適用	1991-1995	CWI	是
1.3 至 1.5.2	1.2	1995-1999	CNRI	是
1.6	1.5.2	2000	CNRI	否
2.0	1.6	2000	BeOpen.com	否
1.6.1	1.6	2001	CNRI	否
2.1	2.0+1.6.1	2001	PSF	否
2.0.1	2.0+1.6.1	2001	PSF	是
2.1.1	2.1+2.0.1	2001	PSF	是
2.1.2	2.1.1	2002	PSF	是
2.1.3	2.1.2	2002	PSF	是
2.2 以上	2.1.1	2001 至今	PSF	是

備註：GPL 相容並不表示我們是在 GPL 下發行 Python。不像 GPL，所有的 Python 授權都可以讓您發行修改後的版本，但不一定要使您的變更成開源。GPL 相容的授權使得 Python 可以結合其他在 GPL 下發行的軟體一起使用；但其它的授權則不行。

感謝許多的外部志工，在 Guido 指導下的付出，使得這些版本的發成可能。

C.2 關於存取或以其他方式使用 Python 的合約條款

Python 軟體和明文件的授權是基於 *PSF 授權合約*。

從 Python 3.8.6 開始，明文件中的範例、程式庫和其他程式碼，是被雙重授權 (dual licensed) 於 PSF 授權合約以及 *Zero-Clause BSD* 授權。

有些被納入 Python 中的軟體是基於不同的授權。這些授權將會與其授權之程式碼一起被列出。關於這些授權的不完整清單，請參被收軟體的授權與致謝。

C.2.1 用於 PYTHON 3.10.11 的 PSF 授權合約

1. This LICENSE AGREEMENT is between the Python Software Foundation,
→ ("PSF"), and
the Individual or Organization ("Licensee") accessing and otherwise
→ using Python
3.10.11 software in source or binary form and its associated
→ documentation.
2. Subject to the terms and conditions of this License Agreement, PSF
→ hereby
grants Licensee a nonexclusive, royalty-free, world-wide license to
→ reproduce,
analyze, test, perform and/or display publicly, prepare derivative
→ works,
distribute, and otherwise use Python 3.10.11 alone or in any derivative
version, provided, however, that PSF's License Agreement and PSF's
→ notice of
copyright, i.e., "Copyright © 2001–2023 Python Software Foundation; All
→ Rights
Reserved" are retained in Python 3.10.11 alone or in any derivative
→ version
prepared by Licensee.
3. In the event Licensee prepares a derivative work that is based on or
incorporates Python 3.10.11 or any part thereof, and wants to make the
derivative work available to others as provided herein, then Licensee
→ hereby
agrees to include in any such work a brief summary of the changes made
→ to Python
3.10.11.
4. PSF is making Python 3.10.11 available to Licensee on an "AS IS" basis.
PSF MAKES NO REPRESENTATIONS OR WARRANTIES, EXPRESS OR IMPLIED. BY WAY
→ OF
EXAMPLE, BUT NOT LIMITATION, PSF MAKES NO AND DISCLAIMS ANY
→ REPRESENTATION OR
WARRANTY OF MERCHANTABILITY OR FITNESS FOR ANY PARTICULAR PURPOSE OR
→ THAT THE
USE OF PYTHON 3.10.11 WILL NOT INFRINGE ANY THIRD PARTY RIGHTS.
5. PSF SHALL NOT BE LIABLE TO LICENSEE OR ANY OTHER USERS OF PYTHON 3.10.11
FOR ANY INCIDENTAL, SPECIAL, OR CONSEQUENTIAL DAMAGES OR LOSS AS A
→ RESULT OF

MODIFYING, DISTRIBUTING, OR OTHERWISE USING PYTHON 3.10.11, OR ANY
 ↳DERIVATIVE
 THEREOF, EVEN IF ADVISED OF THE POSSIBILITY THEREOF.

6. This License Agreement will automatically terminate upon a material
 ↳breach of
 its terms and conditions.

7. Nothing in this License Agreement shall be deemed to create any
 ↳relationship
 of agency, partnership, or joint venture between PSF and Licensee. ↳
 ↳This License
 Agreement does not grant permission to use PSF trademarks or trade name ↳
 ↳in a
 trademark sense to endorse or promote products or services of Licensee, ↳
 ↳or any
 third party.

8. By copying, installing or otherwise using Python 3.10.11, Licensee ↳
 ↳agrees
 to be bound by the terms and conditions of this License Agreement.

C.2.2 用於 PYTHON 2.0 的 BEOPEN.COM 授權合約

BEOPEN PYTHON 開源授權合約第 1 版

1. This LICENSE AGREEMENT is between BeOpen.com ("BeOpen"), having an office at 160 Saratoga Avenue, Santa Clara, CA 95051, and the Individual or Organization ("Licensee") accessing and otherwise using this software in source or binary form and its associated documentation ("the Software").
2. Subject to the terms and conditions of this BeOpen Python License Agreement, BeOpen hereby grants Licensee a non-exclusive, royalty-free, world-wide license to reproduce, analyze, test, perform and/or display publicly, prepare derivative works, distribute, and otherwise use the Software alone or in any derivative version, provided, however, that the BeOpen Python License is retained in the Software, alone or in any derivative version prepared by Licensee.
3. BeOpen is making the Software available to Licensee on an "AS IS" basis. BEOPEN MAKES NO REPRESENTATIONS OR WARRANTIES, EXPRESS OR IMPLIED. BY WAY OF EXAMPLE, BUT NOT LIMITATION, BEOPEN MAKES NO AND DISCLAIMS ANY REPRESENTATION OR WARRANTY OF MERCHANTABILITY OR FITNESS FOR ANY PARTICULAR PURPOSE OR THAT THE USE OF THE SOFTWARE WILL NOT INFRINGE ANY THIRD PARTY RIGHTS.
4. BEOPEN SHALL NOT BE LIABLE TO LICENSEE OR ANY OTHER USERS OF THE SOFTWARE FOR ANY INCIDENTAL, SPECIAL, OR CONSEQUENTIAL DAMAGES OR LOSS AS A RESULT OF USING, MODIFYING OR DISTRIBUTING THE SOFTWARE, OR ANY DERIVATIVE THEREOF, EVEN IF ADVISED OF THE POSSIBILITY THEREOF.
5. This License Agreement will automatically terminate upon a material breach of its terms and conditions.
6. This License Agreement shall be governed by and interpreted in all respects by the law of the State of California, excluding conflict of law provisions. Nothing in this License Agreement shall be deemed to create any relationship of agency, partnership, or joint venture between BeOpen and Licensee. This License Agreement does not grant permission to use BeOpen trademarks or trade names in a trademark sense to endorse or promote products or services of Licensee, or any third party. As an exception, the "BeOpen Python" logos available at

(下页继续)

(繼續上一頁)

<http://www.pythonlabs.com/logos.html> may be used according to the permissions granted on that web page.

7. By copying, installing or otherwise using the software, Licensee agrees to be bound by the terms and conditions of this License Agreement.

C.2.3 用於 PYTHON 1.6.1 的 CNRI 授權合約

1. This LICENSE AGREEMENT is between the Corporation for National Research Initiatives, having an office at 1895 Preston White Drive, Reston, VA 20191 ("CNRI"), and the Individual or Organization ("Licensee") accessing and otherwise using Python 1.6.1 software in source or binary form and its associated documentation.
2. Subject to the terms and conditions of this License Agreement, CNRI hereby grants Licensee a nonexclusive, royalty-free, world-wide license to reproduce, analyze, test, perform and/or display publicly, prepare derivative works, distribute, and otherwise use Python 1.6.1 alone or in any derivative version, provided, however, that CNRI's License Agreement and CNRI's notice of copyright, i.e., "Copyright © 1995-2001 Corporation for National Research Initiatives; All Rights Reserved" are retained in Python 1.6.1 alone or in any derivative version prepared by Licensee. Alternately, in lieu of CNRI's License Agreement, Licensee may substitute the following text (omitting the quotes): "Python 1.6.1 is made available subject to the terms and conditions in CNRI's License Agreement. This Agreement together with Python 1.6.1 may be located on the internet using the following unique, persistent identifier (known as a handle): 1895.22/1013. This Agreement may also be obtained from a proxy server on the internet using the following URL: <http://hdl.handle.net/1895.22/1013>."
3. In the event Licensee prepares a derivative work that is based on or incorporates Python 1.6.1 or any part thereof, and wants to make the derivative work available to others as provided herein, then Licensee hereby agrees to include in any such work a brief summary of the changes made to Python 1.6.1.
4. CNRI is making Python 1.6.1 available to Licensee on an "AS IS" basis. CNRI MAKES NO REPRESENTATIONS OR WARRANTIES, EXPRESS OR IMPLIED. BY WAY OF EXAMPLE, BUT NOT LIMITATION, CNRI MAKES NO AND DISCLAIMS ANY REPRESENTATION OR WARRANTY OF MERCHANTABILITY OR FITNESS FOR ANY PARTICULAR PURPOSE OR THAT THE USE OF PYTHON 1.6.1 WILL NOT INFRINGE ANY THIRD PARTY RIGHTS.
5. CNRI SHALL NOT BE LIABLE TO LICENSEE OR ANY OTHER USERS OF PYTHON 1.6.1 FOR ANY INCIDENTAL, SPECIAL, OR CONSEQUENTIAL DAMAGES OR LOSS AS A RESULT OF MODIFYING, DISTRIBUTING, OR OTHERWISE USING PYTHON 1.6.1, OR ANY DERIVATIVE THEREOF, EVEN IF ADVISED OF THE POSSIBILITY THEREOF.
6. This License Agreement will automatically terminate upon a material breach of its terms and conditions.
7. This License Agreement shall be governed by the federal intellectual property law of the United States, including without limitation the federal copyright law, and, to the extent such U.S. federal law does not apply, by the law of the Commonwealth of Virginia, excluding Virginia's conflict of law provisions. Notwithstanding the foregoing, with regard to derivative works based on Python 1.6.1 that incorporate non-separable material that was previously distributed under the GNU General Public License (GPL), the law of the Commonwealth of Virginia shall govern this License Agreement only as to issues arising under or with respect to Paragraphs 4, 5, and 7 of this License Agreement. Nothing in this License Agreement shall be deemed to create any relationship of agency, partnership, or joint venture between CNRI and Licensee. This License Agreement

(下頁繼續)

(繼續上一頁)

does not grant permission to use CNRI trademarks or trade name in a trademark sense to endorse or promote products or services of Licensee, or any third party.

8. By clicking on the "ACCEPT" button where indicated, or by copying, installing or otherwise using Python 1.6.1, Licensee agrees to be bound by the terms and conditions of this License Agreement.

C.2.4 用於 PYTHON 0.9.0 至 1.2 的 CWI 授權合約

Copyright © 1991 - 1995, Stichting Mathematisch Centrum Amsterdam, The Netherlands. All rights reserved.

Permission to use, copy, modify, and distribute this software and its documentation for any purpose and without fee is hereby granted, provided that the above copyright notice appear in all copies and that both that copyright notice and this permission notice appear in supporting documentation, and that the name of Stichting Mathematisch Centrum or CWI not be used in advertising or publicity pertaining to distribution of the software without specific, written prior permission.

STICHTING MATHEMATISCH CENTRUM DISCLAIMS ALL WARRANTIES WITH REGARD TO THIS SOFTWARE, INCLUDING ALL IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS, IN NO EVENT SHALL STICHTING MATHEMATISCH CENTRUM BE LIABLE FOR ANY SPECIAL, INDIRECT OR CONSEQUENTIAL DAMAGES OR ANY DAMAGES WHATSOEVER RESULTING FROM LOSS OF USE, DATA OR PROFITS, WHETHER IN AN ACTION OF CONTRACT, NEGLIGENCE OR OTHER TORTIOUS ACTION, ARISING OUT OF OR IN CONNECTION WITH THE USE OR PERFORMANCE OF THIS SOFTWARE.

C.2.5 用於 PYTHON 3.10.11 明文程式碼的 ZERO-CLAUSE BSD 授權

Permission to use, copy, modify, and/or distribute this software for any purpose with or without fee is hereby granted.

THE SOFTWARE IS PROVIDED "AS IS" AND THE AUTHOR DISCLAIMS ALL WARRANTIES WITH REGARD TO THIS SOFTWARE INCLUDING ALL IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS. IN NO EVENT SHALL THE AUTHOR BE LIABLE FOR ANY SPECIAL, DIRECT, INDIRECT, OR CONSEQUENTIAL DAMAGES OR ANY DAMAGES WHATSOEVER RESULTING FROM LOSS OF USE, DATA OR PROFITS, WHETHER IN AN ACTION OF CONTRACT, NEGLIGENCE OR OTHER TORTIOUS ACTION, ARISING OUT OF OR IN CONNECTION WITH THE USE OR PERFORMANCE OF THIS SOFTWARE.

C.3 被收軟體的授權與致謝

本節是一個不完整但持續增加的授權與致謝清單，對象是在 Python 發版本中所收的第三方軟體。

C.3.1 Mersenne Twister

`_random` 模組包含了以 <http://www.math.sci.hiroshima-u.ac.jp/~m-mat/MT/MT2002/emt19937ar.html> 的下載內容基礎的程式碼。以下是原始程式碼的完整聲明：

```
A C-program for MT19937, with initialization improved 2002/1/26.
Coded by Takuji Nishimura and Makoto Matsumoto.

Before using, initialize the state by using init_genrand(seed)
or init_by_array(init_key, key_length).

Copyright (C) 1997 - 2002, Makoto Matsumoto and Takuji Nishimura,
All rights reserved.

Redistribution and use in source and binary forms, with or without
modification, are permitted provided that the following conditions
are met:

1. Redistributions of source code must retain the above copyright
   notice, this list of conditions and the following disclaimer.

2. Redistributions in binary form must reproduce the above copyright
   notice, this list of conditions and the following disclaimer in the
   documentation and/or other materials provided with the distribution.

3. The names of its contributors may not be used to endorse or promote
   products derived from this software without specific prior written
   permission.

THIS SOFTWARE IS PROVIDED BY THE COPYRIGHT HOLDERS AND CONTRIBUTORS
"AS IS" AND ANY EXPRESS OR IMPLIED WARRANTIES, INCLUDING, BUT NOT
LIMITED TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR
A PARTICULAR PURPOSE ARE DISCLAIMED. IN NO EVENT SHALL THE COPYRIGHT OWNER OR
CONTRIBUTORS BE LIABLE FOR ANY DIRECT, INDIRECT, INCIDENTAL, SPECIAL,
EXEMPLARY, OR CONSEQUENTIAL DAMAGES (INCLUDING, BUT NOT LIMITED TO,
PROCUREMENT OF SUBSTITUTE GOODS OR SERVICES; LOSS OF USE, DATA, OR
PROFITS; OR BUSINESS INTERRUPTION) HOWEVER CAUSED AND ON ANY THEORY OF
LIABILITY, WHETHER IN CONTRACT, STRICT LIABILITY, OR TORT (INCLUDING
NEGLIGENCE OR OTHERWISE) ARISING IN ANY WAY OUT OF THE USE OF THIS
SOFTWARE, EVEN IF ADVISED OF THE POSSIBILITY OF SUCH DAMAGE.

Any feedback is very welcome.
http://www.math.sci.hiroshima-u.ac.jp/~m-mat/MT/emt.html
email: m-mat @ math.sci.hiroshima-u.ac.jp (remove space)
```

C.3.2 Sockets

`socket` 模組使用 `getaddrinfo()` 和 `getnameinfo()` 函式，它們在 WIDE 專案 (<https://www.wide.ad.jp/>) 中，於不同的原始檔案中被編碼：

```
Copyright (C) 1995, 1996, 1997, and 1998 WIDE Project.
All rights reserved.

Redistribution and use in source and binary forms, with or without
modification, are permitted provided that the following conditions
are met:

1. Redistributions of source code must retain the above copyright
   notice, this list of conditions and the following disclaimer.
2. Redistributions in binary form must reproduce the above copyright
```

(下页继续)

(繼續上一頁)

```

notice, this list of conditions and the following disclaimer in the
documentation and/or other materials provided with the distribution.
3. Neither the name of the project nor the names of its contributors
may be used to endorse or promote products derived from this software
without specific prior written permission.

THIS SOFTWARE IS PROVIDED BY THE PROJECT AND CONTRIBUTORS ``AS IS'' AND
ANY EXPRESS OR IMPLIED WARRANTIES, INCLUDING, BUT NOT LIMITED TO, THE
IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE
ARE DISCLAIMED. IN NO EVENT SHALL THE PROJECT OR CONTRIBUTORS BE LIABLE
FOR ANY DIRECT, INDIRECT, INCIDENTAL, SPECIAL, EXEMPLARY, OR CONSEQUENTIAL
DAMAGES (INCLUDING, BUT NOT LIMITED TO, PROCUREMENT OF SUBSTITUTE GOODS
OR SERVICES; LOSS OF USE, DATA, OR PROFITS; OR BUSINESS INTERRUPTION)
HOWEVER CAUSED AND ON ANY THEORY OF LIABILITY, WHETHER IN CONTRACT, STRICT
LIABILITY, OR TORT (INCLUDING NEGLIGENCE OR OTHERWISE) ARISING IN ANY WAY
OUT OF THE USE OF THIS SOFTWARE, EVEN IF ADVISED OF THE POSSIBILITY OF
SUCH DAMAGE.

```

C.3.3 非同步 socket 服務

asynchat 和 asyncore 模組包含以下聲明：

```

Copyright 1996 by Sam Rushing

All Rights Reserved

Permission to use, copy, modify, and distribute this software and
its documentation for any purpose and without fee is hereby
granted, provided that the above copyright notice appear in all
copies and that both that copyright notice and this permission
notice appear in supporting documentation, and that the name of Sam
Rushing not be used in advertising or publicity pertaining to
distribution of the software without specific, written prior
permission.

SAM RUSHING DISCLAIMS ALL WARRANTIES WITH REGARD TO THIS SOFTWARE,
INCLUDING ALL IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS, IN
NO EVENT SHALL SAM RUSHING BE LIABLE FOR ANY SPECIAL, INDIRECT OR
CONSEQUENTIAL DAMAGES OR ANY DAMAGES WHATSOEVER RESULTING FROM LOSS
OF USE, DATA OR PROFITS, WHETHER IN AN ACTION OF CONTRACT,
NEGLIGENCE OR OTHER TORTIOUS ACTION, ARISING OUT OF OR IN
CONNECTION WITH THE USE OR PERFORMANCE OF THIS SOFTWARE.

```

C.3.4 Cookie 管理

http.cookies 模組包含以下聲明：

```

Copyright 2000 by Timothy O'Malley <timo@alum.mit.edu>

All Rights Reserved

Permission to use, copy, modify, and distribute this software
and its documentation for any purpose and without fee is hereby
granted, provided that the above copyright notice appear in all
copies and that both that copyright notice and this permission
notice appear in supporting documentation, and that the name of
Timothy O'Malley not be used in advertising or publicity

```

(下页继续)

(繼續上一頁)

pertaining to distribution of the software without specific, written prior permission.

Timothy O'Malley DISCLAIMS ALL WARRANTIES WITH REGARD TO THIS SOFTWARE, INCLUDING ALL IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS, IN NO EVENT SHALL Timothy O'Malley BE LIABLE FOR ANY SPECIAL, INDIRECT OR CONSEQUENTIAL DAMAGES OR ANY DAMAGES WHATSOEVER RESULTING FROM LOSS OF USE, DATA OR PROFITS, WHETHER IN AN ACTION OF CONTRACT, NEGLIGENCE OR OTHER TORTIOUS ACTION, ARISING OUT OF OR IN CONNECTION WITH THE USE OR PERFORMANCE OF THIS SOFTWARE.

C.3.5 執行追 F

trace 模組包含以下聲明：

portions copyright 2001, Autonomous Zones Industries, Inc., all rights...
err... reserved and offered to the public under the terms of the
Python 2.2 license.

Author: Zooko O'Whielacronx
<http://zooko.com/>
<mailto:zooko@zooko.com>

Copyright 2000, Mojam Media, Inc., all rights reserved.
Author: Skip Montanaro

Copyright 1999, Bioreason, Inc., all rights reserved.
Author: Andrew Dalke

Copyright 1995-1997, Automatrix, Inc., all rights reserved.
Author: Skip Montanaro

Copyright 1991-1995, Stichting Mathematisch Centrum, all rights reserved.

Permission to use, copy, modify, and distribute this Python software and its associated documentation for any purpose without fee is hereby granted, provided that the above copyright notice appears in all copies, and that both that copyright notice and this permission notice appear in supporting documentation, and that the name of neither Automatrix, Bioreason or Mojam Media be used in advertising or publicity pertaining to distribution of the software without specific, written prior permission.

C.3.6 UUencode 與 UUdecode 函式

uu 模組包含以下聲明：

Copyright 1994 by Lance Ellinghouse
Cathedral City, California Republic, United States of America.

All Rights Reserved

Permission to use, copy, modify, and distribute this software and its documentation for any purpose and without fee is hereby granted, provided that the above copyright notice appear in all copies and that both that copyright notice and this permission notice appear in supporting documentation, and that the name of Lance Ellinghouse not be used in advertising or publicity pertaining to distribution of the software without specific, written prior permission.

(下页继续)

(繼續上一頁)

LANCE ELLINGHOUSE DISCLAIMS ALL WARRANTIES WITH REGARD TO THIS SOFTWARE, INCLUDING ALL IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS, IN NO EVENT SHALL LANCE ELLINGHOUSE CENTRUM BE LIABLE FOR ANY SPECIAL, INDIRECT OR CONSEQUENTIAL DAMAGES OR ANY DAMAGES WHATSOEVER RESULTING FROM LOSS OF USE, DATA OR PROFITS, WHETHER IN AN ACTION OF CONTRACT, NEGLIGENCE OR OTHER TORTIOUS ACTION, ARISING OUT OF OR IN CONNECTION WITH THE USE OR PERFORMANCE OF THIS SOFTWARE.

Modified by Jack Jansen, CWI, July 1995:

- Use binascii module to do the actual line-by-line conversion between ascii and binary. This results in a 1000-fold speedup. The C version is still 5 times faster, though.
- Arguments more compliant with Python standard

C.3.7 XML 遠端程序呼叫

xmlrpc.client 模組包含以下聲明:

The XML-RPC client interface is

Copyright (c) 1999-2002 by Secret Labs AB
Copyright (c) 1999-2002 by Fredrik Lundh

By obtaining, using, and/or copying this software and/or its associated documentation, you agree that you have read, understood, and will comply with the following terms and conditions:

Permission to use, copy, modify, and distribute this software and its associated documentation for any purpose and without fee is hereby granted, provided that the above copyright notice appears in all copies, and that both that copyright notice and this permission notice appear in supporting documentation, and that the name of Secret Labs AB or the author not be used in advertising or publicity pertaining to distribution of the software without specific, written prior permission.

SECRET LABS AB AND THE AUTHOR DISCLAIMS ALL WARRANTIES WITH REGARD TO THIS SOFTWARE, INCLUDING ALL IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS. IN NO EVENT SHALL SECRET LABS AB OR THE AUTHOR BE LIABLE FOR ANY SPECIAL, INDIRECT OR CONSEQUENTIAL DAMAGES OR ANY DAMAGES WHATSOEVER RESULTING FROM LOSS OF USE, DATA OR PROFITS, WHETHER IN AN ACTION OF CONTRACT, NEGLIGENCE OR OTHER TORTIOUS ACTION, ARISING OUT OF OR IN CONNECTION WITH THE USE OR PERFORMANCE OF THIS SOFTWARE.

C.3.8 test_epoll

test_epoll 模組包含以下聲明:

Copyright (c) 2001-2006 Twisted Matrix Laboratories.

Permission is hereby granted, free of charge, to any person obtaining a copy of this software and associated documentation files (the "Software"), to deal in the Software without restriction, including without limitation the rights to use, copy, modify, merge, publish, distribute, sublicense, and/or sell copies of the Software, and to permit persons to whom the Software is furnished to do so, subject to

(下页继续)

(繼續上一頁)

the following conditions:

The above copyright notice and this permission notice shall be included in all copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND, EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE AND NONINFRINGEMENT. IN NO EVENT SHALL THE AUTHORS OR COPYRIGHT HOLDERS BE LIABLE FOR ANY CLAIM, DAMAGES OR OTHER LIABILITY, WHETHER IN AN ACTION OF CONTRACT, TORT OR OTHERWISE, ARISING FROM, OUT OF OR IN CONNECTION WITH THE SOFTWARE OR THE USE OR OTHER DEALINGS IN THE SOFTWARE.

C.3.9 Select kqueue

select 模組對於 kqueue 介面包含以下聲明:

Copyright (c) 2000 Doug White, 2006 James Knight, 2007 Christian Heimes
All rights reserved.

Redistribution and use in source and binary forms, with or without modification, are permitted provided that the following conditions are met:

1. Redistributions of source code must retain the above copyright notice, this list of conditions and the following disclaimer.
2. Redistributions in binary form must reproduce the above copyright notice, this list of conditions and the following disclaimer in the documentation and/or other materials provided with the distribution.

THIS SOFTWARE IS PROVIDED BY THE AUTHOR AND CONTRIBUTORS ``AS IS'' AND ANY EXPRESS OR IMPLIED WARRANTIES, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE ARE DISCLAIMED. IN NO EVENT SHALL THE AUTHOR OR CONTRIBUTORS BE LIABLE FOR ANY DIRECT, INDIRECT, INCIDENTAL, SPECIAL, EXEMPLARY, OR CONSEQUENTIAL DAMAGES (INCLUDING, BUT NOT LIMITED TO, PROCUREMENT OF SUBSTITUTE GOODS OR SERVICES; LOSS OF USE, DATA, OR PROFITS; OR BUSINESS INTERRUPTION) HOWEVER CAUSED AND ON ANY THEORY OF LIABILITY, WHETHER IN CONTRACT, STRICT LIABILITY, OR TORT (INCLUDING NEGLIGENCE OR OTHERWISE) ARISING IN ANY WAY OUT OF THE USE OF THIS SOFTWARE, EVEN IF ADVISED OF THE POSSIBILITY OF SUCH DAMAGE.

C.3.10 SipHash24

Python/pyhash.c 檔案包含 Marek Majkowski 基於 Dan Bernstein 的 SipHash24 演算法的實作。它包含以下聲明:

<MIT License>

Copyright (c) 2013 Marek Majkowski <marek@popcount.org>

Permission is hereby granted, free of charge, to any person obtaining a copy of this software and associated documentation files (the "Software"), to deal in the Software without restriction, including without limitation the rights to use, copy, modify, merge, publish, distribute, sublicense, and/or sell copies of the Software, and to permit persons to whom the Software is furnished to do so, subject to the following conditions:

The above copyright notice and this permission notice shall be included in

(下页继续)

(繼續上一頁)

```

all copies or substantial portions of the Software.
</MIT License>

Original location:
  https://github.com/majek/csiphash/

Solution inspired by code from:
  Samuel Neves (supercop/crypto_auth/siphash24/little)
  djb (supercop/crypto_auth/siphash24/little2)
  Jean-Philippe Aumasson (https://131002.net/siphash/siphash24.c)

```

C.3.11 strtod 與 dtoa

Python/dtoa.c 檔案提供了 C 的 `dtoa` 和 `strtod` 函式，用於將 C 的雙精度浮點數和字串互相轉_F。該檔案是衍生自 David M. Gay 建立的同名檔案，後者現在可以從 <https://web.archive.org/web/20220517033456/http://www.netlib.org/fp/dtoa.c> 下載。於 2009 年 3 月 16 日所檢索的原始檔案包含以下版權與授權聲明：

```

/*****
 *
 * The author of this software is David M. Gay.
 *
 * Copyright (c) 1991, 2000, 2001 by Lucent Technologies.
 *
 * Permission to use, copy, modify, and distribute this software for any
 * purpose without fee is hereby granted, provided that this entire notice
 * is included in all copies of any software which is or includes a copy
 * or modification of this software and in all copies of the supporting
 * documentation for such software.
 *
 * THIS SOFTWARE IS BEING PROVIDED "AS IS", WITHOUT ANY EXPRESS OR IMPLIED
 * WARRANTY. IN PARTICULAR, NEITHER THE AUTHOR NOR LUCENT MAKES ANY
 * REPRESENTATION OR WARRANTY OF ANY KIND CONCERNING THE MERCHANTABILITY
 * OF THIS SOFTWARE OR ITS FITNESS FOR ANY PARTICULAR PURPOSE.
 *
 *****/

```

C.3.12 OpenSSL

如果 OpenSSL 函式庫可被作業系統使用，則 `hashlib`、`posix`、`ssl`、`crypt` 模組會使用它來提升效能。此外，因_F Windows 和 macOS 的 Python 安裝程式可能包含 OpenSSL 函式庫的副本，所以我們也在此收_F OpenSSL 授權的副本：

```

LICENSE ISSUES
=====

The OpenSSL toolkit stays under a dual license, i.e. both the conditions of
the OpenSSL License and the original SSLeay license apply to the toolkit.
See below for the actual license texts. Actually both licenses are BSD-style
Open Source licenses. In case of any license issues related to OpenSSL
please contact openssl-core@openssl.org.

OpenSSL License
-----

/* =====
 * Copyright (c) 1998-2008 The OpenSSL Project. All rights reserved.
 *

```

(下頁繼續)

(繼續上一頁)

```

* Redistribution and use in source and binary forms, with or without
* modification, are permitted provided that the following conditions
* are met:
*
* 1. Redistributions of source code must retain the above copyright
*    notice, this list of conditions and the following disclaimer.
*
* 2. Redistributions in binary form must reproduce the above copyright
*    notice, this list of conditions and the following disclaimer in
*    the documentation and/or other materials provided with the
*    distribution.
*
* 3. All advertising materials mentioning features or use of this
*    software must display the following acknowledgment:
*    "This product includes software developed by the OpenSSL Project
*    for use in the OpenSSL Toolkit. (http://www.openssl.org/)"
*
* 4. The names "OpenSSL Toolkit" and "OpenSSL Project" must not be used to
*    endorse or promote products derived from this software without
*    prior written permission. For written permission, please contact
*    openssl-core@openssl.org.
*
* 5. Products derived from this software may not be called "OpenSSL"
*    nor may "OpenSSL" appear in their names without prior written
*    permission of the OpenSSL Project.
*
* 6. Redistributions of any form whatsoever must retain the following
*    acknowledgment:
*    "This product includes software developed by the OpenSSL Project
*    for use in the OpenSSL Toolkit (http://www.openssl.org/)"
*
* THIS SOFTWARE IS PROVIDED BY THE OpenSSL PROJECT ``AS IS'' AND ANY
* EXPRESSED OR IMPLIED WARRANTIES, INCLUDING, BUT NOT LIMITED TO, THE
* IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR
* PURPOSE ARE DISCLAIMED.  IN NO EVENT SHALL THE OpenSSL PROJECT OR
* ITS CONTRIBUTORS BE LIABLE FOR ANY DIRECT, INDIRECT, INCIDENTAL,
* SPECIAL, EXEMPLARY, OR CONSEQUENTIAL DAMAGES (INCLUDING, BUT
* NOT LIMITED TO, PROCUREMENT OF SUBSTITUTE GOODS OR SERVICES;
* LOSS OF USE, DATA, OR PROFITS; OR BUSINESS INTERRUPTION)
* HOWEVER CAUSED AND ON ANY THEORY OF LIABILITY, WHETHER IN CONTRACT,
* STRICT LIABILITY, OR TORT (INCLUDING NEGLIGENCE OR OTHERWISE)
* ARISING IN ANY WAY OUT OF THE USE OF THIS SOFTWARE, EVEN IF ADVISED
* OF THE POSSIBILITY OF SUCH DAMAGE.
* =====
*
* This product includes cryptographic software written by Eric Young
* (eay@cryptsoft.com).  This product includes software written by Tim
* Hudson (tjh@cryptsoft.com).
*
*/

```

Original SSLeay License

```

/* Copyright (C) 1995-1998 Eric Young (eay@cryptsoft.com)
* All rights reserved.
*
* This package is an SSL implementation written
* by Eric Young (eay@cryptsoft.com).
* The implementation was written so as to conform with Netscapes SSL.
*

```

(下页继续)

(繼續上一頁)

```

* This library is free for commercial and non-commercial use as long as
* the following conditions are aheared to. The following conditions
* apply to all code found in this distribution, be it the RC4, RSA,
* lhash, DES, etc., code; not just the SSL code. The SSL documentation
* included with this distribution is covered by the same copyright terms
* except that the holder is Tim Hudson (tjh@cryptsoft.com).
*
* Copyright remains Eric Young's, and as such any Copyright notices in
* the code are not to be removed.
* If this package is used in a product, Eric Young should be given attribution
* as the author of the parts of the library used.
* This can be in the form of a textual message at program startup or
* in documentation (online or textual) provided with the package.
*
* Redistribution and use in source and binary forms, with or without
* modification, are permitted provided that the following conditions
* are met:
* 1. Redistributions of source code must retain the copyright
* notice, this list of conditions and the following disclaimer.
* 2. Redistributions in binary form must reproduce the above copyright
* notice, this list of conditions and the following disclaimer in the
* documentation and/or other materials provided with the distribution.
* 3. All advertising materials mentioning features or use of this software
* must display the following acknowledgement:
* "This product includes cryptographic software written by
* Eric Young (eay@cryptsoft.com)"
* The word 'cryptographic' can be left out if the rouines from the library
* being used are not cryptographic related :-).
* 4. If you include any Windows specific code (or a derivative thereof) from
* the apps directory (application code) you must include an acknowledgement:
* "This product includes software written by Tim Hudson (tjh@cryptsoft.com)"
*
* THIS SOFTWARE IS PROVIDED BY ERIC YOUNG ``AS IS'' AND
* ANY EXPRESS OR IMPLIED WARRANTIES, INCLUDING, BUT NOT LIMITED TO, THE
* IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE
* ARE DISCLAIMED. IN NO EVENT SHALL THE AUTHOR OR CONTRIBUTORS BE LIABLE
* FOR ANY DIRECT, INDIRECT, INCIDENTAL, SPECIAL, EXEMPLARY, OR CONSEQUENTIAL
* DAMAGES (INCLUDING, BUT NOT LIMITED TO, PROCUREMENT OF SUBSTITUTE GOODS
* OR SERVICES; LOSS OF USE, DATA, OR PROFITS; OR BUSINESS INTERRUPTION)
* HOWEVER CAUSED AND ON ANY THEORY OF LIABILITY, WHETHER IN CONTRACT, STRICT
* LIABILITY, OR TORT (INCLUDING NEGLIGENCE OR OTHERWISE) ARISING IN ANY WAY
* OUT OF THE USE OF THIS SOFTWARE, EVEN IF ADVISED OF THE POSSIBILITY OF
* SUCH DAMAGE.
*
* The licence and distribution terms for any publically available version or
* derivative of this code cannot be changed. i.e. this code cannot simply be
* copied and put under another distribution licence
* [including the GNU Public Licence.]
*/

```

C.3.13 expat

除非在建置 pyexpat 擴充時設定 `--with-system-expat`，否則該擴充會用一個含 expat 原始碼的副本來建置：

```
Copyright (c) 1998, 1999, 2000 Thai Open Source Software Center Ltd
and Clark Cooper

Permission is hereby granted, free of charge, to any person obtaining
a copy of this software and associated documentation files (the
"Software"), to deal in the Software without restriction, including
without limitation the rights to use, copy, modify, merge, publish,
distribute, sublicense, and/or sell copies of the Software, and to
permit persons to whom the Software is furnished to do so, subject to
the following conditions:

The above copyright notice and this permission notice shall be included
in all copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND,
EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF
MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE AND NONINFRINGEMENT.
IN NO EVENT SHALL THE AUTHORS OR COPYRIGHT HOLDERS BE LIABLE FOR ANY
CLAIM, DAMAGES OR OTHER LIABILITY, WHETHER IN AN ACTION OF CONTRACT,
TORT OR OTHERWISE, ARISING FROM, OUT OF OR IN CONNECTION WITH THE
SOFTWARE OR THE USE OR OTHER DEALINGS IN THE SOFTWARE.
```

C.3.14 libffi

除非在建置 _ctypes 擴充時設定 `--with-system-libffi`，否則該擴充會用一個含 libffi 原始碼的副本來建置：

```
Copyright (c) 1996-2008 Red Hat, Inc and others.

Permission is hereby granted, free of charge, to any person obtaining
a copy of this software and associated documentation files (the
`Software'), to deal in the Software without restriction, including
without limitation the rights to use, copy, modify, merge, publish,
distribute, sublicense, and/or sell copies of the Software, and to
permit persons to whom the Software is furnished to do so, subject to
the following conditions:

The above copyright notice and this permission notice shall be included
in all copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED ``AS IS'', WITHOUT WARRANTY OF ANY KIND,
EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF
MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE AND
NONINFRINGEMENT. IN NO EVENT SHALL THE AUTHORS OR COPYRIGHT
HOLDERS BE LIABLE FOR ANY CLAIM, DAMAGES OR OTHER LIABILITY,
WHETHER IN AN ACTION OF CONTRACT, TORT OR OTHERWISE, ARISING FROM,
OUT OF OR IN CONNECTION WITH THE SOFTWARE OR THE USE OR OTHER
DEALINGS IN THE SOFTWARE.
```

C.3.15 zlib

如果在系統上找到的 `zlib` 版本太舊以致於無法用於建置 `zlib` 擴充，則該擴充會用一個_F含 `zlib` 原始碼的副本來建置：

```
Copyright (C) 1995-2011 Jean-loup Gailly and Mark Adler

This software is provided 'as-is', without any express or implied
warranty. In no event will the authors be held liable for any damages
arising from the use of this software.

Permission is granted to anyone to use this software for any purpose,
including commercial applications, and to alter it and redistribute it
freely, subject to the following restrictions:

1. The origin of this software must not be misrepresented; you must not
   claim that you wrote the original software. If you use this software
   in a product, an acknowledgment in the product documentation would be
   appreciated but is not required.

2. Altered source versions must be plainly marked as such, and must not be
   misrepresented as being the original software.

3. This notice may not be removed or altered from any source distribution.

Jean-loup Gailly          Mark Adler
jloup@gzip.org            madler@alumni.caltech.edu
```

C.3.16 cfuhash

`tracemalloc` 使用的雜_F表 (hash table) 實作，是以 `cfuhash` 專案_F基礎：

```
Copyright (c) 2005 Don Owens
All rights reserved.

This code is released under the BSD license:

Redistribution and use in source and binary forms, with or without
modification, are permitted provided that the following conditions
are met:

* Redistributions of source code must retain the above copyright
  notice, this list of conditions and the following disclaimer.

* Redistributions in binary form must reproduce the above
  copyright notice, this list of conditions and the following
  disclaimer in the documentation and/or other materials provided
  with the distribution.

* Neither the name of the author nor the names of its
  contributors may be used to endorse or promote products derived
  from this software without specific prior written permission.

THIS SOFTWARE IS PROVIDED BY THE COPYRIGHT HOLDERS AND CONTRIBUTORS
"AS IS" AND ANY EXPRESS OR IMPLIED WARRANTIES, INCLUDING, BUT NOT
LIMITED TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS
FOR A PARTICULAR PURPOSE ARE DISCLAIMED. IN NO EVENT SHALL THE
COPYRIGHT OWNER OR CONTRIBUTORS BE LIABLE FOR ANY DIRECT, INDIRECT,
INCIDENTAL, SPECIAL, EXEMPLARY, OR CONSEQUENTIAL DAMAGES
(INCLUDING, BUT NOT LIMITED TO, PROCUREMENT OF SUBSTITUTE GOODS OR
```

(下页继续)

(繼續上一頁)

```
SERVICES; LOSS OF USE, DATA, OR PROFITS; OR BUSINESS INTERRUPTION)
HOWEVER CAUSED AND ON ANY THEORY OF LIABILITY, WHETHER IN CONTRACT,
STRICT LIABILITY, OR TORT (INCLUDING NEGLIGENCE OR OTHERWISE)
ARISING IN ANY WAY OUT OF THE USE OF THIS SOFTWARE, EVEN IF ADVISED
OF THE POSSIBILITY OF SUCH DAMAGE.
```

C.3.17 libmpdec

除非在建置 `_decimal` 模組時設定 `--with-system-libmpdec`, 否則該模組會用一個含 `libmpdec` 函式庫的副本來建置:

```
Copyright (c) 2008-2020 Stefan Krah. All rights reserved.
```

```
Redistribution and use in source and binary forms, with or without
modification, are permitted provided that the following conditions
are met:
```

1. Redistributions of source code must retain the above copyright notice, this list of conditions and the following disclaimer.
2. Redistributions in binary form must reproduce the above copyright notice, this list of conditions and the following disclaimer in the documentation and/or other materials provided with the distribution.

```
THIS SOFTWARE IS PROVIDED BY THE AUTHOR AND CONTRIBUTORS "AS IS" AND
ANY EXPRESS OR IMPLIED WARRANTIES, INCLUDING, BUT NOT LIMITED TO, THE
IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE
ARE DISCLAIMED. IN NO EVENT SHALL THE AUTHOR OR CONTRIBUTORS BE LIABLE
FOR ANY DIRECT, INDIRECT, INCIDENTAL, SPECIAL, EXEMPLARY, OR CONSEQUENTIAL
DAMAGES (INCLUDING, BUT NOT LIMITED TO, PROCUREMENT OF SUBSTITUTE GOODS
OR SERVICES; LOSS OF USE, DATA, OR PROFITS; OR BUSINESS INTERRUPTION)
HOWEVER CAUSED AND ON ANY THEORY OF LIABILITY, WHETHER IN CONTRACT, STRICT
LIABILITY, OR TORT (INCLUDING NEGLIGENCE OR OTHERWISE) ARISING IN ANY WAY
OUT OF THE USE OF THIS SOFTWARE, EVEN IF ADVISED OF THE POSSIBILITY OF
SUCH DAMAGE.
```

C.3.18 W3C C14N 測試套件

`test` 程式包中的 `C14N 2.0` 測試套件 (`Lib/test/xmltestdata/c14n-20/`) 是從 W3C 網站 <https://www.w3.org/TR/xml-c14n2-testcases/> 被檢索, 且是基於 3-clause BSD 授權被發:

```
Copyright (c) 2013 W3C(R) (MIT, ERCIM, Keio, Beihang),
All Rights Reserved.
```

```
Redistribution and use in source and binary forms, with or without
modification, are permitted provided that the following conditions
are met:
```

- * Redistributions of works must retain the original copyright notice, this list of conditions and the following disclaimer.
- * Redistributions in binary form must reproduce the original copyright notice, this list of conditions and the following disclaimer in the documentation and/or other materials provided with the distribution.
- * Neither the name of the W3C nor the names of its contributors may be used to endorse or promote products derived from this work without specific prior written permission.

(下页继续)

(繼續上一頁)

```
THIS SOFTWARE IS PROVIDED BY THE COPYRIGHT HOLDERS AND CONTRIBUTORS
"AS IS" AND ANY EXPRESS OR IMPLIED WARRANTIES, INCLUDING, BUT NOT
LIMITED TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR
A PARTICULAR PURPOSE ARE DISCLAIMED. IN NO EVENT SHALL THE COPYRIGHT
OWNER OR CONTRIBUTORS BE LIABLE FOR ANY DIRECT, INDIRECT, INCIDENTAL,
SPECIAL, EXEMPLARY, OR CONSEQUENTIAL DAMAGES (INCLUDING, BUT NOT
LIMITED TO, PROCUREMENT OF SUBSTITUTE GOODS OR SERVICES; LOSS OF USE,
DATA, OR PROFITS; OR BUSINESS INTERRUPTION) HOWEVER CAUSED AND ON ANY
THEORY OF LIABILITY, WHETHER IN CONTRACT, STRICT LIABILITY, OR TORT
(INCLUDING NEGLIGENCE OR OTHERWISE) ARISING IN ANY WAY OUT OF THE USE
OF THIS SOFTWARE, EVEN IF ADVISED OF THE POSSIBILITY OF SUCH DAMAGE.
```

C.3.19 Audioop

The audioop module uses the code base in g771.c file of the SoX project:

```
Programming the AdLib/Sound Blaster
FM Music Chips
Version 2.0 (24 Feb 1992)
Copyright (c) 1991, 1992 by Jeffrey S. Lee
jlee@smylex.uucp
Warranty and Copyright Policy
This document is provided on an "as-is" basis, and its author makes
no warranty or representation, express or implied, with respect to
its quality performance or fitness for a particular purpose. In no
event will the author of this document be liable for direct, indirect,
special, incidental, or consequential damages arising out of the use
or inability to use the information contained within. Use of this
document is at your own risk.
This file may be used and copied freely so long as the applicable
copyright notices are retained, and no modifications are made to the
text of the document. No money shall be charged for its distribution
beyond reasonable shipping, handling and duplication costs, nor shall
proprietary changes be made to this document so that it cannot be
distributed freely. This document may not be included in published
material or commercial packages without the written consent of its
author.
```


APPENDIX D

版權宣告

Python 和這份圖明文件的版權：

Copyright © 2001-2023 Python Software Foundation. All rights reserved.

Copyright © 2000 BeOpen.com 保留一切權利。

Copyright © 1995-2000 Corporation for National Research Initiatives 保留一切權利。

Copyright © 1991-1995 Stichting Mathematisch Centrum 保留一切權利。

完整的授權條款資訊請參見[沿革與授權](#)。

非字母

..., 257
 2to3, 257
 >>>, 257
 __all__ (package variable), 62
 __dict__ (module attribute), 142
 __doc__ (module attribute), 141
 __file__ (module attribute), 141, 142
 __future__, 261
 __import__
 函式, 62
 __loader__ (module attribute), 141
 __main__
 模組, 10, 164, 175
 __name__ (module attribute), 141, 142
 __package__ (module attribute), 141
 __PYENV_LAUNCHER__, 188, 193
 __slots__, 268
 _frozen (C struct), 64
 _inittab (C struct), 64
 _Py_c_diff (C function), 107
 _Py_c_neg (C function), 107
 _Py_c_pow (C function), 107
 _Py_c_prod (C function), 107
 _Py_c_quot (C function), 107
 _Py_c_sum (C function), 107
 _Py_InitializeMain (C function), 199
 _Py_NoneStruct (C var), 211
 _PyBytes_Resize (C function), 110
 _PyCFunctionFast (C type), 214
 _PyCFunctionFastWithKeywords (C type), 214
 _PyFrameEvalFunction (C type), 173
 _PyInterpreterState_GetEvalFrameFunc (C function), 173
 _PyInterpreterState_SetEvalFrameFunc (C function), 173
 _PyObject_New (C function), 211
 _PyObject_NewVar (C function), 211
 _PyTuple_Resize (C function), 130
 _thread
 模組, 170
 物件
 bytearray, 110

bytes, 108
 Capsule, 152
 complex number, 107
 dictionary, 133
 file, 140
 floating point, 106
 frozenset, 136
 function, 137
 instancemethod, 138
 integer, 102
 list, 132
 long integer, 102
 mapping, 133
 memoryview, 151
 method, 139
 module, 141
 None, 102
 numeric, 102
 sequence, 108
 set, 136
 tuple, 130
 type, 6, 99
 環境變數
 __PYENV_LAUNCHER__, 188, 193
 PATH, 11
 PYTHON*, 162
 PYTHONCOERCECLOCALE, 197
 PYTHONDEBUG, 162, 192
 PYTHONDONTWRITEBYTECODE, 162, 195
 PYTHONDUMPPREFS, 189, 225
 PYTHONEXECUTABLE, 193
 PYTHONFAULTHANDLER, 189
 PYTHONHASHSEED, 162, 190
 PYTHONHOME, 11, 162, 168, 190
 PYTHONINSPECT, 163, 190
 PYTHONIOENCODING, 165, 194
 PYTHONLEGACYWINDOWSFSENCODING, 163, 185
 PYTHONLEGACYWINDOWSSSTDIO, 163, 191
 PYTHONMALLOC, 202, 205, 207
 PYTHONMALLOC` (例 如:
 `PYTHONMALLOC=malloc`, 208
 PYTHONMALLOCSTATS, 191, 202
 PYTHONNOUSERSITE, 163, 194

PYTHONOPTIMIZE, 163, 192
 PYTHONPATH, 11, 162, 191
 PYTHONPLATLIBDIR, 191
 PYTHONPROFILEIMPORTTIME, 190
 PYTHONPYCACHEPREFIX, 193
 PYTHONTRACEMALLOC, 194
 PYTHONUNBUFFERED, 163, 188
 PYTHONUTF8, 185, 197
 PYTHONVERBOSE, 163, 195
 PYTHONWARNINGS, 195

A

abort(), 61
 abs
 F建函式, 86
 abstract base class (抽象基底類**F**), 257
 allocfunc (*C type*), 248
 annotation (**F**釋), 257
 argument (引數), 257
 argv (*in module sys*), 167
 ascii
 F建函式, 79
 asynchronous context manager (非同步情境管理器), 258
 asynchronous generator iterator (非同步**F**生器**F**代器), 258
 asynchronous generator (非同步**F**生器), 258
 asynchronous iterable (非同步可**F**代物件), 258
 asynchronous iterator (非同步**F**代器), 258
 attribute (屬性), 258
 awaitable (可等待物件), 258

B

BDFL, 258
 binary file (二進制檔案), 258
 binaryfunc (*C type*), 249
 borrowed reference (借用參照), 258
 buffer interface
 (see buffer protocol), 91
 buffer object
 (see buffer protocol), 91
 buffer protocol, 91
 builtins
 模組, 10, 164, 175
 bytearray
 物件, 110
 bytecode (位元組碼), 259
 bytes
 F建函式, 79
 物件, 108
 bytes-like object (類位元組串物件), 259

C

callable (可呼叫物件), 259
 callback (回呼), 259
 calloc(), 201
 Capsule

物件, 152
 C-contiguous, 94, 259
 class variable (類**F**變數), 259
 classmethod
 F建函式, 216
 class (類**F**), 259
 cleanup functions, 61
 close() (*in module os*), 175
 CO_FUTURE_DIVISION (*C var*), 42
 code object, 139
 coercion (**F**制轉型), 259
 compile
 F建函式, 63
 complex number
 物件, 107
 complex number (**F**數), 259
 context manager (情境管理器), 259
 context variable (情境變數), 259
 contiguous, 94
 contiguous (連續的), 259
 copyright (*in module sys*), 167
 coroutine function (協程函式), 260
 coroutine (協程), 260
 CPython, 260

D

decorator (裝飾器), 260
 descrgetfunc (*C type*), 248
 descriptor (描述器), 260
 descrsetfunc (*C type*), 248
 destructor (*C type*), 248
 dictionary
 物件, 133
 dictionary comprehension (字典綜合運算), 260
 dictionary view (字典檢視), 260
 dictionary (字典), 260
 divmod
 F建函式, 85
 docstring (**F**明字串), 260
 duck-typing (鴨子型**F**), 260

E

EAFP, 260
 EOFError (*built-in exception*), 141
 exc_info() (*in module sys*), 9
 executable (*in module sys*), 166
 exit(), 61
 expression (運算式), 260
 extension module (擴充模組), 261

F

f-string (*f* 字串), 261
 file
 物件, 140
 file object (檔案物件), 261
 file-like object (類檔案物件), 261

filesystem encoding and error
 handler (檔案系統編碼和錯誤處理函式), 261
 finder (尋檢器), 261
 float
 _F建函式, 87
 floating point
 物件, 106
 floor division (向下取整除法), 261
 Fortran contiguous, 94, 259
 free(), 201
 freefunc (C type), 248
 freeze utility, 64
 frozenset
 物件, 136
 function
 物件, 137
 function annotation (函式_F釋), 261
 function (函式), 261

G

garbage collection (垃圾回收), 262
 generator, 262
 generator expression, 262
 generator expression (_F生器運算式), 262
 generator iterator (_F生器_F代器), 262
 generator (_F生器), 262
 generic function (泛型函式), 262
 generic type (泛型型_F), 262
 getattrfunc (C type), 248
 getattrofunc (C type), 248
 getbufferproc (C type), 248
 getiterfunc (C type), 248
 GIL, 262
 global interpreter lock, 168
 global interpreter lock (全域直譯器鎖), 262

H

hash
 _F建函式, 79, 228
 hash-based pyc (雜_F架構的 pyc), 262
 hashable (可雜_F的), 262
 hashfunc (C type), 248

I

IDLE, 263
 immutable (不可變物件), 263
 import path (匯入路徑), 263
 importer (匯入器), 263
 importing (匯入), 263
 incr_item(), 9, 10
 initproc (C type), 248
 inquiry (C type), 253
 instancemethod
 物件, 138
 int
 _F建函式, 87

integer
 物件, 102
 interactive (互動的), 263
 interpreted (直譯的), 263
 interpreter lock, 168
 interpreter shutdown (直譯器關閉), 263
 iterable (可_F代物件), 263
 iterator (_F代器), 263
 iternextfunc (C type), 248

K

key function (鍵函式), 263
 KeyboardInterrupt (built-in exception), 50, 51
 keyword argument (關鍵字引數), 264

L

lambda, 264
 LBYL, 264
 len
 _F建函式, 80, 88, 89, 132, 134, 136
 lenfunc (C type), 248
 list
 物件, 132
 list comprehension (串列綜合運算), 264
 list (串列), 264
 loader (載入器), 264
 locale encoding (區域編碼), 264
 lock, interpreter, 168
 long integer
 物件, 102
 LONG_MAX, 103

M

magic
 method, 264
 magic method (魔術方法), 264
 main(), 165, 167
 malloc(), 201
 mapping
 物件, 133
 mapping (對映), 264
 memoryview
 物件, 151
 meta path finder (元路徑尋檢器), 264
 metaclass (元類_F), 264
 METH_CLASS (_F建變數), 215
 METH_COEXIST (_F建變數), 216
 METH_FASTCALL (_F建變數), 215
 METH_NOARGS (_F建變數), 215
 METH_O (_F建變數), 215
 METH_STATIC (_F建變數), 216
 METH_VARARGS (_F建變數), 215
 method
 magic, 264
 special, 268
 物件, 139
 method resolution order (方法解析順序), 265

MethodType (*in module types*), 137, 139
 method (方法), 264
 module
 search path, 10, 164, 166
 物件, 141
 module spec (模組規格), 265
 modules (*in module sys*), 62, 164
 ModuleType (*in module types*), 141
 module (模組), 265
 MRO, 265
 mutable (可變物件), 265

N

named tuple (附名元組), 265
 namespace package (命名空間套件), 265
 namespace (命名空間), 265
 nested scope (巢狀作用域), 265
 new-style class (新式類), 265
 newfunc (*C type*), 248
 None
 物件, 102
 numeric
 物件, 102

O

object
 code, 139
 object (物件), 265
 objobjargproc (*C type*), 249
 objobjproc (*C type*), 249
 OverflowError (*built-in exception*), 103105

P

package variable
 __all__, 62
 package (套件), 265
 parameter (參數), 266
 PATH, 11
 path
 module search, 10, 164, 166
 path (*in module sys*), 10, 164, 166
 path based finder (基於路徑的尋檢器), 266
 path entry finder (路徑項目尋檢器), 266
 path entry hook (路徑項目), 266
 path-like object (類路徑物件), 266
 PEP, 266
 platform (*in module sys*), 167
 portion (部分), 266
 positional argument (位置引數), 267
 pow
 建函式, 85, 87
 provisional API (暫行 API), 267
 provisional package (暫行套件), 267
 Py_ABS (*C macro*), 4
 Py_AddPendingCall (*C function*), 176
 Py_AddPendingCall(), 176
 Py_AtExit (*C function*), 61

Py_BEGIN_ALLOW_THREADS, 168
 Py_BEGIN_ALLOW_THREADS (*C macro*), 172
 Py_BLOCK_THREADS (*C macro*), 172
 Py_buffer (*C type*), 92
 Py_buffer.buf (*C member*), 92
 Py_buffer.format (*C member*), 92
 Py_buffer.internal (*C member*), 93
 Py_buffer.itemsize (*C member*), 92
 Py_buffer.len (*C member*), 92
 Py_buffer.ndim (*C member*), 92
 Py_buffer.obj (*C member*), 92
 Py_buffer.readonly (*C member*), 92
 Py_buffer.shape (*C member*), 93
 Py_buffer.strides (*C member*), 93
 Py_buffer.suboffsets (*C member*), 93
 Py_BuildValue (*C function*), 71
 Py_BytesMain (*C function*), 39
 Py_BytesWarningFlag (*C var*), 162
 Py_CHARMASK (*C macro*), 5
 Py_CLEAR (*C function*), 44
 Py_CompileString (*C function*), 41
 Py_CompileString(), 42
 Py_CompileStringExFlags (*C function*), 41
 Py_CompileStringFlags (*C function*), 41
 Py_CompileStringObject (*C function*), 41
 Py_complex (*C type*), 107
 Py_DebugFlag (*C var*), 162
 Py_DecompileLocale (*C function*), 58
 Py_DECREF (*C function*), 43
 Py_DecRef (*C function*), 44
 Py_DECREF(), 6
 Py_DEPRECATED (*C macro*), 5
 Py_DontWriteBytecodeFlag (*C var*), 162
 Py_Ellipsis (*C var*), 151
 Py_EncodeLocale (*C function*), 59
 Py_END_ALLOW_THREADS, 168
 Py_END_ALLOW_THREADS (*C macro*), 172
 Py_EndInterpreter (*C function*), 175
 Py_EnterRecursiveCall (*C function*), 53
 Py_eval_input (*C var*), 42
 Py_Exit (*C function*), 61
 Py_False (*C var*), 105
 Py_FatalError (*C function*), 61
 Py_FatalError(), 167
 Py_FdIsInteractive (*C function*), 57
 Py_file_input (*C var*), 42
 Py_Finalize (*C function*), 164
 Py_FinalizeEx (*C function*), 164
 Py_FinalizeEx(), 61, 164, 175
 Py_FrozenFlag (*C var*), 162
 Py_GenericAlias (*C function*), 159
 Py_GenericAliasType (*C var*), 159
 Py_GetArgcArgv (*C function*), 199
 Py_GetBuildInfo (*C function*), 167
 Py_GetCompiler (*C function*), 167
 Py_GetCopyright (*C function*), 167
 Py_GETENV (*C macro*), 5
 Py_GetExecPrefix (*C function*), 165

- Py_GetExecPrefix(), 11
- Py_GetPath (C function), 166
- Py_GetPath(), 11, 165, 166
- Py_GetPlatform (C function), 166
- Py_GetPrefix (C function), 165
- Py_GetPrefix(), 11
- Py_GetProgramFullPath (C function), 166
- Py_GetProgramFullPath(), 11
- Py_GetProgramName (C function), 165
- Py_GetPythonHome (C function), 168
- Py_GetVersion (C function), 166
- Py_HashRandomizationFlag (C var), 162
- Py_IgnoreEnvironmentFlag (C var), 162
- Py_INCREF (C function), 43
- Py_IncRef (C function), 44
- Py_INCREF(), 6
- Py_Initialize (C function), 164
- Py_Initialize(), 10, 165, 175
- Py_InitializeEx (C function), 164
- Py_InitializeFromConfig (C function), 195
- Py_InspectFlag (C var), 162
- Py_InteractiveFlag (C var), 163
- Py_Is (C function), 212
- Py_IS_TYPE (C function), 213
- Py_IsFalse (C function), 213
- Py_IsInitialized (C function), 164
- Py_IsInitialized(), 11
- Py_IsNone (C function), 212
- Py_IsolatedFlag (C var), 163
- Py_IsTrue (C function), 212
- Py_LeaveRecursiveCall (C function), 53
- Py_LegacyWindowsFSEncodingFlag (C var), 163
- Py_LegacyWindowsStdioFlag (C var), 163
- Py_LIMITED_API (C macro), 13
- Py_Main (C function), 39
- PY_MAJOR_VERSION (C macro), 255
- Py_MAX (C macro), 4
- Py_MEMBER_SIZE (C macro), 5
- PY_MICRO_VERSION (C macro), 255
- Py_MIN (C macro), 4
- PY_MINOR_VERSION (C macro), 255
- Py_mod_create (C macro), 145
- Py_mod_create.create_module (C function), 145
- Py_mod_exec (C macro), 145
- Py_mod_exec.exec_module (C function), 145
- Py_NewInterpreter (C function), 175
- Py_NewRef (C function), 43
- Py_None (C var), 102
- Py_NoSiteFlag (C var), 163
- Py_NotImplemented (C var), 77
- Py_NoUserSiteDirectory (C var), 163
- Py_OptimizeFlag (C var), 163
- Py_PreInitialize (C function), 185
- Py_PreInitializeFromArgs (C function), 186
- Py_PreInitializeFromBytesArgs (C function), 185
- Py_PRINT_RAW, 141
- Py_QuietFlag (C var), 163
- Py_REFCNT (C function), 213
- PY_RELEASE_LEVEL (C macro), 255
- PY_RELEASE_SERIAL (C macro), 255
- Py_ReprEnter (C function), 54
- Py_ReprLeave (C function), 54
- Py_RETURN_FALSE (C macro), 105
- Py_RETURN_NONE (C macro), 102
- Py_RETURN_NOTIMPLEMENTED (C macro), 77
- Py_RETURN_TRUE (C macro), 105
- Py_RunMain (C function), 199
- Py_SET_REFCNT (C function), 213
- Py_SET_SIZE (C function), 213
- Py_SET_TYPE (C function), 213
- Py_SetPath (C function), 166
- Py_SetPath(), 166
- Py_SetProgramName (C function), 165
- Py_SetProgramName(), 11, 164, 166
- Py_SetPythonHome (C function), 168
- Py_SetStandardStreamEncoding (C function), 165
- Py_single_input (C var), 42
- Py_SIZE (C function), 213
- Py_ssize_t (C type), 9
- PY_SSIZE_T_MAX, 104
- Py_STRINGIFY (C macro), 4
- Py_TPFLAGS_BASE_EXC_SUBCLASS (F 建變數), 231
- Py_TPFLAGS_BASETYPE (F 建變數), 230
- Py_TPFLAGS_BYTES_SUBCLASS (F 建變數), 231
- Py_TPFLAGS_DEFAULT (F 建變數), 231
- Py_TPFLAGS_DICT_SUBCLASS (F 建變數), 231
- Py_TPFLAGS_DISALLOW_INSTANTIATION (F 建變數), 232
- Py_TPFLAGS_HAVE_FINALIZE (F 建變數), 232
- Py_TPFLAGS_HAVE_GC (F 建變數), 231
- Py_TPFLAGS_HAVE_VECTORCALL (F 建變數), 232
- Py_TPFLAGS_HEAPTYPE (F 建變數), 230
- Py_TPFLAGS_IMMUTABLETYPE (F 建變數), 232
- Py_TPFLAGS_LIST_SUBCLASS (F 建變數), 231
- Py_TPFLAGS_LONG_SUBCLASS (F 建變數), 231
- Py_TPFLAGS_MAPPING (F 建變數), 232
- Py_TPFLAGS_METHOD_DESCRIPTOR (F 建變數), 231
- Py_TPFLAGS_READY (F 建變數), 230
- Py_TPFLAGS_READYING (F 建變數), 231
- Py_TPFLAGS_SEQUENCE (F 建變數), 233
- Py_TPFLAGS_TUPLE_SUBCLASS (F 建變數), 231
- Py_TPFLAGS_TYPE_SUBCLASS (F 建變數), 231
- Py_TPFLAGS_UNICODE_SUBCLASS (F 建變數), 231
- Py_tracefunc (C type), 177
- Py_True (C var), 105
- Py_tss_NEEDS_INIT (C macro), 179
- Py_tss_t (C type), 179
- Py_TYPE (C function), 213

- Py_UCS1 (*C type*), 111
- Py_UCS2 (*C type*), 111
- Py_UCS4 (*C type*), 111
- Py_UNBLOCK_THREADS (*C macro*), 172
- Py_UnbufferedStdioFlag (*C var*), 163
- Py_UNICODE (*C type*), 111
- Py_UNICODE_IS_HIGH_SURROGATE (*C macro*), 115
- Py_UNICODE_IS_LOW_SURROGATE (*C macro*), 115
- Py_UNICODE_IS_SURROGATE (*C macro*), 115
- Py_UNICODE_ISALNUM (*C function*), 114
- Py_UNICODE_ISALPHA (*C function*), 114
- Py_UNICODE_ISDECIMAL (*C function*), 114
- Py_UNICODE_ISDIGIT (*C function*), 114
- Py_UNICODE_ISLINEBREAK (*C function*), 114
- Py_UNICODE_ISLOWER (*C function*), 114
- Py_UNICODE_ISNUMERIC (*C function*), 114
- Py_UNICODE_ISPRINTABLE (*C function*), 114
- Py_UNICODE_ISSPACE (*C function*), 114
- Py_UNICODE_ISTITLE (*C function*), 114
- Py_UNICODE_ISUPPER (*C function*), 114
- Py_UNICODE_JOIN_SURROGATES (*C macro*), 115
- Py_UNICODE_TODECIMAL (*C function*), 114
- Py_UNICODE_TODIGIT (*C function*), 114
- Py_UNICODE_TOLOWER (*C function*), 114
- Py_UNICODE_TONUMERIC (*C function*), 114
- Py_UNICODE_TOTITLE (*C function*), 114
- Py_UNICODE_TOUPPER (*C function*), 114
- Py_UNREACHABLE (*C macro*), 4
- Py_UNUSED (*C macro*), 5
- Py_VaBuildValue (*C function*), 73
- Py_VECTORCALL_ARGUMENTS_OFFSET (*C macro*), 81
- Py_VerboseFlag (*C var*), 163
- Py_VERSION_HEX (*C macro*), 255
- Py_VISIT (*C function*), 253
- Py_XDECREF (*C function*), 44
- Py_XDECREF(), 10
- Py_XINCRREF (*C function*), 43
- Py_XNewRef (*C function*), 43
- PyAIter_Check (*C function*), 90
- PyAnySet_Check (*C function*), 136
- PyAnySet_CheckExact (*C function*), 136
- PyArg_Parse (*C function*), 71
- PyArg_ParseTuple (*C function*), 70
- PyArg_ParseTupleAndKeywords (*C function*), 70
- PyArg_UnpackTuple (*C function*), 71
- PyArg_ValidateKeywordArguments (*C function*), 70
- PyArg_VaParse (*C function*), 70
- PyArg_VaParseTupleAndKeywords (*C function*), 70
- PyASCIIObject (*C type*), 111
- PyAsyncMethods (*C type*), 247
- PyAsyncMethods.am_aiter (*C member*), 247
- PyAsyncMethods.am_anext (*C member*), 247
- PyAsyncMethods.am_await (*C member*), 247
- PyAsyncMethods.am_send (*C member*), 247
- PyBool_Check (*C function*), 105
- PyBool_FromLong (*C function*), 106
- PyBUF_ANY_CONTIGUOUS (*C macro*), 94
- PyBUF_C_CONTIGUOUS (*C macro*), 94
- PyBUF_CONTIG (*C macro*), 95
- PyBUF_CONTIG_RO (*C macro*), 95
- PyBUF_F_CONTIGUOUS (*C macro*), 94
- PyBUF_FORMAT (*C macro*), 93
- PyBUF_FULL (*C macro*), 95
- PyBUF_FULL_RO (*C macro*), 95
- PyBUF_INDIRECT (*C macro*), 94
- PyBUF_ND (*C macro*), 94
- PyBUF_RECORDS (*C macro*), 95
- PyBUF_RECORDS_RO (*C macro*), 95
- PyBUF_SIMPLE (*C macro*), 94
- PyBUF_STRIDED (*C macro*), 95
- PyBUF_STRIDED_RO (*C macro*), 95
- PyBUF_STRIDES (*C macro*), 94
- PyBUF_WRITABLE (*C macro*), 93
- PyBuffer_FillContiguousStrides (*C function*), 97
- PyBuffer_FillInfo (*C function*), 97
- PyBuffer_FromContiguous (*C function*), 97
- PyBuffer_GetPointer (*C function*), 96
- PyBuffer_IsContiguous (*C function*), 96
- PyBuffer_Release (*C function*), 96
- PyBuffer_SizeFromFormat (*C function*), 96
- PyBuffer_ToContiguous (*C function*), 97
- PyBufferProcs, 91
- PyBufferProcs (*C type*), 246
- PyBufferProcs.bf_getbuffer (*C member*), 246
- PyBufferProcs.bf_releasebuffer (*C member*), 246
- PyByteArray_AS_STRING (*C function*), 111
- PyByteArray_AsString (*C function*), 110
- PyByteArray_Check (*C function*), 110
- PyByteArray_CheckExact (*C function*), 110
- PyByteArray_Concat (*C function*), 110
- PyByteArray_FromObject (*C function*), 110
- PyByteArray_FromStringAndSize (*C function*), 110
- PyByteArray_GET_SIZE (*C function*), 111
- PyByteArray_Resize (*C function*), 110
- PyByteArray_Size (*C function*), 110
- PyByteArray_Type (*C var*), 110
- PyByteArrayObject (*C type*), 110
- PyBytes_AS_STRING (*C function*), 109
- PyBytes_AsString (*C function*), 109
- PyBytes_AsStringAndSize (*C function*), 109
- PyBytes_Check (*C function*), 108
- PyBytes_CheckExact (*C function*), 108
- PyBytes_Concat (*C function*), 109
- PyBytes_ConcatAndDel (*C function*), 109
- PyBytes_FromFormat (*C function*), 108
- PyBytes_FromFormatV (*C function*), 109

- PyBytes_FromObject (*C function*), 109
- PyBytes_FromString (*C function*), 108
- PyBytes_FromStringAndSize (*C function*), 108
- PyBytes_GET_SIZE (*C function*), 109
- PyBytes_Size (*C function*), 109
- PyBytes_Type (*C var*), 108
- PyBytesObject (*C type*), 108
- PyCallable_Check (*C function*), 85
- PyCallIter_Check (*C function*), 149
- PyCallIter_New (*C function*), 149
- PyCallIter_Type (*C var*), 148
- PyCapsule (*C type*), 152
- PyCapsule_CheckExact (*C function*), 152
- PyCapsule_Destructor (*C type*), 152
- PyCapsule_GetContext (*C function*), 153
- PyCapsule_GetDestructor (*C function*), 153
- PyCapsule_GetName (*C function*), 153
- PyCapsule_GetPointer (*C function*), 152
- PyCapsule_Import (*C function*), 153
- PyCapsule_IsValid (*C function*), 153
- PyCapsule_New (*C function*), 152
- PyCapsule_SetContext (*C function*), 153
- PyCapsule_SetDestructor (*C function*), 153
- PyCapsule_SetName (*C function*), 153
- PyCapsule_SetPointer (*C function*), 153
- PyCell_Check (*C function*), 139
- PyCell_GET (*C function*), 139
- PyCell_Get (*C function*), 139
- PyCell_New (*C function*), 139
- PyCell_SET (*C function*), 139
- PyCell_Set (*C function*), 139
- PyCell_Type (*C var*), 139
- PyCellObject (*C type*), 139
- PyCFunction (*C type*), 214
- PyCFunctionWithKeywords (*C type*), 214
- PyCMethod (*C type*), 214
- PyCode_Addr2Line (*C function*), 140
- PyCode_Check (*C function*), 140
- PyCode_GetNumFree (*C function*), 140
- PyCode_New (*C function*), 140
- PyCode_NewEmpty (*C function*), 140
- PyCode_NewWithPosOnlyArgs (*C function*), 140
- PyCode_Type (*C var*), 140
- PyCodec_BackslashReplaceErrors (*C function*), 76
- PyCodec_Decompile (*C function*), 75
- PyCodec_Decoder (*C function*), 75
- PyCodec_Encode (*C function*), 75
- PyCodec_Encoder (*C function*), 75
- PyCodec_IgnoreErrors (*C function*), 76
- PyCodec_IncrementalDecoder (*C function*), 76
- PyCodec_IncrementalEncoder (*C function*), 75
- PyCodec_KnownEncoding (*C function*), 75
- PyCodec_LookupError (*C function*), 76
- PyCodec_NameReplaceErrors (*C function*), 76
- PyCodec_Register (*C function*), 75
- PyCodec_RegisterError (*C function*), 76
- PyCodec_ReplaceErrors (*C function*), 76
- PyCodec_StreamReader (*C function*), 76
- PyCodec_StreamWriter (*C function*), 76
- PyCodec_StrictErrors (*C function*), 76
- PyCodec_Unregister (*C function*), 75
- PyCodec_XMLCharRefReplaceErrors (*C function*), 76
- PyCodeObject (*C type*), 140
- PyCompactUnicodeObject (*C type*), 111
- PyCompilerFlags (*C struct*), 42
- PyCompilerFlags.cf_feature_version (*C member*), 42
- PyCompilerFlags.cf_flags (*C member*), 42
- PyComplex_AsCComplex (*C function*), 108
- PyComplex_Check (*C function*), 107
- PyComplex_CheckExact (*C function*), 107
- PyComplex_FromCComplex (*C function*), 107
- PyComplex_FromDoubles (*C function*), 107
- PyComplex_ImagAsDouble (*C function*), 108
- PyComplex_RealAsDouble (*C function*), 108
- PyComplex_Type (*C var*), 107
- PyComplexObject (*C type*), 107
- PyConfig (*C type*), 186
- PyConfig.argv (*C member*), 187
- PyConfig.base_exec_prefix (*C member*), 188
- PyConfig.base_executable (*C member*), 188
- PyConfig.base_prefix (*C member*), 188
- PyConfig.buffered_stdio (*C member*), 188
- PyConfig.bytes_warning (*C member*), 188
- PyConfig.check_hash_pycs_mode (*C member*), 188
- PyConfig.configure_c_stdio (*C member*), 189
- PyConfig.dev_mode (*C member*), 189
- PyConfig.dump_refs (*C member*), 189
- PyConfig.exec_prefix (*C member*), 189
- PyConfig.executable (*C member*), 189
- PyConfig.fault_handler (*C member*), 189
- PyConfig.filesystem_encoding (*C member*), 189
- PyConfig.filesystem_errors (*C member*), 190
- PyConfig.hash_seed (*C member*), 190
- PyConfig.home (*C member*), 190
- PyConfig.import_time (*C member*), 190
- PyConfig.inspect (*C member*), 190
- PyConfig.install_signal_handlers (*C member*), 190
- PyConfig.interactive (*C member*), 190
- PyConfig.isolated (*C member*), 191
- PyConfig.legacy_windows_stdio (*C member*), 191
- PyConfig.malloc_stats (*C member*), 191
- PyConfig.module_search_paths (*C member*), 191
- PyConfig.module_search_paths_set (*C member*), 191
- PyConfig.optimization_level (*C member*), 192

- PyConfig.orig_argv (*C member*), 192
- PyConfig.parse_argv (*C member*), 192
- PyConfig.parser_debug (*C member*), 192
- PyConfig.pathconfig_warnings (*C member*), 192
- PyConfig.platlibdir (*C member*), 191
- PyConfig.prefix (*C member*), 192
- PyConfig.program_name (*C member*), 192
- PyConfig.pycache_prefix (*C member*), 193
- PyConfig.PyConfig_Clear (*C function*), 187
- PyConfig.PyConfig_InitIsolatedConfig (*C function*), 186
- PyConfig.PyConfig_InitPythonConfig (*C function*), 186
- PyConfig.PyConfig_Read (*C function*), 187
- PyConfig.PyConfig_SetArgv (*C function*), 187
- PyConfig.PyConfig_SetBytesArgv (*C function*), 187
- PyConfig.PyConfig_SetBytesString (*C function*), 187
- PyConfig.PyConfig_SetString (*C function*), 186
- PyConfig.PyConfig_SetWideStringList (*C function*), 187
- PyConfig.pythonpath_env (*C member*), 191
- PyConfig.quiet (*C member*), 193
- PyConfig.run_command (*C member*), 193
- PyConfig.run_filename (*C member*), 193
- PyConfig.run_module (*C member*), 193
- PyConfig.show_ref_count (*C member*), 193
- PyConfig.site_import (*C member*), 193
- PyConfig.skip_source_first_line (*C member*), 194
- PyConfig.stdio_encoding (*C member*), 194
- PyConfig.stdio_errors (*C member*), 194
- PyConfig.tracemalloc (*C member*), 194
- PyConfig.use_environment (*C member*), 194
- PyConfig.use_hash_seed (*C member*), 190
- PyConfig.user_site_directory (*C member*), 194
- PyConfig.verbose (*C member*), 194
- PyConfig.warn_default_encoding (*C member*), 188
- PyConfig.warnoptions (*C member*), 195
- PyConfig.write_bytecode (*C member*), 195
- PyConfig.xoptions (*C member*), 195
- PyContext (*C type*), 155
- PyContext_CheckExact (*C function*), 155
- PyContext_Copy (*C function*), 155
- PyContext_CopyCurrent (*C function*), 155
- PyContext_Enter (*C function*), 155
- PyContext_Exit (*C function*), 155
- PyContext_New (*C function*), 155
- PyContext_Type (*C var*), 155
- PyContextToken (*C type*), 155
- PyContextToken_CheckExact (*C function*), 155
- PyContextToken_Type (*C var*), 155
- PyContextVar (*C type*), 155
- PyContextVar_CheckExact (*C function*), 155
- PyContextVar_Get (*C function*), 155
- PyContextVar_New (*C function*), 155
- PyContextVar_Reset (*C function*), 156
- PyContextVar_Set (*C function*), 155
- PyContextVar_Type (*C var*), 155
- PyCoro_CheckExact (*C function*), 154
- PyCoro_New (*C function*), 154
- PyCoro_Type (*C var*), 154
- PyCoroObject (*C type*), 154
- PyDate_Check (*C function*), 156
- PyDate_CheckExact (*C function*), 156
- PyDate_FromDate (*C function*), 156
- PyDate_FromTimestamp (*C function*), 158
- PyDateTime_Check (*C function*), 156
- PyDateTime_CheckExact (*C function*), 156
- PyDateTime_DATE_GET_FOLD (*C function*), 157
- PyDateTime_DATE_GET_HOUR (*C function*), 157
- PyDateTime_DATE_GET_MICROSECOND (*C function*), 157
- PyDateTime_DATE_GET_MINUTE (*C function*), 157
- PyDateTime_DATE_GET_SECOND (*C function*), 157
- PyDateTime_DATE_GET_TZINFO (*C function*), 157
- PyDateTime_DELTA_GET_DAYS (*C function*), 158
- PyDateTime_DELTA_GET_MICROSECONDS (*C function*), 158
- PyDateTime_DELTA_GET_SECONDS (*C function*), 158
- PyDateTime_FromDateAndTime (*C function*), 156
- PyDateTime_FromDateAndTimeAndFold (*C function*), 157
- PyDateTime_FromTimestamp (*C function*), 158
- PyDateTime_GET_DAY (*C function*), 157
- PyDateTime_GET_MONTH (*C function*), 157
- PyDateTime_GET_YEAR (*C function*), 157
- PyDateTime_TIME_GET_FOLD (*C function*), 158
- PyDateTime_TIME_GET_HOUR (*C function*), 158
- PyDateTime_TIME_GET_MICROSECOND (*C function*), 158
- PyDateTime_TIME_GET_MINUTE (*C function*), 158
- PyDateTime_TIME_GET_SECOND (*C function*), 158
- PyDateTime_TIME_GET_TZINFO (*C function*), 158
- PyDateTime_TimeZone_UTC (*C var*), 156
- PyDelta_Check (*C function*), 156
- PyDelta_CheckExact (*C function*), 156
- PyDelta_FromDSU (*C function*), 157
- PyDescr_IsData (*C function*), 149
- PyDescr_NewClassMethod (*C function*), 149
- PyDescr_NewGetSet (*C function*), 149
- PyDescr_NewMember (*C function*), 149
- PyDescr_NewMethod (*C function*), 149

- PyDescr_NewWrapper (*C function*), 149
- PyDict_Check (*C function*), 133
- PyDict_CheckExact (*C function*), 133
- PyDict_Clear (*C function*), 133
- PyDict_Contains (*C function*), 133
- PyDict_Copy (*C function*), 133
- PyDict_DelItem (*C function*), 134
- PyDict_DelItemString (*C function*), 134
- PyDict_GetItem (*C function*), 134
- PyDict_GetItemString (*C function*), 134
- PyDict_GetItemWithError (*C function*), 134
- PyDict_Items (*C function*), 134
- PyDict_Keys (*C function*), 134
- PyDict_Merge (*C function*), 135
- PyDict_MergeFromSeq2 (*C function*), 135
- PyDict_New (*C function*), 133
- PyDict_Next (*C function*), 134
- PyDict_SetDefault (*C function*), 134
- PyDict_SetItem (*C function*), 133
- PyDict_SetItemString (*C function*), 134
- PyDict_Size (*C function*), 134
- PyDict_Type (*C var*), 133
- PyDict_Update (*C function*), 135
- PyDict_Values (*C function*), 134
- PyDictObject (*C type*), 133
- PyDictProxy_New (*C function*), 133
- PyDoc_STR (*C macro*), 5
- PyDoc_STRVAR (*C macro*), 5
- PyErr_BadArgument (*C function*), 46
- PyErr_BadInternalCall (*C function*), 48
- PyErr_CheckSignals (*C function*), 50
- PyErr_Clear (*C function*), 45
- PyErr_Clear(), 9, 10
- PyErr_ExceptionMatches (*C function*), 49
- PyErr_ExceptionMatches(), 10
- PyErr_Fetch (*C function*), 49
- PyErr_Format (*C function*), 46
- PyErr_FormatV (*C function*), 46
- PyErr_GetExcInfo (*C function*), 50
- PyErr_GivenExceptionMatches (*C function*), 49
- PyErr_NewException (*C function*), 51
- PyErr_NewExceptionWithDoc (*C function*), 51
- PyErr_NoMemory (*C function*), 46
- PyErr_NormalizeException (*C function*), 50
- PyErr_Occurred (*C function*), 49
- PyErr_Occurred(), 9
- PyErr_Print (*C function*), 45
- PyErr_PrintEx (*C function*), 45
- PyErr_ResourceWarning (*C function*), 49
- PyErr_Restore (*C function*), 49
- PyErr_SetExcFromWindowsErr (*C function*), 47
- PyErr_SetExcFromWindowsErrWithFilename (*C function*), 47
- PyErr_SetExcFromWindowsErrWithFilenameObject (*C function*), 47
- PyErr_SetExcFromWindowsErrWithFilenameObjects (*C function*), 47
- PyErr_SetFromErrno (*C function*), 46
- PyErr_SetFromErrnoWithFilename (*C function*), 47
- PyErr_SetFromErrnoWithFilenameObject (*C function*), 46
- PyErr_SetFromErrnoWithFilenameObjects (*C function*), 47
- PyErr_SetFromWindowsErr (*C function*), 47
- PyErr_SetFromWindowsErrWithFilename (*C function*), 47
- PyErr_SetImportError (*C function*), 47
- PyErr_SetImportErrorSubclass (*C function*), 48
- PyErr_SetInterrupt (*C function*), 51
- PyErr_SetInterruptEx (*C function*), 51
- PyErr_SetNone (*C function*), 46
- PyErr_SetObject (*C function*), 46
- PyErr_SetString (*C function*), 46
- PyErr_SetString(), 9
- PyErr_SyntaxLocation (*C function*), 48
- PyErr_SyntaxLocationEx (*C function*), 48
- PyErr_SyntaxLocationObject (*C function*), 48
- PyErr_WarnEx (*C function*), 48
- PyErr_WarnExplicit (*C function*), 48
- PyErr_WarnExplicitObject (*C function*), 48
- PyErr_WarnFormat (*C function*), 49
- PyErr_WriteUnraisable (*C function*), 46
- PyEval_AcquireLock (*C function*), 174
- PyEval_AcquireThread (*C function*), 174
- PyEval_AcquireThread(), 170
- PyEval_EvalCode (*C function*), 41
- PyEval_EvalCodeEx (*C function*), 42
- PyEval_EvalFrame (*C function*), 42
- PyEval_EvalFrameEx (*C function*), 42
- PyEval_GetBuiltins (*C function*), 74
- PyEval_GetFrame (*C function*), 74
- PyEval_GetFuncDesc (*C function*), 75
- PyEval_GetFuncName (*C function*), 75
- PyEval_GetGlobals (*C function*), 74
- PyEval_GetLocals (*C function*), 74
- PyEval_InitThreads (*C function*), 170
- PyEval_InitThreads(), 164
- PyEval_MergeCompilerFlags (*C function*), 42
- PyEval_ReleaseLock (*C function*), 174
- PyEval_ReleaseThread (*C function*), 174
- PyEval_ReleaseThread(), 170
- PyEval_RestoreThread (*C function*), 171
- PyEval_RestoreThread(), 169, 170
- PyEval_SaveThread (*C function*), 170
- PyEval_SaveThread(), 169, 170
- PyEval_SetProfile (*C function*), 177
- PyEval_SetTrace (*C function*), 178
- PyEval_ThreadsInitialized (*C function*), 170
- PyExc_ArithmeticError, 54
- PyExc_AssertionError, 54
- PyExc_AttributeError, 54
- PyExc_BaseException, 54

PyExc_BlockingIOError, 54
 PyExc_BrokenPipeError, 54
 PyExc_BufferError, 54
 PyExc_BytesWarning, 56
 PyExc_ChildProcessError, 54
 PyExc_ConnectionAbortedError, 54
 PyExc_ConnectionError, 54
 PyExc_ConnectionRefusedError, 54
 PyExc_ConnectionResetError, 54
 PyExc_DeprecationWarning, 56
 PyExc_EnvironmentError, 55
 PyExc_EOFError, 54
 PyExc_Exception, 54
 PyExc_FileExistsError, 54
 PyExc_FileNotFoundError, 54
 PyExc_FloatingPointError, 54
 PyExc_FutureWarning, 56
 PyExc_GeneratorExit, 54
 PyExc_ImportError, 54
 PyExc_ImportWarning, 56
 PyExc_IndentationError, 54
 PyExc_IndexError, 54
 PyExc_InterruptedError, 54
 PyExc_IOError, 55
 PyExc_IsADirectoryError, 54
 PyExc_KeyboardInterrupt, 54
 PyExc_KeyError, 54
 PyExc_LookupError, 54
 PyExc_MemoryError, 54
 PyExc_ModuleNotFoundError, 54
 PyExc_NameError, 54
 PyExc_NotADirectoryError, 54
 PyExc_NotImplementedError, 54
 PyExc_OSError, 54
 PyExc_OverflowError, 54
 PyExc_PendingDeprecationWarning, 56
 PyExc_PermissionError, 54
 PyExc_ProcessLookupError, 54
 PyExc_RecursionError, 54
 PyExc_ReferenceError, 54
 PyExc_ResourceWarning, 56
 PyExc_RuntimeError, 54
 PyExc_RuntimeWarning, 56
 PyExc_StopAsyncIteration, 54
 PyExc_StopIteration, 54
 PyExc_SyntaxError, 54
 PyExc_SyntaxWarning, 56
 PyExc_SystemError, 54
 PyExc_SystemExit, 54
 PyExc_TabError, 54
 PyExc_TimeoutError, 54
 PyExc_TypeError, 54
 PyExc_UnboundLocalError, 54
 PyExc_UnicodeDecodeError, 54
 PyExc_UnicodeEncodeError, 54
 PyExc_UnicodeError, 54
 PyExc_UnicodeTranslateError, 54
 PyExc_UnicodeWarning, 56
 PyExc_UserWarning, 56
 PyExc_ValueError, 54
 PyExc_Warning, 56
 PyExc_WindowsError, 55
 PyExc_ZeroDivisionError, 54
 PyException_GetCause (*C function*), 52
 PyException_GetContext (*C function*), 52
 PyException_GetTraceback (*C function*), 52
 PyException_SetCause (*C function*), 52
 PyException_SetContext (*C function*), 52
 PyException_SetTraceback (*C function*), 52
 PyFile_FromFd (*C function*), 140
 PyFile_GetLine (*C function*), 141
 PyFile_SetOpenCodeHook (*C function*), 141
 PyFile_WriteObject (*C function*), 141
 PyFile_WriteString (*C function*), 141
 PyFloat_AS_DOUBLE (*C function*), 106
 PyFloat_AsDouble (*C function*), 106
 PyFloat_Check (*C function*), 106
 PyFloat_CheckExact (*C function*), 106
 PyFloat_FromDouble (*C function*), 106
 PyFloat_FromString (*C function*), 106
 PyFloat_GetInfo (*C function*), 106
 PyFloat_GetMax (*C function*), 106
 PyFloat_GetMin (*C function*), 106
 PyFloat_Type (*C var*), 106
 PyFloatObject (*C type*), 106
 PyFrame_GetBack (*C function*), 74
 PyFrame_GetCode (*C function*), 74
 PyFrame_GetLineNumber (*C function*), 75
 PyFrameObject (*C type*), 42
 PyFrozenSet_Check (*C function*), 136
 PyFrozenSet_CheckExact (*C function*), 136
 PyFrozenSet_New (*C function*), 136
 PyFrozenSet_Type (*C var*), 136
 PyFunction_Check (*C function*), 137
 PyFunction_GetAnnotations (*C function*), 138
 PyFunction_GetClosure (*C function*), 138
 PyFunction_GetCode (*C function*), 137
 PyFunction_GetDefaults (*C function*), 138
 PyFunction_GetGlobals (*C function*), 137
 PyFunction_GetModule (*C function*), 138
 PyFunction_New (*C function*), 137
 PyFunction_NewWithQualName (*C function*), 137
 PyFunction_SetAnnotations (*C function*), 138
 PyFunction_SetClosure (*C function*), 138
 PyFunction_SetDefaults (*C function*), 138
 PyFunction_Type (*C var*), 137
 PyFunctionObject (*C type*), 137
 PyGC_Collect (*C function*), 253
 PyGC_Disable (*C function*), 253
 PyGC_Enable (*C function*), 253
 PyGC_IsEnabled (*C function*), 253
 PyGen_Check (*C function*), 154
 PyGen_CheckExact (*C function*), 154
 PyGen_New (*C function*), 154
 PyGen_NewWithQualName (*C function*), 154

- PyGen_Type (*C var*), 154
- PyGenObject (*C type*), 154
- PyGetSetDef (*C type*), 217
- PyGILState_Check (*C function*), 171
- PyGILState_Ensure (*C function*), 171
- PyGILState_GetThisThreadState (*C function*), 171
- PyGILState_Release (*C function*), 171
- PyImport_AddModule (*C function*), 63
- PyImport_AddModuleObject (*C function*), 62
- PyImport_AppendInittab (*C function*), 64
- PyImport_ExecCodeModule (*C function*), 63
- PyImport_ExecCodeModuleEx (*C function*), 63
- PyImport_ExecCodeModuleObject (*C function*), 63
- PyImport_ExecCodeModuleWithPathnames (*C function*), 63
- PyImport_ExtendInittab (*C function*), 65
- PyImport_FrozenModules (*C var*), 64
- PyImport_GetImporter (*C function*), 64
- PyImport_GetMagicNumber (*C function*), 63
- PyImport_GetMagicTag (*C function*), 63
- PyImport_GetModule (*C function*), 64
- PyImport_GetModuleDict (*C function*), 64
- PyImport_Import (*C function*), 62
- PyImport_ImportFrozenModule (*C function*), 64
- PyImport_ImportFrozenModuleObject (*C function*), 64
- PyImport_ImportModule (*C function*), 62
- PyImport_ImportModuleEx (*C function*), 62
- PyImport_ImportModuleLevel (*C function*), 62
- PyImport_ImportModuleLevelObject (*C function*), 62
- PyImport_ImportModuleNoBlock (*C function*), 62
- PyImport_ReloadModule (*C function*), 62
- PyIndex_Check (*C function*), 87
- PyInstanceMethod_Check (*C function*), 138
- PyInstanceMethod_Function (*C function*), 138
- PyInstanceMethod_GET_FUNCTION (*C function*), 138
- PyInstanceMethod_New (*C function*), 138
- PyInstanceMethod_Type (*C var*), 138
- PyInterpreterState (*C type*), 170
- PyInterpreterState_Clear (*C function*), 172
- PyInterpreterState_Delete (*C function*), 172
- PyInterpreterState_Get (*C function*), 173
- PyInterpreterState_GetDict (*C function*), 173
- PyInterpreterState_GetID (*C function*), 173
- PyInterpreterState_Head (*C function*), 178
- PyInterpreterState_Main (*C function*), 178
- PyInterpreterState_New (*C function*), 172
- PyInterpreterState_Next (*C function*), 178
- PyInterpreterState_ThreadHead (*C function*), 178
- PyIter_Check (*C function*), 90
- PyIter_Next (*C function*), 90
- PyIter_Send (*C function*), 91
- PyList_Append (*C function*), 133
- PyList_AsTuple (*C function*), 133
- PyList_Check (*C function*), 132
- PyList_CheckExact (*C function*), 132
- PyList_GET_ITEM (*C function*), 132
- PyList_GET_SIZE (*C function*), 132
- PyList_GetItem (*C function*), 132
- PyList_GetItem(), 8
- PyList_GetSlice (*C function*), 133
- PyList_Insert (*C function*), 132
- PyList_New (*C function*), 132
- PyList_Reverse (*C function*), 133
- PyList_SET_ITEM (*C function*), 132
- PyList_SetItem (*C function*), 132
- PyList_SetItem(), 6
- PyList_SetSlice (*C function*), 133
- PyList_Size (*C function*), 132
- PyList_Sort (*C function*), 133
- PyList_Type (*C var*), 132
- PyListObject (*C type*), 132
- PyLong_AsDouble (*C function*), 105
- PyLong_AsLong (*C function*), 103
- PyLong_AsLongAndOverflow (*C function*), 104
- PyLong_AsLongLong (*C function*), 104
- PyLong_AsLongLongAndOverflow (*C function*), 104
- PyLong_AsSize_t (*C function*), 104
- PyLong_AsSsize_t (*C function*), 104
- PyLong_AsUnsignedLong (*C function*), 104
- PyLong_AsUnsignedLongLong (*C function*), 104
- PyLong_AsUnsignedLongLongMask (*C function*), 105
- PyLong_AsUnsignedLongMask (*C function*), 105
- PyLong_AsVoidPtr (*C function*), 105
- PyLong_Check (*C function*), 103
- PyLong_CheckExact (*C function*), 103
- PyLong_FromDouble (*C function*), 103
- PyLong_FromLong (*C function*), 103
- PyLong_FromLongLong (*C function*), 103
- PyLong_FromSize_t (*C function*), 103
- PyLong_FromSsize_t (*C function*), 103
- PyLong_FromString (*C function*), 103
- PyLong_FromUnicodeObject (*C function*), 103
- PyLong_FromUnsignedLong (*C function*), 103
- PyLong_FromUnsignedLongLong (*C function*), 103
- PyLong_FromVoidPtr (*C function*), 103
- PyLong_Type (*C var*), 102
- PyLongObject (*C type*), 102
- PyMapping_Check (*C function*), 89
- PyMapping_DelItem (*C function*), 89
- PyMapping_DelItemString (*C function*), 90
- PyMapping_GetItemString (*C function*), 89
- PyMapping_HasKey (*C function*), 90
- PyMapping_HasKeyString (*C function*), 90
- PyMapping_Items (*C function*), 90

- PyMapping_Keys (*C function*), 90
- PyMapping_Length (*C function*), 89
- PyMapping_SetItemString (*C function*), 89
- PyMapping_Size (*C function*), 89
- PyMapping_Values (*C function*), 90
- PyMappingMethods (*C type*), 245
- PyMappingMethods.mp_ass_subscript (*C member*), 245
- PyMappingMethods.mp_length (*C member*), 245
- PyMappingMethods.mp_subscript (*C member*), 245
- PyMarshal_ReadLastObjectFromFile (*C function*), 65
- PyMarshal_ReadLongFromFile (*C function*), 65
- PyMarshal_ReadObjectFromFile (*C function*), 65
- PyMarshal_ReadObjectFromString (*C function*), 65
- PyMarshal_ReadShortFromFile (*C function*), 65
- PyMarshal_WriteLongToFile (*C function*), 65
- PyMarshal_WriteObjectToFile (*C function*), 65
- PyMarshal_WriteObjectToString (*C function*), 65
- PyMem_Calloc (*C function*), 203
- PyMem_Del (*C function*), 204
- PyMem_Free (*C function*), 203
- PyMem_GetAllocator (*C function*), 206
- PyMem_Malloc (*C function*), 203
- PyMem_New (*C function*), 203
- PyMem_RawCalloc (*C function*), 202
- PyMem_RawFree (*C function*), 203
- PyMem_RawMalloc (*C function*), 202
- PyMem_RawRealloc (*C function*), 202
- PyMem_Realloc (*C function*), 203
- PyMem_Resize (*C function*), 203
- PyMem_SetAllocator (*C function*), 206
- PyMem_SetupDebugHooks (*C function*), 206
- PyMemAllocatorDomain (*C type*), 205
- PyMemAllocatorDomain.PYMEM_DOMAIN_MEM (*C macro*), 206
- PyMemAllocatorDomain.PYMEM_DOMAIN_OBJ (*C macro*), 206
- PyMemAllocatorDomain.PYMEM_DOMAIN_RAW (*C macro*), 205
- PyMemAllocatorEx (*C type*), 205
- PyMember_GetOne (*C function*), 217
- PyMember_SetOne (*C function*), 217
- PyMemberDef (*C type*), 216
- PyMemoryView_Check (*C function*), 151
- PyMemoryView_FromBuffer (*C function*), 151
- PyMemoryView_FromMemory (*C function*), 151
- PyMemoryView_FromObject (*C function*), 151
- PyMemoryView_GET_BASE (*C function*), 151
- PyMemoryView_GET_BUFFER (*C function*), 151
- PyMemoryView_GetContiguous (*C function*), 151
- PyMethod_Check (*C function*), 139
- PyMethod_Function (*C function*), 139
- PyMethod_GET_FUNCTION (*C function*), 139
- PyMethod_GET_SELF (*C function*), 139
- PyMethod_New (*C function*), 139
- PyMethod_Self (*C function*), 139
- PyMethod_Type (*C var*), 139
- PyMethodDef (*C type*), 214
- PyMethodDef.ml_doc (*C member*), 214
- PyMethodDef.ml_flags (*C member*), 214
- PyMethodDef.ml_meth (*C member*), 214
- PyMethodDef.ml_name (*C member*), 214
- PyModule_AddFunctions (*C function*), 146
- PyModule_AddIntConstant (*C function*), 147
- PyModule_AddIntMacro (*C function*), 147
- PyModule_AddObject (*C function*), 146
- PyModule_AddObjectRef (*C function*), 146
- PyModule_AddStringConstant (*C function*), 147
- PyModule_AddStringMacro (*C function*), 147
- PyModule_AddType (*C function*), 147
- PyModule_Check (*C function*), 141
- PyModule_CheckExact (*C function*), 141
- PyModule_Create (*C function*), 144
- PyModule_Create2 (*C function*), 144
- PyModule_ExecDef (*C function*), 145
- PyModule_FromDefAndSpec (*C function*), 145
- PyModule_FromDefAndSpec2 (*C function*), 145
- PyModule_GetDef (*C function*), 142
- PyModule_GetDict (*C function*), 142
- PyModule_GetFilename (*C function*), 142
- PyModule_GetFilenameObject (*C function*), 142
- PyModule_GetName (*C function*), 142
- PyModule_GetNameObject (*C function*), 142
- PyModule_GetState (*C function*), 142
- PyModule_New (*C function*), 142
- PyModule_NewObject (*C function*), 141
- PyModule_SetDocString (*C function*), 146
- PyModule_Type (*C var*), 141
- PyModuleDef (*C type*), 142
- PyModuleDef_Init (*C function*), 144
- PyModuleDef_Slot (*C type*), 144
- PyModuleDef_Slot.slot (*C member*), 144
- PyModuleDef_Slot.value (*C member*), 144
- PyModuleDef.m_base (*C member*), 142
- PyModuleDef.m_clear (*C member*), 143
- PyModuleDef.m_doc (*C member*), 142
- PyModuleDef.m_free (*C member*), 143
- PyModuleDef.m_methods (*C member*), 143
- PyModuleDef.m_name (*C member*), 142
- PyModuleDef.m_size (*C member*), 143
- PyModuleDef.m_slots (*C member*), 143
- PyModuleDef.m_slots.m_reload (*C member*), 143
- PyModuleDef.m_traverse (*C member*), 143

- PyNumber_Absolute (*C function*), 86
- PyNumber_Add (*C function*), 85
- PyNumber_And (*C function*), 86
- PyNumber_AsSsize_t (*C function*), 87
- PyNumber_Check (*C function*), 85
- PyNumber_Divmod (*C function*), 85
- PyNumber_Float (*C function*), 87
- PyNumber_FloorDivide (*C function*), 85
- PyNumber_Index (*C function*), 87
- PyNumber_InPlaceAdd (*C function*), 86
- PyNumber_InPlaceAnd (*C function*), 87
- PyNumber_InPlaceFloorDivide (*C function*), 86
- PyNumber_InPlaceLshift (*C function*), 87
- PyNumber_InPlaceMatrixMultiply (*C function*), 86
- PyNumber_InPlaceMultiply (*C function*), 86
- PyNumber_InPlaceOr (*C function*), 87
- PyNumber_InPlacePower (*C function*), 87
- PyNumber_InPlaceRemainder (*C function*), 86
- PyNumber_InPlaceRshift (*C function*), 87
- PyNumber_InPlaceSubtract (*C function*), 86
- PyNumber_InPlaceTrueDivide (*C function*), 86
- PyNumber_InPlaceXor (*C function*), 87
- PyNumber_Invert (*C function*), 86
- PyNumber_Long (*C function*), 87
- PyNumber_Lshift (*C function*), 86
- PyNumber_MatrixMultiply (*C function*), 85
- PyNumber_Multiply (*C function*), 85
- PyNumber_Negative (*C function*), 85
- PyNumber_Or (*C function*), 86
- PyNumber_Positive (*C function*), 86
- PyNumber_Power (*C function*), 85
- PyNumber_Remainder (*C function*), 85
- PyNumber_Rshift (*C function*), 86
- PyNumber_Subtract (*C function*), 85
- PyNumber_ToBase (*C function*), 87
- PyNumber_TrueDivide (*C function*), 85
- PyNumber_Xor (*C function*), 86
- PyNumberMethods (*C type*), 243
- PyNumberMethods.nb_absolute (*C member*), 244
- PyNumberMethods.nb_add (*C member*), 243
- PyNumberMethods.nb_and (*C member*), 244
- PyNumberMethods.nb_bool (*C member*), 244
- PyNumberMethods.nb_divmod (*C member*), 244
- PyNumberMethods.nb_float (*C member*), 244
- PyNumberMethods.nb_floor_divide (*C member*), 244
- PyNumberMethods.nb_index (*C member*), 244
- PyNumberMethods.nb_inplace_add (*C member*), 244
- PyNumberMethods.nb_inplace_and (*C member*), 244
- PyNumberMethods.nb_inplace_floor_divide (*C member*), 244
- PyNumberMethods.nb_inplace_lshift (*C member*), 244
- PyNumberMethods.nb_inplace_matrix_multiply (*C member*), 244
- PyNumberMethods.nb_inplace_multiply (*C member*), 244
- PyNumberMethods.nb_inplace_or (*C member*), 244
- PyNumberMethods.nb_inplace_power (*C member*), 244
- PyNumberMethods.nb_inplace_remainder (*C member*), 244
- PyNumberMethods.nb_inplace_rshift (*C member*), 244
- PyNumberMethods.nb_inplace_subtract (*C member*), 244
- PyNumberMethods.nb_inplace_true_divide (*C member*), 244
- PyNumberMethods.nb_inplace_xor (*C member*), 244
- PyNumberMethods.nb_int (*C member*), 244
- PyNumberMethods.nb_invert (*C member*), 244
- PyNumberMethods.nb_lshift (*C member*), 244
- PyNumberMethods.nb_matrix_multiply (*C member*), 244
- PyNumberMethods.nb_multiply (*C member*), 244
- PyNumberMethods.nb_negative (*C member*), 244
- PyNumberMethods.nb_or (*C member*), 244
- PyNumberMethods.nb_positive (*C member*), 244
- PyNumberMethods.nb_power (*C member*), 244
- PyNumberMethods.nb_remainder (*C member*), 244
- PyNumberMethods.nb_reserved (*C member*), 244
- PyNumberMethods.nb_rshift (*C member*), 244
- PyNumberMethods.nb_subtract (*C member*), 244
- PyNumberMethods.nb_true_divide (*C member*), 244
- PyNumberMethods.nb_xor (*C member*), 244
- PyObject (*C type*), 212
- PyObject_AsCharBuffer (*C function*), 97
- PyObject_ASCII (*C function*), 79
- PyObject_AsFileDescriptor (*C function*), 141
- PyObject_AsReadBuffer (*C function*), 97
- PyObject_AsWriteBuffer (*C function*), 97
- PyObject_Bytes (*C function*), 79
- PyObject_Call (*C function*), 83
- PyObject_CallFunction (*C function*), 83
- PyObject_CallFunctionObjArgs (*C function*), 84
- PyObject_CallMethod (*C function*), 83
- PyObject_CallMethodNoArgs (*C function*), 84
- PyObject_CallMethodObjArgs (*C function*), 84
- PyObject_CallMethodOneArg (*C function*), 84
- PyObject_CallNoArgs (*C function*), 83
- PyObject_CallObject (*C function*), 83

- PyObject_Calloc (*C function*), 204
- PyObject_CallOneArg (*C function*), 83
- PyObject_CheckBuffer (*C function*), 96
- PyObject_CheckReadBuffer (*C function*), 97
- PyObject_ClearWeakRefs (*C function*), 152
- PyObject_Del (*C function*), 211
- PyObject_DelAttr (*C function*), 78
- PyObject_DelAttrString (*C function*), 78
- PyObject_DelItem (*C function*), 80
- PyObject_Dir (*C function*), 80
- PyObject_Format (*C function*), 78
- PyObject_Free (*C function*), 204
- PyObject_GC_Del (*C function*), 252
- PyObject_GC_IsFinalized (*C function*), 252
- PyObject_GC_IsTracked (*C function*), 252
- PyObject_GC_New (*C function*), 252
- PyObject_GC_NewVar (*C function*), 252
- PyObject_GC_Resize (*C function*), 252
- PyObject_GC_Track (*C function*), 252
- PyObject_GC_UnTrack (*C function*), 252
- PyObject_GenericGetAttr (*C function*), 78
- PyObject_GenericGetDict (*C function*), 78
- PyObject_GenericSetAttr (*C function*), 78
- PyObject_GenericSetDict (*C function*), 78
- PyObject_GetAIter (*C function*), 80
- PyObject_GetArenaAllocator (*C function*), 208
- PyObject_GetAttr (*C function*), 77
- PyObject_GetAttrString (*C function*), 77
- PyObject_GetBuffer (*C function*), 96
- PyObject_GetItem (*C function*), 80
- PyObject_GetIter (*C function*), 80
- PyObject_HasAttr (*C function*), 77
- PyObject_HasAttrString (*C function*), 77
- PyObject_Hash (*C function*), 79
- PyObject_HashNotImplemented (*C function*), 79
- PyObject_HEAD (*C macro*), 212
- PyObject_HEAD_INIT (*C macro*), 213
- PyObject_Init (*C function*), 211
- PyObject_InitVar (*C function*), 211
- PyObject_IS_GC (*C function*), 252
- PyObject_IsInstance (*C function*), 79
- PyObject_IsSubclass (*C function*), 79
- PyObject_IsTrue (*C function*), 79
- PyObject_Length (*C function*), 80
- PyObject_LengthHint (*C function*), 80
- PyObject_Malloc (*C function*), 204
- PyObject_New (*C function*), 211
- PyObject_NewVar (*C function*), 211
- PyObject_Not (*C function*), 80
- PyObject._ob_next (*C member*), 225
- PyObject._ob_prev (*C member*), 225
- PyObject_Print (*C function*), 77
- PyObject_Realloc (*C function*), 204
- PyObject_Repr (*C function*), 79
- PyObject_RichCompare (*C function*), 78
- PyObject_RichCompareBool (*C function*), 78
- PyObject_SetArenaAllocator (*C function*), 208
- PyObject_SetAttr (*C function*), 78
- PyObject_SetAttrString (*C function*), 78
- PyObject_SetItem (*C function*), 80
- PyObject_Size (*C function*), 80
- PyObject_Str (*C function*), 79
- PyObject_Type (*C function*), 80
- PyObject_TypeCheck (*C function*), 80
- PyObject_VAR_HEAD (*C macro*), 212
- PyObject_Vectorcall (*C function*), 84
- PyObject_VectorcallDict (*C function*), 84
- PyObject_VectorcallMethod (*C function*), 84
- PyObjectArenaAllocator (*C type*), 208
- PyObject.ob_refcnt (*C member*), 224
- PyObject.ob_type (*C member*), 224
- PyOS_AfterFork (*C function*), 58
- PyOS_AfterFork_Child (*C function*), 58
- PyOS_AfterFork_Parent (*C function*), 57
- PyOS_BeforeFork (*C function*), 57
- PyOS_CheckStack (*C function*), 58
- PyOS_double_to_string (*C function*), 74
- PyOS_FSPath (*C function*), 57
- PyOS_getsig (*C function*), 58
- PyOS_InputHook (*C var*), 40
- PyOS_ReadlineFunctionPointer (*C var*), 40
- PyOS_setsig (*C function*), 58
- PyOS_snprintf (*C function*), 73
- PyOS_stricmp (*C function*), 74
- PyOS_string_to_double (*C function*), 73
- PyOS_strnicmp (*C function*), 74
- PyOS_vsnprintf (*C function*), 73
- PyPreConfig (*C type*), 184
- PyPreConfig.allocator (*C member*), 184
- PyPreConfig.coerce_c_locale (*C member*), 184
- PyPreConfig.coerce_c_locale_warn (*C member*), 184
- PyPreConfig.configure_locale (*C member*), 184
- PyPreConfig.dev_mode (*C member*), 185
- PyPreConfig.isolated (*C member*), 185
- PyPreConfig.legacy_windows_fs_encoding (*C member*), 185
- PyPreConfig.parse_argv (*C member*), 185
- PyPreConfig.PyPreConfig_InitIsolatedConfig (*C function*), 184
- PyPreConfig.PyPreConfig_InitPythonConfig (*C function*), 184
- PyPreConfig.use_environment (*C member*), 185
- PyPreConfig.utf8_mode (*C member*), 185
- PyProperty_Type (*C var*), 149
- PyRun_AnyFile (*C function*), 39
- PyRun_AnyFileEx (*C function*), 39
- PyRun_AnyFileExFlags (*C function*), 39
- PyRun_AnyFileFlags (*C function*), 39
- PyRun_File (*C function*), 41

- PyRun_FileEx (*C function*), 41
- PyRun_FileExFlags (*C function*), 41
- PyRun_FileFlags (*C function*), 41
- PyRun_InteractiveLoop (*C function*), 40
- PyRun_InteractiveLoopFlags (*C function*), 40
- PyRun_InteractiveOne (*C function*), 40
- PyRun_InteractiveOneFlags (*C function*), 40
- PyRun_SimpleFile (*C function*), 40
- PyRun_SimpleFileEx (*C function*), 40
- PyRun_SimpleFileExFlags (*C function*), 40
- PyRun_SimpleString (*C function*), 40
- PyRun_SimpleStringFlags (*C function*), 40
- PyRun_String (*C function*), 41
- PyRun_StringFlags (*C function*), 41
- PySendResult (*C type*), 91
- PySeqIter_Check (*C function*), 148
- PySeqIter_New (*C function*), 148
- PySeqIter_Type (*C var*), 148
- PySequence_Check (*C function*), 88
- PySequence_Concat (*C function*), 88
- PySequence_Contains (*C function*), 88
- PySequence_Count (*C function*), 88
- PySequence_DelItem (*C function*), 88
- PySequence_DelSlice (*C function*), 88
- PySequence_Fast (*C function*), 89
- PySequence_Fast_GET_ITEM (*C function*), 89
- PySequence_Fast_GET_SIZE (*C function*), 89
- PySequence_Fast_ITEMS (*C function*), 89
- PySequence_GetItem (*C function*), 88
- PySequence_GetItem(), 8
- PySequence_GetSlice (*C function*), 88
- PySequence_Index (*C function*), 88
- PySequence_InPlaceConcat (*C function*), 88
- PySequence_InPlaceRepeat (*C function*), 88
- PySequence_ITEM (*C function*), 89
- PySequence_Length (*C function*), 88
- PySequence_List (*C function*), 89
- PySequence_Repeat (*C function*), 88
- PySequence_SetItem (*C function*), 88
- PySequence_SetSlice (*C function*), 88
- PySequence_Size (*C function*), 88
- PySequence_Tuple (*C function*), 89
- PySequenceMethods (*C type*), 245
- PySequenceMethods.sq_ass_item (*C member*), 245
- PySequenceMethods.sq_concat (*C member*), 245
- PySequenceMethods.sq_contains (*C member*), 245
- PySequenceMethods.sq_inplace_concat (*C member*), 245
- PySequenceMethods.sq_inplace_repeat (*C member*), 246
- PySequenceMethods.sq_item (*C member*), 245
- PySequenceMethods.sq_length (*C member*), 245
- PySequenceMethods.sq_repeat (*C member*), 245
- PySet_Add (*C function*), 137
- PySet_Check (*C function*), 136
- PySet_CheckExact (*C function*), 136
- PySet_Clear (*C function*), 137
- PySet_Contains (*C function*), 136
- PySet_Discard (*C function*), 137
- PySet_GET_SIZE (*C function*), 136
- PySet_New (*C function*), 136
- PySet_Pop (*C function*), 137
- PySet_Size (*C function*), 136
- PySet_Type (*C var*), 136
- PySetObject (*C type*), 136
- PySignal_SetWakeupFd (*C function*), 51
- PySlice_AdjustIndices (*C function*), 150
- PySlice_Check (*C function*), 149
- PySlice_GetIndices (*C function*), 149
- PySlice_GetIndicesEx (*C function*), 150
- PySlice_New (*C function*), 149
- PySlice_Type (*C var*), 149
- PySlice_Unpack (*C function*), 150
- PyState_AddModule (*C function*), 148
- PyState_FindModule (*C function*), 148
- PyState_RemoveModule (*C function*), 148
- PyStatus (*C type*), 183
- PyStatus.err_msg (*C member*), 183
- PyStatus.exitcode (*C member*), 183
- PyStatus.func (*C member*), 183
- PyStatus.Py_ExitStatusException (*C function*), 183
- PyStatus.PyStatus_Error (*C function*), 183
- PyStatus.PyStatus_Exception (*C function*), 183
- PyStatus.PyStatus_Exit (*C function*), 183
- PyStatus.PyStatus_IsError (*C function*), 183
- PyStatus.PyStatus_IsExit (*C function*), 183
- PyStatus.PyStatus_NoMemory (*C function*), 183
- PyStatus.PyStatus_Ok (*C function*), 183
- PyStructSequence_Desc (*C type*), 131
- PyStructSequence_Field (*C type*), 131
- PyStructSequence_GET_ITEM (*C function*), 131
- PyStructSequence_GetItem (*C function*), 131
- PyStructSequence_InitType (*C function*), 131
- PyStructSequence_InitType2 (*C function*), 131
- PyStructSequence_New (*C function*), 131
- PyStructSequence_NewType (*C function*), 131
- PyStructSequence_SET_ITEM (*C function*), 131
- PyStructSequence_SetItem (*C function*), 131
- PyStructSequence_UnnamedField (*C var*), 131
- PySys_AddAuditHook (*C function*), 61
- PySys_AddWarnOption (*C function*), 60
- PySys_AddWarnOptionUnicode (*C function*), 60
- PySys_AddXOption (*C function*), 60
- PySys_Audit (*C function*), 60
- PySys_FormatStderr (*C function*), 60
- PySys_FormatStdout (*C function*), 60

- PySys_GetObject (*C function*), 59
- PySys_GetXOptions (*C function*), 60
- PySys_ResetWarnOptions (*C function*), 59
- PySys_SetArgv (*C function*), 167
- PySys_SetArgv(), 164
- PySys_SetArgvEx (*C function*), 167
- PySys_SetArgvEx(), 10, 164
- PySys_SetObject (*C function*), 59
- PySys_SetPath (*C function*), 60
- PySys_WriteStderr (*C function*), 60
- PySys_WriteStdout (*C function*), 60
- Python 3000, 267
- Python Enhancement Proposals
 - PEP 1, 266
 - PEP 7, 3, 5
 - PEP 238, 42, 261
 - PEP 278, 269
 - PEP 302, 261, 264
 - PEP 343, 259
 - PEP 353, 9
 - PEP 362, 258, 266
 - PEP 383, 119
 - PEP 387, 13
 - PEP 393, 111, 118
 - PEP 411, 267
 - PEP 420, 261, 265, 266
 - PEP 432, 199, 200
 - PEP 442, 242
 - PEP 443, 262
 - PEP 451, 145, 261
 - PEP 483, 262
 - PEP 484, 257, 261, 262, 269
 - PEP 489, 145
 - PEP 492, 258, 260
 - PEP 498, 261
 - PEP 519, 266
 - PEP 523, 173, 174
 - PEP 525, 258
 - PEP 526, 257, 269
 - PEP 528, 163, 191
 - PEP 529, 119, 163
 - PEP 538, 197
 - PEP 539, 179
 - PEP 540, 197
 - PEP 552, 189
 - PEP 578, 61
 - PEP 585, 262
 - PEP 587, 181
 - PEP 590, 81
 - PEP 623, 111
 - PEP 634, 233
 - PEP 3116, 269
 - PEP 3119, 79
 - PEP 3121, 143
 - PEP 3147, 64
 - PEP 3151, 55
 - PEP 3155, 267
- PYTHON*, 162
- PYTHONCOERCECLOCALE, 197
- PYTHONDEBUG, 162, 192
- PYTHONDONTWRITEBYTECODE, 162, 195
- PYTHONDUMPREFS, 189, 225
- PYTHONEXECUTABLE, 193
- PYTHONFAULTHANDLER, 189
- PYTHONHASHSEED, 162, 190
- PYTHONHOME, 11, 162, 168, 190
- Pythonic (Python 風格的), 267
- PYTHONINSPECT, 163, 190
- PYTHONIOENCODING, 165, 194
- PYTHONLEGACYWINDOWSFSENCODING, 163, 185
- PYTHONLEGACYWINDOWSSSTDIO, 163, 191
- PYTHONMALLOC, 202, 205, 207
- PYTHONMALLOC` (例 如: ``PYTHONMALLOC=malloc`, 208
- PYTHONMALLOCSTATS, 191, 202
- PYTHONNOUSERSITE, 163, 194
- PYTHONOPTIMIZE, 163, 192
- PYTHONPATH, 11, 162, 191
- PYTHONPLATLIBDIR, 191
- PYTHONPROFILEIMPORTTIME, 190
- PYTHONPYCACHEPREFIX, 193
- PYTHONTRACEMALLOC, 194
- PYTHONUNBUFFERED, 163, 188
- PYTHONUTF8, 185, 197
- PYTHONVERBOSE, 163, 195
- PYTHONWARNINGS, 195
- PyThread_create_key (*C function*), 180
- PyThread_delete_key (*C function*), 180
- PyThread_delete_key_value (*C function*), 180
- PyThread_get_key_value (*C function*), 180
- PyThread_ReInitTLS (*C function*), 180
- PyThread_set_key_value (*C function*), 180
- PyThread_tss_alloc (*C function*), 179
- PyThread_tss_create (*C function*), 179
- PyThread_tss_delete (*C function*), 179
- PyThread_tss_free (*C function*), 179
- PyThread_tss_get (*C function*), 180
- PyThread_tss_is_created (*C function*), 179
- PyThread_tss_set (*C function*), 179
- PyThreadState, 168
- PyThreadState (*C type*), 170
- PyThreadState_Clear (*C function*), 172
- PyThreadState_Delete (*C function*), 172
- PyThreadState_DeleteCurrent (*C function*), 172
- PyThreadState_Get (*C function*), 171
- PyThreadState_GetDict (*C function*), 174
- PyThreadState_GetFrame (*C function*), 172
- PyThreadState_GetID (*C function*), 173
- PyThreadState_GetInterpreter (*C function*), 173
- PyThreadState_New (*C function*), 172
- PyThreadState_Next (*C function*), 178
- PyThreadState_SetAsyncExc (*C function*), 174
- PyThreadState_Swap (*C function*), 171
- PyTime_Check (*C function*), 156

- PyTime_CheckExact (*C function*), 156
- PyTime_FromTime (*C function*), 157
- PyTime_FromTimeAndFold (*C function*), 157
- PyTimeZone_FromOffset (*C function*), 157
- PyTimeZone_FromOffsetAndName (*C function*), 157
- PyTrace_C_CALL (*C var*), 177
- PyTrace_C_EXCEPTION (*C var*), 177
- PyTrace_C_RETURN (*C var*), 177
- PyTrace_CALL (*C var*), 177
- PyTrace_EXCEPTION (*C var*), 177
- PyTrace_LINE (*C var*), 177
- PyTrace_OPCODE (*C var*), 177
- PyTrace_RETURN (*C var*), 177
- PyTraceMalloc_Track (*C function*), 209
- PyTraceMalloc_Untrack (*C function*), 209
- PyTuple_Check (*C function*), 130
- PyTuple_CheckExact (*C function*), 130
- PyTuple_GET_ITEM (*C function*), 130
- PyTuple_GET_SIZE (*C function*), 130
- PyTuple_GetItem (*C function*), 130
- PyTuple_GetSlice (*C function*), 130
- PyTuple_New (*C function*), 130
- PyTuple_Pack (*C function*), 130
- PyTuple_SET_ITEM (*C function*), 130
- PyTuple_SetItem (*C function*), 130
- PyTuple_SetItem(), 6
- PyTuple_Size (*C function*), 130
- PyTuple_Type (*C var*), 130
- PyTupleObject (*C type*), 130
- PyType_Check (*C function*), 99
- PyType_CheckExact (*C function*), 99
- PyType_ClearCache (*C function*), 99
- PyType_FromModuleAndSpec (*C function*), 101
- PyType_FromSpec (*C function*), 101
- PyType_FromSpecWithBases (*C function*), 101
- PyType_GenericAlloc (*C function*), 100
- PyType_GenericNew (*C function*), 100
- PyType_GetFlags (*C function*), 99
- PyType_GetModule (*C function*), 100
- PyType_GetModuleState (*C function*), 100
- PyType_GetSlot (*C function*), 100
- PyType_HasFeature (*C function*), 100
- PyType_IS_GC (*C function*), 100
- PyType_IsSubtype (*C function*), 100
- PyType_Modified (*C function*), 100
- PyType_Ready (*C function*), 100
- PyType_Slot (*C type*), 101
- PyType_Slot.PyType_Slot.pfunc (*C member*), 102
- PyType_Slot.PyType_Slot.slot (*C member*), 101
- PyType_Spec (*C type*), 101
- PyType_Spec.PyType_Spec.basicsize (*C member*), 101
- PyType_Spec.PyType_Spec.flags (*C member*), 101
- PyType_Spec.PyType_Spec.itemsize (*C member*), 101
- PyType_Spec.PyType_Spec.name (*C member*), 101
- PyType_Spec.PyType_Spec.slots (*C member*), 101
- PyType_Type (*C var*), 99
- PyTypeObject (*C type*), 99
- PyTypeObject.tp_alloc (*C member*), 239
- PyTypeObject.tp_as_async (*C member*), 227
- PyTypeObject.tp_as_buffer (*C member*), 230
- PyTypeObject.tp_as_mapping (*C member*), 228
- PyTypeObject.tp_as_number (*C member*), 228
- PyTypeObject.tp_as_sequence (*C member*), 228
- PyTypeObject.tp_base (*C member*), 237
- PyTypeObject.tp_bases (*C member*), 240
- PyTypeObject.tp_basicsize (*C member*), 225
- PyTypeObject.tp_cache (*C member*), 241
- PyTypeObject.tp_call (*C member*), 229
- PyTypeObject.tp_clear (*C member*), 234
- PyTypeObject.tp_dealloc (*C member*), 226
- PyTypeObject.tp_del (*C member*), 241
- PyTypeObject.tp_descr_get (*C member*), 237
- PyTypeObject.tp_descr_set (*C member*), 238
- PyTypeObject.tp_dict (*C member*), 237
- PyTypeObject.tp_dictoffset (*C member*), 238
- PyTypeObject.tp_doc (*C member*), 233
- PyTypeObject.tp_finalize (*C member*), 241
- PyTypeObject.tp_flags (*C member*), 230
- PyTypeObject.tp_free (*C member*), 240
- PyTypeObject.tp_getattr (*C member*), 227
- PyTypeObject.tp_getattro (*C member*), 229
- PyTypeObject.tp_getset (*C member*), 237
- PyTypeObject.tp_hash (*C member*), 228
- PyTypeObject.tp_init (*C member*), 238
- PyTypeObject.tp_is_gc (*C member*), 240
- PyTypeObject.tp_itemsize (*C member*), 225
- PyTypeObject.tp_iter (*C member*), 236
- PyTypeObject.tp_ternext (*C member*), 236
- PyTypeObject.tp_members (*C member*), 236
- PyTypeObject.tp_methods (*C member*), 236
- PyTypeObject.tp_mro (*C member*), 240
- PyTypeObject.tp_name (*C member*), 225
- PyTypeObject.tp_new (*C member*), 239
- PyTypeObject.tp_repr (*C member*), 228
- PyTypeObject.tp_richcompare (*C member*), 235
- PyTypeObject.tp_richcompare.Py_RETURN_RICHCOMPARE (*C macro*), 235
- PyTypeObject.tp_setattr (*C member*), 227
- PyTypeObject.tp_setattro (*C member*), 229
- PyTypeObject.tp_str (*C member*), 229
- PyTypeObject.tp_subclasses (*C member*), 241
- PyTypeObject.tp_traverse (*C member*), 233

- PyTypeObject.tp_vectorcall (*C member*), 242
- PyTypeObject.tp_vectorcall_offset (*C member*), 227
- PyTypeObject.tp_version_tag (*C member*), 241
- PyTypeObject.tp_weaklist (*C member*), 241
- PyTypeObject.tp_weaklistoffset (*C member*), 235
- PyTZInfo_Check (*C function*), 156
- PyTZInfo_CheckExact (*C function*), 156
- PyUnicode_1BYTE_DATA (*C function*), 112
- PyUnicode_1BYTE_KIND (*C macro*), 112
- PyUnicode_2BYTE_DATA (*C function*), 112
- PyUnicode_2BYTE_KIND (*C macro*), 112
- PyUnicode_4BYTE_DATA (*C function*), 112
- PyUnicode_4BYTE_KIND (*C macro*), 112
- PyUnicode_AS_DATA (*C function*), 113
- PyUnicode_AS_UNICODE (*C function*), 113
- PyUnicode_AsASCIIString (*C function*), 126
- PyUnicode_AsCharmapString (*C function*), 127
- PyUnicode_AsEncodedString (*C function*), 121
- PyUnicode_AsLatin1String (*C function*), 126
- PyUnicode_AsMBCSString (*C function*), 127
- PyUnicode_AsRawUnicodeEscapeString (*C function*), 125
- PyUnicode_AsUCS4 (*C function*), 117
- PyUnicode_AsUCS4Copy (*C function*), 117
- PyUnicode_AsUnicode (*C function*), 118
- PyUnicode_AsUnicodeAndSize (*C function*), 118
- PyUnicode_AsUnicodeEscapeString (*C function*), 125
- PyUnicode_AsUTF8 (*C function*), 122
- PyUnicode_AsUTF8AndSize (*C function*), 122
- PyUnicode_AsUTF8String (*C function*), 122
- PyUnicode_AsUTF16String (*C function*), 124
- PyUnicode_AsUTF32String (*C function*), 123
- PyUnicode_AsWideChar (*C function*), 121
- PyUnicode_AsWideCharString (*C function*), 121
- PyUnicode_Check (*C function*), 112
- PyUnicode_CheckExact (*C function*), 112
- PyUnicode_Compare (*C function*), 129
- PyUnicode_CompareWithASCIIString (*C function*), 129
- PyUnicode_Concat (*C function*), 128
- PyUnicode_Contains (*C function*), 129
- PyUnicode_CopyCharacters (*C function*), 117
- PyUnicode_Count (*C function*), 129
- PyUnicode_DATA (*C function*), 112
- PyUnicode_Decode (*C function*), 121
- PyUnicode_DecodeASCII (*C function*), 126
- PyUnicode_DecodeCharmap (*C function*), 126
- PyUnicode_DecodeFSDefault (*C function*), 120
- PyUnicode_DecodeFSDefaultAndSize (*C function*), 120
- PyUnicode_DecodeLatin1 (*C function*), 126
- PyUnicode_DecodeLocale (*C function*), 119
- PyUnicode_DecodeLocaleAndSize (*C function*), 119
- PyUnicode_DecodeMBCS (*C function*), 127
- PyUnicode_DecodeMBCSStateful (*C function*), 127
- PyUnicode_DecodeRawUnicodeEscape (*C function*), 125
- PyUnicode_DecodeUnicodeEscape (*C function*), 125
- PyUnicode_DecodeUTF7 (*C function*), 125
- PyUnicode_DecodeUTF7Stateful (*C function*), 125
- PyUnicode_DecodeUTF8 (*C function*), 122
- PyUnicode_DecodeUTF8Stateful (*C function*), 122
- PyUnicode_DecodeUTF16 (*C function*), 124
- PyUnicode_DecodeUTF16Stateful (*C function*), 124
- PyUnicode_DecodeUTF32 (*C function*), 123
- PyUnicode_DecodeUTF32Stateful (*C function*), 123
- PyUnicode_Encode (*C function*), 122
- PyUnicode_EncodeASCII (*C function*), 126
- PyUnicode_EncodeCharmap (*C function*), 127
- PyUnicode_EncodeCodePage (*C function*), 128
- PyUnicode_EncodeFSDefault (*C function*), 120
- PyUnicode_EncodeLatin1 (*C function*), 126
- PyUnicode_EncodeLocale (*C function*), 119
- PyUnicode_EncodeMBCS (*C function*), 128
- PyUnicode_EncodeRawUnicodeEscape (*C function*), 125
- PyUnicode_EncodeUnicodeEscape (*C function*), 125
- PyUnicode_EncodeUTF7 (*C function*), 125
- PyUnicode_EncodeUTF8 (*C function*), 122
- PyUnicode_EncodeUTF16 (*C function*), 124
- PyUnicode_EncodeUTF32 (*C function*), 123
- PyUnicode_Fill (*C function*), 117
- PyUnicode_Find (*C function*), 128
- PyUnicode_FindChar (*C function*), 128
- PyUnicode_Format (*C function*), 129
- PyUnicode_FromEncodedObject (*C function*), 116
- PyUnicode_FromFormat (*C function*), 115
- PyUnicode_FromFormatV (*C function*), 116
- PyUnicode_FromKindAndData (*C function*), 115
- PyUnicode_FromObject (*C function*), 118
- PyUnicode_FromString (*C function*), 115
- PyUnicode_FromString(), 134
- PyUnicode_FromStringAndSize (*C function*), 115
- PyUnicode_FromUnicode (*C function*), 118
- PyUnicode_FromWideChar (*C function*), 121
- PyUnicode_FSConverter (*C function*), 119
- PyUnicode_FSDecoder (*C function*), 120
- PyUnicode_GET_DATA_SIZE (*C function*), 113
- PyUnicode_GET_LENGTH (*C function*), 112

- PyUnicode_GET_SIZE (*C function*), 113
 PyUnicode_GetLength (*C function*), 116
 PyUnicode_GetSize (*C function*), 118
 PyUnicode_InternFromString (*C function*), 129
 PyUnicode_InternInPlace (*C function*), 129
 PyUnicode_IsIdentifier (*C function*), 113
 PyUnicode_Join (*C function*), 128
 PyUnicode_KIND (*C function*), 112
 PyUnicode_MAX_CHAR_VALUE (*C macro*), 113
 PyUnicode_New (*C function*), 115
 PyUnicode_READ (*C function*), 113
 PyUnicode_READ_CHAR (*C function*), 113
 PyUnicode_ReadChar (*C function*), 117
 PyUnicode_READY (*C function*), 112
 PyUnicode_Replace (*C function*), 129
 PyUnicode_RichCompare (*C function*), 129
 PyUnicode_Split (*C function*), 128
 PyUnicode_Splitlines (*C function*), 128
 PyUnicode_Substring (*C function*), 117
 PyUnicode_Tailmatch (*C function*), 128
 PyUnicode_TransformDecimalToASCII (*C function*), 118
 PyUnicode_Translate (*C function*), 127
 PyUnicode_TranslateCharmap (*C function*), 127
 PyUnicode_Type (*C var*), 111
 PyUnicode_WCHAR_KIND (*C macro*), 112
 PyUnicode_WRITE (*C function*), 112
 PyUnicode_WriteChar (*C function*), 117
 PyUnicodeDecodeError_Create (*C function*), 52
 PyUnicodeDecodeError_GetEncoding (*C function*), 52
 PyUnicodeDecodeError_GetEnd (*C function*), 53
 PyUnicodeDecodeError_GetObject (*C function*), 52
 PyUnicodeDecodeError_GetReason (*C function*), 53
 PyUnicodeDecodeError_GetStart (*C function*), 53
 PyUnicodeDecodeError_SetEnd (*C function*), 53
 PyUnicodeDecodeError_SetReason (*C function*), 53
 PyUnicodeDecodeError_SetStart (*C function*), 53
 PyUnicodeEncodeError_Create (*C function*), 52
 PyUnicodeEncodeError_GetEncoding (*C function*), 52
 PyUnicodeEncodeError_GetEnd (*C function*), 53
 PyUnicodeEncodeError_GetObject (*C function*), 52
 PyUnicodeEncodeError_GetReason (*C function*), 53
 PyUnicodeEncodeError_GetStart (*C function*), 53
 PyUnicodeEncodeError_SetEnd (*C function*), 53
 PyUnicodeEncodeError_SetReason (*C function*), 53
 PyUnicodeEncodeError_SetStart (*C function*), 53
 PyVarObject (*C type*), 212
 PyVarObject_HEAD_INIT (*C macro*), 213
 PyVarObject.ob_size (*C member*), 225
 PyVectorcall_Call (*C function*), 82
 PyVectorcall_Function (*C function*), 82
 PyVectorcall_NARGS (*C function*), 82
 PyWeakref_Check (*C function*), 151
 PyWeakref_CheckProxy (*C function*), 151
 PyWeakref_CheckRef (*C function*), 151
 PyWeakref_GET_OBJECT (*C function*), 152
 PyWeakref_GetObject (*C function*), 152
 PyWeakref_NewProxy (*C function*), 152
 PyWeakref_NewRef (*C function*), 151
 PyWideStringList (*C type*), 182
 PyWideStringList.items (*C member*), 182
 PyWideStringList.length (*C member*), 182
 PyWideStringList.PyWideStringList_Append (*C function*), 182
 PyWideStringList.PyWideStringList_Insert (*C function*), 182
 PyWrapper_New (*C function*), 149
- ## Q
- qualified name (限定名稱), 267
- ## R
- realloc(), 201
 reference count (參照計數), 267
 regular package (正規套件), 267
 releasebufferproc (*C type*), 249
 repr
 建函式, 79, 228
 reprfunc (*C type*), 248

richcmpfunc (*C type*), 248

S

stderr

 stdin stdout, 165

search

 path, module, 10, 164, 166

sendfunc (*C type*), 249

sequence

 物件, 108

sequence (序列), 268

set

 物件, 136

set comprehension (集合綜合運算), 268

set_all(), 7

setattrfunc (*C type*), 248

setattrofunc (*C type*), 248

setswitchinterval() (*in module sys*), 168

SIGINT, 50, 51

signal

 模組, 50, 51

single dispatch (單一調度), 268

SIZE_MAX, 104

slice (切片), 268

special

 method, 268

special method (特殊方法), 268

ssizeargfunc (*C type*), 249

ssizeobjargproc (*C type*), 249

statement (陳述式), 268

staticmethod

 函式, 216

stderr (*in module sys*), 175

stdin

 stdout stderr, 165

stdin (*in module sys*), 175

stdout

 stderr, stdin, 165

stdout (*in module sys*), 175

strerror(), 46

string

 PyObject_Str (*C function*), 79

strong reference (參照), 268

sum_list(), 8

sum_sequence(), 8, 9

sys

 模組, 10, 164, 175

SystemError (*built-in exception*), 142

T

ternaryfunc (*C type*), 249

text encoding (文字編碼), 268

text file (文字檔案), 268

traverseproc (*C type*), 252

triple-quoted string (三引號字串), 268

tuple

 函式, 89, 133

 物件, 130

type

 函式, 80

 物件, 6, 99

type alias (型名), 268

type hint (型提示), 269

type (型), 268

U

ULONG_MAX, 104

unaryfunc (*C type*), 249

universal newlines (通用行字元), 269

V

variable annotation (變數釋), 269

函式

 __import__, 62

 abs, 86

 ascii, 79

 bytes, 79

 classmethod, 216

 compile, 63

 divmod, 85

 float, 87

 hash, 79, 228

 int, 87

 len, 80, 88, 89, 132, 134, 136

 pow, 85, 87

 repr, 79, 228

 staticmethod, 216

 tuple, 89, 133

 type, 80

vectorcallfunc (*C type*), 81

version (*in module sys*), 166, 167

virtual environment (擬環境), 269

virtual machine (擬機器), 269

visitproc (*C type*), 252

W

模組

 __main__, 10, 164, 175

 _thread, 170

 builtins, 10, 164, 175

 signal, 50, 51

 sys, 10, 164, 175

Z

Zen of Python (Python 之), 269