
What's New in Python

發 F 3.12.4

A. M. Kuchling

7 月 31, 2024

Python Software Foundation
Email: docs@python.org

Contents

1	發布重點摘要	3
2	新增特性	4
2.1	PEP 695: Type Parameter Syntax	4
2.2	PEP 701: Syntactic formalization of f-strings	5
2.3	PEP 684: A Per-Interpreter GIL	6
2.4	PEP 669: Low impact monitoring for CPython	7
2.5	PEP 688: Making the buffer protocol accessible in Python	7
2.6	PEP 709: Comprehension inlining	7
2.7	Improved Error Messages	8
3	New Features Related to Type Hints	8
3.1	PEP 692: Using TypedDict for more precise **kwargs typing	9
3.2	PEP 698: Override Decorator for Static Typing	9
4	其他語言更動	9
5	新增模組	10
6	改進的模組	10
6.1	array	10
6.2	asyncio	11
6.3	calendar	11
6.4	csv	11
6.5	dis	11
6.6	fractions	12
6.7	importlib.resources	12
6.8	inspect	12
6.9	itertools	12
6.10	math	12
6.11	os	12
6.12	os.path	13
6.13	pathlib	13
6.14	pdb	13
6.15	random	13
6.16	shutil	13
6.17	sqlite3	14
6.18	statistics	14

6.19	sys	14
6.20	tempfile	15
6.21	threading	15
6.22	tkinter	15
6.23	tokenize	15
6.24	types	15
6.25	typing	15
6.26	unicodedata	16
6.27	unittest	16
6.28	uuid	17
7	最佳化	17
8	CPython 位元組碼變更	17
9	Demos and Tools	18
10	已🔪用	18
10.1	Python 3.13 中待🔪議的移除項目	20
10.2	Python 3.14 中待🔪議的移除項目	21
10.3	Python 3.15 中待🔪議的移除項目	23
10.4	Pending Removal in Python 3.16	24
10.5	未來版本中待🔪議的移除項目	24
11	已移除	26
11.1	asynchat 和 asyncore	26
11.2	configparser	26
11.3	distutils	26
11.4	ensurepip	27
11.5	enum	27
11.6	ftplib	27
11.7	gzip	27
11.8	hashlib	27
11.9	importlib	27
11.10	imp	28
11.11	io	29
11.12	locale	29
11.13	smtpd	29
11.14	sqlite3	29
11.15	ssl	29
11.16	unittest	30
11.17	webbrowser	30
11.18	xml.etree.ElementTree	30
11.19	zipimport	31
11.20	其他	31
12	Porting to Python 3.12	31
12.1	Changes in the Python API	31
13	Build Changes	33
14	C API 變更	33
14.1	新增特性	33
14.2	Porting to Python 3.12	35
14.3	已🔪用	37
14.4	已移除	40
15	Notable changes in 3.12.4	41
15.1	ipaddress	41

編輯者

Adam Turner

This article explains the new features in Python 3.12, compared to 3.11. Python 3.12 was released on October 2, 2023. For full details, see the changelog.

也參考

[PEP 693](#) -- Python 3.12 發⌄時程

1 發布重點摘要

Python 3.12 is the latest stable release of the Python programming language, with a mix of changes to the language and the standard library. The library changes focus on cleaning up deprecated APIs, usability, and correctness. Of note, the `distutils` package has been removed from the standard library. Filesystem support in `os` and `pathlib` has seen a number of improvements, and several modules have better performance.

The language changes focus on usability, as f-strings have had many limitations removed and 'Did you mean ...' suggestions continue to improve. The new *type parameter syntax* and `type` statement improve ergonomics for using generic types and type aliases with static type checkers.

This article doesn't attempt to provide a complete specification of all new features, but instead gives a convenient overview. For full details, you should refer to the documentation, such as the Library Reference and Language Reference. If you want to understand the complete implementation and design rationale for a change, refer to the PEP for a particular new feature; but note that PEPs usually are not kept up-to-date once a feature has been fully implemented.

新增語法特性：

- [PEP 695](#), type parameter syntax and the `type` statement

新增語法特性：

- [PEP 701](#), f-strings in the grammar

直譯器改進：

- [PEP 684](#), a unique per-interpreter GIL
- [PEP 669](#), low impact monitoring
- *Improved 'Did you mean ...' suggestions* for `NameError`, `ImportError`, and `SyntaxError` exceptions

Python data model improvements:

- [PEP 688](#), using the buffer protocol from Python

Significant improvements in the standard library:

- `pathlib.Path` 類⌄現在支援子類⌄化
- The `os` module received several improvements for Windows support
- A command-line interface has been added to the `sqlite3` module
- `isinstance()` checks against runtime-checkable protocols enjoy a speed up of between two and 20 times

- The `asyncio` package has had a number of performance improvements, with some benchmarks showing a 75% speed up.
- A command-line interface has been added to the `uuid` module
- Due to the changes in [PEP 701](#), producing tokens via the `tokenize` module is up to 64% faster.

安全性改進：

- Replace the builtin `hashlib` implementations of SHA1, SHA3, SHA2-384, SHA2-512, and MD5 with formally verified code from the [HACL*](#) project. These builtin implementations remain as fallbacks that are only used when OpenSSL does not provide them.

C API 改進：

- [PEP 697](#), unstable C API tier
- [PEP 683](#), immortal objects

CPython implementation improvements:

- [PEP 709](#), comprehension inlining
- CPython support for the Linux `perf` profiler
- Implement stack overflow protection on supported platforms

新增型別特性：

- [PEP 692](#)、使用 `TypedDict` 來標註 `**kwargs`
- [PEP 698](#)、`typing.override()` 裝飾器

Important deprecations, removals or restrictions:

- **PEP 623**: Remove `wstr` from Unicode objects in Python's C API, reducing the size of every `str` object by at least 8 bytes.
- **PEP 632**: Remove the `distutils` package. See [the migration guide](#) for advice replacing the APIs it provided. The third-party [Setuptools](#) package continues to provide `distutils`, if you still require it in Python 3.12 and beyond.
- [gh-95299](#): Do not pre-install `setuptools` in virtual environments created with `venv`. This means that `distutils`, `setuptools`, `pkg_resources`, and `easy_install` will no longer be available by default; to access these run `pip install setuptools` in the activated virtual environment.
- The `asynchat`, `asyncore`, and `imp` modules have been removed, along with several `unittest.TestCase` [method aliases](#).

2 新增特性

2.1 PEP 695: Type Parameter Syntax

Generic classes and functions under [PEP 484](#) were declared using a verbose syntax that left the scope of type parameters unclear and required explicit declarations of variance.

PEP 695 introduces a new, more compact and explicit way to create generic classes and functions:

```
def max[T](args: Iterable[T]) -> T:
    ...

class list[T]:
    def __getitem__(self, index: int, /) -> T:
        ...

    def append(self, element: T) -> None:
        ...
```


multiple lines), making them harder to read. In Python 3.12 you can now define f-strings spanning multiple lines, and add inline comments:

```
>>> f"This is the playlist: {", ".join([
...     'Take me back to Eden', # My, my, those eyes like fire
...     'Alkaline',             # Not acid nor alkaline
...     'Ascensionism'         # Take to the broken skies at last
... ]})"
'This is the playlist: Take me back to Eden, Alkaline, Ascensionism'
```

- Backslashes and unicode characters: before Python 3.12 f-string expressions couldn't contain any `\` character. This also affected unicode escape sequences (such as `\N{snowman}`) as these contain the `\N` part that previously could not be part of expression components of f-strings. Now, you can define expressions like this:

```
>>> print(f"This is the playlist: {\n".join(songs) }")
This is the playlist: Take me back to Eden
Alkaline
Ascensionism
>>> print(f"This is the playlist: {\N{BLACK HEART SUIT}}.join(songs) }")
This is the playlist: Take me back to Eden♥Alkaline♥Ascensionism
```

詳情請見 [PEP 701](#)。

As a positive side-effect of how this feature has been implemented (by parsing f-strings with [the PEG parser](#)), now error messages for f-strings are more precise and include the exact location of the error. For example, in Python 3.11, the following f-string raises a `SyntaxError`:

```
>>> my_string = f"{x z y}" + f"{1 + 1}"
File "<stdin>", line 1
    (x z y)
    ^^^
SyntaxError: f-string: invalid syntax. Perhaps you forgot a comma?
```

but the error message doesn't include the exact location of the error within the line and also has the expression artificially surrounded by parentheses. In Python 3.12, as f-strings are parsed with the PEG parser, error messages can be more precise and show the entire line:

```
>>> my_string = f"{x z y}" + f"{1 + 1}"
File "<stdin>", line 1
    my_string = f"{x z y}" + f"{1 + 1}"
                  ^^^
SyntaxError: invalid syntax. Perhaps you forgot a comma?
```

(Contributed by Pablo Galindo, Batuhan Taskaya, Lysandros Nikolaou, Cristián Maureira-Fredes and Marta Gómez in [gh-102856](#). PEP written by Pablo Galindo, Batuhan Taskaya, Lysandros Nikolaou and Marta Gómez).

2.3 PEP 684: A Per-Interpreter GIL

[PEP 684](#) introduces a per-interpreter GIL, so that sub-interpreters may now be created with a unique GIL per interpreter. This allows Python programs to take full advantage of multiple CPU cores. This is currently only available through the C-API, though a Python API is [anticipated for 3.13](#).

Use the new `Py_NewInterpreterFromConfig()` function to create an interpreter with its own GIL:

```
PyInterpreterConfig config = {
    .check_multi_interp_extensions = 1,
    .gil = PyInterpreterConfig_OWN_GIL,
};
PyThreadState *tstate = NULL;
PyStatus status = Py_NewInterpreterFromConfig(&tstate, &config);
if (PyStatus_Exception(status)) {
```

(繼續下一頁)

```

    return -1;
}
/* The new interpreter is now active in the current thread. */

```

For further examples how to use the C-API for sub-interpreters with a per-interpreter GIL, see [Modules/_xxsubinterpretersmodule.c](#).

(由 Eric Snow 於 [gh-104210](#) 等貢獻。)

2.4 PEP 669: Low impact monitoring for CPython

PEP 669 defines a new API for profilers, debuggers, and other tools to monitor events in CPython. It covers a wide range of events, including calls, returns, lines, exceptions, jumps, and more. This means that you only pay for what you use, providing support for near-zero overhead debuggers and coverage tools. See [sys.monitoring](#) for details.

(由 Mark Shannon 於 [gh-103082](#) 中貢獻。)

2.5 PEP 688: Making the buffer protocol accessible in Python

PEP 688 introduces a way to use the buffer protocol from Python code. Classes that implement the `__buffer__()` method are now usable as buffer types.

The new `collections.abc.Buffer` ABC provides a standard way to represent buffer objects, for example in type annotations. The new `inspect.BufferFlags` enum represents the flags that can be used to customize buffer creation. (Contributed by Jelle Zijlstra in [gh-102500](#).)

2.6 PEP 709: Comprehension inlining

Dictionary, list, and set comprehensions are now inlined, rather than creating a new single-use function object for each execution of the comprehension. This speeds up execution of a comprehension by up to two times. See **PEP 709** for further details.

Comprehension iteration variables remain isolated and don't overwrite a variable of the same name in the outer scope, nor are they visible after the comprehension. Inlining does result in a few visible behavior changes:

- There is no longer a separate frame for the comprehension in tracebacks, and tracing/profiling no longer shows the comprehension as a function call.
- The `symtable` module will no longer produce child symbol tables for each comprehension; instead, the comprehension's locals will be included in the parent function's symbol table.
- Calling `locals()` inside a comprehension now includes variables from outside the comprehension, and no longer includes the synthetic `.0` variable for the comprehension "argument".
- A comprehension iterating directly over `locals()` (e.g. `[k for k in locals()]`) may see "RuntimeError: dictionary changed size during iteration" when run under tracing (e.g. code coverage measurement). This is the same behavior already seen in e.g. `for k in locals():`. To avoid the error, first create a list of keys to iterate over: `keys = list(locals()); [k for k in keys]`.

(由 Carl Meyer 和 Vladimir Matveev 於 **PEP 709** 中貢獻。)

2.7 Improved Error Messages

- Modules from the standard library are now potentially suggested as part of the error messages displayed by the interpreter when a `NameError` is raised to the top level. (Contributed by Pablo Galindo in [gh-98254](#).)

```
>>> sys.version_info
Traceback (most recent call last):
  File "<stdin>", line 1, in <module>
NameError: name 'sys' is not defined. Did you forget to import 'sys'?
```

- Improve the error suggestion for `NameError` exceptions for instances. Now if a `NameError` is raised in a method and the instance has an attribute that's exactly equal to the name in the exception, the suggestion will include `self.<NAME>` instead of the closest match in the method scope. (Contributed by Pablo Galindo in [gh-99139](#).)

```
>>> class A:
...     def __init__(self):
...         self.blech = 1
...
...     def foo(self):
...         somethin = blech
...
>>> A().foo()
Traceback (most recent call last):
  File "<stdin>", line 1
    somethin = blech
                ^^^^^
NameError: name 'blech' is not defined. Did you mean: 'self.blech'?
```

- Improve the `SyntaxError` error message when the user types `import x from y` instead of `from y import x`. (Contributed by Pablo Galindo in [gh-98931](#).)

```
>>> import a.y.z from b.y.z
Traceback (most recent call last):
  File "<stdin>", line 1
    import a.y.z from b.y.z
    ^^^^^^^^^^^^^^^^^^^^^
SyntaxError: Did you mean to use 'from ... import ...' instead?
```

- `ImportError` exceptions raised from failed `from <module> import <name>` statements now include suggestions for the value of `<name>` based on the available names in `<module>`. (Contributed by Pablo Galindo in [gh-91058](#).)

```
>>> from collections import chainmap
Traceback (most recent call last):
  File "<stdin>", line 1, in <module>
ImportError: cannot import name 'chainmap' from 'collections'. Did you mean:
↳ 'ChainMap'?
```

3 New Features Related to Type Hints

This section covers major changes affecting [type hints](#) and the `typing` module.

3.1 PEP 692: Using TypedDict for more precise **kwargs typing

Typing `**kwargs` in a function signature as introduced by [PEP 484](#) allowed for valid annotations only in cases where all of the `**kwargs` were of the same type.

[PEP 692](#) specifies a more precise way of typing `**kwargs` by relying on typed dictionaries:

```
from typing import TypedDict, Unpack

class Movie(TypedDict):
    name: str
    year: int

def foo(**kwargs: Unpack[Movie]): ...
```

詳情請見 [PEP 692](#)。

(由 Franek Magiera 於 [gh-103629](#) 中貢獻。)

3.2 PEP 698: Override Decorator for Static Typing

A new decorator `typing.override()` has been added to the `typing` module. It indicates to type checkers that the method is intended to override a method in a superclass. This allows type checkers to catch mistakes where a method that is intended to override something in a base class does not in fact do so.

範例：

```
from typing import override

class Base:
    def get_color(self) -> str:
        return "blue"

class GoodChild(Base):
    @override # ok: overrides Base.get_color
    def get_color(self) -> str:
        return "yellow"

class BadChild(Base):
    @override # type checker error: does not override Base.get_color
    def get_colour(self) -> str:
        return "red"
```

詳情請見 [PEP 698](#)。

(由 Steven Troxler 於 [gh-101561](#) 中貢獻。)

4 其他語言更動

- The parser now raises `SyntaxError` when parsing source code containing null bytes. (Contributed by Pablo Galindo in [gh-96670](#).)
- A backslash-character pair that is not a valid escape sequence now generates a `SyntaxWarning`, instead of `DeprecationWarning`. For example, `re.compile("\d+\.\d+")` now emits a `SyntaxWarning` ("`\d`" is an invalid escape sequence, use raw strings for regular expression: `re.compile(r"\d+\.\d+")`). In a future Python version, `SyntaxError` will eventually be raised, instead of `SyntaxWarning`. (Contributed by Victor Stinner in [gh-98401](#).)
- Octal escapes with value larger than `0o377` (ex: `"\477"`), deprecated in Python 3.11, now produce a `SyntaxWarning`, instead of `DeprecationWarning`. In a future Python version they will be eventually a `SyntaxError`. (Contributed by Victor Stinner in [gh-98401](#).)

- Variables used in the target part of comprehensions that are not stored to can now be used in assignment expressions (`:=`). For example, in `[(b := 1) for a, b.prop in some_iter]`, the assignment to `b` is now allowed. Note that assigning to variables stored to in the target part of comprehensions (like `a`) is still disallowed, as per [PEP 572](#). (Contributed by Nikita Sobolev in [gh-100581](#).)
- Exceptions raised in a class or type's `__set_name__` method are no longer wrapped by a `RuntimeError`. Context information is added to the exception as a [PEP 678](#) note. (Contributed by Irit Katriel in [gh-77757](#).)
- When a `try-except*` construct handles the entire `ExceptionGroup` and raises one other exception, that exception is no longer wrapped in an `ExceptionGroup`. Also changed in version 3.11.4. (Contributed by Irit Katriel in [gh-103590](#).)
- The Garbage Collector now runs only on the eval breaker mechanism of the Python bytecode evaluation loop instead of object allocations. The GC can also run when `PyErr_CheckSignals()` is called so C extensions that need to run for a long time without executing any Python code also have a chance to execute the GC periodically. (Contributed by Pablo Galindo in [gh-97922](#).)
- All builtin and extension callables expecting boolean parameters now accept arguments of any type instead of just `bool` and `int`. (Contributed by Serhiy Storchaka in [gh-60203](#).)
- `memoryview` now supports the half-float type (the "e" format code). (Contributed by Donghee Na and Antoine Pitrou in [gh-90751](#).)
- `slice` objects are now hashable, allowing them to be used as dict keys and set items. (Contributed by Will Bradshaw, Furkan Onder, and Raymond Hettinger in [gh-101264](#).)
- `sum()` now uses Neumaier summation to improve accuracy and commutativity when summing floats or mixed ints and floats. (Contributed by Raymond Hettinger in [gh-100425](#).)
- `ast.parse()` now raises `SyntaxError` instead of `ValueError` when parsing source code containing null bytes. (Contributed by Pablo Galindo in [gh-96670](#).)
- The extraction methods in `tarfile`, and `shutil.unpack_archive()`, have a new `filter` argument that allows limiting tar features that may be surprising or dangerous, such as creating files outside the destination directory. See `tarfile` extraction filters for details. In Python 3.14, the default will switch to `'data'`. (Contributed by Petr Viktorin in [PEP 706](#).)
- `types.MappingProxyType` instances are now hashable if the underlying mapping is hashable. (Contributed by Serhiy Storchaka in [gh-87995](#).)
- Add support for the perf profiler through the new environment variable `PYTHONPERFSUPPORT` and command-line option `-X perf`, as well as the new `sys.activate_stack_trampoline()`, `sys.deactivate_stack_trampoline()`, and `sys.is_stack_trampoline_active()` functions. (Design by Pablo Galindo. Contributed by Pablo Galindo and Christian Heimes with contributions from Gregory P. Smith [Google] and Mark Shannon in [gh-96123](#).)

5 新增模組

- None.

6 改進的模組

6.1 array

- The `array.array` class now supports subscripting, making it a generic type. (Contributed by Jelle Zijlstra in [gh-98658](#).)

6.2 asyncio

- The performance of writing to sockets in `asyncio` has been significantly improved. `asyncio` now avoids unnecessary copying when writing to sockets and uses `sendmsg()` if the platform supports it. (Contributed by Kumar Aditya in [gh-91166](#).)
- Add `asyncio.eager_task_factory()` and `asyncio.create_eager_task_factory()` functions to allow opting an event loop in to eager task execution, making some use-cases 2x to 5x faster. (Contributed by Jacob Bower & Itamar Oren in [gh-102853](#), [gh-104140](#), and [gh-104138](#))
- On Linux, `asyncio` uses `asyncio.PidfdChildWatcher` by default if `os.pidfd_open()` is available and functional instead of `asyncio.ThreadedChildWatcher`. (Contributed by Kumar Aditya in [gh-98024](#).)
- The event loop now uses the best available child watcher for each platform (`asyncio.PidfdChildWatcher` if supported and `asyncio.ThreadedChildWatcher` otherwise), so manually configuring a child watcher is not recommended. (Contributed by Kumar Aditya in [gh-94597](#).)
- Add `loop_factory` parameter to `asyncio.run()` to allow specifying a custom event loop factory. (Contributed by Kumar Aditya in [gh-99388](#).)
- Add C implementation of `asyncio.current_task()` for 4x-6x speedup. (Contributed by Itamar Oren and Pranav Thulasiram Bhat in [gh-100344](#).)
- `asyncio.iscoroutine()` now returns `False` for generators as `asyncio` does not support legacy generator-based coroutines. (Contributed by Kumar Aditya in [gh-102748](#).)
- `asyncio.wait()` and `asyncio.as_completed()` now accepts generators yielding tasks. (Contributed by Kumar Aditya in [gh-78530](#).)

6.3 calendar

- Add enums `calendar.Month` and `calendar.Day` defining months of the year and days of the week. (Contributed by Prince Roshan in [gh-103636](#).)

6.4 csv

- Add `csv.QUOTE_NOTNULL` and `csv.QUOTE_STRINGS` flags to provide finer grained control of `None` and empty strings by `csv.writer` objects.

6.5 dis

- Pseudo instruction opcodes (which are used by the compiler but do not appear in executable bytecode) are now exposed in the `dis` module. `HAVE_ARGUMENT` is still relevant to real opcodes, but it is not useful for pseudo instructions. Use the new `dis.hasarg` collection instead. (Contributed by Irit Katriel in [gh-94216](#).)
- Add the `dis.hasexc` collection to signify instructions that set an exception handler. (Contributed by Irit Katriel in [gh-94216](#).)

6.6 fractions

- Objects of type `fractions.Fraction` now support float-style formatting. (Contributed by Mark Dickinson in [gh-100161](#).)

6.7 importlib.resources

- `importlib.resources.as_file()` now supports resource directories. (Contributed by Jason R. Coombs in [gh-97930](#).)
- Rename first parameter of `importlib.resources.files()` to *anchor*. (Contributed by Jason R. Coombs in [gh-100598](#).)

6.8 inspect

- Add `inspect.markcoroutinefunction()` to mark sync functions that return a coroutine for use with `inspect.iscoroutinefunction()`. (Contributed by Carlton Gibson in [gh-99247](#).)
- Add `inspect.getasynccgenstate()` and `inspect.getasynccgenlocals()` for determining the current state of asynchronous generators. (Contributed by Thomas Krennwallner in [gh-79940](#).)
- The performance of `inspect.getattr_static()` has been considerably improved. Most calls to the function should be at least 2x faster than they were in Python 3.11. (Contributed by Alex Waygood in [gh-103193](#).)

6.9 itertools

- Add `itertools.batched()` for collecting into even-sized tuples where the last batch may be shorter than the rest. (Contributed by Raymond Hettinger in [gh-98363](#).)

6.10 math

- 新增 `math.sumprod()` 以計算乘積總和。(由 Raymond Hettinger 於 [gh-100485](#) 中貢獻。)
- Extend `math.nextafter()` to include a *steps* argument for moving up or down multiple steps at a time. (Contributed by Matthias Goergens, Mark Dickinson, and Raymond Hettinger in [gh-94906](#).)

6.11 os

- Add `os.PIDFD_NONBLOCK` to open a file descriptor for a process with `os.pidfd_open()` in non-blocking mode. (Contributed by Kumar Aditya in [gh-93312](#).)
- `os.DirEntry` now includes an `os.DirEntry.is_junction()` method to check if the entry is a junction. (Contributed by Charles Machalow in [gh-99547](#).)
- Add `os.listdrives()`, `os.listvolumes()` and `os.listmounts()` functions on Windows for enumerating drives, volumes and mount points. (Contributed by Steve Dower in [gh-102519](#).)
- `os.stat()` and `os.lstat()` are now more accurate on Windows. The `st_birthtime` field will now be filled with the creation time of the file, and `st_ctime` is deprecated but still contains the creation time (but in the future will return the last metadata change, for consistency with other platforms). `st_dev` may be up to 64 bits and `st_ino` up to 128 bits depending on your file system, and `st_rdev` is always set to zero rather than incorrect values. Both functions may be significantly faster on newer releases of Windows. (Contributed by Steve Dower in [gh-99726](#).)

- As of 3.12.4, `os.mkdir()` and `os.makedirs()` on Windows now support passing a *mode* value of `0o700` to apply access control to the new directory. This implicitly affects `tempfile.mkdtemp()` and is a mitigation for [CVE-2024-4030](#). Other values for *mode* continue to be ignored. (Contributed by Steve Dower in [gh-118486](#).)

6.12 os.path

- Add `os.path.isjunction()` to check if a given path is a junction. (Contributed by Charles Machalow in [gh-99547](#).)
- Add `os.path.splitroot()` to split a path into a triad (*drive*, *root*, *tail*). (Contributed by Barney Gale in [gh-101000](#).)

6.13 pathlib

- Add support for subclassing `pathlib.PurePath` and `pathlib.Path`, plus their Posix- and Windows-specific variants. Subclasses may override the `pathlib.PurePath.with_segments()` method to pass information between path instances.
- Add `pathlib.Path.walk()` for walking the directory trees and generating all file or directory names within them, similar to `os.walk()`. (Contributed by Stanislav Zmiev in [gh-90385](#).)
- Add *walk_up* optional parameter to `pathlib.PurePath.relative_to()` to allow the insertion of `..` entries in the result; this behavior is more consistent with `os.path.relpath()`. (Contributed by Domenico Ragusa in [gh-84538](#).)
- Add `pathlib.Path.is_junction()` as a proxy to `os.path.isjunction()`. (Contributed by Charles Machalow in [gh-99547](#).)
- Add *case_sensitive* optional parameter to `pathlib.Path.glob()`, `pathlib.Path.rglob()` and `pathlib.PurePath.match()` for matching the path's case sensitivity, allowing for more precise control over the matching process.

6.14 pdb

- Add convenience variables to hold values temporarily for debug session and provide quick access to values like the current frame or the return value. (Contributed by Tian Gao in [gh-103693](#).)

6.15 random

- 新增 `random.binomialvariate()`。(由 Raymond Hettinger 於 [gh-81620](#) 中貢獻。)
- Add a default of `lamdb=1.0` to `random.expovariate()`. (Contributed by Raymond Hettinger in [gh-100234](#).)

6.16 shutil

- `shutil.make_archive()` now passes the *root_dir* argument to custom archivers which support it. In this case it no longer temporarily changes the current working directory of the process to *root_dir* to perform archiving. (Contributed by Serhiy Storchaka in [gh-74696](#).)
- `shutil.rmtree()` now accepts a new argument *onexc* which is an error handler like *onerror* but which expects an exception instance rather than a (*typ*, *val*, *tb*) triplet. *onerror* is deprecated. (Contributed by Irit Katriel in [gh-102828](#).)

- `shutil.which()` now consults the *PATHEXT* environment variable to find matches within *PATH* on Windows even when the given *cmd* includes a directory component. (Contributed by Charles Machalow in [gh-103179](#).)

`shutil.which()` will call `NeedCurrentDirectoryForExePathW` when querying for executables on Windows to determine if the current working directory should be prepended to the search path. (Contributed by Charles Machalow in [gh-103179](#).)

`shutil.which()` will return a path matching the *cmd* with a component from *PATHEXT* prior to a direct match elsewhere in the search path on Windows. (Contributed by Charles Machalow in [gh-103179](#).)

6.17 sqlite3

- 新增命令列介面。(由 Erlend E. Aasland 於 [gh-77617](#) 中貢獻。)
- Add the `sqlite3.Connection.autocommit` attribute to `sqlite3.Connection` and the *autocommit* parameter to `sqlite3.connect()` to control [PEP 249](#)-compliant transaction handling. (Contributed by Erlend E. Aasland in [gh-83638](#).)
- Add *entrypoint* keyword-only parameter to `sqlite3.Connection.load_extension()`, for overriding the SQLite extension entry point. (Contributed by Erlend E. Aasland in [gh-103015](#).)
- Add `sqlite3.Connection.getconfig()` and `sqlite3.Connection.setconfig()` to `sqlite3.Connection` to make configuration changes to a database connection. (Contributed by Erlend E. Aasland in [gh-103489](#).)

6.18 statistics

- Extend `statistics.correlation()` to include as a ranked method for computing the Spearman correlation of ranked data. (Contributed by Raymond Hettinger in [gh-95861](#).)

6.19 sys

- Add the `sys.monitoring` namespace to expose the new [PEP 669](#) monitoring API. (Contributed by Mark Shannon in [gh-103082](#).)
- Add `sys.activate_stack_trampoline()` and `sys.deactivate_stack_trampoline()` for activating and deactivating stack profiler trampolines, and `sys.is_stack_trampoline_active()` for querying if stack profiler trampolines are active. (Contributed by Pablo Galindo and Christian Heimes with contributions from Gregory P. Smith [Google] and Mark Shannon in [gh-96123](#).)
- Add `sys.last_exc` which holds the last unhandled exception that was raised (for post-mortem debugging use cases). Deprecate the three fields that have the same information in its legacy form: `sys.last_type`, `sys.last_value` and `sys.last_traceback`. (Contributed by Irit Katriel in [gh-102778](#).)
- `sys._current_exceptions()` now returns a mapping from thread-id to an exception instance, rather than to a `(typ, exc, tb)` tuple. (Contributed by Irit Katriel in [gh-103176](#).)
- `sys.setrecursionlimit()` and `sys.getrecursionlimit()`. The recursion limit now applies only to Python code. Builtin functions do not use the recursion limit, but are protected by a different mechanism that prevents recursion from causing a virtual machine crash.

6.20 tempfile

- The `tempfile.NamedTemporaryFile` function has a new optional parameter `delete_on_close` (Contributed by Evgeny Zorin in [gh-58451](#).)
- `tempfile.mkdtemp()` now always returns an absolute path, even if the argument provided to the `dir` parameter is a relative path.
- As of 3.12.4 on Windows, the default mode `0o700` used by `tempfile.mkdtemp()` now limits access to the new directory due to changes to `os.mkdir()`. This is a mitigation for [CVE-2024-4030](#). (Contributed by Steve Dower in [gh-118486](#).)

6.21 threading

- Add `threading.settrace_all_threads()` and `threading.setprofile_all_threads()` that allow to set tracing and profiling functions in all running threads in addition to the calling one. (Contributed by Pablo Galindo in [gh-93503](#).)

6.22 tkinter

- `tkinter.Canvas.coords()` now flattens its arguments. It now accepts not only coordinates as separate arguments (`x1, y1, x2, y2, ...`) and a sequence of coordinates (`[x1, y1, x2, y2, ...]`), but also coordinates grouped in pairs (`(x1, y1), (x2, y2), ...` and `[(x1, y1), (x2, y2), ...]`), like `create_*()` methods. (Contributed by Serhiy Storchaka in [gh-94473](#).)

6.23 tokenize

- The `tokenize` module includes the changes introduced in [PEP 701](#). (Contributed by Marta Gómez Macías and Pablo Galindo in [gh-102856](#).) See *Porting to Python 3.12* for more information on the changes to the `tokenize` module.

6.24 types

- Add `types.get_original_bases()` to allow for further introspection of user-defined-generics when subclassed. (Contributed by James Hilton-Balfe and Alex Waygood in [gh-101827](#).)

6.25 typing

- `isinstance()` checks against runtime-checkable protocols now use `inspect.getattr_static()` rather than `hasattr()` to lookup whether attributes exist. This means that descriptors and `__getattr__()` methods are no longer unexpectedly evaluated during `isinstance()` checks against runtime-checkable protocols. However, it may also mean that some objects which used to be considered instances of a runtime-checkable protocol may no longer be considered instances of that protocol on Python 3.12+, and vice versa. Most users are unlikely to be affected by this change. (Contributed by Alex Waygood in [gh-102433](#).)
- The members of a runtime-checkable protocol are now considered "frozen" at runtime as soon as the class has been created. Monkey-patching attributes onto a runtime-checkable protocol will still work, but will have no impact on `isinstance()` checks comparing objects to the protocol. For example:

```
>>> from typing import Protocol, runtime_checkable
>>> @runtime_checkable
... class HasX(Protocol):
...     x = 1
... 
```

(繼續下一頁)

(繼續上一頁)

```
>>> class Foo: ...
...
>>> f = Foo()
>>> isinstance(f, HasX)
False
>>> f.x = 1
>>> isinstance(f, HasX)
True
>>> HasX.y = 2
>>> isinstance(f, HasX) # unchanged, even though HasX now also has a "y"
↳ attribute
True
```

This change was made in order to speed up `isinstance()` checks against runtime-checkable protocols.

- The performance profile of `isinstance()` checks against runtime-checkable protocols has changed significantly. Most `isinstance()` checks against protocols with only a few members should be at least 2x faster than in 3.11, and some may be 20x faster or more. However, `isinstance()` checks against protocols with many members may be slower than in Python 3.11. (Contributed by Alex Waygood in [gh-74690](#) and [gh-103193](#).)
- All `typing.TypedDict` and `typing.NamedTuple` classes now have the `__orig_bases__` attribute. (Contributed by Adrian Garcia Badaracco in [gh-103699](#).)
- Add `frozen_default` parameter to `typing.dataclass_transform()`. (Contributed by Erik De Bonte in [gh-99957](#).)

6.26 unicodedata

- The Unicode database has been updated to version 15.0.0. (Contributed by Benjamin Peterson in [gh-96734](#).)

6.27 unittest

新增 `--durations` 命令列選項，顯示 N 個最慢的測試案例：

```
python3 -m unittest --durations=3 lib.tests.test_threading
.....
Slowest test durations
-----
1.210s      test_timeout (Lib.test.test_threading.BarrierTests)
1.003s      test_default_timeout (Lib.test.test_threading.BarrierTests)
0.518s      test_timeout (Lib.test.test_threading.EventTests)

(0.000 durations hidden.  Use -v to show these durations.)
-----
Ran 158 tests in 9.869s

OK (skipped=3)
```

(由 Giampaolo Rodola 於 [gh-48330](#) 中貢獻。)

6.28 uuid

- Add a command-line interface. (Contributed by Adam Chhina in [gh-88597](#).)

7 最佳化

- Remove `wstr` and `wstr_length` members from Unicode objects. It reduces object size by 8 or 16 bytes on 64bit platform. (**PEP 623**) (Contributed by Inada Naoki in [gh-92536](#).)
- Add experimental support for using the BOLT binary optimizer in the build process, which improves performance by 1-5%. (Contributed by Kevin Modzelewski in [gh-90536](#) and tuned by Donghee Na in [gh-101525](#))
- Speed up the regular expression substitution (functions `re.sub()` and `re.subn()` and corresponding `re.Pattern` methods) for replacement strings containing group references by 2--3 times. (Contributed by Serhiy Storchaka in [gh-91524](#).)
- Speed up `asyncio.Task` creation by deferring expensive string formatting. (Contributed by Itamar Oren in [gh-103793](#).)
- The `tokenize.tokenize()` and `tokenize.generate_tokens()` functions are up to 64% faster as a side effect of the changes required to cover **PEP 701** in the `tokenize` module. (Contributed by Marta Gómez Macías and Pablo Galindo in [gh-102856](#).)
- Speed up `super()` method calls and attribute loads via the new `LOAD_SUPER_ATTR` instruction. (Contributed by Carl Meyer and Vladimir Matveev in [gh-103497](#).)

8 CPython 位元組碼變更

- Remove the `LOAD_METHOD` instruction. It has been merged into `LOAD_ATTR`. `LOAD_ATTR` will now behave like the old `LOAD_METHOD` instruction if the low bit of its `oparg` is set. (Contributed by Ken Jin in [gh-93429](#).)
- Remove the `JUMP_IF_FALSE_OR_POP` and `JUMP_IF_TRUE_OR_POP` instructions. (Contributed by Irit Katriel in [gh-102859](#).)
- Remove the `PRECALL` instruction. (Contributed by Mark Shannon in [gh-92925](#).)
- Add the `BINARY_SLICE` and `STORE_SLICE` instructions. (Contributed by Mark Shannon in [gh-94163](#).)
- Add the `CALL_INTRINSIC_1` instructions. (Contributed by Mark Shannon in [gh-99005](#).)
- Add the `CALL_INTRINSIC_2` instruction. (Contributed by Irit Katriel in [gh-101799](#).)
- Add the `CLEANUP_THROW` instruction. (Contributed by Brandt Bucher in [gh-90997](#).)
- Add the `END_SEND` instruction. (Contributed by Mark Shannon in [gh-103082](#).)
- Add the `LOAD_FAST_AND_CLEAR` instruction as part of the implementation of **PEP 709**. (Contributed by Carl Meyer in [gh-101441](#).)
- Add the `LOAD_FAST_CHECK` instruction. (Contributed by Dennis Sweeney in [gh-93143](#).)
- Add the `LOAD_FROM_DICT_OR_DEREF`, `LOAD_FROM_DICT_OR_GLOBALS`, and `LOAD_LOCALS` opcodes as part of the implementation of **PEP 695**. Remove the `LOAD_CLASSDEREF` opcode, which can be replaced with `LOAD_LOCALS` plus `LOAD_FROM_DICT_OR_DEREF`. (Contributed by Jelle Zijlstra in [gh-103764](#).)
- Add the `LOAD_SUPER_ATTR` instruction. (Contributed by Carl Meyer and Vladimir Matveev in [gh-103497](#).)
- Add the `RETURN_CONST` instruction. (Contributed by Wenyang Wang in [gh-101632](#).)

9 Demos and Tools

- Remove the `Tools/demo/` directory which contained old demo scripts. A copy can be found in the [old-demos project](#). (Contributed by Victor Stinner in [gh-97681](#).)
- Remove outdated example scripts of the `Tools/scripts/` directory. A copy can be found in the [old-demos project](#). (Contributed by Victor Stinner in [gh-97669](#).)

10 已弃用

- `argparse`: The *type*, *choices*, and *metavar* parameters of `argparse.BooleanOptionalAction` are deprecated and will be removed in 3.14. (Contributed by Nikita Sobolev in [gh-92248](#).)
- `ast`: The following `ast` features have been deprecated in documentation since Python 3.8, now cause a `DeprecationWarning` to be emitted at runtime when they are accessed or used, and will be removed in Python 3.14:

- `ast.Num`
- `ast.Str`
- `ast.Bytes`
- `ast.NameConstant`
- `ast.Ellipsis`

Use `ast.Constant` instead. (Contributed by Serhiy Storchaka in [gh-90953](#).)

- `asyncio`:
 - The `child watcher` classes `asyncio.MultiLoopChildWatcher`, `asyncio.FastChildWatcher`, `asyncio.AbstractChildWatcher` and `asyncio.SafeChildWatcher` are deprecated and will be removed in Python 3.14. (Contributed by Kumar Aditya in [gh-94597](#).)
 - `asyncio.set_child_watcher()`, `asyncio.get_child_watcher()`, `asyncio.AbstractEventLoopPolicy.set_child_watcher()` and `asyncio.AbstractEventLoopPolicy.get_child_watcher()` are deprecated and will be removed in Python 3.14. (Contributed by Kumar Aditya in [gh-94597](#).)
 - The `get_event_loop()` method of the default event loop policy now emits a `DeprecationWarning` if there is no current event loop set and it decides to create one. (Contributed by Serhiy Storchaka and Guido van Rossum in [gh-100160](#).)
- `calendar`: `calendar.January` and `calendar.February` constants are deprecated and replaced by `calendar.JANUARY` and `calendar.FEBRUARY`. (Contributed by Prince Roshan in [gh-103636](#).)
- `collections.abc`: Deprecate `collections.abc.ByteString`. Prefer `Sequence` or `collections.abc.Buffer`. For use in typing, prefer a union, like `bytes | bytearray`, or `collections.abc.Buffer`. (Contributed by Shantanu Jain in [gh-91896](#).)
- `datetime`: `datetime.datetime.utcnow()` and `datetime.datetime.fromtimestamp()` are deprecated and will be removed in a future version. Instead, use timezone-aware objects to represent datetimes in UTC: respectively, call `now()` and `fromtimestamp()` with the `tz` parameter set to `datetime.UTC`. (Contributed by Paul Ganssle in [gh-103857](#).)
- `email`: 弃用 `email.utils.localtime()` 中的 `isdst` 参数。(由 Alan Williams 於 [gh-72346](#) 中貢獻。)
- `importlib.abc`: 弃用下列類別，預定於 Python 3.14 中移除：
 - `importlib.abc.ResourceReader`
 - `importlib.abc.Traversable`

- `importlib.abc.TraversableResources`

請改用 `importlib.resources.abc` 類：

- `importlib.resources.abc.Traversable`
- `importlib.resources.abc.TraversableResources`

(由 Jason R. Coombs 和 Hugo van Kemenade 於 [gh-93963](#) 中貢獻。)

- **itertools:** Deprecate the support for `copy`, `deepcopy`, and `pickle` operations, which is undocumented, inefficient, historically buggy, and inconsistent. This will be removed in 3.14 for a significant reduction in code volume and maintenance burden. (Contributed by Raymond Hettinger in [gh-101588](#).)
- **multiprocessing:** In Python 3.14, the default `multiprocessing` start method will change to a safer one on Linux, BSDs, and other non-macOS POSIX platforms where `'fork'` is currently the default ([gh-84559](#)). Adding a runtime warning about this was deemed too disruptive as the majority of code is not expected to care. Use the `get_context()` or `set_start_method()` APIs to explicitly specify when your code *requires* `'fork'`. See contexts and start methods.
- **pkgutil:** `pkgutil.find_loader()` and `pkgutil.get_loader()` are deprecated and will be removed in Python 3.14; use `importlib.util.find_spec()` instead. (Contributed by Nikita Sobolev in [gh-97850](#).)
- **pty:** The module has two undocumented `master_open()` and `slave_open()` functions that have been deprecated since Python 2 but only gained a proper `DeprecationWarning` in 3.12. Remove them in 3.14. (Contributed by Soumendra Ganguly and Gregory P. Smith in [gh-85984](#).)
- **os:**
 - The `st_ctime` fields return by `os.stat()` and `os.lstat()` on Windows are deprecated. In a future release, they will contain the last metadata change time, consistent with other platforms. For now, they still contain the creation time, which is also available in the new `st_birthtime` field. (Contributed by Steve Dower in [gh-99726](#).)
 - On POSIX platforms, `os.fork()` can now raise a `DeprecationWarning` when it can detect being called from a multithreaded process. There has always been a fundamental incompatibility with the POSIX platform when doing so. Even if such code *appeared* to work. We added the warning to raise awareness as issues encountered by code doing this are becoming more frequent. See the `os.fork()` documentation for more details along with [this discussion on fork being incompatible with threads](#) for *why* we're now surfacing this longstanding platform compatibility problem to developers.

When this warning appears due to usage of `multiprocessing` or `concurrent.futures` the fix is to use a different `multiprocessing` start method such as `"spawn"` or `"forkserver"`.

- **shutil:** `shutil.rmtree()` 的 `onerror` 引數已被廢用，請改用 `onexc`。(由 Irit Katriel 於 [gh-102828](#) 中貢獻。)
- **sqlite3:**
 - default adapters and converters are now deprecated. Instead, use the `sqlite3-adaptor-converter-recipes` and tailor them to your needs. (Contributed by Erlend E. Aasland in [gh-90016](#).)
 - In `execute()`, `DeprecationWarning` is now emitted when named placeholders are used together with parameters supplied as a sequence instead of as a `dict`. Starting from Python 3.14, using named placeholders with parameters supplied as a sequence will raise a `ProgrammingError`. (Contributed by Erlend E. Aasland in [gh-101698](#).)
- **sys:** The `sys.last_type`, `sys.last_value` and `sys.last_traceback` fields are deprecated. Use `sys.last_exc` instead. (Contributed by Irit Katriel in [gh-102778](#).)
- **tarfile:** Extracting tar archives without specifying `filter` is deprecated until Python 3.14, when `'data'` filter will become the default. See `tarfile-extraction-filter` for details.
- **typing:**
 - `typing.Hashable` and `typing.Sized`, aliases for `collections.abc.Hashable` and `collections.abc.Sized` respectively, are deprecated. ([gh-94309](#).)

- `typing.ByteString`, deprecated since Python 3.9, now causes a `DeprecationWarning` to be emitted when it is used. (Contributed by Alex Waygood in [gh-91896](#).)
- `xml.etree.ElementTree`: The module now emits `DeprecationWarning` when testing the truth value of an `xml.etree.ElementTree.Element`. Before, the Python implementation emitted `FutureWarning`, and the C implementation emitted nothing. (Contributed by Jacob Walls in [gh-83122](#).)
- The 3-arg signatures (`type`, `value`, `traceback`) of `coroutine.throw()`, `generator.throw()` and `async generator.throw()` are deprecated and may be removed in a future version of Python. Use the single-arg versions of these functions instead. (Contributed by Ofey Chan in [gh-89874](#).)
- `DeprecationWarning` is now raised when `__package__` on a module differs from `__spec__.parent` (previously it was `ImportWarning`). (Contributed by Brett Cannon in [gh-65961](#).)
- Setting `__package__` or `__cached__` on a module is deprecated, and will cease to be set or taken into consideration by the import system in Python 3.14. (Contributed by Brett Cannon in [gh-65961](#).)
- The bitwise inversion operator (`~`) on `bool` is deprecated. It will throw an error in Python 3.14. Use `not` for logical negation of bools instead. In the rare case that you really need the bitwise inversion of the underlying `int`, convert to `int` explicitly: `~int(x)`. (Contributed by Tim Hoffmann in [gh-103487](#).)
- Accessing `co_notab` on code objects was deprecated in Python 3.10 via [PEP 626](#), but it only got a proper `DeprecationWarning` in 3.12, therefore it will be removed in 3.14. (Contributed by Nikita Sobolev in [gh-101866](#).)

10.1 Python 3.13 中待📦議的移除項目

Modules (see [PEP 594](#)):

- `aifc`
- `audioop`
- `cgi`
- `cgitb`
- `chunk`
- `crypt`
- `imghdr`
- `mailcap`
- `msilib`
- `nis`
- `nntplib`
- `ossaudiodev`
- `pipes`
- `sndhdr`
- `spwd`
- `sunau`
- `telnetlib`
- `uu`
- `xdrlib`

其他模組：

- `lib2to3` 以及 `2to3` 程式 ([gh-84540](#))

API:

- `configparser.LegacyInterpolation` ([gh-90765](#))
- `locale.resetlocale()` ([gh-90817](#))
- `turtle.RawTurtle.settiltangle()` ([gh-50096](#))
- `unittest.findTestCases()` ([gh-50096](#))
- `unittest.getTestCaseNames()` ([gh-50096](#))
- `unittest.makeSuite()` ([gh-50096](#))
- `unittest.TestProgram.usageExit()` ([gh-67048](#))
- `webbrowser.MacOSX` ([gh-86421](#))
- `classmethod` 描述器鏈結 ([gh-89519](#))
- `importlib.resources` 中被`🔍`用的方法:
 - `contents()`
 - `is_resource()`
 - `open_binary()`
 - `open_text()`
 - `path()`
 - `read_binary()`
 - `read_text()`

Use `importlib.resources.files()` instead. Refer to [importlib-resources: Migrating from Legacy](#) ([gh-106531](#))

10.2 Python 3.14 中待`🔍`議的移除項目

- `argparse`: The *type*, *choices*, and *metavar* parameters of `argparse.BooleanOptionalAction` are deprecated and will be removed in 3.14. (Contributed by Nikita Sobolev in [gh-92248](#).)
- `ast`: The following features have been deprecated in documentation since Python 3.8, now cause a `DeprecationWarning` to be emitted at runtime when they are accessed or used, and will be removed in Python 3.14:
 - `ast.Num`
 - `ast.Str`
 - `ast.Bytes`
 - `ast.NameConstant`
 - `ast.Ellipsis`

Use `ast.Constant` instead. (Contributed by Serhiy Storchaka in [gh-90953](#).)

- `asyncio`:
 - The `child watcher` classes `MultiLoopChildWatcher`, `FastChildWatcher`, `AbstractChildWatcher` and `SafeChildWatcher` are deprecated and will be removed in Python 3.14. (Contributed by Kumar Aditya in [gh-94597](#).)
 - `asyncio.set_child_watcher()`, `asyncio.get_child_watcher()`, `asyncio.AbstractEventLoopPolicy.set_child_watcher()` and `asyncio.AbstractEventLoopPolicy.get_child_watcher()` are deprecated and will be removed in Python 3.14. (Contributed by Kumar Aditya in [gh-94597](#).)

- The `get_event_loop()` method of the default event loop policy now emits a `DeprecationWarning` if there is no current event loop set and it decides to create one. (Contributed by Serhiy Storchaka and Guido van Rossum in [gh-100160](#).)
- `collections.abc`: **Deprecated** `ByteString`. Prefer `Sequence` or `Buffer`. For use in typing, prefer a union, like `bytes | bytearray`, or `collections.abc.Buffer`. (Contributed by Shantanu Jain in [gh-91896](#).)
- `email`: **Deprecated** the `isdst` parameter in `email.utils.localtime()`. (Contributed by Alan Williams in [gh-72346](#).)
- `importlib`: `__package__` and `__cached__` will cease to be set or taken into consideration by the import system ([gh-97879](#)).
- `importlib.abc` deprecated classes:
 - `importlib.abc.ResourceReader`
 - `importlib.abc.Traversable`
 - `importlib.abc.TraversableResources`
 請改用 `importlib.resources.abc` 類☐:
 - `importlib.resources.abc.Traversable`
 - `importlib.resources.abc.TraversableResources`
 (由 Jason R. Coombs 和 Hugo van Kemenade 於 [gh-93963](#) 中貢獻。)
- `itertools` had undocumented, inefficient, historically buggy, and inconsistent support for `copy`, `deepcopy`, and `pickle` operations. This will be removed in 3.14 for a significant reduction in code volume and maintenance burden. (Contributed by Raymond Hettinger in [gh-101588](#).)
- `multiprocessing`: The default start method will change to a safer one on Linux, BSDs, and other non-macOS POSIX platforms where `'fork'` is currently the default ([gh-84559](#)). Adding a runtime warning about this was deemed too disruptive as the majority of code is not expected to care. Use the `get_context()` or `set_start_method()` APIs to explicitly specify when your code *requires* `'fork'`. See `multiprocessing-start-methods`.
- `pathlib`: `is_relative_to()` and `relative_to()`: passing additional arguments is deprecated.
- `pkgutil`: `find_loader()` and `get_loader()` now raise `DeprecationWarning`; use `importlib.util.find_spec()` instead. (Contributed by Nikita Sobolev in [gh-97850](#).)
- `pty`:
 - `master_open()`: use `pty.openpty()`.
 - `slave_open()`: use `pty.openpty()`.
- `sqlite3`:
 - `version` and `version_info`.
 - `execute()` and `executemany()` if named placeholders are used and *parameters* is a sequence instead of a dict.
 - date and datetime adapter, date and timestamp converter: see the `sqlite3` documentation for suggested replacement recipes.
- `types.CodeType`: Accessing `co_lnotab` was deprecated in **PEP 626** since 3.10 and was planned to be removed in 3.12, but it only got a proper `DeprecationWarning` in 3.12. May be removed in 3.14. (Contributed by Nikita Sobolev in [gh-101866](#).)
- `typing`: `ByteString`, deprecated since Python 3.9, now causes a `DeprecationWarning` to be emitted when it is used.
- `urllib`: `urllib.parse.Quoter` is deprecated: it was not intended to be a public API. (Contributed by Gregory P. Smith in [gh-88168](#).)

10.3 Python 3.15 中待^F議的移除項目

- `http.server.CGIHTTPRequestHandler` will be removed along with its related `--cgi` flag to `python -m http.server`. It was obsolete and rarely used. No direct replacement exists. *Anything* is better than CGI to interface a web server with a request handler.
- `locale`: `locale.getdefaultlocale()` was deprecated in Python 3.11 and originally planned for removal in Python 3.13 ([gh-90817](#)), but removal has been postponed to Python 3.15. Use `locale.setlocale()`, `locale.getencoding()` and `locale.getlocale()` instead. (Contributed by Hugo van Kemenade in [gh-111187](#).)
- `pathlib`: `pathlib.PurePath.is_reserved()` is deprecated and scheduled for removal in Python 3.15. From Python 3.13 onwards, use `os.path.isreserved` to detect reserved paths on Windows.
- `platform`: `java_ver()` is deprecated and will be removed in 3.15. It was largely untested, had a confusing API, and was only useful for Jython support. (Contributed by Nikita Sobolev in [gh-116349](#).)
- `threading`: Passing any arguments to `threading.RLock()` is now deprecated. C version allows any numbers of args and kwargs, but they are just ignored. Python version does not allow any arguments. All arguments will be removed from `threading.RLock()` in Python 3.15. (Contributed by Nikita Sobolev in [gh-102029](#).)
- `typing.NamedTuple`:
 - The undocumented keyword argument syntax for creating `NamedTuple` classes (`NT = NamedTuple("NT", x=int)`) is deprecated, and will be disallowed in 3.15. Use the class-based syntax or the functional syntax instead.
 - When using the functional syntax to create a `NamedTuple` class, failing to pass a value to the *fields* parameter (`NT = NamedTuple("NT")`) is deprecated. Passing `None` to the *fields* parameter (`NT = NamedTuple("NT", None)`) is also deprecated. Both will be disallowed in Python 3.15. To create a `NamedTuple` class with 0 fields, use `class NT(NamedTuple): pass` or `NT = NamedTuple("NT", [])`.
- `typing.TypedDict`: When using the functional syntax to create a `TypedDict` class, failing to pass a value to the *fields* parameter (`TD = TypedDict("TD")`) is deprecated. Passing `None` to the *fields* parameter (`TD = TypedDict("TD", None)`) is also deprecated. Both will be disallowed in Python 3.15. To create a `TypedDict` class with 0 fields, use `class TD(TypedDict): pass` or `TD = TypedDict("TD", {})`.
- `wave`: Deprecate the `getmark()`, `setmark()` and `getmarkers()` methods of the `wave.Wave_read` and `wave.Wave_write` classes. They will be removed in Python 3.15. (Contributed by Victor Stinner in [gh-105096](#).)

10.4 Pending Removal in Python 3.16

- `array`: `array.array 'u' type (wchar_t)`: use the `'w'` type instead (Py_UCS4).
- `symtable`: Deprecate `symtable.Class.get_methods()` due to the lack of interest. (Contributed by Bénédict Tran in [gh-119698](#).)

10.5 未來版本中待討論的移除項目

The following APIs will be removed in the future, although there is currently no date scheduled for their removal.

- `argparse`: Nesting argument groups and nesting mutually exclusive groups are deprecated.
- `array`'s `'u'` format code ([gh-57281](#))
- builtins:
 - `~bool`, bitwise inversion on `bool`.
 - `bool(NotImplemented)`.
 - Generators: `throw(type, exc, tb)` and `athrow(type, exc, tb)` signature is deprecated: use `throw(exc)` and `athrow(exc)` instead, the single argument signature.
 - Currently Python accepts numeric literals immediately followed by keywords, for example `0 in x, 1 or x, 0 if 1 else 2`. It allows confusing and ambiguous expressions like `[0x1 for x in y]` (which can be interpreted as `[0x1 for x in y]` or `[0x1 if or x in y]`). A syntax warning is raised if the numeric literal is immediately followed by one of keywords `and`, `else`, `for`, `if`, `in`, `is` and `or`. In a future release it will be changed to a syntax error. ([gh-87999](#))
 - Support for `__index__()` and `__int__()` method returning non-int type: these methods will be required to return an instance of a strict subclass of `int`.
 - Support for `__float__()` method returning a strict subclass of `float`: these methods will be required to return an instance of `float`.
 - Support for `__complex__()` method returning a strict subclass of `complex`: these methods will be required to return an instance of `complex`.
 - Delegation of `int()` to `__trunc__()` method.
 - Passing a complex number as the *real* or *imag* argument in the `complex()` constructor is now deprecated; it should only be passed as a single positional argument. (Contributed by Serhiy Storchaka in [gh-109218](#).)
- `calendar`: `calendar.January` and `calendar.February` constants are deprecated and replaced by `calendar.JANUARY` and `calendar.FEBRUARY`. (Contributed by Prince Roshan in [gh-103636](#).)
- `codeobject.co_notab`: use the `codeobject.co_lines()` method instead.
- `datetime`:
 - `utcnow()`: use `datetime.datetime.now(tz=datetime.UTC)`.
 - `utcfromtimestamp()`: use `datetime.datetime.fromtimestamp(timestamp, tz=datetime.UTC)`.
- `gettext`: Plural value must be an integer.
- `importlib`:
 - `load_module()` method: use `exec_module()` instead.
 - `cache_from_source()` *debug_override* parameter is deprecated: use the *optimization* parameter instead.
- `importlib.metadata`:
 - `EntryPoints` tuple interface.

- Implicit None on return values.
- mailbox: Use of StringIO input and text mode is deprecated, use BytesIO and binary mode instead.
- os: Calling `os.register_at_fork()` in multi-threaded process.
- `pydoc.ErrorDuringImport`: A tuple value for `exc_info` parameter is deprecated, use an exception instance.
- re: More strict rules are now applied for numerical group references and group names in regular expressions. Only sequence of ASCII digits is now accepted as a numerical reference. The group name in bytes patterns and replacement strings can now only contain ASCII letters and digits and underscore. (Contributed by Serhiy Storchaka in [gh-91760](#).)
- `sre_compile`, `sre_constants` and `sre_parse` modules.
- `shutil.rmtree()`'s `onerror` parameter is deprecated in Python 3.12; use the `onexc` parameter instead.
- ssl options and protocols:
 - `ssl.SSLContext` without protocol argument is deprecated.
 - `ssl.SSLContext`: `set_npn_protocols()` and `selected_npn_protocol()` are deprecated: use ALPN instead.
 - `ssl.OP_NO_SSL*` options
 - `ssl.OP_NO_TLS*` options
 - `ssl.PROTOCOL_SSLv3`
 - `ssl.PROTOCOL_TLS`
 - `ssl.PROTOCOL_TLSv1`
 - `ssl.PROTOCOL_TLSv1_1`
 - `ssl.PROTOCOL_TLSv1_2`
 - `ssl.TLSVersion.SSLv3`
 - `ssl.TLSVersion.TLSv1`
 - `ssl.TLSVersion.TLSv1_1`
- `sysconfig.is_python_build()` `check_home` parameter is deprecated and ignored.
- threading methods:
 - `threading.Condition.notifyAll()`: use `notify_all()`.
 - `threading.Event.isSet()`: use `is_set()`.
 - `threading.Thread.isDaemon()`, `threading.Thread.setDaemon()`: use `threading.Thread.daemon` attribute.
 - `threading.Thread.getName()`, `threading.Thread.setName()`: use `threading.Thread.name` attribute.
 - `threading.currentThread()`: use `threading.current_thread()`.
 - `threading.activeCount()`: use `threading.active_count()`.
- `typing.Text` ([gh-92332](#)).
- `unittest.IsolatedAsyncioTestCase`: it is deprecated to return a value that is not None from a test case.
- `urllib.parse` deprecated functions: `urlparse()` instead
 - `splitattr()`
 - `splithost()`
 - `splitnport()`

- `splitpasswd()`
- `splitport()`
- `splitquery()`
- `splittag()`
- `splitttype()`
- `splituser()`
- `splitvalue()`
- `to_bytes()`
- `urllib.request`: `URLopener` and `FancyURLopener` style of invoking requests is deprecated. Use newer `urlopen()` functions and methods.
- `wsgiref`: `SimpleHandler.stdout.write()` should not do partial writes.
- `xml.etree.ElementTree`: Testing the truth value of an `Element` is deprecated. In a future release it will always return `True`. Prefer explicit `len(elem)` or `elem is not None` tests instead.
- `zipimport.zipimporter.load_module()` is deprecated: use `exec_module()` instead.

11 已移除

11.1 `asynchat` 和 `asyncore`

- These two modules have been removed according to the schedule in [PEP 594](#), having been deprecated in Python 3.6. Use `asyncio` instead. (Contributed by Nikita Sobolev in [gh-96580](#).)

11.2 `configparser`

- Several names deprecated in the `configparser` way back in 3.2 have been removed per [gh-89336](#):
 - `configparser.ParsingError` no longer has a `filename` attribute or argument. Use the `source` attribute and argument instead.
 - `configparser` no longer has a `SafeConfigParser` class. Use the shorter `ConfigParser` name instead.
 - `configparser.ConfigParser` no longer has a `readfp` method. Use `read_file()` instead.

11.3 `distutils`

- Remove the `distutils` package. It was deprecated in Python 3.10 by [PEP 632](#) "Deprecate `distutils` module". For projects still using `distutils` and cannot be updated to something else, the `setuptools` project can be installed: it still provides `distutils`. (Contributed by Victor Stinner in [gh-92584](#).)

11.4 ensurepip

- Remove the bundled setuptools wheel from ensurepip, and stop installing setuptools in environments created by venv.

pip (>= 22.1) does not require setuptools to be installed in the environment. setuptools-based (and distutils-based) packages can still be used with pip install, since pip will provide setuptools in the build environment it uses for building a package.

easy_install, pkg_resources, setuptools and distutils are no longer provided by default in environments created with venv or bootstrapped with ensurepip, since they are part of the setuptools package. For projects relying on these at runtime, the setuptools project should be declared as a dependency and installed separately (typically, using pip).

(由 Pradyun Gedam 於 [gh-95299](#) 中貢獻。)

11.5 enum

- Remove enum's EnumMeta.__getattr__, which is no longer needed for enum attribute access. (Contributed by Ethan Furman in [gh-95083](#).)

11.6 ftplib

- 移除 ftplib 的 FTP_TLS.ssl_version 類別屬性: 請改用 context 參數。(由 Victor Stinner 於 [gh-94172](#) 中貢獻。)

11.7 gzip

- Remove the filename attribute of gzip's gzip.GzipFile, deprecated since Python 2.6, use the name attribute instead. In write mode, the filename attribute added '.gz' file extension if it was not present. (Contributed by Victor Stinner in [gh-94196](#).)

11.8 hashlib

- Remove the pure Python implementation of hashlib's hashlib.pbkdf2_hmac(), deprecated in Python 3.10. Python 3.10 and newer requires OpenSSL 1.1.1 ([PEP 644](#)): this OpenSSL version provides a C implementation of pbkdf2_hmac() which is faster. (Contributed by Victor Stinner in [gh-94199](#).)

11.9 importlib

- Many previously deprecated cleanups in importlib have now been completed:
 - References to, and support for module_repr() has been removed. (Contributed by Barry Warsaw in [gh-97850](#).)
 - importlib.util.set_package, importlib.util.set_loader and importlib.util.module_for_loader have all been removed. (Contributed by Brett Cannon and Nikita Sobolev in [gh-65961](#) and [gh-97850](#).)
 - Support for find_loader() and find_module() APIs have been removed. (Contributed by Barry Warsaw in [gh-98040](#).)
 - importlib.abc.Finder, pkgutil.ImpImporter, and pkgutil.ImpLoader have been removed. (Contributed by Barry Warsaw in [gh-98040](#).)

11.10 imp

- The `imp` module has been removed. (Contributed by Barry Warsaw in [gh-98040](#).)

To migrate, consult the following correspondence table:

imp	importlib
<code>imp.NullImporter</code>	將 None 插入 <code>sys.path_importer_cache</code>
<code>imp.cache_from_source()</code>	<code>importlib.util.cache_from_source()</code>
<code>imp.find_module()</code>	<code>importlib.util.find_spec()</code>
<code>imp.get_magic()</code>	<code>importlib.util.MAGIC_NUMBER</code>
<code>imp.get_suffixe</code>	<code>importlib.machinery.SOURCE_SUFFIXES,</code> <code>machinery.EXTENSION_SUFFIXES,</code> and <code>importlib.</code> <code>machinery.BYTECODE_SUFFIXES</code>
<code>imp.get_tag()</code>	<code>sys.implementation.cache_tag</code>
<code>imp.load_module()</code>	<code>importlib.import_module()</code>
<code>imp.new_module()</code>	<code>types.ModuleType(name)</code>
<code>imp.reload()</code>	<code>importlib.reload()</code>
<code>imp.source_from</code>	<code>importlib.util.source_from_cache()</code>
<code>imp.load_source</code>	見下文

用以下取代 `imp.load_source()` :

```
import importlib.util
import importlib.machinery

def load_source(modname, filename):
    loader = importlib.machinery.SourceFileLoader(modname, filename)
    spec = importlib.util.spec_from_file_location(modname, filename,
    ↪ loader=loader)
    module = importlib.util.module_from_spec(spec)
    # The module is always executed and not cached in sys.modules.
    # Uncomment the following line to cache the module.
    # sys.modules[module.__name__] = module
    loader.exec_module(module)
    return module
```

- 移除 `imp` 函式和屬性、[☞](#)有替代方案：
 - 未以文件記`☞`的函式：
 - `* imp.init_builtin()`
 - `* imp.load_compiled()`
 - `* imp.load_dynamic()`
 - `* imp.load_package()`
 - `imp.lock_held()`, `imp.acquire_lock()`, `imp.release_lock()`: the locking scheme has changed in Python 3.3 to per-module locks.

- `imp.find_module()` 常數: `SEARCH_ERROR`, `PY_SOURCE`, `PY_COMPILED`, `C_EXTENSION`, `PY_RESOURCE`, `PKG_DIRECTORY`, `C_BUILTIN`, `PY_FROZEN`, `PY_CODERESOURCE`, `IMP_HOOK`.

11.11 io

- Remove `io`'s `io.OpenWrapper` and `_pyio.OpenWrapper`, deprecated in Python 3.10: just use `open()` instead. The `open()` (`io.open()`) function is a built-in function. Since Python 3.10, `_pyio.open()` is also a static method. (Contributed by Victor Stinner in [gh-94169](#).)

11.12 locale

- Remove `locale`'s `locale.format()` function, deprecated in Python 3.7: use `locale.format_string()` instead. (Contributed by Victor Stinner in [gh-94226](#).)

11.13 smtpd

- The `smtpd` module has been removed according to the schedule in [PEP 594](#), having been deprecated in Python 3.4.7 and 3.5.4. Use the `aiosmtpd` PyPI module or any other `asyncio`-based server instead. (Contributed by Oleg Iarygin in [gh-93243](#).)

11.14 sqlite3

- The following undocumented `sqlite3` features, deprecated in Python 3.10, are now removed:

- `sqlite3.enable_shared_cache()`
- `sqlite3.OptimizedUnicode`

If a shared cache must be used, open the database in URI mode using the `cache=shared` query parameter.

The `sqlite3.OptimizedUnicode` text factory has been an alias for `str` since Python 3.3. Code that previously set the text factory to `OptimizedUnicode` can either use `str` explicitly, or rely on the default value which is also `str`.

(由 Erlend E. Aasland 於 [gh-92548](#) 中貢獻。)

11.15 ssl

- Remove `ssl`'s `ssl.RAND_pseudo_bytes()` function, deprecated in Python 3.6: use `os.urandom()` or `ssl.RAND_bytes()` instead. (Contributed by Victor Stinner in [gh-94199](#).)
- Remove the `ssl.match_hostname()` function. It was deprecated in Python 3.7. OpenSSL performs hostname matching since Python 3.7, Python no longer uses the `ssl.match_hostname()` function. (Contributed by Victor Stinner in [gh-94199](#).)
- Remove the `ssl.wrap_socket()` function, deprecated in Python 3.7: instead, create a `ssl.SSLContext` object and call its `ssl.SSLContext.wrap_socket` method. Any package that still uses `ssl.wrap_socket()` is broken and insecure. The function neither sends a SNI TLS extension nor validates the server hostname. Code is subject to [CWE-295](#) (Improper Certificate Validation). (Contributed by Victor Stinner in [gh-94199](#).)

11.16 unittest

- 移除許多 `unittest` 中被使用已久的功能：
 - A number of `TestCase` method aliases:

已使用的名	方法名	Deprecated in
<code>failUnless</code>	<code>assertTrue()</code>	3.1
<code>failIf</code>	<code>assertFalse()</code>	3.1
<code>failUnlessEqual</code>	<code>assertEqual()</code>	3.1
<code>failIfEqual</code>	<code>assertNotEqual()</code>	3.1
<code>failUnlessAlmostEqual</code>	<code>assertAlmostEqual()</code>	3.1
<code>failIfAlmostEqual</code>	<code>assertNotAlmostEqual()</code>	3.1
<code>failUnlessRaises</code>	<code>assertRaises()</code>	3.1
<code>assert_</code>	<code>assertTrue()</code>	3.2
<code>assertEquals</code>	<code>assertEqual()</code>	3.2
<code>assertNotEquals</code>	<code>assertNotEqual()</code>	3.2
<code>assertAlmostEquals</code>	<code>assertAlmostEqual()</code>	3.2
<code>assertNotAlmostEquals</code>	<code>assertNotAlmostEqual()</code>	3.2
<code>assertRegexpMatches</code>	<code>assertRegex()</code>	3.2
<code>assertRaisesRegexp</code>	<code>assertRaisesRegex()</code>	3.2
<code>assertNotRegexpMatches</code>	<code>assertNotRegex()</code>	3.5

You can use <https://github.com/isidentical/teyit> to automatically modernise your unit tests.

- Undocumented and broken `TestCase` method `assertDictContainsSubset` (deprecated in Python 3.2).
 - Undocumented `TestLoader.loadTestsFromModule` parameter `use_load_tests` (deprecated and ignored since Python 3.5).
 - An alias of the `TextTestResult` class: `_TextTestResult` (deprecated in Python 3.2).
- (由 Serhiy Storchaka 於 [gh-89325](#) 中貢獻。)

11.17 webbrowser

- Remove support for obsolete browsers from `webbrowser`. The removed browsers include: Grail, Mosaic, Netscape, Galeon, Skipstone, Iceape, Firebird, and Firefox versions 35 and below ([gh-102871](#)).

11.18 xml.etree.ElementTree

- Remove the `ElementTree.Element.copy()` method of the pure Python implementation, deprecated in Python 3.10, use the `copy.copy()` function instead. The C implementation of `xml.etree.ElementTree` has no `copy()` method, only a `__copy__()` method. (Contributed by Victor Stinner in [gh-94383](#).)

11.19 zipimport

- Remove `zipimport`'s `find_loader()` and `find_module()` methods, deprecated in Python 3.10: use the `find_spec()` method instead. See [PEP 451](#) for the rationale. (Contributed by Victor Stinner in [gh-94379](#).)

11.20 其他

- Remove the `suspicious` rule from the documentation `Makefile` and `Doc/tools/rstlint.py`, both in favor of `sphinx-lint`. (Contributed by Julien Palard in [gh-98179](#).)
- Remove the `keyfile` and `certfile` parameters from the `ftplib`, `imaplib`, `poplib` and `smtplib` modules, and the `key_file`, `cert_file` and `check_hostname` parameters from the `http.client` module, all deprecated since Python 3.6. Use the `context` parameter (`ssl_context` in `imaplib`) instead. (Contributed by Victor Stinner in [gh-94172](#).)
- 移除數個標準函式庫模組與測試中的 Jython 相容性修補程式。(由 Nikita Sobolev 於 [gh-99482](#) 中貢獻。)
- 移除 `ctypes` 模組中的 `_use_broken_old_ctypes_structure_semantics_` 旗標。(由 Nikita Sobolev 於 [gh-99285](#) 中貢獻。)

12 Porting to Python 3.12

This section lists previously described changes and other bugfixes that may require changes to your code.

12.1 Changes in the Python API

- More strict rules are now applied for numerical group references and group names in regular expressions. Only sequence of ASCII digits is now accepted as a numerical reference. The group name in bytes patterns and replacement strings can now only contain ASCII letters and digits and underscore. (Contributed by Serhiy Storchaka in [gh-91760](#).)
- Remove `randrange()` functionality deprecated since Python 3.10. Formerly, `randrange(10.0)` losslessly converted to `randrange(10)`. Now, it raises a `TypeError`. Also, the exception raised for non-integer values such as `randrange(10.5)` or `randrange('10')` has been changed from `ValueError` to `TypeError`. This also prevents bugs where `randrange(1e25)` would silently select from a larger range than `randrange(10**25)`. (Originally suggested by Serhiy Storchaka [gh-86388](#).)
- `argparse.ArgumentParser` changed encoding and error handler for reading arguments from file (e.g. `fromfile_prefix_chars` option) from default text encoding (e.g. `locale.getpreferredencoding(False)`) to filesystem encoding and error handler. Argument files should be encoded in UTF-8 instead of ANSI Codepage on Windows.
- Remove the `asyncore`-based `smtpd` module deprecated in Python 3.4.7 and 3.5.4. A recommended replacement is the `asyncio`-based `aiosmtpd` PyPI module.
- `shlex.split()`: Passing `None` for `s` argument now raises an exception, rather than reading `sys.stdin`. The feature was deprecated in Python 3.9. (Contributed by Victor Stinner in [gh-94352](#).)
- The `os` module no longer accepts bytes-like paths, like `bytearray` and `memoryview` types: only the exact `bytes` type is accepted for bytes strings. (Contributed by Victor Stinner in [gh-98393](#).)
- `syslog.openlog()` and `syslog.closelog()` now fail if used in subinterpreters. `syslog.syslog()` may still be used in subinterpreters, but now only if `syslog.openlog()` has already been called in the main interpreter. These new restrictions do not apply to the main interpreter, so only a very small set of users might be affected. This change helps with interpreter isolation. Furthermore, `syslog` is a wrapper around process-global resources, which are best managed from the main interpreter. (Contributed by Donghee Na in [gh-99127](#).)

- The undocumented locking behavior of `cached_property()` is removed, because it locked across all instances of the class, leading to high lock contention. This means that a cached property getter function could now run more than once for a single instance, if two threads race. For most simple cached properties (e.g. those that are idempotent and simply calculate a value based on other attributes of the instance) this will be fine. If synchronization is needed, implement locking within the cached property getter function or around multi-threaded access points.
- `sys._current_exceptions()` now returns a mapping from thread-id to an exception instance, rather than to a `(typ, exc, tb)` tuple. (Contributed by Irit Katriel in [gh-103176](#).)
- When extracting tar files using `tarfile` or `shutil.unpack_archive()`, pass the *filter* argument to limit features that may be surprising or dangerous. See [tarfile-extraction-filter](#) for details.
- The output of the `tokenize.tokenize()` and `tokenize.generate_tokens()` functions is now changed due to the changes introduced in [PEP 701](#). This means that `STRING` tokens are not emitted any more for f-strings and the tokens described in [PEP 701](#) are now produced instead: `FSTRING_START`, `FSTRING_MIDDLE` and `FSTRING_END` are now emitted for f-string "string" parts in addition to the appropriate tokens for the tokenization in the expression components. For example for the f-string `f"start {1+1} end"` the old version of the tokenizer emitted:

```
1, 0-1, 18:          STRING          'f"start {1+1} end"'
```

while the new version emits:

```
1, 0-1, 2:          FSTRING_START   'f"'
1, 2-1, 8:          FSTRING_MIDDLE  'start '
1, 8-1, 9:          OP              '{'
1, 9-1, 10:         NUMBER          '1'
1, 10-1, 11:        OP              '+'
1, 11-1, 12:        NUMBER          '1'
1, 12-1, 13:        OP              '}'
1, 13-1, 17:        FSTRING_MIDDLE  ' end'
1, 17-1, 18:        FSTRING_END     '"""'
```

Additionally, there may be some minor behavioral changes as a consequence of the changes required to support [PEP 701](#). Some of these changes include:

- The `type` attribute of the tokens emitted when tokenizing some invalid Python characters such as `!` has changed from `ERRORTOKEN` to `OP`.
- Incomplete single-line strings now also raise `tokenize.TokenError` as incomplete multiline strings do.
- Some incomplete or invalid Python code now raises `tokenize.TokenError` instead of returning arbitrary `ERRORTOKEN` tokens when tokenizing it.
- Mixing tabs and spaces as indentation in the same file is not supported anymore and will raise a `TabError`.
- The `threading` module now expects the `_thread` module to have an `_is_main_interpreter` attribute. It is a function with no arguments that returns `True` if the current interpreter is the main interpreter. Any library or application that provides a custom `_thread` module should provide `_is_main_interpreter()`. (See [gh-112826](#).)

13 Build Changes

- Python no longer uses `setup.py` to build shared C extension modules. Build parameters like headers and libraries are detected in `configure` script. Extensions are built by `Makefile`. Most extensions use `pkg-config` and fall back to manual detection. (Contributed by Christian Heimes in [gh-93939](#).)
- `va_start()` with two parameters, like `va_start(args, format)`, is now required to build Python. `va_start()` is no longer called with a single parameter. (Contributed by Kumar Aditya in [gh-93207](#).)
- CPython now uses the ThinLTO option as the default link time optimization policy if the Clang compiler accepts the flag. (Contributed by Donghee Na in [gh-89536](#).)
- Add `COMPILEALL_OPTS` variable in `Makefile` to override `compileall` options (default: `-j0`) in `make install`. Also merged the 3 `compileall` commands into a single command to build `.pyc` files for all optimization levels (0, 1, 2) at once. (Contributed by Victor Stinner in [gh-99289](#).)
- Add platform triplets for 64-bit LoongArch:
 - `loongarch64-linux-gnusr`
 - `loongarch64-linux-gnuf32`
 - `loongarch64-linux-gnu`(由 Zhang Na 於 [gh-90656](#) 中貢獻。)
- `PYTHON_FOR_REGEN` now require Python 3.10 or newer.
- Autoconf 2.71 and `aclocal` 1.16.4 is now required to regenerate `!configure`. (Contributed by Christian Heimes in [gh-89886](#).)
- Windows builds and macOS installers from `python.org` now use OpenSSL 3.0.

14 C API 變更

14.1 新增特性

- **PEP 697**: Introduce the Unstable C API tier, intended for low-level tools like debuggers and JIT compilers. This API may change in each minor release of CPython without deprecation warnings. Its contents are marked by the `PyUnstable_` prefix in names.

程式碼物件建構函式:

- `PyUnstable_Code_New()` (自 `PyCode_New` 重新命名)
- `PyUnstable_Code_NewWithPosOnlyArgs()` (自 `PyCode_NewWithPosOnlyArgs` 重新命名)

Extra storage for code objects (**PEP 523**):

- `PyUnstable_Eval_RequestCodeExtraIndex()` (自 `_PyEval_RequestCodeExtraIndex` 重新命名)
- `PyUnstable_Code_GetExtra()` (自 `_PyCode_GetExtra` 重新命名)
- `PyUnstable_Code_SetExtra()` (自 `_PyCode_SetExtra` 重新命名)

The original names will continue to be available until the respective API changes.

(由 Petr Viktorin 於 [gh-101101](#) 中貢獻。)

- **PEP 697**: Add an API for extending types whose instance memory layout is opaque:
 - `PyType_Spec.basicsize` can be zero or negative to specify inheriting or extending the base class size.

- `PyObject_GetTypeData()` and `PyType_GetTypeDataSize()` added to allow access to subclass-specific instance data.
- `Py_TPFLAGS_ITEMS_AT_END` and `PyObject_GetItemData()` added to allow safely extending certain variable-sized types, including `PyType_Type`.
- `Py_RELATIVE_OFFSET` added to allow defining members in terms of a subclass-specific struct.

(由 Petr Viktorin 於 [gh-103509](#) 中貢獻。)

- Add the new limited C API function `PyType_FromMetaclass()`, which generalizes the existing `PyType_FromModuleAndSpec()` using an additional metaclass argument. (Contributed by Wenzel Jakob in [gh-93012](#).)
- API for creating objects that can be called using the vectorcall protocol was added to the Limited API:
 - `Py_TPFLAGS_HAVE_VECTORCALL`
 - `PyVectorcall_NARGS()`
 - `PyVectorcall_Call()`
 - `vectorcallfunc`

The `Py_TPFLAGS_HAVE_VECTORCALL` flag is now removed from a class when the class's `__call__()` method is reassigned. This makes vectorcall safe to use with mutable types (i.e. heap types without the immutable flag, `Py_TPFLAGS_IMMUTABLETYPE`). Mutable types that do not override `tp_call` now inherit the `Py_TPFLAGS_HAVE_VECTORCALL` flag. (Contributed by Petr Viktorin in [gh-93274](#).)

The `Py_TPFLAGS_MANAGED_DICT` and `Py_TPFLAGS_MANAGED_WEAKREF` flags have been added. This allows extensions classes to support object `__dict__` and weakrefs with less bookkeeping, using less memory and with faster access.

- API for performing calls using the vectorcall protocol was added to the Limited API:
 - `PyObject_Vectorcall()`
 - `PyObject_VectorcallMethod()`
 - `Py_VECTORCALL_ARGUMENTS_OFFSET`

This means that both the incoming and outgoing ends of the vector call protocol are now available in the Limited API. (Contributed by Wenzel Jakob in [gh-98586](#).)

- Add two new public functions, `PyEval_SetProfileAllThreads()` and `PyEval_SetTraceAllThreads()`, that allow to set tracing and profiling functions in all running threads in addition to the calling one. (Contributed by Pablo Galindo in [gh-93503](#).)
- Add new function `PyFunction_SetVectorcall()` to the C API which sets the vectorcall field of a given `PyFunctionObject`. (Contributed by Andrew Frost in [gh-92257](#).)
- The C API now permits registering callbacks via `PyDict_AddWatcher()`, `PyDict_Watch()` and related APIs to be called whenever a dictionary is modified. This is intended for use by optimizing interpreters, JIT compilers, or debuggers. (Contributed by Carl Meyer in [gh-91052](#).)
- Add `PyType_AddWatcher()` and `PyType_Watch()` API to register callbacks to receive notification on changes to a type. (Contributed by Carl Meyer in [gh-91051](#).)
- Add `PyCode_AddWatcher()` and `PyCode_ClearWatcher()` APIs to register callbacks to receive notification on creation and destruction of code objects. (Contributed by Itamar Oren in [gh-91054](#).)
- Add `PyFrame_GetVar()` and `PyFrame_GetVarString()` functions to get a frame variable by its name. (Contributed by Victor Stinner in [gh-91248](#).)
- Add `PyErr_GetRaisedException()` and `PyErr_SetRaisedException()` for saving and restoring the current exception. These functions return and accept a single exception object, rather than the triple arguments of the now-deprecated `PyErr_Fetch()` and `PyErr_Restore()`. This is less error prone and a bit more efficient. (Contributed by Mark Shannon in [gh-101578](#).)

- Add `_PyErr_ChainExceptions1`, which takes an exception instance, to replace the legacy-API `_PyErr_ChainExceptions`, which is now deprecated. (Contributed by Mark Shannon in [gh-101578](#).)
- Add `PyException_GetArgs()` and `PyException_SetArgs()` as convenience functions for retrieving and modifying the args passed to the exception's constructor. (Contributed by Mark Shannon in [gh-101578](#).)
- Add `PyErr_DisplayException()`, which takes an exception instance, to replace the legacy-api `PyErr_Display()`. (Contributed by Irit Katriel in [gh-102755](#)).
- **PEP 683**: Introduce *Immortal Objects*, which allows objects to bypass reference counts, and related changes to the C-API:
 - **`_Py_IMMORTAL_REFCNT`**: The reference count that defines an object as immortal.
 - `_Py_IsImmortal` Checks if an object has the immortal reference count.
 - **`PyObject_HEAD_INIT`** This will now initialize reference count to `_Py_IMMORTAL_REFCNT` when used with `Py_BUILD_CORE`.
 - **`SSTATE_INTERNEDED_IMMORTAL`** An identifier for interned unicode objects that are immortal.
 - **`SSTATE_INTERNEDED_IMMORTAL_STATIC`** An identifier for interned unicode objects that are immortal and static
 - **`sys.getunicodeinternedsize`** This returns the total number of unicode objects that have been interned. This is now needed for `refleak.py` to correctly track reference counts and allocated blocks
 (由 Eddie Elizondo 於 [gh-84436](#) 中貢獻。)
- **PEP 684**: Add the new `Py_NewInterpreterFromConfig()` function and `PyInterpreterConfig`, which may be used to create sub-interpreters with their own GILs. (See [PEP 684: A Per-Interpreter GIL](#) for more info.) (Contributed by Eric Snow in [gh-104110](#).)
- In the limited C API version 3.12, `Py_INCREF()` and `Py_DECREF()` functions are now implemented as opaque function calls to hide implementation details. (Contributed by Victor Stinner in [gh-105387](#).)

14.2 Porting to Python 3.12

- Legacy Unicode APIs based on `Py_UNICODE*` representation has been removed. Please migrate to APIs based on UTF-8 or `wchar_t*`.
- Argument parsing functions like `PyArg_ParseTuple()` doesn't support `Py_UNICODE*` based format (e.g. `u`, `Z`) anymore. Please migrate to other formats for Unicode like `s`, `z`, `es`, and `U`.
- `tp_weaklist` for all static builtin types is always `NULL`. This is an internal-only field on `PyTypeObject` but we're pointing out the change in case someone happens to be accessing the field directly anyway. To avoid breakage, consider using the existing public C-API instead, or, if necessary, the (internal-only) `_PyObject_GET_WEAKREFS_LISTPTR()` macro.
- This internal-only `PyTypeObject.tp_subclasses` may now not be a valid object pointer. Its type was changed to `void*` to reflect this. We mention this in case someone happens to be accessing the internal-only field directly.

To get a list of subclasses, call the Python method `__subclasses__()` (using `PyObject_CallMethod()`, for example).

- Add support of more formatting options (left aligning, octals, uppercase hexadecimals, `intmax_t`, `ptrdiff_t`, `wchar_t` C strings, variable width and precision) in `PyUnicode_FromFormat()` and `PyUnicode_FromFormatV()`. (Contributed by Serhiy Storchaka in [gh-98836](#).)
- An unrecognized format character in `PyUnicode_FromFormat()` and `PyUnicode_FromFormatV()` now sets a `SystemError`. In previous versions it caused all the

rest of the format string to be copied as-is to the result string, and any extra arguments discarded. (Contributed by Serhiy Storchaka in [gh-95781](#).)

- Fix wrong sign placement in `PyUnicode_FromFormat()` and `PyUnicode_FromFormatV()`. (Contributed by Philip Georgi in [gh-95504](#).)
- Extension classes wanting to add a `__dict__` or weak reference slot should use `Py_TPFLAGS_MANAGED_DICT` and `Py_TPFLAGS_MANAGED_WEAKREF` instead of `tp_dictoffset` and `tp_weaklistoffset`, respectively. The use of `tp_dictoffset` and `tp_weaklistoffset` is still supported, but does not fully support multiple inheritance ([gh-95589](#)), and performance may be worse. Classes declaring `Py_TPFLAGS_MANAGED_DICT` should call `_PyObject_VisitManagedDict()` and `_PyObject_ClearManagedDict()` to traverse and clear their instance's dictionaries. To clear weakrefs, call `PyObject_ClearWeakRefs()`, as before.
- The `PyUnicode_FSDecoder()` function no longer accepts bytes-like paths, like `bytearray` and `memoryview` types: only the exact `bytes` type is accepted for bytes strings. (Contributed by Victor Stinner in [gh-98393](#).)
- The `Py_CLEAR`, `Py_SETREF` and `Py_XSETREF` macros now only evaluate their arguments once. If an argument has side effects, these side effects are no longer duplicated. (Contributed by Victor Stinner in [gh-98724](#).)
- The interpreter's error indicator is now always normalized. This means that `PyErr_SetObject()`, `PyErr_SetString()` and the other functions that set the error indicator now normalize the exception before storing it. (Contributed by Mark Shannon in [gh-101578](#).)
- `_Py_RefTotal` is no longer authoritative and only kept around for ABI compatibility. Note that it is an internal global and only available on debug builds. If you happen to be using it then you'll need to start using `_Py_GetGlobalRefTotal()`.
- The following functions now select an appropriate metaclass for the newly created type:
 - `PyType_FromSpec()`
 - `PyType_FromSpecWithBases()`
 - `PyType_FromModuleAndSpec()`

Creating classes whose metaclass overrides `tp_new` is deprecated, and in Python 3.14+ it will be disallowed. Note that these functions ignore `tp_new` of the metaclass, possibly allowing incomplete initialization.

Note that `PyType_FromMetaclass()` (added in Python 3.12) already disallows creating classes whose metaclass overrides `tp_new` (`__new__()` in Python).

Since `tp_new` overrides almost everything `PyType_From*` functions do, the two are incompatible with each other. The existing behavior -- ignoring the metaclass for several steps of type creation -- is unsafe in general, since (meta)classes assume that `tp_new` was called. There is no simple general workaround. One of the following may work for you:

- If you control the metaclass, avoid using `tp_new` in it:
 - * If initialization can be skipped, it can be done in `tp_init` instead.
 - * If the metaclass doesn't need to be instantiated from Python, set its `tp_new` to `NULL` using the `Py_TPFLAGS_DISALLOW_INSTANTIATION` flag. This makes it acceptable for `PyType_From*` functions.
- Avoid `PyType_From*` functions: if you don't need C-specific features (slots or setting the instance size), create types by calling the metaclass.
- If you *know* the `tp_new` can be skipped safely, filter the deprecation warning out using `warnings.catch_warnings()` from Python.
- `PyOS_InputHook` and `PyOS_ReadlineFunctionPointer` are no longer called in subinterpreters. This is because clients generally rely on process-wide global state (since these callbacks have no way of recovering extension module state).

This also avoids situations where extensions may find themselves running in a subinterpreter that they don't support (or haven't yet been loaded in). See [gh-104668](#) for more info.

- `PyLongObject` has had its internals changed for better performance. Although the internals of `PyLongObject` are private, they are used by some extension modules. The internal fields should no longer be accessed directly, instead the API functions beginning `PyLong_...` should be used instead. Two new *unstable* API functions are provided for efficient access to the value of `PyLongObjects` which fit into a single machine word:

- `PyUnstable_Long_IsCompact()`
- `PyUnstable_Long_CompactValue()`

- Custom allocators, set via `PyMem_SetAllocator()`, are now required to be thread-safe, regardless of memory domain. Allocators that don't have their own state, including "hooks", are not affected. If your custom allocator is not already thread-safe and you need guidance then please create a new GitHub issue and CC [@eric snow currently](#).

14.3 已用

- In accordance with [PEP 699](#), the `ma_version_tag` field in `PyDictObject` is deprecated for extension modules. Accessing this field will generate a compiler warning at compile time. This field will be removed in Python 3.14. (Contributed by Ramvikrams and Kumar Aditya in [gh-101193](#). PEP by Ken Jin.)

- Deprecate global configuration variable:

- `Py_DebugFlag`: 請改用 `PyConfig.parser_debug`
- `Py_VerboseFlag`: 請改用 `PyConfig.verbose`
- `Py_QuietFlag`: 請改用 `PyConfig.quiet`
- `Py_InteractiveFlag`: 請改用 `PyConfig.interactive`
- `Py_InspectFlag`: 請改用 `PyConfig.inspect`
- `Py_OptimizeFlag`: 請改用 `PyConfig.optimization_level`
- `Py_NoSiteFlag`: 請改用 `PyConfig.site_import`
- `Py_BytesWarningFlag`: 請改用 `PyConfig.bytes_warning`
- `Py_FrozenFlag`: 請改用 `PyConfig.pathconfig_warnings`
- `Py_IgnoreEnvironmentFlag`: 請改用 `PyConfig.use_environment`
- `Py_DontWriteBytecodeFlag`: 請改用 `PyConfig.write_bytecode`
- `Py_NoUserSiteDirectory`: 請改用 `PyConfig.user_site_directory`
- `Py_UnbufferedStdioFlag`: 請改用 `PyConfig.buffered_stdio`
- `Py_HashRandomizationFlag`: 請改用 `PyConfig.use_hash_seed` 和 `PyConfig.hash_seed`
- `Py_IsolatedFlag`: 請改用 `PyConfig.isolated`
- `Py_LegacyWindowsFSEncodingFlag`: 請改用 `PyPreConfig.legacy_windows_fs_encoding`
- `Py_LegacyWindowsStdioFlag`: 請改用 `PyConfig.legacy_windows_stdio`
- `Py_FileSystemDefaultEncoding`: 請改用 `PyConfig.filesystem_encoding`
- `Py_HasFileSystemDefaultEncoding`: 請改用 `PyConfig.filesystem_encoding`
- `Py_FileSystemDefaultEncodeErrors`: 請改用 `PyConfig.filesystem_errors`
- `Py_UTF8Mode`: 請改用 `PyPreConfig.utf8_mode` (參見 `Py_PreInitialize()`)

`Py_InitializeFromConfig()` API 應改與 `PyConfig` 一起使用。(由 Victor Stinner 於 [gh-77782](#) 中貢獻。)

- `Creating immutable types with mutable bases` is deprecated and will be disabled in Python 3.14. ([gh-95388](#))
- `structmember.h` 標頭已用，但仍可使用，且還有移除它的計畫。

Its contents are now available just by including `Python.h`, with a `Py` prefix added if it was missing:

- `PyMemberDef`、`PyMember_GetOne()` 和 `PyMember_SetOne()`
- Type macros like `Py_T_INT`, `Py_T_DOUBLE`, etc. (previously `T_INT`, `T_DOUBLE`, etc.)
- `Py_READONLY` (先前 `READONLY`) 和 `Py_AUDIT_READ` (先前全大寫) 旗標

數個項目不再從 `Python.h` 中公開：

- `T_OBJECT` (請改用 `Py_T_OBJECT_EX`)
- `T_NONE` (先前未記於文件上，且相當古怪)
- 不做任何事的巨集 `WRITE_RESTRICTED`。
- `RESTRICTED` 和 `READ_RESTRICTED` 這兩個巨集，相當於 `Py_AUDIT_READ`。
- In some configurations, `<stddef.h>` is not included from `Python.h`. It should be included manually when using `offsetof()`.

The deprecated header continues to provide its original contents under the original names. Your old code can stay unchanged, unless the extra include and non-namespaced macros bother you greatly.

(Contributed in [gh-47146](#) by Petr Viktorin, based on earlier work by Alexander Belopolsky and Matthias Braun.)

- `PyErr_Fetch()` and `PyErr_Restore()` are deprecated. Use `PyErr_GetRaisedException()` and `PyErr_SetRaisedException()` instead. (Contributed by Mark Shannon in [gh-101578](#).)
- `PyErr_Display()` 已用，請改用 `PyErr_DisplayException()`。(由 Irit Katriel 於 [gh-102755](#) 中貢獻。)
- `_PyErr_ChainExceptions` 已用，請改用 `_PyErr_ChainExceptions1`。(由 Irit Katriel 於 [gh-102192](#) 中貢獻。)
- Using `PyType_FromSpec()`, `PyType_FromSpecWithBases()` or `PyType_FromModuleAndSpec()` to create a class whose metaclass overrides `tp_new` is deprecated. Call the metaclass instead.

Python 3.14 中待議的移除項目

- The `ma_version_tag` field in `PyDictObject` for extension modules ([PEP 699](#); [gh-101193](#)).
- `Creating immutable types with mutable bases` ([gh-95388](#)).
- Functions to configure Python's initialization, deprecated in Python 3.11:

- `PySys_SetArgvEx()`: set `PyConfig.argv` instead.
- `PySys_SetArgv()`: set `PyConfig.argv` instead.
- `Py_SetProgramName()`: set `PyConfig.program_name` instead.
- `Py_SetPythonHome()`: set `PyConfig.home` instead.

`Py_InitializeFromConfig()` API 應改與 `PyConfig` 一起使用。

- Global configuration variables:
 - `Py_DebugFlag`: use `PyConfig.parser_debug` instead.
 - `Py_VerboseFlag`: use `PyConfig.verbose` instead.

- `Py_QuietFlag`: use `PyConfig.quiet` instead.
- `Py_InteractiveFlag`: use `PyConfig.interactive` instead.
- `Py_InspectFlag`: use `PyConfig.inspect` instead.
- `Py_OptimizeFlag`: use `PyConfig.optimization_level` instead.
- `Py_NoSiteFlag`: use `PyConfig.site_import` instead.
- `Py_BytesWarningFlag`: use `PyConfig.bytes_warning` instead.
- `Py_FrozenFlag`: use `PyConfig.pathconfig_warnings` instead.
- `Py_IgnoreEnvironmentFlag`: use `PyConfig.use_environment` instead.
- `Py_DontWriteBytecodeFlag`: use `PyConfig.write_bytecode` instead.
- `Py_NoUserSiteDirectory`: use `PyConfig.user_site_directory` instead.
- `Py_UnbufferedStdioFlag`: use `PyConfig.buffered_stdio` instead.
- `Py_HashRandomizationFlag`: use `PyConfig.use_hash_seed` and `PyConfig.hash_seed` instead.
- `Py_IsolatedFlag`: use `PyConfig.isolated` instead.
- `Py_LegacyWindowsFSEncodingFlag`: use `PyPreConfig.legacy_windows_fs_encoding` instead.
- `Py_LegacyWindowsStdioFlag`: use `PyConfig.legacy_windows_stdio` instead.
- `Py_FileSystemDefaultEncoding`: use `PyConfig.filesystem_encoding` instead.
- `Py_HasFileSystemDefaultEncoding`: use `PyConfig.filesystem_encoding` instead.
- `Py_FileSystemDefaultEncodeErrors`: use `PyConfig.filesystem_errors` instead.
- `Py_UTF8Mode`: use `PyPreConfig.utf8_mode` instead. (see `Py_PreInitialize()`)

`Py_InitializeFromConfig()` API 應改與 `PyConfig` 一起使用。

Python 3.15 中待議的移除項目

- The bundled copy of `libmpdecimal`.
- `PyImport_ImportModuleNoBlock()`: use `PyImport_ImportModule()` instead.
- `PyWeakref_GET_OBJECT()`: use `PyWeakref_GetRef()` instead.
- `PyWeakref_GetObject()`: use `PyWeakref_GetRef()` instead.
- `Py_UNICODE_WIDE` type: use `wchar_t` instead.
- `Py_UNICODE` type: use `wchar_t` instead.
- Python 初始化函式：
 - `PySys_ResetWarnOptions()`: clear `sys.warnoptions` and `warnings.filters` instead.
 - `Py_GetExecPrefix()`: get `sys.exec_prefix` instead.
 - `Py_GetPath()`: get `sys.path` instead.
 - `Py_GetPrefix()`: get `sys.prefix` instead.
 - `Py_GetProgramFullPath()`: get `sys.executable` instead.
 - `Py_GetProgramName()`: get `sys.executable` instead.
 - `Py_GetPythonHome()`: get `PyConfig.home` or the `PYTHONHOME` environment variable instead.

未來版本中待討論的移除項目

以下 API 已廢用，且將會被移除，雖目前尚未定下移除日期。

- `Py_TPFLAGS_HAVE_FINALIZE`: **unneeded since Python 3.8.**
- `PyErr_Fetch()`: **use `PyErr_GetRaisedException()` instead.**
- `PyErr_NormalizeException()`: **use `PyErr_GetRaisedException()` instead.**
- `PyErr_Restore()`: **use `PyErr_SetRaisedException()` instead.**
- `PyModule_GetFilename()`: **use `PyModule_GetFilenameObject()` instead.**
- `PyOS_AfterFork()`: **use `PyOS_AfterFork_Child()` instead.**
- `PySlice_GetIndicesEx()`: **use `PySlice_Unpack()` and `PySlice_AdjustIndices()` instead.**
- `PyUnicode_AsDecodedObject()`: **use `PyCodec_Decode()` instead.**
- `PyUnicode_AsDecodedUnicode()`: **use `PyCodec_Decode()` instead.**
- `PyUnicode_AsEncodedObject()`: **use `PyCodec_Encode()` instead.**
- `PyUnicode_AsEncodedUnicode()`: **use `PyCodec_Encode()` instead.**
- `PyUnicode_READY()`: **自 Python 3.12 起不再需要**
- `PyErr_Display()`: **use `PyErr_DisplayException()` instead.**
- `_PyErr_ChainExceptions()`: **use `_PyErr_ChainExceptions1` instead.**
- `PyBytesObject.ob_shash` member: **call `PyObject_Hash()` instead.**
- `PyDictObject.ma_version_tag` member.
- **Thread Local Storage (TLS) API:**
 - `PyThread_create_key()`: **use `PyThread_tss_alloc()` instead.**
 - `PyThread_delete_key()`: **use `PyThread_tss_free()` instead.**
 - `PyThread_set_key_value()`: **use `PyThread_tss_set()` instead.**
 - `PyThread_get_key_value()`: **use `PyThread_tss_get()` instead.**
 - `PyThread_delete_key_value()`: **use `PyThread_tss_delete()` instead.**
 - `PyThread_ReInitTLS()`: **unneeded since Python 3.7.**

14.4 已移除

- Remove the `token.h` header file. There was never any public tokenizer C API. The `token.h` header file was only designed to be used by Python internals. (Contributed by Victor Stinner in [gh-92651](#).)
- Legacy Unicode APIs have been removed. See [PEP 623](#) for detail.
 - `PyUnicode_WCHAR_KIND`
 - `PyUnicode_AS_UNICODE()`
 - `PyUnicode_AsUnicode()`
 - `PyUnicode_AsUnicodeAndSize()`
 - `PyUnicode_AS_DATA()`
 - `PyUnicode_FromUnicode()`
 - `PyUnicode_GET_SIZE()`
 - `PyUnicode_GetSize()`

- `PyUnicode_GET_DATA_SIZE()`
- 移除 `PyUnicode_InternImmortal()` 函式巨集。(由 Victor Stinner 於 [gh-85858](#) 中貢獻。)

15 Notable changes in 3.12.4

15.1 `ipaddress`

- 修正 `IPv4Address`、`IPv6Address`、`IPv4Network` 和 `IPv6Network` 中的 `is_global` 和 `is_private` 行^[F]。

索引

非依字母順序

環境變數

PYTHONHOME, 39

PYTHONPERFSUPPORT, 10

P

Python Enhancement Proposals

PEP 249, 14

PEP 451, 31

PEP 484, 4, 8, 9

PEP 523, 33

PEP 554, 6

PEP 572, 10

PEP 594, 20, 26, 29

PEP 617, 6

PEP 623, 4, 17, 40

PEP 626, 20, 22

PEP 632, 4, 26

PEP 644, 27

PEP 669, 7

PEP 678, 10

PEP 683, 35

PEP 684, 6, 35

PEP 688, 7

PEP 692, 9

PEP 693, 3

PEP 695, 4, 5, 17

PEP 697, 33

PEP 698, 9

PEP 699, 37, 38

PEP 701, 5, 6, 15, 17, 32

PEP 706, 10

PEP 709, 7, 17

PYTHONHOME, 39

PYTHONPERFSUPPORT, 10